City of Poughkeepsie
Planning Board
Meeting Agenda

Common Council Chambers
Tuesday, April 18, 2023
6:00 PM

I. CALL TO ORDER

II. APPROVAL OF MEETING MINUTES

1. Approval of March 21, 2023 Meeting Minutes

III. PUBLIC HEARINGS FOR SITE PLANS

1. SOUTH AVENUE LOT #937583: MULTIFAMILY RESIDENTIAL BUILDING

Application for Site Plan Review for property at South Avenue lot of record #6061-52-937583 for construction of 87-unit, 5-story mid-rise multifamily residential development with 60 underground and 55 surface-level parking spaces. South Avenue Real Estate Associates LLC Owner/Applicant: Michael Abuladez, CEO, Argo Development; Consultant: Christopher Lapine, P.E., LEED AP, LaBella Associates; Grid #6061-52-937583; Zoning District: R-D Research and Development District; File #2022-055

IV. SITE PLANS/SPECIAL PERMITS

1. 117 NORTH HAMILTON STREET: SITE PLAN

Application for site plan review relative to the proposed wholesale storage, warehousing, manufacturing, creative, retail, contracting business. Two story structure with 40 off-street parking spaces are planned. Owner: 117 N Hamilton, LLC/North Hamilton Parcel LLC; Applicant: Baxter Development Corp.; Consultant: Rohde, Soyka & Andrews, Consulting Engineers, PC; Grid #6162-63-271278/266293; Zoning District: Light

Industrial (I-1) District; File #2022-020

2. 13 HARRISON STREET: SPECIAL PERMIT
Application for a special permit as required by Section 19-4.20 of the City code for the construction of a two (2) story single family modular home. Owner: Habitat for Humanity Dutchess County Applicant/Consultant: David Freeman, RA, Architect; Grid: # 6162-79-3390686; Zoning District: Central Low-Density (R-2A)

V. ADJOURNMENT

CITY OF POUGHKEEPSIE PLANNING BOARD

DRAFT Meeting Minutes
Common Council Chambers
Tuesday, March 21, 2023 6:00 PM

ATTENDANCE	EXCUSED	ABSENT	STAFF
Anne Saylor			Joe Donat, Development Director
Marge Smith			Richard Distel, City Planner
Nick DeLucca			Chris Kroner, MASS Design
Rosaura Andújar-McNeil			Lori Garcia, Board Administrative Assistant
Robert Mallory			
Sean O'Donnell			
Paul Ackerman			
Brian Veltre, Non-Voting Alternate			

I. CALL TO ORDER 6:03pm

Chair Anne Saylor gave a few brief words regarding Natalie Quinn, former City of Poughkeepsie Development Director.

II. BOARD BUSINESS

Nomination of Rosaura Andújar-McNeil as Vice Chair by Sean O'Donnell
Second: Marge Smith
Carried: 7:0:0

III. APPROVAL OF MEETING MINUTES

Approval of February 22, 2023 Meeting Minutes
Motion: Marge Smith
Second: Nick DeLuccia
Carried: 5:0:2 (Marge and Nick were excused in February)

IV. SITE PLANS

1) 117 NORTH HAMILTON STREET

REVIEW POSTPONED TO APRIL AT APPLICANT'S REQUEST

2) SOUTH AVENUE LOT #937583: MULTIFAMILY RESIDENTIAL BUILDING

Application for Site Plan Review for property at South Avenue lot of record #6061-52-937583 for construction of 87-unit, 5-story mid-rise multifamily residential development with 60 underground and 55 surface-level parking spaces. South Avenue Real Estate Associates LLC Owner/Applicant: Michael Abuladez, CEO, Argo Development; Consultant: Christopher

Lapine, P.E., LEED AP, LaBella Associates; Grid #6061-52-937583; Zoning District: R-D Research and Development District; File #2022-055

Presenting: Christopher Levine, LaBella Associates
Michael Arbogast, Applicant
Michael McCormack, McCormack and VanVoorhis Architects
Matthew Tether, McCormack and VanVoorhis Architects

- The response to department and architectural consultant comments were read by Michael McCormick.
- Michael Arbogast presented material samples to the board and explained where they will be used. He confirmed the finish of the zinc will be flat long panels in the darker color.

The Board made several comments regarding the project:

- Chris Kroner requested a color rendering showing the color palette of the added trees, especially in the fall.
- Anne Saylor requested that the elevations and renderings be fixed so that they more closely resemble one another.
- The addition of the trees were addressed and it was pointed out that they need to be reviewed by the fire department.
- The County comments were discussed. Rosaura pointed out the suggestion to add vegetation to the retention basin and add a better pedestrian connection between the four parking spaces, between the refuse enclosure and the parking garage entrance, and the courtyard entrance to the building.

A motion was made to schedule a public hearing
With regard to South Avenue, Lot 937583 a multifamily residential building file #2022-055, the public hearing is set for April the 18th 2023.
Motion: Marge Smith
Second: Sean O'Donnel
Carried: 7:0:0

Anne Saylor pointed out that the application will need to go before the ZBA regarding variances for the parking. The applicant stated that they are waiting to hear comments from the public hearing before they move forward with their ZBA application.

V. ADJOURN THE PLANNING BOARD TO APRIL 18,2023

Motion: Anne Saylor
Second: Marge Smith
Carried: 7:0:0

For more details regarding the meeting, please visit the Meeting Webcast or the Agendas and Minutes page on the City of Poughkeepsie website.

APPLICATION TO THE PLANNING BOARD
CITY OF POUGHKEEPSIE, NEW YORK

Application for Site Plan, Special Permit & Facade Approval

OFFICE USE ONLY

CODE: PLSF

ID #_____

FEE: _____
Total, from:
$500, plus
$_____
($150 per 1000 square feet of floor area), plus
$_____
($35 per number of required parking spaces), plus
$_____
($500 for special permit, if applicable)

I. PROPERTY ADDRESS: South Avenue, City of Poughkeepsie, Dutchess Co., New York; Tax Parcel ID 6061-52-937583

II. PROPERTY OWNER: South Ave Real Est Assoc LLC
ADDRESS: 510 Haight Avenue,
Poughkeepsie, NY 12603

New York, 12603 (state and zip code)

PHONE NUMBER: 914-494-2610 (include area code)

III. NAME OF APPLICANT: ARGO Development (Contact: Mr. Michael Abuladze, CEO)

ADDRESS: 95 Chestnut Ridge Road,
Montvale, NJ 07645

New Jersey, 07045 (state and zip code)

PHONE NUMBER: 914-494-2610 (include area code)

EMAIL ADDRESS: mike@argodev.com

(If applicant is NOT the owner, proof of owner's consent to the application MUST be provided.)

IV. CONSULTANT: Christopher Lapine, P.E., LEED AP

ADDRESS: 21 Fox Street,
Poughkeepsie, NY 12601

New York, 12601 (state and zip code)

PHONE NUMBER: 845-486-1478 (include area code)

V. PROPOSED USE or FAÇADE CHANGE (Summarize proposed use or uses):

87-unit, 5-story mid-rise multifamily residential development with underground and surface-level parking.

VI. ZONING DISTRICT: R-D, Research and Development District

(Proceed to XVII for special permit & façade approval only)

PROJECT INFORMATION

New construction: __X__(yes)_____ (no)

Change of use:_____ (yes) __X__ (no)

Expansion/addition:_____ (yes) __X__ (no)

Alteration:_____ (yes) __X__ (no)

Cost of Construction: $__9.3 million_____

LOT AND BULK INFORMATION:

Lot area: _____2.76_____ (acres) _____~120,226_____ (square feet)

Building Footprint: _____22,640_____ (proposed square feet for new construction)

_____NA_____ (existing square feet for change of use/expansion)

_____NA_____ (additional proposed square feet for expansion)

_____22,640_____ (total building footprint, square feet)

Lot Coverage: _____~19%_____ (percentage, building coverage only)

Gross Floor Area: _____113,200_____ (proposed square feet for new construction)

_____NA_____ (existing square feet for change of use/expansion)

_____NA_____ (additional proposed square feet for expansion)

_____113,200_____ (total gross floor area, square feet)

Building Height: 5 stories of MF residential units over one level of underground parking. (stories) _____70_____ (feet)

Floor Area Ratio: _____0.94_____ (ratio of gross floor area divided by lot area)

VIII. PROJECT PARKING INFORMATION

A) Number of Off-Street Parking Spaces required: _____143.5_____

B) Number of Off-Street Parking Spaces provided: _____144_____

C) Waiver Requested: _____ (Yes) _____X_____ (No)

Is municipal parking available within 600 feet? _____ (Yes) __X__ (No)

If yes, name all such municipal facilities: NA

(If a waiver is requested based on proximity to municipal facilities, a written request for such waiver, addressed to the City Planning Staff and the Chairman of the Planning Board, must be submitted with the application.)

If a private parking facility is to be utilized, is such facility within 600 feet?

_____ (Yes) __X__ (No)

If yes, provide the address of the facility, name of the property owner, number of spaces in the lot, number of spaces available for lease, and length of lease. Attach copy of lease. Additional information may be required by the Planning Board): NA

IX. RESIDENTIAL PROPOSALS

A) Type of Development: Multifamily residential development with underground and surface-level parking.
(Townhouse, condominium, multiple residence rental, etc.)

B) Unit Breakdown:

Number of efficiency or "studio" units: 0

Number of one (1) bedroom units: 87

Number of two (2) bedroom unit's 0

Number with three or more bedrooms: 0

Total number of units: 87

C) Is funding public? ____ Yes __X__ No
If yes, describe funding source: ARGO Development

NA

X. OFFICE PROPOSALS (____ Medical/Dental ____ Professional ____ Business)

A) Number of Employees: _____
B) Number of doctors/dentists/medical practitioners: _____
C) Days/Hours of Operation: _____

NA **XI. SERVICE BUSINESS PROPOSALS**

A) Specify Business: _____
(e.g., laundromat, drycleaner, beauty parlor, travel agency, banks)

B) Number of Employees: _____

C) Number of Washing Machines (for laundromat): _____

D) Days/Hours of Operation: _____

NA **XII. MERCANTILE PROPOSALS** (Retail _____ Wholesale _____)

A) Type of Mercantile (specify): _____

B) Number of Employees: _____

C) Days/Hours of Operation: _____

NA **XIII. STANDARD RESTAURANT/FAST FOOD RESTAURANT/COFFEE SHOP/DONUT SHOP/NIGHTCLUB/DISCOTHEQUE/BAR PROPOSALS**

A) Specify Use: _____

B) Number of seats (excluding bar stools and outdoor seating):_____

C) Meals served (i.e., breakfast, lunch, dinner): _____

D) Type of Menu: _____

E) Days/Hours of Operation: _____

F) Entertainment (live and/or recorded):_____

G) Will the restaurant contain a bar/lounge?: _____ Yes _____ No

H) If yes, how many seats at the bar? _____

I) Is a drive-through window proposed? _____

J) Is a walk-up window proposed? _____

K) Is an outdoor seating area proposed? _____

L) If yes, how many seats are proposed? _____

M) If yes, is outdoor cooking proposed? _____

NA **XIV. INDUSTRIAL/COMMERCIAL PROPOSALS** (Automobile repair, taxi, motor vehicle sales, warehouse, manufacturing, animal hospital, research facilities, etc.)

A) Specify Use: _____

B) Number of shifts (if any): _____

C) Number of employees: _____
(If shifts are proposed, list number of employees per shift)

E) Number of work bays (if automobile repair): _____

F) Days/Hours of operation: _____

NA **XV. EDUCATIONAL/INSTITUTIONAL/RECREATIONAL PROPOSALS** (e.g., Museums, Theatres, Conference Centers, Hotels, Motels, Hospitals, Nursing Homes, Assisted Living Facilities, Nursery Schools, Private Schools, Day Care Centers, Places of Worship, Marinas, Membership Clubs, etc.)

A) Specify: _____

B) Number of shifts (if any): _____

C) Number of employees: _____
(If shifts are proposed, list number of employees per shift)

D) Number of beds (hospitals, nursing homes, etc): _____

E) Number of seats in largest assembly space: _____

NA

F) Number of classrooms (schools): _____

G) Number of rental units (hotels, motels, etc.) _____

H) Number of boat slips/courts (e.g., tennis, handball, etc.), alleys: _____

I) Days/Hours of Operation: _____

XVI. PROPOSALS NOT MENTIONED ABOVE (Please be specific):

NA

XVII. APPLICANT CERTIFICATION

I, Mr. Michael Abuladze, CEO of ARGO Development, certify that the this application has addressed the objectives outlined in the Zoning Ordinance with consideration given to the public health, safety and welfare; the comfort and convenience of the public in general or the residents or users of the proposed development and of the immediate neighborhood.

The applicant certifies that all information contained herein is accurate and complete as of the date of this application.



Signature of Applicant

11/29/22

Date

March 7, 2023

Ms. Anne Saylor, Chairperson
City of Poughkeepsie Planning Board
63 Civic Center Plaza
Poughkeepsie, NY 12601

Re: **ARGO Development – South Avenue Multi-Family Housing**
South Avenue, Poughkeepsie, NY, 12601
Tax Lot 937583

Dear Ms. Saylor:

The Applicant for the above referenced project, Argo Development, and our office, appeared before the City of Poughkeepsie Planning Board on February 22, 2023. Our office received comments issued for consideration by the City of Poughkeepsie Engineering and MASS Design n response to the site plan application for proposed development on South Avenue. The plan set has been revised in response to these comments. Below is a point-by-point response to each of the comments received:

MASS DESIGN GROUP COMMENTS, DATED FEBRUARY 20, 2023:

Drawings/Elevations:

In the conversation the development team shared example renderings that were evolving the design; these renderings have key differences to the elevations, especially as it pertains to the scale of the entrance volumes. We would encourage coordinating renderings and elevations for better clarity in subsequent review, or adding notations as to which document governs.

Response: The intent is to have both the Renderings and Elevations accurate and fully coordinated. Some components of the design (for example, the entrance volumes noted above) have been subject of additional design scrutiny and on occasion some drawings have been more advanced than others. Regardless, the design team will make every effort to submit fully coordinated renderings and elevations. It has been agreed to clearly indicate the issue DATE on each drawing so it will be clear which is the most current version.

Exterior Staircase:

The project hopes to activate the streetscape sidewalk with both a ramped sidewalk and exterior staircase near the South Avenue entrance. The sidewalk as currently drawn while it may meet minimum requirements however feels small in comparison with the building. We recommend widening the staircase to be grander in scale with the width of the entry volume of the building, or a similar study by the design team

Response: The design team acknowledges and shares the same concerns regarding the South Avenue Entrance. In response, this entry has been completely reconfigured and now includes and intermediate floor level which has a new Entrance Lobby which is at

the same level of the adjacent grade, allows for a higher ceiling height, and is composed on the exterior to a grander scale appropriate for a significant entrance.

Exterior Windows/Balconies:

We understand that the operation of the windows will be fixed picture windows above with awning (pull-in) windows below. Through discussion with the design team, we see that this choice mates well with the architectural intent.

MASS appreciates the inclusion of balconies, understanding the importance of outdoor space in a post-pandemic development that looks not just for fresh air intake, but access to fresh air. We see the balustrades on the included rendered images as an opportunity to consider patterns, material and/or craft of the region as the basis for a fabricated railing that helps to land this new project in an existing context.

Response: We confirm the window configuration as stated above (fixed picture windows above with awning in-swing windows below). Regarding the balustrades at the exterior balconies, as proposed at the previous meeting, the design team is citing the patterned metalwork at the top of the Mid Hudson Bridge as inspiration for a contextual reference. It is agreed that this must be appropriately detailed to be successful. This referenced motif may also be utilized at other locations throughout the project, such as ventilation openings at the Garage Level, or screening at the Roof Level, to unify the design.

Parking Lot Apertures:

Discussion was held regarding the ground floor and subsurface parking lots, and how the fresh air intakes would be treated in the building wall. This has been the discussion of previous applicants, and we would ask the design team to elaborate on the intent there (louvers, metal mesh, vine supporting grids, etc.)

Response: The intent is to develop the design of the infill of the openings at the Garage Level consistent with the referenced motif inspired by the top of the Mid Hudson Bridge, similar to the balconies.

Roof:

Roof plan needs clarification as we understand there will be Rooftop Mechanical Units, but we want to understand any proposed Bulkheads, Openspace, MEP Areas, Screening, etc for another review.

Response: The design team is developing a Roof Level Plan which will include roof top equipment, bulkheads, screening, and access for residents. Any visible elements will be indicated on the exterior elevations.

Generator:

Please clarify the generator location, fuel source and utility runs associated for the planning board to understand.

Response: The generator has been shown adjacent to the refuse area. The fuel source is yet to be determined.

Materials:

In the workshop we heard that the applicant is considering Cement Board Paneling vs Sheet Metals. Alternative Metal Sheeting approaches such as Zinc, and different shingling strategies such as at the Lace Mill Factory in Kingston were discussed. Please submit a materials sheet and/or physical samples for the planning board to review.

Response: The design of the exterior elevations has been updated to include zinc accent areas in a shingle pattern inspired by the precedent of the Lace Mill Factory in Kingston.

Exterior Lighting:

Discussion was held regarding lighting, and which lighting approach would be most appropriate on the facade. Given the contemporary look of the design, we encourage the design team to revise their wall mounted and parking lamp pole luminaires with something in the same spirit as the design building.

Response: The on-site lighting has been modified to be contemporary in nature and a modified photometric plan has been provided.

Benches, Tables, Site Features:

Similar to the lighting, the current detail for the benches appears to be a stock historical bench, and we would encourage them to specify a bench more compatible with the contemporary architecture design. Are these the same benches that are shown in the seating area with crushed stone on the Northwest corner of the site? Please clarify the proposed picnic table specification (material/style). Please clarify the field stone planter with a bench in the center of the pedestrian circle near the back entry with a drawing or precedent image.

Response: Benches, tables , and seating wall have been updated to speak to the same vocabulary as the building.

Landscaping:

We are encouraged that the siting of the building provides some screening of the surface parking lot behind and encourage additional density of tree plantings to add screening. We notice the shrubline along South Avenue, and while that is an encouraging buffer zone, we would ask the applicant to consider adding street trees (especially deciduous) along South Avenue to help enliven the streetscape further.

Response: The ramps along the frontage of South Avenue has been removed and red-oaks have been placed along the frontage of the site.

CITY OF POUGHKEEPSIE DEPT. OF PUBLIC WORKS & ENGINEERING COMMENTS, DATED FEBRUARY 17, 2023:

1. Verify and demonstrate available water utility is sufficient for proposed development for both domestic and fire suppression. Any fire suppression requirements to be discussed with City Fire Department and must demonstrate what is being requested is achieved.

Response: Fire service discharge calculations were provided as part of our January 27, 2023 submission.

2. Provide utility report demonstrating available sanitary sewer utility is sufficient for proposed development. Include discussion of water utility for domestic and fire suppression requirements.

   Response: The proposed project connects to the existing trunk main in the City of Poughkeepsie.

3. Indicate location of all proposed backflow devices. Coordinate with City Building Department on type that meets requirements per code.

   Response: A note has been added under City of Poughkeepsie Water Notes, on Sheet G002, indicating reduced pressure zone valve is to be provided on the fire supply line and double check valve shall be provided on the domestic supply at each location where water line enters the building. Backlfow assemblies shall be used in University of Southern California list of approved backflow prevention assemblies.

4. Provide City Standard details for Curbs, Sidewalk, Driveway, Aprons, Pipe Trench, Water TS&V etc. for work within City ROW.

   Response: City curb details has been updated with rebar reinforcement, sidewalk detail has been updated to the required thickness, concrete apron detail has been further refined with rebar reinforcement, and standard City of Poughkeepsie trench detail has been provided for water and sanitary sewer work within the ROW

5. Sheet C160 and C560 indicates Mueller Hydrant. Provide and indicate on Site Plan City Standard Hydrant – American Darling B-62-B. No equivalent or exceptions.

   Response: Said details have been updated accordingly.

6. Indicate and show on Sheet C160 and C560 water tapping sleeve and valve and redundant valve on back side of the curb. Both valves to be Red Top, Right Open.

   Response: Said details have been updated accordingly.

7. Provide design, stability calculations and certification by NYS Licensed PE for retaining walls greater than 5 feet in height.

   Response: Upon completion of geotechnical report, retaining wall designs will be provided.

8. The engineer shall certify that the native soils are acceptable for use as in infiltration practice for the development. In the event the proposed infiltration practice cannot be used, an alternative means to handle site stormwater will need to be developed and implemented for the project. Any alternative must be approved by the City Engineer.

   Response: Additional hydraulic conductivity tests will be performed in the area of the infiltration gallery to confirmed the design rate.

9. Proposed development indicates 2.5 acres of disturbance. Provide SWPPP for review.

   Response: A SWPPP was provided in November 2022. A copy of the SWPPP has been provided.

10. Prosed development indicates storm sewer discharge to NYSDOT owned storm sewer. Any work within or adjacent to NYSDOT ROW or Utility Easements must be reviewed and approved by the respective agency. Provide copies of correspondence and/or approvals.

    Response: Comment noted.

11. Any food prep areas within development requires properly sized and designed grease trap. Provide size, location, and maintenance schedule on site plan, if applicable.

    Response: No food preparation areas are proposed with the exception of the typical kitchen associated with each unit.

12. Show on Site Plan maintenance and protection of traffic for work within City ROW.

    Response: A traffic control plan has been provided on Sheet C200.

13. Provide an estimate of costs for site work.

    Response: Upon approval, and opinion of probable cost estimate will be provided.

Please find enclosed:

- 1 copy of the site plan set dated 3/7/2023
- 1 copy of the EAF, dated 1/27/2023
- 1 copy of the Architectural Elevations, dated 3/7/2023
- 1 copy of Roof Plan, dated 3/7/2023
- 1 copy of the NRI, dated 3/7/2023
- 1 copy of fire supply calculations (dated 1/27/2023 – previously provided)

We believe all remaining comments have been responded to and request to be placed on the March 21st Planning Board agenda. If you should have any questions or comments during your review of the submitted documents, feel free to reach out to me directly at (845) 486-1478.

Sincerely,

Christopher Lapine

Christopher Lapine, PE
LaBella Associates | Senior Civil Engineer
Regional Marketing Leader

cc: Michael Abuladze

File

SOUTH AVENUE MULTI-FAMILY DEVELOPMENT

EAST (SOUTH AVENUE) ELEVATION



SOUTH AVENUE SECTION

SOUTH ELEVATION

NORTHWEST ELEVATION

WEST (INTERIOR COURTYARD) ELEVATION

NORTHWEST (INTERIOR COURTYARD) ELEVATION

NORTH ELEVATION

0 8' 16' 32'

SCALE: 1/16" = 1'-0"

4.4.23
22054

ARGO CONSTRUCTION AND DEVELOPMENT

VANVOORHIS

LISCUM McCORMACK VANVOORHIS
ARCHITECTS PLANNERS INTERIORS 181 CHURCH STREET POUGHKEEPSIE NY 12601

SOUTH AVENUE MULTI-FAMILY DEVELOPMENT

EAST (SOUTH AVENUE) ELEVATION



SOUTH AVENUE SECTION

SOUTH ELEVATION

NORTHWEST ELEVATION

WEST (INTERIOR COURTYARD) ELEVATION

NORTHWEST (INTERIOR COURTYARD) ELEVATION

NORTH ELEVATION

0 8' 16' 32'

SCALE: 1/16" = 1'-0"

4.4.23
22054

ARGO CONSTRUCTION AND DEVELOPMENT

VANVOORHIS

LISCUM McCORMACK VANVOORHIS
ARCHITECTS PLANNERS INTERIORS
181 CHURCH STREET
POUGHKEEPSIE NY 12601

A-1 PROPOSED GARAGE LEVEL

1/8"=1'-0"

N

No.	REVISION/SUBMISSION	DATE

Liscum McCormack VanVoorhis
181 Church Street Poughkeepsie, New York 12601
tel. 845.452.2268 fax. 845.452.3752 lmvarchitects.com
ARCHITECTURE PLANNING INTERIORS

PROJECT
SOUTH AVENUE PARCEL
POUGHKEEPSIE MID-RISE MULTIPLE

DRAWING
PROPOSED GARAGE LEVEL

SEAL

DRAWN BY	PROJECT No.
CQ	22054
CHECKED BY	DATE
MTM	4-4-2023

DRAWING No. A100

FILE P:\2022\22054



A-1 PROPOSED ROOF PLAN

1/8" = 1'-0"

N

No.	REVISION/SUBMISSION	DATE

Liscum McCormack VanVoorhis
ARCHITECTURE PLANNING INTERIORS
181 Church Street Poughkeepsie, New York 12601
tel. 845.452.2268 fax. 845.452.3752 lmvarchitects.com

PROJECT
SOUTH AVENUE PARCEL
POUGHKEEPSIE MID-RISE MULTIPLE

DRAWING
PROPOSED ROOF PLAN

SEAL

DRAWN BY

PROJECT No. 22054

CHECKED BY

DATE 3-7-2023

DRAWING No. A103

FILE P:\2022\22054

SITE PLAN

SOUTH AVENUE MULTI-FAMILY DEVELOPMENT

SOUTH AVENUE

CITY OF POUGHKEEPSIE, DUTCHESS COUNTY, NEW YORK

PROJECT NO: 2222201

NOVEMBER 28, 2022

LAST REVISED:
APR 4, 2023

INDEX OF DRAWINGS

PAGE NO.	REV	SHEET NO.	DATE	DESCRIPTION
1	3	G001	04/04/23	COVER SHEET
2	1	G002	01/27/23	NOTES
3	0	SVY1	11/04/22	MAP OF EXISTING CONDITIONS PREPARED FOR ARGO DEVELOPMENT
4	2	C120	03/07/23	DEMOLITION PLAN
5	3	C130	04/04/23	SITE PLAN
6	1	C131	01/27/23	TRUCK MANEUVERING PLAN
7	1	C140	01/27/23	GRADING AND EROSION &SEDIMENT CONTROL PLAN
8	3	C160	04/04/23	UTILITY PLAN
9	2	C180	03/07/23	LANDSCAPE PLAN
10	2	C190	03/07/23	PHOTOMETRIC LIGHTING PLAN
11	1	C200	03/07/23	TRAFFIC CONTROL PLAN
12	2	C530	03/07/23	SITE DETAILS
13	1	C531	03/07/23	SITE DETAILS
14	1	C532	03/07/23	SITE DETAILS
15	1	C540	01/27/23	EROSION AND SEDIMENT CONTROL DETAILS
16	1	C550	01/27/23	STORM SEWER DETAILS
17	1	C551	01/27/23	STORM SEWER DETAILS
18	2	C560	03/07/23	WATER SYSTEM DETAILS
19	2	C570	03/07/23	SANITARY SEWER DETAILS
20	2	C580	03/07/23	LANDSCAPE DETAILS



LOCATION MAP
1"=500'

Parcel #	Owner/ Owner Address
980578	Spyglass Lane LLC 235 South Ave Poughkeepsie, NY 12601
935565	City Of Poughkeepsie PO Box 300 Poughkeepsie, NY 12602
911602	Vassar Brothers Hospital 54 Page Park Dr Poughkeepsie, NY 12603
911593	Fox Street Condominiums LLC 21 Fox St Poughkeepsie, NY 12601
951552	Latham Interests Inc 250 South Ave Poughkeepsie, NY 12601
977590	South Ave of Dutchess LLC 278 Mill St Ste 100 Poughkeepsie, NY 12601
949661	John R. Satterfield, Jr 248 South Av Poughkeepsie, NY 12601
937583	South Ave Real Est Assoc LLC 510 Haight Ave Poughkeepsie, NY 12603
972609	Executive Park Assoc No 2 Ltd 60 Morrow Ave Scarsdale, NY 10583
949612	Sharad Deedwaniya PO Box 1995 Poughkeepsie, NY 12602

BULK TABLE:

CITY OF POUGHKEEPSIE ZONING DISTRICT: R-D

(SUBJECT TO REQUIREMENTS HIGH DENSITY R-5 DISTRICT PERMITTED USES [SECTION 19-3-16(2)] AND ALL OTHER REQUIREMENTS APPLICABLE TO HIGH DENSITY R-5.

ZONING REQUIREMENTS:	REQUIRED	PROPOSED
MINIMUM LOT AREA	20,000 SF	121,000± SF
MINIMUM LOT WIDTH	50 FT	321 FT
MINIMUM SETBACK REQUIREMENTS:		
FRONT	20 FT	21 FT
SIDES	35 FT	36 FT
REAR	35 FT	98 FT
MAXIMUM BUILDING HEIGHT	6 STORIES OR 70 FT	5 STORIES OVER 1-STORY GARAGE, 70 FT
MAXIMUM BUILDING LOT COVERAGE	50%	22,640 SF OR 18.8%
MINIMUM GREEN SPACE	26,100 SF	52,569 SF

PARKING SPACES REQUIRED OFF-STREET PARKING	# UNITS	REQUIRED SPACES	PROPOSED SPACES
1.0 SPACE FOR EACH STUDIO OR EFFICIENCY APARTMENT;	0 UNITS X 1.0	0 SPACES	0 SPACES
1.5 SPACES FOR EACH 1-BEDROOM APARTMENT;	87 UNITS X 1.5	130.5 SPACES	108 SPACES (1)
2.0 SPACES FOR EACH 2-BEDROOM OR LARGER APARTMENT;	0 UNITS X 2.0	0 SPACES	0 SPACES
TOTAL	87 UNITS	130.5 SPACES REQUIRED	108 SPACES* PROPOSED

* VARIANCE REQUIRED
(1) FIFTY-THREE (53) SPACES IN GARAGE, AND 55 SPACES ON SURFACE

CITY OF POUGHKEEPSIE DEPARTMENTAL SIGNATURES

Fire Chief — Date

Police Chief — Date

Building Inspector — Date

City Engineer — Date

Commissioner of Public Works — Date

CITY PLANNING BOARD
CITY OF POUGHKEEPSIE, NEW YORK
SITE PLAN APPROVAL

FILE NO:

PROJECT NAME: SOUTH AVENUE MULTI-FAMILY DEVELOPMENT

PROJECT LOCATION: SOUTH AVENUE

APPLICANT: ARGO DEVELOPMENT

OFFICIALLY APPROVED at the Planning Board

meeting held the ____ day of _____ 2____

PLANNING CHAIR:

DESIGNEE:

DATE SIGNED:

CONDITION(S):

OWNER/APPLICANT SIGNATURE

THE UNDERSIGNED APPLICANT FOR THE PROPERTY AND THE UNDERSIGNED OWNER OF THE PROPERTY SHOWN HEREON, STATE THAT THEY ARE FAMILIAR WITH THIS MAP, ITS NOTES AND ITS CONTENTS, AND HEREBY CONSENT TO ALL SAID TERMS AND CONDITIONS AS STATED HEREON.

THE APPLICANT AND OWNER UNDERSTAND THEIR OBLIGATION TO THE TOWN TO KEEP THIS SITE AS PER SITE PLAN APPROVAL BY THE TOWN PLANNING BOARD UNTIL A NEW OR REVISED SITE PLAN IS APPROVED FOR THE SITE. THE APPLICANT AND OWNER UNDERSTAND THEIR OBLIGATION TO THE TOWN NOT TO OCCUPY THE PREMISES BEFORE A CO IS ISSUED BY THE TOWN BUILDING DEPARTMENT.

APPLICANT — DATE

OWNER — DATE

OWNER:

SOUTH AVENUE REAL ESTATE ASSOCIATION, LLC
510 HAIGHT AVENUE
POUGHKEEPSIE, NY 12603

APPLICANT:

ARGO DEVELOPMENT
95 CHESTNUT ROAD
MONTVALE, NJ 07645

TAX MAP INFORMATION:

CITY OF POUGHKEEPSIE
SECTION 6061, BLOCK 52, LOT 937583

AREA:

TOTAL PROJECT ACREAGE : 2.77± ACRES

UTILITY COMPANIES:

ELECTRIC: CENTRAL HUDSON GAS & ELECTRIC CORP
284 SOUTH AVENUE
POUGHKEEPSIE, NY 12601
(845) 452-2700

GAS: CENTRAL HUDSON GAS & ELECTRIC CORP
284 SOUTH AVENUE
POUGHKEEPSIE, NY 12601
(845) 452-2700

WATER: CITY OF POUGHKEEPSIE WATER DEPARTMENT
62 CIVIC CENTER PLAZA,
POUGHKEEPSIE, NY 12601
(845) 451-4173

SEWER: CITY OF POUGHKEEPSIE WASTEWATER (SEWER) DEPARTMENT
62 CIVIC CENTER PLAZA,
POUGHKEEPSIE, NY 12601
(845) 451-4173

Dig Safely. New York
Call Before You Dig
Wait The Required Time
Confirm Utility Response
Respect The Marks
Dig With Care
800-962-7962
www.digsafelynewyork.com

LaBella
Powered by partnership.

21 Fox Street
Poughkeepsie, NY 12601
(845) 454-3980

labellapc.com

STATE OF NEW YORK
CHRISTOPHER E. CAPPIELLO
079470
LICENSED PROFESSIONAL ENGINEER

It is a violation of New York Education Law Article 145 Sec.7209, for any person, unless acting under the direction of a licensed architect, professional engineer, or land surveyor, to alter an item in any way. If an item bearing the seal of an architect, engineer, or land surveyor is altered; the altering architect, engineer, or land surveyor shall affix to the item their seal and notation "altered by" followed by their signature and date of such alteration, and a specific description of the alteration.

© 2022 LaBella Associates

APPLICANT NAME & ADDRESS:

ARGO DEVELOPMENT
95 CHESTNUT RIDGE ROAD
MONTVALE, NJ 07645

PROJECT NAME & LOCATION:

SOUTH AVE MULTI-FAMILY DEVELOPMENT
SOUTH AVENUE
CITY OF POUGHKEEPSIE, NY 12601

NO:	DATE:	DESCRIPTION:
3	04/04/23	REVISED PER INTERNAL COORDINATION
2	03/07/23	REVISED PER PLANNING BOARD COMMENTS
1	01/27/23	REVISED PER CITY COMMENTS
Revisions		

PROJECT NUMBER: 2222201

DRAWN BY:

REVIEWED BY: CPL

ISSUED FOR: PLANNING BOARD REVIEW

DATE: 11/28/2022

DRAWING NAME:

COVER SHEET

DRAWING NUMBER:

G001

4/3/2023 12:20:15 PM
B:\GLOBAL\Projects\ARGO\2222201 - South Ave Multi Family Dev\06_Drawings\Civil\00_G001_2222201_COVER.dwg

Drawing Name: B:\GLOBAL\Projects\ARGO\2222201 - South Ave Multi Family Dev\06_Drawings\Civil\00_G001_2222201_COVER.dwg
Xref's Attached: XBORDER_2222201
Date Printed: Apr 03, 2023, 12:20pm

DEMOLITION NOTES:

1. REFER TO REQUIREMENTS OUTLINED IN THE MATERIALS MANAGEMENT, HEALTH AND SAFETY, AND EROSION & SEDIMENT CONTROL PLANS AND NOTES & REMEDIAL NOTES (THIS SHEET) PRIOR TO COMMENCEMENT OF WORK.
2. CONFORM TO APPLICABLE CODE FOR SAFETY OF ADJACENT STRUCTURES, DUST CONTROL, RUNOFF CONTROL, AND HAULING, DISPOSAL AND STORAGE OF DEBRIS.
3. PROVIDE, ERECT, AND MAINTAIN TEMPORARY BARRIERS AND SECURITY DEVICES.
4. MAINTAIN EXISTING UTILITIES TO REMAIN IN SERVICE AND PROTECT THEM AGAINST DAMAGE DURING SELECTIVE DEMOLITION OPERATIONS. DO NOT INTERRUPT EXISTING UTILITIES SERVING OPERATING FACILITIES, EXCEPT WHEN AUTHORIZED IN WRITING BY OWNER AND AUTHORITIES HAVING JURISDICTION.
5. NOTIFY ADJACENT OWNERS OF WORK THAT MAY AFFECT THEIR PROPERTY, POTENTIAL NOISE, UTILITY OUTAGE, OR DISRUPTION. COORDINATE WITH OWNER.
6. PREVENT MOVEMENT OR SETTLEMENT OF ADJACENT STRUCTURES. PROVIDE BRACING AND SHORING.
7. LOCATE AND IDENTIFY ALL EXISTING UTILITIES WITHIN THE CONSTRUCTION AREA. DISCONNECT AND SEAL OR CAP OFF UTILITY SERVICES THAT WILL BE AFFECTED BY THIS PROJECT. NOTIFY AFFECTED UTILITY COMPANIES BEFORE STARTING WORK AND COMPLY WITH THEIR REQUIREMENTS. VERIFY THAT UTILITIES HAVE BEEN DISCONNECTED AND CAPPED.
8. DEMOLISH AND REMOVE COMPONENTS IN AN ORDERLY AND CAREFUL MANNER.
9. PROTECT EXISTING FEATURES THAT ARE NOT TO BE DEMOLISHED.
10. CONDUCT OPERATIONS WITH MINIMUM INTERFERENCE TO PUBLIC OR PRIVATE ACCESSES.
11. MAINTAIN EGRESS AND ACCESS AT ALL TIMES. DO NOT CLOSE OR OBSTRUCT ROADWAYS, OR SIDEWALKS WITHOUT PERMITS. COORDINATE W/ AUTHORITY HAVING JURISDICTION.
12. CEASE OPERATIONS IMMEDIATELY IF ADJACENT STRUCTURES APPEAR TO BE IN DANGER. NOTIFY AUTHORITY HAVING JURISDICTION.
13. ROUGH GRADE AND COMPACT AREAS AFFECTED BY DEMOLITION TO MAINTAIN SITE GRADES AND CONTOURS.
14. FIELD VERIFY EXISTING CONDITIONS AND CORRELATE WITH REQUIREMENTS INDICATED ON DEMOLITION PLAN TO DETERMINE EXTENT OF SELECTIVE DEMOLITION REQUIRED.
15. CONDUCT DEMOLITION OPERATIONS AND REMOVE DEBRIS TO ENSURE MINIMUM INTERFERENCE WITH SELECTIVE DEMOLITION OPERATIONS.
16. CONDUCT DEMOLITION OPERATIONS TO PREVENT INJURY TO PEOPLE AND DAMAGE TO ADJACENT BUILDINGS AND FACILITIES TO REMAIN. ENSURE SAFE PASSAGE OF PEOPLE AROUND SELECTIVE DEMOLITION AREA.
17. USE WATER MIST, TEMPORARY ENCLOSURES AND OTHER SUITABLE METHODS TO LIMIT THE SPREAD OF DUST AND DIRT. COMPLY WITH GOVERNING ENVIRONMENTAL PROTECTION REGULATIONS. DO NOT USE WATER WHEN IT MAY DAMAGE EXISTING CONSTRUCTION, SUCH AS CAUSING ICING, FLOODING, AND TRANSPORTING POLLUTANTS.
18. REMOVE AND TRANSPORT DEBRIS IN A MANNER THAT WILL PREVENT SPILLAGE ON ADJACENT SURFACES AND AREAS.
19. CLEAN ADJACENT STRUCTURES AND IMPROVEMENTS OF DUST, DIRT AND DEBRIS CAUSED BY SELECTIVE DEMOLITION OPERATIONS. RETURN ADJACENT AREAS TO CONDITION EXISTING BEFORE START OF SELECTIVE DEMOLITION.
20. PROMPTLY DISPOSE OF DEMOLISHED MATERIALS. ALL DEBRIS RESULTING FROM DEMOLITION ACTIVITIES SHALL BE DISPOSED OF OFF–SITE AT A FACILITY APPROVED TO RECEIVE THE DEBRIS. DO NOT ALLOW DEMOLISHED MATERIALS TO ACCUMULATE ON–SITE. DO NOT BURN DEMOLISHED MATERIALS ON–SITE.
21. PRIOR TO THE START OF CONSTRUCTION OR EXCAVATION, TREES TO BE RETAINED SHALL BE PROTECTED BY SILT FENCE, SNOW FENCE, CONSTRUCTION FENCE, OR EQUAL, WHICH WILL BE PLACED AT THE DRIP LINE OR SEVERAL FEET BEYOND. HOWEVER, THE FENCING SHALL NOT CROSS PUBLIC SIDEWALKS. NO STORAGE OR STOCKPILING OF CONSTRUCTION MATERIALS, DEBRIS, OR EQUIPMENT SHALL OCCUR WITHIN THE FENCED AREA.
22. THE CONTRACTOR IS RESPONSIBLE FOR COMPLIANCE WITH LOCAL DUST CONTROL AND/OR MONITORING ORDINANCES, AND REMEDIAL ACTION WORK PLAN PREPARED FOR THE SITE.

GENERAL CONSTRUCTION NOTES:

1. ALL UNDERGROUND UTILITIES ARE SHOWN IN THEIR RELATIVE POSITION AND DEPTH FOR INFORMATIONAL PURPOSES ONLY. CONTRACTOR TO VERIFY THEIR ACTUAL LOCATION IN THE FIELD PRIOR TO THE COMMENCEMENT OF CONSTRUCTION.
2. ANY CONDITION ENCOUNTERED IN THE FIELD DIFFERING FROM THOSE SHOWN HEREON, SHALL BE REPORTED TO THE DESIGN ENGINEER BEFORE CONSTRUCTION IS TO PROCEED.
3. ALL STORM SEWER SHALL BE SMOOTH INTERIOR HDPE WITH WATER TIGHT FITTINGS.
4. CONTRACTOR TO VERIFY STATUS OF ALL UTILITY SERVICES PRIOR TO INTERRUPTION.
5. EXPLORATORY EXCAVATIONS SHALL BE PERFORMED BY THE CONTRACTOR AT ALL UTILITY CONNECTION LOCATIONS AND AS NEEDED TO VERIFY EXISTING CONDITIONS PRIOR TO PERFORMING WORK.
6. BEFORE CONSTRUCTING LINES TO CONNECT TO EXISTING UTILITIES, VERIFY EXISTING UTILITY INVERTS AND NOTIFY THE ENGINEER IF ANY VARIATION FROM THE PLAN IS REQUIRED.
7. THE CONTRACTOR SHALL MAINTAIN ALL EXISTING UTILITIES IN SERVICE FOR THE DURATION OF THE WORK.
8. THE CONTRACTOR SHALL COMPLY WITH ALL REQUIRED PERMITS AND ASSOCIATED CONDITIONS.
9. CONTRACTOR SHALL BE RESPONSIBLE FOR DEWATERING UTILITY TRENCHES AND EXCAVATIONS AND FOR THE MAINTENANCE OF SURFACE DRAINAGE DURING THE COURSE OF THE WORK.
10. SEWER MAINS IN RELATION TO WATER MAINS: WHERE POSSIBLE, SEWERS SHALL BE LAID AT LEAST 10 (TEN) FEET HORIZONTALLY FROM ANY EXISTING OR PROPOSED WATER MAIN. VERTICAL SEPARATION SHALL BE MAINTAINED TO PROVIDE 18 (EIGHTEEN) INCHES BETWEEN TOP OF SEWER AND BOTTOM OF THE WATER MAIN AT UTILITY CROSSINGS. WHEN NOT POSSIBLE TO OBTAIN THE PROPER VERTICAL SEPARATION, SEWER PIPE SHALL BE PRESSURE RATED AND TESTED @ 150PSI, 10 (TEN) FEET ON EACH SIDE OF THE WATER MAIN BEING CROSSED.
11. ALL PROPOSED UTILITIES SHALL TERMINATE 5 FEET FROM ANY PROPOSED BUILDING FACE. CONTRACTOR TO COORDINATE WITH BUILDING PLANS FOR ANY CONNECTIONS.
12. ALL GRAVITY SANITARY SEWER SHALL BE SDR 21 PVC UNLESS OTHERWISE SPECIFIED.
13. IF ROCK REMOVAL BY BLASTING IS REQUIRED, THE CONTRACTOR SHALL OBTAIN ALL NECESSARY APPROVALS AND PERMITS REQUIRED BY THE AUTHORITY HAVING JURISDICTION.
14. REDUCE PRESSURE ZONE VALVE TO BE PROVIDED ON FIRE SUPPLY AND DOUBLE CHECK VALVE ON DOMESTIC SUPPLY AT EACH LOCATION WHERE WATER LINE ENTERS THE BUILDING. BACKFLOW ASSEMBLES SHALL BE LISTED IN UNIVERSITY OF SOUTHERN CALIFORNIA LIST OF APPROVED BACKFLOW PREVENTION ASSEMBLES.
15. ALL BACKFLOW PREVENTION AND METER SHALL BE LOCATED INSIDE THE BUILDING.
16. CONTRACTOR SHALL PROVIDE AN AS–BUILT PLAN OF THE PROPOSED IMPROVEMENTS BY A LICENSED NYS SURVEYOR. IT SHALL INCLUDE BUT NOT BE LIMITED TO BUILDINGS, ROADWAYS, WALLS, UTILITIES (INCLUDING INVERTS, RIMS, PIPE SIZE AND DIMENSIONS), SIDEWALKS, ROADWAY RAMPS, CURBING, PARKING LOTS (INCLUDING STRIPING), LANDSCAPE AREAS, ETC. HARDCOPY AND ELECTRONIC COPIES SHALL BE PROVIDED TO OWNER AND PROJECT ENGINEER SEE CITY OF POUGHKEEPSIE NOTES.
17. UNDERGROUND ELECTRIC SHOWN ON THIS PLAN FOR REFERENCE ONLY. REFER TO MEP AND LIGHTING PLANS.

GRADING NOTES:

1. PRIOR TO SITE DISTURBANCE, CONTRACTOR TO INSTALL EROSION & SEDIMENT CONTROL MEASURES.
2. BOX ALL TREES AND HOUSE ALL SHRUBS AND HEDGES BEFORE PLACING EARTH AGAINST OR NEAR THEM. ORNAMENTAL TREES, SHRUBS AND HEDGES WHICH MUST BE REMOVED DURING CONSTRUCTION SHALL BE HEALED IN AND RE–PLANTED IN AS GOOD A CONDITION AS THEY WERE BEFORE THEIR REMOVAL. ANY DAMAGED TREES, SHRUBS, AND/OR HEDGES SHALL BE REPLACED AT THE CONTRACTOR'S EXPENSE, REFER TO LANDSCAPE DRAWINGS.
3. ALL EARTHWORK SHALL BE SMOOTHLY AND EVENLY BLENDED INTO EXISTING CONDITIONS. NO WORK, STORAGE OR TRESPASS SHALL BE PERMITTED BEYOND THE BOUNDARIES OF ANY EASEMENT OR PROPERTY LINE.
4. REMOVE ALL VEGETATION, TREES, STUMPS, GRASSES, ORGANIC SOILS, DEBRIS AND DELETERIOUS MATERIALS WITHIN THE AREAS SLATED FOR CONSTRUCTION, REFER TO LANDSCAPE DRAWINGS.
5. IF PREVIOUSLY UNKNOWN CULTURAL, ARCHEOLOGICAL, OR HISTORIC REMAINS OR ARTIFACTS ARE DISCOVERED IN THE COURSE OF CONSTRUCTION OF THIS PROJECT, THE PROJECT SPONSORS SHALL SUSPEND CONSTRUCTION OPERATIONS IN THE PERTINENT AREA AND SHALL NOTIFY THE PROJECT ENGINEER. CONSTRUCTION IN THAT AREA SHALL RESUME ONLY AFTER COMPLETION OF FEDERAL, TRIBAL, AND STATE COORDINATION TO DETERMINE WHETHER PROTECTION OR RECOVERY OF THE REMAINS IS WARRANTED, OR WHETHER THE SITE IS ELIGIBLE FOR LISTING IN THE NATIONAL REGISTER OF HISTORIC PLACES.

TREE CLEARING NOTES:

1. TREE CLEARING SHALL BE LIMITED TO THE PERIOD BETWEEN OCTOBER 30TH AND MARCH 31ST TO ENSURE NO POTENTIAL TAKE OF BAT SPECIES.

SITE PLAN NOTES:

GENERAL CONSTRUCTION NOTES:

1. THE CONTRACTOR SHALL PROTECT EXISTING PROPERTY LINE MONUMENTATION. ANY MONUMENTATION DISTURBED OR DESTROYED, AS JUDGED BY THE ENGINEER OR OWNER, SHALL BE REPLACED AT THE CONTRACTOR'S EXPENSE AND UNDER THE SUPERVISION OF A NEW YORK STATE LICENSED LAND SURVEYOR.
2. ALL PAVEMENT RESTORATION SHALL MEET AND MATCH EXISTING GRADES.
3. ALL SAWCUT LINES SHALL BE PARALLEL AND CURVILINEAR TO EXISTING OR PROPOSED CURBING AND SHALL BE A CONSTANT DISTANCE OF 18" MIN AWAY.
4. NOTIFY ENGINEER 48 HOURS PRIOR TO INITIALIZATION OF ANY WORK ON SITE.
5. THE ENGINEER SHALL BE NOTIFIED IN WRITING OF ANY CONDITIONS THAT VARY FROM THOSE SHOWN ON THE PLANS. THE CONTRACTOR'S WORK SHALL NOT VARY FROM THE PLANS WITHOUT PRIOR REVIEW FROM THE ENGINEER.
6. CONTRACTOR IS RESPONSIBLE FOR EMPLOYING AND MAINTAINING ALL TRAFFIC CONTROL AND SAFETY MEASURES DURING CONSTRUCTION.
7. CONTRACTOR IS RESPONSIBLE FOR PROPERLY & SAFELY MAINTAINING AREA BETWEEN ALL ADJOINING PROPERTIES.
8. NO WORK, STORAGE OR TRESPASS SHALL BE PERMITTED BEYOND THE SITE PROPERTY LINES OR PUBLIC RIGHT–OF–WAY. ADJACENT PROPERTY OWNED BY THE DEVELOPER MAY BE BE USED FOR EQUIPMENT STORAGE DURING CONSTRUCTION OF THE PROPERTY.
9. ALL EXISTING LAWN AREA, CURBING, PAVING, SIDEWALKS, CULVERTS OR OTHER PUBLIC OR PRIVATE PROPERTY DAMAGED BY TRENCHING OR EXCAVATION OPERATIONS SHALL BE REPLACED OR REPAIRED TO A CONDITION EQUAL TO EXISTING, AS DESCRIBED IN CONTRACT DOCUMENTS OR AS ORDERED BY ENGINEER (AOBE). MAILBOXES, SIGN POSTS, ETC SHALL BE PROTECTED OR REMOVED AND REPLACED EXACTLY AS THEY WERE BEFORE BEING DISTURBED. REMOVE AND REPLACE AFFECTED CURBING AND SIDEWALK TO NEAREST JOINT. REMOVE PAVEMENT AND REPLACE TO SAW CUT LINE, SAW CUT IN STRAIGHT LINE TO POINT NEEDED TO BLEND GRADE, REMOVE LAWN AND REPLACE TO MINIMUM LIMIT OF EXCAVATION.
10. CONTRACTOR SHALL PROVIDE AN AS–BUILT PLAN OF THE PROPOSED IMPROVEMENTS BY A LICENSED SURVEYOR. IT SHALL INCLUDE BUT NOT LIMITED TO BUILDINGS, ROADWAYS, WALLS, UTILITIES (INCLUDING INVERTS, RIMS, PIPE SIZE AND DIMENSIONS), SIDEWALKS, ROADWAY RAMPS, CURBING, PARKING LOTS (INCLUDING STRIPING), LANDSCAPE AREAS, ETC. HARDCOPY AND ELECTRONIC COPIES SHALL BE PROVIDED TO OWNER AND PROJECT ENGINEER.

LAYOUT NOTES:

1. THE CONTRACTOR SHALL BE RESPONSIBLE FOR COORDINATING ALL FIELD LAYOUT. THE CONTRACTOR SHALL TAKE TIES TO ALL UTILITY CONNECTIONS AND PROVIDE MARKED–UP AS BUILT PLANS FOR ALL UTILITIES SHOWING TIES TO CONNECTIONS, BENDS, VALVES, LENGTHS OF LINES AND INVERTS. AS–BUILT PLANS SHALL BE REVIEWED BY THE OWNER AND THE ENGINEER. THE CONTRACTOR SHALL PROVIDE ANY CORRECTION OR ADDITIONS TO THE SATISFACTION OF THE OWNER AND THE ENGINEER BEFORE UTILITIES WILL BE ACCEPTED.
2. BUILDING DIMENSIONS TO BE TAKEN FROM ARCHITECTURAL BUILDING PLANS. NOTIFY THE ENGINEER OF ANY DEVIATION FROM CONDITIONS SHOWN ON THIS PLAN.
3. PRIOR TO THE START OF CONSTRUCTION OR EXCAVATION, TREES TO BE RETAINED SHALL BE PROTECTED BY SILT FENCE, SNOW FENCE, CONSTRUCTION FENCE, OR EQUAL, WHICH WILL BE PLACED AT THE DRIP LINE OR SEVERAL FEET BEYOND.
4. FENCING SHALL NOT CROSS PUBLIC SIDEWALKS.
5. NO STORAGE OR STOCKPILING OF CONSTRUCTION MATERIALS, DEBRIS, OR EQUIPMENT SHALL OCCUR WITHIN THE FENCED AREA.

ROCK REMOVAL NOTES:

ROCK REMOVAL IS NOT ANTICIPATED. IF ROCK REMOVAL SHALL BE NECESSARY FOR THE INSTALLATION OF THE PROPOSED WORK, SHALL BE BY MECHANICAL MEANS ONLY. BLASTING IS NOT PERMITTED.

PAVING NOTES:

1. NO VEHICULAR TRAFFIC OF ANY SORT SHALL BE PERMITTED ON THE SURFACE OF SUBBASE COURSE MATERIAL ONCE IT HAS BEEN FINE GRADED, COMPACTED, AND IS READY FOR PAVING. SUBBASE MATERIAL SO PREPARED FOR PAVING SHALL BE PAVED WITHIN THREE DAYS OF PREPARATION.
2. SUBBASE MATERIAL AND THE VARIOUS ASPHALT CONCRETE MATERIALS CALLED FOR IN THESE DRAWINGS SHALL CONFORM WITH THE MOST RECENT REFERENCED SECTION OF THE NEW YORK STATE DEPARTMENT OF TRANSPORTATION STANDARD SPECIFICATIONS FOR CONSTRUCTION AND MATERIALS. CONSTRUCTION SHALL BE AS FURTHER SET FORTH IN THOSE SPECIFICATIONS AND AS OTHERWISE PROVIDED FOR IN THESE DRAWINGS.
3. PLACE ASPHALT CONCRETE MIXTURE ON PREPARED SURFACE, SPREAD AND STRIKE–OFF USING A SELF–PROPELLED PAVING MACHINE, WITH VIBRATING SCREED. PLACEMENT IN INACCESSIBLE AND SMALL AREAS MAY BE BY HAND.
4. PROVIDE JOINTS BETWEEN OLD AND NEW PAVEMENTS OR BETWEEN SUCCESSIVE DAY'S WORK.
5. TACK COAT WHEN SPECIFIED OR CALLED OUT ON THE DRAWINGS OR REQUIRED BY THE REFERENCED SPECIFICATION SHALL CONFORM WITH THE FOLLOWING:
   - A. TACK COAT SHALL MEET THE MATERIAL REQUIREMENTS OF 702–90 ASPHALT EMULSION FOR TACK COAT OF THE NEW YORK STATE DEPARTMENT OF TRANSPORTATION STANDARD SPECIFICATIONS FOR CONSTRUCTION AND MATERIALS, DATED 2017, SHALL BE APPLIED IN ACCORDANCE WITH SECTION 407 – TACK COAT SHALL BE IN ACCORDANCE WITH THOSE SPECIFICATIONS AND AS OTHERWISE PROVIDED FOR IN THESE DRAWINGS.
   - B. REMOVE LOOSE AND FOREIGN MATERIAL FROM ASPHALT SURFACE BEFORE PAVING NEXT COURSE. USE POWER BROOMS, BLOWERS OR HAND BROOM.
   - C. APPLY TACK COAT TO ASPHALT PAVEMENT SURFACES & AND SURFACES OF CURBS, GUTTERS, MANHOLES, AND OTHER STRUCTURES PROJECTING INTO OR ABUTTING PAVEMENT. DRY TO A "TACKY" CONSISTENCY BEFORE PAVING.
   - D. TACK COAT ENTIRE VERTICAL SURFACE OF ABUTTING EXISTING PAVEMENT.
6. AFTER COMPLETION OF PAVING AND SURFACING OPERATIONS, CLEAN SURFACES OF EXCESS OR SPILLED ASPHALT, GRAVEL OR STONE MATERIALS TO THE SATISFACTION OF THE ENGINEER.

CITY OF POUGHKEEPSIE PLANNING BOARD - SANITARY & SEWER NOTES:

1. FLOOR DRAINS, IF CONSTRUCTED, SHALL BE CONNECTED TO THE SANITARY SEWER. FLOOR DRAINS DO NOT INCLUDE FOUNDATION/FOOTER DRAIN: ALL DISCHARGES TO THE SANITARY SEWER SHALL COMPLY WITH THE EFFLUENT LIMITS OF THE LOCAL AND/OR DUTCHESS COUNTY SANITARY CODE.
2. SANITARY SEWERS AND APPURTENANCES SHALL BE CONSTRUCTED IN ACCORDANCE WITH THE LATEST STANDARDS AND SPECIFICATIONS OF THE CITY OF POUGHKEEPSIE. ALL SANITARY SEWER SYSTEM COMPONENTS SHALL BE INSTALLED BY OR UNDER THE SUPERVISION OF A CITY OF POUGHKEEPSIE LICENSED PLUMBER IN ACCORDANCE WITH THE CITY PLUMBING CODE.
3. MAJOR EARTHWORK SHALL BE COMPLETED PRIOR TO INSTALLATION OF ANY SANITARY SEWER MAINS AND APPURTENANCES. ALL CONNECTING SEWER LINES SHALL BE FLUSHED BEFORE TESTED.
4. CITY SANITARY SEWER MAINS ARE TO BE POLYVINYL CHLORIDE (PVC) SDR–21. PROJECT SANITARY LATERALS SHALL BE PVC, SDR–35, UNLESS OTHERWISE NOTED.
5. FINAL SEWER COLLECTION SYSTEM LAYOUT IS SUBJECT TO REVIEW, REVISION AND APPROVAL BY THE MUNICIPAL SEWER DEPARTMENT.
6. ALL SANITARY PIPE AND/OR MANHOLES SHALL BE A MINIMUM OF TEN (10) HORIZONTAL FEET FROM THE WATER MAIN. SANITARY PIPE SHALL HAVE A MINIMUM 18" SEPARATION FROM ANY WATER MAIN OR WATER SERVICE LINE. IF FOR SOME REASON THIS SEPARATION CANNOT BE ACHIEVED, SANITARY SEWER PIPE IN THE AREA SHALL BE SDR–21 PRESSURE RATED PIPE, AND ONE FULL LENGTH OF WATER MAIN SHALL BE CENTERED UNDER OR OVER THE SEWER. ALL SANITARY SEWER CONSTRUCTION SHALL BE TO SPECIFICATIONS OF THE MUNICIPAL SEWER DEPARTMENT.
7. ALL SANITARY TESTING SHALL BE PERFORMED UNDER THE SUPERVISION OF THE PROJECT ENGINEER, AND, CERTIFICATES OF COMPLIANCE WITH THE INSTALLATION SPECIFICATIONS, TEST STANDARDS, APPROVED PLANS OR APPROVED AMENDMENTS SHALL BE PROVIDED TO THE APPROPRIATE SEWER AUTHORITY AS A CONDITION OF APPROVAL FOR OPERATION.
8. ALL SANITARY SEWER CONSTRUCTION SHALL BE SUBJECT TO INSPECTION BY THE MUNICIPAL SEWER SUPERINTENDENT PRIOR TO BACKFILLING. PIPE BEDDING AND PIPE ZONE MATERIAL SHALL BE IN ACCORDANCE WITH THIS SHEET, DETAIL 1.
9. ALL NEW SANITARY SEWER MANHOLE COVERS SHALL BE MINIMUM NOMINAL 24" DIAMETER CAST IRON AND SHALL READ "SANITARY SEWER". FRAMES SHALL BE 8–INCHES IN HEIGHT.
10. INDICATOR TAPE SHALL BE PLACED 12" BELOW FINISHED GRADE DIRECTLY ABOVE ALL SANITARY LINES.
11. LOCATION OF SEWER LATERAL CLEAN OUTS ARE TO BE PLACED AS SHOWN ON THE APPROVED SITE PLAN AND NOT TO EXCEED EVERY 75' MEASURED FROM THE SEWER MAIN CONNECTION OR AS DETERMINED BY THE MUNICIPAL SUPERINTENDENT OF SEWERS WHERE LOCATIONS ARE NOT SPECIFICALLY SHOWN.
12. EXTERNAL DROP MANHOLES SHALL BE USED FOR SEWERS ENTERING AT AN ELEVATION OF 24 INCHES OR HIGHER AT THE INLET OF A SEWER MANHOLE.

TESTING GRAVITY SEWER SYSTEM:

1. CONTRACTOR SHALL INSPECT AND TEST THE INSTALLATIONS AS REQUIRED BY THE AUTHORITY HAVING JURISDICTION WHEN WORK IS READY FOR TESTING. AFTER ALL TESTS HAVE BEEN PERFORMED, EVIDENCE OF COMPLIANCE SHALL BE FORWARDED TO OWNER/ENGINEER AND THE AUTHORITY HAVING JURISDICTION PRIOR TO ACCEPTANCE.
2. THE CONTRACTOR SHALL TEST AND INSPECT FOR ALIGNMENT OF ALL SANITARY SEWERS.
3. EACH MANHOLE–TO–MANHOLE SECTION SHALL BE REJECTED OR ACCEPTED BASED ONLY ON RESULTS OF ITS OWN INDEPENDENT SECTION TEST AND NOT ON RESULTS OF ANY ONE TEST RUN SIMULTANEOUSLY OVER MORE THAN ONE CONSECUTIVE MANHOLE–TO–MANHOLE SECTION. THE ONLY EXCEPTION ALLOWED: ACCEPTING SEVERAL CONSECUTIVE MANHOLE–TO–MANHOLE SECTIONS BASED ON ONE COMBINED INFILTRATION TEST INDICATING ZERO INFILTRATION.
4. LOW PRESSURE AIR TESTING SHALL BE PERFORMED UNDER DIRECTION OF ENGINEER ACCORDING TO ASTM F1417. LOW PRESSURE AIR TEST IS A COMPARISON OF THE MEASURED TIME NECESSARY FOR ONE (1) PSIG PRESSURE DROP TO OCCUR, IF AT ALL, WITH MINIMUM ALLOWABLE TIME FOR THAT PRESSURE DROP TO OCCUR DETERMINED BY METHODS INDICATED IN ASTM F1417. IF THE ONE (1) PSIG PRESSURE DROP OCCURS FASTER THAN ALLOWABLE TIME, SECTION IS UNACCEPTABLE.
5. AN AIR TEST SHALL NOT BE RUN UNTIL SECTION OF LINE TO BE TESTED HAS BEEN CLEANED OF ALL FOREIGN MATERIAL BY FLUSHING AND HAS BEEN VISUALLY INSPECTED AND APPROVED BY THE ENGINEER. CERTAIN PIPE MATERIALS PRODUCE MORE CONSISTENT RESULTS WHEN INTERIOR OF PIPE IS WETTED PRIOR TO TESTING.
6. WHERE FLEXIBLE PIPE IS USED, CONTRACTOR SHALL TEST ALL MAINLINE PIPE FOR MAXIMUM ALLOWABLE DEFLECTION OF 5% OF OUTSIDE DIAMETER. DEFLECTION TESTS SHALL BE PERFORMED USING A CIRCULAR STEEL BALL ON SLED 1/16–INCH IN DIAMETER SMALLER THAN ALLOWABLE INSIDE DIAMETER OF FLEXIBLE PIPE WHEN DEFLECTED A MAXIMUM OF 5% OF OUTSIDE DIAMETER. DEFLECTION TESTING OF ANY PIPE SHALL BE DONE NO SOONER THAN 30 DAYS AFTER DATE OF INSTALLATION OF PIPE SECTION UNLESS WRITTEN EXCEPTION.
7. SEWERS SHALL BE LAID WITH STRAIGHT ALIGNMENT BETWEEN MANHOLES. STRAIGHT ALIGNMENT SHALL BE CHECKED EITHER USING A LASER BEAM OR LAMPING. TESTING SHALL COMPLY WITH REQUIREMENTS OF THE AUTHORITY HAVING JURISDICTION.
8. MANHOLES, WHICH CANNOT BE PROPERLY AIR TESTED, SHOULD BE VISUALLY INSPECTED AND LEAKAGE–TESTED USING INTERNAL OR EXTERNAL HYDROSTATIC PRESSURE. LEAKAGE TESTING SHALL COMPLY WITH REQUIREMENTS OF THE AUTHORITY HAVING JURISDICTION.
9. IN AREAS WHERE CONVENTIONAL TESTING IS IMPRACTICAL (I.E. AREAS DESIGNATED BY ENGINEER WHERE EXISTING SERVICES ARE TIED INTO NEW LINE IMMEDIATELY AND ANY BLOCKAGE COULD RESULT IN HEALTH PROBLEMS) NO LINES SHALL BE BACKFILLED UNTIL EACH PIPE SECTION AND CONNECTION IS INSPECTED AND APPROVED.
10. WHERE SEWERS ARE CONSTRUCTED OF PRESSURE–RATED PIPE AND INSTALLED WITH LESS THAN 18 INCHES VERTICAL SEPARATION FROM EXISTING OR PROPOSED WATER MAINS, SEWERS SHALL BE HYDROSTATICALLY TESTED AT 150 PSI TO ASSURE WATER TIGHTNESS. HYDROSTATIC ACCEPTANCE TESTS SHALL BE CONDUCTED AS SPECIFIED FOR TESTING WATER MAINS, EXCEPT THAT TESTING MAY BE PERFORMED WITH THE PIPE SECTION PARTIALLY BACK–FILLED.
11. IF THE ALLOWABLE RATE OF AIR LEAKAGE IS EXCEEDED, THE CONTRACTOR SHALL LOCATE POINTS OF EXCESSIVE LEAKAGE AND SHALL PROMPTLY CORRECT, REPAIR, AND BRING SYSTEM UP TO THE STANDARD. COSTS OF ALL SUCH REPAIRS AND CORRECTIVE MEASURES, INCLUDING COSTS OF REPEATED TESTS, SHALL BE BORN BY CONTRACTOR, THE SEWER LINE SECTION (INCLUDING MANHOLES AND BUILDING SERVICES) UNDER TEST SHALL NOT BE ACCEPTED UNTIL THESE TEST CRITERIA ARE MET.
12. SANITARY MANHOLES SHALL BE VACUUM TESTED IN ACCORDANCE WITH ASTM C1244. A VACUUM OF 10 INCHES OF Hg SHOULD BE DRAWN ON THE MANHOLE AFTER ALL HOLES ARE PLUGGED, AND INLETS/OUTLETS ARE TEMPORARILY PLUGGED AND SECURED. THE TIME IS MEASURED FOR THE VACUUM TO DROP TO 9 INCHES Hg. THE MANHOLE IS ACCEPTED IF THE MEASURED TIME MEETS OR EXCEEDS THE VALVES PRESENTED IN TABLE 1 OF ASTM C1244. IF THE MANHOLE FAILS THE INITIAL TEST, IT SHALL BE REPAIRED BY AN APPROVED METHOD UNTIL A SATISFACTORY TEST IS OBTAINED. MANHOLES, WHICH CANNOT BE PROPERLY AIR TESTED, SHOULD BE VISUALLY INSPECTED AND LEAKAGE–TESTED USING INTERNAL OR EXTERNAL HYDROSTATIC PRESSURE. LEAKAGE TESTING SHALL COMPLY WITH REQUIREMENTS OF THE AUTHORITY HAVING JURISDICTION.

WATER MAIN DISINFECTION NOTES:

1. APPROVED AND TESTED WATER MAIN SHALL BE DISINFECTED PER A.W.W.A. SECTION C651, LATEST EDITION. TABLET OR POWDERED METHOD IS NOT ALLOWED.
2. THE CONTRACTOR SHALL NOTIFY THE MUNICIPALITY AND THE PROJECT ENGINEER 48 HOURS PRIOR TO DISINFECTING THE SERVICE LINES.
3. DISINFECTED WATER MUST REMAIN IN THE WATER MAINS FOR A MINIMUM OF 24 HOURS BEFORE BEING THOROUGHLY FLUSHED OUT.
4. WATER SERVICE LINES SHALL BE DISINFECTED AS PER AWWA SECTION C651 WHERE:
   - A. CHLORINE CONCENTRATION IN WATER LINES SHALL BE NO LESS THAN 50 MG/L AT START OF 24–HOUR TEST.
   - B. CHLORINE RESIDUAL SHALL BE NO LESS THAN 10 MG/L AT END OF TEST.
5. PRIOR TO RECEIVING CERTIFICATE OF OCCUPANCY, MICROBIOLOGICAL SAMPLES SHALL BE COLLECTED FROM BOTH ENDS AND THE MIDDLE OF EACH NEW LINE. ALL LINES SHALL NOT BE USED UNTIL MICROBIOLOGICAL SAMPLES ARE ACCEPTED BY THE CITY OF POUGHKEEPSIE. RESULTS OF ALL MICROBIOLOGICAL TESTING SHALL BE SUBMITTED TO THE CITY OF POUGHKEEPSIE ALONG WITH ENGINEER'S CERTIFICATE OF COMPLETION.

TESTING WATER MAINS:

1. AFTER TRENCH HAS BEEN BACKFILLED, HYDROSTATIC ACCEPTANCE TESTS, CONSISTING OF A PRESSURE TEST AND A LEAKAGE TEST, SHALL BE PERFORMED ON ALL SECTIONS OF WATER MAINS INSTALLED. LEAKAGE TEST SHALL BE CONDUCTED CONCURRENTLY WITH PRESSURE TEST. TEST SECTION SHALL BE LIMITED TO 1,500 FT (MAX.). TESTS SHOULD BE CONDUCTED TO FIRST VALVE IN BUILDING.
2. AFTER ALL TESTS AND INSPECTIONS HAVE BEEN PERFORMED EVIDENCE OF COMPLIANCE SHALL BE FORWARDED TO OWNER/ENGINEER AND THE CITY OF POUGHKEEPSIE PRIOR TO ACCEPTANCE.
3. ALL WATER FOR TESTS SHALL BE FURNISHED AND DISPOSED OF BY THE CONTRACTOR AT THE CONTRACTOR'S EXPENSE. SOURCE AND/OR QUALITY OF WATER WHICH THE CONTRACTOR PROPOSES TO USE IN TESTING LINES SHALL BE ACCEPTABLE TO THE ENGINEER.
4. HYDROSTATIC PRESUMPTIVE TESTS MAY BE PERFORMED WHEN SYSTEM IS PARTIALLY BACKFILLED TO SIMPLY CHECK WORK, BUT ACCEPTANCE OF SYSTEM SHALL BE BASED ON HYDROSTATIC TESTS RUN ON FINISHED SYSTEM AFTER IT HAS BEEN COMPLETELY BACKFILLED. ALL HYDROSTATIC TESTS SHALL BE PERFORMED IN ACCORDANCE WITH SECTION 4 OF AWWA STANDARD C 600 OR LATER ADDITION, AS MODIFIED HEREIN.
5. FOR THE PRESSURE TEST, SYSTEM SHALL BE PRESSURIZED AND MAINTAINED AT A MINIMUM OF 150 POUNDS PER SQUARE INCH, OR 1.5 TIMES THE WORKING PRESSURE, WHICHEVER IS GREATER, BASED ON THE ELEVATION OF THE LOWEST POINT IN THE SECTION BEING TESTED AND CORRECTED TO THE ELEVATION OF THE GAUGE. PROVISIONS SHALL BE MADE TO RELIEVE AIR TRAPPED AT HIGH POINTS IN THE SYSTEM THROUGH ADJACENT HYDRANTS OR THROUGH TAPS AND CORPORATION STOPS INSTALLED FOR THIS PURPOSE BY THE CONTRACTOR. AFTER SAID PRESSURE HAS BEEN MAINTAINED SUCCESSFULLY, WITH FURTHER PUMPING AS REQUIRED, FOR A PERIOD OF AT LEAST TWO HOURS, THE SECTION UNDER TEST SHALL BE CONSIDERED TO HAVE PASSED THE PRESSURE TEST.
6. LEAKAGE TEST SHALL BE PERFORMED CONCURRENTLY USING A MINIMUM TEST PRESSURE OF 150 LBS/SQUARE INCH, OR 1.5 TIMES THE WORKING PRESSURE, WHICHEVER IS GREATER, BASED ON THE ELEVATION OF THE LOWEST POINT IN THE SECTION UNDER TEST AND CORRECTED TO ELEVATION OF THE GAUGE. LEAKAGE TEST DURATION SHALL BE A MINIMUM OF 2 HOURS AFTER LEAKAGE RATE HAS STABILIZED.
7. MAXIMUM ALLOWABLE LEAKAGE SHALL BE AS SHOWN IN THE FOLLOWING TABLE: ALLOWABLE LEAKAGE PER 1000 FT (305M) OF PIPELINE (GPH)

AVG. TEST PRESSURE	NOMINAL PIPE DIAMETER–IN.						
PSI	4	6	8	10	12	14	16
450	0.57	0.86	1.15	1.43	1.72	2.01	2.29
400	0.54	0.81	1.08	1.35	1.62	1.89	2.16
350	0.51	0.76	1.01	1.26	1.52	1.77	2.02
300	0.47	0.70	0.94	1.17	1.40	1.64	1.87
275	0.45	0.67	0.90	1.12	1.34	1.57	1.79
250	0.43	0.64	0.85	1.07	1.28	1.50	1.71
225	0.41	0.61	0.81	1.01	1.22	1.42	1.62
200	0.38	0.57	0.76	0.96	1.15	1.34	1.53
175	0.36	0.54	0.72	0.89	1.07	1.25	1.43
150	0.33	0.50	0.66	0.83	0.99	1.16	1.32
125	0.30	0.45	0.60	0.76	0.91	1.06	1.21
100	0.27	0.41	0.54	0.68	0.81	0.95	1.08

8. IF LEAKAGE IN SYSTEM EXCEEDS THE SPECIFIED AMOUNT, THE CONTRACTOR SHALL, AT NO ADDED COST TO THE OWNER, LOCATE, REPAIR, AND/OR REPLACE DEFECT(S) AND RE–TEST PIPING SYSTEM.

COMPACTION REQUIREMENTS

LOCATION	COMPACTION	TESTING FREQUENCY
PIPE TRENCH BACKFILL (IN PAVED AREAS)	95% ASTM D1557	1 SERIES OF TESTS FOR EACH 150 FT OR LESS OF TRENCH LENGTH. SERIES INCLUDE 3 COMPACTION TESTS SPREAD EVENLY ALONG TRENCH PROFILE.
PIPE TRENCH BACKFILL (IN UNPAVED AREAS)	90% ASTM D1557	1 SERIES OF TESTS FOR EACH 150 LF OR LESS OF TRENCH LENGTH. SERIES INCLUDE 3 COMPACTION TESTS SPREAD EVENLY ALONG TRENCH PROFILE.
PIPE BEDDING AND PIPE ZONE BACKFILL	95% ASTM D1557	1 TEST FOR EACH 150 FT OR LESS OF TRENCH LENGTH.
PAVEMENT SUBBASE AND LAST LIFT OF SELECT GRANULAR FILL (FILL BETWEEN SHEET PILES)	95% ASTM D1557	1 TEST FOR EVERY 2,000 SQ FT, OF LIFT AREA BUT NO FEWER THAN TWO TESTS PER LIFT

CITY OF POUGHKEEPSIE WATER MAIN NOTES:

1. ALL WATER MAINS SHALL BE CEMENT LINED DUCTILE IRON PIPE, CLASS 52 PUSH–ON JOINT, UNLESS OTHERWISE SPECIFIED BY OR APPROVED BY THE CITY OF POUGHKEEPSIE WATER DEPARTMENT. JOINING SHALL EMPLOY MECHANICAL JOINT RESTRAINT CONNECTIONS SUCH AS CLOW F–1058, MEGALUG, STAR PIPE SERIES 600 "MEGALUG" CONNECTIONS, FIELD LOK GASKET, OR AS ALTERNATIVELY SPECIFIED BY THE CITY OF POUGHKEEPSIE WATER DEPARTMENT. ALL WATER PIPING CONSTRUCTION SHALL BE TO THE SPECIFICATIONS OF THE CITY OF POUGHKEEPSIE WATER DEPARTMENT. WET TAP OF PUBLIC WATER SYSTEM SHALL BE APPROVED AND SUPERVISED BY THE CITY OF POUGHKEEPSIE WATER DEPARTMENT. TAPPING SLEEVE SHALL BE STAINLESS STEEL OR APPROVED EQUAL. ALL MAINLINE VALVES SHALL BE RESILIENT WEDGE OR APPROVED EQUAL.
2. THE WATER LINE MAY BE FLEXED WITHIN PIPE SPECIFICATIONS OR LAID DEEPER IN AREAS WHERE A CROSSING WITH A SANITARY LINE OCCURS, TO ACHIEVE THE REQUIRED 1.5' VERTICAL SEPARATION DISTANCE. IF THIS DISTANCE CANNOT BE REASONABLY ACHIEVED, THE CONTRACTOR SHALL USE PRESSURE RATED SANITARY SEWER PIPE OF EQUAL OR GREATER RATEING THAT THE PRESSURE CLASS FOR THE WATER LINE.
3. MINIMUM VERTICAL SEPARATION BETWEEN WATER MAINS AND SEWER PIPE SHALL BE 18 INCHES MEASURED FROM THE OUTSIDE OF THE PIPES AT THE POINT OF CROSSING. ONE FULL STANDARD LAYING LENGTH OF WATER MAIN SHALL BE CENTERED UNDER OR OVER THE SEWER SO THAT BOTH JOINTS WILL BE AS FAR FROM THE SEWER LINE AS POSSIBLE. IN ADDITION, WHEN THE WATER MAIN PASSES UNDER A SEWER, ADEQUATE STRUCTURAL SUPPORT (COMPACTED SELECT FILL) SHALL BE PROVIDED FOR THE SEWER TO PREVENT EXCESSIVE DEFLECTION OF JOINTS AND SETTLING OF THE SEWER PIPE ON THE WATER MAIN. MINIMUM HORIZONTAL SEPARATION BETWEEN PARALLEL WATER MAINS AND SEWER PIPES (INCLUDING MANHOLES AND VAULTS) SHALL BE 10 FEET MEASURED FROM THE OUTSIDE OF THE PIPES, MANHOLES OR VAULTS.
4. ALL WATER MAINS SHALL HAVE A MINIMUM OF (5) FIVE FEET OF COVER FROM THE TOP OF THE MAIN TO FINISHED GRADE. THE CONTRACTOR SHALL CHECK ALL FINISHED GRADE STAKES BEFORE TRENCHING TO ENSURE THAT ALL INSTALLED WATERMAINS WILL HAVE THE REQUIRED COVER.
5. THE SUPPLIER OF WATER MUST RECEIVE AT LEAST 48–HOUR ADVANCE NOTIFICATION REQUESTING SAMPLING SERVICES. SAMPLING WILL NOT BE PERFORMED PRIOR TO RECEIPT FROM A NEW YORK STATE LICENSED OR REGISTERED DESIGN PROFESSIONAL (ENGINEER, ARCHITECT, OR LAND SURVEYOR WITH A SPECIAL EXEMPTION UNDER SECTION 7208(N) OF THE EDUCATION LAW) CERTIFYING THAT THE WATER SUPPLY IMPROVEMENTS, TESTING AND DISINFECTION PROCEDURES WERE COMPLETED IN ACCORDANCE WITH THE APPROVAL PLANS, REPORTS, SPECIFICATIONS AND ANY APPROVED AMENDMENTS. A NYSDOH CERTIFIED LABORATORY WILL COLLECT SAMPLES FOR FREE CHLORINE RESIDUAL, TOTAL AND FECAL COLIFORM AND 24–HOUR BACTERIAL PLATE COUNT. THE CERTIFICATE OF COMPLIANCE SHALL BE PROVIDED TO THE WATER MAINTENANCE SUPERVISOR AS A CONDITION OF APPROVAL FOR OPERATION.
6. THE CONTRACTOR SHALL COORDINATE THE TESTING WITH THE WATER DEPARTMENT SO AS TO MAINTAIN THE AMOUNT OF SERVICE INTERRUPTION TO EXISTING USERS TO THE LEAST EXTENT PRACTICABLE. WATER MAIN INSTALLATION AND TESTING SHALL BE PERFORMED UNDER THE SUPERVISION OF THE PROJECT ENGINEER OR HIS DESIGNEE AS NECESSARY TO MEET CONDITIONS IN NOTE 5 ABOVE.
7. THE WATER MAIN SHALL BE DISINFECTED EQUAL TO AWWA STANDARD FOR DISINFECTING WATER MAINS DESIGNATION C651 (LATEST REVISION). FOLLOWING DISINFECTION, THE WATER MAIN SHALL BE FLUSHED UNTIL THE CHLORINE CONCENTRATION IN THE WATER LEAVING THE MAIN IS NO HIGHER THAN THAT GENERALLY PREVAILING IN THE SYSTEM. THE PROJECT ENGINEER OR HIS DESIGNEE SHALL ALSO WITNESS DISINFECTION AND FLUSHING.
8. ALL WATER MAIN FITTINGS NOT RECEIVING 24–HOUR CHLORINE DISINFECTION TIME MUST BE SWAB–DISINFECTED 30 MINUTES PRIOR TO INSTALLATION.
9. THE SAMPLING POINT(S) MUST BE DECONTAMINATED BY FLAMING.
10. FIRE HYDRANTS ARE NOT ACCEPTABLE SAMPLING POINTS.
11. FIRE HYDRANTS WEEP HOLES (DRAINS) SHALL BE PLUGGED WHEN GROUND WATER IS ENCOUNTERED WITHIN SEVEN FEET OF THE FINISHED GRADE. WHEN DRAINS ARE PLUGGED, THE BARRELS MUST BE PUMPED DRY AFTER USE DURING FREEZING WEATHER. SUCH HYDRANTS SHALL BE IDENTIFIED BY MARKINGS APPROVED BY THE CITY OF POUGHKEEPSIE WATER DEPARTMENT.
12. PROPOSED WATER METERS LOCATED WITHIN THE METER PIT OR BUILDING SHALL BE A COMPATIBLE REMOTE STYLE TYPE (SENSUS OR APPROVED EQUAL), AND SHALL BE APPROVED BY THE CITY OF POUGHKEEPSIE WATER DEPARTMENT PRIOR TO INSTALLATION. WATER METERS SHALL BE EQUIPPED WITH (RADIO TYPE) TRANSCEIVER PROVIDED BY THE CITY OF POUGHKEEPSIE WATER DEPARTMENT.
13. THE WATER LINE SHALL BE INSTALLED AT A CONTINUOUS GRADE WITH NO ABRUPT HIGH POINTS OR LOW POINTS.
14. FINAL WATER DISTRIBUTION SYSTEM IS SUBJECT TO REVIEW, REVISION AND APPROVAL BY THE CITY OF POUGHKEEPSIE WATER DEPARTMENT.
15. ALL WATER MAINS AND RELATED APPURTENANCES SHALL BE CONSTRUCTED TO THE LATEST STANDARDS AND SPECIFICATIONS OF THE CITY OF POUGHKEEPSIE.
16. THE WATER MAIN SHALL NOT BE PLACED INTO SERVICE UNTIL SO AUTHORIZED BY THE CITY OF POUGHKEEPSIE.
17. ALL WATER SERVICE CONSTRUCTION SHALL BE SUBJECT TO INSPECTION BY THE CITY WATER DEPARTMENT PRIOR TO BACKFILLING.
18. THE SITE UTILITY CONTRACTOR SHALL BE RESPONSIBLE FOR ALL BURIED PIPING TO THE LOCATION OF THE PROPOSED BUILDING CONNECTION POINT (I.E. INSIDE THE BUILDING). THIS INCLUDES THE TESTING AND CERTIFICATION OF ALL WATER SERVICE WORK FROM THE CITY WATER CONNECTION POINT TO THE PROPOSED BUILDINGS INTERIOR CONNECTION POINT.
19. ALL WATER SERVICE PIPING INSTALLATION, BACKFILL AND TESTING SHALL BE REVIEWED, AND APPROVED BY THE CITY OF POUGHKEEPSIE WATER MAINTENANCE SUPERVISOR OR HIS DESIGNEE.
20. PIPE BEND FITTINGS SHOWN ON THE DRAWINGS ARE INDICATIVE OF PROBABLE DIRECTIONAL CHANGES IN THE PROPOSED WATER MAIN ALIGNMENT. THE CONTRACTOR SHALL PROVIDE AND INSTALL ALL FITTINGS, EITHER SHOWN OR FIELD REQUIRED, AS PART OF THE CONTRACTOR'S CONTRACT AT NO ADDITIONAL COST TO THE OWNER.
21. THE CONTRACTOR SHALL PROVIDE AND INSTALL BRASS WEDGES ACROSS ALL PIPE JOINTS TO ENSURE ELECTRICAL CONDUCTIVITY. THE LOCATION AND THE NUMBER OF WEDGES TO BE PROVIDED SHALL BE ACCORDING TO THE PIPE MANUFACTURER'S RECOMMENDATIONS AND THE SPECIFICATIONS.
22. SHEETING AND EXCAVATION BRACING FOR THE WATERMAIN INSTALLATION SHALL BE PROVIDED IN ACCORDANCE WITH OSHA REQUIREMENTS TO SUIT EXISTING SOIL CONDITIONS. SHEETING, IF REQUIRED, SHALL BE TIGHT WOOD SHEETING AND SHALL BE LEFT IN PLACE, AND AFTER BACKFILLING SHALL BE CUT AT GROUND LEVEL OR AS ORDERED BY THE OWNER'S REPRESENTATIVE.
23. REDUCE PRESSURE ZONE VALVE TO BE PROVIDED ON FIRE SUPPLY AND DOUBLE CHECK VALVE TO BE PROVIDED ON THE DOMESTIC SUPPLY AT EACH LOCATION WHERE WATER LINE ENTERS THE BUILDING. BACKFLOW ASSEMBLES SHALL BE LISTED IN UNIVERSITY OF SOUTHERN CALIFORNIA LIST OF APPROVED BACKFLOW PREVENTION ASSEMBLES.
24. ALL BACKFLOW PREVENTION AND METER SHALL BE LOCATED INSIDE THE NEW BUILDING.

DUTCHESS COUNTY STANDARD NOTES FOR SEWER/WATER SYSTEMS:

THE DESIGN, CONSTRUCTION AND INSTALLATION SHALL BE IN ACCORDANCE WITH THIS PLAN AND GENERALLY ACCEPTED STANDARDS IN EFFECT AT THE TIME OF CONSTRUCTION WHICH INCLUDE:

- "NEW YORK STATE DESIGN STANDARDS FOR INTERMEDIATE SIZED WASTEWATER TREATMENT SYSTEMS", NYSDEC
- "RECOMMENDED STANDARDS FOR SEWAGE TREATMENT WORKS, (TEN STATES)."
- "RECOMMENDED STANDARDS FOR WATER WORKS, (TEN STATES)."
- "NEW YORK STATE DEPARTMENT OF HEATH AND DUTCHESS COUNTY ENVIRONMENTAL HEALTH SERVICES DIVISION POLICIES, PROCEDURES AND STANDARDS."
- "DUTCHESS COUNTY AND NEW YORK STATE SANITARY CODES."
- "DUTCHESS COUNTY ENVIRONMENTAL HEALTH SERVICES DIVISION CERTIFICATE OF APPROVAL LETTER."

THIS PLAN IS APPROVED AS MEETING THE APPROPRIATE AND APPLIED TECHNICAL STANDARDS, GUIDELINES, POLICIES AND PROCEDURES FOR ARRANGEMENT OF SEWAGE DISPOSAL AND WATER SUPPLY FACILITIES.

UPON COMPLETION OF THE FACILITIES, THE FINISHED WORKS SHALL BE INSPECTED, TESTED, AND CERTIFIED COMPLETE TO THE DC EHSD BY THE NEW YORK STATE LICENSED PROFESSIONAL ENGINEER SUPERVISING CONSTRUCTION. NO PART OF THE FACILITIES SHALL BE PLACED INTO SERVICE UNTIL ACCEPTED BY THE DC EHSD.

APPROVAL OF ANY PLAN(S) OR AMENDMENT THERETO SHALL BE VALID FOR A PERIOD OF FIVE (5) YEARS FROM THE DATE OF APPROVAL. FOLLOWING THE EXPIRATION OF SAID APPROVAL, THE PLAN(S) SHALL BE RE–SUBMITTED TO THE COMMISSIONER OF HEALTH FOR CONSIDERATION FOR RE–APPROVAL. RE–SUBMISSION OR REVISED SUBMISSION OF PLANS AND/OR ASSOCIATED DOCUMENTS SHALL BE SUBJECT TO COMPLIANCE WITH THE TECHNICAL STANDARDS, GUIDELINES, POLICIES AND PROCEDURES IN EFFECT AT THE TIME OF THE RE–SUBMISSION.

NO CELLAR, FOOTING, FLOOR, GARAGE, COOLER OR ROOF DRAINS SHALL BE DISCHARGED INTO THE SEWAGE COLLECTION SYSTEM.

ALL BUILDINGS SHALL BE CONSTRUCTED AT AN ELEVATION HIGH ENOUGH TO ENSURE GRAVITY FLOW TO THE SEWAGE COLLECTION SYSTEM.

ALL REQUIRED EROSION & SEDIMENT CONTROL AND STORMWATER POLLUTION PREVENTION WATER QUALITY & QUANTITY CONTROL STRUCTURES, PERMANENT AND TEMPORARY, ARE SHOWN ON THE PLANS.

THE DC EHSD SHALL BE NOTIFIED SIXTY DAYS PRIOR TO ANY CHANGE IN USE; USE CHANGES MAY REQUIRE RE–APPROVAL BY THE DC EHSD.

NO BUILDINGS ARE TO BE OCCUPIED AND THE NEW WATER SYSTEM SHALL NOT BE PLACED INTO SERVICE, UNTIL A "COMPLETED WORKS APPROVAL" IS USED UNDER SECTION 5–1.22(D) OF PART 5 OF THE NEW YORK STATE SANITARY CODE (10NYCRR5)

NO BUILDINGS ARE TO BE OCCUPIED AND THE NEW WASTEWATER COLLECTION SYSTEM SHALL NOT BE PLACED INTO SERVICE UNTIL, A "CERTIFICATE OF CONSTRUCTION COMPLIANCE" IS ISSUED UNDER SECTION 19.7 OF ARTICLE 19 OF THE DUTCHESS COUNTY SANITARY CODE

ALL SERVICE LINES ARE THE RESPONSIBILITY OF THE OWNER UP TO THE PROPERTY LINE. THE WATER AND SEWER COMPANIES SHALL BE RESPONSIBLE FOR ALL VALVES AND PIPES WHICH ARE NOT ON THE OWNER'S PROPERTY.

THE UNDERSIGNED OWNERS OF THE PROPERTY HEREON STATE THAT THEY ARE FAMILIAR WITH THIS MAP, ITS CONTENTS AND ITS LEGENDS AND HEREBY CONSENT TO ALL SAID TERMS AND CONDITIONS STATES HEREON.

LaBella
Powered by partnership.

21 Fox Street
Poughkeepsie, NY 12601
(845) 454-3980

labellapc.com



It is a violation of New York Education Law Article 145 Sec.7209, for any person, unless acting under the direction of a licensed architect, professional engineer, or land surveyor, to alter an item in any way. If an item bearing the seal of an architect, engineer, or land surveyor is altered; the altering architect, engineer, or land surveyor shall affix to the item their seal and notation "altered by" followed by their signature and date of such alteration, and a specific description of the alteration.

© 2022 LaBella Associates

APPLICANT NAME & ADDRESS:

ARGO DEVELOPMENT
95 CHESTNUT RIDGE ROAD
MONTVALE, NJ 07645

PROJECT NAME & LOCATION:

SOUTH AVE MULTI-FAMILY DEVELOPMENT
SOUTH AVENUE
CITY OF POUGHKEEPSIE, NY 12601

NO:	DATE:	DESCRIPTION:
1	01/27/23	NO CHANGE THIS SHEET

Revisions

PROJECT NUMBER: 2222201

DRAWN BY:

REVIEWED BY: CPL

ISSUED FOR: PLANNING BOARD REVIEW

DATE: 11/28/2022

DRAWING NAME:

NOTES

DRAWING NUMBER:

G002

4/3/2023 12:20:23 PM
B:\GLOBAL\Projects\ARGO\2222201 - South Ave Multi Family Dev\06_Drawings\Civil\00_G002_2222201_LEGNOTE.dwg

Drawing Name: B:\GLOBAL\Projects\ARGO\2222201 – South Ave Multi Family Dev\06_Drawings\Civil\00_G002_2222201_LEGNOTE.dwg
Xref's Attached: XBORDER_2222201
Date Printed: Apr 03, 2023, 12:20pm



VICINITY MAP
SCALE: 1"=1,000'



1 SV1 EXISTING CONDITIONS SURVEY
SCALE: 1" = 30'

LEGEND:

EXISTING CONDITIONS:

- PROPERTY LINE NO PHYSICAL BOUNDS
- ADJACENT PROPERTY LINE
- 110 EXISTING MAJOR CONTOUR
- EXISTING MINOR CONTOUR
- ×200.3 EXISTING SPOT GRADE
- EXISTING PROPERTY EASEMENT
- EXISTING BUILDING
- CONC. CURB EXISTING CURB/GUTTER
- X X X EXISTING FENCE
- EXISTING TREE LINE
- EXISTING BRUSH LINE
- OHW EXISTING OVERHEAD WIRES
- W EXISTING WATER LINE
- G EXISTING GAS LINE
- UE EXISTING UNDERGROUND ELECTRIC LINE
- UT EXISTING UNDERGROUND COMMUNICATIONS LINE
- S 8"SAN EXISTING UNDERGROUND SEWER LINE
- ST 15"RCP EXISTING UNDERGROUND STORM LINE

SYMBOLS:

- EXISTING SIGN
- PST EXISTING POST
- EXISTING DECIDUOUS TREE
- EXISTING MONUMENT
- IRF EXISTING IRON PIPE FOUND
- EXISTING BENCHMARK
- S EXISTING SANITARY MANHOLE
- D EXISTING DRAINAGE MANHOLE
- C EXISTING CATCH BASIN
- E EXISTING ELECTRIC MANHOLE
- E EXISTING ELECTRIC BOX
- EXISTING GUY WIRE
- EXISTING UTILITY POLE
- EXISTING LIGHT POLE
- UGC EXISTING CONDUIT TO/FROM UNDERGROUND
- EXISTING GAS VALVE
- EXISTING HYDRANT
- EXISTING WATER VALVE
- EXISTING TEST PIT

ABBREVIATIONS:

- ×BC:200.3 EXISTING SPOT GRADE BOTTOM CURB
- ×TC:200.3 EXISTING SPOT GRADE TOP CURB
- ×R:216.3 EXISTING RIM ELEVATION
- ×I:200.3 EXISTING INVERT ELEVATION

NOTES:

UNAUTHORIZED ALTERATION OR ADDITION TO A SURVEY MAP BEARING A LICENSED LAND SURVEYOR'S SEAL IS A VIOLATION OF SECTION 7209, SUBDIVISION 2 OF THE NEW YORK STATE EDUCATION LAW.

SURVEYED WITHOUT THE BENEFIT OF A TITLE SEARCH.

SUBJECT TO COVENANTS, EASEMENTS, RESTRICTIONS, CONDITIONS AND AGREEMENTS OF RECORD.

COPYRIGHT LABELLA ASSOCIATES PC, ALL RIGHTS RESERVED.

SUBSURFACE STRUCTURES NOT VISIBLE OR READILY APPARENT ARE NOT SHOWN AND THEIR LOCATION AND EXTENT ARE NOT CERTIFIED.

TOPOGRAPHY SHOWN HEREON WAS COMPILED FROM A FIELD SURVEY COMPLETED SEPTEMBER 26, 2022 BY LABELLA ASSOCIATES PC, DATUM NAVD-88, 1 FOOT CONTOUR INTERVAL.

NORTH ORIENTATION IS PER FILED MAP NO. 6217, SEE FILED MAP REFERENCE NO. 1 BELOW.

THE UNDERGROUND UTILITIES SHOWN HAVE BEEN LOCATED FROM FIELD SURVEY INFORMATION AND EXISTING DRAWINGS. THE SURVEYOR MAKES NO GUARANTEES THAT THE UNDERGROUND UTILITIES SHOWN COMPRISE ALL SUCH UTILITIES IN THE AREA, EITHER IN SERVICE OR ABANDONED. THE SURVEYOR FURTHER DOES NOT WARRANT THAT THE UNDERGROUND UTILITIES SHOWN ARE IN THE EXACT LOCATION INDICATED ALTHOUGH THE SURVEYOR DOES CERTIFY THAT THEY ARE LOCATED AS ACCURATELY AS POSSIBLE FROM INFORMATION AVAILABLE. THE SURVEYOR HAS NOT PHYSICALLY LOCATED THE UNDERGROUND UTILITIES.

THE CONTRACTOR SHALL COMPLY WITH NEW YORK STATE INDUSTRIAL CODE RULE 753 - 48 HOURS PRIOR TO DIGGING CALL DIGSAFELY NEW YORK 1-800-962-7962 TO HAVE PUBLIC UTILITY LOCATIONS PAINTED.

FILED MAP REFERENCE:

1. REFERENCE IS HEREBY MADE TO A CERTAIN MAP ENTITLED "SUBDIVISION PLAT BENDERSON DEVELOPMENT CO. INC., SITUATE IN THE CITY OF POUGHKEEPSIE DUTCHESS CO., N.Y." AND FILED IN THE DUTCHESS COUNTY CLERK'S OFFICE ON OCTOBER 6, 1981 AS FILED MAP NO. 6217.
2. REFERENCE IS HEREBY MADE TO A CERTAIN MAP ENTITLED "FOX STREET, LLC. SUBDIVISION PLAT OF LANDS OF FOX STREET, LLC., CITY OF POUGHKEEPSIE, DUTCHESS COUNTY, NEW YORK" AND FILED IN THE DUTCHESS COUNTY CLERK'S OFFICE ON NOVEMBER 1, 2002 AS FILED MAP NO. 11469.

DEED REFERENCE:

1. CITY OF POUGHKEEPSIE TO SOUTH AVENUE REAL ESTATE ASSOCIATES, LLC, DATED FEBRUARY 18, 1998 AND RECORDED IN THE DUTCHESS COUNTY CLERK'S OFFICE ON MARCH 10, 1998 AS LIBER 2006 OF DEEDS AT PAGE 456.

TAX PARCEL DESIGNATION:

CITY OF POUGHKEEPSIE, DUTCHESS COUNTY, NEW YORK
6061-52-937583

AREA:

2.77 AC.

FLOOD ZONE NOTE:

PARCEL IS SHOWN TO LIE WITHIN "OTHER AREAS, ZONE X" AS SHOWN ON FEDERAL EMERGENCY MANAGEMENT AGENCY (FEMA), NATIONAL FLOOD INSURANCE PROGRAM (NFIP) FLOOD INSURANCE RATE MAP (FIRM) FOR THE CITY OF POUGHKEEPSIE, IDENTIFIED AS MAP NUMBER 36027C0358E, BEARING AN EFFECTIVE DATE OF MAY 2, 2012.

STATE OF NEW YORK
DAVID H. DIPPEL
050677
LICENSED LAND SURVEYOR

David H. Dippel, L.S. NYS #050677

SURVEYOR'S CERTIFICATE:

I HEREBY CERTIFY THAT THIS SURVEY MAP IS BASED ON AN ACTUAL FIELD SURVEY COMPLETED ON OCTOBER 4, 2022 AND THAT THIS SURVEY MAP WAS MADE BY ME OR UNDER MY DIRECTION, AND CONFORMS WITH THE MINIMUM STANDARD OF PRACTICE ADOPTED BY THE NEW YORK STATE ASSOCIATION OF PROFESSIONAL LAND SURVEYORS.

LaBella
Powered by partnership.

21 Fox Street
Poughkeepsie, NY 12601
(845) 454-3980

labellapc.com

It is a violation of New York Education Law Article 145 Sec.7209, for any person, unless acting under the direction of a licensed architect, professional engineer, or land surveyor, to alter an item in any way. If an item bearing the seal of an architect, engineer, or land surveyor is altered; the altering architect, engineer, or land surveyor shall affix to the item their seal and notation "altered by" followed by their signature and date of such alteration, and a specific description of the alteration.

© 2022 LaBella Associates

ARGO DEVELOPMENT
95 CHESTNUT RIDGE ROAD
MONTVALE, NJ 07645

SOUTH AVE
MULTI-FAMILY DEVELOPMENT
SOUTH AVENUE
CITY OF POUGHKEEPSIE, NY 12601

30 0 30
SCALE IN FEET
1"=30'

NO:	DATE:	DESCRIPTION:
Revisions		

PROJECT NUMBER: 2222201
DRAWN BY: FJM
REVIEWED BY: DHD
ISSUED FOR:
DATE: 10/04/2022
DRAWING NAME:

MAP OF EXISTING CONDITIONS PREPARED FOR ARGO DEVELOPMENT

DRAWING NUMBER:

SV1

11/16/2022 9:04:27 AM
Z:\2022Projects\ARGO\2222201 - South Ave Multi Family Dev\06_Drawings\Survey\dwg\05_SV1_2222201-EXCOND.dwg



1 C-120 DEMOLITIONS PLAN
SCALE: 1" = 30'

LEGEND:

- EXISTING FEATURE TO BE REMOVED
- EXISTING TREE TO BE REMOVED
- EXISTING SITE FEATURE TO BE REMOVED
- EXISTING PAVEMENT & SIDEWALK TO BE REMOVED
- EXISTING BUILDING TO BE REMOVED
- WORKLIMITS
- TREE PROTECTION FENCING
- N.I.C. NOT IN CONTRACT
- EXISTING STRUCTURE TO BE REMOVED, N.I.C
- PAVEMENT SAWCUT LINE

LaBella
Powered by partnership.

21 Fox Street
Poughkeepsie, NY 12601
(845) 454-3980

labellapc.com

STATE OF NEW YORK
CHRISTOPHER PAUL LABELLA
LICENSED PROFESSIONAL ENGINEER
079470

It is a violation of New York Education Law Article 145 Sec.7209, for any person, unless acting under the direction of a licensed architect, professional engineer, or land surveyor, to alter an item in any way. If an item bearing the seal of an architect, engineer, or land surveyor is altered; the altering architect, engineer, or land surveyor shall affix to the item their seal and notation "altered by" followed by their signature and date of such alteration, and a specific description of the alteration.

© 2022 LaBella Associates

APPLICANT NAME & ADDRESS:

ARGO DEVELOPMENT
95 CHESTNUT RIDGE ROAD
MONTVALE, NJ 07645

PROJECT NAME & LOCATION:

SOUTH AVE
MULTI-FAMILY DEVELOPMENT
SOUTH AVENUE
CITY OF POUGHKEEPSIE, NY 12601

NO:	DATE:	DESCRIPTION:
2	03/07/23	REVISED PER PLANNING BOARD COMMENTS
1	01/27/23	REVISED PER CITY COMMENTS
Revisions		

PROJECT NUMBER: 2222201
DRAWN BY:
REVIEWED BY: CPL
ISSUED FOR: PLANNING BOARD REVIEW
DATE: 11/28/2022
DRAWING NAME:

DEMOLITION PLAN

DRAWING NUMBER:

C120

4/3/2023 12:20:42 PM
B:\GLOBAL\Projects\ARGO\2222201 - South Ave Multi Family Dev\06_Drawings\Civil\01_C120_2222201_DEMO.dwg

Drawing Name: B:\GLOBAL\Projects\ARGO\2222201 – South Ave Multi Family Dev\06_Drawings\Civil\01_C120_2222201_DEMO.dwg
Xref's Attached: XLANDSC-2222201; XENG_2222201; XLAYOUT-2222201; XBORDER_2222201; XBASE-ENG_2222201
Date Printed: Apr 03, 2023, 12:20pm



SITE LEGEND:

- PROPERTY LINE
- SETBACK LINE
- BUILDING
- PAVEMENT
- ROAD CENTER LINE
- SIDEWALK
- CURB
- WORK LIMITS
- CONCRETE SURFACE
- ROAD LINING & STRIPING
- SIGN
- 2 POSTED SIGN
- BOLLARD
- MAILBOX
- PARKING COUNT

LaBella
Powered by partnership.

21 Fox Street
Poughkeepsie, NY 12601
(845) 454-3980

labellapc.com

STATE OF NEW YORK
CHRISTOPHER PAUL LINE
079470
LICENSED PROFESSIONAL ENGINEER

It is a violation of New York Education Law Article 145 Sec.7209, for any person, unless acting under the direction of a licensed architect, professional engineer, or land surveyor, to alter an item in any way. If an item bearing the seal of an architect, engineer, or land surveyor is altered; the altering architect, engineer, or land surveyor shall affix to the item their seal and notation "altered by" followed by their signature and date of such alteration, and a specific description of the alteration.

© 2022 LaBella Associates

APPLICANT NAME & ADDRESS:

ARGO DEVELOPMENT
95 CHESTNUT RIDGE ROAD
MONTVALE, NJ 07645

PROJECT NAME & LOCATION:

SOUTH AVE MULTI-FAMILY DEVELOPMENT
SOUTH AVENUE
CITY OF POUGHKEEPSIE, NY 12601

NO:	DATE:	DESCRIPTION:
3	04/04/23	REVISIONS PER INTERNAL COORDINATION
2	03/07/23	REVISED PER PLANNING BOARD COMMENTS
1	01/27/23	REVISED PER CITY COMMENTS

Revisions

PROJECT NUMBER: 2222201

DRAWN BY:

REVIEWED BY: CPL

ISSUED FOR: PLANNING BOARD REVIEW

DATE: 11/28/2022

DRAWING NAME:

SITE PLAN

DRAWING NUMBER:

C130

4/3/2023 12:21:12 PM
B:\GLOBAL\Projects\ARGO\2222201 - South Ave Multi Family Dev\05_Drawings\Civil\01_C130_2222201_SITE.dwg

Drawing Name: B:\GLOBAL\Projects\ARGO\2222201 – South Ave Multi Family Dev\06_Drawings\Civil\01_C130_2222201_SITE.dwg
Xref's Attached: XENG_2222201; XLAYOUT-2222201; XBORDER_2222201; XLANDSC-2222201; XBASE-ENG_2222201
Date Printed: Apr 03, 2023, 12:21pm





100 ft Tower Ladder 2-City Pok NY

Overall Length	43.830ft
Overall Width	8.167ft
Overall Body Height	7.745ft
Min Body Ground Clearance	0.656ft
Track Width	8.167ft
Lock-to-lock time	6.00s
Curb to Curb Turning Radius	35.440ft

2 / C-131 CITY OF POUGHKEEPSIE LADDER TRUCK

SCALE: NTS

1 / C-131 TRUCK MANEUVERING PLAN

SCALE: 1" = 30'

LaBella
Powered by partnership.

21 Fox Street
Poughkeepsie, NY 12601
(845) 454-3980

labellapc.com

STATE OF NEW YORK
CHRISTOPHER EARL LUTINE
079470
LICENSED PROFESSIONAL ENGINEER

It is a violation of New York Education Law Article 145 Sec.7209, for any person, unless acting under the direction of a licensed architect, professional engineer, or land surveyor, to alter an item in any way. If an item bearing the seal of an architect, engineer, or land surveyor is altered; the altering architect, engineer, or land surveyor shall affix to the item their seal and notation "altered by" followed by their signature and date of such alteration, and a specific description of the alteration.

© 2022 LaBella Associates

APPLICANT NAME & ADDRESS:

ARGO DEVELOPMENT
95 CHESTNUT RIDGE ROAD
MONTVALE, NJ 07645

PROJECT NAME & LOCATION:

SOUTH AVE
MULTI-FAMILY DEVELOPMENT
SOUTH AVENUE
CITY OF POUGHKEEPSIE, NY 12601

NO:	DATE:	DESCRIPTION:
1	01/27/23	REVISED PER CITY COMMENTS
Revisions		

PROJECT NUMBER: 2222201

DRAWN BY:

REVIEWED BY: CPL

ISSUED FOR: PLANNING BOARD REVIEW

DATE: 11/28/2022

DRAWING NAME:

TRUCK MANEUVERING PLAN

DRAWING NUMBER:

C131

4/3/2023 12:21:41 PM
B:\GLOBAL\Projects\ARGO\2222201 - South Ave Multi Family Dev\05_Drawings\Civil\01_C131_2222201_TRUCK.dwg

Drawing Name: B:\GLOBAL\Projects\ARGO\2222201 – South Ave Multi Family Dev\06_Drawings\Civil\01_C131_2222201_TRUCK.dwg
Xref's Attached: XENG_2222201; XLAYOUT-2222201; XBORDER_2222201; XBASE-ENG_2222201
Date Printed: Apr 03, 2023, 12:21pm

ESC AND GRADING LEGEND:

- PROPERTY LINE
- BUILDING
- XXX — 10 FT CONTOUR
- XXX — 2 FT CONTOUR
- XXX.X — SPOT GRADE
- TREE LINE
- SHRUB LINE
- DRAINAGE SWALE
- SILT FENCE
- STRAW BALE DIKE / FIBER ROLL
- FILTER FABRIC DROP INLET PROTECTION
- CATCH BASIN GRATE DROP INLET PROTECTION
- CATCH BASIN SILT SAC DROP INLET PROTECTION
- EROSION CONTROL MATTING
- STABILIZED CONSTRUCTION ENTRANCE
- RIPRAP
- CONCRETE WASH OUT AREA
- TREE PROTECTION
- SOIL BORING
- TEST PIT
- WORK LIMIT LINE

ABBREVIATIONS:

TF	TOP OF FRAME
HP	HIGH POINT
LP	LOW POINT
TC	TOP OF CURB
BC	BOTTOM OF CURB
INV	INVERT



1 C-140 GRADING AND EROSION & SEDIMENT CONTROL PLAN

SCALE: 1" = 30'

LaBella
Powered by partnership.

21 Fox Street
Poughkeepsie, NY 12601
(845) 454-3980

labellapc.com

STATE OF NEW YORK
CHRISTOPHER PAUL TIMINE
079470
LICENSED PROFESSIONAL ENGINEER

It is a violation of New York Education Law Article 145 Sec.7209, for any person, unless acting under the direction of a licensed architect, professional engineer, or land surveyor, to alter an item in any way. If an item bearing the seal of an architect, engineer, or land surveyor is altered; the altering architect, engineer, or land surveyor shall affix to the item their seal and notation "altered by" followed by their signature and date of such alteration, and a specific description of the alteration.

© 2022 LaBella Associates

APPLICANT NAME & ADDRESS:

ARGO DEVELOPMENT
95 CHESTNUT RIDGE ROAD
MONTVALE, NJ 07645

PROJECT NAME & LOCATION:

SOUTH AVE
MULTI-FAMILY DEVELOPMENT
SOUTH AVENUE
CITY OF POUGHKEEPSIE, NY 12601

NO:	DATE:	DESCRIPTION:
1	01/27/23	REVISIONS PER CITY COMMENTS
Revisions		

PROJECT NUMBER: 2222201
DRAWN BY:
REVIEWED BY: CPL
ISSUED FOR: PLANNING BOARD REVIEW
DATE: 11/28/2022
DRAWING NAME:

GRADING AND EROSION & SEDIMENT CONTROL PLAN

DRAWING NUMBER:

C140

4/3/2023 12:22:03 PM
B:\GLOBAL\Projects\ARGO\2222201 - South Ave Multi Family Dev\06_Drawings\Civil\01_C140_2222201_GRAD_ESC.dwg

Drawing Name: B:\GLOBAL\Projects\ARGO\2222201 – South Ave Multi Family Dev\06_Drawings\Civil\01_C140_2222201_GRAD_ESC.dwg
Xref's Attached: XENG_2222201; XBASE-SVY_2222201; XLAYOUT-2222201; XBORDER_2222201; XBASE-ENG_2222201
Date Printed: Apr 03, 2023, 12:22pm



1 C-160 UTILITY PLAN
SCALE: 1" = 30'

LaBella
Powered by partnership.
21 Fox Street
Poughkeepsie, NY 12601
(845) 454-3980
labellapc.com

STATE OF NEW YORK CHRISTOPHER PAUL LINE 079470 LICENSED PROFESSIONAL ENGINEER

It is a violation of New York Education Law Article 145 Sec.7209, for any person, unless acting under the direction of a licensed architect, professional engineer, or land surveyor, to alter an item in any way. If an item bearing the seal of an architect, engineer, or land surveyor is altered; the altering architect, engineer, or land surveyor shall affix to the item their seal and notation "altered by" followed by their signature and date of such alteration, and a specific description of the alteration.

© 2022 LaBella Associates

APPLICANT NAME & ADDRESS:

ARGO DEVELOPMENT
95 CHESTNUT RIDGE ROAD
MONTVALE, NJ 07645

PROJECT NAME & LOCATION:

SOUTH AVE MULTI-FAMILY DEVELOPMENT
SOUTH AVENUE
CITY OF POUGHKEEPSIE, NY 12601

NO:	DATE:	DESCRIPTION:
3	04/04/23	REVISIONS PER INTERNAL COORDINATION
2	03/07/23	REVISED PER PLANNING BOARD COMMENTS
1	01/27/23	GENERAL REVISIONS
Revisions		

PROJECT NUMBER: 2222201
DRAWN BY:
REVIEWED BY: CPL
ISSUED FOR: PLANNING BOARD REVIEW
DATE: 11/28/2022
DRAWING NAME:

UTILITY PLAN

DRAWING NUMBER:

C160

4/3/2023 12:22:27 PM
B:\GLOBAL\Projects\ARGO\2222201 - South Ave Multi Family Dev\05_Drawings\Civil\01_C160_2222201_UTIL.dwg

Drawing Name: B:\GLOBAL\Projects\ARGO\2222201 – South Ave Multi Family Dev\06_Drawings\Civil\01_C160_2222201_UTIL.dwg
Xref's Attached: XBORDER_2222201; XENG_2222201; XLAYOUT-2222201; XBASE-ENG_2222201
Date Printed: Apr 03, 2023, 12:22pm

LANDSCAPING & LIGHTING LEGEND:

PROPOSED BUILDING

PROPOSED TREE LINE

LANDSCAPE BED EDGING

PROPOSED DECIDUOUS TREES

PROPOSED CONIFEROUS TREES

PROPOSED SHRUBS

43 CO — PLANT QUANTITY / PLANT NAME



2 C-180 LANDSCAPE PLAN
SCALE: 1" = 20'

PLANT LIST

QTY	ABRV						
TREES							
6	AR	Acer rubrum 'Red Sunset'	October Glory Red Maple	2"–2.5" Cal.	B&B	As Shown	
5	BP	Betula populifolia	Gray Birch	8'–10' Clump	B&B	As Shown	
2	CF	Cornus florida	Flowering Dogwood	8'–10' Ht.	B&B	As Shown	
9	GT	Gleditsia triacanthos inermis	Thornless Honeylocust	2"–2.5" Cal.	B&B	As Shown	
4	PG	Picea pungens glauca	Colorado Blue Spruce	8'–10' Ht.	B&B	As Shown	
3	QP	Quercus palustris	Pin Oak	2"–2.5" Cal.	B&B	As Shown	
6	QR	Quercus rubra	Red Oak	2 – 2.5" Cal.	B&B	As Shown	Deciduous Tree
5	TG	Thuja plicata x standishii 'Green Giant'	Thuja Green Giant	6–7 FT.	B&B	As Shown	Evergreen Conifer Tree
3	SL	Salix Lutea	Yellow Willow	2"–2.5" Cal.	B&B	As Shown	
SHRUBS							
5	Am	Amelanchier canadensis	Serviceberry	42"–48" Ht.	B&B	As Shown	
10	Ar	Aronia arbutifolia 'Brilliantissima'	Brilliant Red Chokeberry	30"–36" Ht.	Cont.	As Shown	
41	Bm	Buxus x 'Green Mountain'	'Green Mountain' Boxwood	24"–30" Ht.	Cont.	3' O.C.	
3	Ca	Clethra alnifolia 'Hummingbird'	Hummingbird Summersweet	30"–36" Ht.	Cont.	As Shown	
9	Ci	Comptonia peregrina	Sweet Fern	24"–30" Ht.	Cont.	As Shown	
5	Cb	Cornus sericea baileyii	Bailey Red Twig Dogwood	42"–48" Ht.	B&B	As Shown	
13	Gl	Genista lydia 'Select'	Bangal Genista	24"–30" Ht.	Cont.	As Shown	
4	Hm	Hamamelis virginiana	Witchhazel	42"–48" Ht.	B&B	As Shown	
8	Hc	Hydrangea macrophylla 'Mini Penny'	Mini Penny Hydrangea	30"–36" Ht.	Cont.	4' O.C.	
1	7	Kalmia latifolia	Mountain Laurel	42"–48" Ht.	B&B	As Shown	
2	Lb	Lindera benzoin	Spicebush	42"–48" Ht.	B&B	As Shown	
3	Sy	Symphoricarpos x doorenbosii 'Marleen'	Marleen Coral Berry	30"–36" Ht.	Cont	As Shown	
19	Va	Viburnum acerifolium	Mapleleaf Viburnum	30"–36" Ht.	Cont.	As Shown	
4	Vm	Viburnum latana 'Mohican'	Mohican Viburnum	42"–48" Ht.	B&B	As Shown	
3	Df	Viburnum plicatum f. tomentosum 'Marisii'	Doublefile Viburnum, marisii	5–6 FT.	B&B	As Shown	Deciduous Shrub
3	Xc	Ilex crenata 'Steeds'	Steeds Upright Holly	6 FT.	B&B	As Shown	
PERNNIALS/GRASSES							
36	nm	Adiantum pedatum	Northern Maidenhair Fern	#3	Cont.	24" O.C.	mulched bed
22	ca	Calamagrostis x acutiflora 'Karl Foerster'	Foerster's Feather Reed Grass	#3	Cont.	As Shown	
13	hc	Hemerocallis 'Happy Returns'	Happy Returns Dwarf Daylily	#3	Cont.	18" O.C.	White & Purple Flowering Variety
12	hh	Hemerocallis 'Hyperion'	Hyperion Daylily	#3	Cont.	24" O.C.	Canary yellow, mid / late summe
11	ha	Hemerocallis 'Autumn Accent'	Autumn Accent Daylily	#3	Cont.	24" O.C.	crimson, late summer bloom
10	pa	Pennisetum alopcuroides 'Hameln'	Hameln Fountain Grass	#3	Cont.	24" O.C.	

1 C-180 PLANT LIST
SCALE: NTS

* ALL DISTURBED AREAS NOT SPECIFICALLY CALLED OUT FOR NEW IMPROVEMENTS SHALL BE TOPSOILED, SEEDED WITH LAWN SEED MIX, & MULCHED (TYP)

LaBella Powered by partnership.

21 Fox Street
Poughkeepsie, NY 12601
(845) 454-3980

labellapc.com

STATE OF NEW YORK — CHRISTOPHER PAUL LAFRATTINE — 079470 — LICENSED PROFESSIONAL ENGINEER

It is a violation of New York Education Law Article 145 Sec.7209, for any person, unless acting under the direction of a licensed architect, professional engineer, or land surveyor, to alter an item in any way. If an item bearing the seal of an architect, engineer, or land surveyor is altered; the altering architect, engineer, or land surveyor shall affix to the item their seal and notation "altered by" followed by their signature and date of such alteration, and a specific description of the alteration.

© 2022 LaBella Associates

APPLICANT NAME & ADDRESS:

ARGO DEVELOPMENT
95 CHESTNUT RIDGE ROAD
MONTVALE, NJ 07645

PROJECT NAME & LOCATION:

SOUTH AVE MULTI-FAMILY DEVELOPMENT
SOUTH AVENUE
CITY OF POUGHKEEPSIE, NY 12601

NO:	DATE:	DESCRIPTION:
2	03/07/23	REVISED PER PLANNING BOARD COMMENTS
1	01/27/23	REVISED PER CITY COMMENTS
Revisions		

PROJECT NUMBER: 2222201
DRAWN BY:
REVIEWED BY: CPL
ISSUED FOR: PLANNING BOARD REVIEW
DATE: 11/28/2022
DRAWING NAME:

LANDSCAPE PLAN

DRAWING NUMBER:

C180

4/3/2023 12:23:10 PM
B:\GLOBAL\Projects\ARGO\2222201 - South Ave Multi Family Dev\06_Drawings\Civil\01_C180_2222201_LANDSC.dwg

Drawing Name: B:\GLOBAL\Projects\ARGO\2222201 – South Ave Multi Family Dev\06_Drawings\Civil\01_C180_2222201_LANDSC.dwg
Xref's Attached: XBORDER_2222201; XLAYOUT-2222201; XLANDSC-2222201; XENG_2222201; XBASE-ENG_2222201
Date Printed: Apr 03, 2023, 12:23pm

LEGEND:

- PROPOSED BUILDING
- WALL MOUNTED LIGHT
- POST–TOP MOUNTED LUMINAIRE / POLE
- POST AND LUMINAIRE
- CEILING–MOUNTED CANOPY LIGHT FIXTURE
- $\times^{1.2}$ FOOT CANDLE SPOT VALUES AT GROUND
- PHOTOMETRIC CONTOUR, FOOT CANDLE VALUE
- EXISTING UTILITY POLE
- BLC BACK–LIGHT SHIELD, ALSO KNOWN AS A "HOUSE–SIDE"SHIELD
- P LIGHT POLE
- PT LIGHT POLE, W POST–TOP FIXTURE
- W WALL MOUNTED
- C FIXTURE MOUNTED UNDER CANOPY

NOTE:

1. WALL MOUNTED FIXTURE SHALL BE INSTALLED WITH THE LIGHT IN THE DOWNWARD POSITION.

WALL MOUNTED LUMINAIRE:
MANUFACTURER: LIGMAN LIGHTING
MODEL: ULEE–30001 LEEDS 2 SMALL SURFACE DOWNLIGHT
ADA DARK SKY APPROVED, FULL CUT–OFF
WARM WHITE (2700K), AND AMBER

4 C190 WALL MOUNTED LIGHTING FIXTURE DETAIL
SCALE: NTS

LIGHTING NOTES:

1. PROPOSED LIGHTING AS MANUFACTURED BY GARDCO/SIGNIFY LIGHTING, SELUX LIGHTING, AND LIGMAN LIGHTING.
2. GRID NUMBERS SHOWN REPRESENT FOOT CANDLE VALUES AT GROUND PLANE.
3. THE LIGHTING FIXTURES, SURFACE LOCATIONS AND ASSOCIATED PHOTOMETRIC VALUES ARE IDENTIFIED BY LABELLA ASSOCIATES. DETAILED DESIGN OF THE LIGHTING SPECIFICATIONS, LIGHTING CONDUIT, WIRING, AND CONTROL CIRCUITRY SHALL BE BY OTHERS.
4. IF DISCREPANCIES EXIST BETWEEN THE LIGHTING SCHEDULE AND LIGHTING PLAN, THE PLAN SHALL DICTATE.
5. THE EXISTING STREET LIGHTS IN THE RIGHT–OF–WAYS HAVE NOT BEEN INCLUDED IN THIS PHOTOMETRIC ANALYSIS. THE LIGHT LEVELS SHOWN HEREON REFLECT THE PROPOSED LIGHTING ON SITE.
6. EXISTING AND PROPOSED UTILITIES NOT SHOWN ON THIS SHEET FOR CLARITY. REFER TO SHEET C160 FOR UTILITY PLANS.
7. ALL LIGHTING FIXTURES SHALL BE FULL CUT–OFF.
8. PER CITY OF POUGHKEEPSIE CODE, ALLOWABLE LIGHT LEVEL AT PROPERTY BOUNDARY IS ____ FOOTCANDLES.

5.5w LED 570 Lumens
IP65 - Suitable For Wet Locations
IK07 - Impact Resistant
Weight 1.7 lbs



4" junction box cover plate is available as an option

SW Short Arm Wall
EPA = 0.39ft² (0.04m²)
Weight = 23lbs. (10kg)



WALL MOUNTED LUMINAIRE:
SELUX LIGHTING
DISCERA 4, SHORT ARM WALL MOUNT
ADA DARK SKY APPROVED, FULL CUT–OFF
WARM WHITE (3000 K)

3 C190 WALL MOUNTED LIGHTING FIXTURE DETAIL
SCALE: NTS

Rigid Stem Mounting (RS)



Rigid Stem Mounting (RS)



WALL MOUNTED LUMINAIRE:
SELUX LIGHTING
M60, SHORT ARM WALL MOUNT
ADA DARK SKY APPROVED, FULL CUT–OFF
WARM WHITE (3000 K)

6 C190 CANOPY MOUNTED LIGHTING FIXTURE DETAIL
SCALE: NTS



1 C-190 PHOTOMETRIC PLAN
SCALE: 1" = 30'

LUMINAIRE:
GARDCO BY SIGNIFY:
P26 PUREFORM MEDIUM LED AREA LIGHT
ADA DARK SKY APPROVED, FULL CUT–OFF
WARM WHITE (3000 K)



NOTES: 1. CONTRACTOR SHALL SUBMIT SHOP DRAWINGS TO THE ENGINEER FOR APPROVAL PRIOR TO INSTALLATION.
2. ALL EXCAVATIONS SHALL BE BACKFILLED WITH STRUCTURAL FILL AND COMPACTED TO 95% OF MAXIMUM MATERIAL DENSITY.
3. ELECTRICAL POWER SUPPLY, WIRE, AND CONDUIT BY OTHERS.

2 C190 AREA LIGHTING FIXTURE DETAIL
SCALE: N.T.S.



1. CONTRACTOR SHALL SUBMIT SHOP DRAWINGS TO THE ENGINEER FOR APPROVAL PRIOR TO INSTALLATION.
2. ALL EXCAVATIONS SHALL BE BACKFILLED WITH STRUCTURAL FILL AND COMPACTED TO 95% OF MAXIMUM MATERIAL DENSITY.
3. ELECTRICAL POWER SUPPLY, WIRE, AND CONDUIT BY OTHERS.

8 C190 BOLLARD DETAIL
SCALE: N.T.S.

POST TOP LUMINAIRE:
GARDCO BY SIGNIFY:
PPT PUREFORM POST TOP LIGHT
ADA DARK SKY APPROVED, FULL CUT–OFF
WARM WHITE (3000 K)



NOTES: CONTRACTOR SHALL SUBMIT SHOP DRAWINGS TO THE ENGINEER FOR APPROVAL PRIOR TO INSTALLATION.
2. ALL EXCAVATIONS SHALL BE BACKFILLED WITH STRUCTURAL FILL AND COMPACTED TO 95% OF MAXIMUM MATERIAL DENSITY.
3. ELECTRICAL POWER SUPPLY, WIRE, AND CONDUIT BY OTHERS.

7 C190 PEDESTRIAN SCALE LIGHTING FIXTURE DETAIL
SCALE: N.T.S.

Statistics

Description	Avg	Symbol	Max	Min	Avg/Min	Max/Min
Stat Zone # 1_TO PROPERTY LINE	0.6 fc	×	7.1 fc	0.0 fc	N/A	N/A
Stat Zone # 2_PAVEMENT	0.9 fc	+	3.7 fc	0.0 fc	N/A	N/A
Stat Zone # 3_PED. WALK at BLDG	1.2 fc	+	3.4 fc	0.5 fc	2.4:1	6.8:1

Schedule

Label	QTY	MOUNT HEIGHT	POLE LENGTH	Manufacturer	Catalog	Description	Number Lamps	Lamp Output LUMINS	LLF	Input Power WATTS	Notes
P-A	4	20 FT	19 FT	PHILIPS GARDCO	P26-48L-400-WW-G2-5	PureForm Gen2 - Area Medium (P26), 48 LED's, 3000K CCT, TYPE 5 OPTIC, .	1	7917	0.95	60.07694	Post and Arm
P-B	1	20 FT	19 FT	PHILIPS GARDCO	P26-48L-400-WW-G2-BLC	PureForm Gen2 - Area Medium (P26), 48 LED's, 3000K CCT, TYPE BLC OPTIC, .	1	5872	0.95	60.07694	Post and Arm, Back Lgt Cutoff
PT-C	4	15 FT	14FT	GARDCO	PPT-196L-450-WW-G2-5--UNV	PPT Pureform Post Top, 196 LED's, 3000K CCT, TYPE 5 OPTIC, Comfort Light Engine, 80CRI	1	2127	0.95	20.9	Post Top
B-3	8	4.9 FT		SIGNIFY GARDCO	PBL-14L-100-NW-G2-3-UNV	Pureform Gen2 - PBL Bollard, Type 3. 3000K	1	492	0.95	6.1	Bollard
B-5	3	4.9 FT		SIGNIFY GARDCO	PBL-14L-100-NW-G2-5-UNV	Pureform Gen2 - PBL Bollard, Type 5. 3000K	1	538	0.95	6.1	Bollard
W-1	2	12 FT.		Selux Corporation	DSC4Lx-R3-5G350-30-XX-XX-UNV-HS	Discera 4, Type 3. 3000K CCT	1	2473	0.95	32	wall mount at parking entrance and exit
W-2	9	12 FT.		LIGMAN	ULEE-30011-EW-Amber	Leeds One side	2	197	0.95	10.4	wall mount
C-1	4	12 FT.		Selux Corporation	L60W-1C20-35-LW-X-04--XX-UNV	M60 LED Direct Wet Location	1	1658	0.95	19.3	suspended under entrance canopy

LaBella
Powered by partnership.
21 Fox Street
Poughkeepsie, NY 12601
(845) 454-3980
labellapc.com

NOT FOR CONSTRUCTION

It is a violation of New York Education Law Article 145 Sec.7209, for any person, unless acting under the direction of a licensed architect, professional engineer, or land surveyor, to alter an item in any way. If an item bearing the seal of an architect, engineer, or land surveyor is altered; the altering architect, engineer, or land surveyor shall affix to the item their seal and notation "altered by" followed by their signature and date of such alteration, and a specific description of the alteration.

© 2022 LaBella Associates

APPLICANT NAME & ADDRESS:
ARGO DEVELOPMENT
95 CHESTNUT RIDGE ROAD
MONTVALE, NJ 07645

PROJECT NAME & LOCATION:
SOUTH AVE MULTI-FAMILY DEVELOPMENT
SOUTH AVENUE
CITY OF POUGHKEEPSIE, NY 12601

NO:	DATE:	DESCRIPTION:
2	03/07/23	REVISED PER PLANNING BOARD COMMENTS
1	01/27/23	REVISED PER CITY COMMENTS
Revisions		

PROJECT NUMBER: 2222201
DRAWN BY:
REVIEWED BY: CPL
ISSUED FOR: PLANNING BOARD REVIEW
DATE: 11/28/2022
DRAWING NAME:

PHOTOMETRIC PLAN

DRAWING NUMBER:

C190

4/3/2023 12:23:53 PM
D:\GLOBAL\Projects\ARGO\2222201 - South Ave Multi Family Dev\06_Drawings\Civil\01_C190_2222201_PHOTO.dwg

Drawing Name: B:\GLOBAL\Projects\ARGO\2222201 - South Ave Multi Family Dev\06_Drawings\Civil\01_C190_2222201_PHOTO.dwg
Xref's Attached: XBORDER_2222201; XLAYOUT-2222201; XPHOTOMTRC-2222201; XBASE-ENG_2222201
Date Printed: Apr 03, 2023, 12:23pm

CONSTRUCTION PHASING NOTES:

1. THE CONTRACTOR SHALL NOTIFY THE OWNER, CITY ENGINEER, AND HIGHWAY DEPARTMENT IN WRITING WHEN CONSTRUCTION WILL BEGIN, AT LEAST TWO (2) WEEKS PRIOR TO THE START OF WORK.
2. PRIOR TO LEAVING THE WORK SITE EACH DAY, THE CONTRACTOR SHALL REMOVE OR PROTECT ANY PART OF THE WORK SITE THAT MAY BE CONSIDERED HAZARDOUS TO THE TRAVELING PUBLIC.
3. WHILE PAVING WITHIN WORK ZONE, THE CONTRACTOR SHALL FOLLOW FIGURE 302-9B ON PAGE 2532 OF THE NEW YORK STATE DEPARTMENT OF TRANSPORTATION MANUAL OF UNIFORM TRAFFIC CONTROL DEVICES.
4. PAVEMENT RESURFACING OPERATIONS SHALL BE SCHEDULED SO AS TO MINIMIZE THE LONGITUDINAL LENGTH OF EXPOSED PAVEMENT EDGE LEFT OVERNIGHT. REFER TO NYSDOT STANDARD SPECIFICATION SECTION 402-3.09 JOINTS.

TRENCHING & UTILITY INSTALLATION NOTES:

1. ALL AREAS DISTURBED DURING TRENCHING WITHIN THE CITY RIGHT-OF-WAY MUST BE BACKFILLED THE SAME DAY. PAVEMENT SHALL BE SWEPT REGULARLY AND KEPT CLEAN AND FREE OF DEBRIS.
2. ALL TRENCHING IN PAVEMENT SHOULD BE SAWCUT PRIOR TO TRENCHING. PAVEMENT RESTORATIONS MAY REQUIRE ADDITIONAL CUTBACKS AFTER TRENCHING OPERATIONS HAVE BEEN COMPLETED.
3. ALL PAVED AREAS MUST BE RESTORED WITH A MINIMUM OF 4" TEMPORARY PAVING AT THE CLOSE OF EACH DAY'S WORK OPERATIONS.
4. PERMANENT PAVING MUST BE COMPLETED AT AMBIENT TEMPERATURES OF 40 DEGREES (45 DEGREES FOR TOP COURSE) AND RISING. ANY PAVING OPERATIONS COMPLETED BELOW 40 DEGREES (45 DEGREES FOR TOP COURSE) SHALL BE CONSIDERED TEMPORARY.
5. ALL SIGNS REMOVED FOR CONSTRUCTION MUST BE RESET USING TYPE A POSTS.



1 C-200 TRAFFIC CONTROL PLAN
SCALE: 1" = 30'

SPECIAL NOTES:

1. MAINTENANCE AND PROTECTION OF TRAFFIC IS THE RESPONSIBILITY OF THE CONTRACTOR. ANY SUBCONTRACTORS WORKING FOR THE CONTRACTOR MUST HAVE A COPY OF THE HIGHWAY WORK PERMIT ON THE SITE AND MUST BE FAMILIAR WITH THE TRAFFIC CONTROL REQUIREMENTS. IT IS STRONGLY ADVISED THAT A "TAILGATE" SAFETY MEETING WITH EACH WORK CREW BE INITIATED BEFORE THE START OF WORK.
2. TRAFFIC CONTROL SCHEMES MUST BE IN PLACE, AND MAINTAINED, THROUGHOUT THE DURATION OF WORK.
3. ALL MAINTENANCE AND PROTECTION OF TRAFFIC TO BE IN ACCORDANCE WITH THE NATIONAL MANUAL OF UNIFORM TRAFFIC CONTROL DEVICES AND THE NYS SUPPLEMENT.
4. ANYONE WORKING WITHIN THE HIGHWAY RIGHT-OF-WAY SHALL WEAR HIGH-VISIBILITY APPAREL MEETING THE ANSI 107-2004 CLASS II STANDARDS AND A HARD HAT.
5. AT THE START OF WORK ON THE PROJECT, ALL WORK ZONE TRAFFIC CONTROL DEVICES SHALL APPEAR IN "ACCEPTABLE" CONDITION. THESE DEVICES SHALL NOT BE ALLOWED TO FALL BELOW THE "MARGINAL" CONDITION AT ANY TIME DURING THE LIFE OF THE PROJECT. FADED AND DETERIORATED PANELS AND NON-STANDARD LEGENDS ARE NOT ACCEPTABLE.
6. FLAGGER SIGNS ARE TO BE USED ONLY WHEN A FLAGGER IS ACTUALLY PRESENT AND VISIBLE TO THE MOTORIST. THEY SHALL BE COVERED OR REMOVED AT ALL OTHER TIMES. STOP/SLOW PADDLES ARE REQUIRED.
7. NO LOW-MOUNTED SIGNS SHALL BE PERMITTED, EXCEPT FOR FLEXIBLE PANELS MEETING THE CURRENT SPECIFICATION REQUIREMENTS. PROVIDE 7' TO BOTTOM OF SIGN.
8. ALL DISTURBED AREAS WITHIN THE CITY RIGHT-OF-WAY NOT RECEIVING HARDSCAPE SHALL BE TOPSOILED, SEEDED, AND MULCHED TO GUARANTEE AN ACCEPTABLE STAND OF GRASS.

WINTER WORK:

SNOW PLOWING REQUIREMENTS:

DUE TO POSSIBLE SNOW FALL AND SNOW PLOWING OPERATIONS, ANY STEEL PLATES USED TO COVER AN EXCAVATION SHALL BE:

1. RECESSED INTO THE PAVEMENT AND PINNED; OR
2. PINNED WITH ASPHALT RAMPS PLACED ALONG ALL EDGES. RAMPS SHALL BE SLOPED AT 1 INCH RISE PER 12" RUN MAXIMUM. "RAISE PLOW" SIGNS SUPPLEMENTED WITH TYPE A FLASHING LIGHTS MUST BE ERECTED AN APPROPRIATE DISTANCE BEFORE THE EXCAVATION; SIGNS AND LIGHTS MUST MEET NYSDOT MUTCD SPECIFICATIONS.

WINTER TIME EARTHWORK REQUIREMENTS:

ALL PERMIT WORK UNDER CONSTRUCTION BETWEEN THE DATES OF NOVEMBER 1 THROUGH MAY 1 SHALL CONFORM TO THE FOLLOWING REQUIREMENTS:

1. GRANULAR OR OTHER FROST SUSCEPTIBLE MATERIAL SHALL NOT BE PLACED WHEN THE TEMPERATURE IS BELOW 32 DEGREES FAHRENHEIT.
2. FROZEN MATERIAL SHALL NOT BE INCORPORATED INTO EMBANKMENTS OR BACKFILLS.
3. MATERIAL SHALL NOT BE PLACED ON FROZEN GROUND.
4. THE MATERIAL SHALL BE COMPACTED IN ACCORDANCE WITH HIGHWAY DESIGN MANUAL CHAPTER 13 APPENDIX 13C,"REQUIREMENTS FOR THE DESIGN AND CONSTRUCTION OF UNDERGROUND UTILITY INSTALLATIONS WITHIN THE STATE HIGHWAY RIGHT-OF-WAY" (AKA BLUE BOOK), LATEST REVISION, AND/OR EI04-015 (ENGINEERING INSTRUCTION).
5. ANY SPECIAL CONDITIONS AND RESTRICTIONS AS MAY BE IMPOSED BY THE CITY ENGINEER OR THE REGIONAL GEOTECHNICAL (SOILS) ENGINEER.

PAVEMENT REPLACEMENT REQUIREMENTS:

1. DUE TO ASPHALT PLANTS CLOSED IN THE WINTER, TEMPORARY PAVEMENT REPLACEMENTS SHALL BE AS PER THE CITY ENGINEER. CONTRACTOR MUST MONITOR AND MAINTAIN THE TEMPORARY PAVEMENT REPLACEMENT.
2. TEMPORARY PAVEMENT REPLACEMENTS ARE REQUIRED TO BE REPLACED IN-KIND IN THE SPRING WHEN THE WEATHER ALLOWS NYSDOT STANDARD SPECIFICATIONS TO BE MET.
3. THERE MAY BE DIFFERENT MATERIAL REQUIREMENTS, PAVEMENT/SUBBASE COURSES AND PAVEMENT/SUBBASE THICKNESS FOR THE DIFFERENT PAVEMENT AREAS. ALL AREAS ARE REQUIRED TO BE REPLACED IN-KIND, AS PER THE CITY ENGINEER.
4. CONTRACTOR MUST MAKE ARRANGEMENTS WITH THE CITY ENGINEER FOR FIELD VISIT TO ENSURE PAVEMENT REPLACEMENT IS DONE PROPERLY TO CORRECT THICKNESS.

WORK ZONE TRAFFIC CONTROL GENERAL NOTES:

GENERAL NOTES:

1. THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE MAINTENANCE AND PROTECTION OF TRAFFIC (M&PT) FOR THE DURATION OF THE CONTRACT. M&PT SHALL BE PROVIDED IN ACCORDANCE WITH THE FOLLOWING DOCUMENTS:
   A. THE HIGHWAY ENTRANCE PLANS, DETAILS, AND REQUIREMENTS SET FORTH IN THE PLANS AND/OR PROPOSAL OF THIS CONTRACT.
   B. THE MOST CURRENT EDITION OF THE MANUAL OF UNIFORM TRAFFIC CONTROL DEVICES (MUTCD).
   C. NEW YORK STATE DEPARTMENT OF TRANSPORTATION (NYSDOT) STANDARD SPECIFICATIONS – CHAPTER 19 WORK ZONE TRAFFIC CONTROL.
   D. NYSDOT STANDARD SHEETS FOR WORK ZONE TRAFFIC CONTROL FOR LONG TERM OPERATION – 619 SERIES FOR LONG TERM OPERATIONS. I.E THE WORK ZONE IS IN EFFECT FOR OVERNIGHT.
   E. NYSDOT WORK ZONE TRAFFIC CONTROL MANUAL FOR SHORT TERM OPERATIONS, I.E THE WORK ZONE IS IN EFFECT ONLY DURING THE DAY AND IS NOT MAINTAINED OVERNIGHT.
2. THE MANUAL OF UNIFORM TRAFFIC CONTROL DEVICES (MUTCD) IS DEFINED AS THE NATIONAL MUTCD FOR STREETS AND HIGHWAYS (US DEPARTMENT OF TRANSPORTATION/FEDERAL HIGHWAY ADMINISTRATION) AS MODIFIED BY THE NEW YORK STATE SUPPLEMENT TO THE NATIONAL MUTCD. WHEN MUTCD IS NOTED IT REFERS TO THE MOST CURRENT EDITION.
3. THE TYPICAL DETAILS DEPICTED ON THE NYSDOT STANDARD SHEETS AND IN THE MUTCD, REFLECT MINIMUM REQUIREMENTS. ADDITIONAL DEVICES AND/OR METHODS OF TRAFFIC CONTROL MAY BE ORDERED BY THE ENGINEER TO MEET FIELD CONDITIONS.
4. THE CONTRACTOR SHALL PROVIDE THE ENGINEER, IN WRITING, WITH THE NAMES, ADDRESSES, AND TELEPHONE NUMBERS OF STAFF WHO ARE AUTHORIZED TO SECURE LABOR, MATERIALS, AND EQUIPMENT FOR EMERGENCY REPAIRS OUTSIDE OF NORMAL WORKING HOURS. THE ENGINEER SHALL PROVIDE THE SUBMITTED INFORMATION TO THE CITY ENGINEER AND HIGHWAY DEPARTMENT, THE NEW YORK STATE POLICE, AND THE LOCAL POLICE.
5. PROPOSED REVISIONS TO ANY WORK OCCURRING WITHIN THE CITY RIGHT-OF-WAY MUST BE SUBMITTED FOR APPROVAL BY THE CONTRACTOR TO THE CITY ENGINEER. PROPOSED REVISIONS MUST BE SUBMITTED FIVE (5) WORK DAYS PRIOR TO THE PLANNED IMPLEMENTATION OF THE PROPOSED REVISIONS.
6. THE CONTRACTOR SHALL PROVIDE A TENTATIVE SCHEDULE OF OPERATIONS TO THE DESIGN ENGINEER AND ALL LOCAL AUTHORITIES AND EMERGENCY SERVICE PROVIDERS TWO WEEKS BEFORE BEGINNING CONSTRUCTION ACTIVITIES. DURING CONSTRUCTION, THE CONTRACTOR SHALL BE REQUIRED TO PROVIDE NOTIFICATION OF CHANGES TO THE PREVIOUS WORK PLAN/WORK LOCATIONS. PROVISIONS SHALL BE MADE AT THE PRE-CONSTRUCTION MEETING OR OTHER MEETING PRIOR TO THE START OF WORK BETWEEN THE CONTRACTOR, LOCAL AUTHORITIES AND EMERGENCY SERVICE PROVIDERS TO ADDRESS A SITUATION WHEN EMERGENCY ACCESS IS NEEDED THROUGH A CONSTRUCTION OPERATION WITHIN THE CONTRACT LIMITS.

ACTIVITY AREA

1. THE CONTRACTOR SHALL MAINTAIN A MINIMUM 500' LONGITUDINAL DISTANCE BETWEEN CONSTRUCTION OPERATIONS ON ALTERNATE SIDES OF THE ROADWAY, UNLESS OTHERWISE APPROVED BY THE CITY ENGINEER AND HIGHWAY DEPARTMENT.
2. WHEN TWO OR MORE AREAS ARE ADJACENT, OVERLAP, OR ARE IN CLOSE PROXIMITY, THE CONTRACTOR SHALL ENSURE THERE ARE NO CONFLICTING SIGNS AND THAT LANE CONTINUITY IS MAINTAINED THROUGHOUT ALL WORK AREAS.

SIGNS:

1. THE LOCATIONS OF TRAFFIC CONTROL SIGNS SHALL BE PER NYSDOT STANDARD SHEETS, EXCEPT WHERE ADJUSTMENT IS NECESSARY FOR SIGHT DISTANCE AND OTHER CONSIDERATIONS. THE FINAL LOCATIONS OF SIGNS ARE SUBJECT TO APPROVAL BY THE CITY ENGINEER AND HIGHWAY DEPARTMENT.
2. ANY EXISTING SIGNS, INCLUDING OVERHEAD SIGNS, WHICH CONFLICT WITH THE TEMPORARY TRAFFIC CONTROL SIGN LAYOUT SHALL BE COVERED, REMOVED, STORED OR RESET, AS APPROVED BY THE CITY ENGINEER AND HIGHWAY DEPARTMENT. ALL APPROPRIATE EXISTING SIGNS SHALL BE RESTORED TO THEIR ORIGINAL CONDITION AND/OR LOCATION UNLESS OTHERWISE REPLACED IN THIS CONTRACT.
3. SIGNS AT OR NEAR INTERSECTIONS SHALL BE PLACED SO THAT THEY DO NOT OBSTRUCT A MOTORIST'S LINE OF SIGHT.
4. IN CASES WHERE LANE RESTRICTIONS REDUCE THE TRAVEL LANE TO ONE LANE, SIGNS SHALL BE POSTED ON THE RIGHT SIDE OF THE ACTIVE TRAVEL LANE, UNLESS OTHERWISE AUTHORIZED BY THE CITY ENGINEER OR HIGHWAY DEPARTMENT.
5. THE DIMENSIONS OF WORK ZONE TRAFFIC CONTROL SIGNS ARE DESCRIBED IN THE MUTCD. ANY CHANGES TO THE DIMENSIONS SHALL BE APPROVED BY THE CITY.
6. SIGN INSTALLATION NOTES:
   A. SIGN SUPPORT – THE CONTRACTOR SHALL SUPPLY ADEQUATE SUPPORTS SO THAT THE SIGNS ARE IN PROPER POSITION AND ALIGNMENT AS SHOWN IN THE WORK ZONE TRAFFIC CONTROL PLAN, AND OTHER M&PT REQUIREMENT DOCUMENTATION. ALL WOOD SUPPORTS SHALL BE PAINTED WITH TWO (2) COATS OF WHITE PAINT.
   B. SIGN PANELS MAY BE MADE OF ALUMINUM, STEEL OR PLYWOOD. THE BACKS OF ALL PLYWOOD PANELS SHALL BE PAINTED WITH TWO (2) COATS OF WHITE PAINT.
   C. SIGN LEGEND – SIGN LEGEND, BORDERS AND MARGINS SHALL BE IN ACCORDANCE WITH MUTCD.
   D. SIGN COLOR – THE COLOR OF THE SIGN BACKGROUND AND LEGEND SHALL BE AS SPECIFIED IN MUTCD. THE MARGIN SHALL BE THE SAME COLOR SPECIFIED FOR THE BACKGROUND, AND THE BORDER SHALL BE THE SAME COLOR SPECIFIED FOR THE LEGEND.
   E. SIGN SHAPE – THE SHAPE OF ALL SIGNS SHALL BE AS SPECIFIED IN MUTCD. CORNERS OF SIGNS SHALL BE ROUNDED.
   F. REFLECTORIZATION – ALL SIGNS SHALL BE REFLECTIVE USING HIGH INTENSITY REFLECTORIZED TAPE OR PAINT. ALL SIGNS SHALL BE REVIEWED AT NIGHT AFTER ERECTION FOR VISIBILITY AND REFLECTORIZATION. ANY SIGNS NOT MEETING PROPER REFLECTION REQUIREMENTS SHALL BE REPLACED.
8. THE CONTRACTOR SHALL KEEP SIGNS CLEANED AND CLEARED AT ALL TIMES. ALL SIGNS ARE THE PROPERTY OF THE CONTRACTOR AND SHALL BE MAINTAINED IN GOOD CONDITION FOR THE DURATION OF THE CONTRACT. ALL SIGNS SHALL BE REMOVED FROM THE WORK SITE WHEN THE CONTRACT WORK IS ACCEPTED.

CHANNELIZING DEVICES:

1. WHERE POSSIBLE ALL CHANNELIZING AND GUIDING DEVICES ARE TO BE PLACED SO AS TO PROVIDE A MINIMUM 2' LATERAL CLEARANCE TO THE TRAVELED WAY.

PUBLIC ACCESS:

1. PROPERTY OWNERS WHOSE DRIVEWAYS WILL BE MADE INACCESSIBLE SHALL BE NOTIFIED BY THE CONTRACTOR AT LEAST 24 HOURS PRIOR TO RESTRICTING USE OF THE DRIVEWAY. FOR MULTIPLE ACCESS PROPERTIES, AT LEAST ONE DRIVEWAY SHALL BE OPEN AT ALL TIMES. ACCESS SHALL BE RESTORED TO ALL DRIVEWAYS AS SOON AS POSSIBLE.
2. SUITABLE RAMPS SHALL BE INSTALLED TO MAINTAIN SMOOTH TRANSITIONS FROM RESIDENTIAL AND COMMERCIAL DRIVEWAYS TO AND FROM THE WORK AREA.

LANE CLOSURES:

1. THE CONTRACTOR SHALL LOCATE LANE CLOSURES TO PROVIDE OPTIMUM VISIBILITY, I.E. BEFORE CURVES AND CRESTS, TO THE EXTENT CONDITIONS PERMIT.
2. THE CITY MAY REQUIRE THAT ALL LANES BE RE-OPENED AT ANY TIME IF THE ROUTE IS NEEDED FOR EMERGENCY PURPOSES. THIS COULD INCLUDE INCIDENTS AT LOCATIONS OUTSIDE THE CONTRACT LIMITS.
3. REFER TO RESTRICTIONS ON LANE CLOSURE NOTES, THIS SHEET.

LANE WIDTHS:

1. UNLESS AUTHORIZED BY THE CITY ENGINEER, THE MINIMUM LANE WIDTHS FOR WORK ZONE TRAVEL LANES SHALL BE 10'.
2. THE CONTRACTOR SHALL PROVIDE WRITTEN NOTICE TO THE CITY ENGINEER AND HIGHWAY DEPARTMENT, A MINIMUM OF 21 CALENDAR DAYS IN ADVANCE OF PERFORMING ANY WORK THAT RESULTS IN THE REDUCED WIDTH OF AN EXISTING ROADWAY.

BARRIER/SHADOW VEHICLES:

1. BARRIER AND SHADOW VEHICLES SHALL BE REQUIRED AS PER NYSDOT STANDARD SHEET TITLED "WORK ZONE TRAFFIC CONTROL LEGENDS AND NOTES".
2. NO WORK ACTIVITY, EQUIPMENT, VEHICLES AND/OR MATERIALS SHALL BE LOCATED BETWEEN THE BARRIER OR SHADOW VEHICLE AND THE ACTIVE WORK AREA (ROLL AHEAD DISTANTANCE).
3. THE CONTRACTOR MAY BE REQUIRED TO PROVIDE A BARRIER VEHICLE IN CONJUNCTION WITH POLICE PRESENCE IN THE WORK ZONE, TO BE INCLUDED IN THE UNIT BID PRICE FOR BASIC WORK ZONE TRAFFIC CONTROL.

PAVEMENT MARKINGS:

1. ALL TEMPORARY PAVEMENT MARKINGS SHALL CONFORM TO THE MATERIAL AND PLACEMENT REQUIREMENTS OF THE CONTRACT DOCUMENTS, MUTCD, AND NYSDOT STANDARD SPECIFICATIONS.
2. IF REQUIRED TEMPORARY PAVEMENT MARKINGS CONFLICT IN MESSAGE OR LOCATION WITH EXISTING PAVEMENT MARKINGS, THE EXISTING PAVEMENT MARKINGS WILL BE REMOVED OR COVERED FOR THE DURATION OF THE TEMPORARY MARKINGS AS APPROVED BY THE CITY ENGINEER. ALL APPROPRIATE EXISTING MARKINGS SHALL BE RESTORED TO THEIR ORIGINAL CONDITION AND/OR LOCATION UNLESS REPLACED UNDER THIS CONTRACT.

WORK DURATION:

1. WORK DURATION DIRECTLY INFLUENCES THE REQUIREMENTS FOR WORK ZONE TRAFFIC CONTROL. TO FACILITATE THE UNDERSTANDING OF THE INFORMATION PRESENTED HEREIN, THE FOLLOWING DEFINITIONS ARE PRESENTED:
   a. LONG TERM STATIONARY WORK: WORK THAT OCCUPIES A LOCATION MORE THAN THREE CONSECUTIVE DAYS. TYPICALLY THE WORK AREA IS OCCUPIED BY EXCAVATIONS, MATERIALS, AND/OR EQUIPMENT AT TIMES WHEN WORKERS ARE NOT PRESENT.
   b. INTERMEDIATE-TERM STATIONARY WORK: WORK THAT OCCUPIES A LOCATION MORE THAN ONE DAYLIGHT PERIOD UP TO THREE CONSECUTIVE DAYS, OR NIGHTTIME WORK LASTING MORE THAN ONE HOUR. TYPICALLY THE WORK AREA IS OCCUPIED BY EXCAVATIONS, MATERIALS, AND/OR EQUIPMENT AT TIMES WHEN WORKERS ARE NOT PRESENT.
   c. SHORT-TERM STATIONARY WORK: DAYTIME WORK THAT OCCUPIES A LOCATION FOR MORE THAN ONE HOUR WITHIN A SINGLE DAYLIGHT PERIOD. EXAMPLES ARE GUIDERAIL REPAIR, DITCH MAINTENANCE, AND BRIDGE INSPECTION.
   d. SHORT DURATION WORK: WORK THAT OCCUPIES A LOCATION UP TO ONE HOUR. EXAMPLES ARE POT HOLE REPAIR, MINOR GUIDERAIL REPAIR, AND SIGN REPAIR.
   e. MOBILE WORK: WORK THAT MOVES INTERMITTENTLY OR CONTINUOUSLY. EXAMPLES ARE PAINT STRIPING OPERATIONS, SWEEPING OPERATIONS, AND HERBICIDE SPRAYING
2. THE ABOVE DEFINITIONS ARE PER NYSDOT STANDARD SHEET 619-11, EFFECTIVE DATE 01/08/09, AND THE NYSDOT WORK ZONE TRAFFIC CONTROL MANUAL.
3. LONG-TERM AND INTERMEDIATE-TERM WORK ZONE TRAFFIC CONTROL REQUIREMENTS ARE COVERED BY THE 619 SERIES OF THE NYSDOT STANDARD SHEETS.
4. SHORT-TERM, SHORT DURATION, AND MOBILE WORK ZONE TRAFFIC CONTROL REQUIREMENTS ARE COVERED BY THE NYSDOT WORK ZONE TRAFFIC CONTROL MANUAL.

TRAFFIC CONTROL PLAN:

TEMPORARY SIDEWALK AND LANE CLOSURES:

IT WILL BE NECESSARY TO TEMPORARILY CLOSE SIDEWALKS AND TRAVEL LANES IN ORDER TO PERFORM THE CONTRACT WORK. THE FOLLOWING RESTRICTIONS SHALL APPLY:

1. NO SIDEWALK OR LANE CLOSURES SHALL BE PERMITTED WITHOUT THE PRIOR APPROVAL OF THE CITY ENGINEER OR HIGHWAY DEPARTMENT.
2. THE CONTRACTOR IS RESPONSIBLE TO SUBMIT REQUESTS FOR SIDEWALK OR LANE CLOSURES TO THE CITY ENGINEER AND HIGHWAY DEPARTMENT A MINIMUM OF SEVEN (7) DAYS IN ADVANCE OF SCHEDULED CLOSURES FOR APPROVAL. DUE TO POSSIBLE TRAFFIC CONTROL CONFLICTS, APPROVAL MAY OR MAY NOT BE GRANTED FOR THE DATE(S) REQUESTED. ANY ADDITIONAL COSTS, DELAYS OR REMOBILIZATION ASSOCIATED WITH THE APPROVAL PROCESS SHALL BE INCLUDED IN THE BID PRICE FOR BASIC WORK ZONE TRAFFIC CONTROL.
3. NO CLOSURES WILL BE PERMITTED DURING NON-WORKING HOURS, UNLESS SPECIFICALLY PROVIDED ELSEWHERE IN THE CONTRACT.
4. ON ALL ROUTES, THE SAME NUMBER OF TRAVEL LANES (INCLUDING TURNING LANES), AS EXIST PRIOR TO THIS CONTRACT, SHALL BE MAINTAINED IN EACH DIRECTION DURING THE HOURS OF 6:30 A.M. TO 9:30 A.M. AND 4:00 P.M. TO 6:30 P.M. – MONDAY TO FRIDAY, INCLUSIVE OR AS PER PERMIT STATED TIME RESTRICTIONS.
5. IN AREAS OF MAJOR SHOPPING MALLS, THE SAME NUMBER OF TRAVEL LANES (INCLUDING TURNING LANES), AS EXIST PRIOR TO THIS CONTRACT, SHALL BE MAINTAINED IN EACH DIRECTION DURING THE HOURS OF 10:00 A.M. TO 4:00 P.M. ON SATURDAYS.
6. THE TIME RESTRICTIONS LISTED ABOVE CAN BE SHIFTED AS TRAFFIC CONDITIONS WARRANT, AND THE CONTRACTOR SHALL BE AWARE THAT CITY OF POUGHKEEPSIE HAS THE ABILITY TO ORDER ADDITIONAL TIME RESTRICTIONS OF UP TO ONE HOUR PER WORK DAY TO THE TIME RESTRICTIONS LISTED ABOVE IF TRAFFIC CONDITIONS WARRANT, AT NO COST TO THE OWNER. THE CONTRACTOR SHALL NOT HAVE ANY DELAY CLAIMS AGAINST THE OWNER OR CITY IF THE CITY ORDERS UP TO ONE HOUR OF ADDITIONAL TIME RESTRICTIONS PER DAY.
6. THE CITY ENGINEER IS AUTHORIZED TO REDUCE THE ABOVE TIME RESTRICTIONS, AS TRAFFIC CONDITIONS WARRANT.
7. THE CONTRACTOR IS ALSO ADVISED THAT THE CITY RESERVES THE RIGHT TO PRECLUDE LANE CLOSURES DURING PERIODS OF INCLEMENT WEATHER, WET OR ICY PAVEMENT, REDUCED VISIBILITY, TRAFFIC ACCIDENTS OR ANY OTHER EMERGENCIES. THE CITY MAY ALTER ANY LANE CLOSURES SHOULD TRAFFIC CONDITIONS OR OTHER UNFORESEEN CIRCUMSTANCES ARISE WHICH WOULD ADVERSELY AFFECT THE TRAFFIC FLOW. THE CONTRACTOR IS ALSO ALERTED TO THE FACT THAT INCIDENT MANAGEMENT OR TRAFFIC CONDITIONS MIGHT FORCE HIS/HER CONSTRUCTION OPERATION TO STOP, EVEN DURING TIME WHERE SUCH OPERATION WOULD NORMALLY BE PERMITTED. TEN SUCH OCCURRENCES PER CALENDAR YEAR SHOULD BE TAKEN INTO CONSIDERATION AS A REASONABLE FREQUENCY OF SUCH EVENT WHEN BIDDING THIS PROJECT. THE CONTRACTOR SHALL HAVE NO CLAIM AGAINST THE OWNER OR CITY FOR ANY DELAYS OR EXTRA COSTS INCURRED IN COMPLYING WITH THESE RESTRICTIONS.

TABLE 6C-3
TAPER LENGTH FOR TEMPORARYTRAFFIC CONTROL ZONES

TYPE OF TAPER	TAPER LENGTH (L)
MERGING TAPER	L
SHIFTING TAPER	L/2
SHOULDER TAPER	L/3
ONE-LANE, TWO-WAY TRAFFIC TAPER	100 FT. MAXIMUM
DOWNSTREAM TAPER	100 FT. PER LANE

TABLE NYGH-3
ADVANCE WARNING SIGN SPACING

ROAD TYPE	DISTANCE BETWEEN SIGNS			SIGN LEGEND	
	A (FT.)	B (FT.)	C (FT.)	XX	YY
URBAN (≤ 30 MPH*)	100	100	100	AHEAD	AHEAD
URBAN (35-40 MPH*)	200	200	200	AHEAD	AHEAD
URBAN (≥ 45 MPH*)	350	350	350	1000 FT.	AHEAD
RURAL	500	500	500	1500 FT.	1000 FT.
EXPRESSWAY / FREEWAY	1000	1500	2640	1 MILE	1/2 MILE

* PRECONSTRUCTION POSTED SPEED LIMIT

- URBAN: (MEETS MORE THAN 1 OF THE FOLLOWING CRITERIA)SIDEWALKS, BICYCLE USAGE, CURBING, CLOSED DRAINAGE SYSTEMS,DRIVEWAY DENSITIES GREATER THAN 24 DRIVEWAYS PER MILE, MINOR COMMERCIAL DRIVEWAY DENSITIES OF 10 DRIVEWAYS PER MILE OR GREATER, MAJOR COMMERCIAL DRIVEWAYS, NUMEROUS RIGHT OF WAY CONSTRAINTS, HIGH DENSITY OF CROSS STREETS, 85TH PERCENTILE SPEEDS OF 45 MPH OR LESS.
- RURAL: ANY AREA NOT EXHIBITING MORE THAN ONE OF THE ABOVE CHARACTERISTICS.
- EXPRESSWAY: DIVIDED HIGHWAYS FOR TRAFFIC WITH FULL OR PARTIAL CONTROL OF ACCESS AND GENERALLY WITH GRADE SEPARATION SAT MAJOR CROSSROADS.
- FREEWAYS/INTERSTATE: LOCAL OR INTER REGIONAL HIGH-SPEED, DIVIDED,HIGH-VOLUME FACILITIES WITH FULL OR PARTIAL CONTROL OF ACCESS.

NOTE:
TABLES, TABLE NOTES & WORK ZONE TRAFFIC CONTROL FROM NYSDOT STANDARD SHEET 619-11 (01/08/09)

LaBella
Powered by partnership.
21 Fox Street
Poughkeepsie, NY 12601
(845) 454-3980
labellapc.com

It is a violation of New York Education Law Article 145 Sec.7209, for any person, unless acting under the direction of a licensed architect, professional engineer, or land surveyor, to alter an item in any way. If an item bearing the seal of an architect, engineer, or land surveyor is altered; the altering architect, engineer, or land surveyor shall affix to the item their seal and notation "altered by" followed by their signature and date of such alteration, and a specific description of the alteration.

© 2022 LaBella Associates

APPLICANT NAME & ADDRESS:
ARGO DEVELOPMENT
95 CHESTNUT RIDGE ROAD
MONTVALE, NJ 07645

PROJECT NAME & LOCATION:
SOUTH AVE MULTI-FAMILY DEVELOPMENT
SOUTH AVENUE
CITY OF POUGHKEEPSIE, NY 12601

NO:	DATE:	DESCRIPTION:
1	03/07/23	SHEET ADDED
Revisions		

PROJECT NUMBER: 2222201
DRAWN BY:
REVIEWED BY: CPL
ISSUED FOR: PLANNING BOARD REVIEW
DATE: 11/28/2022
DRAWING NAME: TRAFFIC CONTROL PLAN
DRAWING NUMBER: C200

4/3/2023 12:24:40 PM B:\GLOBAL\Projects\ARGO\2222201 - South Ave Multi Family Dev\06_Drawings\Civil\01 C200_2222201_TRAFFIC.dwg
Drawing Name: B:\GLOBAL\Projects\ARGO\2222201 – South Ave Multi Family Dev\06_Drawings\Civil\01_C200_2222201_TRAFFIC.dwg
Xref's Attached: XBORDER_2222201; XENG_2222201; XLAYOUT-2222201; XBASE-ENG_2222201
Date Printed: Apr 03, 2023, 12:24pm



A **ON-SITE**

B **CITY ROW**

NOTES:
1. MATERIALS AND METHODS OF CONSTRUCTION SHALL BE IN CONFORMANCE WITH THE NEW YORK STATE DEPARTMENT OF TRANSPORTATION (NYSDOT) STANDARD SPECIFICATIONS FOR CONSTRUCTION AND MATERIALS, DATED **"CURRENT VERSION"**, AND ALL ADDENDA THERE TO.
2. SUBBASE MATERIAL SHALL CONFORM WITH **SECTION 304** – SUBBASE COURSE OF THE ABOVE REFERENCED NYSDOT STANDARD SPECIFICATIONS AND THE TYPE CALLED OUT IN THESE DRAWINGS.
3. HOT MIX ASPHALT (HMA) PAVEMENT SHALL CONFORM WITH **SECTION 400**–HOT MIX ASPHALT OF THE ABOVE REFERENCED NYSDOT STANDARD SPECIFICATIONS AND THE TYPE CALLED OUT IN THESE DRAWINGS. ALTHOUGH **SECTION 400** IN ITS ENTIRETY IS REFERENCED, THE HOT MIX ASPHALT (HMA) PAVEMENT(S) SPECIFIED FOR THIS CONTRACT SHALL BE AS SPECIFIED UNDER **SECTION 402**–HOT MIX ASPHALT (HMA) PAVEMENTS.
4. TACK COAT WHEN SPECIFIED OR CALLED OUT IN THESE DRAWINGS OR REQUIRED BY THE REFERENCED SPECIFICATIONS SHALL CONFORM WITH **SECTION 407**–TACK COAT OF THE ABOVE REFERENCED NYSDOT STANDARD SPECIFICATIONS.
5. WHERE IT IS NECESSARY TO PLACE FILL FOR PURPOSES OF BRINGING THE SUBGRADE ELEVATION UP TO A SPECIFIED GRADE, THE FILL MATERIAL PLACED SHALL BE IN CONFORMANCE WITH **SECTION 203**–EXCAVATION AND EMBANKMENT OF THE ABOVE REFERENCED NYSDOT STANDARD SPECIFICATIONS.

© 1 **PAVEMENT SECTION DETAIL**
SCALE: NOT TO SCALE



DOME PLAN



SECTION A-A THRU RAMP

SECTION B-B THRU RAMP

APPLY TACK COAT IN ACCORDANCE WITH THE NYSDOT SPECIFICATION SECTION 704 ON VERTICAL FACE OF CONCRETE SIDEWALK PRIOR TO PLACEMENT OF BINDER AND TOP COURSE.

NOTES:
1. COORDINATE W/ OWNER FOR COLOR.
2. DETECTABLE WARNING UNIT SHALL BE ADA COMPLIANT, AND SHALL CONTRAST VISUALLY WITH ADJOINING SURFACES.
3. MATERIALS: UNIT SHALL BE 24–INCH DETECTABLE WARNING ADA PAVERS, DOME STRAIGHT ROW SPACING PATTERN ADA–2 OR ADA–3, ADA COMPLIANT WARNING PAVER AS MANUFACTURED BY WAUSAU TILE OR CAST IRON, CAST IN PLACE ADA COMPLIANT WARNING PLATE A MANUFACTURED BY TUFTILE OR EQUAL.

© 3 **DETECTABLE WARNING UNITS FOR RAMPS**
SCALE: NOT TO SCALE



SECTION A-A



SECTION B-B



APPLY SIKAFLEX SELF LEVELING SEALANT, OR APPROVED EQUAL, ALONG LENGTH OF CONCRETE/ASPHALT INTERFACE WITH ATLEAST 1" WIDE BEAD

APPLY TACK COAT IN ACCORDANCE WITH THE NYSDOT SPECIFICATION SECTION 704 ON VERTICAL FACE OF CONCRETE SIDEWALK PRIOR TO PLACEMENT OF BINDER AND TOP COURSE.

NOTES:
1. ALL WORK SHALL CONFORM WITH THE NYSDOT STANDARD SPECIFICATION FOR CONSTRUCTION AND MATERIALS DATED, **"CURRENT VERSION"**, AND ALL ADDENDA THERE TO; SPECIFICALLY **SECTION 608**– SIDEWALKS, DRIVEWAYS, AND BICYCLE PATHS.
2. SLOPE RAMP AND SIDE FLARES AS INDICATED IN THE PLANS OR AS ORDERED BY THE ENGINEER.
3. DETECTABLE WARNING UNITS SHALL BE PROVIDED ON ALL RAMPS IN ACCORDANCE W/ ADA REQUIREMENTS.

© 2 **PEDESTRIAN RAMP SECTION - DROP CURB**
SCALE: NOT TO SCALE



PLAN

ELEVATION



SECTION A–A

NOTES:
1. ALL WORK SHALL CONFORM WITH THE NYSDOT STANDARD SPECIFICATION FOR CONSTRUCTION AND MATERIALS DATED, **"CURRENT VERSION"**, AND ALL ADDENDA THERE TO; SPECIFICALLY **SECTION 608**– SIDEWALKS, DRIVEWAYS, AND BICYCLE PATHS.
2. SLOPE RAMP AND SIDE FLARES AS INDICATED IN THE PLANS OR AS ORDERED BY THE ENGINEER.



CONCRETE SLAB NOTES:

CONCRETE SECTION

1. MATERIAL AND METHODS OF CONSTRUCTION SHALL BE IN CONFORMANCE WITH THE NEW YORK STATE DEPARTMENT OF TRANSPORTATION (NYSDOT) STANDARD SPECIFICATIONS FOR CONSTRUCTION AND MATERIALS, DATED MAY 1, 2008, AND ALL ADDENDA THERETO.
2. CONCRETE SHALL HAVE A MINIMUM COMPRESSION STRENGTH OF 4500 PSI @ 28 DAY AND SHALL BE PLACED IN ACCORDANCE WITH ACI SPECIFICATIONS AND ITS LATEST REVISION.
3. REINFORCING STEEL FOR CONCRETE SHALL CONFORM WITH SECTION 556 – REINFORCING STEEL FOR CONCRETE STRUCTURES OF THE ABOVE REFERENCED NYSDOT STANDARD SPECIFICATIONS AND AS SPECIFICALLY CALLED OUT IN THE DRAWINGS.
4. ALL EXPOSED SURFACED SHALL HAVE A BROOM TEXTURED FINISH & TOOLED EDGES. TOOL SHALL BE PROVIDE MAX 1–1/2" WIDE SMOOTH TROWEL FINISH AT JOINT.
5. EXPANSION JOINTS SHALL BE LOCATED A MAXIMUM OF 20' ON CENTER, OR AS INDICATED ON PLANS.
6. CONTROL JOINTS SHALL BE LOCATED A MAXIMUM OF 5' ON CENTER, OR AS INDICATED ON PLANS.
7. JOINTS SHALL NOT BE SAW CUT.
8. EXPOSED CONCRETE SURFACES SHALL BE TREATED WITH "SUREBOND"/"SAFEBOND" SB–7000 INTENSIFIER BRIGHT PROTECTOR AND SIDEWALK SEALER, OR EQUAL. RATE AND METHOD OF APPLICATION SHALL BE IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDATIONS.
9. SUBBASE MATERIAL SHALL CONFORM WITH SECTION 304 OF THE ABOVE REFERENCED NYSDOT STANDARD.
10. WHERE IT IS NECESSARY TO PLACE FILL FOR PURPOSE OF BRINGING THE SUBGRADE ELEVATION UP TO A SPECIFIED GRADE, THE FILL MATERIAL PLACED SHALL BE IN ACCORDANCE WITH SECTION 203–EXCAVATION AND EMBANKMENT OF THE ABOVE REFERENCED NYSDOT STANDARD SPECIFICATIONS.

© 9 **CONCRETE DRIVEWAY RAMP WITH DROP CURB**
SCALE: NOT TO SCALE



PLAN



PLAN



PLAN



SECTION A-A



SECTION B-B



SECTION C-C



EXPANSION JOINT



CONSTRUCTION JOINT



CONTROL JOINT

© 4 **CONCRETE SIDEWALK DETAIL**
SCALE: NOT TO SCALE



TOOLED EDGE

NOTES:
1. MATERIAL AND METHODS OF CONSTRUCTION SHALL BE IN CONFORMANCE WITH THE NEW YORK STATE DEPARTMENT OF TRANSPORTATION (NYSDOT) STANDARD SPECIFICATIONS FOR CONSTRUCTION AND MATERIALS, DATED "CURRENT VERSION", AND ALL ADDENDA THERE TO.
2. ALL CONCRETE SHALL BE **4,500** CONCRETE. CONCRETE MATERIALS, PLACEMENT, AND CONSTRUCTION SHALL CONFORM WITH **SECTION 500** OF THE ABOVE REFERENCED NYSDOT STANDARD SPECIFICATIONS.
3. REINFORCING STEEL FOR CONCRETE SHALL CONFORM WITH SECTION 556 – REINFORCING STEEL FOR CONCRETE STRUCTURES OF THE ABOVE REFERENCED NYSDOT STANDARD SPECIFICATIONS AND AS SPECIFICALLY CALLED OUT IN THE DRAWINGS.
4. ALL EXPOSED SURFACES SHALL HAVE A BROOM TEXTURED FINISH & TOOLED EDGES. TOOL SHALL PROVIDE MAX 1–1/2" WIDE SMOOTH TROWEL FINISH AT JOINT.
5. EXPANSION JOINTS SHALL BE LOCATED A MAXIMUM OF 20' ON CENTER, OR AS INDICATED ON PLANS.
6. JOINTS SHALL NOT BE SAW CUT.
7. EXPOSED CONCRETE SURFACES SHALL BE TREATED WITH **"SUREBOND" 1100 RESIN–BASED, WATER EMULSION CONCRETE CURING COMPOUND**, OR EQUAL. RATE AND METHOD OF APPLICATION SHALL BE IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDATIONS.
8. SUBBASE MATERIAL SHALL CONFORM WITH **SECTION 304** OF THE ABOVE REFERENCED NYSDOT STANDARD.
9. WHERE IT IS NECESSARY TO PLACE FILL FOR PURPOSE OF BRINGING THE SUBGRADE ELEVATION UP TO A SPECIFIED GRADE, THE FILL MATERIAL PLACED SHALL BE IN ACCORDANCE WITH SECTION 203–EXCAVATION AND EMBANKMENT OF THE ABOVE REFERENCED NYSDOT STANDARD SPECIFICATIONS.
10. ALL WORK SHALL CONFORM WITH **SECTION 608**–SIDEWALK, DRIVEWAYS, AND BICYCLE PATHS OF THE ABOVE REFERENCED NYSDOT STANDARD SPECIFICATIONS.
11. ALL WORK SHALL CONFORM WITH AASHTO GEOMETRIC DESIGN OF HIGHWAYS AND STREET 2011, ICC A117.1 2009. OR LATEST EDITION.
12. SIDEWALK WIDTH SHOWN ON THE PLANS IS TO BE MEASURED FROM THE BACK OF THE CURB.
13. SIDEWALKS SHALL HAVE A CROSS SLOPE OF **1.5%** MAX. UNLESS OTHERWISE NOTED ON PLAN.
14. INSTALL EXPANSION JOINT WITH PREMOLDED RESILIENT JOINT FILLER & SEALANT AT ALL EXISTING SIDEWALKS, CURBS, FIXED OBJECTS, ETC., INCLUDING THOSE PLACED ON PREVIOUS DAYS.
15. WHERE SIDWALK REPLACMENT OCCURS IN CITY ROW, SIDEWALK SHALL BE 5–INCH THICK.

NOTES:
1. CONCRETE CURB SHALL BE INSTALLED IN ACCORDANCE WITH NYSDOT STANDARD SPECIFICATION **SECTION 609**.

© 5 **CAST IN PLACE MOUNTABLE CONCRETE CURB AT SIDEWALK**
SCALE: NOT TO SCALE



NOTES:
1. CONCRETE CURB SHALL BE INSTALLED IN ACCORDANCE WITH NYSDOT STANDARD SPECIFICATION **SECTION 609**.

© 7 **CAST IN PLACE CONCRETE CURB AT SIDEWALK**
SCALE: NOT TO SCALE



NOTES:
1. CONCRETE CURB SHALL BE INSTALLED IN ACCORDANCE WITH NYSDOT STANDARD SPECIFICATION **SECTION 609**.

© 8 **CAST IN PLACE CONCRETE CURB**
SCALE: NOT TO SCALE



NOTES:
1. CONCRETE CURB SHALL BE INSTALLED IN ACCORDANCE WITH NYSDOT STANDARD SPECIFICATION **SECTION 609**.
2. PRECAST CONCRETE CURB MAY BE SUBSTITUTED, WHEN ALTERNATE CONSTRUCTION DETAILS ARE SUBMITTED BY THE CONTRACTOR AND APPROVED BY THE ENGINEER. ALTERNATE CURB SHALL BE INSTALLED IN ACCORDANCE WITH NYSDOT SPEC SECTION 609.

© 10 **CITY OF POUGHKEEPSIE CAST IN PLACE CONCRETE CURB**
SCALE: NOT TO SCALE

LaBella
Powered by partnership.

21 Fox Street
Poughkeepsie, NY 12601
(845) 454-3980

labellapc.com

It is a violation of New York Education Law Article 145 Sec.7209, for any person, unless acting under the direction of a licensed architect, professional engineer, or land surveyor, to alter an item in any way. If an item bearing the seal of an architect, engineer, or land surveyor is altered; the altering architect, engineer, or land surveyor shall affix to the item their seal and notation "altered by" followed by their signature and date of such alteration, and a specific description of the alteration.

© 2022 LaBella Associates

APPLICANT NAME & ADDRESS:

ARGO DEVELOPMENT
95 CHESTNUT RIDGE ROAD
MONTVALE, NJ 07645

PROJECT NAME & LOCATION:

SOUTH AVE MULTI-FAMILY DEVELOPMENT
SOUTH AVENUE
CITY OF POUGHKEEPSIE, NY 12601

NO:	DATE:	DESCRIPTION:
2	03/07/23	REVISED PER PLANNING BOARD COMMENTS
1	01/27/23	NO CHANGES THIS SHEET
Revisions		

PROJECT NUMBER: 2222201

DRAWN BY:

REVIEWED BY: CPL

ISSUED FOR: PLANNING BOARD REVIEW

DATE: 11/28/2022

DRAWING NAME:

SITE DETAILS

DRAWING NUMBER:

C530

4/3/2023 12:25:03 PM
B:\GLOBAL\Projects\ARGO\2222201 - South Ave Multi Family Dev\06_Drawings\Civil\01_C530_C531_2222201_SITED.dwg

Drawing Name: B:\GLOBAL\Projects\ARGO\2222201 – South Ave Multi Family Dev\06_Drawings\Civil\01_C530_C531_2222201_SITED.dwg
Xrefs Attached: XBORDER_2222201
Date Printed: Apr 03, 2023, 12:25pm



SINGLE POST SIGN MOUNTING DETAIL

SCALE: NOT TO SCALE



TUBULAR POST SIGN MOUNTING DETAIL

SCALE: NOT TO SCALE



SINGLE POST STOP SIGN MOUNTING DETAIL

SCALE: NOT TO SCALE



PAVEMENT MARKING DETAIL STOP BAR

SCALE: NOT TO SCALE



PAVEMENT MARKING DETAIL DIRECTIONAL ARROW

SCALE: NOT TO SCALE



NOTES:
1. ALL CROSS WALK STRIPING SHALL BE WHITE
2. TYPE S CROSS WALK SHALL BE USED IN LOW TRAFFIC VOLUME STREET CROSSINGS.
3. TYPE L CROSS WALK SHALL BE USED IN MEDIUM TRAFFIC VOLUME STREET CROSSINGS.
4. TYPE LS CROSS WALK SHALL BE USED IN HIGH TRAFFIC VOLUME STREET CROSSINGS.

PAVEMENT MARKING DETAIL CROSS WALK STRIPING

SCALE: NOT TO SCALE

STRIPING NOTES:
1. ALL STRIPING SHALL CONFORM TO THE LATEST EDITION OF THE NYSDOT STANDARD SPECIFICATIONS, **SECTION 640** AND THE "NATIONAL MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES" – **2009 EDITION** AND THE "NYS SUPPLEMENT."
2. STRIPE PAVEMENT AS INDICATED ON THE PLANS AND/OR IN ACCORDANCE WITH ALL APPLICABLE LOCAL, STATE AND FEDERAL REQUIREMENTS.
3. STRIPING WORK WILL BE REVIEWED AND ACCEPTED BY THE AUTHORITY HAVING JURISDICTION.
4. COLOR: DRIVE LANE DIVIDERS – WHITE OR AOBE
   NO PARKING ZONE MARKINGS – WHITE OR AOBE
   PARKING DIVIDERS – WHITE OR AOBE
   WALKING LINES – WHITE OR AOBE
   ACCESSIBLE PARKING LINES & SYMBOL – BLUE

SIGNAGE NOTES:
1. ALL SIGNS SHALL CONFORM TO THE LATEST EDITION OF THE NYSDOT STANDARD SPECIFICATIONS, **SECTION 645** AND THE "NATIONAL MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES" – **2009 EDITION** AND THE "NYS SUPPLEMENT."
2. SIGN MOUNTING HEIGHT SHALL BE A MINIMUM OF 7', MINIMUM MOUNTING HEIGHT MAY BE ADJUSTED ONLY IN ACCORDANCE WITH PROVISIONS OUTLINED IN THE "NATIONAL MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES" – **2009 EDITION** AND THE "NYS SUPPLEMENT."
3. SIGN POST SHALL BE IN ACCORDANCE W/ NYSDOT STANDARD SPECS **SECTION 730**.



TYPICAL STRIPING | ACCESSIBLE STRIPING

NOTES:
1. ALL DIMENSIONS SHALL BE IN ACCORDANCE WITH ADA STANDARD AND CURRENT ZONING AND SITE REGULATIONS. REFER TO TOWN OF **WAPPINGER ZONING CODE 240 ATTACHMENT 5.**
2. PARKING SPACE LENGTH SHALL BE 20'. WHERE ACCESS AISLE IS 26' WIDE PARKING SPACE LENGTH MAY BE REDUCED TO 18'.
3. PAINTED ACCESSIBLE LOGO TO BE IN ACCORDANCE W/ NEW YORK STATE LAW.
4. SLOPE OF PAVEMENT SURFACE IN ACCESSIBLE PARKING AREA SHALL NOT EXCEED 1.5% IN ANY DIRECTION.
5. SEE PLAN FOR ACTUAL LOCATION OF SIGNAGE

PAVEMENT MARKING DETAIL PARKING STRIPING

SCALE: NOT TO SCALE

MUTCD SIGN SCHEDULE

SIGN NO.	SIGN FACE	MUTCD NUMBER	MIN SIZE	COLORS BCK GRND	COLORS LEGEND	MOUNTING
①	STOP	R1-1	30"x30"	RED	WHITE	3 C531
②	ONE WAY	R6-1L	36"x12"	BLACK	WHITE	1 C531
③	ONE WAY	R6-1R	36"x12"	BLACK	WHITE	1 C531
④	DO NOT ENTER	R5-1	30"x30"	RED	WHITE	1 C531
⑤	RESERVED PARKING	NY R7-8D	12"x18"	WHITE/ BLUE	GREEN/ WHITE	2 C531
⑥	VAN ACCESSIBLE	R7-8P	12"x6"	WHITE	BLUE	2 C531
⑦	NO PARKING ANY TIME	R7-1	12"x18"	WHITE	RED	1 C531
⑧	ELECTRIC VEHICLE CHARGING STATION	AS SHOWN	12"x18"	WHITE	GREEN	1 C531

MUTCD SIGN SCHEDULE

SCALE: NOT TO SCALE



NOTES
1. CONCRETE SHALL HAVE A MINIMUM COMPRESSIVE STRENGTH OF 4,000 PSI AT 28 DAYS WITH A MINIMUM CEMENT CONTENT OF 600 POUNDS PER CUBIC YARD FOR ALL FOOTINGS.
2. ALL CONCRETE SHALL HAVE A SLUMP OF NO GREATER THAN 3"–5" TO WITHIN A TOLERANCE OF 0"–1".
3. ALL EXPOSED CONCRETE SHALL BE 5% AIR–ENTRAINED (WITHIN 1% TOLERANCES) CONFORMING TO ASTM C260.
4. ALL FORMWORK AND PLACEMENT OF CONCRETE SHALL COMPLY WITH GOOD CONSTRUCTION PRACTICES AND BE IN ACCORDANCE WITH GOVERNING CODES, AND REGULATIONS.

BOLLARD DETAIL - FOR REFUSE ENCLOSURE

SCALE: NOT TO SCALE

SIDEWALK RAMP HAND RAIL DETAIL

SCALE: NOT TO SCALE

MASONRY WALL DETAIL FOR REFUSE ENCLOSURE

SCALE: NOT TO SCALE



BLUE LIMESTONE PAD

SCALE: NOT TO SCALE

TOOLED EDGE - CONTROL JOINT

NOTE:
1. THICKENED (HAUNCH) & ADDITIONALLY REINFORCED CONCRETE SIDEWALK ENDS ARE REQUIRED AT ALL EXISTING/PROPOSED BUILDING ENTRANCES.
2. SEE CONCRETE SIDEWALK DETAIL FOR ADDITIONAL DETAILS & NOTES.

CONCRETE SIDEWALK AT BUILDING ENTRANCES

SCALE: NOT TO SCALE



REFUSE ENCLOSURE

SCALE: NOT TO SCALE



CONCRETE SLAB:
1. MATERIAL AND METHODS OF CONSTRUCTION SHALL BE IN CONFORMANCE WITH THE NEW YORK STATE DEPARTMENT OF TRANSPORTATION (NYSDOT) STANDARD SPECIFICATIONS FOR CONSTRUCTION AND MATERIALS, DATED MAY 1, 2008, AND ALL ADDENDA THERETO.
2. CONCRETE SHALL HAVE A MINIMUM COMPRESSION STRENGTH OF 4500 PSI @ 28 DAY AND SHALL BE PLACED IN ACCORDANCE WITH ACI SPECIFICATIONS AND ITS LATEST REVISION.
3. REINFORCING STEEL FOR CONCRETE SHALL CONFORM WITH SECTION 556 – REINFORCING STEEL FOR CONCRETE STRUCTURES OF THE ABOVE REFERENCED NYSDOT STANDARD SPECIFICATIONS AND AS SPECIFICALLY CALLED OUT IN THE DRAWINGS.
4. ALL EXPOSED SURFACED SHALL HAVE A BROOM TEXTURED FINISH & TOOLED EDGES. TOOL SHALL BE PROVIDE MAX 1–1/2" WIDE SMOOTH TROWEL FINISH AT JOINT.
5. EXPANSION JOINTS SHALL BE LOCATED A MAXIMUM OF 20' ON CENTER, OR AS INDICATED ON PLANS.
6. CONTROL JOINTS SHALL BE LOCATED A MAXIMUM OF 5' ON CENTER, OR AS INDICATED ON PLANS.
7. JOINTS SHALL NOT BE SAW CUT.
8. EXPOSED CONCRETE SURFACES SHALL BE TREATED WITH "SUREBOND"/"SAFEBOND" SB–7000 INTENSIFIER BRIGHT PROTECTOR AND SIDEWALK SEALER, OR EQUAL. RATE AND METHOD OF APPLICATION SHALL BE IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDATIONS.
9. SUBBASE MATERIAL SHALL CONFORM WITH SECTION 304 OF THE ABOVE REFERENCED NYSDOT STANDARD.
10. WHERE IT IS NECESSARY TO PLACE FILL FOR PURPOSE OF BRINGING THE SUBGRADE ELEVATION UP TO A SPECIFIED GRADE, THE FILL MATERIAL PLACED SHALL BE IN ACCORDANCE WITH SECTION 203–EXCAVATION AND EMBANKMENT OF THE ABOVE REFERENCED NYSDOT STANDARD SPECIFICATIONS.

CONCRETE SLAB

SCALE: NOT TO SCALE

LaBella
Powered by partnership.

21 Fox Street
Poughkeepsie, NY 12601
(845) 454-3980

labellapc.com

It is a violation of New York Education Law Article 145 Sec.7209, for any person, unless acting under the direction of a licensed architect, professional engineer, or land surveyor, to alter an item in any way. If an item bearing the seal of an architect, engineer, or land surveyor is altered; the altering architect, engineer, or land surveyor shall affix to the item their seal and notation "altered by" followed by their signature and date of such alteration, and a specific description of the alteration.

© 2022 LaBella Associates

APPLICANT NAME & ADDRESS:

ARGO DEVELOPMENT
95 CHESTNUT RIDGE ROAD
MONTVALE, NJ 07645

PROJECT NAME & LOCATION:

SOUTH AVE MULTI-FAMILY DEVELOPMENT
SOUTH AVENUE
CITY OF POUGHKEEPSIE, NY 12601

NO:	DATE:	DESCRIPTION:
1	01/27/23	NO CHANGES THIS SHEET
Revisions		

PROJECT NUMBER: 2222201
DRAWN BY:
REVIEWED BY: CPL
ISSUED FOR: PLANNING BOARD REVIEW
DATE: 11/28/2022
DRAWING NAME:

SITE DETAILS

DRAWING NUMBER:

C531

4/3/2023 12:25:13 PM
B:\GLOBAL\Projects\ARGO\2222201 - South Ave Multi Family Dev\06_Drawings\Civil\01_C530_C531_2222201_SITED.dwg

Drawing Name: B:\GLOBAL\Projects\ARGO\2222201 – South Ave Multi Family Dev\06_Drawings\Civil\01_C530_C531_2222201_SITED.dwg
Xref's Attached: XBORDER_2222201
Date Printed: Apr 03, 2023, 12:25pm



1 **SEATWALL TYPICAL SECTION**
SCALE: 1/2" = 1'-0"



NOTES:
1. PAVER TO BE 'BEACON HILL SMOOTH' BY UNILOCK OR APPROVED EQUAL.
   1.1. LAYING PATTERN: 'LP BEACON HILL FIXED RANDOM A'
   1.2. COLORS:
      1.2.1. PRIMARY: CHAMPAGNE
      1.2.2. ACCENT: CHARCOAL

4 **UNIT PAVERS OVER CONCRETE BASE**
SCALE: NOT TO SCALE





NOTES:
1. GRANITE CURB TO BE INSTALLED IN ACCORDANCE WITH NYSDOT STANDARD SPECIFICATION **SECTION 609**.

5 **FLUSH GRANITE CURB**
SCALE: NOT TO SCALE



2 **6' TABLES**
SCALE: NOT TO SCALE



3 **6' BENCH**
SCALE: NOT TO SCALE

LaBella
Powered by partnership.

21 Fox Street
Poughkeepsie, NY 12601
(845) 454-3980

labellapc.com

It is a violation of New York Education Law Article 145 Sec.7209, for any person, unless acting under the direction of a licensed architect, professional engineer, or land surveyor, to alter an item in any way. If an item bearing the seal of an architect, engineer, or land surveyor is altered; the altering architect, engineer, or land surveyor shall affix to the item their seal and notation "altered by" followed by their signature and date of such alteration, and a specific description of the alteration.

© 2022 LaBella Associates

APPLICANT NAME & ADDRESS:

ARGO DEVELOPMENT
95 CHESTNUT RIDGE ROAD
MONTVALE, NJ 07645

PROJECT NAME & LOCATION:

SOUTH AVE
MULTI-FAMILY DEVELOPMENT
SOUTH AVENUE
CITY OF POUGHKEEPSIE, NY 12601

NO:	DATE:	DESCRIPTION:
1	01/27/23	NO CHANGES THIS SHEET
Revisions		

PROJECT NUMBER: 2222201
DRAWN BY:
REVIEWED BY: CPL
ISSUED FOR: PLANNING BOARD REVIEW
DATE: 11/28/2022
DRAWING NAME:

SITE DETAILS

DRAWING NUMBER:

C532

4/3/2023 12:25:23 PM
B:\GLOBAL\Projects\ARGO\2222201 - South Ave Multi Family Dev\06_Drawings\Civil\01_C530_C531_2222201_SITED.dwg
Drawing Name: B:\GLOBAL\Projects\ARGO\2222201 - South Ave Multi Family Dev\06_Drawings\Civil\01_C530_C531_2222201_SITED.dwg
Xref's Attached: XBORDER_2222201
Date Printed: Apr 03, 2023, 12:25pm

EROSION AND SEDIMENT CONTROL MEASURES:

1. DAMAGE TO SURFACE WATERS RESULTING FROM EROSION AND SEDIMENTATION SHALL BE MINIMIZED BY STABILIZING DISTURBED AREAS AND BY REMOVING SEDIMENT FROM CONSTRUCTION SITE DISCHARGES.
2. AS MUCH AS IS PRACTICAL, EXISTING VEGETATION SHALL BE PRESERVED. FOLLOWING THE COMPLETION OF CONSTRUCTION ACTIVITIES IN ANY PORTION OF THE SITE, PERMANENT VEGETATION SHALL BE ESTABLISHED ON ALL EXPOSED SOILS.
3. SITE PREPARATION ACTIVITIES SHALL BE PLANNED TO MINIMIZE THE SCOPE AND DURATION OF SOIL DISRUPTION.
4. PERMANENT TRAFFIC CORRIDORS SHALL BE ESTABLISHED AND "ROUTES OF CONVENIENCE" SHALL BE AVOIDED. STABILIZED CONSTRUCTION ENTRANCES SHALL BE INSTALLED AT ALL POINTS OF ENTRY ONTO THE PROJECT SITE.

GENERAL EROSION AND SEDIMENT CONTROL NOTES:

1. ALL EROSION AND SEDIMENT CONTROL MEASURES ARE TO BE IN STRICT COMPLIANCE WITH "NEW YORK STATE STANDARDS AND SPECIFICATIONS FOR EROSION AND SEDIMENT CONTROL", LATEST EDITION.
2. EXCESS SOIL TO BE STOCKPILED WITHIN THE LIMITS OF SITE DISTURBANCE IF NOT USED IMMEDIATELY FOR GRADING PURPOSES. INSTALL SILT FENCE AROUND SOIL STOCKPILES.
3. APPLY SURFACE STABILIZATION AND RESTORATION MEASURES. AREAS UNDERGOING CLEARING OR GRADING AND ANY AREAS DISTURBED BY CONSTRUCTION ACTIVITIES WHERE WORK IS DELAYED, SUSPENDED, OR INCOMPLETE AND WILL NOT BE REDISTURBED FOR 21 DAYS OR MORE SHALL BE STABILIZED WITH TEMPORARY VEGETATIVE COVER WITHIN 14 DAYS AFTER CONSTRUCTION ACTIVITY IN THAT PORTION OF THE SITE HAS CEASED. (SEE SPECIFICATIONS FOR TEMPORARY VEGETATIVE COVER). AREAS UNDERGOING CLEARING OR GRADING AND ANY AREAS DISTURBED BY CONSTRUCTION ACTIVITIES WHERE WORK IS COMPLETE AND WILL NOT BE REDISTURBED SHALL BE STABILIZED AND RESTORED WITH PERMANENT VEGETATIVE COVER AS SOON AS SITE AREAS ARE AVAILABLE AND WITHIN 14 DAYS AFTER WORK IS COMPLETE. (SEE SPECIFICATIONS FOR PERMANENT VEGETATIVE COVER). SEEDING FOR PERMANENT VEGETATIVE COVER SHALL BE WITHIN THE SEASONAL LIMITATIONS. PROVIDE STABILIZATION WITH TEMPORARY VEGETATIVE COVER WITHIN 14 DAYS AFTER WORK IS COMPLETE, FOR SEEDING OUTSIDE PERMITTED SEEDING PERIODS.
4. SEEDED AREAS TO BE MULCHED WITH STRAW OR HAY MULCH IN ACCORDANCE WITH VEGETATIVE COVER SPECIFICATIONS.
5. THE CONTRACTOR IS RESPONSIBLE FOR THE INSTALLATION AND MAINTENANCE OF ALL EROSION AND SEDIMENT CONTROL MEASURES THROUGHOUT THE COURSE OF CONSTRUCTION.
6. THE CONTRACTOR IS RESPONSIBLE FOR CONTROLLING DUST BY SPRINKLING EXPOSED SOIL AREAS PERIODICALLY WITH WATER AS REQUIRED. THE CONTRACTOR IS TO SUPPLY ALL EQUIPMENT AND WATER.
7. WHEN ALL DISTURBED AREAS ARE STABLE, ALL TEMPORARY EROSION AND SEDIMENT CONTROL MEASURES SHALL BE REMOVED.

MAINTENANCE OF EROSION AND SEDIMENT CONTROL MEASURES:

PERMANENT AND TEMPORARY VEGETATION:
INSPECT ALL AREAS THAT HAVE RECEIVED VEGETATION EVERY SEVEN DAYS & AFTER EVERY RAIN EVENT. ALL AREAS DAMAGED BY EROSION OR WHERE SEED HAS NOT ESTABLISHED SHALL BE REPAIRED AND RESTABILIZED IMMEDIATELY.

STABILIZED CONSTRUCTION ENTRANCE:
INSPECT THE ENTRANCE PAD EVERY SEVEN DAYS & AFTER EVERY RAIN EVENT. CHECK FOR MUD, SEDIMENT BUILD-UP AND PAD INTEGRITY. MAKE DAILY INSPECTIONS DURING WET WEATHER. RESHAPE PAD AS NEEDED FOR DRAINAGE AND RUNOFF CONTROL. WASH AND REPLACE STONE AS NEEDED. THE STONE IN THE ENTRANCE SHOULD BE WASHED OR REPLACED WHENEVER THE ENTRANCE FAILS TO REDUCE MUD BEING CARRIED OFF-SITE BY VEHICLES. IMMEDIATELY REMOVE MUD AND SEDIMENT TRACKED OR WASHED ONTO PUBLIC ROADS BY BRUSHING OR SWEEPING. REMOVE TEMPORARY CONSTRUCTION ENTRANCE AS SOON AS THEY ARE NO LONGER NEEDED TO PROVIDE ACCESS TO THE SITE.

SILT FENCE:
INSPECT FOR DAMAGE EVERY SEVEN DAYS & AFTER EVERY RAIN EVENT. MAKE ALL REPAIRS IMMEDIATELY. REMOVE SEDIMENT FROM THE UP-SLOPE FACE OF THE FENCE BEFORE IT ACCUMULATES TO A HEIGHT EQUAL TO 1/3 THE HEIGHT OF THE FENCE. IF FENCE FABRIC TEARS, BEGINS TO DECOMPOSE, OR IN ANY WAY BECOMES INEFFECTIVE, REPLACE THE AFFECTED SECTION OF FENCE IMMEDIATELY.

SOIL STOCKPILE:
INSPECT SEDIMENT CONTROL BARRIERS (SILT FENCE OR HAY BALE) AND VEGETATION FOR DAMAGE EVERY SEVEN DAYS & AFTER EVERY RAIN EVENT. MAKE ALL REPAIRS IMMEDIATELY. REMOVE SEDIMENT FROM THE UP-SLOPE FACE OF THE SEDIMENT CONTROL BARRIER BEFORE IT ACCUMULATES TO A HEIGHT EQUAL TO 1/3 THE HEIGHT OF THE SEDIMENT CONTROL BARRIER. IF SEDIMENT CONTROL BARRIER TEARS, BEGINS TO DECOMPOSE, OR IN ANYWAY BECOMES INEFFECTIVE, REPLACE THE AFFECTED SECTION OF SEDIMENT CONTROL BARRIER IMMEDIATELY. REVEGETATE DISTURBED AREA TO STABILIZE SOIL STOCK PILE. REMOVE THE SEDIMENT CONTROL BARRIER WHEN THE SOIL STOCKPILE HAS BEEN REMOVED. REFER TO REMEDIAL ACTION WORK PLAN FOR SPECIFICATIONS REGARDING STOCKPILING OF CONTAMINATED SOILS.

DUST CONTROL:
SCHEDULE CONSTRUCTION OPERATIONS TO MINIMIZE THE AMOUNT OF DISTURBED AREAS AT ANY ONE TIME DURING THE COURSE OF WORK. APPLY TEMPORARY SOIL STABILIZATION PRACTICES SUCH AS MULCHING, SEEDING, AND SPRAYING (WATER). STRUCTURAL MEASURES (MULCH, SEEDING) SHALL BE INSTALLED IN DISTURBED AREAS BEFORE SIGNIFICANT BLOWING PROBLEMS DEVELOP. WATER SHALL BE SPRAYED AS NEEDED. REPEAT AS NEEDED, BUT AVOID EXCESSIVE SPRAYING, WHICH COULD CREATE RUNOFF AND EROSION PROBLEMS.

EROSION CONTROL BLANKET:
INSPECT THE BLANKET EVERY SEVEN DAYS & AFTER EVERY RAIN EVENT. REPLACE WIRE STAPLES AS REQUIRED. REPAIR AND RESEED WHERE CRACKS AND DAMAGED VEGETATION IS EVIDENT. WHEN DAMAGED BEYOND REPAIR OR NO LONGER FUNCTIONING, THE BLANKET SHALL BE REPLACED.

EARTH DIKE:
INSPECT ALL EARTH DIKES EVERY SEVEN DAYS & AFTER EVERY RAIN EVENT. ALL AREAS DAMAGED BY EROSION SHALL BE REPAIRED IMMEDIATELY.

STORM DRAIN INLET PROTECTION:
INSPECT ALL STORM DRAIN INLET PROTECTION DEVICES EVERY SEVEN DAYS & AFTER EVERY RAIN EVENT. MAKE REPAIRS AS NEEDED, REMOVE SEDIMENT FROM THE POOL AREA AS NECESSARY.

DEWATERING PITS:
IF GROUNDWATER IS ENCOUNTERED DURING EXCAVATION AND REQUIRES REMOVAL, GROUNDWATER WILL BE PUMPED , VIA SUBMERSIBLE PUMPS INTO APPROVED HOLDING CONTAINERS (NYSDOT RATED 55 GALLON DRUMS). CONTAINERS SHOULD BE STAGED ON SITE IN A SECURE, LOCKED AREA PENDING CHARACTERIZATION. Samples OF THE CONTAINERIZED WATER SHALL BE COLLECTED AND ANALYZED TO DETERMINE THE APPROPRIATE DISPOSAL FACILITY. BASED ON THE RESULTS OF THE ANALYSIS THE ON-SITE REMEDIAL CONSULTANT WILL DETERMINE MEANS OF OFF-SITE DISPOSAL AND TREATMENT (AS REQUIRED).

SNOW AND ICE CONTROL:
PARKING LOTS, ROADWAYS, AND DRIVEWAYS ADJACENT TO WATER QUALITY FILTERS SHALL NOT BE SANDED DURING SNOW EVENTS DUE TO HIGH POTENTIAL FOR CLOGGING FROM SAND IN SURFACE WATER RUNOFF. USE SALT ONLY FOR SNOW AND ICE CONTROL.

GENERAL NOTES:

1. EROSION AND SEDIMENT CONTROL MEASURES SHALL NOT BE PLACED IN PUBLIC ACCESS AREAS OR INTERFERE WITH PUBLIC ACCESS.
2. ALL OFF-SITE ROADS AND CORRIDORS SHALL BE KEPT CLEAN AT ALL TIMES DURING CONSTRUCTION. THIS SHALL INCLUDE STREET CLEANING AND SWEEPING OF PARKER AVENUE AND BROOKSVILLE AVENUE AS NEEDED OR DIRECTED BY THE REMEDIATION ENGINEER OR QUALIFIED PROFESSIONAL IN EROSION AND SEDIMENT CONTROL PERFORMING EROSION AND SEDIMENT CONTROL INSPECTION (QPESC). THE CONTRACTOR SHALL IMMEDIATELY CLEAN UP SPILLS OR TRACKED DEBRIS ON OR OFF-SITE.
3. CONTRACTOR SHALL BE RESPONSIBLE FOR ALL SNOW REMOVAL DURING THE COURSE OF CONSTRUCTION, TO INCLUDE ALL WORK AREAS AND ASSOCIATED PUBLIC ACCESS WAYS AND SIDEWALKS ALONG PROPERTY, CONSTRUCTION ACCESS CORRIDORS, AND STAGING AREAS.
4. THE CONTRACTOR SHALL TAKE ALL NECESSARY MEASURES PROTECT THE PUBLIC. OPEN TRENCHES, HOLES AND CONSTRUCTION OPERATIONS ARE TO BE SEPARATED FROM PUBLIC ACCESS WAYS BY CONSTRUCTION FENCE AND OTHER METHODS SET A PRUDENT DISTANCE FROM OPENINGS.
5. CONTRACTOR IS RESPONSIBLE FOR ALL DEWATERING OPERATIONS AS REQUIRED FOR CONSTRUCTION.
6. THE WORD "PROVIDE," WHEN USED IN CONNECTION WITH SERVICES, MATERIALS, OR EQUIPMENT, SHALL MEAN TO FURNISH AND INSTALL SAID SERVICES, MATERIALS, OR EQUIPMENT COMPLETE AND READY FOR INTENDED USE.
7. CONTRACTOR SHALL PROVIDE AND INSTALL TEMPORARY CHAIN LINK FENCE WITH SCREENING AROUND LIMITS OF WORK, AS APPROVED BY OWNER.

SPDES GENERAL PERMIT GP-0-20-001 COMPLIANCE NOTES:

THIS PLAN SET AND THE ACCOMPANYING SWPPP ENTITLED "SOUTH AVENUE MULTI-FAMILY DEVELOPMENT" WILL BE SUBMITTED AS A SET. THESE ENGINEERING DRAWINGS ARE CONSIDERED AN INTEGRAL PART OF THE SWPPP, THEREFORE THE PLAN SET IS NOT CONSIDERED COMPLETE WITHOUT THE SWPPP AND FOLLOWING DOCUMENTS.

1. REFER TO REQUIREMENTS OUTLINED IN THE MATERIALS MANAGEMENT, HEALTH AND SAFETY, AND EROSION & SEDIMENT CONTROL PLANS & NOTES PRIOR TO COMMENCEMENT OF WORK.



NOTES:
1. SEDIMENT COLLECTION BAG SHALL BE EQUAL TO DIRTBAG® 55, AS MARKETED BY ACF ENVIRONMENTAL. RICHMOND. VIRGINIA (800-448-3636). OR APPROVED EQUIVALENT.
2. SEDIMENT COLLECTION BAG SHALL BE A NONWOVEN BAG SEWN WITH HIGH STRENGTH THREAD. THE SEAMS SHALL BE HIGH STRENGTH, DOUBLE STITCHED, "J" TYPE SEAMS.
3. BAGS SHALL HAVE SEWN IN FILL SPOUT LARGE ENOUGH TO ACCOMMODATE UP TO A 4" DISCHARGE HOSE. FILL SPOUT SHALL HAVE HIGH STRENGTH STRAPPING TO HOLD HOSE IN PLACE AND PREVENT PUMPED WATER FROM ESCAPING WITHOUT BEING FILTERED.
4. SEDIMENT COLLECTION BAGS SHALL BE INSTALLED IN ACCORDANCE WITH THE MANUFACTURERS INSTRUCTIONS, OR AS DIRECTED BY THE ENGINEER.
5. SEDIMENT COLLECTED SHALL BE DISPOSED OF AT AN APPROPRIATE FACILITY.
6. SEDIMENT COLLECTION BAGS SHALL BE REMOVED AND REPLACED UNDER ANY OF THE FOLLOWING CONDITIONS:
   - WHEN BAGS ARE FULL.
   - WHEN BAGS HAVE BEEN IN PLACE FOR MORE THAN 30 DAYS (REMOVAL REQUIRED DUE TO ULTRAVIOLET DETERIORATION).
   - WHEN BAGS ARE DAMAGED.
4. ALL SEDIMENT COLLECTION BAGS SHALL BE INSPECTED DAILY BY THE CONTRACTOR.
5. CARE SHALL BE TAKEN DURING REMOVAL TO MINIMIZE LOSS OF ENTRAPPED SEDIMENT.

© 7 **SEDIMENT COLLECTION DEWATERING BAG DETAIL**
SCALE: NOT TO SCALE

STONE APRON SIZING REQUIREMENT - TABLE "A"

CULVERT DIA. (D)	CULVERT SLOPE, %	NYSDOT STANDARD STONE FILLING APRON MATERIAL	d50	dMAX	MINIMUM APRON THICKNESS (IN)	MINIMUM OUTLET APRON LENGTH(FT) (La)
12"	< 8	LIGHT	6"	9"	18	10
	8–10	MEDIUM	9"–12"	14"–18"	24	10
18"	< 4	LIGHT	6"	9"	18	10
	4–6	MEDIUM	9"–12"	14"–18"	24	12
	6–8	HEAVY	15"–18"	22"–27"	36	12
	8–10	HEAVY	15"–18"	22"–27"	36	18
24"	< 3	LIGHT	6"	9"	18	12
	3–4	MEDIUM	9"–12"	14"–18"	24	16
	4–8	HEAVY	15"–18"	22"–27"	36	24
30"	< 1	LIGHT	6"	9"	18	15
	1–2	MEDIUM	9"–12"	14"–18"	24	20
	2–4	HEAVY	15"–18"	22"–27"	36	25
	4–6	HEAVY	15"–18"	22"–27"	36	30
36"	< 2	MEDIUM	9"–12"	14"–18"	24	24
	2–3	HEAVY	15"–18"	22"–27"	36	30
	3–5	HEAVY	15"–18"	22"–27"	36	36
42"	< 1	MEDIUM	9"–12"	14"–18"	24	28
	1–2	HEAVY	15"–18"	22"–27"	36	35
	2–3	HEAVY	15"–18"	22"–27"	36	42
48"	< 1	MEDIUM	9"–12"	14"–18"	24	32
	1–2	HEAVY	15"–18"	22"–27"	36	40
	2–3	HEAVY	15"–18"	22"–27"	36	48



© 3 **END SECTION WITH STONE LINED APRON DETAIL**
SCALE: NOT TO SCALE

CONSTRUCTION SEQUENCING NOTES:
1. PRIOR TO COMMENCING ANY CLEARING, GRUBBING, EARTHWORK ACTIVITIES, ETC.AT THE SITE, THE CONTRACTOR SHALL FLAG THE WORK LIMITS AND SHALL INSTALL TEMPORARY EROSION AND SEDIMENT CONTROL MEASURES (I.E. SILT FENCES, TREE PROTECTION/BARRIER FENCES, STABILIZED CONSTRUCTION ENTRANCES, STORM DRAIN SEDIMENT FILTERS, DRAINAGE DITCH SEDIMENT FILTERS, ETC.) INDICATED ON THE PROJECT DRAWINGS. TEMPORARY EROSION AND SEDIMENT CONTROL MEASURES MUST BE CONSTRUCTED, STABILIZED, AND FUNCTIONAL BEFORE SITE DISTURBANCE BEGINS WITHIN THEIR TRIBUTARY AREAS.
2. THE CONTRACTOR SHALL CLEAR AND GRUB THE AREA OF THE STORMWATER MANAGEMENT FACILITIES. THIS AREA SHALL NOT EXCEED FIVE (5) ACRES IN EXTENT WITHOUT TEMPORARY STABILIZATION.
3. THE CONTRACTOR SHALL COMMENCE SITE CONSTRUCTION ACTIVITIES INCLUDING CLEARING & GRADING OF THE PROPOSED AREA OF DISTURBANCE AS REQUIRED.
4. INSTALL PROTECTIVE MEASURES AT THE LOCATIONS OF ALL GRATE INLETS, CURB INLETS, AND AT THE ENDS OF ALL EXPOSED STORM SEWER PIPES.
5. CONSTRUCT ALL UTILITIES, CURB AND GUTTER, GUTTER INLETS, AREA INLETS, AND STORM SEWER MANHOLES, AS SHOWN ON THE PLANS. INLET PROTECTION MAY BE REMOVED TEMPORARILY FOR THIS CONSTRUCTION. PLACE REQUIRED RIP-RAP AT LOCATIONS SHOWN ON THE PLANS.
6. FINALIZE PAVEMENT SUB-GRADE PREPARATION.
7. REMOVE PROTECTIVE MEASURES AROUND INLETS AND MANHOLES NO MORE THAN 24 HOURS PRIOR TO PLACING STABILIZED BASE COURSE.
8. INSTALL SUB-BASE MATERIAL AS REQUIRED FOR PAVEMENT.
9. PRIOR TO FINALIZING CONSTRUCTION OF THE STORMWATER MANAGEMENT FACILITY, ALL CATCH BASINS AND DRAINAGE LINES SHALL BE CLEANED OF ALL SILT AND SEDIMENT.
10. UPON COMPLETION OF SITE CONSTRUCTION ACTIVITIES, THE CONTRACTOR SHALL FINALIZE CONSTRUCTION OF THE STORMWATER MANAGEMENT FACILITY. CONTRACTOR SHALL FINISH GRADE THE FORBAY(S) AND STABILIZE AS INDICATED IN THE PROJECT DRAWINGS.
11. THE CONTRACTOR SHALL REMOVE ALL TEMPORARY EROSION AND SEDIMENT CONTROL MEASURES AND IMMEDIATELY ESTABLISH PERMANENT VEGETATION ON THE AREAS DISTURBED DURING THEIR REMOVAL.



NOTES:
1. FILTER FABRIC SHALL HAVE AN EOS OF 40-85.
2. CUT FABRIC FROM CONTINUOUS ROLL TO ELIMINATE JOINTS. IF JOINTS ARE NEEDED, OVERLAP TO THE NEXT STAKE.
3. STAKE MATERIALS WILL BE STANDARD 2"x4" WOOD OR EQUIVALENT, WITH A MINIMUM LENGTH OF 3 FEET.
4. SPACE STAKES EVENLY AROUND INLET 3 FEET APART AND DRIVE MINIMUM 18" DEEP. SPANS GREATER THAN 3 FEET MAY BE BRIDGED WITH THE USE OF WIRE MESH BEHIND FABRIC FOR SUPPORT.
5. FABRIC SHALL BE EMBEDDED 1 FOOT MINIMUM BELOW GROUND AND BACKFILLED. IT SHALL BE SECURELY FASTENED TO THE STAKES AND FRAME.
6. A 2"x4" WOOD FRAME SHALL BE COMPLETED AROUND THE CREST OF THE FABRIC FOR OVERFLOW STABILITY.
7. MAXIMUM DRAINAGE AREA IS 1 ACRE.
8. INLET PROTECTION SHALL REMAIN IN-PLACE UNTIL SITE HAS BEEN STABILIZED.

© 6 **TEMPORARY OUT OF PAVEMENT FILTER FABRIC DROP INLET PROTECTION DETAIL**
SCALE: NOT TO SCALE



© 8 **SILT SACK DETAIL**
SCALE: NOT TO SCALE



TYPICAL SECTION OF SUMP PIT

NOTES:
1. SUMP PIT QUANTITY & LOCATION SHALL BE DETERMINED BY CONTRACTOR.
2. PERFORATIONS IN THE STANDPIPE SHALL BE EITHER CIRCULAR OR SLOTS. PERFORATION SIZE SHALL NOT EXCEED 1/2" INCH DIAMETER. PUMP RATE SHALL NOT EXCEED INFLOW RATE INTO STAND PIPE.
3. CRUSHED STONE OR GRAVEL SHALL BE NYSDOT #2 SIZE OR EQUIVALENT AND SHALL BE WASHED PRIOR TO PLACEMENT WITHIN SUMP.
4. DISCHARGE SHALL BE THROUGH DEWATERING BAGS, OR AS DIRECTED BY ENGINEER.
5. CONTRACTOR TO SUBMIT DEWATERING PLAN TO ENGINEER FOR REVIEW & APPROVAL.

© 10 **DEWATERING & SUMP PIT DETAIL**
SCALE: NOT TO SCALE



CONSTRUCTION ENTRANCE SPECIFICATIONS:
1. STONE SIZE – USE 2" STONE, OR RECLAIMED OR RECYCLED CONCRETE EQUIVALENT.
2. THICKNESS – NOT LESS THAN SIX (6) INCHES.
3. WIDTH – TWELVE (12) FOOT MINIMUM, BUT NOT LESS THAN THE FULL WIDTH AT POINTS WHERE INGRESS OR EGRESS OCCURS. TWENTY FOUR (24) FEET IF SINGLE ENTRANCE TO SITE.
4. LENGTH – NOT LESS THAN 50' (EXCEPT ON A SINGLE RESIDENCE LOT WHERE A 30' MINIMUM LENGTH WOULD APPLY).
5. GEOTEXTILE – WILL BE PLACED OVER THE ENTIRE AREA PRIOR TO PLACING OF STONE.
6. SURFACE WATER – ALL SURFACE WATER FLOWING OR DIVERTED TOWARD CONSTRUCTION ENTRANCES SHALL BE PIPED ACROSS THE ENTRANCE. IF PIPING IS IMPRACTICAL, A MOUNTABLE BERM WITH 5:1 SLOPES WILL BE PERMITTED.
7. MAINTENANCE – THE ENTRANCE SHALL BE MAINTAINED IN A CONDITION WHICH WILL PREVENT TRACKING OR FLOWING OF SEDIMENT ONTO PUBLIC RIGHTS-OF-WAY. THIS MAY REQUIRE PERIODIC TOP DRESSING WITH ADDITIONAL STONE AS CONDITIONS DEMAND AND REPAIR AND/OR CLEANOUT OF ANY MEASURES USED TO TRAP SEDIMENT. ALL SEDIMENT SPILLED, DROPPED, WASHED OR TRACKED ONTO PUBLIC RIGHTS-OF-WAY MUST BE REMOVED IMMEDIATELY.
8. WASHING – WHEELS SHALL BE CLEANED TO REMOVE SEDIMENT PRIOR TO ENTRANCE ONTO PUBLIC RIGHTS-OF-WAY. WHEN WASHING IS REQUIRED, IT SHALL BE DONE ON AN AREA STABILIZED WITH STONE AND WHICH DRAINS INTO AN APPROVED SEDIMENT TRAPPING DEVICE.
9. PERIODIC INSPECTION AND NEEDED MAINTENANCE SHALL BE PROVIDED AFTER EACH RAIN.

© 1 **STABILIZED CONSTRUCTION ACCESS DETAIL**
SCALE: NOT TO SCALE



NOTES:
1. TOPSOIL, SEED, MULCH, AND FERTILIZE DISTURBED SOIL AREAS THAT WILL BE LEFT EXPOSED FOR 14 DAYS OR MORE.

© 4 **TEMPORARY TOPSOIL, FERTILIZER, SEED & MULCH DETAIL**
SCALE: NOT TO SCALE



NOTES:
1. AREA CHOSEN FOR STOCKPILING OPERATIONS SHALL BE DRY AND STABLE.
2. MAXIMUM SLOPE OF STOCKPILE SHALL BE 1V:2H.
3. UPON COMPLETION OF SOIL STOCKPILING, EACH PILE SHALL BE SURROUNDED WITH SILT FENCING, THEN STABILIZED WITH VEGETATION OR COVERED.
4. SEE SPECIFICATIONS FOR INSTALLATION OF SILT FENCE.

© 9 **TEMPORARY SOIL STOCKPILE DETAIL**
SCALE: NOT TO SCALE



NOTES:

1. PREPARE THE TOPSOIL (SEEDBED) FIRST BY RAKING, SHAPING, FINE GRADING, COMPACTING, SEEDING & FERTILIZING THE SLOPES.

2. USE THE TRENCHING & ANCHORING PROCEDURES DETAILED HEREIN TO SECURE ANY EXPOSED MATERIAL ENDS. SECURE ALL PRODUCT OVERLAPS. OVERLAP IN THE DIRECTION OF WATER FLOW, PERPENDICULAR TO THE SLOPE.

3. KEEP EROSION CONTROL BLANKET IN SOLID CONTACT WITH THE TOPSOIL.

4. USE THE REQUIRED NUMBER OF STAPLES/STAKES TO SECURELY FASTEN THE EROSION CONTROL BLANKET TO THE SLOPE. IN LOOSE SOIL CONDITIONS, THE USE OF STAPLES/STAKES LENGTHS GREATER THAN 6" MAYBE NECESSARY FOR PROPER SECURING. STAPLE PATTERNS & OVERLAPS ARE DEPENDENT ON SITE CONDITIONS & MANUFACTURER'S REQUIREMENTS. CONTRACTOR SHALL CONSULT WITH MANUFACTURER FOR ACTUAL SITE SPECIFIC REQUIREMENTS.

TRENCHING & ANCHORING PROCEDURE NOTES:

SIDE SEAM OVERLAP: THE EDGES OF PARALLEL BLANKETS SHALL BE STAPLED WITH A 5" OVERLAP.

TOP OF SLOPE TRENCH: BEGIN AT THE TOP OF SLOPE BY ANCHORING THE EROSION CONTROL BLANKET IN A 6"D x 6"W TRENCH WITH A 12" OVERLAP EXTENDED BEYOND THE UP-SLOPE PORTION OF THE TRENCH. ANCHOR WITH A ROW OF STAPLES/STAKES 12" O.C. IN THE BOTTOM OF THE TRENCH. BACKFILL & COMPACT THE TRENCH AFTER STAPLING. APPLY SEED TO THE COMPACTED SOIL & FOLD THE REMAINING 12" PORTION OF THE EROSION CONTROL BLANKET BACK OVER THE SEED & COMPACTED SOIL. SECURE THE EROSION CONTROL BLANKET OVER THE COMPACTED SOIL WITH A ROW OF STAPLES/STAKES SPACED 12" O.C. ACROSS THE ENTIRE WIDTH.

END ROLL OVERLAP: CONSECUTIVE BLANKETS SPLICED DOWN THE SLOPE SHALL BE PLACED END OVER END (SHINGLE-STYLE) WITH A 3" OVERLAP. STAPLE THRU OVERLAPPED AREAS, 12" APART ACROSS THE ENTIRE WIDTH.

© 5 **EROSION CONTROL BLANKET INSTALLATION DETAIL**
SCALE: NTS



NOTES:
1. WOVEN WIRE FENCE TO BE FASTENED SECURELY TO FENCE POSTS WITH WIRE TIES OR STAPLES. POSTS SHALL BE STEEL "T" OR "U" TYPE OR HARDWOOD.
2. FILTER FABRIC TO BE FASTENED SECURELY TO WOVEN WIRE FENCE WITH TIES SPACED EVERY 24" AT TOP AND MID SECTION. FENCE SHALL BE WOVEN WIRE, 6" MAX MESH OPENING.
3. WHEN TWO SECTIONS OF FILTER FABRIC ADJOIN EACH OTHER THEY SHALL BE OVERLAPPED BY 6" AND FOLDED.
4. MAINTENANCE SHALL BE PERFORMED AS NEEDED AND MATERIALS REMOVED WHEN "BULGES" DEVELOP IN THE SILT FENCE.
5. MAXIMUM DRAINAGE AREA FOR OVERLAND FLOW TO A SILT FENCE SHALL NOT EXCEED 1/4 ACRE PER 100 FEET OF FENCE.
6. SILT FENCE SHALL BE USED WHERE EROSION COULD OCCUR IN THE FORM OF SHEET EROSION.
7. SILT FENCE SHALL NOT BE USED WHEN A CONCENTRATION OF WATER IS FLOWING TO THE BARRIER.
8. MAXIMUM ALLOWABLE SLOPE LENGTHS CONTRIBUTING RUN-OFF TO A SILT FENCE ARE:

SLOPE STEEPNESS	MAXIMUM SLOPE LENGTH(FT)
2:1	25
3:1	50
4:1	75
5:1 OR FLATTER	100

© 2 **SILT FENCE INSTALLATION DETAIL**
SCALE: NOT TO SCALE



NOTES:
1. CONTAINMENT MUST BE STRUCTURALLY SOUND AND LEAK FREE AND CONTAIN ALL LIQUID WASTES.
2. CONTAINMENT DEVICES MUST BE OF SUFFICIENT QUANTITY OR VOLUME TO COMPLETELY CONTAIN THE LIQUID WASTES GENERATED.
3. WASHOUT MUST BE CLEANED OR NEW FACILITIES CONSTRUCTED AND READY TO USE ONCE WASHOUT IS 75% FULL. THIS INCLUDES REPLACEMENT OF THE 10 MIL POLYETHLENE SHEETING.
4. WASHOUT AREA(S) SHALL BE INSTALLED IN A LOCATION EASILY ACCESSIBLE BY CONCRETE TRUCKS.
5. ONE OR MORE AREAS MAY BE INSTALLED ON THE CONSTRUCTION SITE AND MAY BE RELOCATED AS CONSTRUCTION PROGRESSES.
6. AT LEAST WEEKLY, REMOVE ACCUMULATION OF SAND AND AGGREGATE AND DISPOSE OF PROPERLY.

© 11 **CONCRETE WASHOUT AREA DETAIL**
SCALE: NOT TO SCALE

LaBella
Powered by partnership.

21 Fox Street
Poughkeepsie, NY 12601
(845) 454-3980

labellapc.com

It is a violation of New York Education Law Article 145 Sec.7209, for any person, unless acting under the direction of a licensed architect, professional engineer, or land surveyor, to alter an item in any way. If an item bearing the seal of an architect, engineer, or land surveyor is altered; the altering architect, engineer, or land surveyor shall affix to the item their seal and notation "altered by" followed by their signature and date of such alteration, and a specific description of the alteration.

© 2022 LaBella Associates

APPLICANT NAME & ADDRESS:
ARGO DEVELOPMENT
95 CHESTNUT RIDGE ROAD
MONTVALE, NJ 07645

PROJECT NAME & LOCATION:
SOUTH AVE MULTI-FAMILY DEVELOPMENT
SOUTH AVENUE
CITY OF POUGHKEEPSIE, NY 12601

NO:	DATE:	DESCRIPTION:
1	01/27/23	NO CHANGES THIS SHEET

Revisions

PROJECT NUMBER: 2222201
DRAWN BY:
REVIEWED BY: CPL
ISSUED FOR: PLANNING BOARD REVIEW
DATE: 11/28/2022
DRAWING NAME:
EROSION SEDIMENT CONTROL DETAILS
DRAWING NUMBER:
C540

4/3/2023 12:25:37 PM
B:\GLOBAL\Projects\ARGO\2222201 - South Ave Multi Family Dev\06_Drawings\Civil\01_C540_2222201_ESC_DETAILS.dwg

Drawing Name: B:\GLOBAL\Projects\ARGO\2222201 – South Ave Multi Family Dev\06_Drawings\Civil\01_C540_2222201_ESC_DETAILS.dwg
Xref's Attached: XBORDER_2222201
Date Printed: Apr 03, 2023, 12:25pm



NOTES:

1. PIPE BEDDING & PIPE ZONE BACKFILL SHALL BE A NATURAL RUN-OF-BANK (R.O.B.) SAND OR A MIXTURE OF CRUSHED STONE AND GRAVEL, FREE OF SOFT, NONDURABLE PARTICLES, ORGANIC MATERIALS AND ELONGATED PARTICLES, AND SHALL BE WELL GRADED FROM FINE TO COARSE PARTICLES. BEDDING GRADATIONS SHALL BE APPROVED BY THE ENGINEER AND SHALL MEET THE FOLLOWING GRADATION REQUIREMENTS:

SIEVE DESIGNATION	% PASSING
3/4"	100%
NO. 40	0-70%
NO. 200	0-10%

2. TRENCH BACKFILL SHALL BE A NATURAL RUN-OF-BANK (R.O.B.) OR PROCESSED GRAVEL, OR EXCAVATED MATERIAL FREE OF SOFT, NONDURABLE PARTICLES, ORGANIC MATERIALS AND ELONGATED PARTICLES, AND SHALL BE WELL GRADED FROM FINE TO COARSE PARTICLES. TRENCH BACKFILL GRADATIONS SHALL BE APPROVED BY THE ENGINEER AND SHALL MEET THE FOLLOWING GRADATION REQUIREMENTS:

SIEVE DESIGNATION	% PASSING
4"	100%
NO. 40	0-70%
NO. 200	0-10%

IN NON-TRAFFIC UNPAVED AREAS TRENCH BACKFILL CAN BE MATERIALS EXCAVATED FROM THE TRENCH AS APPROVED BY THE ENGINEER AND COMPACTED TO 90% MODIFIED PROCTOR.

3. INSTALL CONTINUOUS DETECTABLE MARKING TAPE DURING BACKFILLING OF TRENCH FOR UNDERGROUND PIPING. LOCATE TAPE 12" BELOW FINISHED GRADE, DIRECTLY OVER PIPING, EXCEPT 6" BELOW SUBGRADE UNDER PAVEMENTS & SLAB.

4. TRENCHING SHALL BE IMPLEMENTED IN ACCORDANCE WITH O.S.H.A. STANDARDS.

5. 5'-0" MIN COVER SHALL BE APPLIED TO WATER MAIN OR SANITARY SEWER FORCE MAINS ONLY.

6. DEWATERING:

7. TRENCH BOX:

© 1 PIPE TRENCH DETAIL (TYPICAL)
SCALE: NOT TO SCALE

TYPICAL HDPE END SECTION				
PIPE DIA.	END SECTION DIMENSIONS			
	A	B	C	D
12"	42"	14"	34"	6"
15"	42"	17"	34"	6"
18"	59"	21"	48"	6"
24"	59"	27"	48"	6"
30"	82"	34"	58"	6"
36"	82"	41"	58"	6"



NOTES:

1. SCOPE: THIS SPECIFICATION DESCRIBES 12" THROUGH 36-INCH ADS FLARED END SECTIONS FOR USE IN CULVERT AND DRAINAGE OUTLET APPLICATIONS. FES LARGER THAN 36" SHALL USE CIRCULAR CORRUGATED METAL FLARED END SECTIONS.
2. REQUIREMENTS: THE INVERT OF THE PIPE AND THE END SECTION SHALL BE AT THE SAME ELEVATION. THE ADS FLARED END SECTION SHALL BE HIGH DENSITY POLYETHYLENE MEETING **ASTM D3350** MINIMUM CELL **CLASSIFICATION 213320C**; CONTACT MANUFACTURER FOR ADDITIONAL CELL CLASSIFICATION INFORMATION. WHEN PROVIDED, THE METAL THREADED FASTENING ROD SHALL BE STAINLESS STEEL.
3. INSTALLATION: INSTALLATION SHALL BE IN ACCORDANCE WITH ADS INSTALLATION INSTRUCTIONS AND WITH THOSE ISSUED BY STATE OR LOCAL AUTHORITIES. CONTACT YOUR LOCAL ADS REPRESENTATIVE OR VISIT WWW.ADS-PIPE.COM FOR THE LATEST INSTALLATION INSTRUCTIONS.
4. PROVIDE TRASH RACK ONLY WHERE SPECIFIED ON SITE PLANS.

© 5 TYPICAL END SECTION - HDPE
SCALE: NOT TO SCALE



© 2 PIPE CONNECTION TO DRAINAGE STRUCTURE- CMP OR HDPE CEMENT GROUT SEAL JOINT
SCALE: NOT TO SCALE



NOTE:

1. CASTINGS RATED STANDARD HS20-44 LOADING
2. MATERIAL SHALL CONFORM TO **ASTM A48-CLASS 30B**
3. PAINT: CASTINGS TO BE FURNISHED WITH A BLACK PAINT
4. IN-LINE DRAIN BY NYLOPLAST OR APPROVED EQUIVALENT
5. DRAIN AREA = 62.7 SQ. INCH

© 3 12" IN-LINE DRAIN & GRATE
SCALE: NOT TO SCALE



NOTES:

1. CATCH BASIN SHALL BE PRECAST CONCRETE. DESIGNED FOR HS20-44 VEHICULAR LOADING AND 25% IMPACT.
2. FRAME AND COVER SHALL BE DESIGNED FOR HS20-44 VEHICULAR LOADING & 25% IMPACT.
3. CONCRETE CATCH BASIN CASTING CLEAR OPENING DIMENSION MUST MATCH FRAME AND GRATE CLEAR OPENING DIMENSION.
4. CATCH BASINS HAVING A DEPTH GREATER THAN 48" FROM FINISHED SURFACE TO THE TOP OF THE CONCRETE BASE SHALL BE PROVIDED WITH STEPS.
5. BACKFILL USING TRENCH BACKFILL, COMPACTED IN 6" LIFTS.
6. SUMPS FOR CATCH BASINS SHALL BE 12".
7. **EJ GROUP** GRATE & FRAME **PN#00758535A01** OR EQUIVALENT.



© 7 PRECAST CONCRETE RECTANGULAR CATCH BASIN DETAIL
SCALE: NOT TO SCALE

NOTES:

1. DEPTH OF TRENCH DRAINS VARY. SEE GRADING AND DRAINAGE PLAN FOR DIMENSIONS OF EACH INDIVIDUAL TRENCH DRAIN.
2. ALL GRATES SHALL BE "BICYCLE SAFETY" APPROVED.
3. PROVIDE HORIZONTAL OUTLET END PLATES AT DOWNSTREAM END OF EACH TRENCH DRAIN.

© 4 TRENCH DRAIN DETAIL
SCALE: NOT TO SCALE



NOTES:

1. EMBANKMENT FILL FOR THE STORM WATER BASIN BERM SHALL CONSIST OF A CLEAN WELL GRADED MIXTURE OF SILT, CLAY,SAND AND GRAVEL WITH NO PARTICLES LARGER THAN 6 INCHES. IF SUITABLE, EXCAVATED ON SITE SOILS SHALL BE SELECTIVELY STOCKPILED FOR USE AS EMBANKMENT FILL IN AREAS DESIGNATED BY THE ENGINEER. SOIL SUITABLE FOR USE AS EMBANKMENT FILL SHALL HAVE AT LEAST 40 PERCENT BY WEIGHT FINER THAN THE No. 200 SIEVE AND NO MORE THAN 15 PERCENT BY WEIGHT COARSER THAN THE No. 4 SIEVE. THE FILL SHALL BE FREE OF VEGETATION, ORGANIC MATERIAL AND FROZEN SOIL.
2. ALL AREAS TO BE FILLED SHALL BE FIRST PREPARED BY STRIPPING ALL TOPSOIL AND REMOVING ALL SOFT, WET OR ORGANIC SOIL THAT CANNOT BE COMPACTED BY PROOFROLLING WITH A VIBRATOR ROLLER WEIGHING AT LEAST 10 TONS. PROOFROLLING SHALL BE PERFORMED IN THE PRESENCE OF THE ENGINEER AND SOIL WHICH CANNOT BE COMPACTED SHALL BE REMOVED.
3. ALL FILL SHALL BE PLACED IN LIFTS NOT EXCEEDING 8 INCHES IN THICKNESS WHEN LOOSE AND BE COMPACTED TO A DENSITY OF AT LEAST 95 PERCENT OF THE MAXIMUM DRY DENSITY AS DETERMINED IN ACCORDANCE WITH **ASTM-1557**, ROUGH UP SUBGRADE TO BLEND WITH FIRST LIFT.

© 9 TYPICAL SECTION THRU OVERFLOW WEIR
SCALE: NOT TO SCALE



NOTES:

1. SEE LANDLOCK "INSTALLATION GUIDELINES" FOR EMERGENCY OVERFLOW WEIR EROSION CONTROL INSTALLATION.

© 10 SECTION THRU STORM WATER MANAGEMENT BASIN OVER FLOW WEIR
SCALE: NOT TO SCALE

ACCEPTABLE MANHOLE STEPS

MANUFACTURER	PATTERN NUMBER	"A" STEP WIDTH	"B" LEG LENGTH	"C" RUNG CLEAR	"D" EMBED-MENT	"E" RUNG CLEAR
M.A. INDUSTRIES INC*	**PS2-PF**	14 3/4	9 1/4	13 3/4	3 3/8	5 7/8
M.A. INDUSTRIES INC*	**PS2-PFS**	14 3/4	8 1/4	13 3/4	3 3/8	4 7/8

* OR EQUIVALENT

MH STEP DESIGN AND INSTALLATION SHALL COMPLY WITH ALL OSHA REGULATIONS



© 6 COPOLYMER POLYPROPYLENE MH STEP
SCALE: NOT TO SCALE



NOTES:

1. SIGN SHALL BE ALUMINUM IN ACCORDANCE WITH NYSDOT STANDARD SPECS SECTION 730.
2. SIGN POST SHALL BE IN ACCORDANCE W/ NYSDOT STANDARD SPECS SECTION 730.
3. ANY DAMAGED OR MISSING STORMWATER PRACTICE SIGNS SHALL BE REPLACED BY THE GOVERNING HOA.
4. CONTRACTOR SHALL ERECT SIGN THE IMMEDIATE VICINITY (NOT IN) OF EACH STORMWATER MANAGEMENT PRACTICE.
5. BACKGROUND COLOR OF SIGN SHALL BE MUTCD BROWN, THE LEGEND AND BORDER SHALL BE MUTCD WHITE.
6. LETTERING OF THE SIGN SHALL BE SIZED SO THAT SIGN IS LEGIBLE.
7. NAMES AND SPDES PERMIT NUMBER SHALL BE OBTAINED BY CONTRACTOR FROM PLANS AND ISSUED SPDES CONSTRUCTION PERMIT.

© 8 STORMWATER MANAGEMENT PRACTICE PERMANENT SIGN
SCALE: NOT TO SCALE



SECTION

NOTES:

1. STRUCTURE SHALL BE PRECAST CONCRETE. DESIGNED FOR HS20-44 VEHICULAR LOADING AND 25% IMPACT.
2. FRAME AND COVER SHALL BE DESIGNED FOR HS20-44 VEHICULAR LOADING & 25% IMPACT.
3. CONCRETE CATCH BASIN LID CLEAR OPENING DIMENSION MUST MATCH FRAME AND GRATE CLEAR OPENING DIMENSION.
4. STRUCTURES HAVING A DEPTH GREATER THAN 48" FROM FINISHED SURFACE TO THE FLOOR OF THE CONCRETE BASE SHALL BE PROVIDED WITH STEPS.
5. BACKFILL USING TRENCH BACKFILL, COMPACTED IN 6" LIFTS.
6. SUMPS FOR CATCH BASINS SHALL BE 12".
7. ECCENTRIC CONE TOP CAN BE USED FOR MANHOLES DEPTH GREATER THAN 7 FEET.
8. SEE CHART FOR REQUIRED MANHOLE DIAMETERS.
9. ALL PRECAST CONSTRUCTION IN ACCORDANCE W/**ASTM C478**
10. ALL PRECAST CONCRETE SHALL BE COATED INSIDE AND OUTSIDE (TOP ONLY) WITH A CLEAR POLYMER RESIN.
11. MH #1 IS 6' IN DIAMETER.

© 9 PRECAST CONCRETE MANHOLE - 5' DIAMETER DETAIL
SCALE: NOT TO SCALE

LaBella
Powered by partnership.

21 Fox Street
Poughkeepsie, NY 12601
(845) 454-3980

labellapc.com

It is a violation of New York Education Law Article 145 Sec.7209, for any person, unless acting under the direction of a licensed architect, professional engineer, or land surveyor, to alter an item in any way. If an item bearing the seal of an architect, engineer, or land surveyor is altered; the altering architect, engineer, or land surveyor shall affix to the item their seal and notation "altered by" followed by their signature and date of such alteration, and a specific description of the alteration.

© 2022 LaBella Associates

APPLICANT NAME & ADDRESS:

ARGO DEVELOPMENT
95 CHESTNUT RIDGE ROAD
MONTVALE, NJ 07645

PROJECT NAME & LOCATION:

SOUTH AVE MULTI-FAMILY DEVELOPMENT
SOUTH AVENUE
CITY OF POUGHKEEPSIE, NY 12601

NO:	DATE:	DESCRIPTION:
1	01/27/23	NO CHANGES THIS SHEET
Revisions		

PROJECT NUMBER: 2222201
DRAWN BY:
REVIEWED BY: CPL
ISSUED FOR: PLANNING BOARD REVIEW
DATE: 11/28/2022
DRAWING NAME:

STORM SEWER DETAILS

DRAWING NUMBER:

C550

4/3/2023 12:28:22 PM
B:\GLOBAL\Projects\ARGO\2222201 - South Ave Multi Family Dev\06_Drawings\Civil\01_C550_C551_2222201_STORMD.dwg

Drawing Name: B:\GLOBAL\Projects\ARGO\2222201 - South Ave Multi Family Dev\06_Drawings\Civil\01_C550_C551_2222201_STORMD.dwg
Xref's Attached: XBORDER_2222201; XENG_2222201
Date Printed: Apr 03, 2023, 12:26pm



NOTE:
PRECAST LID TO BE DESIGNED TO WITHSTAND MAX AASHTO HS20-44 TRUCK LOADINGS & 25% IMPACT

MANHOLES:
EJ GROUP
SOLID COVER **PN# 00120329**
8" THK FRAME **PN#00120715**
OR APPROVED EQUAL COVER MUST BE CLEARLY LABELED "STORM SEWER"
LOCATE MANHOLE COVER OPENING DIRECTLY OVER MANHOLE STEPS

CATCH BASINS:
EJ GROUP – 5419M/Z ASSEMBLY
GRATE **PN#00541931**
4 1/2" THK FRAME **PN#00541911**
OR APPROVED EQUAL
LOCATE OPENING FOR FRAME AND GRATE IN CENTER OF PRECAST LID

PLAN



SECTION

NOTES:
1. CATCH BASIN SHALL BE PRECAST CONCRETE. DESIGNED FOR HS20-44 VEHICULAR LOADING AND 25% IMPACT.
2. FRAME AND COVER SHALL BE DESIGNED FOR HS20-44 VEHICULAR LOADING & 25% IMPACT.
3. CONCRETE CATCH BASIN LID CLEAR OPENING DIMENSION MUST MATCH FRAME AND GRATE CLEAR OPENING DIMENSION.
4. CATCH BASINS HAVING A DEPTH GREATER THAN 48" FROM FINISHED SURFACE TO THE FLOOR OF THE CONCRETE BASE SHALL BE PROVIDED WITH STEPS.
5. BACKFILL USING TRENCH BACKFILL, COMPACTED IN 6" LIFTS.
6. SUMPS FOR CATCH BASINS SHALL BE 12".
7. ECCENTRIC CONE TOP CAN BE USED FOR MANHOLES DEPTH GREATER THAN 7 FEET.
8. SEE CHART FOR REQUIRED MANHOLES / CATCH BASINS DIAMETERS.
9. ALL PRECAST CONSTRUCTION IN ACCORDANCE W/**ASTM C478**

© 1 **PRECAST CONCRETE CATCH BASIN/MANHOLE DETAIL**
SCALE: NOT TO SCALE



FRAME AND COVER
(DIAMETER VARIES)
NOT TO SCALE

PLAN VIEW B-B
NOT TO SCALE



ELEVATION A-A
NOT TO SCALE

GENERAL NOTES
1. CONTECH TO PROVIDE ALL MATERIALS UNLESS NOTED OTHERWISE.
2. FOR SITE SPECIFIC DRAWINGS WITH DETAILED STRUCTURE DIMENSIONS AND WEIGHT, PLEASE CONTACT YOUR CONTECH ENGINEERED SOLUTIONS LLC REPRESENTATIVE. www.ContechES.com
3. CASCADE SEPARATOR WATER QUALITY STRUCTURE SHALL BE IN ACCORDANCE WITH ALL DESIGN DATA AND INFORMATION CONTAINED IN THIS DRAWING. CONTRACTOR TO CONFIRM STRUCTURE MEETS REQUIREMENTS OF PROJECT.
4. CASCADE SEPARATOR STRUCTURE SHALL MEET AASHTO HS20 LOAD RATING, ASSUMING EARTH COVER OF 0' - 2' [610], AND GROUNDWATER ELEVATION AT, OR BELOW, THE OUTLET PIPE INVERT ELEVATION. ENGINEER OF RECORD TO CONFIRM ACTUAL GROUNDWATER ELEVATION. CASTINGS SHALL MEET AASHTO M306 AND BE CAST WITH THE CONTECH LOGO.
5. CASCADE SEPARATOR STRUCTURE SHALL BE PRECAST CONCRETE CONFORMING TO ASTM C478 AND AASHTO LOAD FACTOR DESIGN METHOD.
6. ALTERNATE UNITS ARE SHOWN IN MILLIMETERS [mm].

INSTALLATION NOTES
A. ANY SUB-BASE, BACKFILL DEPTH, AND/OR ANTI-FLOTATION PROVISIONS ARE SITE-SPECIFIC DESIGN CONSIDERATIONS AND SHALL BE SPECIFIED BY ENGINEER OF RECORD.
B. CONTRACTOR TO PROVIDE EQUIPMENT WITH SUFFICIENT LIFTING AND REACH CAPACITY TO LIFT AND SET THE CASCADE SEPARATOR MANHOLE STRUCTURE.
C. CONTRACTOR TO INSTALL JOINT SEALANT BETWEEN ALL STRUCTURE SECTIONS AND ASSEMBLE STRUCTURE.
D. CONTRACTOR TO PROVIDE, INSTALL, AND GROUT INLET AND OUTLET PIPE(S). MATCH PIPE INVERTS WITH ELEVATIONS SHOWN. ALL PIPE CENTERLINES TO MATCH PIPE OPENING CENTERLINES.
E. CONTRACTOR TO TAKE APPROPRIATE MEASURES TO ASSURE UNIT IS WATER TIGHT, HOLDING WATER TO FLOWLINE INVERT MINIMUM. IT IS SUGGESTED THAT ALL JOINTS BELOW PIPE INVERTS ARE GROUTED.

© 2 **CONTECH CS-4 HYDRODYNAMIC SEPERATOR**
SCALE: NOT TO SCALE

CO #	TYPE
5,6,7	A
1-4, 8-20	B

NOTES:
1. SEWER PIPE FITTINGS TO BE ASTM D-3033 OR D-3034 SDR-35.
2. TO BE USED FOR GRAVITY PORTION OF SANITARY SYSTEM AS WELL AS THE STORM DRAINAGE SYSTEM.

© 11 **CLEAN OUT - NON TRAFFIC AREA**
SCALE: NOT TO SCALE



© 6 **SUBSURFACE INFILTRATION SYSTEM - PLAN VIEW**
SCALE: NOT TO SCALE



SECTION A-A

© 8 **SUBSURFACE INFILTRATION SYSTEM - SECTION VIEW**
SCALE: NOT TO SCALE

NOTES:
1. PIPE BEDDING MATERIAL SHALL BE COMPOSED OF CRUSHED STONE OR GRAVEL FREE OF SOFT NONDURABLE PARTICLES, ORGANIC MATERIALS AND THIN OR ELONGATED PARTICLES WITH THE FOLLOWING GRADATION REQUIREMENTS:

SIEVE DESIGNATION	% PASSING
3/4"	100
3/8"	95–100
1/4"	0–15
No. 40	0–5

2. ALL CONNECTIONS SHALL BE WATERTIGHT AND PROVIDED TO ENGINEER FOR REVIEW.
3. HEADERS, MAINTENANCE MANHOLE/BARREL CONNECTIONS, INLET/BARREL CONNECTIONS, INLET/MAINTENANCE MANHOLE/ BARREL CONNECTIONS, SHALL BE PRE-FABRICATED BY MANUFACTURER.
4. MAINTENANCE SHALL BE IN ACCORDANCE WITH SWPPP.



SECTION A-A

NOTES:
1. PIPE BEDDING MATERIAL SHALL BE COMPOSED OF CRUSHED STONE OR GRAVEL FREE OF SOFT NONDURABLE PARTICLES, ORGANIC MATERIALS AND THIN OR ELONGATED PARTICLES WITH THE FOLLOWING GRADATION REQUIREMENTS:

SIEVE DESIGNATION	% PASSING
3/4"	100
3/8"	95–100
1/4"	0–15
No. 40	0–5

2. ALL CONNECTIONS SHALL BE WATERTIGHT AND PROVIDED TO ENGINEER FOR REVIEW.
3. HEADERS, MAINTENANCE MANHOLE/BARREL CONNECTIONS, INLET/BARREL CONNECTIONS, INLET/MAINTENANCE MANHOLE/ BARREL CONNECTIONS, SHALL BE PRE-FABRICATED BY MANUFACTURER.
4. MAINTENANCE SHALL BE IN ACCORDANCE WITH SWPPP.

© 9 **SUBSURFACE DETENTION SYSTEM - SECTION VIEW**
SCALE: NOT TO SCALE



© 7 **SUBSURFACE DETENTION SYSTEM - PLAN VIEW**
SCALE: NOT TO SCALE

PLAN



SECTION

MATERIALS SPECIFICATION FOR BIORETENTION

PARAMETERS	SPECIFICATIONS	SIZE	NOTES:
SEEDING SOIL: ERNMX-126 RETENTION BASIN FLOOR SEEDING-LOW MAINTENANCE	SAND 35–60% SILT 30-55% CLAY 10–25%	N/A	USDA SOIL TYPES LOAMY SAND, SANDY LOAM OR LOAM
UNDERDRAIN	PEA GRAVEL: ASTM D 448 ORNAMENTAL STONE: WASHED, COBBLES	PEA GRAVEL: NO 6 STONE: 2"–5"	
GEOTEXTILE	CLASS "C" APPARENT OPENING SIZE (ASTM-D-4751) GRAB TENSILE STRENGTH (ASTM-D-4632) BURST STRENGTH (ASTM-D-4833)	N/A	FOR USE AS NECESSARY BENEATH UNDERDRAINS ONLY
UNDERDRAIN GRAVEL	AASHTO M-43. NO. 67.	0.25" – 0.75"	3/8" PERF. @ 6" O.C. 4 HOLES PER ROW. MINIMUM OF 3" GRAVEL OVER PIES. NOT NECESSARY UNDERNEATH PIPES
UNDERDRAIN PIPING	ASTM D 1785 OR AASHTO M-278	6" RIGID SCHEDULE 40 PVC	3/8" PERF. @ 6" O.C., 4 HOLES PER ROW

© 3 **BIORETENTION DETAIL**
SCALE: NTS

NOTES:
1. BIORETENTION AREA SHALL BE SURROUNDED WITH SILT FENCE BARRIER AND BARRIER SHALL NOT BE REMOVED UNTIL ALL UPSTREAM AREAS ARE STABILIZED.
2. BACK FILLING OF BIORETENTION FACILITY SHALL BE PLACED IN 12" LIFTS.
3. MAIN COLLECTOR PIPE OF THE UNDER DRAIN SYSTEM SHALL BE CONSTRUCTED AT A MINIMUM SLOPE OF 0.5%. OBSERVATION WELLS OR CLEAN OUT PIPES MUST BE PLACED EVERY 1000SF OF SURFACE AREA.
4. BIORETENTION AREA MAY NOT BE CONSTRUCTED UNTIL ALL CONTRIBUTING DRAINAGE AREA HAS BEEN STABILIZED.
5. PIPE SHALL BE SCHEDULE 40 3/8" PERFORATED AT 6" ON CENTER, 4 HOLES PER ROW
6. BASIN FLOOR SEEDING TO BE BIORETENTION BASIN FLOOR MIX APPROVED BY ENGINEER.
7. INSPECT AND REPAIR/REPLACE TREATMENT AREA COMPONENTS AFTER SIGNIFICANT RAIN EVENTS.
8. BIORETENTION AREA SHALL NOT BE USED AS SEDIMENT TRAP. RUNOFF SHALL NOT BE DISCHARGED TO BIORETENTION AREA UNTIL VEGETATIVE COVER IS ESTABLISHED.
9. BIORETENTION AREA 1 SHALLE HAVE A MEDIA DEPTH OF 4.0' AND BIORETENTION AREA 2 SHALL HAVE A MEDIA DEPTH OF 2.5'.



NOTES:
1. DIMENSIONS ARE SUBJECT TO MANUFACTURING TOLERANCES.
2. COMPLETE SHOP DRAWINGS SHALL BE FURNISHED FOR FABRICATION.
3. REINFORCEMENT AND/OR SLIP JOINT MAY BE REQUIRED FOR MANHOLE RISER.
4. STEPS TO EXTEND TO BOTTOM OF CORRUGATED PIPE.

CROSS-SECTION

AN ALUMINUM WARNING PLATE SHALL BE RIVETED OR OTHERWISE PERMANENTLY ATTACHED TO EACH ACCESS COVER. THE PLATE SHALL BE A MINIMUM OF 12"x12" AND SHALL BE ENGRAVED WITH THE FOLLOWING LANGUAGE: "WARNING: CONFINED SPACE – ENTRY PROHIBITED WITHOUT AUTHORIZATION – CALL OWNER FOR APPROVAL TO ACCESS". VENTILATION SHALL CONFORM TO EXISTING LOCAL AND/OR STATE CODES AND AS PER SECTION 6.2.5 OF "RECOMMENDED STANDARDS FOR WATER WORKS LATEST EDITION (TEN STATES STANDARDS)

© 4 **MAINTENANCE MANHOLE DETAIL**
SCALE: NOT TO SCALE



NOTES:
1. THE CONCRETE CAP SHALL BE SIZED AND DESIGNED SO THAT LOADS ARE TRANSMITTED TO THE SOIL AND NOT THE RISER. DESIGN FOR H-20 LOADING.
2. THE CONCRETE CAP SHALL BE SIZED TO PROVIDE AN ADEQUATE BOTTOM AREA BASED ON THE ALLOWABLE BEARING CAPACITY OF THE SOIL.

© 5 **CONCRETE CAP**
SCALE: NOT TO SCALE

LaBella
Powered by partnership.

21 Fox Street
Poughkeepsie, NY 12601
(845) 454-3980

labellapc.com

It is a violation of New York Education Law Article 145 Sec.7209, for any person, unless acting under the direction of a licensed architect, professional engineer, or land surveyor, to alter an item in any way. If an item bearing the seal of an architect, engineer, or land surveyor is altered; the altering architect, engineer, or land surveyor shall affix to the item their seal and notation "altered by" followed by their signature and date of such alteration, and a specific description of the alteration.

© 2022 LaBella Associates

APPLICANT NAME & ADDRESS:

ARGO DEVELOPMENT
95 CHESTNUT RIDGE ROAD
MONTVALE, NJ 07645

PROJECT NAME & LOCATION:

SOUTH AVE MULTI-FAMILY DEVELOPMENT
SOUTH AVENUE
CITY OF POUGHKEEPSIE, NY 12601

NO:	DATE:	DESCRIPTION:
1	01/27/23	NO CHANGES THIS SHEET
Revisions		

PROJECT NUMBER: 2222201
DRAWN BY:
REVIEWED BY: CPL
ISSUED FOR: PLANNING BOARD REVIEW
DATE: 11/28/2022
DRAWING NAME:

STORM SEWER DETAILS

DRAWING NUMBER:

C551

4/3/2023 12:26:46 PM
B:\GLOBAL\Projects\ARGO\2222201 - South Ave Multi Family Dev\06_Drawings\Civil\01_C550_C551_2222201_STORMD.dwg

Drawing Name: B:\GLOBAL\Projects\ARGO\2222201 – South Ave Multi Family Dev\06_Drawings\Civil\01_C550_C551_2222201_STORMD.dwg
Xref's Attached: XBORDER_2222201; XENG_2222201
Date Printed: Apr 03, 2023, 12:26pm



NOTES:
1. WET TAP OF PUBLIC WATER MAIN SHALL BE PERFORMED UNDER THE SUPERVISION OF THE ENGINEER, AND THE AUTHORITY HAVING JURISDICTION.
2. TAPPING SLEEVE AND VALVE SUPPORT SHALL BE COORDINATED WITH THE ENGINEER TO SUIT FIELD CONDITIONS.
3. MINIMUM DISTANCE TO JOINTS, FITTINGS, OR OTHER WET TAPS OR STOPS SHALL BE 3 FEET.
4. VALVE SHALL BE RED TOP AND OPERATING DIRECTION SHALL BE **CLOCKWISE** TO OPEN (TURNING RIGHT).
5. TAPPING SLEEVE SHALL BE SELECTED TO FIT EXISTING PIPE MATERIAL (C.I., D.I., A.C.) AND OUTSIDE DIAMETERS.
6. THRUST BLOCK IS REQUIRED WHERE THE BRANCH OF THE TAPPING SLEEVE DOES NOT HAVE RESTRAINED JOINT.
7. TAPPING SLEEVE, VALVE & VALVE BOX SHALL BE IN ACCORDANCE WITH MUNICIPAL STANDARDS & AS MANUFACTURED BY **(MUELLER, CLOW OR WATEROUS)** OR APPROVED EQUIVALENT.

1 TAPPING SLEEVE AND VALVE DETAIL
SCALE: NOT TO SCALE



NOTES:
1. DITCH WIDTH SHALL EXTEND A MINIMUM OF ONE AND ONE-HALF FT. FROM THE EDGES OF THE TRENCH.
2. REPLACED BASE MATERIAL OVER TRENCH SHALL BE NYSDOT TYPE 2 SUBBASE COMPACTED IN 12" LIFTS.
3. PIPE BEDDING SHALL BE A MINIMUM OF 6" ABOVE AND BELOW PIPE.
4. ALL JOINTS SHALL BE MECHANICALLY SAWED.
5. ALL JOINTS SHALL BE SQUARED TO THE EXISTING EDGE OF CURB AND/OR PAVEMENT, AND TACK COATED PER DETAIL.
6. ROAD SURFACE REPLACEMENT SHALL BE MINIMUM 6" OF ASPHALTIC CONCRETE.
7. BINDER COURSE ASPHALT PAVEMENT TO BE PLACED IN 2 LIFTS.
8. DEMARCATION LAYER TO BE INSTALLED ALONG SIDES AND BOTTOM OF TRENCH FOR ALL PORTIONS ON THE SUBJECT PROPERTY.
9. WHERE THE SURFACE CONDITION IS LANDSCAPED, APPLY A MINIMUM 2-FT DEPTH OF TOPSOIL.

6 CITY OF POUGHKEEPSIE UTILITY TRENCH DETAIL IN PUBLIC ROW OR EASEMENT AREA
SCALE: NOT TO SCALE



REDUCERS
ALL JOINTS WITHIN LENGTH "L" SHALL BE RESTRAINED



HORIZONTAL BENDS
ALL JOINTS WITHIN LENGTH "L" SHALL BE RESTRAINED



DEAD ENDS
ALL JOINTS WITHIN LENGTH "L" SHALL BE RESTRAINED



TEES
ALL JOINTS WITHIN LENGTH "L" SHALL BE RESTRAINED ON THE TEE BRANCH

8 RESTRAINED JOINT PIPE DIAGRAMS
SCALE: NOT TO SCALE



VERTICAL SEPARATION



HORIZONTAL SEPARATION

NOTES:
1. NO DEVIATION IN THE SEPARATION REQUIREMENTS WILL BE PERMITTED WITHOUT THE EXPRESS APPROVAL OF THE NYS HEALTH DEPARTMENT. OFFSETTING OF WATERLINE SHALL BE REQUIRED WHERE SEPARATION DISTANCES CANNOT BE MAINTAINED.
2. WHEN IT IS IMPOSSIBLE TO OBTAIN VERTICAL SEPARATION AS INDICATED ABOVE, BOTH THE WATER MAIN AND THE SEWER MAIN SHALL BE CONSTRUCTED OF MECHANICAL JOINT, DUCTILE IRON PIPE OR PVC WATER WORKS GRADE PRESSURE PIPE FOR 10' EACH SIDE OF CROSSING AND SHALL BE PRESSURE TESTED TO **150psi** TO ASSURE WATER TIGHTNESS.

2 SANITARY/STORM SEWER AND WATERMAIN SEPARATION DETAIL
SCALE: NOT TO SCALE



NOTES:
1. WHEN THE ELEVATION OF THE SEWER CAN NOT BE VARIED TO MEET THE ABOVE REQUIREMENTS, THE WATER MAIN SHALL BE RELOCATED TO PROVIDE THIS REQUIRED SEPARATION.
2. WHEN IT IS IMPOSSIBLE TO OBTAIN VERTICAL SEPARATION AS INDICATED ABOVE, BOTH THE WATER MAIN AND THE SEWER MAIN SHALL BE CONSTRUCTED OF MECHANICAL JOINT DUCTILE IRON PIPE OR PVC WATER WORKS GRADE PRESSURE PIPE FOR 10' EACH SIDE OF CROSSING AND SHALL BE PRESSURE TESTED TO **150psi** TO ASSURE WATER TIGHTNESS.

3 WATERLINE OFFSET DETAIL
SCALE: NOT TO SCALE

SCHEDULE OF JOINT RESTRAINT- (PVC OR POLYWRAPPED DIP) (LENGTH OF PIPE EACH SIDE OF FITTING TO BE RESTRAINED IN FEET "L"															
PIPE SIZE (INCHES)	FITTING TYPE							REDUCER							
	90°	45°	22½°	11¼°	TEE	VALVE	DEAD END	24"	18"	16"	14"	12"	10"	8"	6"	4"
30"	241	100	48	24	202	206	206	72	130	145	159					
24"	196	82	39	20	163	166	166		72	91	108	123	136			
18"	149	62	30	15	122	125	125			26	49	68	85	99		
16"	134	56	27	14	109	112	112				26	48	67	82	95	
14"	118	49	24	12	95	98	98					26	47	64	79	89
12"	102	43	21	11	82	85	85						25	45	62	74
10"	86	36	17	9	68	71	71							25	44	58
8"	71	30	15	7	56	59	59								25	43
6"	54	22	11	6	41	44	44									23
4"	38	16	8	4	28	31	31									

NOTES:
1. THE LENGTH OF PIPE REQUIRING RESTRAINT IS BASED UPON THE FOLLOWING ASSUMPTIONS:
   A. BEDDING TYPE 2 – FLAT BOTTOM TRENCH, BACKFILL LIGHTLY CONSOLIDATED TO CENTER LINE OF PIPE.
   B. SOIL TYPE CLAY 1 – CLAY OF MEDIUM TO LOW PLASTICITY, LL<50, <25% COURSE PARTICLES [CL & CL–ML] :
      CL – INORGANIC CLAYS OF LOW TO MEDIUM PLASTICITY GRAVELY CLAYS, SANDY CLAYS, SILTY CLAYS. LEAN CLAYS
      ML – INORGANIC SILTS, VERY FINE SAND, ROCK FLOUR, SILTY OR CLAYEY FINE SANDS.
   C. PIPE TABLE CALCULATION IS BASED ON PVC OR POLYWRAPPED DIP
   D. DEPTH TO TOP OF PIPE 5'–0" MINIMUM
   E. MAXIMUM OPERATING PRESSURE OF 150 PSI
   F. FACTOR OF SAFETY OF 1.5
2. FOR END PLUGS, USE RESTRAIN PIPE LENGTH GIVEN FOR DEAD END FITTING.
3. THE LENGTH ("L") OF NEW PIPE TO BE RESTRAINED IS THE LENGTH FOR EACH SIDE OF THE FITTING.
4. THE ABOVE INFORMATION WAS PROVIDED USING THE THRUST RESTRAINT PROGRAM ISSUED BY THE DUCTILE IRON PIPE RESEARCH ASSOCIATION (DIPRA) AND IS BASED ON THE ASSUMPTIONS LISTED IN NOTE 1. RESTRAINED LENGTH REQUIREMENTS FOR FIELD CONDITIONS AND PIPE SIZES DIFFERING FROM THOSE LISTED ABOVE SHOULD BE EVALUATED SEPARATELY.
5. RESTRAINED JOINT PIPE AND FITTINGS SHALL BE USED ONLY AS ALLOWED BY THE PROJECT PLANS AND/OR SPECIFICATION. (IF THRUST BLOCKS ARE USED SEE THRUST BLOCK DETAIL)
6. TEE FITTINGS: PIPE SIZE SHOWN FOR THE TEE IS THE SIZE OF THE RUN. THE RESTRAINED LENGTH SHOWN IS FOR THE BRANCH. THE VALUE OF THE RESTRAINED LENGTH ASSUMES THAT THE SIZE OF THE BRANCH IS EQUAL TO OR LESS THAN THE RUN. THE VALUE OF THE Lr=USED IN THE TABLE IS 10 FEET. (Lr= TOTAL LENGTH BETWEEN FIRST JOINTS ON EITHER SIDE OF THE TEE ON THE RUN.)

7 JOINT RESTRAINT SCHEDULE AND NOTES
SCALE: NOT TO SCALE





NOTE:
1. HYDRANT SHALL MEET REQUIREMENTS OF **AWWA C502**.

4 HYDRANT ASSEMBLY DETAIL
SCALE: NOT TO SCALE

NOTES:
1. HYDRANTS SHALL BE AMERICAN DARLING B-62-B (NO EQUIVALENT OR EXCEPTIONS). HYDRANTS SHALL MEET REQUIREMENTS OF **AWWA STANDARD C-502**.
2. HYDRANTS SHALL BE CAST IRON BODY, DRY BARREL DESIGN, COMPRESSION-TYPE VALVE, OPENING AGAINST PRESSURE AND CLOSING WITH PRESSURE, 6-INCH MECHANICAL JOINT INLET FOOT PIECE, 5 ¼ INCH MAIN VALVE OPENING, O-RING TYPE PACKING, RATED FOR 250-PSI WORKING PRESSURE, TWO (2) 2 ½ INCH HOSE NOZZLES AND ONE (1) 4 ½ INCH PUMPER NOZZLE.
3. NOZZLE OUTLET THREADS SHALL MEET LOCAL FIRE DEPARTMENT REQUIREMENTS AND HAVE CAST IRON CAPS WITH NON-KINKING STEEL CHAINS. OPERATING AND CAP NUTS: PENTAGON 1 ½ INCH POINT TO FLAT. HYDRANT VALVES SHALL BE OPENED BY TURNING OPERATING NUT TO THE LEFT, OR **COUNTERCLOCKWISE**.
4. HYDRANTS SHALL BE TRAFFIC TYPE WITH BREAKABLE SAFETY FLANGE WITH RED EXTERIOR ALKYD GLOSS ENAMEL PAINT. HYDRANTS SHALL BE TOUCHED UP TO REMOVE ANY MARKS OR SCRAPED PAINT CAUSED BY INSTALLATION OR TRANSIT.



NOTES:
1. PIPE BEDDING & PIPE ZONE BACKFILL SHALL BE A NATURAL RUN-OF-BANK (R.O.B.) SAND OR A MIXTURE OF CRUSHED STONE AND GRAVEL, FREE OF SOFT, NONDURABLE PARTICLES, ORGANIC MATERIALS AND ELONGATED PARTICLES, AND SHALL BE WELL GRADED FROM FINE TO COARSE PARTICLES. BEDDING GRADATIONS SHALL BE APPROVED BY THE ENGINEER AND SHALL MEET THE FOLLOWING GRADATION REQUIREMENTS:

SIEVE DESIGNATION	% PASSING
3/4"	100%
NO. 40	0–70%
NO. 200	0–10%

2. INSTALL CONTINUOUS DETECTABLE MARKING TAPE DURING BACKFILLING OF TRENCH FOR UNDERGROUND PIPING. LOCATE TAPE 12" BELOW FINISHED GRADE, DIRECTLY OVER PIPING, EXCEPT 6" BELOW SUBGRADE UNDER PAVEMENTS & SLAB.
3. TRENCHING SHALL BE IMPLEMENTED IN ACCORDANCE WITH O.S.H.A. STANDARDS.
4. WIDTH DIFFERS WHERE WATER LINE IS PLACED IN ROCK BELOW FIVE-FEET. REFER TO TECHNICAL SPECIFICATIONS.

5 PIPE TRENCH DETAIL (WATER)
SCALE: NOT TO SCALE

12 RESTRAINED JOINT THRUST RESTRAINT DETAIL
SCALE: NOT TO SCALE



TEE WITH PLUG

REQUIRED BEARING AREAS –B (SQFT) FOR BEARING BLOCKS*

PIPE SIZE (INCHES)	TEE	90° BEND	45° BEND	22 1/2 ° BEND	11 1/4 ° BEND
4	2.0	2.8	1.5	0.8	0.4
6	4.2	5.9	3.2	1.6	0.8
8	7.2	10.1	5.5	2.8	1.4
10	10.9	15.4	8.3	4.2	2.1
12	15.4	21.8	11.8	6.0	3.0
14	20.6	29.1	15.8	8.0	4.0
16	26.8	37.9	20.5	10.4	5.2
18	33.6	47.5	25.7	13.1	6.6
20	41.2	58.2	31.5	16.1	8.1
24	58.8	83.1	45.0	22.9	11.5
30	90.5	128.0	69.2	35.3	17.7
36	129.6	183.3	99.1	50.5	25.4

*FACTOR OF SAFETY=1.5 SOIL BEARING OF 3,000 PSF 225 PSI DESIGN PRESSURE

*BEARING AREA (B) = bxh

NOTES:
1. CONCRETE SHALL NOT TO OVERLAP ANY JOINT.
2. THRUST BLOCKS SHALL BE CONFIGURED IN A MANNER THAT DOES NOT INTERFERE WITH REMOVAL OR INSTALLATION OF ANY JOINTING COMPONENTS.
3. FOR REDUCERS, USE MECHANICAL JOINT FITTINGS WITH RETAINER GLANDS.
4. BEARING SURFACE SHALL, WHERE POSSIBLE, BE PLACED AGAINST UNDISTURBED SOIL. WHERE THAT IS NOT POSSIBLE, THE FILL BETWEEN THE BEARING SURFACE AND UNDISTURBED SOIL MUST BE COMPACTED TO AT LEAST 90% STANDARD PROCTOR DENSITY.
5. BLOCK HEIGHT (h) SHALL BE EQUAL TO OR LESS THAN ONE-HALF THE TOTAL DEPTH TO THE BOTTOM OF THE BLOCK, (HT), BUT NOT LESS THAN THE PIPE DIAMETER (D).
6. BLOCK HEIGHT (h) SHALL BE ESTABLISHED SUCH THAT THE CALCULATED BLOCK WIDTH (b) VARIES BETWEEN ONE AND TWO TIMES THE HEIGHT.
7. VALUES FOR TEES APPLY TO TEES, END PLUGS, CAPS, AND TAPERING SLEEVES.
8. REQUIRED BEARING AREAS ARE DEVELOPED TO RESIST THRUSTS RESULTING FROM 150 PSI WORKING PRESSURE PLUS 50%(75 PSI) SURGE ALLOWANCE RESULTING IN 225 PSI TOTAL INTERNAL PRESSURE. REQUIRED BEARING AREAS ARE BASED UPON AN ALLOWABLE SOIL BEARING CAPACITY OF 3,000 POUNDS PER SQUARE FOOT. IN RESPONSE TO OTHER SOIL CONDITIONS ENCOUNTERED, BEARING AREAS REQUIRED MAY BE MODIFIED BY THE ENGINEER.

SOIL	BEARING STRENGTH Sa (LB/SQ FT)
MUCK	0
SOFT CLAY	1,000
SILT	1,500
SANDY SILT	3,000
SAND	4,000
SANDY CLAY	6,000
HARD CLAY	9,000

9. IN MUCK, PEAT, OR RECENTLY PLACED FILL, ALL THRUSTS SHALL BE RESISTED BY PILES OR TIE RODS TO SOLID FOUNDATIONS, OR BY REMOVAL OF SUCH UNSTABLE MATERIAL AND REPLACEMENT WITH BALLAST OF SUFFICIENT STABILITY TO RESIST THE THRUSTS; ALL AS REQUIRED BY THE ENGINEER.
10. CONCRETE THRUST BLOCK SHALL BE USED ONLY AS ALLOWED BY THE PROJECT PLANS AND/OR SPECIFICATION. (IF RESTRAINED JOINT PIPE IS TO BE USED SEE SCHEDULE OF JOINT RESTRAINED PIPE.)

10 CONCRETE THRUST BLOCK DETAILS
SCALE: NOT TO SCALE

NO. OF TIE RODS REQUIRED

PIPE SIZE INCHES	MIN NO. OF 3/4 "RODS
2	2 [1]
3	2 [1]
4	2
6	2
8	2
10	2
12	2
14	4
16	4
18	6
20	6
24	8
30	14(8) [2]
36	18(12) [2]

NOTES:
1. APPLIES TO 5/8" RODS AS WELL.
2. MIN NO. OF 1" RODS.



RESTRAINED END CAP

RETAINER CLAMPS

ALTERNATE STYLE
AS MANUFACTURED BY **STAR SUPPLY CORP** OR APP EQUAL, HIGH-STRENGTH CORTEN

ANCHORING PIPE

9 JOINT RESTRAINT OPTIONS
SCALE: NOT TO SCALE



NOTES:
1. NON-RISING STEM GATE VALVE, OPERATING DIRECTION SHALL BE CLOCKWISE TO OPEN.
2. MINIMUM DISTANCE TO JOINTS, FITTINGS, OR OTHER WET TAPS OR STOPS SHALL BE 3 FEET.
3. RESTRAIN VALVE WITH MEGALUG CONNECTION.
4. DIRECT BURY VALVE SHALL BE MODEL A-2360 RESILIENT WEDGE GATE VALVE WITH MECHANICAL JOINT ENDS AS MANUFACTURED BY MUELLER CO. OR APPROVED EQUIVALENT. VALVE SHALL COMPLY WITH AWWA C-509 AND NSF/ANSI 61 STANDARDS.
5. VALVE OPERATING DIRECTION SHALL BE CLOCKWISE (TURNING RIGHT).
6. VALVE BOX SHALL BE 2-PIECE SLIDING TYPE WITH 5 ¼" SHAFT EXTENSION SERIES 6850 AS MANUFACTURED BY TYLER/UNION OR APPROVED EQUIVALENT.

11 TYPICAL GATE VALVE DETAIL
SCALE: NOT TO SCALE

GENERAL CONSTRUCTION NOTES:

1. ALL UTILITY WORK INVOLVING CONNECTION TO EXISTING MUNICIPAL WATER MAIN SHALL BE COORDINATED WITH OWNER AND OWNER'S REPRESENTATIVE. NOTIFY OWNER AND THE OWNER'S REPRESENTATIVE 3 WORKING DAYS BEFORE CONNECTION IS MADE.
2. THE CONTRACTOR SHALL VERIFY THE PRESENCE OF AND EXACT LOCATION OF ALL UTILITIES PRIOR TO COMMENCING ANY EXCAVATION WORK AS THE EXACT LOCATION OF UTILITIES MAY DIFFER FROM THE LOCATION SHOWN, AND ADDITIONAL UTILITIES MAY EXIST.
3. THE CONTRACTOR SHALL REVIEW ALL FIELD UTILITY MARKOUT INFORMATION AND BRING ANY CONFLICTS TO THE ATTENTION OF THE PROJECT ENGINEER PRIOR TO COMMENCING ANY WORK OPERATIONS. TEST PITS MAY BE REQUIRED BY THE CONTRACTOR TO VERIFY ACTUAL UTILITY LOCATIONS AND/OR DEPTHS. TEST PIT OPERATIONS WILL MEET ALL NECESSARY REQUIREMENTS AS SET FORTH IN THESE PLANS, DETAILS, FEDERAL/STATE/LOCAL REGULATIONS AND ANY SPECIFIC PERMIT REQUIREMENTS.
4. THE CONTRACTOR SHALL PERFORM EXPLORATORY EXCAVATIONS AT ALL UTILITY CONNECTION LOCATIONS AND AS NEEDED TO VERIFY EXISTING CONDITIONS PRIOR TO PERFORMING WORK. THE CONTRACTOR SHALL NOTIFY THE OWNER AND OWNER'S REPRESENTATIVE 3 WORKING DAYS PRIOR TO SUCH EXCAVATIONS TO ENSURE THEIR PRESENCE.
5. THE CONTRACTOR SHALL EXERCISE CAUTION WHEN EXCAVATING FOR THE PROPOSED STRUCTURES AND WATER LINES AS THE EXACT LOCATION OF UNDERGROUND STRUCTURES AND UTILITIES ARE NOT KNOWN. ANY DAMAGE TO EXISTING STRUCTURES/UTILITIES ABOVE OR BELOW GRADE, CAUSED BY THE CONTRACTOR SHALL BE REPAIRED IMMEDIATELY BY THE CONTRACTOR AT HIS OWN EXPENSE.

LaBella
Powered by partnership.
21 Fox Street
Poughkeepsie, NY 12601
(845) 454-3980
labellapc.com

It is a violation of New York Education Law Article 145 Sec.7209, for any person, unless acting under the direction of a licensed architect, professional engineer, or land surveyor, to alter an item in any way. If an item bearing the seal of an architect, engineer, or land surveyor is altered, the altering architect, engineer, or land surveyor shall affix to the item their seal and notation "altered by" followed by their signature and date of such alteration, and a specific description of the alteration.

© 2022 LaBella Associates

APPLICANT NAME & ADDRESS:
ARGO DEVELOPMENT
95 CHESTNUT RIDGE ROAD
MONTVALE, NJ 07645

PROJECT NAME & LOCATION:
SOUTH AVE MULTI-FAMILY DEVELOPMENT
SOUTH AVENUE
CITY OF POUGHKEEPSIE, NY 12601

NO:	DATE:	DESCRIPTION:
2	03/06/23	REVISED PER PLANNING BOARD COMMENTS
1	01/27/23	NO CHANGES THIS SHEET
Revisions		

PROJECT NUMBER: 2222201
DRAWN BY:
REVIEWED BY: CPL
ISSUED FOR: PLANNING BOARD REVIEW
DATE: 11/28/2022
DRAWING NAME:

WATER SYSTEM DETAILS

DRAWING NUMBER:

C560

4/3/2023 12:28:14 PM
B:\GLOBAL\Projects\ARGO\2222201 - South Ave Multi Family Dev\05_Drawings\Civil\01_C560_2222201_WATRD.dwg

Drawing Name: B:\GLOBAL\Projects\ARGO\2222201 – South Ave Multi Family Dev\06_Drawings\Civil\01_C560_2222201_WATRD.dwg
Xref's Attached: XBORDER_2222201
Date Printed: Apr 03, 2023, 12:28pm



NOTES: USE ONLY WET–CAST UNITS. DRY–CAST NOT ACCEPTABLE

1.

CONE DIMENSIONS	
DIAM. OPENING	HEIGHT
24"	24" OR 42"
30"	34"

2. INVERT SHALL BE FILLETED.
3. REINFORCEMENT FOR MANHOLE COMPONENTS SHALL BE DESIGNED BY A LICENSED NEW YORK STATE PROFESSIONAL ENGINEER PRIOR TO CONSTRUCTION. SHOP DRAWINGS SHALL BE SUBMITTED FOR REVIEW. STRUCTURE SHALL BE DESIGNED FOR HS20–44 VEHICULAR LOADING PLUS 25% IMPACT.
4. CONCRETE TO TEST **4,500 PSI** AT 28 DAYS IN CONFORMANCE WITH **A.S.T.M. C–478.**
5. BENCH SHALL BE BUILT FOR FLOW BETWEEN INLET AND OUTLET.
6. EACH MANHOLE EXTERIOR SHALL RECEIVE TWO BITUMINOUS COATS.

© 1 **PRECAST CONCRETE MANHOLE**
SCALE: NOT TO SCALE

NOTE:
1. FRAME AND COVER SHALL BE DESIGNED FOR HS20–44 VEHICLE LOADING AND 25% IMPACT.

© 5 **HEAVY DUTY STANDARD CAST IRON MH COVER**
SCALE: NOT TO SCALE



NOTE:
INLET AND OUTLET OF PIPES SHOWN ON PLAN VIEW OF BASE ARE NOT NECESSARILY TYPICAL OF ALL MANHOLES. REFER TO UTILITY PLAN FOR INLET AND OUTLET DIRECTIONS.

© 6 **INVERT, CHANNEL AND BENCHWALLS**
SCALE: NOT TO SCALE



FLEXIBLE JOINT & WATERSTOP REQUIREMENTS

SEWER PIPE TYPE	FLEXIBLE JOINT TYPE IN & OUT	"A"DISTANCE (FEET)	"B"DISTANCE (FEET)	MH WATER STOP REQD
DUCTILE IRON	STD RUBBER GASKET PIPE JOINT ONLY	10"MAX	NO LIMIT	YES
PVC	SPECIAL FLEXIBLE JOINT COUPLING	1"MAX	3"MAX	YES

NOTES:
1. THIS DETAIL SHALL BE USED AT NO EXTRA COST IN PLACE OF EITHER OF THE PIPE–TO–MANHOLE CONNECTION DETAILS ONLY WHEN CONNECTING TO EXISTING MANHOLES THAT HAVE NO FLEXIBLE RUBBER BOOT PROVIDED.
2. REFERENCE MANHOLE DETAIL(S) FOR REQUIRED INVERT CHANNEL CONFIGURATION.

© 2 **PIPE CONNECTION TO EXISTING MANHOLE– CEMENT GROUT SEAL WITH WATER STOP**
SCALE: NOT TO SCALE

MANHOLES AND OTHER BELOW GRADE STRUCTURES:

1. STRUCTURAL DESIGN FOR MANHOLES AND OTHER BELOW–GRADE PRECAST CONCRETE STRUCTURES:
A. NON–TRAFFIC LOADS:
BELOW GRADE PRECAST CONCRETE STRUCTURES SHALL BE DESIGNED TO WITHSTAND LOADS IMPOSED BY STRUCTURE WEIGHT, EARTH COVER, LATERAL PRESSURE FROM EARTH AND GROUND WATER, AND LIVE LOADS SUCH AS PEDESTRIAN TRAFFIC OR MACHINERY ON OR ABOVE THE STRUCTURE; AND
B. TRAFFIC LOADS:
BELOW GRADE PRECAST CONCRETE STRUCTURES SHALL BE DESIGNED TO ALSO WITHSTAND TRAFFIC LOADS CREATED BY AN HS20–44 TRUCK PLUS 25% IMPACT AS DEFINED IN THE LATEST EDITION OF THE AMERICAN ASSOCIATION OF STATE HIGHWAY AND TRANSPORTATION OFFICIALS (AASHTO) DESIGN STANDARDS.

2. MATERIAL WHICH SHALL BE UTILIZED IN THE CONSTRUCTION OF PRECAST CONCRETE STRUCTURES:
CEMENT: ASTM C–150, TYPES **I,II,III,V**
SAND: NYSDOT STD. SPEC. **SECTION NO. 703–0** CONCRETE SAND
STONE: NYSDOT STD. SPEC. **SECTION NO. 703–02** COARSE AGGREGATE
STEEL BAR REINFORCEMENT: **ASTM A615**, GRADE 60
WIRE MESH REINFORCEMENT: **ASTM A185** PLAIN
CONCRETE STRENGTH (28 DAY): **4,500** PSI (F'C)
ENTRAINED AIR: 5% MIN.

3. ALL CASTINGS (FRAMES AND COVERS, FRAMES AND GRATES, ETC.) FOR USE IN CONJUNCTION WITH MANHOLES AND OTHER BELOW GRADE STRUCTURES SHALL BE MANUFACTURED FROM GRAY IRON OR DUCTILE IRON. GRAY IRON SHALL CONFORM WITH ASTM A 48, CLASS 30B AND DUCTILE IRON SHALL CONFORM WITH **ASTM A 536** AND BE OF A GRADE APPROPRIATE TO ITS INTENDED USE.

4. ALL CASTINGS (FRAMES AND COVERS, FRAMES AND GRATES, ETC.) FOR USE IN CONJUNCTION WITH MANHOLES AND OTHER BELOW GRADE STRUCTURES SHALL BE DESIGNED TO WITHSTAND AASHTO HS 20–44 HIGHWAY LOADING PLUS 25% IMPACT.

5. ALL ASTM REFERENCES SHALL BE FOR THE LATEST ACTIVE STANDARD.

ACCEPTABLE MANHOLE STEPS

MANUFACTURER	PATTERN NUMBER	"A" STEP WIDTH	"B" LEG LENGTH	"C" RUNG CLEAR	"D" EMBED–MENT	"E" RUNG CLEAR
M.A. INDUSTRIES INC*	**PS2–PF**	14 3/4	9 1/4	13 3/4	3 3/8	5 7/8
M.A. INDUSTRIES INC*	**PS2–PFS**	14 3/4	8 1/4	13 3/4	3 3/8	4 7/8

* OR EQUIVALENT
MH STEP DESIGN AND INSTALLATION SHALL COMPLY WITH ALL OSHA REGULATIONS



© 7 **COPOLYMER POLYPROPYLENE MH STEP**
SCALE: NOT TO SCALE



FLEXIBLE JOINT REQUIREMENTS

SEWER PIPE TYPE	FLEXIBLE JOINT TYPE IN & OUT	"A"DISTANCE (FEET)
DUCTILE IRON	STD RUBBER GASKET PIPE JOINT ONLY	10" MAX
PVC	STD RUBBER GASKET PIPE JOINT ONLY	3" MAX

NOTE:
REFERENCE MANHOLE DETAIL(S) FOR REQUIRED INVERT CHANNEL CONFIGURATION.

© 3 **PIPE CONNECTION TO MANHOLE– PRECAST OR CORED HOLE W/ INSERTED FLEXIBLE BOOT**
SCALE: NOT TO SCALE



MANHOLE INSIDE DIAMETER	SIZE OF BUTYL ROPE JOINT SEALER
4'–0"	1"
5'–0" & LARGER	1 1/2"

© 4 **MANHOLE JOINT**
SCALE: NOT TO SCALE



NOTES:
1. PIPE BEDDING & PIPE ZONE BACKFILL SHALL BE AN IMPORTED NATURAL RUN–OF–BANK (R.O.B.) SAND OR A MIXTURE OF CRUSHED STONE AND GRAVEL, FREE OF SOFT, NONDURABLE PARTICLES, ORGANIC MATERIALS AND ELONGATED PARTICLES, AND SHALL BE WELL GRADED FROM FINE TO COARSE PARTICLES. BEDDING GRADATIONS SHALL BE APPROVED BY THE ENGINEER AND SHALL MEET THE FOLLOWING GRADATION REQUIREMENTS:

SIEVE DESIGNATION	% PASSING
3/4"	100%
NO. 40	0–70%
NO. 200	0–10%

2. TRENCH BACKFILL SHALL BE A NATURAL RUN–OF–BANK (R.O.B.) OR PROCESSED GRAVEL, OR EXCAVATED MATERIAL FREE OF SOFT, NONDURABLE PARTICLES, ORGANIC MATERIALS AND ELONGATED PARTICLES, AND SHALL BE WELL GRADED FROM FINE TO COARSE PARTICLES. TRENCH BACKFILL GRADATIONS SHALL BE APPROVED BY THE ENGINEER AND SHALL MEET THE FOLLOWING GRADATION REQUIREMENTS:

SIEVE DESIGNATION	% PASSING
4"	100%
NO. 40	0–70%
NO. 200	0–10%

IN NON–TRAFFIC UNPAVED AREAS TRENCH BACKFILL CAN BE MATERIALS EXCAVATED FROM THE TRENCH AS APPROVED BY THE ENGINEER AND COMPACTED TO 90% MODIFIED PROCTOR.

3. INSTALL CONTINUOUS DETECTABLE MARKING TAPE DURING BACKFILLING OF TRENCH FOR UNDERGROUND PIPING. LOCATE TAPE 12" BELOW FINISHED GRADE, DIRECTLY OVER PIPING, EXCEPT 6" BELOW SUBGRADE UNDER PAVEMENTS & SLAB.
4. TRENCHING SHALL BE IMPLEMENTED IN ACCORDANCE WITH O.S.H.A. STANDARDS.
5. 5'–0" MIN COVER SHALL BE APPLIED TO WATER MAIN OR SANITARY SEWER FORCE MAINS ONLY.

© 8 **PIPE TRENCH DETAIL (TYPICAL)**
SCALE: NOT TO SCALE



NOTES:
1. DITCH WIDTH SHALL EXTEND A MINIMUM OF ONE AND ONE–HALF FT. FROM THE EDGES OF THE TRENCH.
2. REPLACED BASE MATERIAL OVER TRENCH SHALL BE NYSDOT TYPE 2 SUBBASE COMPACTED IN 12" LIFTS.
3. PIPE BEDDING SHALL BE A MINIMUM OF 6" ABOVE AND BELOW PIPE.
4. ALL JOINTS SHALL BE MECHANICALLY SAWED.
5. ALL JOINTS SHALL BE SQUARED TO THE EXISTING EDGE OF CURB AND/OR PAVEMENT, AND TACK COATED PER DETAIL.
6. ROAD SURFACE REPLACEMENT SHALL BE MINIMUM 6" OF ASPHALTIC CONCRETE.
7. BINDER COURSE ASPHALT PAVEMENT TO BE PLACED IN 2 LIFTS.
8. DEMARCATION LAYER TO BE INSTALLED ALONG SIDES AND BOTTOM OF TRENCH FOR ALL PORTIONS ON THE SUBJECT PROPERTY.
9. WHERE THE SURFACE CONDITION IS LANDSCAPED, APPLY A MINIMUM 2–FT DEPTH OF TOPSOIL.

© 9 **CITY OF POUGHKEEPSIE UTILITY TRENCH DETAIL IN PUBLIC ROW OR EASEMENT AREA**
SCALE: NOT TO SCALE

LaBella
Powered by partnership.
21 Fox Street
Poughkeepsie, NY 12601
(845) 454-3980
labellapc.com

It is a violation of New York Education Law Article 145 Sec.7209, for any person, unless acting under the direction of a licensed architect, professional engineer, or land surveyor, to alter an item in any way. If an item bearing the seal of an architect, engineer, or land surveyor is altered; the altering architect, engineer, or land surveyor shall affix to the item their seal and notation "altered by" followed by their signature and date of such alteration, and a specific description of the alteration.

© 2022 LaBella Associates

APPLICANT NAME & ADDRESS:
ARGO DEVELOPMENT
95 CHESTNUT RIDGE ROAD
MONTVALE, NJ 07645

PROJECT NAME & LOCATION:
SOUTH AVE MULTI-FAMILY DEVELOPMENT
SOUTH AVENUE
CITY OF POUGHKEEPSIE, NY 12601

NO:	DATE:	DESCRIPTION:
2	03/07/23	REVISED PER PLANNING BOARD COMMENTS
1	01/27/23	NO CHANGES THIS SHEET
Revisions		

PROJECT NUMBER: 2222201
DRAWN BY:
REVIEWED BY: CPL
ISSUED FOR: PLANNING BOARD REVIEW
DATE: 11/28/2022
DRAWING NAME:

SANITARY SEWER DETAILS

DRAWING NUMBER:

C570

4/3/2023 12:28:28 PM
B:\GLOBAL\Projects\ARGO\2222201 - South Ave Multi Family Dev\05_Drawings\Civil\01_C570_2222201_SAND.dwg
Drawing Name: B:\GLOBAL\Projects\ARGO\2222201 – South Ave Multi Family Dev\06_Drawings\Civil\01_C570_2222201_SAND.dwg
Xref's Attached: XBORDER_2222201
Date Printed: Apr 03, 2023, 12:28pm



NOTE:
STAKES SHALL BE REMOVED AT THE END OF THE FIRST GROWING SEASON AFTER PLANTING

1 PLANTING AND GUYING DETAILS-FOR TREES SMALLER THAN 3" CALIPER, BALLED AND BURLAPPED

SCALE: NOT TO SCALE



NOTES:
1. SPRAY WITH ANTIDESICCANT IN ACCORDANCE WITH MFG.'S RECOMMENDATIONS.
2. TREES LESS THAN 3" CALIPER SHALL BE STAKED.
3. TREES GREATER THAN 3" CALIPER AND UP SHALL BE GUYED AND ANCHORED.
4. STAKES SHALL BE REMOVED AT THE END OF THE FIRST GROWING SEASON AFTER PLANTING.

2 EVERGREEN PLANTING DETAIL

SCALE: NOT TO SCALE



NOTE:
DETAIL SHALL BE UTILIZED FOR DECIDUOUS AND CONIFEROUS TREE PLANTING ON SLOPE.

3 TREE PLANTING ON SLOPE

SCALE: NOT TO SCALE



NOTE:
SPRAY WITH ANTIDESICCANT IN ACCORDANCE WITH MFG.'S RECOMMENDATIONS IF FOLIAGE IS PRESENT.

4 SHRUB PLANTING DETAIL FOR ALL SHRUBS BALLED AND BURLAPPED

SCALE: NOT TO SCALE

NOTE:
SPRAY WITH ANTIDESICCANT IN ACCORDANCE WITH MFG.'S RECOMMENDATIONS IF FOLIAGE IS PRESENT.

5 SHRUB PLANTING DETAIL FOR CONTAINERIZED SHRUBS

SCALE: NOT TO SCALE



SECTIONAL ELEVATION

NOTES:
1. SPADED PLANTING SOIL MIX (4"–6" DEPTH), ADD FERTILIZER WHEN MIXING. DO NOT COMPACT AFTER PLANTING.
2. WATER THOROUGHLY AFTER PLANTING.
3. PROVIDE WELL DRAINING SUBSOIL WHEN SOIL IS HEAVY OR COMPACTED.
4. PLANTS SHALL BE REMOVED FROM ALL CONTAINERS WHEN PLANTED, UNLESS OTHERWISE STATED IN THE PLANT SCHEDULE.

6 CONTAINERIZED PERENNIAL PLANTING

SCALE: NOT TO SCALE



NOTE:
GROUND COVERS SHOULD BE POT OR CONTAINER GROWN.

7 GROUND COVER & ANNUAL PLUG PLANTING

SCALE: NOT TO SCALE



NOTES:
1. 16'–0" SECTIONS TO INCLUDE FIVE (5) 12" STAKES
2. 8'–0" SECTIONS TO INCLUDE THREE (3) 12" STAKES
3. COMPACT GRADES ADJACENT TO EDGING TO MINIMIZE SETTLING
4. CORNERS – CUT BASE OF EDGING HALF WAY AND FORM A CONTINUOUS CORNER.

8 LANDSCAPE BED EDGING

SCALE: NOT TO SCALE



LIGHT POLE FOUNDATIONS				
POLE HEIGHT	DIAM.	DEPTH*	REINF BARS	TIES
≤15'	18"	5'–0"	(6)#6	#3@18"
25'	24"	5'–0"	(6)#6	#3@12"
30'	24"	5'–6"	(6)#6	#3@12"
35'	24"	6'–0"	(6)#6	#3@12"
40'	24"	6'–0"	(6)#6	#3@12"
50'	24"	7'–0"	(6)#8	#3@12"

NOTES:
1. CONDUITS AND GROUNDING SHALL BE AS REQUIRED BY THE ELECTRICAL DESIGN.
2. ALL CONCRETE SHALL BE **4,500 PSI** @ 28 DAYS.
3. ALL REINFORCING STEEL SHALL BE GRADE 60.
4. DESIGNED FOR **90 MPH** WIND WITH FIXTURE AREA OF **13 SF.**
5. FOUNDATION DIAMETER AND REINFORCING CIRCLE SHALL BE COORDINATED WITH ANCHOR BOLT LIMITS.
6.
7. FOUNDATIONS SHALL BE AUGGERED INTO UNDISTURBED NATURAL SOIL OR COMPACTED FILL PER SITE GRADING PLANS.

* DEPTH OF FOUNDATION BELOW GRADE

9 / C580 **CONCRETE BASE FOR LIGHT POLE**

SCALE: N.T.S.

LANDSCAPING NOTES:

1. THE LANDSCAPE CONTRACTOR SHALL CAREFULLY COORDINATE CONSTRUCTION ACTIVITIES WITH THAT OF THE EARTHWORK CONTRACTOR AND OTHER SITE DEVELOPMENT.
2. THE CONTRACTOR SHALL VERIFY DRAWING DIMENSIONS WITH ACTUAL FIELD CONDITIONS AND INSPECT RELATED WORK AND ADJACENT SURFACES. THE CONTRACTOR SHALL VERIFY THE ACCURACY OF ALL FINISH GRADES WITHIN THE WORK AREA. THE CONTRACTOR SHALL REPORT TO THE LANDSCAPE ARCHITECT/ENGINEER AND OWNER ALL CONDITIONS WHICH PREVENT PROPER EXECUTION OF THIS WORK.
3. THE EXACT LOCATION OF ALL EXISTING UTILITIES, STRUCTURES AND UNDERGROUND UTILITIES, WHICH MAY NOT BE INDICATED ON THE DRAWINGS, SHALL BE DETERMINED BY THE CONTRACTOR. THE CONTRACTOR SHALL PROTECT EXISTING STRUCTURES AND UTILITY SERVICES AND IS RESPONSIBLE FOR THEIR REPLACEMENT IF DAMAGED.
4. THE CONTRACTOR SHALL KEEP THE PREMISES FREE FROM RUBBISH AND ALL DEBRIS AT ALL TIMES AND SHALL ARRANGE MATERIAL STORAGE SO AS NOT TO INTERFERE WITH THE OPERATION OF THE PROJECT. ALL UNUSED MATERIALS, RUBBISH AND DEBRIS SHALL BE REMOVED FROM THE SITE.
5. NO TREES OR SHRUBS SHALL BE PLANTED ON EXISTING OR PROPOSED UTILITY LINES.
6. QUALITY ASSURANCE:
   A. NOMENCLATURE: PLANT NAMES SHALL CONFORM TO THE LATEST EDITION OF "STANDARDIZED PLANT NAMES" AS ADOPTED BY THE AMERICAN JOINT COMMITTEE ON HORTICULTURAL NOMENCLATURE.
   B. SIZE AND GRADING: PLANT SIZES AND GRADING SHALL CONFORM TO THE LATEST EDITION OF "AMERICAN STANDARD FOR NURSERY STOCK" AS SPONSORED BY THE AMERICAN ASSOCIATION OF NURSERYMEN, INC (AAN), UNLESS OTHERWISE SPECIFIED.
   C. NURSERY SOURCE: OBTAIN FRESHLY DUG, HEALTHY, VIGOROUS PLANTS NURSERY GROWN UNDER CLIMACTIC CONDITIONS SIMILAR TO THOSE IN THE LOCALITY OF THE PROJECT FOR A MINIMUM OF 2 YEARS. PLANTS SHALL HAVE BEEN LINED OUT IN ROWS, ANNUALLY CULTIVATED, SPRAYED, PRUNED AND FERTILIZED IN ACCORDANCE WITH GOOD HORTICULTURAL PRACTICE. ALL PLANTS SHALL HAVE BEEN TRANSPLANTED OR ROOT PRUNED AT LEAST ONCE IN THE PAST 3 YEARS. BALLED AND BURLAPPED PLANTS MUST COME FROM SOIL WHICH WILL HOLD A FIRM ROOT BALL. HEELED IN PLANTS AND PLANTS FROM COLD STORAGE ARE NOT ACCEPTABLE.
   D. SUBSTITUTIONS: DO NOT MAKE SUBSTITUTIONS OF TREES AND/OR SHRUB MATERIALS. IF REQUIRED LANDSCAPE MATERIAL IS NOT OBTAINABLE, SUBMIT PROOF OF NON–AVAILABILITY AND PROPOSAL FOR USE OF EQUIVALENT MATERIAL. WHEN AUTHORIZED, ADJUSTMENTS OF CONTRACT AMOUNT (IF ANY) WILL BE MADE BY CHANGE ORDER.
7. SEEDING & PLANTING SEASONS AND TIMING CONDITIONS:
   A. UNLESS OTHERWISE DIRECTED IN WRITING, SEED LAWNS FROM MARCH 15 TO JUNE 15, AND FROM AUGUST 15 TO OCTOBER 15.
   B. UNLESS OTHERWISE DIRECTED IN WRITING PLANT TREES AND SHRUBS FROM MARCH 15 TO JUNE 1, AND FROM AUGUST 15 TO OCTOBER 30.
   C. AREAS UNDERGOING CLEARING OR GRADING AND ANY AREAS DISTURBED BY CONSTRUCTION ACTIVITIES WHERE LAWNS OR PLANTINGS ARE TO BE ESTABLISHED AND WORK IS COMPLETE, SHALL BE RESTORED WITH PERMANENT VEGETATIVE COVER AS SOON AS SITE AREAS ARE AVAILABLE AND WITHIN 14 DAYS AFTER WORK IS COMPLETE; WORK SHALL BE WITHIN THE SEASONAL LIMITATIONS FOR EACH KIND OF LANDSCAPE WORK REQUIRED. PROVIDE STABILIZATION WITH TEMPORARY VEGETATIVE COVER (TOPSOIL AND TEMPORARY COVER SEED MIX) WITHIN 14 DAYS AFTER WORK IS COMPLETE, FOR SEEDING OUTSIDE PERMITTED SEEDING PERIODS.
8. PRODUCTS:
   A. IMPORTED TOPSOIL: PROVIDE TOPSOIL CONFORMING TO THE FOLLOWING:
      i. LOAM TOPSOIL, WELL DRAINED HOMOGENEOUS TEXTURE AND OF UNIFORM GRADE, WITHOUT THE ADMIXTURE OF SUBSOIL MATERIAL AND FREE OF DENSE MATERIAL, HARDPAN, CLAY, STONES, SOD OR OTHER OBJECTIONABLE MATERIAL.
      ii. CONTAINING NOT LESS THAN 5% NOR MORE THAN 20% ORGANIC MATTER IN THAT PORTION OF A SAMPLING PASSING A 1/4" SIEVE WHEN DETERMINED BY THE WET COMBUSTION METHOD ON A SAMPLE DRIED AT 105°C.
      iii. CONTAINING A PH VALUE WITHIN THE RANGE OF 6.5 TO 7.5 ON THAT PORTION OF THE SAMPLE WHICH PASSES A 1/4" SIEVE.
      iv. CONTAINING THE FOLLOWING WASHED GRADATIONS:

SIEVE DESIGNATION	% PASSING
1"	100
1/4"	97–100
NO 200	20–60

   B. SEED MIXTURE:
      PROVIDE FRESH, CLEAN, NEW–CROP SEED MIXED IN THE PROPORTIONS SPECIFIED FOR SPECIES AND VARIETY, AND CONFORMING TO FEDERAL AND STATE STANDARDS. PROVIDE THE FOLLOWING MIXTURES:
      i. LAWN SEED MIX

SUN AND PARTIAL SHADE:

AMOUNT BY: WEIGHT	SPECIES OR VARIETY	MINIMUM % PURITY	MINIMUM % GERMINATION
50%	KENTUCKY BLUE GRASS*	95%	80%
20%	PERENNIAL RYE	98%	90%
30%	CREEPING RED FESCUE	97%	85%
100%			

*MINIMUM 2 (EQUAL PROPORTIONS) VARIETIES AS LISTED IN CORNELL RECOMMENDATIONS FOR TURFGRASS.

SHADE:

AMOUNT BY: WEIGHT	SPECIES OR VARIETY	MINIMUM % PURITY	MINIMUM % GERMINATION
25%	KENTUCKY BLUE GRASS**	95%	80%
20%	PERENNIAL RYE	98%	90%
35%	CREEPING RED FESCUE	97%	85%
20%	CHEWINGS RED FESCUE	97%	85%
100%			

**SHADE TOLERANT VARIETY

      ii TEMPORARY COVER SEED MIX

AMOUNT BY: WEIGHT	SPECIES OR VARIETY	MINIMUM % PURITY	MINIMUM % GERMINATION
100%	ANNUAL RYEGRASS	98%	90%

   C. LIME: NATURAL LIMESTONE CONTAINING AT LEAST 85% OF TOTAL CARBONATES, GROUND TO SUCH FINENESS THAT AT LEAST 90% PASSES A 10–MESH SIEVE AND AT LEAST 50% PASSES A 100–MESH SIEVE.
   D. FERTILIZER:
      i. FOR STARTER FERTILIZING: COMMERCIAL STARTER FERTILIZER, GRANULAR, NONBURNING PRODUCT CONTAINING 5% NITROGEN, 10% AVAILABLE PHOSPHOROUS, AND 5% WATER SOLUABLE POTASH (5–10–5).
      ii. FOR FINAL FERTILIZING: IF APPLIED IN SPRING SEASON, SHALL BE A SLOW RELEASE COMMERCIAL FERTILIZER, GRANULAR, WITH 3–1–2 NPK. IF APPLIED IN FALL SEASON, SHALL BE AS SPECIFIED IN (8.D.i) ABOVE.
   E. TREES, SHRUBS, GROUND COVERS, PERENNIALS, ANNUALS:
      i. PLANTING SOIL MIXTURE: SHALL BE PREMIXED IN BULK, AND CONTAIN THE FOLLOWING BY VOLUME:
         30 PARTS TOPSOIL
         10 PARTS PEAT
         1 PART BONE MEAL
      ii. PEAT: BROWN TO BLACK IN COLOR, WEED AND SEED FREE. DRIED SPHAGNUM PEAT, CONTAINING NOT MORE THAN 9% MINERAL ON A DRY BASIS AND CONFORMING TO NYSDOT 713–15.
      iii. BONE MEAL: FINELY GROUND, RAW, MINIMUM 4% NITROGEN AND 20% PHOSPHORIC ACID. IT SHALL BE DELIVERED IN SEALED BAGS SHOWING THE MANUFACTURER'S GUARANTEED ANALYSIS.
   F. STAKES: 8 FEET LONG, 3 INCH DIA. CEDAR OR P.T. WOOD STAKES.
   G. HOSE: NEW, 2–PLY GARDEN HOSE NOT LESS THAN 1/2 INCH IN DIAMETER.
   H. WEED CONTROL FABRIC: SOIL CHECK AS MANUFACTURED BY BRIGHTON BYPRODUCTS CO. INC, NEW BRIGHTON, PA; MIRASCAPE OR MIRAFI GEOSYNTHETIC PRODUCTS, NORCROSS, PA, OR APPROVED EQUIVALENT.
   I. MULCH:
      i. LAWN AREAS
         OAT OR WHEAT STRAW, FREE OF WEEDS. AN ALTERNATIVE IS WOOD FIBER CELLULOSE IF HYDROSEEDING IS USED.
      ii. PLANT BED AREAS
         GROUND OR SHREDDED HARDWOOD BARK, UNCOLORED. NO PIECES OVER 2 INCHES GREATEST DIMENSION. FREE FROM SAWDUST.
9. EXECUTION:
   A. LANDSCAPE WORK SHALL BE UNDERTAKEN AS SOON AS SITE AREAS ARE AVAILABLE.
   B. TOPSOIL SHALL BE SPREAD NO LESS THAN 4" OVER SUB–GRADE MATERIAL SOIL AMENDMENTS SHALL BE THOROUGHLY MIXED INTO THE TOP 4" OF TOPSOIL, FOLLOWING THE SPECIFICATIONS STATED BELOW.
   C. PERFORM FINE GRADING TO FINISHED ELEVATION ONLY IMMEDIATELY PRIOR TO PLANTING. PLANTING AREAS SHALL BE GRADED TO A SMOOTH, EVEN SURFACE, FREE OF DEPRESSIONS OR RIDGES WITH A UNIFORM LOOSE, FINE TEXTURE.
   D. FERTILIZING:
      i. THE SOIL SHALL BE TESTED FOR PH AND LIME ADDED AS NECESSARY. ALL AMENDMENTS SHALL BE CHECKED AND APPROVED BY LANDSCAPE ARCHITECT BEFORE AMENDMENTS ARE MADE.
      ii. APPLY FERTILIZER AT RATE OF 4 LBS/1000 SF FOR LAWN AREAS.
   E. LAWN:
      i. LAWN SEED MIX: SEED AT THE RATE OF 5 TO 6 LBS PER 1,000 SF.
      ii. TEMPORARY COVER SEED MIX: SEED AT THE RATE OF 3 TO 4 LBS PER 1,000 SF.
      iii. TEMPORARY COVER SEED MIX TO BE APPLIED ONLY FOR LATE FALL OR SUMMER SOIL STABILIZATION OUTSIDE ALLOWED SEEDING PERIODS.
   F. ALL SEEDED AREAS SHALL BE PROTECTED FROM EROSION BY ONE OF THE FOLLOWING METHODS:
      i. A UNIFORM BLANKET OF STRAW APPLIED AT A RATE OF 2 TONS/ACRE MIN, TO BE APPLIED ONCE SEEDING IS COMPLETE.
      ii. WOOD FIBER CELLULOSE APPLIED WITH SEED MIX BY A HYDROSEEDER AT A RATE OF 2,000 LBS/ACRE.
   G. ALL SEEDED SLOPES 3:1 OR GREATER SHALL BE PROTECTED FROM EROSION WITH JUTE MESH OR APPROVED EQUAL.
   H. ALL NEWLY PLANTED AREAS SHALL BE KEPT MOIST BY WATERING UNTIL GRASSES AND GROUND COVERS ARE WELL ESTABLISHED. THE LANDSCAPE CONTRACTOR MUST WATER PLANT MATERIAL WHEN NECESSARY FOR 60 DAYS AFTER INSTALLATION.
   I. LAWNS ARE TO BE WARRANTED UNTIL THEY BECOME ESTABLISHED, UNTIL FINAL ACCEPTANCE, AND NOT LESS THAN 60 DAYS AFTER COMPLETION OF ALL WORK. TREES, SHRUBS, GROUND COVERS, AND PERENNIALS SHALL BE WARRANTED AGAINST DEFECTS INCLUDING POOR GROWTH AND DEATH, EXCEPT WHEN RESULTING FROM OWNER NEGLECT, INCIDENTS THAT ARE BEYOND THE CONTROL OF THE LANDSCAPE INSTALLER AND DAMAGE OR ABUSE BY OTHERS, FOR AT LEAST ONE FULL YEAR AFTER PROJECT COMPLETION.

LaBella
Powered by partnership.
21 Fox Street
Poughkeepsie, NY 12601
(845) 454-3980
labellapc.com

It is a violation of New York Education Law Article 145 Sec.7209, for any person, unless acting under the direction of a licensed architect, professional engineer, or land surveyor, to alter an item in any way. If an item bearing the seal of an architect, engineer, or land surveyor is altered; the altering architect, engineer, or land surveyor shall affix to the item their seal and notation "altered by" followed by their signature and date of such alteration, and a specific description of the alteration.

© 2022 LaBella Associates

APPLICANT NAME & ADDRESS:

ARGO DEVELOPMENT
95 CHESTNUT RIDGE ROAD
MONTVALE, NJ 07645

PROJECT NAME & LOCATION:

SOUTH AVE MULTI-FAMILY DEVELOPMENT
SOUTH AVENUE
CITY OF POUGHKEEPSIE, NY 12601

NO:	DATE:	DESCRIPTION:
2	03/07/23	REVISED PER PLANNING BOARD COMMENTS
1	01/27/23	NO CHANGES THIS SHEET
Revisions		

PROJECT NUMBER: 2222201
DRAWN BY:
REVIEWED BY: CPL
ISSUED FOR: PLANNING BOARD REVIEW
DATE: 11/28/2022
DRAWING NAME:

LANDSCAPE DETAILS

DRAWING NUMBER:

C580

4/3/2023 12:29:04 PM
B:\GLOBAL\Projects\ARGO\2222201 - South Ave Multi Family Dev\06_Drawings\Civil\01_C580_2222201_LANDSCD.dwg

Drawing Name: B:\GLOBAL\Projects\ARGO\2222201 – South Ave Multi Family Dev\06_Drawings\Civil\01_C580_2222201_LANDSCD.dwg
Xref's Attached: XBORDER_2222201
Date Printed: Apr 03, 2023, 12:29pm

SOUTH AVENUE MULTI-FAMILY DEVELOPMENT

4.4.23
22054

ARGO CONSTRUCTION AND DEVELOPMENT

LISCUM McCORMACK VANVOORHIS
ARCHITECTS PLANNERS INTERIORS
181 CHURCH STREET
POUGHKEEPSIE NY 12601

SOUTH AVENUE MULTI-FAMILY DEVELOPMENT

EAST (SOUTH AVENUE) ELEVATION



SOUTH AVENUE SECTION

SOUTH ELEVATION

NORTHWEST ELEVATION

WEST (INTERIOR COURTYARD) ELEVATION

NORTHWEST (INTERIOR COURTYARD) ELEVATION



NORTH ELEVATION

0 8' 16' 32'

SCALE: 1/16" = 1'-0"

3.7.23
22054

ARGO CONSTRUCTION AND DEVELOPMENT

VANVOORHIS

LISCUM McCORMACK VANVOORHIS
ARCHITECTS PLANNERS INTERIORS 181 CHURCH STREET POUGHKEEPSIE NY 12601

SOUTH AVENUE MULTI-FAMILY DEVELOPMENT

4.4.23
22054

ARGO CONSTRUCTION AND DEVELOPMENT

LISCUM McCORMACK VANVOORHIS
ARCHITECTS PLANNERS INTERIORS 181 CHURCH STREET POUGHKEEPSIE NY 12601

New York State
Parks, Recreation and
Historic Preservation

KATHY HOCHUL
Governor

ERIK KULLESEID
Commissioner

February 28, 2023

Brittany Micheline
LaBella Associates
21 Fox Street
Poughkeepsie, NY 12480

Re: DEC
South Avenue Multi-Family Development
City of Poughkeepsie, Dutchess County, NY
23PR00880

Dear Brittany Micheline:

Thank you for requesting the comments of the Office of Parks, Recreation and Historic Preservation (OPRHP). We have reviewed the project in accordance with the New York State Historic Preservation Act of 1980 (Section 14.09 of the New York Parks, Recreation and Historic Preservation Law). These comments are those of the OPRHP and relate only to Historic/Cultural resources. They do not include potential environmental impacts to New York State Parkland that may be involved in or near your project. Such impacts must be considered as part of the environmental review of the project pursuant to the State Environmental Quality Review Act (New York Environmental Conservation Law Article 8) and its implementing regulations (6 NYCRR Part 617).

Based upon this review, it is the opinion of OPRHP that no properties, including archaeological and/or historic resources, listed in or eligible for the New York State and National Registers of Historic Places will be impacted by this project.

If further correspondence is required regarding this project, please be sure to refer to the OPRHP Project Review (PR) number noted above.

Sincerely,

R. Daniel Mackay

Deputy Commissioner for Historic Preservation
Division for Historic Preservation

rev: J. Carter

Full Environmental Assessment Form

South Avenue Multi-Family Development
South Avenue
City of Poughkeepsie
Dutchess County, New York

Issued: November 29, 2022
Revised: January 27, 2023

Prepared for:
ARGO Development
95 Chestnut Ridge Road
Montvale, NJ 07645

Prepared by:
LaBella Associates
21 Fox Street Suite 201
Poughkeepsie, NY 12601
845-486-1541

LaBella Project No. 2222201

TABLE OF CONTENTS

1.0 PROJECT DESCRIPTION 1
1.1 Introduction 1
1.2 Approvals, Consultations and Referrals 1

2.0 ENVIRONMENTAL ASSESSMENT 1
2.1 Land Use, Zoning and Public Policy 1
2.1.1 Land Use 1
2.1.2 Zoning 2
2.1.3 Public Policy 2
2.2 Utilities 2
2.3 Soils and Water Resources 3
2.3.1 Soils 3
2.3.2 Surface Water Resources and Floodplains 3
2.4 Vegetation and Wildlife 3
2.5 Historic and Archaeological Resources 4
2.6 Environmental Contamination 4
2.7 Traffic and Parking 6
2.7.1 Traffic 6
2.7.2 Parking 7

FULL ENVIRONMENTAL ASSESSMENT FORM, PART 1

FIGURES

Figure 1: USGS Location Map
Figure 2: Orthophoto Tax Map
Figure 3: Land Use Map
Figure 4: Soils Map
Figure 5: Wetlands and Streams Map
Figure 6: DEC Environmental Resources Map
Figure 7: CRIS Map
Figure 8: Scenic Resources Map

ATTACHMENTS

Attachment A - United States Fish and Wildlife Service (USFWS) Informal Species List

Site Plan Set will be submitted separately

1.0 PROJECT DESCRIPTION

1.1 Introduction

The Applicant, ARGO Development is seeking site plan approval from the City of Poughkeepsie, to develop an 87-unit, mid-rise multifamily residential development with underground and surface-level parking. The proposed action will be located on an approximately 2.76-acre parcel on the west side of South Avenue (Tax Lot 937583) in the City of Poughkeepsie. The proposed action includes construction of a five-story building with 87, one-bedroom, apartments located over one level of underground parking (60 spaces), and 56 off-street surface parking spaces (115 total parking spaces). The parcel is currently a wooded lot. The parcel is located within the R-D, Research and Development District. Residential development is a permitted use within the R-D zone, subject to the requirements of the High-Density R-5 District Permitted Uses [Section 19-3.16(2)], and further subject to all other requirements applicable to High-Density R-5 District residential development. An area variance to allow 115 parking spaces where 130 parking spaces are required is being sought from the Zoning Board of Appeals. Primary access will be provided via South Avenue. Municipal water and sanitary sewer are available in South Road. The proposed ground disturbance is approximately 2.5 acres. Since the site will have more than 1 acre of ground disturbance, the proposed action will also require a SPDES General Permit for stormwater.

1.2 Approvals, Consultations and Referrals

The following approvals are required for the implementation of the proposed project:

1. City of Poughkeepsie Planning Board - Site Plan Approval
2. City of Poughkeepsie Zoning Board of Appeals - Area Variance (Parking)
3. City of Poughkeepsie Department of Public Works (DPW) – Highway Work Permit; Water and Sewer Connections
4. Dutchess County Planning Board – GML 239-m referral
5. NYS Department of Environmental Conservation (NYSDEC) – State Pollutant Discharge Elimination System (SPDES) General Permit GP-0-20-001
6. NYS Department of Transportation (NYSDOT) - Drainage Connection
7. NYS Office of Parks, Recreation, and Historic Preservation (OPRHP) – SHPO Consult

2.0 ENVIRONMENTAL ASSESSMENT

2.1 Land Use, Zoning and Public Policy

2.1.1 Land Use

The project site is located in the Research and Development District (R&D). The land uses located within 1,000 feet of the project site are characterized by commercial (office buildings

with associated parking), vacant (wooded areas), public services (Central Hudson Gas & Electric), and single-family residential properties (see Figure 3).

The proposed use, as an 87-unit, mid-rise multifamily residential development with underground and surface-level parking, is a permitted use within the R&D zone, subject to the requirements of the High-Density R-5 District Permitted Uses [Section 19-3.16(2)],798 and further subject to all other requirements applicable to High-Density R-5 District residential development.

The proposed use is permitted and will be consistent with the mixed land use character of the area.

2.1.2 Zoning

In the City of Poughkeepsie, the project site is located within the R&D zoning district. Residential development is classified as a permitted use within the R-D zone, subject to the requirements of the High-Density R-5 District Permitted Uses and all other requirements applicable to High-Density R-5 District residential development. Per ZS 19-3.16(2)(a)(4), multifamily dwellings are classified as permitted uses within the R-5 District. The proposed project requires an area variance to allow 115 parking spaces, where 130 parking spaces are required.

2.1.3 Public Policy

The 2022 City of Poughkeepsie Comprehensive Plan, PK4 Keeps, discusses expanding access to good and affordable housing opportunities, strengthening civic life and commercial vitality, as well as improving residential quality of life, as three of five chosen priorities for the City. The Comprehensive Plan classifies the project site as within the Type 2 residential block type. Goals for this block type include a combination of condition stabilization and inclusive reinvestment that leverages the presence of stronger properties and community assets. The proposed multifamily development will signify reinvestment in the South Avenue community and will revitalize the immediate area. The Comprehensive Plan also classifies the project site as within a five-minute walkshed area, thus creating convenience and accessibility to commercial uses in the immediate vicinity.

2.2 Utilities

The proposed project will involve greater than one acre of ground disturbance; therefore, coverage under the State Pollutant Discharge Elimination System (SPDES) General Permit for Stormwater Discharges from Construction Activities will be sought. A Stormwater Pollution Prevention Plan (SWPPP) will be prepared in conformance with the most current New York State Stormwater Management Design Manual and New York State Standards and Specifications for Erosion and Sediment Control.

Municipal water and sanitary sewer are available, and the project is proposed to connect to water and sewer infrastructure within South Road. The Applicant will coordinate with the City of Poughkeepsie Department of Public Works for water and sewer connections.

A drainage connection will be made to the NYSDOT drainage system on the southern side of the property.

2.3 Soils and Water Resources

2.3.1 Soils

The following table provides the soil characteristics for each soil type expected to be found on the project site, according to the USDA Natural Resources Conservation Service website (see Figure 4). Groundwater encountered during the construction will be pumped from the open excavations and discharged to approved sediment trapping devices in accordance with NYSDEC guidelines.

Table 1: Characteristics of Anticipated Soil Types within Project Site

% of SITE	SOIL SYMBOL	SOIL TYPE	FARMLAND CLASSIFICATION	SLOPES	DRAINAGE	DEPTH TO WATER TABLE	DEPTH TO BEDROCK
98.2	Ud	Udorthents, smoothed	Not prime farmland	0-8%	Well drained	~36 to 72 inches	>80 inches
1.8	Ur	Urban Land	Not prime farmland				

2.3.2 Surface Water Resources and Floodplains

According to NYSDEC Wetland and Stream information available through GIS (Figure 5), the EAF Mapper, and National Wetland Inventory mapping, there are no wetlands or other waterbodies on or near the project site.

Therefore, the proposed project will not result in any adverse impacts to wetlands or streams.

2.4 Vegetation and Wildlife

According to the NYSDEC Environmental Resource Mapper (Figure 6), there are known occurrences of the atlantic sturgeon, shortnose sturgeon, and bald eagle on or in the vicinity of the project site.

According to the United States Fish and Wildlife Service (USFWS) Information for Planning and Consultation (IPaC), the project lies within the range of records for indiana bat (endangered) and the monarch butterfly, a candidate species. Candidate species are not regulated by the USFWS (See Attachment A). The IPaC also states that there are no critical habitats at the project location.

The proposed project will require clearing of the entire wooded site (2.5 acres) for construction of the proposed apartment building. To avoid direct or indirect take of bat species, it is recommended that any forest clearing take place between October 30 and March 31, as during this time, the bats would be hibernating and not present onsite.

The atlantic sturgeon and shortnose sturgeon are aquatic species and are found within the Hudson River or immediately adjacent tributaries. The Hudson River is approximately 1,450 feet away from the project site, and therefore the proposed project will not result in any adverse impacts to these species.

An information request has been submitted to NYSDEC for further information regarding the bald eagle. However, based on the NYSDEC Environmental Resource Mapper, the centroid for the bald eagle element occurrence record appears to lie in the vicinity of the Poughkeepsie Rural Cemetery. The heavily traveled NYS Route 9 and the offices for Central Hudson Gas & Electric, lie between the project site and the element occurrence record.

Based on Google Earth, the area within 330 feet of the southern edge of the property is dominated by the heavily traveled NYS Route 9 and the northern portion of the Central Hudson Gas & Electric offices. From 330 to 660 feet from the southern property boundary, the area is dominated by the parking lots for Central Hudson Gas & Electric offices. From 660 to approximately 2,795 feet, the area is dominated by the Poughkeepsie Rural Cemetery. A pond, in the center of the Poughkeepsie Rural Cemetery, which may be close to the location of the bald eagle nest, is more than a ½ mile (2,795 feet) from the southern limits of the project area. Given the intervening highway and commercial land use, and the ½ mile distance from the project area, it is unlikely that the construction or operation of the proposed project will have adverse impacts on the bald eagle. LaBella is making an inquiry to NYSDEC Region 3 to determine the location of the nest and to consult on the bald eagle as necessary.

The project site lies in the vicinity of a significant natural community as shown by the crosshatched pattern on figure 6. This significant natural community is the Hudson River Estuary. The project site lies approximately 1,450 feet away from the Hudson River, and thus is not expected to have any effect on the significant natural community.

2.5 Historic and Archaeological Resources

According to the NYS Office of Parks, Recreation, and Historic Preservation (NYSOPRHP) Cultural Resource Information System (CRIS) mapping (Figure 7), there are no National or State Historic Register sites on the project site nor are there any located substantially contiguous to the site.

Approximately 500 feet away from the project site, along the eastern border of Academy Street, there is a National Register Historic Building Site. The Matthew Vassar Estate (NR# 90PR04179) is located at Academy Street in the City of Poughkeepsie and is listed on the National Register. The estate was nominated for its significance based on National Register Criterion C, due to its representation of Mid-19th Century Gothic Revival Architecture

The project site is located within a known archaeologically sensitive area. Therefore, a consultation request has been submitted to NYSOPRHP.

2.6 Environmental Contamination

On-site

Historic uses of the project site include a filling station (circa 1952), with no indication of automotive work that would generate waste oils was provided. Other former uses of the project site include a freight yard, warehouse, coal and coke storage, and a fuel company with five apparent storage tanks. By the 1980s, all structures were removed from the property and it appears as it does today, wooded and overgrown.

A Phase I ESA was completed for the site by LaBella and documented in a July 7, 2022 report. The following recognized environmental conditions (RECs) and significant data gaps (SDGs) were identified in the report for further investigation to determine potential impacts to the site's subsurface soil and groundwater.

RECs: The Subject Property was developed as a freight yard in or before 1936, and has also been used as a biscuit warehouse, an office, a filling station with two gasoline tanks, coal and coke storage, and a fuel company, and five features that appeared to be aboveground gasoline storage systems were on the property.

SDGs: In at least the mid-1900s, the northern adjoining property was previously a filling station with eight gasoline tanks. The southern adjoining property was developed in or before the 1940s and has been used as a filling station, auto repair, a lumber yard, and a railroad spur extended to this property. Additionally, an eastern adjoining property was noted in the EDR report to have previously been a gas station and trucking terminal, and truck-sized features are visible on this property in historical aerial photographs. No information has been provided regarding the condition of the subsurface on these adjoining properties, and it is unknown if impacts to the Subject Property may have occurred.

The Limited Phase II ESA investigation included:

- Subsurface utility mark out and/or use a magnetometer (geophysical survey) to assess for evidence of underground storage tanks (USTs) and backfilled excavations in limited accessible areas at the site.

- Shallow and subsurface sampling at various site locations to assess soil and groundwater conditions.

Based on the completion of this investigation, the following findings were made:

- The geophysical survey did not identify anomalies suggestive of USTs or backfilled excavations in the eastern site area.

- Select SVOCs (primarily PAHs) and metals exceeded soil cleanup guidelines (SCGs) (arsenic, lead, and mercury in shallow soil; lead, mercury, and selenium in groundwater). The majority of the samples came from locations/intervals where fill materials (coal/ash, slag, building materials) were noted. As such, the detections appear related to the presence of these fill materials and are not indicative of a chemical or petroleum release. Metals noted in dissolved groundwater samples are interpreted to likely represent a “false positive” caused by fine particulate passing through the filtration medium and are likely not representative of actual groundwater conditions. VOCs and herbicides were either detected at trace concentrations less than SCGs, or were not detected above laboratory MDLs.

  While these SVOC and metals results may be associated with former site activities, they were identified in intervals containing fill materials, and no direct exposure is anticipated under current site conditions. Should the material be excavated or dewatering be planned, as in the proposed project, then excavated materials and/or groundwater would need to be handled and disposed of properly. Fill material can be reused on site, consistent with 6 NYCRR Part 360.13(c) as backfill for the excavation

from which the fill material was taken, or as fill in areas of similar physical characteristics on the Site. If fill material exhibits historical or visual evidence of contamination (including odors), and will be used in an area with public access, the relocated fill material must be covered with a minimum of 12 inches of soil or fill material that meets the criteria for general fill.

- During subsequent installation of test pits in November to support redevelopment engineering designs, one of the five test pits encountered subsurface fill material (including ash layers) and exhibited an odor and a PID reading of 6.9 ppm. Based on the field observations, a spill was called in to NYSDEC who assigned Spill # 2206980. As these conditions were not noted in the four other test pits installed on the Site nor in the soil borings installed in July 2022, the area with the odor and PID reading appeared to be isolated. LaBella contacted NYSDEC Case Manager, Michael Kilmer, with the plan that the impacted fill material be excavated and disposed of off-Site as part of site redevelopment activities.

- Bulk building materials samples were obtained from various site areas of observed debris on-Site. Among the 67 samples of building materials collected, one material (black asphalt shingles located near and in SS-3C) was identified as ACM. If this material is disturbed during Site redevelopment activities, excavated building materials and associated soils will be Regulated Asbestos-Containing Material (RACM) and disturbance of this material would constitute a form of asbestos abatement and require associated NYSDOL Site-specific variance. LaBella recommends treating this area of buried building debris as RACM since the shingles were broken up and mixed in with other roofing debris, and also since the condition of the debris prevented identify and sampling of all building materials emplaced in this Site area. If other RACM debris is discovered and planned for disturbance during redevelopment, then that material needs to either be tested to confirm if it is not RACM or assumed to be RACM and managed and disposed as such. While the horizontal limits of this RACM were not identified, we estimate an approximate area of 600 square feet. Based on an approximate thickness of 1 foot, project planning could estimate approximately 25 cubic yards of material.

Off-site

Central Hudson Gas and Electric (CHG&E) facility at 284 South Avenue is identified on the Recovered Govt. Archives Landfill (RGA LF) Database in the years 1992 to 1996. This property is adjoining the Subject Property to the southwest but is approximately 250 feet away across Route 9. CHG&E is listed as a RCRA small quantity generator and a RCRA large quantity generator, generating mercury, paint thinner, and corrosive and ignitable waste. No information has been provided indicating a release of hazardous waste to the property and this facility is downgradient of the project site. Therefore, the RCRA generator status of this facility is not expected to have impacted the project.

2.7 Traffic and Parking

2.7.1 Traffic

According to the Institute of Transportation Engineers (ITE) Traffic Generation Manual, 11th Edition, multifamily housing, specifically 87 apartment units, (Land Use Code 221) is expected

to generate 27 vehicle trip ends (vtes) per weekday a.m. peak hour of adjacent street traffic (6 entry/21 exit) and 34 vtes per weekday p.m. peak hour of adjacent street traffic (21 entry/13 exit). The total of 27 a.m. peak hour vtes and total of 34 p.m. peak hour vtes, are each below the NYSDOT and ITE guideline of 100 peak hour trips for warranting a detailed traffic analysis.

Therefore, it is safe to assume that the proposed project will not adversely affect the traffic operations on the surrounding roadway network.

2.7.2 Parking

A parking assessment was undertaken to compare the number of parking spaces proposed for the project against industry standards, the city's zoning code, and other local zoning codes. The South Avenue Multifamily Development consists of 87 single bedroom apartment units with 115 parking spaces. The Institute of Transportation Engineers' (ITE) Parking Generation Manual, 5th Edition, is the industry standard for estimating parking spaces for proposed land uses based on studies of similar existing developments. Land use code (LUC) 221 for Multifamily Housing (mid-rise) was used to estimate the number of parking spaces for the project. A range of parking rates is provided in Parking Generation that include the average rate, the 33rd percentile rate, and the 85th percentile rate. The parking generation is summarized in Table 2.

Table 2: Parking Generation Summary

LUC 221 Multifamily Housing (Mid-rise)		
	Rate	Spaces
Average	0.75	65
33rd Percentile	0.65	57
85th Percentile	0.87	76

Rate: spaces per bedroom

As the table shows, the proposed number of parking spaces exceeds the estimates provided by Parking Generation. The city's draft zoning code requires 1.25 spaces per bedroom which totals 112 spaces. The City of Newburgh requires 0.75 spaces per bedroom (65 spaces) and the City of Beacon requires 1.0 space for each dwelling unit (87 spaces).

Based on ITE's industry parking standard and other local city zoning codes, it is anticipated that the project is proposing sufficient parking at 115 spaces.

FULL ENVIRONMENTAL ASSESSMENT FORM PART 1

Instructions for Completing Part 1

Part 1 is to be completed by the applicant or project sponsor. Responses become part of the application for approval or funding, are subject to public review, and may be subject to further verification.

Complete Part 1 based on information currently available. If additional research or investigation would be needed to fully respond to any item, please answer as thoroughly as possible based on current information; indicate whether missing information does not exist, or is not reasonably available to the sponsor; and, when possible, generally describe work or studies which would be necessary to update or fully develop that information.

Applicants/sponsors must complete all items in Sections A & B. In Sections C, D & E, most items contain an initial question that must be answered either "Yes" or "No". If the answer to the initial question is "Yes", complete the sub-questions that follow. If the answer to the initial question is "No", proceed to the next question. Section F allows the project sponsor to identify and attach any additional information. Section G requires the name and signature of the applicant or project sponsor to verify that the information contained in Part 1is accurate and complete.

A. Project and Applicant/Sponsor Information.

Name of Action or Project: South Avenue Multi-Family Development		
Project Location (describe, and attach a general location map): South Avenue, City of Poughkeepsie, Dutchess Co., New York ; Tax Parcel ID 6061-52-937583		
Brief Description of Proposed Action (include purpose or need): The Applicant, ARGO Development is seeking site plan approval from the City of Poughkeepsie, to develop an 87-unit, mid-rise multifamily residential development with underground and surface-level parking. The proposed action will be located on an approximately 2.76-acre parcel on the west side of South Avenue (Tax Lot 937583) in the City of Poughkeepsie. The proposed action includes construction of a five-story building with 87, one-bedroom, apartments located over one level of underground parking (60 spaces), and 56 off-street surface parking spaces (115 total). The parcel is currently a wooded lot. The parcel is located within the R-D, Research and Development District. Residential development is a permitted use within the R-D zone, subject to the requirements of the High-Density R-5 District Permitted Uses [Section 19-3.16(2)], and further subject to all other requirements applicable to High-Density R-5 District residential development. Primary access will be provided via South Avenue. Municipal water and sanitary sewer connections are available in South Road. The proposed ground disturbance is approximately 2.5 acres. Since the site will have more than 1 acre of ground disturbance, the proposed action will also require a SPDES General Permit for stormwater. An area variance for 116 parking spaces is required from the ZBA.		
Name of Applicant/Sponsor: ARGO Development (Contact: Mr. Michael Abuladze, CEO)	Telephone: 914-494-2610 E-Mail: mike@argodev.com	
Address: 95 Chestnut Ridge Road		
City/PO: Montvale	State: NJ	Zip Code: 07645
Project Contact (if not same as sponsor; give name and title/role): Same as Applicant/Sponsor	Telephone: E-Mail:	
Address:		
City/PO:	State:	Zip Code:
Property Owner (if not same as sponsor): South Ave Real Est Assoc LLC	Telephone: 914-494-2610 E-Mail: mike@argodev.com	
Address: 510 Haight Ave		
City/PO: Poughkeepsie	State: NY	Zip Code: 12603

B. Government Approvals

B. Government Approvals, Funding, or Sponsorship. ("Funding" includes grants, loans, tax relief, and any other forms of financial assistance.)

Government Entity	If Yes: Identify Agency and Approval(s) Required	Application Date (Actual or projected)
a. City Counsel, Town Board, or Village Board of Trustees ☐Yes ☑No		
b. City, Town or Village Planning Board or Commission ☑Yes ☐No	City of Poughkeepsie Planning Board - Site Plan Approval	Winter 2022
c. City, Town or Village Zoning Board of Appeals ☑Yes ☐No	City of Poughkeepsie Zoning Board of Appeals - Area Variance (parking)	Winter 2023
d. Other local agencies ☑Yes ☐No	City of Poughkeepsie DPW - Highway Work Permit; Water & Sewer Connections	Winter 2022/2023
e. County agencies ☑Yes ☐No	Dutchess County Planning - GML 239-m Referral	Winter 2022
f. Regional agencies ☐Yes ☑No		
g. State agencies ☑Yes ☐No	NYSDEC - SPDES GP-0-20-001; SWPPP; NYSOPRHP SHPO consult, NYSDOT - Drainage	Winter 2022/2023
h. Federal agencies ☐Yes ☑No		

i. Coastal Resources.

i. Is the project site within a Coastal Area, or the waterfront area of a Designated Inland Waterway? ☑Yes ☐No

ii. Is the project site located in a community with an approved Local Waterfront Revitalization Program? ☐Yes ☑No

iii. Is the project site within a Coastal Erosion Hazard Area? ☐Yes ☑No

C. Planning and Zoning

C.1. Planning and zoning actions.

Will administrative or legislative adoption, or amendment of a plan, local law, ordinance, rule or regulation be the only approval(s) which must be granted to enable the proposed action to proceed? ☐Yes ☑No

- **If Yes,** complete sections C, F and G.
- **If No,** proceed to question C.2 and complete all remaining sections and questions in Part 1

C.2. Adopted land use plans.

a. Do any municipally- adopted (city, town, village or county) comprehensive land use plan(s) include the site where the proposed action would be located? ☑Yes ☐No

If Yes, does the comprehensive plan include specific recommendations for the site where the proposed action would be located? ☐Yes ☑No

b. Is the site of the proposed action within any local or regional special planning district (for example: Greenway; Brownfield Opportunity Area (BOA); designated State or Federal heritage area; watershed management plan; or other?) ☑Yes ☐No

If Yes, identify the plan(s):

Dutchess County Greenway Compact Program; Hudson River Valley Greenway

c. Is the proposed action located wholly or partially within an area listed in an adopted municipal open space plan, or an adopted municipal farmland protection plan? ☐Yes ☑No

If Yes, identify the plan(s):

C.3. Zoning

a. Is the site of the proposed action located in a municipality with an adopted zoning law or ordinance. ☑ Yes ☐ No
If Yes, what is the zoning classification(s) including any applicable overlay district?
Research and Development District (R-D)

b. Is the use permitted or allowed by a special or conditional use permit? ☑ Yes ☐ No

c. Is a zoning change requested as part of the proposed action? ☐ Yes ☑ No
If Yes,
i. What is the proposed new zoning for the site? _____

C.4. Existing community services.

a. In what school district is the project site located? Poughkeepsie City School District

b. What police or other public protection forces serve the project site?
City of Poughkeepsie Police Department

c. Which fire protection and emergency medical services serve the project site?
City of Poughkeepsie Fire Department

d. What parks serve the project site?
Eastman Park, Harriet Tubman Park, Murphy Park, Mansion Square Park, Kaal Rock Park

D. Project Details

D.1. Proposed and Potential Development

a. What is the general nature of the proposed action (e.g., residential, industrial, commercial, recreational; if mixed, include all components)? Residential Development - Apartments

b. a. Total acreage of the site of the proposed action? 2.76 acres
b. Total acreage to be physically disturbed? ~2.5 acres
c. Total acreage (project site and any contiguous properties) owned or controlled by the applicant or project sponsor? 2.76 acres

c. Is the proposed action an expansion of an existing project or use? ☐ Yes ☑ No
i. If Yes, what is the approximate percentage of the proposed expansion and identify the units (e.g., acres, miles, housing units, square feet)? % _____ Units: _____

d. Is the proposed action a subdivision, or does it include a subdivision? ☐ Yes ☑ No
If Yes,
i. Purpose or type of subdivision? (e.g., residential, industrial, commercial; if mixed, specify types)
_____
ii. Is a cluster/conservation layout proposed? ☐ Yes ☐ No
iii. Number of lots proposed? _____
iv. Minimum and maximum proposed lot sizes? Minimum _____ Maximum _____

e. Will the proposed action be constructed in multiple phases? ☐ Yes ☑ No
i. If No, anticipated period of construction: 12 months
ii. If Yes:
- Total number of phases anticipated _____
- Anticipated commencement date of phase 1 (including demolition) _____ month _____ year
- Anticipated completion date of final phase _____ month _____year
- Generally describe connections or relationships among phases, including any contingencies where progress of one phase may determine timing or duration of future phases: _____

f. Does the project include new residential uses? ☑ Yes ☐ No

If Yes, show numbers of units proposed.

	One Family	Two Family	Three Family	Multiple Family (four or more)
Initial Phase	0	0	0	87
At completion of all phases	0	0	0	87

g. Does the proposed action include new non-residential construction (including expansions)? ☐ Yes ☑ No

If Yes,

i. Total number of structures _____

ii. Dimensions (in feet) of largest proposed structure: _____height; _____width; and _____ length

iii. Approximate extent of building space to be heated or cooled: _____ square feet

h. Does the proposed action include construction or other activities that will result in the impoundment of any liquids, such as creation of a water supply, reservoir, pond, lake, waste lagoon or other storage? ☐ Yes ☑ No

If Yes,

i. Purpose of the impoundment: _____

ii. If a water impoundment, the principal source of the water: ☐ Ground water ☐ Surface water streams ☐ Other specify:

_____

iii. If other than water, identify the type of impounded/contained liquids and their source.

_____

iv. Approximate size of the proposed impoundment. Volume: _____ million gallons; surface area: _____ acres

v. Dimensions of the proposed dam or impounding structure: _____ height; _____ length

vi. Construction method/materials for the proposed dam or impounding structure (e.g., earth fill, rock, wood, concrete):

_____

D.2. Project Operations

a. Does the proposed action include any excavation, mining, or dredging, during construction, operations, or both? (Not including general site preparation, grading or installation of utilities or foundations where all excavated materials will remain onsite) ☐ Yes ☑ No

If Yes:

i .What is the purpose of the excavation or dredging? _____

ii. How much material (including rock, earth, sediments, etc.) is proposed to be removed from the site?

- Volume (specify tons or cubic yards): _____
- Over what duration of time? _____

iii. Describe nature and characteristics of materials to be excavated or dredged, and plans to use, manage or dispose of them.

_____

_____

i*v.* Will there be onsite dewatering or processing of excavated materials? ☐ Yes ☐ No

If yes, describe. _____

_____

v. What is the total area to be dredged or excavated? _____acres

vi. What is the maximum area to be worked at any one time? _____ acres

vii. What would be the maximum depth of excavation or dredging? _____ feet

viii. Will the excavation require blasting? ☐ Yes ☐ No

ix. Summarize site reclamation goals and plan: _____

_____

_____

b. Would the proposed action cause or result in alteration of, increase or decrease in size of, or encroachment into any existing wetland, waterbody, shoreline, beach or adjacent area? ☐ Yes ☑ No

If Yes:

i. Identify the wetland or waterbody which would be affected (by name, water index number, wetland map number or geographic description): _____

_____

ii. Describe how the proposed action would affect that waterbody or wetland, e.g. excavation, fill, placement of structures, or alteration of channels, banks and shorelines. Indicate extent of activities, alterations and additions in square feet or acres:

_____

_____

_____

_____

iii. Will the proposed action cause or result in disturbance to bottom sediments? ☐Yes ☐No

If Yes, describe: _____

iv. Will the proposed action cause or result in the destruction or removal of aquatic vegetation? ☐Yes ☐No

If Yes:

- acres of aquatic vegetation proposed to be removed: _____
- expected acreage of aquatic vegetation remaining after project completion: _____
- purpose of proposed removal (e.g. beach clearing, invasive species control, boat access): _____

_____

- proposed method of plant removal: _____
- if chemical/herbicide treatment will be used, specify product(s): _____

v. Describe any proposed reclamation/mitigation following disturbance: _____

_____

c. Will the proposed action use, or create a new demand for water? ☑Yes ☐No

If Yes: The apartment units would require 110 gallons per day. Assuming 87 apartment units (110 gpd) x 87 units = 9,570 GPD.

i. Total anticipated water usage/demand per day: 9,570 gallons/day

ii. Will the proposed action obtain water from an existing public water supply? ☑Yes ☐No

If Yes:

- Name of district or service area: The City of Poughkeepsie Townwide Water District
- Does the existing public water supply have capacity to serve the proposal? ☑Yes ☐No
- Is the project site in the existing district? ☑Yes ☐No
- Is expansion of the district needed? ☐Yes ☑No
- Do existing lines serve the project site? ☑Yes ☐No

iii. Will line extension within an existing district be necessary to supply the project? ☐Yes ☑No

If Yes:

- Describe extensions or capacity expansions proposed to serve this project: _____

_____

- Source(s) of supply for the district: _____

iv. Is a new water supply district or service area proposed to be formed to serve the project site? ☐Yes ☑No

If, Yes:

- Applicant/sponsor for new district: _____
- Date application submitted or anticipated: _____
- Proposed source(s) of supply for new district: _____

v. If a public water supply will not be used, describe plans to provide water supply for the project: _____

NA _____

vi. If water supply will be from wells (public or private), what is the maximum pumping capacity: NA gallons/minute.

d. Will the proposed action generate liquid wastes? ☑Yes ☐No

If Yes: The apartment units would require 110 gallons per day. Assuming 87 apartment units (110 gpd) x 87 units = 9,570 GPD.

i. Total anticipated liquid waste generation per day: 9,570 gallons/day

ii. Nature of liquid wastes to be generated (e.g., sanitary wastewater, industrial; if combination, describe all components and approximate volumes or proportions of each): _____

sanitary wastewater

_____

iii. Will the proposed action use any existing public wastewater treatment facilities? ☑Yes ☐No

If Yes:

- Name of wastewater treatment plant to be used: City of Poughkeepsie Sewage Treatment Plant
- Name of district: City of Poughkeepsie
- Does the existing wastewater treatment plant have capacity to serve the project? ☑Yes ☐No
- Is the project site in the existing district? ☑Yes ☐No
- Is expansion of the district needed? ☐Yes ☑No

- Do existing sewer lines serve the project site? ☑ Yes ☐ No
- Will a line extension within an existing district be necessary to serve the project? ☐ Yes ☑ No

  If Yes:
  - Describe extensions or capacity expansions proposed to serve this project: _____

iv. Will a new wastewater (sewage) treatment district be formed to serve the project site? ☐ Yes ☑ No

If Yes:
- Applicant/sponsor for new district: _____
- Date application submitted or anticipated: _____
- What is the receiving water for the wastewater discharge? _____

v. If public facilities will not be used, describe plans to provide wastewater treatment for the project, including specifying proposed receiving water (name and classification if surface discharge or describe subsurface disposal plans):

NA

vi. Describe any plans or designs to capture, recycle or reuse liquid waste:

None

e. Will the proposed action disturb more than one acre and create stormwater runoff, either from new point sources (i.e. ditches, pipes, swales, curbs, gutters or other concentrated flows of stormwater) or non-point source (i.e. sheet flow) during construction or post construction? ☑ Yes ☐ No

If Yes:

i. How much impervious surface will the project create in relation to total size of project parcel?

_____ Square feet or 1.48 acres (impervious surface)

_____ Square feet or 2.76 acres (parcel size)

ii. Describe types of new point sources. New building, parking lot, sidewalks, pavement

iii. Where will the stormwater runoff be directed (i.e. on-site stormwater management facility/structures, adjacent properties, groundwater, on-site surface water or off-site surface waters)?

Areas impacted by development will be diverted to on-site stormwater practices focused on meeting NYSDEC detention and qualitative requirements. In areas not impacted by proposed development, stormwater runoff will continue to flow along existing flow paths.

- If to surface waters, identify receiving water bodies or wetlands:

  No
- Will stormwater runoff flow to adjacent properties? ☑ Yes ☐ No

iv. Does the proposed plan minimize impervious surfaces, use pervious materials or collect and re-use stormwater? ☐ Yes ☑ No

f. Does the proposed action include, or will it use on-site, one or more sources of air emissions, including fuel combustion, waste incineration, or other processes or operations? ☑ Yes ☐ No

If Yes, identify:

i. Mobile sources during project operations (e.g., heavy equipment, fleet or delivery vehicles)

ii. Stationary sources during construction (e.g., power generation, structural heating, batch plant, crushers)

Temporary sources during construction

iii. Stationary sources during operations (e.g., process emissions, large boilers, electric generation)

Boilers, Electric generation

g. Will any air emission sources named in D.2.f (above), require a NY State Air Registration, Air Facility Permit, or Federal Clean Air Act Title IV or Title V Permit? ☐ Yes ☑ No

If Yes:

i. Is the project site located in an Air quality non-attainment area? (Area routinely or periodically fails to meet ambient air quality standards for all or some parts of the year) ☐ Yes ☐ No

ii. In addition to emissions as calculated in the application, the project will generate:
- _____Tons/year (short tons) of Carbon Dioxide (CO_2)
- _____Tons/year (short tons) of Nitrous Oxide (N_2O)
- _____Tons/year (short tons) of Perfluorocarbons (PFCs)
- _____Tons/year (short tons) of Sulfur Hexafluoride (SF_6)
- _____Tons/year (short tons) of Carbon Dioxide equivalent of Hydroflourocarbons (HFCs)
- _____Tons/year (short tons) of Hazardous Air Pollutants (HAPs)

h. Will the proposed action generate or emit methane (including, but not limited to, sewage treatment plants, landfills, composting facilities)? ☐Yes ☑No

If Yes:

i. Estimate methane generation in tons/year (metric): _____

ii. Describe any methane capture, control or elimination measures included in project design (e.g., combustion to generate heat or electricity, flaring): _____

i. Will the proposed action result in the release of air pollutants from open-air operations or processes, such as quarry or landfill operations? ☐Yes ☑No

If Yes: Describe operations and nature of emissions (e.g., diesel exhaust, rock particulates/dust):

j. Will the proposed action result in a substantial increase in traffic above present levels or generate substantial new demand for transportation facilities or services? ☐Yes ☑No

If Yes:

i. When is the peak traffic expected (Check all that apply): ☑ Morning ☑ Evening ☐Weekend ☐ Randomly between hours of _____ to _____.

ii. For commercial activities only, projected number of truck trips/day and type (e.g., semi trailers and dump trucks): NA

iii. Parking spaces: Existing 0 Proposed 115 Net increase/decrease +115

iv. Does the proposed action include any shared use parking? ☐Yes ☑No

v. If the proposed action includes any modification of existing roads, creation of new roads or change in existing access, describe: Primary access will be provided via South Avenue.

vi. Are public/private transportation service(s) or facilities available within ½ mile of the proposed site? ☐Yes ☑No

vii Will the proposed action include access to public transportation or accommodations for use of hybrid, electric or other alternative fueled vehicles? ☑Yes ☐No EV vehicles may be included inside the parking garage.

viii. Will the proposed action include plans for pedestrian or bicycle accommodations for connections to existing pedestrian or bicycle routes? ☐Yes ☑No

k. Will the proposed action (for commercial or industrial projects only) generate new or additional demand for energy? ☐Yes ☑No

If Yes:

i. Estimate annual electricity demand during operation of the proposed action: NA

ii. Anticipated sources/suppliers of electricity for the project (e.g., on-site combustion, on-site renewable, via grid/local utility, or other): NA

iii. Will the proposed action require a new, or an upgrade, to an existing substation? ☐Yes ☐No

l. Hours of operation. Answer all items which apply.

i. During Construction:

- Monday - Friday: 6:30AM-9PM
- Saturday: 6:30AM-9PM
- Sunday: 6:30AM-9PM
- Holidays: 6:30AM-9PM

ii. During Operations:

- Monday - Friday: 24/7
- Saturday: 24/7
- Sunday: 24/7
- Holidays: 24/7

m. Will the proposed action produce noise that will exceed existing ambient noise levels during construction, operation, or both? ☑ Yes ☐ No

If yes:

i. Provide details including sources, time of day and duration:

The proposed construction activities may result in noise that exceeds local ambient noise levels. These activities are temporary and will be limited to the hours stated in subsection I above.

ii. Will the proposed action remove existing natural barriers that could act as a noise barrier or screen? ☑ Yes ☐ No

Describe: The entire project site will be cleared. Adjoining properties are commercial uses.

n. Will the proposed action have outdoor lighting? ☑ Yes ☐ No

If yes:

i. Describe source(s), location(s), height of fixture(s), direction/aim, and proximity to nearest occupied structures:

Lightpoles and wall mounted lighting (3000K), Full cut-off. Surrounding properties are commercial uses.

ii. Will proposed action remove existing natural barriers that could act as a light barrier or screen? ☐ Yes ☐ No

Describe: The entire project site will be cleared. Adjoining properties are commercial uses.

o. Does the proposed action have the potential to produce odors for more than one hour per day? ☐ Yes ☑ No

If Yes, describe possible sources, potential frequency and duration of odor emissions, and proximity to nearest occupied structures: _____

p. Will the proposed action include any bulk storage of petroleum (combined capacity of over 1,100 gallons) or chemical products 185 gallons in above ground storage or any amount in underground storage? ☐ Yes ☑ No

If Yes:

i. Product(s) to be stored _____

ii. Volume(s) _____ per unit time _____ (e.g., month, year)

iii. Generally, describe the proposed storage facilities: _____

q. Will the proposed action (commercial, industrial and recreational projects only) use pesticides (i.e., herbicides, insecticides) during construction or operation? ☑ Yes ☐ No

If Yes:

i. Describe proposed treatment(s):

Typical treatments by licensed professionals.

ii. Will the proposed action use Integrated Pest Management Practices? ☐ Yes ☐ No

r. Will the proposed action (commercial or industrial projects only) involve or require the management or disposal of solid waste (excluding hazardous materials)? ☐ Yes ☑ No

If Yes:

i. Describe any solid waste(s) to be generated during construction or operation of the facility:

- Construction: NA tons per NA (unit of time)
- Operation : NA tons per NA (unit of time)

ii. Describe any proposals for on-site minimization, recycling or reuse of materials to avoid disposal as solid waste:

- Construction: NA
- Operation: NA

iii. Proposed disposal methods/facilities for solid waste generated on-site:

- Construction: NA
- Operation: NA

s. Does the proposed action include construction or modification of a solid waste management facility? ☐ Yes ☑ No

If Yes:

i. Type of management or handling of waste proposed for the site (e.g., recycling or transfer station, composting, landfill, or other disposal activities): _____

ii. Anticipated rate of disposal/processing:

- _____ Tons/month, if transfer or other non-combustion/thermal treatment, or
- _____ Tons/hour, if combustion or thermal treatment

iii. If landfill, anticipated site life: _____ years

t. Will the proposed action at the site involve the commercial generation, treatment, storage, or disposal of hazardous waste? ☐ Yes ☑ No

If Yes:

i. Name(s) of all hazardous wastes or constituents to be generated, handled or managed at facility: _____

ii. Generally describe processes or activities involving hazardous wastes or constituents: _____

iii. Specify amount to be handled or generated _____ tons/month

iv. Describe any proposals for on-site minimization, recycling or reuse of hazardous constituents: _____

v. Will any hazardous wastes be disposed at an existing offsite hazardous waste facility? ☐ Yes ☐ No

If Yes: provide name and location of facility: _____

If No: describe proposed management of any hazardous wastes which will not be sent to a hazardous waste facility:

E. Site and Setting of Proposed Action

E.1. Land uses on and surrounding the project site

a. Existing land uses.

i. Check all uses that occur on, adjoining and near the project site.

☐ Urban ☐ Industrial ☑ Commercial ☑ Residential (suburban) ☐ Rural (non-farm)
☐ Forest ☐ Agriculture ☐ Aquatic ☑ Other (specify): parking lots

ii. If mix of uses, generally describe:

b. Land uses and covertypes on the project site.

Land use or Covertype	Current Acreage	Acreage After Project Completion	Change (Acres +/-)
• Roads, buildings, and other paved or impervious surfaces	0	1.48	+1.48
• Forested	2.56	0.08	-2.48
• Meadows, grasslands or brushlands (non-agricultural, including abandoned agricultural)	0.20	1.20	+1.00
• Agricultural (includes active orchards, field, greenhouse etc.)	0	0	0
• Surface water features (lakes, ponds, streams, rivers, etc.)	0	0	0
• Wetlands (freshwater or tidal)	0	0	0
• Non-vegetated (bare rock, earth or fill)	0	0	0
• Other Describe: None	0	0	0

c. Is the project site presently used by members of the community for public recreation? ☐ Yes ☑ No

i. If Yes: explain: _____

d. Are there any facilities serving children, the elderly, people with disabilities (e.g., schools, hospitals, licensed day care centers, or group homes) within 1500 feet of the project site? ☑ Yes ☐ No

If Yes,

i. Identify Facilities:

Precious Keepers LLC (adult day care center); Vassar Brothers Hospital

e. Does the project site contain an existing dam? ☐ Yes ☑ No

If Yes:

i. Dimensions of the dam and impoundment:

- Dam height: _____ feet
- Dam length: _____ feet
- Surface area: _____ acres
- Volume impounded: _____ gallons OR acre-feet

ii. Dam's existing hazard classification: _____

iii. Provide date and summarize results of last inspection:

_____

f. Has the project site ever been used as a municipal, commercial or industrial solid waste management facility, or does the project site adjoin property which is now, or was at one time, used as a solid waste management facility? ☐ Yes ☑ No

If Yes:

i. Has the facility been formally closed? **Unknown** ☐ Yes ☐ No

- If yes, cite sources/documentation: _____

ii. Describe the location of the project site relative to the boundaries of the solid waste management facility:

_____

iii. Describe any development constraints due to the prior solid waste activities: _____

g. Have hazardous wastes been generated, treated and/or disposed of at the site, or does the project site adjoin property which is now or was at one time used to commercially treat, store and/or dispose of hazardous waste? ☑ Yes ☐ No

If Yes:

i. Describe waste(s) handled and waste management activities, including approximate time when activities occurred:

_____

h. Potential contamination history. Has there been a reported spill at the proposed project site, or have any remedial actions been conducted at or adjacent to the proposed site? ☑ Yes ☐ No

If Yes:

i. Is any portion of the site listed on the NYSDEC Spills Incidents database or Environmental Site Remediation database? Check all that apply: ☑ Yes ☐ No

☑ Yes – Spills Incidents database — Provide DEC ID number(s): 2206980 (open). See Section 2.6.

☐ Yes – Environmental Site Remediation database — Provide DEC ID number(s): _____

☐ Neither database

ii. If site has been subject of RCRA corrective activities, describe control measures: _____

iii. Is the project within 2000 feet of any site in the NYSDEC Environmental Site Remediation database? ☑ Yes ☐ No

If yes, provide DEC ID number(s): B00190, 546031

iv. If yes to (i), (ii) or (iii) above, describe current status of site(s):

1. Hudson River Waterfront-DeLaval Property (B00190) - Class C: Remediation was successfully completed through the Environmental Restoration Program, and there is an Environmental Easement on the property. 2. Hudson River PCB Sediments (546031) - Class 2: State Superfund Program; Remedial actions vary from deploying signs to installing various covers and are intended to reduce exposures to PCBs in floodplain soils until a permanent remedy is developed. Additionally, a remedial investigation to address floodplain soils in the Upper Hudson River Floodplain under USEPA and State oversight is now underway.

v. Is the project site subject to an institutional control limiting property uses? ☐ Yes ☑ No

- If yes, DEC site ID number: _____
- Describe the type of institutional control (e.g., deed restriction or easement): _____
- Describe any use limitations: _____
- Describe any engineering controls: _____
- Will the project affect the institutional or engineering controls in place? ☐ Yes ☐ No
- Explain: _____

E.2. Natural Resources On or Near Project Site

a. What is the average depth to bedrock on the project site? >6 feet

b. Are there bedrock outcroppings on the project site? ☐ Yes ☑ No
If Yes, what proportion of the site is comprised of bedrock outcroppings? _____%

c. Predominant soil type(s) present on project site:

Udorthents, smoothed (Ud)	98.2 %
Urban Land (Ur)	1.8 %
	%

d. What is the average depth to the water table on the project site? Average: ~3-6 feet

e. Drainage status of project site soils:

☑	Well Drained:	98.2 % of site
☐	Moderately Well Drained:	_____% of site
☐	Poorly Drained	_____% of site

f. Approximate proportion of proposed action site with slopes:

☑	0-10%:	98.2 % of site
☐	10-15%:	_____% of site
☐	15% or greater:	_____% of site

g. Are there any unique geologic features on the project site? ☐ Yes ☑ No
If Yes, describe: _____

h. Surface water features.

i. Does any portion of the project site contain wetlands or other waterbodies (including streams, rivers, ponds or lakes)? ☐ Yes ☑ No

ii. Do any wetlands or other waterbodies adjoin the project site? ☐ Yes ☑ No

If Yes to either *i* or *ii*, continue. If No, skip to E.2.i.

iii. Are any of the wetlands or waterbodies within or adjoining the project site regulated by any federal, state or local agency? ☐ Yes ☑ No

iv. For each identified regulated wetland and waterbody on the project site, provide the following information:

- Streams: Name _____ Classification _____
- Lakes or Ponds: Name _____ Classification _____
- Wetlands: Name _____ Approximate Size _____
- Wetland No. (if regulated by DEC) _____

v. Are any of the above water bodies listed in the most recent compilation of NYS water quality-impaired waterbodies? ☐ Yes ☑ No

If yes, name of impaired water body/bodies and basis for listing as impaired: _____

i. Is the project site in a designated Floodway? ☐ Yes ☑ No

j. Is the project site in the 100-year Floodplain? ☐ Yes ☑ No

k. Is the project site in the 500-year Floodplain? ☐ Yes ☑ No

l. Is the project site located over, or immediately adjoining, a primary, principal or sole source aquifer? ☐ Yes ☑ No
If Yes:

i. Name of aquifer: _____

m. Identify the predominant wildlife species that occupy or use the project site:
Wildlife native to Dutchess County

n. Does the project site contain a designated significant natural community? ☐ Yes ☑ No
If Yes: The project site does not contain a designated significant natural community, however it is near the Hudson River Estuary, which is located off-site and west of the project site.
i. Describe the habitat/community (composition, function, and basis for designation):
ii. Source(s) of description or evaluation:
iii. Extent of community/habitat:
- Currently: _____ acres
- Following completion of project as proposed: _____ acres
- Gain or loss (indicate + or -): _____ acres

o. Does project site contain any species of plant or animal that is listed by the federal government or NYS as endangered or threatened, or does it contain any areas identified as habitat for an endangered or threatened species? ☑ Yes ☐ No

If Yes:
i. Species and listing (endangered or threatened):
NYSDEC: Atlantic Sturgeon, Bald Eagle, Shortnose Sturgeon; IPaC: Indiana Bat

p. Does the project site contain any species of plant or animal that is listed by NYS as rare, or as a species of special concern? ☐ Yes ☑ No

If Yes:
i. Species and listing:

q. Is the project site or adjoining area currently used for hunting, trapping, fishing or shell fishing? ☐ Yes ☑ No
If yes, give a brief description of how the proposed action may affect that use:

E.3. Designated Public Resources On or Near Project Site

a. Is the project site, or any portion of it, located in a designated agricultural district certified pursuant to Agriculture and Markets Law, Article 25-AA, Section 303 and 304? ☐ Yes ☑ No
If Yes, provide county plus district name/number:

b. Are agricultural lands consisting of highly productive soils present? ☐ Yes ☑ No
i. If Yes: acreage(s) on project site?
ii. Source(s) of soil rating(s):

c. Does the project site contain all or part of, or is it substantially contiguous to, a registered National Natural Landmark? ☐ Yes ☑ No
If Yes:
i. Nature of the natural landmark: ☐ Biological Community ☐ Geological Feature
ii. Provide brief description of landmark, including values behind designation and approximate size/extent:

d. Is the project site located in or does it adjoin a state listed Critical Environmental Area? ☐ Yes ☑ No
If Yes:
i. CEA name:
ii. Basis for designation:
iii. Designating agency and date:

e. Does the project site contain, or is it substantially contiguous to, a building, archaeological site, or district which is listed on the National or State Register of Historic Places, or that has been determined by the Commissioner of the NYS Office of Parks, Recreation and Historic Preservation to be eligible for listing on the State Register of Historic Places? ☐ Yes ☑ No

If Yes: The historic resource is not substantially contiguous to the project site.

i. Nature of historic/archaeological resource: ☐ Archaeological Site ☑ Historic Building or District

ii. Name: Vassar, Matthew, Estate

iii. Brief description of attributes on which listing is based:

Mid-19th Century Gothic Revival Architecture

f. Is the project site, or any portion of it, located in or adjacent to an area designated as sensitive for archaeological sites on the NY State Historic Preservation Office (SHPO) archaeological site inventory? ☑ Yes ☐ No

g. Have additional archaeological or historic site(s) or resources been identified on the project site? ☐ Yes ☑ No

If Yes:

i. Describe possible resource(s): _____

ii. Basis for identification: _____

h. Is the project site within fives miles of any officially designated and publicly accessible federal, state, or local scenic or aesthetic resource? ☑ Yes ☐ No

If Yes:

i. Identify resource: Refer to Figure 8

ii. Nature of, or basis for, designation (e.g., established highway overlook, state or local park, state historic trail or scenic byway, etc.): Refer to Figure 8

iii. Distance between project and resource: 0-5 miles.

i. Is the project site located within a designated river corridor under the Wild, Scenic and Recreational Rivers Program 6 NYCRR 666? ☐ Yes ☑ No

If Yes:

i. Identify the name of the river and its designation: _____

ii. Is the activity consistent with development restrictions contained in 6NYCRR Part 666? ☐ Yes ☐ No

F. Additional Information

Attach any additional information which may be needed to clarify your project.

If you have identified any adverse impacts which could be associated with your proposal, please describe those impacts plus any measures which you propose to avoid or minimize them.

G. Verification

I certify that the information provided is true to the best of my knowledge.

Applicant/Sponsor Name Michael Abuladze, ARGO Development Date 1/27/22

Signature Krithika Prabhakaran, Agent for Applicant Krithika Prabhakaran Title Urban Planner, LaBella Associates

PRINT FORM

Disclaimer: The EAF Mapper is a screening tool intended to assist project sponsors and reviewing agencies in preparing an environmental assessment form (EAF). Not all questions asked in the EAF are answered by the EAF Mapper. Additional information on any EAF question can be obtained by consulting the EAF Workbooks. Although the EAF Mapper provides the most up-to-date digital data available to DEC, you may also need to contact local or other data sources in order to obtain data not provided by the Mapper. Digital data is not a substitute for agency determinations.

B.i.i [Coastal or Waterfront Area]	Yes
B.i.ii [Local Waterfront Revitalization Area]	No
C.2.b. [Special Planning District]	Digital mapping data are not available or are incomplete. Refer to EAF Workbook.
E.1.h [DEC Spills or Remediation Site - Potential Contamination History]	Digital mapping data are not available or are incomplete. Refer to EAF Workbook.
E.1.h.i [DEC Spills or Remediation Site - Listed]	Digital mapping data are not available or are incomplete. Refer to EAF Workbook.
E.1.h.i [DEC Spills or Remediation Site - Environmental Site Remediation Database]	Digital mapping data are not available or are incomplete. Refer to EAF Workbook.
E.1.h.iii [Within 2,000' of DEC Remediation Site]	Yes
E.1.h.iii [Within 2,000' of DEC Remediation Site - DEC ID]	B00190, 546031
E.2.g [Unique Geologic Features]	No
E.2.h.i [Surface Water Features]	No
E.2.h.ii [Surface Water Features]	No
E.2.h.iii [Surface Water Features]	No
E.2.h.v [Impaired Water Bodies]	No
E.2.i. [Floodway]	No
E.2.j. [100 Year Floodplain]	No
E.2.k. [500 Year Floodplain]	No
E.2.l. [Aquifers]	No
E.2.n. [Natural Communities]	No
E.2.o. [Endangered or Threatened Species]	Yes

E.2.o. [Endangered or Threatened Species - Name]	Atlantic Sturgeon, Bald Eagle, Shortnose Sturgeon
E.2.p. [Rare Plants or Animals]	No
E.3.a. [Agricultural District]	No
E.3.c. [National Natural Landmark]	No
E.3.d [Critical Environmental Area]	No
E.3.e. [National or State Register of Historic Places or State Eligible Sites]	Yes - Digital mapping data for archaeological site boundaries are not available. Refer to EAF Workbook.
E.3.e.ii [National or State Register of Historic Places or State Eligible Sites - Name]	Vassar, Matthew, Estate
E.3.f. [Archeological Sites]	Yes
E.3.i. [Designated River Corridor]	No

FIGURES

Creator: EG Reviewer: KP



Path: B:\GIS\DIG\Projects\FEAF\ARGO\Maps\MXD\2022_11\Fig1_USGS_Location_Map.mxd

Sources:
1. Project Area: LaBella 2022; Regrid 2021
2. Streets: NYS GIS Program Office 2022
3. Basemap: USGS Topo Map

LaBella
Powered by partnership

South Avenue,
City of Poughkeepsie,
Dutchess Co., New York

South Avenue
ARGO Development

LaBella Project No: 2222201
Date: 11/14/2022

USGS Location Map

FIGURE 1

Creator: EG Reviewer: KP

Path: B:\GIS\DIG\Projects\FEAF\ARGO\Maps\MXD\2022_11\Fig2_Orthophoto_Tax_Map.mxd

Sources:
1. Project Area: LaBella 2022
2. Tax Parcels: Regrid 2021
3. Streets: NYS GIS Program Office 2022
4. Basemap: Bing Maps

LaBella
Powered by partnership

South Avenue,
City of Poughkeepsie,
Dutchess Co., New York

South Avenue
ARGO Development

LaBella Project No: 2222201
Date: 11/14/2022

Orthophoto Tax Map

FIGURE 2



Creator: EG Reviewer: KP

Path: B:\GIS\DIG\Projects\FEAF\ARGO\Maps\MXD\2022_11\Fig3_Land Use_Map.mxd

Sources:
1. Project Area: LaBella, 2022
2. Tax Parcels: Regrid, 2021
3. Land Use: Regrid, 2021
4. Streets: NYS GIS Program Office, 2022
5. Basemap: Bing Maps

LaBella
Powered by partnership

South Avenue,
City of Poughkeepsie,
Dutchess Co., New York

South Avenue
ARGO Development

LaBella Project No: 2222201
Date: 11/14/2022

Land Use Map

FIGURE 3

Creator: EG Reviewer: KP

Path: B:\GIS\DIG\Projects\FEAF\ARGO\Maps\MXD\2022_11\Fig4_Soils_Map.mxd

Sources:
1. Project Area: LaBella 2022
2. Soil Map Unit: USDA/NRCS 2021
3. Streets: NYS GIS Program Office 2022
4. Basemap: Bing Maps

LaBella
Powered by partnership

South Avenue,
City of Poughkeepsie,
Dutchess Co., New York

South Avenue
ARGO Development

LaBella Project No: 2222201
Date: 11/14/2022

Soils Map

FIGURE 4



Creator: EG Reviewer: KP

Path: B:\GIS\DIG\Projects\FEAF\ARGO\Maps\MXD\2022_11\Fig5_Wetland_Stream_Floodplain_Map.mxd

Sources:
1. Project Area: LaBella 2022; Regrid 2021
2. NYSDEC Streams: NYSDEC 2021
3. NYSDEC Wetlands: NYSDEC 2006
4. NWI Wetlands: USFWS 2022
5. Flood Zones: FEMA 2021
6. Streets: NYS GIS Program Office 2022
7. Basemap: Bing Maps

LaBella
Powered by partnership

South Avenue,
City of Poughkeepsie,
Dutchess Co., New York

South Avenue
ARGO Development

LaBella Project No: 2222201
Date: 11/14/2022

Wetland, Stream, and Floodplain Map

FIGURE 5

Creator: EG Reviewer: KP

Path: B:\GIS\DIG\Projects\FEAF\ARGO\Maps\MXD\2022_11\Fig6_DEC_ERM_Map.mxd

Sources:
1. Project Area: LaBella 2022
2. Rare Plants or Animals and Significant Natural Communities: NYSDEC Environmental Resource Mapper (ERM) 2022
3. NYSDEC Wetlands: NYSDEC 2006
4. Streets: NYS GIS Program Office 2022
5. Basemap: Bing Maps

LaBella
Powered by partnership

South Avenue,
City of Poughkeepsie,
Dutchess Co., New York

South Avenue
ARGO Development

LaBella Project No: 2222201
Date: 11/15/2022

NYSDEC Environmental Resource Map

FIGURE 6



Creator: EG Reviewer: KP

Path: B:\GIS\DIG\Projects\FEAF\ARGO\Maps\MXD\2022_11\Fig7_CRIS.mxd

Sources:
1. Project Area: LaBella, 2022
2. Archaeologically Sensitive Areas/National Register Sites: NYSOPRHP Cultural Resource Information System (CRIS), 2022
3. Streets: NYS GIS Program Office, 2022
4. Basemap: Bing Maps

LaBella
Powered by partnership

South Avenue,
City of Poughkeepsie,
Dutchess Co., New York

South Avenue
ARGO Development

LaBella Project No: 2222201
Date: 11/15/2022

NYSOPRHP Cultural Resource Information System (CRIS) Map

FIGURE 7



Sources:
1. Project Area: LaBella 2022
2. Streets: NYS GIS Program Office 2022
3. Scenic Resources: NYS GIS Program Office; NYSDEC; NYSDOT; NYSOPRHP; CRIS 2022
4. Basemap: Bing

Note: National and State building districts shown. However, isolated listed and eligible buildings are too many to show at this scale.

LaBella
Powered by partnership

South Avenue,
City of Poughkeepsie,
Dutchess Co., New York

South Avenue
ARGO Development

LaBella Project No: 2222201
Date: 11/15/2022

Publicly Accessible Federal, State, or Local Scenic or Aesthetic Resources Map

FIGURE 8

Creator: EG Reviewer: KP

Path: B:\GIS\DIG\Projects\FEAF\ARGO\Maps\MXD\2022_11\Fig8_Scenic_Resources_Map.mxd

Attachment A
United States Fish and Wildlife Service (USFWS) Informal Species List

IPaC resource list

This report is an automatically generated list of species and other resources such as critical habitat (collectively referred to as *trust resources*) under the U.S. Fish and Wildlife Service's (USFWS) jurisdiction that are known or expected to be on or near the project area referenced below. The list may also include trust resources that occur outside of the project area, but that could potentially be directly or indirectly affected by activities in the project area. However, determining the likelihood and extent of effects a project may have on trust resources typically requires gathering additional site-specific (e.g., vegetation/species surveys) and project-specific (e.g., magnitude and timing of proposed activities) information.

Below is a summary of the project information you provided and contact information for the USFWS office(s) with jurisdiction in the defined project area. Please read the introduction to each section that follows (Endangered Species, Migratory Birds, USFWS Facilities, and NWI Wetlands) for additional information applicable to the trust resources addressed in that section.

NOT FOR CONSULTATION

Location

Dutchess County, New York

Local office

New York Ecological Services Field Office

(607) 753-9334
(607) 753-9699

3817 Luker Road
Cortland, NY 13045-9385

http://www.fws.gov/northeast/nyfo/es/section7.htm

NOT FOR CONSULTATION

Endangered species

This resource list is for informational purposes only and does not constitute an analysis of project level impacts.

The primary information used to generate this list is the known or expected range of each species. Additional areas of influence (AOI) for species are also considered. An AOI includes areas outside of the species range if the species could be indirectly affected by activities in that area (e.g., placing a dam upstream of a fish population even if that fish does not occur at the dam site, may indirectly impact the species by reducing or eliminating water flow downstream). Because species can move, and site conditions can change, the species on this list are not guaranteed to be found on or near the project area. To fully determine any potential effects to species, additional site-specific and project-specific information is often required.

Section 7 of the Endangered Species Act **requires** Federal agencies to "request of the Secretary information whether any species which is listed or proposed to be listed may be present in the area of such proposed action" for any project that is conducted, permitted, funded, or licensed by any Federal agency. A letter from the local office and a species list which fulfills this requirement can **only** be obtained by requesting an official species list from either the Regulatory Review section in IPaC (see directions below) or from the local field office directly.

For project evaluations that require USFWS concurrence/review, please return to the IPaC website and request an official species list by doing the following:

1. Draw the project location and click CONTINUE.
2. Click DEFINE PROJECT.
3. Log in (if directed to do so).
4. Provide a name and description for your project.
5. Click REQUEST SPECIES LIST.

Listed species[1] and their critical habitats are managed by the Ecological Services Program of the U.S. Fish and Wildlife Service (USFWS) and the fisheries division of the National Oceanic and Atmospheric Administration (NOAA Fisheries[2]).

Species and critical habitats under the sole responsibility of NOAA Fisheries are **not** shown on this list. Please contact NOAA Fisheries for species under their jurisdiction.

---

1. Species listed under the Endangered Species Act are threatened or endangered; IPaC also shows species that are candidates, or proposed, for listing. See the listing status page for more information. IPaC only shows species that are regulated by USFWS (see FAQ).

NOT FOR CONSULTATION

2. NOAA Fisheries, also known as the National Marine Fisheries Service (NMFS), is an office of the National Oceanic and Atmospheric Administration within the Department of Commerce.

The following species are potentially affected by activities in this location:

Mammals

NAME	STATUS
Indiana Bat Myotis sodalis Wherever found There is **final** critical habitat for this species. The location of the critical habitat is not available. https://ecos.fws.gov/ecp/species/5949	Endangered

Insects

NAME	STATUS
Monarch Butterfly Danaus plexippus Wherever found No critical habitat has been designated for this species. https://ecos.fws.gov/ecp/species/9743	Candidate

Critical habitats

Potential effects to critical habitat(s) in this location must be analyzed along with the endangered species themselves.

THERE ARE NO CRITICAL HABITATS AT THIS LOCATION.

NOT FOR CONSULTATION

Migratory birds

Certain birds are protected under the Migratory Bird Treaty Act[1] and the Bald and Golden Eagle Protection Act[2].

Any person or organization who plans or conducts activities that may result in impacts to migratory birds, eagles, and their habitats should follow appropriate regulations and consider implementing appropriate conservation measures, as described below.

1. The Migratory Birds Treaty Act of 1918.
2. The Bald and Golden Eagle Protection Act of 1940.

Additional information can be found using the following links:

- Birds of Conservation Concern https://www.fws.gov/program/migratory-birds/species
- Measures for avoiding and minimizing impacts to birds https://www.fws.gov/library/collections/avoiding-and-minimizing-incidental-take-migratory-birds
- Nationwide conservation measures for birds https://www.fws.gov/sites/default/files/documents/nationwide-standard-conservation-measures.pdf

The birds listed below are birds of particular concern either because they occur on the USFWS Birds of Conservation Concern (BCC) list or warrant special attention in your project location. To learn more about the levels of concern for birds on your list and how this list is generated, see the FAQ below. This is not a list of every bird you may find in this location, nor a guarantee that every bird on this list will be found in your project area. To see exact locations of where birders and the general public have sighted birds in and around your project area, visit the E-bird data mapping tool (Tip: enter your location, desired date range and a species on your list). For projects that occur off the Atlantic Coast, additional maps and models detailing the relative occurrence and abundance of bird species on your list are available. Links to additional information about Atlantic Coast birds, and other important information about your migratory bird list, including how to properly interpret and use your migratory bird report, can be found below.

For guidance on when to schedule activities or implement avoidance and minimization measures to reduce impacts to migratory birds on your list, click on the PROBABILITY OF PRESENCE SUMMARY at the top of your list to see when these birds are most likely to be present and breeding in your project area.

NOT FOR CONSULTATION

NAME	BREEDING SEASON (IF A BREEDING SEASON IS INDICATED FOR A BIRD ON YOUR LIST, THE BIRD MAY BREED IN YOUR PROJECT AREA SOMETIME WITHIN THE TIMEFRAME SPECIFIED, WHICH IS A VERY LIBERAL ESTIMATE OF THE DATES INSIDE WHICH THE BIRD BREEDS ACROSS ITS ENTIRE RANGE. "BREEDS ELSEWHERE" INDICATES THAT THE BIRD DOES NOT LIKELY BREED IN YOUR PROJECT AREA.)

Bald Eagle *Haliaeetus leucocephalus* This is not a Bird of Conservation Concern (BCC) in this area, but warrants attention because of the Eagle Act or for potential susceptibilities in offshore areas from certain types of development or activities. https://ecos.fws.gov/ecp/species/1626	Breeds Dec 1 to Aug 31
Blue-winged Warbler *Vermivora pinus* This is a Bird of Conservation Concern (BCC) only in particular Bird Conservation Regions (BCRs) in the continental USA	Breeds May 1 to Jun 30
Canada Warbler *Cardellina canadensis* This is a Bird of Conservation Concern (BCC) throughout its range in the continental USA and Alaska.	Breeds May 20 to Aug 10
Eastern Whip-poor-will *Antrostomus vociferus* This is a Bird of Conservation Concern (BCC) throughout its range in the continental USA and Alaska.	Breeds May 1 to Aug 20
Prairie Warbler *Dendroica discolor* This is a Bird of Conservation Concern (BCC) throughout its range in the continental USA and Alaska.	Breeds May 1 to Jul 31
Red-headed Woodpecker *Melanerpes erythrocephalus* This is a Bird of Conservation Concern (BCC) throughout its range in the continental USA and Alaska.	Breeds May 10 to Sep 10
Wood Thrush *Hylocichla mustelina* This is a Bird of Conservation Concern (BCC) throughout its range in the continental USA and Alaska.	Breeds May 10 to Aug 31

NOT FOR CONSULTATION

Probability of Presence Summary

The graphs below provide our best understanding of when birds of concern are most likely to be present in your project area. This information can be used to tailor and schedule your project activities to avoid or minimize impacts to birds. Please make sure you read and understand the FAQ "Proper Interpretation and Use of Your Migratory Bird Report" before using or attempting to interpret this report.

Probability of Presence (■)

Each green bar represents the bird's relative probability of presence in the 10km grid cell(s) your project overlaps during a particular week of the year. (A year is represented as 12 4-week months.) A taller bar indicates a higher probability of species presence. The survey effort (see below) can be used to establish a level of confidence in the presence score. One can have higher confidence in the presence score if the corresponding survey effort is also high.

How is the probability of presence score calculated? The calculation is done in three steps:

1. The probability of presence for each week is calculated as the number of survey events in the week where the species was detected divided by the total number of survey events for that week. For example, if in week 12 there were 20 survey events and the Spotted Towhee was found in 5 of them, the probability of presence of the Spotted Towhee in week 12 is 0.25.
2. To properly present the pattern of presence across the year, the relative probability of presence is calculated. This is the probability of presence divided by the maximum probability of presence across all weeks. For example, imagine the probability of presence in week 20 for the Spotted Towhee is 0.05, and that the probability of presence at week 12 (0.25) is the maximum of any week of the year. The relative probability of presence on week 12 is 0.25/0.25 = 1; at week 20 it is 0.05/0.25 = 0.2.
3. The relative probability of presence calculated in the previous step undergoes a statistical conversion so that all possible values fall between 0 and 10, inclusive. This is the probability of presence score.

To see a bar's probability of presence score, simply hover your mouse cursor over the bar.

Breeding Season (■)
Yellow bars denote a very liberal estimate of the time-frame inside which the bird breeds across its entire range. If there are no yellow bars shown for a bird, it does not breed in your project area.

Survey Effort (|)
Vertical black lines superimposed on probability of presence bars indicate the number of surveys performed for that species in the 10km grid cell(s) your project area overlaps. The number of surveys is expressed as a range, for example, 33 to 64 surveys.

To see a bar's survey effort range, simply hover your mouse cursor over the bar.

No Data (–)
A week is marked as having no data if there were no survey events for that week.

Survey Timeframe
Surveys from only the last 10 years are used in order to ensure delivery of currently relevant information. The exception to this is areas off the Atlantic coast, where bird returns are based on all years of available data, since data in these areas is currently much more sparse.

NOT FOR CONSULTATION

■ probability of presence ■ breeding season | survey effort – no data

NOT FOR CONSULTATION

Eastern Whip-poor-will BCC Rangewide (CON) (This is a Bird of Conservation Concern (BCC) throughout its range in the continental USA and Alaska.)



Prairie Warbler BCC Rangewide (CON) (This is a Bird of Conservation Concern (BCC) throughout its range in the continental USA and Alaska.)



Red-headed Woodpecker BCC Rangewide (CON) (This is a Bird of Conservation Concern (BCC) throughout its range in the continental USA and Alaska.)

Wood Thrush BCC Rangewide (CON) (This is a Bird of Conservation Concern (BCC) throughout its range in the continental USA and Alaska.)

NOT FOR CONSULTATION

Tell me more about conservation measures I can implement to avoid or minimize impacts to migratory birds.

Nationwide Conservation Measures describes measures that can help avoid and minimize impacts to all birds at any location year round. Implementation of these measures is particularly important when birds are most likely to occur in the project area. When birds may be breeding in the area, identifying the

locations of any active nests and avoiding their destruction is a very helpful impact minimization measure. To see when birds are most likely to occur and be breeding in your project area, view the Probability of Presence Summary. Additional measures or permits may be advisable depending on the type of activity you are conducting and the type of infrastructure or bird species present on your project site.

What does IPaC use to generate the migratory birds potentially occurring in my specified location?

The Migratory Bird Resource List is comprised of USFWS Birds of Conservation Concern (BCC) and other species that may warrant special attention in your project location.

The migratory bird list generated for your project is derived from data provided by the Avian Knowledge Network (AKN). The AKN data is based on a growing collection of survey, banding, and citizen science datasets and is queried and filtered to return a list of those birds reported as occurring in the 10km grid cell(s) which your project intersects, and that have been identified as warranting special attention because they are a BCC species in that area, an eagle (Eagle Act requirements may apply), or a species that has a particular vulnerability to offshore activities or development.

Again, the Migratory Bird Resource list includes only a subset of birds that may occur in your project area. It is not representative of all birds that may occur in your project area. To get a list of all birds potentially present in your project area, please visit the AKN Phenology Tool.

What does IPaC use to generate the probability of presence graphs for the migratory birds potentially occurring in my specified location?

The probability of presence graphs associated with your migratory bird list are based on data provided by the Avian Knowledge Network (AKN). This data is derived from a growing collection of survey, banding, and citizen science datasets .

Probability of presence data is continuously being updated as new and better information becomes available. To learn more about how the probability of presence graphs are produced and how to interpret them, go the Probability of Presence Summary and then click on the "Tell me about these graphs" link.

How do I know if a bird is breeding, wintering, migrating or present year-round in my project area?

To see what part of a particular bird's range your project area falls within (i.e. breeding, wintering, migrating or year-round), you may refer to the following resources: The Cornell Lab of Ornithology All About Birds Bird Guide, or (if you are unsuccessful in locating the bird of interest there), the Cornell Lab of Ornithology Neotropical Birds guide. If a bird on your migratory bird species list has a breeding season associated with it, if that bird does occur in your project area, there may be nests present at some point within the timeframe specified. If "Breeds elsewhere" is indicated, then the bird likely does not breed in your project area.

What are the levels of concern for migratory birds?

Migratory birds delivered through IPaC fall into the following distinct categories of concern:

1. "BCC Rangewide" birds are Birds of Conservation Concern (BCC) that are of concern throughout their range anywhere within the USA (including Hawaii, the Pacific Islands, Puerto Rico, and the Virgin Islands);
2. "BCC - BCR" birds are BCCs that are of concern only in particular Bird Conservation Regions (BCRs) in the continental USA; and

NOT FOR CONSULTATION

3. "Non-BCC - Vulnerable" birds are not BCC species in your project area, but appear on your list either because of the Eagle Act requirements (for eagles) or (for non-eagles) potential susceptibilities in offshore areas from certain types of development or activities (e.g. offshore energy development or longline fishing).

Although it is important to try to avoid and minimize impacts to all birds, efforts should be made, in particular, to avoid and minimize impacts to the birds on this list, especially eagles and BCC species of rangewide concern. For more information on conservation measures you can implement to help avoid and minimize migratory bird impacts and requirements for eagles, please see the FAQs for these topics.

Details about birds that are potentially affected by offshore projects

For additional details about the relative occurrence and abundance of both individual bird species and groups of bird species within your project area off the Atlantic Coast, please visit the Northeast Ocean Data Portal. The Portal also offers data and information about other taxa besides birds that may be helpful to you in your project review. Alternately, you may download the bird model results files underlying the portal maps through the NOAA NCCOS Integrative Statistical Modeling and Predictive Mapping of Marine Bird Distributions and Abundance on the Atlantic Outer Continental Shelf project webpage.

Bird tracking data can also provide additional details about occurrence and habitat use throughout the year, including migration. Models relying on survey data may not include this information. For additional information on marine bird tracking data, see the Diving Bird Study and the nanotag studies or contact Caleb Spiegel or Pam Loring.

What if I have eagles on my list?

If your project has the potential to disturb or kill eagles, you may need to obtain a permit to avoid violating the Eagle Act should such impacts occur.

Proper Interpretation and Use of Your Migratory Bird Report

The migratory bird list generated is not a list of all birds in your project area, only a subset of birds of priority concern. To learn more about how your list is generated, and see options for identifying what other birds may be in your project area, please see the FAQ "What does IPaC use to generate the migratory birds potentially occurring in my specified location". Please be aware this report provides the "probability of presence" of birds within the 10 km grid cell(s) that overlap your project; not your exact project footprint. On the graphs provided, please also look carefully at the survey effort (indicated by the black vertical bar) and for the existence of the "no data" indicator (a red horizontal bar). A high survey effort is the key component. If the survey effort is high, then the probability of presence score can be viewed as more dependable. In contrast, a low survey effort bar or no data bar means a lack of data and, therefore, a lack of certainty about presence of the species. This list is not perfect; it is simply a starting point for identifying what birds of concern have the potential to be in your project area, when they might be there, and if they might be breeding (which means nests might be present). The list helps you know what to look for to confirm presence, and helps guide you in knowing when to implement conservation measures to avoid or minimize potential impacts from your project activities, should presence be confirmed. To learn more about conservation measures, visit the FAQ "Tell me about conservation measures I can implement to avoid or minimize impacts to migratory birds" at the bottom of your migratory bird trust resources page.

NOT FOR CONSULTATION

Coastal Barrier Resources System

Projects within the John H. Chafee Coastal Barrier Resources System (CBRS) may be subject to the restrictions on federal expenditures and financial assistance and the consultation requirements of the Coastal Barrier Resources Act (CBRA) (16 U.S.C. 3501 et seq.). For more information, please contact the local Ecological Services Field Office or visit the CBRA Consultations website. The CBRA website provides tools such as a flow chart to help determine whether consultation is required and a template to facilitate the consultation process.

THERE ARE NO KNOWN COASTAL BARRIERS AT THIS LOCATION.

Data limitations

The CBRS boundaries used in IPaC are representations of the controlling boundaries, which are depicted on the official CBRS maps. The boundaries depicted in this layer are not to be considered authoritative for in/out determinations close to a CBRS boundary (i.e., within the "CBRS Buffer Zone" that appears as a hatched area on either side of the boundary). For projects that are very close to a CBRS boundary but do not clearly intersect a unit, you may contact the Service for an official determination by following the instructions here: https://www.fws.gov/service/coastal-barrier-resources-system-property-documentation

Data exclusions

CBRS units extend seaward out to either the 20- or 30-foot bathymetric contour (depending on the location of the unit). The true seaward extent of the units is not shown in the CBRS data, therefore projects in the offshore areas of units (e.g., dredging, breakwaters, offshore wind energy or oil and gas projects) may be subject to CBRA even if they do not intersect the CBRS data. For additional information, please contact CBRA@fws.gov.

NOT FOR CONSULTATION

Facilities

Wildlife refuges and fish hatcheries

REFUGE AND FISH HATCHERY INFORMATION IS NOT AVAILABLE AT THIS TIME

Wetlands in the National Wetlands Inventory

Impacts to NWI wetlands and other aquatic habitats may be subject to regulation under Section 404 of the Clean Water Act, or other State/Federal statutes.

For more information please contact the Regulatory Program of the local U.S. Army Corps of Engineers District.

WETLAND INFORMATION IS NOT AVAILABLE AT THIS TIME

This can happen when the National Wetlands Inventory (NWI) map service is unavailable, or for very large projects that intersect many wetland areas. Try again, or visit the NWI map to view wetlands at this location.

Data limitations

The Service's objective of mapping wetlands and deepwater habitats is to produce reconnaissance level information on the location, type and size of these resources. The maps are prepared from the analysis of high altitude imagery. Wetlands are identified based on vegetation, visible hydrology and geography. A margin of error is inherent in the use of imagery; thus, detailed on-the-ground inspection of any particular site may result in revision of the wetland boundaries or classification established through image analysis.

The accuracy of image interpretation depends on the quality of the imagery, the experience of the image analysts, the amount and quality of the collateral data and the amount of ground truth verification work conducted. Metadata should be consulted to determine the date of the source imagery used and any mapping problems.

Wetlands or other mapped features may have changed since the date of the imagery or field work. There may be occasional differences in polygon boundaries or classifications between the information depicted on the map and the actual conditions on site.

Data exclusions

Certain wetland habitats are excluded from the National mapping program because of the limitations of aerial imagery as the primary data source used to detect wetlands. These habitats include seagrasses or submerged aquatic vegetation that are found in the intertidal and subtidal zones of estuaries and nearshore coastal waters. Some deepwater reef communities (coral or tuberficid worm reefs) have also been excluded from the inventory. These habitats, because of their depth, go undetected by aerial imagery.

Data precautions

Federal, state, and local regulatory agencies with jurisdiction over wetlands may define and describe wetlands in a different manner than that used in this inventory. There is no attempt, in either the design or products of this inventory, to define the limits of proprietary jurisdiction of any Federal, state, or local government or to establish the geographical scope of the regulatory programs of government agencies. Persons intending to engage in activities involving modifications within or adjacent to wetland areas should seek the advice of appropriate federal, state, or local agencies concerning specified agency regulatory programs and proprietary jurisdictions that may affect such activities.

NOT FOR CONSULTATION

THE CITY OF POUGHKEEPSIE
NEW YORK
DEVELOPMENT DEPARTMENT
62 CIVIC CENTER PLAZA, 2ND FLOOR
POUGHKEEPSIE, NY 12601
Phone: (845) 451-4263 Fax: (845) 451-4006

MEMORANDUM

To: ARGO Development, Applicant

From: Natalie Quinn, Development Director

Date: February 17, 2023

Re: South Avenue #937583, #PB2023-055 - SEQRA Classification

Upon review of project materials provided by the applicant, including Short EAF Part 1 and site plan application, it is my understanding that the proposed action to be undertaken includes the construction of an 87 unit, 5 story mid-rise multifamily residential development with underground and surface-level parking.

Based on the above description it is the determination of the planning division that the proposed action is classified as an Unlisted Action with regards to SEQRA, and therefore is subject to an uncoordinated or coordinated (optional) environmental review. This determination was made due to the fact that the proposed action was not expressly listed in 6 NYCRR Section 617.4 (Type I Actions) or 617.5 (Type II Actions).

January 27, 2023

Ms. Anne Saylor, Chair
Poughkeepsie Planning Board
62 Civic Center Plaza
3rd Floor
Poughkeepsie, NY 12601

RE: Parking Assessment
South Avenue Multifamily Development
City of Poughkeepsie, NY
LaBella Project: 2222201

Dear Ms. Saylor:

LaBella Associates has completed a Parking Generation Assessment for the South Avenue Multifamily Development in the City of Poughkeepsie. The purpose of this assessment is to compare the number of parking spaces proposed for the project against industry standards, the city's zoning code, and other local zoning codes.

The South Avenue Multifamily Development consists of 87 single bedroom apartment units with 115 parking spaces. The Institute of Transportation Engineers' (ITE) *Parking Generation Manual, 5th Edition*, is the industry standard for estimating parking spaces for proposed land uses based on studies of similar existing developments. Land use code (LUC) 221 for Multifamily Housing (mid-rise) was used to estimate the number of parking spaces for the project. A range of parking rates is provided in *Parking Generation* that include the average rate, the 33rd percentile rate, and the 85th percentile rate. The parking generation is summarized in Table 1.

Table 1 – Parking Generation Summary

LUC 221 Multifamily Housing (Mid-rise)		
	Rate	**Spaces**
Average	0.75	65
33rd Percentile	0.65	57
85th Percentile	0.87	76

Rate: spaces per bedroom

As the table shows, the proposed number of parking spaces exceeds the estimates provided by *Parking Generation*. The parking results from the *Parking Generation Manual* are attached.

The city's draft zoning code requires 1.25 spaces per bedroom which totals 112 spaces. The City of Newburgh requires 0.75 spaces per bedroom (65 spaces) and the City of Beacon requires 1.0 space for each dwelling unit (87 spaces).

Based on ITE's industry parking standard and other local city zoning codes, it is LaBella's professional opinion that the project is proposing sufficient parking at 115 spaces. We are providing this information to you for review as the applicant will be seeking an area variance for parking from the Zoning Board of Appeals.

Respectfully submitted,

LaBella Associates



Thomas R. Johnson, P.E., PTOE
Senior Transporation Engineer

Attachment

Multifamily Housing (Mid-Rise)
(221)

Peak Period Parking Demand vs: **Bedrooms**
On a: **Weekday (Monday - Friday)**
Setting/Location: **General Urban/Suburban (no nearby rail transit)**
Peak Period of Parking Demand: **10:00 p.m. - 5:00 a.m.**
Number of Studies: 35
Avg. Num. of Bedrooms: 294

Peak Period Parking Demand per Bedroom

Average Rate	Range of Rates	33rd / 85th Percentile	95% Confidence Interval	Standard Deviation (Coeff. of Variation)
0.75	0.41 - 1.00	0.65 / 0.87	0.70 - 0.80	0.15 (20%)

Data Plot and Equation



Parking Generation Manual, 5th Edition ● Institute of Transportation Engineers

Hydraulic Overview

Job Number: 2497
Report Description: Ordinary Group I

Job

Job Number: 2497	Design Engineer: Paul Tirums
Job Name: South Avenue	Phone: 914-490-3269
Address 1: Multi-Family Development	State Certification/License Number: 073178-1
Address 2: Poughkeepsie, NY 12601	AHJ: City of Poughkeepsie
Address 3:	Job Site/Building: Parking Garage

System

Density: 0.15 gpm/ft²	Area of Application: 2030 ft² (Actual 2030 ft²)
Most Demanding Sprinkler Data: 5.6 K-Factor 19.50 at 12.125	Hose Streams: 250.00
Coverage Per Sprinkler: 130 ft²	Number Of Sprinklers Calculated: 17 0
System Pressure Demand: 51.679	System Flow Demand: 350.08
Total Demand: 600.08 @ 51.679	Pressure Result: +30.140 (36.8%)

Supplies

Node	Name	Flow(gpm)	Hose Flow(gpm)	Static(psi)	Residual(psi)
110	Water Supply	919.00	250.00	110.000	48.000

Check Point Gauges

Identifier	Pressure(psi)	K-Factor(K)	Flow(gpm)

Garage 1.17.23.cad



Water Supply at Node 110 (919.00, 0.00, 110.000, 48.000)



Hydraulic Summary

Job

Job Number: 2497	Design Engineer: Paul Tirums
Job Name: South Avenue	State Certification/License Number: 073178-1
Address 1: Multi-Family Development	AHJ: City of Poughkeepsie
Address 2: Poughkeepsie, NY 12601	Job Site/Building: Parking Garage
Address 3:	Drawing Name: Garage 1.17.23.cad

System

Most Demanding Sprinkler Data: 5.6 K-Factor 19.50 at 12.125

Hose Allowance At Source: 250.00

Additional Hose Supplies

Node	Flow(gpm)

Total Hose Streams: 250.00

System Flow Demand	Total Water Required (Including Hose Allowance)
350.08	600.08

Maximum Pressure Unbalance In Loops: 0.000

Maximum Velocity Above Ground: 11.71 between nodes 106 and 118

Maximum Velocity Under Ground: 3.63 between nodes 110 and 109

Volume capacity of Wet Pipes	Volume capacity of Dry Pipes
115.93 gal	497.93 gal

Remote Area(s)

Occupancy	Job Suffix
Ordinary Group I	

Density	Area of Application
0.15 gpm/ft²	2030 ft² (Actual 2030 ft²)

Number Of Sprinklers Calculated	Number Of Nozzles Calculatec	Coverage Per Sprinkler
17	0	130 ft²

AutoPeak Results: Pressure For Remote Area(s) Adjacent To Most Remote Area: Right: 50.322

Supplies

Node	Name	Hose Flow (gpm)	Static (psi)	Residual (psi)	@	Flow (gpm)	Available (psi)	@	Total Demand (gpm)	Required (psi)	Safety Margin (psi)
110	Water Supply	250.00	110.000	48.000		919.00	81.820		600.08	51.679	30.140

Contractor

Contractor Number: 21		Contact Name: Amie Gerundo	Contact Title: Designer
Name of Contractor: Calculated Fire Protection		Phone: 845-677-5201	Extension: 7
Address 1: 2510 Route 44		FAX:	
Address 2: Salt Point, NY 12578		E-mail: Amie@calculatedfire.com	
Address 3:		Web-Site: Calculatedfire.com	

Water Supply at Node 110



Hydraulic Graph
Water Supply at Node 110

Static: Pressure
110.000

Residual: Pressure
48.000 @ 919.00

Available Pressure at System Demand
81.820 @ 600.08

Required Pressure at System Demand
51.679 @ 350.08

Required Pressure at System Demand (Including Hose Allowance at Source)
51.679 @ 600.08

Summary Of Outflowing Devices

Job Number: 2497
Report Description: Ordinary Group I

Device		Actual Flow (gpm)	Minimum Flow (gpm)	K-Factor (K)	Pressure (psi)
⇨ **Sprinkler**	**1**	**19.50**	**19.50**	**5.6**	**12.125**
Sprinkler	2	19.54	19.50	5.6	12.176
Sprinkler	3	19.63	19.50	5.6	12.290
Sprinkler	4	19.67	19.50	5.6	12.341
Sprinkler	5	19.69	19.50	5.6	12.357
Sprinkler	6	19.82	19.50	5.6	12.524
Sprinkler	7	20.10	19.50	5.6	12.886
Sprinkler	8	20.14	19.50	5.6	12.939
Sprinkler	9	20.29	19.50	5.6	13.131
Sprinkler	10	21.08	19.50	5.6	14.170
Sprinkler	11	21.12	19.50	5.6	14.228
Sprinkler	12	21.28	19.50	5.6	14.438
Sprinkler	13	21.37	19.50	5.6	14.567
Sprinkler	14	21.44	19.50	5.6	14.656
Sprinkler	15	21.52	19.50	5.6	14.762
Sprinkler	16	21.58	19.50	5.6	14.851
Sprinkler	17	22.31	19.50	5.6	15.865

⇨ Most Demanding Sprinkler Data

Node Analysis

Job Number: 2497
Report Description: Ordinary Group I

Node	Elevation(Foot)	Fittings	Pressure(psi)	Discharge(gpm)	
1	0'-3	Spr(-12.125)	12.125	19.50	
2	0'-3	Spr(-12.176)	12.176	19.54	
3	0'-3	Spr(-12.290)	12.290	19.63	
4	0'-3	Spr(-12.341)	12.341	19.67	
5	0'-3	Spr(-12.357)	12.357	19.69	
6	0'-3	Spr(-12.524)	12.524	19.82	
7	0'-3	Spr(-12.886)	12.886	20.10	
8	0'-3	Spr(-12.939)	12.939	20.14	
9	0'-3	Spr(-13.131)	13.131	20.29	
10	0'-3	Spr(-14.170)	14.170	21.08	
11	0'-3	Spr(-14.228)	14.228	21.12	
12	0'-3	Spr(-14.438)	14.438	21.28	
13	0'-3	Spr(-14.567)	14.567	21.37	
14	0'-3	Spr(-14.656)	14.656	21.44	
15	0'-3	Spr(-14.762)	14.762	21.52	
16	0'-3	Spr(-14.851)	14.851	21.58	
17	0'-3	Spr(-15.865)	15.865	22.31	
110	-4'-0	S	51.679	350.08	
100	-0'-10½	PO(3'-7)	13.433		
101	-0'-10½	PO(3'-7)	13.607		
102	-0'-10½	PO(3'-7)	14.241		
103	-0'-10½	PO(3'-7)	15.604		
104	-0'-10½	PO(7'-0½)	17.435		
105	-0'-10½	PO(7'-0½)	17.504		
106	-0'-10½	PO(7'-0½)	17.752		
107	-6'-5		35.012		
108	-8'-0	T(37'-8½)	46.128		
109	-4'-0	E(17'-7)	51.551		
111	-0'-10½	PO(3'-7)	13.486		
112	-0'-10½	PO(3'-7)	13.661		
113	-0'-10½	PO(3'-7)	14.297		
114	-0'-10½	PO(3'-7)	15.666		
115	-0'-10½	PO(3'-7)	13.679		
116	-0'-10½	PO(3'-7)	13.857		
117	-0'-10½	PO(3'-7)	14.501		
118	-0'-10½	PO(3'-7)	15.889		
119	-0'-10½	PO(3'-7)	16.026		
120	-0'-10½	PO(3'-7)	16.233		
121	-0'-10½	PO(3'-7)	16.120		
122	-0'-10½	PO(3'-7)	16.328		
123	-0'-10½	PO(3'-7)	17.403		

Pipe Type / Downstream / Upstream	Diameter / Elevation	Flow / Discharge	Velocity / K-Factor	HWC / Pt / Pn	Friction Loss / Fittings	Length / Eq. Length / Total Length	Pressure / Summary
• • • • • Route 1 • • • • •							
SP	1.0490	19.50	7.24	100	0.173991	1'-1½	Pf 0.817
1	0'-3	19.50	5.6	12.125	Sprinkler,	3'-7	Pe 0.490
100	-0'-10½			13.433	PO(3'-7)	4'-8½	Pv
BL	1.6820	19.50	2.82	100	0.017455	10'-0	Pf 0.175
100	-0'-10½			13.433			Pe
101	-0'-10½			13.607		10'-0	Pv
BL	1.6820	39.13	5.65	100	0.063320	10'-0	Pf 0.633
101	-0'-10½	19.63		13.607	Flow (q) from Route 3		Pe
102	-0'-10½			14.241		10'-0	Pv
BL	1.6820	59.23	8.55	100	0.136339	10'-0	Pf 1.363
102	-0'-10½	20.10		14.241	Flow (q) from Route 7		Pe
103	-0'-10½			15.604		10'-0	Pv
BL	1.6820	80.31	11.60	100	0.239457	0'-7	Pf 1.831
103	-0'-10½	21.08		15.604	Flow (q) from Route 10	7'-0½	Pe
104	-0'-10½			17.435	PO(7'-0½)	7'-8	Pv
CM	4.2600	123.20	2.77	100	0.005722	12'-0	Pf 0.069
104	-0'-10½	42.89		17.435	Flow (q) from Route 13		Pe 0.000
105	-0'-10½			17.504		12'-0	Pv
CM	4.2600	246.70	5.55	100	0.020674	12'-0	Pf 0.248
105	-0'-10½	80.48 + 43.02		17.504	Flow (q) from Route 2 and 14		Pe
106	-0'-10½			17.752		12'-0	Pv
CM	4.2600	350.08	7.88	100	0.039503	344'-3½	Pf 14.861
106	-0'-10½	81.07 + 22.31		17.752	Flow (q) from Route 5 and 17	31'-11	Pe 2.399
107	-6'-5			35.012	Ee2(3'-9), 3E(9'-4½), 2f(-0.000)	376'-2½	Pv
CM	4.2600	350.08	7.88	120	0.028193	2'-1	Pf 10.430
107	-6'-5			35.012		13'-2	Pe 0.686
108	-8'-0			46.128	DPV(-10.000), E(13'-2)	15'-3	Pv
FR	6.3570	350.08	3.54	120	0.004014	4'-0	Pf 7.157
108	-8'-0			46.128		35'-2½	Pe -1.734
109	-4'-0			51.551	BFP(-7.000), 2E(17'-7)	39'-2½	Pv
UG	6.2800	350.08	3.63	140	0.003202	40'-0	Pf 0.128
109	-4'-0			51.551			Pe
110	-4'-0			51.679	Water Supply	40'-0	Pv
		250.00			Hose Allowance At Source		
110		600.08					
• • • • • Route 2 • • • • •							
SP	1.0490	19.54	7.25	100	0.174657	1'-1½	Pf 0.820
2	0'-3	19.54	5.6	12.176	Sprinkler,	3'-7	Pe 0.490
111	-0'-10½			13.486	PO(3'-7)	4'-8½	Pv
BL	1.6820	19.54	2.82	100	0.017522	10'-0	Pf 0.175
111	-0'-10½			13.486			Pe
112	-0'-10½			13.661		10'-0	Pv
BL	1.6820	39.21	5.66	100	0.063563	10'-0	Pf 0.636
112	-0'-10½	19.67		13.661	Flow (q) from Route 4		Pe
113	-0'-10½			14.297		10'-0	Pv
BL	1.6820	59.36	8.57	100	0.136861	10'-0	Pf 1.369
113	-0'-10½	20.14		14.297	Flow (q) from Route 8		Pe
114	-0'-10½			15.666		10'-0	Pv
BL	1.6820	80.48	11.62	100	0.240371	0'-7	Pf 1.838
114	-0'-10½	21.12		15.666	Flow (q) from Route 11	7'-0½	Pe 0.000
105	-0'-10½			17.504	PO(7'-0½)	7'-8	Pv
• • • • • Route 3 • • • • •							
SP	1.0490	19.63	7.29	100	0.176171	1'-1½	Pf 0.827
3	0'-3	19.63	5.6	12.290	Sprinkler,	3'-7	Pe 0.490
101	-0'-10½			13.607	PO(3'-7)	4'-8½	Pv
• • • • • Route 4 • • • • •							
SP	1.0490	19.67	7.30	100	0.176845	1'-1½	Pf 0.831
4	0'-3	19.67	5.6	12.341	Sprinkler,	3'-7	Pe 0.490
112	-0'-10½			13.661	PO(3'-7)	4'-8½	Pv
• • • • • Route 5 • • • • •							
SP	1.0490	19.69	7.31	100	0.177065	1'-1½	Pf 0.832
5	0'-3	19.69	5.6	12.357	Sprinkler,	3'-7	Pe 0.490
115	-0'-10½			13.679	PO(3'-7)	4'-8½	Pv
BL	1.6820	19.69	2.84	100	0.017764	10'-0	Pf 0.178
115	-0'-10½			13.679			Pe
116	-0'-10½			13.857		10'-0	Pv

Pipe Type / Downstream / Upstream	Diameter / Elevation	Flow / Discharge	Velocity / K-Factor	HWC Pt	Pn	Friction Loss / Fittings	Length / Eq. Length / Total Length	Pressure Summary
BL	1.6820	39.50	5.70	100		0.064439	10'-0	Pf 0.644
116	-0'-10½	19.82		13.857		Flow (q) from Route 6		Pe
117	-0'-10½			14.501			10'-0	Pv
BL	1.6820	59.80	8.63	100		0.138744	10'-0	Pf 1.387
117	-0'-10½	20.29		14.501		Flow (q) from Route 9		Pe
118	-0'-10½			15.889			10'-0	Pv
BL	1.6820	81.07	11.71	100		0.243671	0'-7	Pf 1.864
118	-0'-10½	21.28		15.889		Flow (q) from Route 12	7'-0½	Pe 0.000
106	-0'-10½			17.752		PO(7'-0½)	7'-8	Pv
• • • • • Route 6 • • • • •								
SP	1.0490	19.82	7.36	100		0.179280	1'-1½	Pf 0.842
6	0'-3	19.82	5.6	12.524		Sprinkler,	3'-7	Pe 0.490
116	-0'-10½			13.857		PO(3'-7)	4'-8½	Pv
• • • • • Route 7 • • • • •								
SP	1.0490	20.10	7.46	100		0.184061	1'-1½	Pf 0.864
7	0'-3	20.10	5.6	12.886		Sprinkler,	3'-7	Pe 0.490
102	-0'-10½			14.241		PO(3'-7)	4'-8½	Pv
• • • • • Route 8 • • • • •								
SP	1.0490	20.14	7.48	100		0.184763	1'-1½	Pf 0.868
8	0'-3	20.14	5.6	12.939		Sprinkler,	3'-7	Pe 0.490
113	-0'-10½			14.297		PO(3'-7)	4'-8½	Pv
• • • • • Route 9 • • • • •								
SP	1.0490	20.29	7.53	100		0.187300	1'-1½	Pf 0.880
9	0'-3	20.29	5.6	13.131		Sprinkler,	3'-7	Pe 0.490
117	-0'-10½			14.501		PO(3'-7)	4'-8½	Pv
• • • • • Route 10 • • • • •								
SP	1.0490	21.08	7.83	100		0.200965	1'-1½	Pf 0.944
10	0'-3	21.08	5.6	14.170		Sprinkler,	3'-7	Pe 0.490
103	-0'-10½			15.604		PO(3'-7)	4'-8½	Pv
• • • • • Route 11 • • • • •								
SP	1.0490	21.12	7.84	100		0.201727	1'-1½	Pf 0.947
11	0'-3	21.12	5.6	14.228		Sprinkler,	3'-7	Pe 0.490
114	-0'-10½			15.666		PO(3'-7)	4'-8½	Pv
• • • • • Route 12 • • • • •								
SP	1.0490	21.28	7.90	100		0.204479	1'-1½	Pf 0.960
12	0'-3	21.28	5.6	14.438		Sprinkler,	3'-7	Pe 0.490
118	-0'-10½			15.889		PO(3'-7)	4'-8½	Pv
• • • • • Route 13 • • • • •								
SP	1.0490	21.37	7.93	100		0.206173	1'-1½	Pf 0.968
13	0'-3	21.37	5.6	14.567		Sprinkler,	3'-7	Pe 0.490
119	-0'-10½			16.026		PO(3'-7)	4'-8½	Pv
BL	1.6820	21.37	3.09	100		0.020684	10'-0	Pf 0.207
119	-0'-10½			16.026				Pe
120	-0'-10½			16.233			10'-0	Pv
BL	1.6820	42.89	6.19	100		0.075026	8'-11½	Pf 1.203
120	-0'-10½	21.52		16.233		Flow (q) from Route 15	7'-0½	Pe
104	-0'-10½			17.435		PO(7'-0½)	16'-0½	Pv
• • • • • Route 14 • • • • •								
SP	1.0490	21.44	7.96	100		0.207329	1'-1½	Pf 0.974
14	0'-3	21.44	5.6	14.656		Sprinkler,	3'-7	Pe 0.490
121	-0'-10½			16.120		PO(3'-7)	4'-8½	Pv
BL	1.6820	21.44	3.10	100		0.020800	10'-0	Pf 0.208
121	-0'-10½			16.120				Pe
122	-0'-10½			16.328			10'-0	Pv
BL	1.6820	43.02	6.21	100		0.075447	8'-6½	Pf 1.176
122	-0'-10½	21.58		16.328		Flow (q) from Route 16	7'-0½	Pe 0.000
105	-0'-10½			17.504		PO(7'-0½)	15'-7	Pv
• • • • • Route 15 • • • • •								
SP	1.0490	21.52	7.99	100		0.208723	1'-1½	Pf 0.980
15	0'-3	21.52	5.6	14.762		Sprinkler,	3'-7	Pe 0.490
120	-0'-10½			16.233		PO(3'-7)	4'-8½	Pv
• • • • • Route 16 • • • • •								
SP	1.0490	21.58	8.01	100		0.209892	1'-1½	Pf 0.986
16	0'-3	21.58	5.6	14.851		Sprinkler,	3'-7	Pe 0.490
122	-0'-10½			16.328		PO(3'-7)	4'-8½	Pv
• • • • • Route 17 • • • • •								

Hydraulic Analysis

Job Number: 2497
Report Description: Ordinary Group I

Pipe Type / Downstream / Upstream	Diameter / Elevation	Flow / Discharge	Velocity / K-Factor	HWC / Pt	Pn	Friction Loss / Fittings	Length / Eq. Length / Total Length	Pressure Summary
SP	1.0490	22.31	8.28	100		0.223108	1'-1½	Pf 1.048
17	0'-3	22.31	5.6	15.865		Sprinkler,	3'-7	Pe 0.490
123	-0'-10½			17.403		PO(3'-7)	4'-8½	Pv
BL	1.6820	22.31	3.22	100		0.022383	8'-6½	Pf 0.349
123	-0'-10½			17.403			7'-0½	Pe 0.000
106	-0'-10½			17.752		PO(7'-0½)	15'-7	Pv

Equivalent Pipe Lengths of Valves and Fittings (C=120 only)

$$\left(\frac{\text{Actual Inside Diameter}}{\text{Schedule 40 Steel Pipe Inside Diameter}}\right)^{4.87} = \text{Factor}$$

C Value Multiplier

Value Of C	100	130	140	150
Multiplying Factor	0.713	1.16	1.33	1.51

Pipe Type Legend

AO	Arm-Over
BL	Branch Line
CM	Cross Main
DN	Drain
DR	Drop
DY	Dynamic
FM	Feed Main
FR	Feed Riser
MS	Miscellaneous
OR	Outrigger
RN	Riser Nipple
SN	Swing Nipple
SP	Sprig
ST	Stand Pipe
UG	Underground

Units Legend

Diameter	Inch
Elevation	Foot
Flow	gpm
Discharge	gpm
Velocity	fps
Pressure	psi
Length	Foot
Friction Loss	psi/Foot
HWC	Hazen-Williams Constant
Pt	Total pressure at a point in a pipe
Pn	Normal pressure at a point in a pipe
Pf	Pressure loss due to friction between points
Pe	Pressure due to elevation difference between indicated points
Pv	Velocity pressure at a point in a pipe

Fittings Legend

ALV	Alarm Valve
AngV	Angle Valve
b	Bushing
BalV	Ball Valve
BFP	Backflow Preventer
BV	Butterfly Valve
C	Cross Flow Turn 90°
cplg	Coupling
Cr	Cross Run
CV	Check Valve
DelV	Deluge Valve
DPV	Dry Pipe Valve
E	90° Elbow
EE	45° Elbow
Ee1	11¼° Elbow
Ee2	22½° Elbow
f	Flow Device
fd	Flex Drop
FDC	Fire Department Connection
fE	90° FireLock(TM) Elbow
fEE	45° FireLock(TM) Elbow
flg	Flange
FN	Floating Node
fT	FireLock(TM) Tee
g	Gauge
GloV	Globe Valve
GV	Gate Valve
Ho	Hose
Hose	Hose
HV	Hose Valve
Hyd	Hydrant
LtE	Long Turn Elbow
mecT	Mechanical Tee
Noz	Nozzle
P1	Pump In
P2	Pump Out
PIV	Post Indicating Valve
PO	Pipe Outlet
PrV	Pressure Relief Valve
PRV	Pressure Reducing Valve
red	Reducer/Adapter
S	Supply
sCV	Swing Check Valve
SFx	Seismic Flex
Spr	Sprinkler
St	Strainer
T	Tee Flow Turn 90°
Tr	Tee Run
U	Union
WirF	Wirsbo
WMV	Water Meter Valve
Z	Cap

Stormwater Pollution Prevention Plan

Prepared for:
ARGO Development
95 Chestnut Ridge Rd
Montvale, NJ 07645

Submitted by:
LaBella Associates
21 Fox Street
Poughkeepsie, NY 12601
(845) 454-3980

LaBella
Powered by partnership.

South Ave Multi-Family Development

City of Poughkeepsie, Dutchess County, New York

DATE: OCTOBER 2022
LAST REVISED: NOVEMBER 2022
PROJECT NO. 2222201

This Page Intentionally Left Blank

PREPARER OF THE SWPPP

"I hereby certify that the Stormwater Pollution Prevention Plan (SWPPP) for this project has been prepared in accordance with the terms and conditions of the GP-0-20-001. Furthermore, I understand that certifying false, incorrect or inaccurate information is a violation of this permit and the laws of the State of New York and could subject me to criminal, civil and/or administrative proceedings."

Name and Title[1]: Chris Lapine, PE

Date: November 2022



[1] This is a signature of a New York State licensed Professional Engineer employed by LaBella Associates that is duly authorized to sign and seal Stormwater Pollution Prevention Plans (SWPPPs), NOIs, and NOTs prepared under their direct supervision. Refer to Appendix B for the SWPPP Preparer Certification Form, and Appendix I for the LaBella Certifying Professionals Letter.

TABLE OF CONTENTS

1.0 EXECUTIVE SUMMARY 1

1.1 Project Description 2

1.2 Stormwater Pollution Controls 2

2.0 SITE CHARACTERISTICS 3

2.1 Land Use and Topography 3

2.2 Soils and Groundwater 3

2.3 Watershed Designation 4

2.4 Receiving Water Bodies 4

2.5 Aquifer Designation 4

2.6 Wetlands 4

2.7 Flood Plains 4

2.8 Listed, Endangered, or Threatened Species 5

2.9 Historic Places 5

2.10 Rainfall Data 5

2.11 Pre-development Watershed Conditions 5

2.12 Post-development Watershed Conditions 6

2.13 Description of Analysis Points 6

3.0 STORMWATER MANAGEMENT PLANNING 6

3.1 STEP 1 – Site Planning 7

3.2 STEP 2 – Calculate Water Quality Treatment Volume (WQv) 7

3.3 STEP 3 – Apply RR Techniques and Standard SMPs with RRv Capacity to Reduce Total WQv 8

3.4 STEP 4 – Calculate the Minimum RRv Required 9

3.5 STEP 5 – Apply Standard SMPs to Address Remaining Water Quality Volume 10

3.6 STEP 6 - Apply Volume and Peak Rate Control 10

4.0 CONSTRUCTION SEQUENCE 12

5.0 CONSTRUCTION-PHASE POLLUTION CONTROL 13

5.1 Temporary Erosion and Sediment Control Measures 13

5.2 Permanent Erosion and Sediment Control Measures 16

5.3 Other Pollutant Controls 17

5.4 Construction Housekeeping Practices 17

6.0 INSPECTIONS, MAINTENANCE, AND REPORTING 18

6.1 Inspection and Maintenance Requirements 18
6.2 Reporting Requirements 20
7.0 SWPPP IMPLEMENTATION RESPONSIBILITIES 22
7.1 Owner's/Operator's Responsibilities 22
7.2 Owner's/Operator's Engineer's Responsibilities 24
7.3 Contractor's Responsibilities 25
7.4 Qualified Inspector's/Qualified Professional's Responsibilities 26
7.5 SWPPP Participants 28

LIST OF TABLES

Table 1: USDA Soil Data 3
Table 2: Project Site HSG Data 4
Table 3: Rainfall Data 5
Table 4: Required WQv Summary 7
Table 5: Summary of Standard SMPs with RRv Capacity being Applied 9
Table 6: RRv Summary 9
Table 7: Minimum RRv Summary 10
Table 8: Design Events 12
Table 9: Summary of Pre- and Post-Development Peak Discharge Rates 12

APPENDICES

Appendix A: Figures

- A-1: Site Location Map
- A-2: Soils Map
- A-3: Historic Places Screening Map
- A-4: Environmental Resource Map
- A-5: Pre-Development Watershed Delineation Map (Pocket)
- A-6: Post-Development Watershed Delineation Map (Pocket)

Appendix B: Forms

- Notice of Intent (NOI)
- MS4 SWPPP Acceptance Form
- SWPPP Preparer Certification Form
- Owner/Operator Certification Form
- Contractor and Subcontractor Certification Forms
- Notice of Termination (NOT)

Appendix C: Project Evaluation and Design Calculations

Appendix D: Pre-Development Stormwater Modeling

Appendix E: Post-Development Stormwater Modeling

Appendix F: SWPPP Inspection Report (Sample Form)

Appendix G: Post-Construction Inspections and Maintenance

Appendix H: NYSDEC “Deep-Ripping and Decompaction,” April 2008

Appendix I: LaBella Certifying Professionals Letter

Appendix J: NYSDEC SPDES General Permit GP-0-20-001

1.0 EXECUTIVE SUMMARY

This Stormwater Pollution Prevention Plan (SWPPP) has been prepared for major activities associated with construction of a 89-unit, mid-rise multifamily apartment building in the City of Poughkeepsie. This SWPPP includes the elements necessary to comply with the national baseline general permit for construction activities enacted by the U.S. Environmental Protection Agency (EPA) under the National Pollutant Discharge Elimination System (NPDES) program and all local governing agency requirements. This SWPPP must be executed and permit coverage must be obtained prior to the commencement of construction activity.

This SWPPP has been developed in accordance with the "New York State Department of Environmental Conservation (NYSDEC) State Pollutant Discharge Elimination System (SPDES) General Permit for Stormwater Discharges from Construction Activity," Permit No. GP-0-20-001, effective January 29, 2020 through January 28, 2025. The SWPPP and accompanying plans identify and detail stormwater management, pollution prevention, and erosion and sediment control measures necessary during and following completion of construction.

This SWPPP and the accompanying plans entitled "South Avenue Multi-Family Development" have been submitted as a set. These engineering drawings are considered an integral part of this SWPPP. Therefore, this SWPPP is not considered complete without them. References made herein to "the plans" or to a specific "sheet" refer to these drawings.

This report considers the impacts associated with the intended development with the purpose of:

1. Maintaining existing drainage patterns as much as possible while continuing the conveyance of upland watershed runoff;
2. Controlling increases in the rate of stormwater runoff resulting from the proposed development so as not to adversely alter downstream conditions; and
3. Mitigating potential stormwater quality impacts and preventing soil erosion and sedimentation resulting from stormwater runoff generated both during and after construction.

The analysis and design completed and documented in this report is intended to be part of the application made for a multi-family residential development project completed on behalf of the Owner/Operator.

This Master Stormwater Pollution Prevention Plan (SWPPP) has been prepared to support the state environmental quality review (SEQR) of the proposed project. The intent of this Master SWPPP is to provide sufficient documentation for an overall SEQR determination, and to serve as the baseline for the final SWPPP that will be prepared for the proposed development, as approved. As such, design concepts are provided for stormwater collection and conveyance systems, and water quality and quantity control facilities. This report is not intended to be a final engineering document as certain detailed aspects of the project are likely to change during the site plan review process. Portions of the design were advanced to substantiate regulatory compliance determinations and to provide input pertinent to the environmental assessment of impacts of the proposed project. Final stormwater practice designs will be advanced in support of and during the site plan permitting process.

The methodology used to develop this Master SWPPP shall be adhered to for the preparation of the project's final SWPPP. Stormwater quality and quantity controls designed for this Master SWPPP are preliminary in nature and are intended to demonstrate their location, approximate size, and design concept. Detailed analysis of these practices must be performed, and their design refined as part of the final SWPPP.

The stormwater analysis identified herein follows *the "NYS Stormwater Management Design Manual," dated January 2015 (Design Manual) and the USDA Technical Release No. 20.* This Master SWPPP and analysis are an integral part of the project's natural resource management plan which takes into consideration existing parameters of site topography, soils, erosion potential, surface waters, their connectivity and water quality of receiving water bodies.

Stormwater mitigation measures primarily involve preventing soil erosion and sedimentation resulting from stormwater run-off during and after construction. During construction, this is accomplished by sequencing site disturbance activities to establish erosion controls, minimize disturbed areas, maintain existing vegetation as much as possible, and stabilize newly disturbed areas as soon as possible. Stormwater pollutant controls utilized during construction will include temporary sediment barriers and sediment traps designed in accordance with the *"NYS Standards and Specifications for Erosion and Sediment Control"*. Stormwater pollutant controls utilized after construction will include stormwater quality control practices designed in accordance with the Manual.

Land development can also have an effect on site hydrology. Impervious areas such as rooftops, roads, driveways, and parking lots can cause rainfall to rapidly convert into stormwater runoff. Increases in runoff can cause stream bank erosion and floodplain expansion. To mitigate these impacts, stormwater quantity controls will be implemented to capture and release run-off at less than pre-development discharge rates. A hydrologic and hydraulic analysis was/will be performed using computer modeling and an evaluation of the proposed improvements across the project site.

1.1 Project Description

ARGO Development is proposing development project, to include: a 89-unit, mid-rise multifamily apartment building with the associated parking and stormwater installation. The project will disturb greater than 1-acre of land. A Site Location Map has been provided in Appendix A, as Figure A-1.

This type of project is included in Table 2 of Appendix B of GP-0-20-001; and the project site is not located in one of the watersheds listed in Appendix C of GP-0-20-001. Therefore, this SWPPP includes post-construction stormwater management practices, as well as erosion and sediment controls.

This project is located within the City Of Poughkeepsie regulated, traditional land use control Municipal Separate Stormwater Sewer System (MS4). Therefore, an MS4 SWPPP Acceptance Form is required to accompany NOIs submitted to the NYSDEC.

Runoff from the project site will discharge to the Hudson River, which is not included in the list of Section 303(d) water bodies included in Appendix E of GP-0-20-001.

Project construction activities will consist primarily of site grading, paving, building construction, and the installation of storm drainage, water supply, sanitary sewer, and public utility infrastructure necessary to support the proposed development project. Construction phase pollutant sources anticipated at the site are disturbed (exposed) soil, vehicle fuels and lubricants, chemicals associated with building construction, and building materials. Without adequate control there is the potential for each type of pollutant to be transported by stormwater.

1.2 Stormwater Pollution Controls

The stormwater pollution controls outlined herein have been designed and evaluated in accordance with the following standards and guidelines:

- New York State Stormwater Management Design Manual, dated January 2015 (Design Manual).
- New York State Standards and Specifications for Erosion and Sediment Control, dated November 2016 (SSESC).
- City of Poughkeepsie Stormwater Management and Erosion and Sediment Control

Stormwater quality will be enhanced through the implementation of temporary and permanent erosion and sediment control measures, the proposed stormwater management practice(s), and other construction-phase pollution controls outlined herein.

The proposed stormwater management approach consisting of pipes and on-site stormwater management practices will adequately collect, treat, and convey the stormwater runoff.

An infiltration pond and detention basin will be used to manage and treat stormwater runoff generated by the proposed development project.

Pre- and post-development surface runoff rates have been evaluated for the 1-, 10-, and 100-year 24-hour storm events. Comparison of pre- and post-development watershed conditions demonstrates that the peak rate of runoff from the project site will not be increased.

2.0 SITE CHARACTERISTICS

2.1 Land Use and Topography

The project site is located within the Research and Development (R-D) zoning district. Multifamily housing development is a permitted use within this district.

The overall site is moderately sloping, with slopes ranging from 3 to 55 percent. Site elevations range from approximately 72.5 feet above mean sea level (MSL) to 92.4 feet MSL. The site is highest in elevation along the northern property line where is slopes down to the south-western corner of the property. There are two depressions within the site that trap some stormwater and allow it to infiltrate.

2.2 Soils and Groundwater

The US Department of Agriculture (USDA) Web Soil Survey (http://websoilsurvey.nrcs.usda.gov/app/) was used to obtain surficial soil conditions for the study area, as follows:

Table 1: USDA Soil Data

Map Symbol & Description	Hydrologic Soil Group	Permeability (inches/hour)	Erosion Factor K	Depth to Water Table (feet)	Depth to Bedrock (feet)
Ud—Udorthents, smoothed	A	0.06 - 5.95	0.17	4.5	>6.0
Ur – Urban fill	D	NA	NA	NA	>6.0

Upon review of the soil data presented in Table 1, the project site does not contain soils with a soil slope phase of D with a map unit name that inclusive of slopes greater than 25%, and does not contain soils with a soil slope phase of E or F.

The project site is composed of HSG A soils and HSG D soils, as shown in the table below. For the purposes of this report, HSG X/D soils were modeled as HSG D soils to reflect the undrained condition.

Table 2: Project Site HSG Data

HSG A	HSG B	HSG C	HSG D
96%	0%	0%	4%

The Soil Conservation Service defines the hydrologic soil groups as follows:

- Type A Soils: Soils having a high infiltration rate and low runoff potential when thoroughly wet. These soils consist mainly of deep, well drained to excessively drained sands or gravelly sands. These soils have a moderate rate of water transmission.
- Type D Soils: Soils having a very low infiltration rate and high runoff potential when thoroughly wet. These soils consist chiefly of clays that have high shrink-swell potential, soils that have a permanent high water table, soils that have a clay pan or clay layer at or near the surface, and soils that are shallow over nearly impervious material. These soils have a very low rate of water transmission.

The soils map for the study area is presented in Appendix A, as Figure A-2.

2.3 Watershed Designation

The project site is not located in a restricted watershed identified in Appendix C of GP-0-20-001.

2.4 Receiving Water Bodies

The nearest natural classified water body into which runoff from the project site will discharge is the Hudson River. The Hudson River is classified by NYSDEC as a Class A water course, and is not included in the Section 303(d) list of impaired waters found in Appendix E of GP-0-20-001.

2.5 Aquifer Designation

The project site is not located over a US EPA designated Sole Source aquifer; nor is it located over a Primary or Principal aquifer listed in the NYSDEC Technical and Operational Guidance Series (TOGS) 2.1.3 (1980).

2.6 Wetlands

A search on the NYSDEC Environmental Resource Mapper on October 10, 2022, and a review of GIS data, determined that there are no known regulated wetlands located on or in the vicinity of the project site.

2.7 Flood Plains

According to the National Flood Insurance Program Flood Insurance Rate Map (FIRM), City of Poughkeepsie, New York, Community Panel Number 36027C0358E, the project site lies within Flood Zone X, areas determined to be outside 500-year floodplain.

2.8 Listed, Endangered, or Threatened Species

A search was performed on the NYSDEC Environmental Resource Mapper on October 10, 2022, and determined that the project site may contain threatened or endangered species, or critical habitat. An Environmental Resource Map has been provided in Appendix A, as Figure A-4.

2.9 Historic Places

A search on the New York State Cultural Resource Information System (CRIS) database, performed on October 10, 2022, revealed that the property is not located within an archeologically sensitive area, and is not located on or immediately adjacent to a property listed or determined to be eligible for listing on the National or State Registers of Historic Places. Additionally, the construction activity does not include the construction of a new building within 20 feet of any structure more than 50 years old. A printout of the historic places screening map is presented in Appendix A, as Figure A-3.

2.10 Rainfall Data

Rainfall data utilized in the modeling and analysis was obtained from the Cornell University online Extreme Precipitation in New York & New England website (http://precip.eas.cornell.edu/). The standard SCS/NRCS rainfall distributions were applied to evaluate the pre- and post-development stormwater runoff characteristics. Rainfall data specific to the portion of Dutchess County under consideration, for various 24-hour storm events, is presented in the following Table:

Table 3: Rainfall Data

Storm Event Return Period	24-Hour Rainfall (inches)
1-year	2.61
10-year	4.67
100-year	8.20

2.11 Pre-development Watershed Conditions

The pre-development project site is covered predominantly by woods with a small amount of grass along the South Ave and Fox St frontage . Analysis of pre-development conditions considered existing drainage patterns, soil types, ground cover, and topography. The Pre-Development Watershed Delineation Map has been provided in Appendix A, as Figure A-5.

The results of the computer modeling used to analyze the overall watershed under pre-development conditions are presented in Appendix D. A summary of the pre-development watershed runoff rates at each analysis point is presented in Table 9.

Subcatchment 1 is a 0.65± acre watershed consisting of mostly woods with some grass. Runoff flows in a southeastern direction overland via sheet flow then shallow concentrated flow toward the depression 1P. Once the depression becomes filled, the stormwater will flow into Subcatchment ES2. This subcatchment is tributary to Analysis Point (AP) 1.

Subcatchment 2 is a 1.67± acre watershed consisting of mostly woods with some grass. Runoff flows in a southeastern direction overland via sheet flow then shallow concentrated flow. This subcatchment is tributary to Analysis Point (AP) 1.

Subcatchment 3 is a 0.57± acre watershed consisting of mostly woods with some grass. Runoff flows in a south-western direction overland via sheet flow then shallow concentrated flow toward the depression 2P. Once the depression becomes filled, the stormwater will flow into Subcatchment ES2. This subcatchment is tributary to Analysis Point (AP) 1.

2.12 Post-development Watershed Conditions

The post-development project site is covered predominantly by impervious surfaces with areas of grass spread throughout. The analysis of post-development conditions considered existing drainage patterns, soil types, ground cover to remain, planned site development, site grading, and stormwater management facilities proposed as part of site improvements. The Post-Development Watershed Delineation Map has been provided in Appendix A, as Figure A-6.

The results of the computer modeling used to analyze the overall watershed under post-development conditions are presented in Appendix E. A summary of the post-development watershed runoff rates at each analysis point is presented in Table 9.

There are numerous locations and methods for providing controls of off-site discharge of stormwater from the project site. Each has been designed to provide the above quantity controls by attenuating stormwater runoff and releasing runoff to off-site locations at a rate equal to or less than that which existed prior to development of the site. Each device is detailed on the accompanying plans.

2.13 Description of Analysis Points

The study area consists of an overall watershed that encompasses approximately 2.82 acres, including the 2.76 ± acre project site and 2.46 ± acre area of disturbance. The overall watershed was broken down into smaller watersheds, or subcatchments, to allow for analysis of runoff conditions at several locations throughout the study area. Each of these locations was defined as Analysis Point (AP) in order to compare the effects resulting from stormwater management facilities proposed as part of the project. Descriptions of each of the selected analysis points are provided below.

- Analysis Point 1: Off-site discharge to low spot located at the southwest corner of site. Runoff collects in an existing catch basin connected to a NYSDOT drainage system.

3.0 STORMWATER MANAGEMENT PLANNING

Chapter 3 of the Design Manual outlines a six-step planning process for site planning and selection of stormwater management practices that must be implemented for both new development and redevelopment projects. This process is intended to develop a design that maintains pre-construction hydrologic conditions through the application of environmentally sound development principles, as well as treatment and control of runoff discharges from the site. The following sections outline the step-by-step process and how it has been applied to this project.

The goals of this Stormwater Management Plan are to analyze the peak rate of runoff under pre- and post-development conditions, to maintain the pre-development rate of runoff in order to minimize

impacts to adjacent or downstream properties, and to minimize the impact to the quality of runoff exiting the site.

The Design Manual provides both water quality and water quantity objectives to be met by projects requiring a "Full SWPPP". These objectives will be met by applying stormwater control practices to limit peak runoff rates and improve the quality of runoff leaving the developed site.

3.1 STEP 1 – Site Planning

During the Site Planning process, the project site is evaluated for implementation of the green infrastructure planning measures identified in Table 3.1 of the Design Manual, in order to preserve natural resources and reduce impervious cover. Table A of Appendix C provides a description of each green infrastructure planning measure, along with a project specific evaluation.

3.2 STEP 2 – Calculate Water Quality Treatment Volume (WQv)

Stormwater runoff from impervious surfaces is recognized as a significant contributor of pollution that can adversely affect the quality of receiving water bodies. Therefore, treatment of stormwater runoff is important since most runoff related water quality contaminants are transported from land, particularly the impervious surfaces, during the initial stages of storm events.

3.2.1 NYSDEC Requirements for Water Quality Volume

The Design Manual requires that water quality treatment be provided for the initial flush of runoff from every storm. The NYSDEC refers to the amount of runoff to be treated as the "Water Quality Volume" (WQv). Section 4.2 of the Design Manual defines the Water Quality Volume as follows:

$$WQv = \frac{[(P)(R_v)(A)]}{12}$$

Where: P = 90% Rainfall Event Number
R_v = 0.05 + 0.009 (I)
I = Impervious Cover (Percent)
A = Contributing Area in Acres

This definition ensures that, all other things being equal, the Water Quality Volume will increase along with the impervious cover percentage.

3.2.2 Methodology for New Development

The Water Quality Volume equation has been applied to the drainage area tributary to the stormwater quality practice proposed for this project. The practice has been sized to accommodate the Water Quality Volume, as per the performance criteria presented in Chapter 5 and/or Chapter 6 of the Design Manual. Water quality volume calculations for each of the proposed practices are presented in Table B of Appendix C.

Table 4: Required WQv Summary

Required WQv	
7,392 CF	0.170 AF

3.2.3 Methodology

The Water Quality Volume equation has been applied to the drainage area tributary to each stormwater quality practice proposed for this project. The practice has been sized to accommodate the Water Quality Volume, as per the performance criteria presented in Chapter 6 of the Design Manual. Water quality volume calculations for each of the proposed practices are presented in Table B of Appendix C.

3.3 STEP 3 – Apply RR Techniques and Standard SMPs with RRv Capacity to Reduce Total WQv

Land use change and development in the watershed increases the volume of runoff. As such, reductions in the amount of runoff from new development, accomplished through the implementation of a stormwater management plan for the site, will play an important role in the success or failure of the watershed-wide stormwater management plan. Runoff reduction techniques can be applied to manage, reduce, and treat stormwater, while maintaining and restoring natural hydrology through infiltration, evapo-transpiration, and the capture and reuse of stormwater. Volume reduction techniques by themselves typically are not sufficient to provide adequate attenuation of stormwater runoff, but they can decrease the size of the peak runoff rate reduction facilities.

3.3.1 NYSDEC Requirements for New Development

The Design Manual states that runoff reduction shall be achieved through infiltration, groundwater recharge, reuse, recycle, and/or evaporation/evapotranspiration of 100-percent of the post-development water quality volume to replicate pre-development hydrology. Runoff control techniques provide treatment in a distributed manner before runoff reaches the collection system, by maintaining pre-construction infiltration, peak runoff flow, discharge volume, as well as minimizing concentrated flow. This can be accomplished by applying a combination of Runoff Reduction Techniques, standard Stormwater Management Practices (SMPs) with RRv capacity, and good operation and maintenance.

3.3.2 Methodology

In order to reduce the required WQv and meet the RRv criteria, a site specific evaluation must be performed to determine the most practical means of reducing runoff volume by application of a combination of RR techniques and standard SMPs with RRv capacity.

3.3.3 Application of Standard Stormwater Management Practices (SMPs) with RRv Capacity

The following Table demonstrates a summary of the standard SMP(s) with RRv capacity that have been incorporated into the stormwater management plan for this project. The standard SMP(s) with RRv capacity have been designed in accordance with Chapter 6 of the Design Manual. Refer to the contract drawings for practice dimensions, material specifications, and installation details. Practice specific calculations are presented in Appendix C.

Table 5: Summary of Standard SMPs with RRv Capacity being Applied

Standard SMP with RRv Capacity	Design Variant	Pretreatment Volume Required (% of WQv)	Pretreatment Volume Provided (CF)	RRv Capacity	WQv Required (CF)	WQv Reduced /RRv Provided (CF)	WQv Treated[1] (CF)	Total WQv Provided[2] (CF)
Underground Infiltration System	I-4	25%	1,566	100%	6,299	6,299	0	6,299
Bioretention (with underdrains)	F-5	25%	803	40%	1,280	907	373	2,187
Standard SMP with RRv Capacity Totals					**7,579**	**7,206**	**373**	**8,486**

Footnotes:
[1]*WQv Treated = WQV Required - RRv Provided*
[2]*Total WQv Provided = WQV Treated + RRv Provided*

3.3.4 RRv Performance Summary

A summary of the RRv provided is presented in the following table:

Table 6: RRv Summary

WQv Required (CF)	RRv Provided WQv Reduced (CF)	% RRv Provided/ WQv Reduced
7,392	7,206	97%

As indicated in the above table, the RRv provided is not greater than or equal to the RRv required for the project site. A good faith effort has been made to reduce runoff to the greatest extent practical. However, the project site has soils with an infiltration rate less than 0.5 in/hr, which prevents reduction of the total WQv. As such, Table C of Appendix C provides a project specific evaluation for each RR technique and standard SMP with RRv capacity, demonstrating why these practices are infeasible.

3.4 STEP 4 – Calculate the Minimum RRv Required

Projects that cannot achieve 100% of the runoff reduction requirement due to site limitations, shall provide a minimum runoff reduction volume as calculated by the following equation:

$$RRv_{min} = \frac{[(P)(R_V*)(Aic)(S)]}{12}$$

Where:

RRv_{min} = Runoff Reduction Volume (in acre-feet)
P = 90% Rainfall Event Number
Aic = Total area of new impervious cover (acres)
Rv* = 0.05+0.009(I), where I is 100% impervious
S = Hydrologic Soil Group (HSG) Specific Reduction Factor where:
HSG A = 0.55 HSG C = 0.30

HSG B = 0.40 HSG D = 0.20

Based upon the soil survey data, the site consists of soils having a hydrologic soil type of A and D. As such, a specific reduction factor of 0.54 has been applied. Calculation of the required minimum RRv is presented in Table D of Appendix C.

Table 7: Minimum RRv Summary

Minimum RRv Required (CF)	RRv Provided/ WQv Reduced (CF)	% of Minimum RRv Provided
3,868	7,206	186%

As indicated in the above table, the RRv provided is greater than the minimum RRv required for the project site. Therefore, the runoff reduction volume criteria has been met for the project and the design can proceed to Step 5.

3.5 STEP 5 – Apply Standard SMPs to Address Remaining Water Quality Volume

As previously discussed, 100% of the required WQv is being provided and reduced through RRv practice. As such, the water quality and runoff reduction volume criteria have been met and no other standard SMPs are required.

3.6 STEP 6 - Apply Volume and Peak Rate Control

This report presents the pre-development and post-development features and conditions associated with the rate of surface water runoff within the study area. For both cases, the drainage patterns, drainage structures, soil types, and ground cover types are considered in this study.

3.6.1 NYSDEC Requirements for New Development

Chapter 4 of the Design Manual requires that projects meet three separate stormwater quantity criteria:

1. The Channel Protection (CPv) requirement is designed to protect stream channels from erosion. This is accomplished by providing 24 hours of extended detention for the 1-year, 24-hour storm event. The Manual defines the CPv detention time as the center of mass detention time through each stormwater management practice.

2. The Overbank Flood Control (Qp) requirement is designed to prevent an increase in the frequency and magnitude of flow events that exceed the bank-full capacity of a channel, and therefore must spill over into the floodplain. This is accomplished by providing detention storage to ensure that, at each analysis point, the post-development 10-year 24-hour peak discharge rate does not exceed the corresponding pre-development rate.

3. The Extreme Flood Control (Qf) requirement is designed to prevent the increased risk of flood damage from large storm events, to maintain the boundaries of the pre-development 100-year floodplain, and to protect the physical integrity of stormwater management practices. This is accomplished by providing detention storage to ensure that, at each analysis point, the post-development 100-year 24-hour peak discharge rate does not exceed the corresponding pre-development rate.

3.6.2 Methodology

In order to demonstrate that the NYSDEC detention requirements are being met, the Design Manual requires that a hydrologic and hydraulic analysis of the pre- and post-development conditions be performed using the Natural Resources Conservation Service Technical Release 20 (TR-20) and Technical Release 55 (TR-55) methodologies. HydroCAD, developed by HydroCAD Software Solutions LLC of Tamworth, New Hampshire, is a Computer-Aided-Design (CAD) program for analyzing the hydrologic and hydraulic characteristics of a given watershed and associated stormwater management facilities. HydroCAD uses the TR-20 algorithms and TR-55 methods to create and route runoff hydrographs.

HydroCAD has the capability of computing hydrographs (which represent discharge rates characteristic of specified watershed conditions, precipitation, and geologic factors) combining hydrographs and routing flows though pipes, streams and ponds. HydroCAD can also calculate the center of mass detention time for various hydraulic features. Documentation for HydroCAD can be found on their website: http://www.hydrocad.net/.

For this analysis, the watershed and drainage system was broken down into a network consisting of three types of components as described below:

1. Subcatchment: A relatively homogeneous area of land, which produces a volume and rate of runoff unique to that area.
2. Reach: Uniform streams, channels, or pipes that convey stormwater from one point to another.
3. Pond: Natural or man-made impoundment, which temporarily stores stormwater runoff and empties in a manner determined by its geometry and the hydraulic structure located at its outlets.

Subcatchments, reaches, and ponds are represented by hexagons, squares, and triangles, respectively, on the watershed routing diagrams provided with the computations included in Appendix D and Appendix E.

The analysis of hydrologic and hydraulic conditions and proposed stormwater management facilities, servicing the study area, was performed by dividing the tributary watershed into relatively homogeneous subcatchments. The separation of the watershed into subcatchments was dictated by watershed conditions, methods of collection, conveyance, and points of discharge. Watershed characteristics for each subcatchment were then assessed from United States Geological Service (USGS) 7.5-minute topographic maps, aerial photographs, a topographical survey, soil surveys, site investigations, and land use maps.

Proposed stormwater management practices were designed and evaluated in accordance with the Design Manual and local regulatory requirements. The hydrologic and hydraulic analysis considered the SCS Type III 24-hour storm events identified in the following Table.

Table 8: Design Events

Facility	24-hour Storm Event
Storm Sewer	10-year
Stormwater Management Practice(s)	1-year
	10-year
	100-year
Flood Conditions	100-year

3.6.3 Performance Summary

The CPv requirement does not apply as the reduction of the entire CPv is achieved by application of runoff reduction techniques or infiltration systems.

A comparison of the pre- and post-development watershed conditions was performed for the analysis point and storm events evaluated herein. For the analysis point and design storms, this comparison demonstrates that the peak rate of runoff will not be increased. Therefore, the project will not have a significant adverse impact on the adjacent or downstream properties or receiving water courses.

The results of the computer modeling used to analyze the pre- and post-development watersheds are presented in Appendix D and Appendix E, respectively. The following Table summarizes the results of this analysis.

Table 9: Summary of Pre- and Post-Development Peak Discharge Rates

Pre- vs. Post-Development Discharge Rate (cfs)						
Analysis Point (AP)	1-year 24-hour storm event		10-year 24-hour storm event		100-year 24-hour storm event	
	Pre	Post	Pre	Post	Pre	Post
1	0.09	0.02	1.52	0.38	8.04	2.13

4.0 CONSTRUCTION SEQUENCE

This project encompasses less than five acres of land and disturbance of additional off-site properties to facilitate construction is not anticipated. Therefore, written approval from the City of Poughkeepsie allowing the disturbance of more than five acres of land at any one time is not required. If the Contractor's construction sequence requires the disturbance of more than five acres at any one time, written approval must be obtained from the City of Poughkeepsie prior to disturbing more than five acres at once.

The "Erosion and Sediment Control Plan" in the accompanying drawings identifies the major construction activities that are the subject of this SWPPP. The order (or sequence) in which the major activities are expected to begin is presented on the accompanying drawings, though each activity will not necessarily be completed before the next begins. In addition, these activities could occur in a different order if necessary to maintain adequate erosion and sediment control. If this is the case, the contractor shall notify the Owner's/Operator's Engineer overseeing the implementation of the SWPPP.

The Contractor will be responsible for implementing the erosion and sediment control measures identified on the plans. The Contractor may designate these tasks to certain subcontractors as they see fit, but the ultimate responsibility for implementing these controls and ensuring their proper function remains with the Contractor.

Refer to the accompanying plans for details and specifications regarding the construction sequencing schedule.

5.0 CONSTRUCTION-PHASE POLLUTION CONTROL

The SWPPP and accompanying plans identify the temporary and permanent erosion and sediment control measures that have been incorporated into the design of this project. These measures will be implemented during construction, to minimize soil erosion and control sediment transport off-site, and after construction, to control the quality and quantity of stormwater runoff from the developed site.

Erosion control measures, designed to minimize soil loss, and sediment control measures, intended to retain eroded soil and prevent it from reaching water bodies or adjoining properties, have been developed in accordance with the following documents:

- NYSDEC SPDES General Permit for Stormwater Discharges From Construction Activity, Permit No. GP-0-20-001 (effective January 29, 2020 through January 28, 2025)
- New York State Standards and Specifications for Erosion and Sediment Control, NYSDEC (November 2016)
- City of Poughkeepsie Erosion and Sediment Control Ordinance

The SWPPP and accompanying plans outline the construction scheduling for implementing the erosion and sediment control measures. These documents include limitations on the duration of soil exposure, criteria and specifications for placement and installation of the erosion and sediment control measures, a maintenance schedule, and specifications for the implementation of erosion and sediment control practices and procedures.

Temporary and permanent erosion and sediment control measures that shall be applied during construction generally include:

1. Minimizing soil erosion and sedimentation by stabilization of disturbed areas and by removing sediment from construction site discharges.
2. Preservation of existing vegetation to the greatest extent practical. Following the completion of construction activities in any portion of the site, permanent vegetation shall be established on all exposed soils.
3. Site preparation activities to minimize the area and duration of soil disruption.
4. Establishment of permanent traffic corridors to ensure that “routes of convenience” are avoided.

5.1 Temporary Erosion and Sediment Control Measures

The temporary erosion and sediment control measures described in the following sections are included as part of the construction documents.

5.1.1 Stabilized Construction Access

Prior to construction, stabilized construction access(es) will be installed, per accompanying plans, to reduce the tracking of sediment onto public roadways.

Construction traffic must enter and exit the site at the stabilized construction access(es). The intent is to trap dust and mud that would otherwise be carried off-site by construction traffic.

The access(es) shall be maintained in a condition, which will control tracking of sediment onto public rights-of-way or streets. When necessary, additional aggregate will be placed atop the filter fabric to assure the minimum thickness is maintained. All sediment and/or soil spilled, dropped, or washed onto public rights-of-way must be removed immediately. Periodic inspection and needed maintenance shall be provided after each substantial rainfall event.

5.1.2 Dust Control

Water trucks shall be used as needed during construction to reduce dust generated on-site. Dust control must be provided by the Contractor(s) to a degree that is acceptable to the Owner, and in compliance with the applicable local and state dust control requirements.

5.1.3 Temporary Soil Stockpile

Materials, such as topsoil, will be temporarily stockpiled (if necessary) on the site during the construction process. Stockpiles shall be located in an area away from storm drainage, water bodies and/or courses, and will be properly protected from erosion by a surrounding silt fence barrier.

5.1.4 Silt Fencing

Prior to the initiation of and during construction activities, a geotextile filter fabric (or silt fence) will be established downgradient of all disturbed areas. These barriers may extend into non-impact areas to provide adequate protection of adjacent lands.

Clearing and grubbing will be performed only as necessary for the installation of the sediment control barrier. To facilitate effectiveness of the silt fencing, daily inspections and inspections immediately after significant storm events will be performed by the Contractor(s). Maintenance of the fence will be performed as needed.

5.1.5 Temporary Seeding

For areas undergoing clearing, grading, and disturbance as part of construction activities, where work has temporarily ceased, temporary soil stabilization measures must be initiated by the end of the next business day and completed within fourteen (14) days from the date the soil disturbance activity has temporarily ceased.

5.1.6 Stone and Block Drop Inlet Protection

Concrete blocks surrounded by wire mesh and crushed stone will be placed around both existing catch basins, and proposed catch basins once they have been installed, to prevent sediment from entering the catch basins and storm sewer system. During construction, crushed stone shall be replaced as necessary to ensure proper function.

5.1.1 Manufactured Insert Inlet Protection

Install insert inlet protection beneath the grate of all catch basins, to prevent sediment from entering the catch basins and storm sewer system. Remove sediment accumulation and repair or replace insert as necessary to ensure proper function.

5.1.2 Filter Fabric Drop Inlet Protection

Install filter fabric or silt fence with wooden stakes at the perimeter of existing or proposed catch basins located in lawn areas, to prevent sediment from entering the catch basins and storm sewer system. Remove sediment accumulation and repair or replace fabric as necessary to ensure proper function.

5.1.3 Erosion Control Blanket

Erosion control blankets shall be installed in accordance with manufacturer's requirements on all slopes exceeding 3:1. Erosion control blankets provide temporary erosion protection, rapid vegetative establishment, and long-term erosion resistance to shear stresses generated by high runoff flow velocities associated with steep slopes.

5.1.4 Stone Check Dams

Stone check dams will be installed within drainage ditches to reduce the velocity of stormwater runoff, promote settling of sediment, and reduce sediment transport off-site.

Sediment accumulated behind the stone check dam will be removed as needed to maintain flow through the stone check dam and prevent large flows from carrying sediment over or around the dam. Stones shall be replaced as needed to maintain the design cross section of the structures.

5.1.5 Temporary Sediment Trap

Temporary sediment traps shall be constructed to intercept sediment-laden runoff, reduce the amount of sediment leaving the disturbed areas, and protect drainage ways, properties, and rights-of-way.

Accumulated sediment shall be removed from the trap when it reaches no greater than 50 percent of the design capacity. Sediment shall not be placed downstream from the embankment, adjacent to a stream, or floodplain.

Temporary sediment traps depicted on the accompanying plans have been designed to provide 3,600 CF of storage per acre of tributary watershed.

5.1.6 Temporary Diversion Swales

Temporary diversion swales shall be used to divert off-site runoff around the construction site and divert runoff from stabilized areas around disturbed areas. Temporary diversion swales can be used to direct runoff from disturbed areas into sediment traps.

5.1.7 Dewatering Operations

Dewatering will be used to intercept sediment-laden stormwater or pumped groundwater and allow it to settle out of the pumped discharge prior to being discharged from the site. Water from dewatering operations shall be treated to eliminate the discharge of sediment and other pollutants. Water resulting from dewatering operations shall be directed to temporary sediment traps or dewatering devices. Temporary sediment traps and dewatering bags will be provided, installed, and maintained at downgradient locations to control sediment deposits to downstream surfaces.

5.1.8 Fiber Roll

Prior to the initiation of and during construction activities, fiber rolls (12" minimum diameter) will be established downgradient of all disturbed areas to reduce sheet flow on slopes. These rolls may extend into non-impact areas to provide adequate protection of adjacent lands. Spacing will conform to NYSDEC specification for straw bale dike.

Clearing and grubbing will be performed only as necessary for the installation of the fiber rolls. To facilitate effectiveness, daily inspections and inspections immediately after significant storm events will be performed by the Contractor(s) and maintenance will be performed as needed.

5.1.9 Compost Filter Sock

Prior to the initiation of and during construction activities, a compost filter sock (or silt sock) will be established downgradient of all disturbed areas. These filters may extend into non-impact areas to provide adequate protection of adjacent lands. The spacing of the compost filter sock, which will depend on the ground slope and diameter of the sock, shall be based upon New York State or EPA guidance.

Clearing and grubbing will be performed only as necessary for the installation of the sediment control filter; and unlike sediment control barriers, trenching is not required. The ends of the filter sock should be directed upslope, to prevent stormwater from running around the end of the sock. The preferred anchoring method is to drive stakes through the center of the sock at regular intervals; alternatively, stakes can be placed on the downstream side of the sock. To facilitate effectiveness of the compost filter sock, daily inspections and inspections immediately after significant storm events will be performed by the Contractor(s) to ensure that they are intact and the area behind the sock is not filled with sediment. Maintenance of the sock will be performed as needed.

5.2 Permanent Erosion and Sediment Control Measures

The permanent erosion and sediment control measures described in the following sections are included as part of the construction documents.

5.2.1 Establishment of Permanent Vegetation

Disturbed areas that will be vegetated must be seeded in accordance with the contract documents. The type of seed, mulch, and maintenance measures as described in the contract documents shall also be followed.

Permanent soil stabilization measures must be initiated by the end of the next business day and completed within fourteen (14) days from the date the soil disturbance activity has permanently ceased.

Final site stabilization is achieved when all soil-disturbing activities at the site have been completed and a uniform, perennial vegetative cover with a density of 80 percent has been established or equivalent stabilization measures (such as the use of mulches or geotextiles) have been employed on all unpaved areas and areas not covered by permanent structures.

5.2.2 Rock Outlet Protection

Rock outlet protection shall be installed at the locations as indicated and detailed on the accompanying plans. The installation of rock outlet protection will reduce the velocity and energy of water, such that the flow will not erode downstream surfaces.

5.2.3 Permanent Turf Reinforcement

Permanent turf reinforcement mats (TRMs) provide long-term erosion protection and vegetation establishment assistance while permanently reinforcing vegetation. TRMs shall be installed on slopes/channels where specified. TRM's provide two key advantages. First, their unique fiber shape and 3-D pattern create a thick matrix of voids that trap seed, soil, and water in place for quicker, thicker vegetation growth. Secondly, they provide additional reinforcement that doubles the vegetation's natural erosion protection abilities by remaining a permanent part of the application and anchoring mature plants to the soil for superior, long-term erosion resistance.

5.3 Other Pollutant Controls

Part I.B.1.e of GP-0-20-001 prohibits discharges from construction material wastewater, pollutants used in vehicle and equipment operation and maintenance, vehicle and equipment washing and toxic or hazardous substances.

The following table identifies materials and/or chemicals commonly used and/or stored on construction sites and should be addressed in the site-specific spill prevention and response plan:

5.4 Construction Housekeeping Practices

During the construction phase, the Contractor(s) will implement the following measures:

5.4.1 Sediment Sweeping/Vacuuming

Any sediment that is tracked by construction vehicles or erosion onto adjacent public or private impervious surfaces must be swept or vacuumed, utilizing self-propelled and/or walk-behind equipment, and removed on a daily basis. Kick brooms and sweeper attachments are not an acceptable means of sweeping. Sweeping or vacuuming should not take place while tracked sediment is wet. If tracked sediment is compacted, the sediment must be scraped loose prior to sweeping or vacuuming.

5.4.2 Material Stockpiles

Material resulting from clearing and grubbing operations that will be stockpiled on-site, must be adequately protected with downgradient erosion and sediment controls.

5.4.3 Equipment Cleaning and Maintenance

The Contractor(s) will designate areas for equipment cleaning, maintenance, and repair. The Contractor(s) and subcontractor(s) will utilize those areas. The areas will be protected by a temporary perimeter berm.

5.4.4 Detergents

The use of detergents for large-scale washing is prohibited (i.e., vehicles, buildings, pavement surfaces, etc.)

5.4.5 Spill Prevention and Response

A Spill Prevention and Response Plan shall be developed, for the pollutants identified in Section 5.3, for the site by the Contractor(s) that addresses the following:

1. Reducing chance of spills
2. Stopping the source of spills

3. Containing and cleaning up spills
4. Disposing of materials contaminated by spills
5. Training personnel responsible for spill prevention/response
6. Material handling procedures
7. Material storage requirements

The plan shall detail the steps required in the event of an accidental spill and shall identify contact names and phone numbers of people and agencies that must be notified.

The plan shall include Safety Data Sheets (SDS) for all materials to be stored on-site. All workers on-site will be required to be trained on safe handling and spill prevention procedures for all materials used during construction. Regular tailgate safety meetings shall be held and all workers that are expected on the site during the week shall be required to attend.

5.4.6 Concrete Washout Areas

A temporary concrete washout area shall be provided for every project where concrete will be poured or otherwise formed on-site and shall consist of an excavated or above-ground lined construction pit where concrete trucks or equipment can be washed out after their loads have been discharged. Waste generated from concrete wash water that shall not be allowed to flow into drainage ways, inlets, receiving waters, highway right-of-way, or any location other than the designated concrete washout area(s). Proper signage shall be placed adjacent to the facility to designate the "Concrete Washout Area". Locate the facility a minimum of 100-feet from drainage swales, storm drain inlets, wetlands, streams, and other surface waters. Prevent surface water from entering the washout area.

The hardened residue from the concrete wash areas will be disposed of in the same manner as other non-hazardous construction waste materials. Maintenance of the washout area shall include removal of hardened material when 75% of the storage capacity is filled, and a minimum freeboard of 12 inches shall be maintained. The Contractor will be responsible for seeing that these procedures are followed. The project may require the use of multiple concrete washout areas based on the frequency of concrete pours.

5.4.7 Material Storage

Construction materials shall be stored in a dedicated staging area. The staging area shall be located in an area that prevents negative impacts of construction materials on stormwater quality.

Chemicals, paints, solvents, fertilizers, and other toxic material must be stored in waterproof containers. Except during application, the contents must be kept in trucks or within storage facilities. Runoff containing such material must be collected, removed from the site, treated, and disposed of at an approved solid waste or chemical disposal facility.

6.0 INSPECTIONS, MAINTENANCE, AND REPORTING

6.1 Inspection and Maintenance Requirements

6.1.1 Pre-Construction Inspection and Certification

Prior to the commencement of construction, the Qualified Inspector/Qualified Professional shall conduct an assessment of the site and certify that the appropriate erosion and sediment control measures have

been adequately installed and implemented. The Contractor shall contact the Qualified Inspector/Qualified Professional once the erosion and sediment control measures have been installed.

6.1.2 Construction Phase Inspections and Maintenance

A Qualified Inspector/Qualified Professional, as defined in Appendix A of the General Permit GP-0-20-001, shall conduct regular site inspections between the time this SWPPP is implemented and final site stabilization. Site inspections shall occur at an interval of at least once every seven (7) calendar days.

The purpose of site inspections is to assess performance of pollutant controls. Based on these inspections, the Qualified Inspector/Qualified Professional will decide whether it is necessary to modify this SWPPP, add or relocate sediment barriers, or whatever else may be needed in order to prevent pollutants from leaving the site via stormwater runoff. The general contractor has the duty to cause pollutant control measures to be repaired, modified, maintained, supplemented, or whatever else is necessary in order to achieve effective pollutant control.

Examples of particular items to evaluate during site inspections are listed below. This list is not intended to be comprehensive. During each inspection the inspector must evaluate overall pollutant control system performance as well as particular details of individual system components. Additional factors should be considered as appropriate to the circumstances.

1. Locations where vehicles enter and exit the site must be inspected for evidence of off-site sediment tracking. A stabilized construction access will be constructed where vehicles enter and exit. This access will be maintained or supplemented as necessary to prevent sediment from leaving the site on vehicles.
2. Sediment barriers must be inspected and, if necessary, they must be enlarged or cleaned in order to provide additional capacity. All material from behind sediment barriers will be stockpiled on the up slope side. Additional sediment barriers must be constructed as needed.
3. Inspections will evaluate disturbed areas and areas used for storing materials that are exposed to rainfall for evidence of, or the potential for, pollutants entering the drainage system. If necessary, the materials must be covered or original covers must be repaired or supplemented. Also, protective berms must be constructed, if needed, in order to contain runoff from material storage areas.
4. Grassed areas will be inspected to confirm that a healthy stand of grass is maintained. The site has achieved final stabilization once all areas are covered with building foundation or pavement, or have a stand of grass with at least 80 percent density. The density of 80 percent or greater must be maintained to be considered as stabilized. Areas must be watered, fertilized, and reseeded as needed to achieve this goal.
5. All discharge points must be inspected to determine whether erosion control measures are effective in preventing significant impacts to receiving waters.

The inspection reports must be completed entirely and additional remarks should be included if needed to fully describe a situation. An important aspect of the inspection report is the description of additional measures that need to be taken to enhance plan effectiveness. The inspection report must identify whether the site was in compliance with the SWPPP at the time of inspection and specifically identify all incidents of non-compliance.

Within one (1) business day of the completion of an inspection, the *Qualified Inspector/Qualified Professional* shall notify the Owner/Operator and appropriate contractor or subcontractor of any corrective actions that need to be taken. The contractor or subcontractor shall begin implementing the

corrective actions within one (1) business day of the notification and shall complete the corrective actions in a reasonable time frame.

In addition to the inspections performed by the *Qualified Inspector/Qualified Professional*, the Contractor shall perform routine inspections that include a visual check of all erosion and sediment control measures. All inspections and maintenance shall be performed in accordance with the inspection and maintenance schedule provided on the accompanying plans. Sediment removed from erosion and sediment control measures will be exported from the site, stockpiled for later use, or used immediately for general non-structural fill.

It is the responsibility of the general contractor to assure the adequacy of site pollutant discharge controls. Actual physical site conditions or contractor practices could make it necessary to install more structural controls than are shown on the accompanying plans. (For example, localized concentrations of runoff could make it necessary to install additional sediment barriers, sediment traps, etc.) Assessing the need for additional controls and implementing them or adjusting existing controls will be a continuing aspect of this SWPPP until the site achieves final stabilization.

6.1.3 Temporary Suspension of Construction Activities

For construction sites where soil disturbance activities have been temporarily suspended (e.g. Winter shutdown) and temporary stabilization measures have been applied to all disturbed areas, the frequency of Qualified Inspector/Qualified Professional inspections can be reduced to once every 30 calendar days. Prior to reducing the frequency of inspections, the Owner/Operator shall notify the NYSDEC Region 3 stormwater contact person and the City of Poughkeepsie in writing.

6.1.4 Partial Project Completion

For construction sites where soil disturbance activities have been shut down with partial project completion, all areas disturbed as of the project shutdown date have achieved final stabilization, and all post-construction stormwater management practices required for the completed portion of the project have been constructed in conformance with the SWPPP and are operational, the inspections by the Qualified Inspector/Qualified Professional can stop. Prior to the shutdown, the Owner/Operator shall notify the NYSDEC Region 3 stormwater contact person and the City of Poughkeepsie in writing.

If soil disturbance activities have not resumed within two years from the date of shutdown, a Notice of Termination (NOT) shall be properly completed and submitted to the NYSDEC.

6.1.5 Post-Construction Inspections and Maintenance

Inspections and maintenance of final stabilization measures and post-construction stormwater management practices shall be performed in accordance with Appendix G, once all disturbed areas are stabilized and all stormwater management systems are in place and operable.

6.2 Reporting Requirements

6.2.1 Inspection Reports

Pursuant to Part IV.C of GP-0-20-001, inspection reports shall be prepared for the duration of construction, as outlined herein, and shall be signed by the *Qualified Inspector* or *Qualified Professional*. A sample inspection form is provided in Appendix F.

At a minimum, each inspection report shall record the following information:

1. Date and time of inspection.
2. Name and title of person(s) performing inspection.
3. A description of the weather and soil conditions (e.g. dry, wet, saturated) at the time of the inspection.
4. A description of the condition of the runoff at all points of discharge from the construction site. This shall include identification of any discharges of sediment from the construction site. Include discharges from conveyance systems (i.e. pipes, culverts, ditches, etc.) and overland flow.
5. A description of the condition of all natural surface waterbodies located within, or immediately adjacent to, the property boundaries of the construction site which receive runoff from disturbed areas. This shall include identification of any discharges of sediment to the surface waterbody.
6. Identification of all erosion and sediment control practices and pollution prevention measures that need repair or maintenance.
7. Identification of all erosion and sediment control practices and pollution prevention measures that were not installed properly or are not functioning as designed and need to be reinstalled or replaced.
8. Description and sketch of areas with active soil disturbance activity, areas that have been disturbed but are inactive at the time of the inspection, and areas that have been stabilized (temporary and/or final) since the last inspection.
9. Indication of the current phase of construction of all post-construction stormwater management practices and identification of all construction that is not in conformance with the SWPPP and technical standards.
10. Corrective action(s) that must be taken to install, repair, replace or maintain erosion and sediment control practices and pollution prevention measures; and to correct deficiencies identified with the construction of the post-construction stormwater management practice(s).
11. Identification and status of all corrective actions that were required by previous inspection.
12. Color photographs, with date stamp, that clearly show the condition of all practices that have been identified as needing corrective actions. The *Qualified Inspector/Qualified Professional* shall attach paper color copies of the digital photographs to the inspection report being maintained onsite within seven (7) calendar days of the date of the inspection. The *Qualified Inspector/Qualified Professional* shall also take digital photographs, with date stamp, that clearly show the condition of the practice(s) after the corrective action has been completed. The *Qualified Inspector/Qualified Professional* shall attach the paper color copies of the digital photographs to the inspection report that documents the completion of the corrective action work within seven (7) calendar days of that inspection.

6.2.2 Site Log Book

Pursuant to Part II.D.2 of GP-0-20-001, the Owner/Operator shall retain a copy of the General Permit, NOI, NOI Acknowledgment Letter, MS4 SWPPP Acceptance Form (if applicable), inspection reports, contractor and subcontractor certification forms, and all documentation necessary to demonstrate eligibility under the permit, at the construction site from commencement of construction activity until the date that all areas of disturbance have achieved final stabilization and the Notice of Termination has been submitted to the NYSDEC.

The Site Log Book shall be maintained on-site in a secure location (i.e. job trailer, on-site construction office, or mailbox with lock) and must be accessible during normal business hours to an individual performing a compliance inspection.

6.2.3 Post Construction Records and Archiving

Following construction, the Owner/Operator shall retain copies of the SWPPP, the complete construction Site Log Book, and records of all data used to complete the NOI to be covered by this permit, for a period of at least five years from the date that the site is finally stabilized. This period may be extended by the NYSDEC, at its sole discretion, at any time upon written notification.

Records shall be maintained of all post construction inspections and maintenance work performed in accordance with the requirements outlined in Appendix G.

7.0 SWPPP IMPLEMENTATION RESPONSIBILITIES

A summary of the responsibilities and obligations of all parties involved with compliance with the NYSDEC SPDES General Permit GP-0-20-00 conditions is outlined in the subsequent sections. For a complete listing of the definitions, responsibilities, and obligations, refer to the SPDES General Permit GP-0-20-001 presented in Appendix J.

7.1 Owner's/Operator's Responsibilities

1. Ensure that control measures are selected, designed, installed, implemented and maintained to minimize the discharge of pollutants and prevent a violation of the water quality standards, meeting the non-numeric effluent limitations in Part I.B.1.(a)-(f) of the SPDES General Permit and in accordance with the New York State Standards and Specifications for Erosion and Sediment Control, dated November 2016.

2. Ensure that practices are selected, designed, installed, and maintained to meet the performance criteria in the Design Manual. Practices must be designed to meet the applicable sizing criteria in Part I.C.2.a., b., c. or d. of GP-0-20-001.

3. Retain the services of a "Qualified Inspector" or "Qualified Professional" as defined under Section 2.1, to provide the services outlined in Section 2.5 "Qualified Inspector's/Qualified Professional's Responsibilities."

4. Retain the services of a "Qualified Professional," as defined under Section 2.1, to provide the services outlined in Section 2.3 "Owner's/Operator's Engineers Responsibilities."

5. Have an authorized corporate officer sign the Owner/Operator Certification Form to accompany the eNOI. A copy of the completed NOI is included in Appendix B.

6. Submit the electronic version of the NOI (eNOI) along with the MS4 SWPPP acceptance form using the NYSDEC's website (http://www.dec.ny.gov/chemical/43133.html).

7. Pay the required initial and annual fees upon receipt of invoices from NYSDEC. These invoices are generally issued in the fall of each year. The initial fee is calculated as $110.00 per acre disturbed plus $675.00 per acre of net increase in impervious cover, and the annual fee is $110.00.

8. Prior to the commencement of construction activity, identify the contractor(s) and subcontractor(s) that will be responsible for implementing the erosion and sediment control measures and stormwater management practices described in this SWPPP. Have each of these

contractors and subcontractors identify at least one "Trained Contractor", as defined under Section 2.1 that will be responsible for the implementation of the SWPPP. Ensure that the Contractor has at least one "Trained Contractor" on site on a daily basis when soil disturbance activities are being performed.

9. Schedule a pre-construction meeting which shall include the City of Poughkeepsie representative, Owner's/Operator's Engineer, Qualified Inspector, Contractor, and their sub-contractors to discuss responsibilities as they relate to the implementation of this SWPPP.

10. Retain the services of an independent certified materials testing and inspection firm operating under the direction of a licensed Professional Engineer to perform regular tests, inspections, and certifications of the construction materials used in the construction of all post-construction stormwater management practices.

11. Retain the services of a NYS licensed land surveyor to perform an as-built topographic survey of the completed post-construction stormwater management facilities.

12. Require the Contractor to fully implement the SWPPP prepared for the site by the Owner/Operator's Engineer to ensure that the provisions of the SWPPP are implemented from the commencement of construction activity until all areas of disturbance have achieved final stabilization and the Notice of Termination (NOT) has been submitted to the NYSDEC.

13. Forward a copy of the NOI Acknowledgement Letter received from the regulatory agency to the Owner's/Operator's Engineer for project records, and to the Contractor for display at the construction site.

14. Maintain a copy of the General Permit (GP-0-20-001), NOI, NOI Acknowledgement Letter, SWPPP, MS4 SWPPP Acceptance Form, inspection reports, Spill Prevention, Countermeasures, Cleanup ("SPCC") Plan, and all documentation in accordance with Part I.F.8.a.-d of GP-0-20-001 necessary to demonstrate eligibility with the permit at the construction site, until all disturbed areas have achieved final stabilization and the NOT has been submitted to the NYSDEC. Place documents in a secure location that must be accessible during normal business hours to an individual performing a compliance inspection.

15. Prior to submitting a Notice of Termination, ensure for post-construction stormwater management practice(s) that are privately owned, the Owner/Operator has a deed restriction in place that requires operation and maintenance of the practice(s) in accordance with the operation and maintenance plan.

16. Submit a Notice of Termination (NOT) form (see Appendix B) within 48 hours of receipt of the Owner's/Operator's Engineer's certification of final site stabilization to the following:

    NOTICE OF TERMINATION
    NYS DEC, Bureau of Water Permits
    625 Broadway, 4th Floor
    Albany, New York 12233-3505

    City of Poughkeepsie
    62 Civic Center Plaza
    Poughkeepsie, NY 12601

17. Request and receive all SWPPP records from the Owner's/Operator's Engineer and archive those records for a minimum of five (5) years after the NOT is filed.

18. Implement the Post-Construction Inspections and Maintenance procedures outlined in Appendix G.

19. The NOI, SWPPP, and inspection reports required by GP-0-20-001 are public documents that the Owner/Operator must make available for review and copying by any person within five (5) business days of the Owner/Operator receiving a written request by any such person to review the NOI, SWPPP, or inspection reports. Copying of documents will be done at the requester's expense.

20. The Owner/Operator must keep the SWPPP current so that it at all times accurately documents the erosion and sediment controls practices that are being used or will be used during construction, and all post-construction stormwater management practices that will be constructed on the site. At a minimum, the Owner/Operator shall amend the SWPPP, including construction drawings:

    a) Whenever the current provisions prove to be ineffective in minimizing pollutants in stormwater discharges from the project site;

    b) Whenever there is a change in design, construction, or operation at the construction site that has or could have an effect on the discharge of pollutants; and

    c) To address issues or deficiencies identified during an inspection by the "Qualified Inspector," the Department, or other Regulatory Authority.

    d) To document the final construction conditions.

21. When property ownership changes or when there is a change in operational control over the construction plans and specifications, the original owner or operator must notify the new owner or operator, in writing, of the requirement to obtain permit coverage by submitting a NOI with the Department. For construction activities subject to the requirements of a regulated, traditional land use control MS4, the original owner or operator must also notify the MS4, in writing, of the change in ownership at least 30 calendar days prior to the change in ownership.

    a) Once the new owner or operator obtains permit coverage, the original owner or operator shall then submit a completed NOT with the name and permit identification number of the new owner or operator to the Department at the address in Part II.B.1. of the permit. If the original owner or operator maintains ownership of a portion of the construction activity and will disturb soil, they must maintain their coverage under the permit.

    b) Permit coverage for the new owner or operator will be effective as of the date the Department receives a complete NOI, provided the original owner or operator was not subject to a sixty (60) business day authorization period that has not expired as of the date the Department receives the NOI from the new owner or operator.

7.2 Owner's/Operator's Engineer's Responsibilities

1. Prepare the SWPPP using good engineering practices, best management practices, and in compliance with all federal, state, and local regulatory requirements.

2. Prepare the electronic Notice of Intent (eNOI) (see Appendix B) and sign the "SWPPP Preparer Certification Form." Forward the Owner/Operator Certification Form to the Owner/Operator for signature.

3. Provide copies of the SWPPP to the City of Poughkeepsie once all signatures and attachments are complete.

4. Enter Contractor's information in Section 2.5 "SWPPP Participants" once a Contractor is selected by the Owner/Operator.

5. Participate in a pre-construction meeting which shall include the City of Poughkeepsie representative, Owner/Operator, Qualified Inspector, Contractor, and all subcontractors to discuss responsibilities as they relate to the implementation of this SWPPP.

6. Update the SWPPP each time there is a significant modification to the pollution prevention measures or a change of the principal Contractor working on the project who may disturb site soil.

7.3 Contractor's Responsibilities

1. Sign the SWPPP Contractor's Certification Form contained within Appendix B and forward to the Owner's/Operator's Engineer for inclusion in the Site Log Book.

2. Identify at least one Trained Contractor that will be responsible for implementation of this SWPPP. Ensure that at least one Trained Contractor is on site on a daily basis when soil disturbance activities are being performed. The Trained Contractor shall inspect the erosion and sediment control practices and pollution prevention measures being implemented within the active work area daily to ensure that they are being maintained in effective operating conditions at all times. If deficiencies are identified, the contractor shall begin implementing corrective actions within one business day and shall complete the corrective actions in a reasonable time frame.

3. Provide the names and addresses of all subcontractors working on the project site. Require all subcontractors who will be involved with construction activities that will result in soil disturbance to identify at least one Trained Contractor that will be on site on a daily basis when soil disturbance activities are being performed; and to sign a copy of the Subcontractor's Certification Form contained within Appendix B, then forward to the Owner's/Operator's Engineer for inclusion into the Site Log Book. This information must be retained as part of the Site Log Book.

4. Maintain a Spill Prevention and Response Plan in accordance with requirements outlined in Section 5 of this SWPPP. This plan shall be provided to the Owner's/Operator's Engineer for inclusion in the Site Log Book, prior to mobilization on-site.

5. Participate in a pre-construction meeting which shall include the City of Poughkeepsie representative, Owner/Operator, Owner's/Operator's Engineer, Qualified Inspector, and all subcontractors to discuss responsibilities as they relate to the implementation of this SWPPP.

6. If Contractor plans on utilizing adjacent properties for material, waste, borrow, or equipment storage areas, or if Contractor plans to engage in industrial activity other than construction (such as operating asphalt and/or concrete plants) at the site, Contractor shall submit appropriate documentation to the Owner's/Operator's Engineer so that the SWPPP can be modified accordingly.

7. Implement site stabilization, erosion and sediment control measures, and other requirements of the SWPPP.

8. In accordance with the requirements in the most current version of the NYS Standards and Specifications for Erosion and Sediment Control, conduct inspections of erosion and sediment control measures installed at the site to ensure that they remain in effective operating condition at all times. Prepare and retain written documentation of inspections as well as of all repairs/maintenance activities performed. This information must be retained as part of the Site Log Book.

9. Begin implementing corrective actions within one (1) business day of receipt of notification by the Qualified Inspector/Qualified Professional that deficiencies exist with the erosion and sediment control measures employed at the site. Corrective actions shall be completed within a reasonable time frame.

10. Maintain a record of the date(s) and location(s) that soil restoration is performed in accordance with the accompanying plans and NYSDEC Division of Water's publication "Deep-Ripping and Decompaction," dated April 2008. A copy of this is publication is provided in Appendix H. The record that is to be maintained shall be a copy of the overall site grading plan delineating the area(s) and date(s) that the soil was restored.

11. Upon completion of all construction at the site, the contractor responsible for overall SWPPP Compliance shall sign the certification on their Contractor Certification Form indicating that: a.) all temporary erosion and sediment control measures have been removed from the site, b.) the on-site soils disturbed by construction activity have been restored in accordance with the SWPPP and the NYSDEC Division of Water's publication "Deep-Ripping and Decompaction," and c.) all permanent stormwater management practices required by the SWPPP have been installed in accordance with the contract documents.

7.4 Qualified Inspector's/Qualified Professional's Responsibilities

1. Participate in a pre-construction meeting with the City of Poughkeepsie representative, Owner/Operator, Owner/Operator's Engineer, Contractor, and their subcontractors to discuss responsibilities as they relate to the implementation of this SWPPP.

2. Conduct an initial assessment of the site prior to the commencement of construction and certify in an inspection report that the appropriate erosion and sediment control measures described within this SWPPP have been adequately installed and implemented to ensure overall preparedness of the site.

3. Provide on-site inspections to determine compliance with the SWPPP. Site inspections shall occur at an interval of at least once every seven calendar days. A written inspection report shall be provided to the Owner/Operator and general contractor within one business day of the completion of the inspection, with any deficiencies identified. A sample inspection form is provided in Appendix F.

4. Prepare an inspection report subsequent to each and every inspection that shall include/address the items listed in Part IV.C.4.a-k of GP-0-20-001. Sign all inspection reports and maintain on site with the SWPPP.

5. Notify the owner/operator and appropriate contractor or subcontractor of any corrective actions that need to be taken.

6. Prepare a construction Site Log Book to be used as a record of all inspection reports generated throughout the duration of construction. Ensure that the construction Site Log Book is maintained and kept up-to-date throughout the duration of construction.

7. Review the Contractor's SWPPP records on a periodic basis to ensure compliance with the requirements for daily reports, soil restoration, inspections, and maintenance logs.

8. Based on the as-built survey and material testing certifications performed by others, the Qualified Professional shall perform evaluations of the completed stormwater management practices to determine whether they were constructed in accordance with this SWPPP.

9. The Qualified Professional shall conduct a final site assessment and prepare a certification letter to the Owner/Operator indicating that, upon review of the material testing and inspection reports prepared by the firm retained by the Owner/Operator, review of the completed topographic survey, and evaluation of the completed stormwater management facilities, the stormwater management facilities have been constructed substantially in accordance with the contract documents and should function as designed.

10. Prepare the Notice of Termination (NOT). The Qualified Professional shall sign the NOT Certifications VI (Final Stabilization) and VII (Post-construction Stormwater Management Practices), and forward the NOT to the Owner/Operator for signature on Certification VIII (Owner/Operator Certification).

11. Transfer the SWPPP documents, along with all NOI's, permit certificates, NOT's, construction Site Log Book, and written records required by the General Permit to the Owner/Operator for archiving.

7.5 SWPPP Participants

1. Owner's/Operator's Engineer [2]: Christopher Lapine, PE
   LaBella Associates, DPC
   21 Fox Street
   Poughkeepsie, NY 12601
   Phone: (845) 454-3980

2. Owner/Operator [3]: Mr. Michael Abuladze, CEO
   ARGO Development
   95 Chestnut Ridge Rd
   Montvale, NJ 07645

3. Contractor[4,6]:

   Name and Title: _____

   Company Name: _____

   Mailing Address: _____

   _____

   Phone: _____

   Fax: _____

[2] *Refer to Appendix B for the SWPPP Preparer Certification Form.*
[3] *Refer to Appendix B for the Owner/Operator Certification Form.*
[5] *Refer to Appendix B for Contractor and Subcontractor Certification Form.*
[6] *Contractor's information to be entered once the Contractor has been selected.*

APPENDIX A:
FIGURES

A-1: Site Location Map
A-2: Soils Map
A-3: Historic Places Screening Map
A-4: Environmental Resource Map
A-5: Pre-Development Watershed Delineation Map
A-6: Post-Development Watershed Delineation Map

LaBella
Powered by partnership.

This Page Intentionally Left Blank



Sources:
1. Project Area: LaBella 2022; Regrid 2021
2. Streets: NYS GIS Program Office 2022
3. Basemap: USGS Topo Map

LaBella
Powered by partnership.

South Avenue,
City of Poughkeepsie,
Dutchess Co., New York

South Avenue
ARGO Development

LaBella Project No: 2222201
Date: 11/14/2022

USGS Location Map

FIGURE 1

Creator: EG Reviewer: KP

Path: B:\GIS\DIG\Projects\FEAF\ARGO\Maps\MXD\2022_11\Fig1_USGS_Location_Map.mxd

Sources:
1. Project Area: LaBella 2022
2. Soil Map Unit: USDA/NRCS 2021
3. Streets: NYS GIS Program Office 2022
4. Basemap: Bing Maps

LaBella
Powered by partnership.

South Avenue,
City of Poughkeepsie,
Dutchess Co., New York

South Avenue
ARGO Development

LaBella Project No: 2222201
Date: 11/14/2022

Soils Map

FIGURE 2

Creator: EG Reviewer: KP

Path: B:\GIS\DIG\Projects\FEAF\ARGO\Maps\MXD\2022_11\Fig4_Soils_Map.mxd



Creator: EG Reviewer: KP

Path: B:\GIS\DIG\Projects\FEAF\ARGO\Maps\MXD\2022_11\Fig7_CRIS.mxd

Sources:
1. Project Area: LaBella, 2022
2. Archaeologically Sensitive Areas/National Register Sites: NYSOPRHP Cultural Resource Information System (CRIS), 2022
3. Streets: NYS GIS Program Office, 2022
4. Basemap: Bing Maps

LaBella
Powered by partnership.

South Avenue,
City of Poughkeepsie,
Dutchess Co., New York

South Avenue
ARGO Development

LaBella Project No: 2222201
Date: 11/15/2022

NYSOPRHP Cultural Resource Information System (CRIS) Map

FIGURE 3

Creator: EG Reviewer: KP

Path: B:\GIS\DIG\Projects\FEAF\ARGO\Maps\MXD\2022_11\Fig6_DEC_ERM_Map.mxd

Sources:
1. Project Area: LaBella 2022
2. Rare Plants or Animals and Significant Natural Communities: NYSDEC Environmental Resource Mapper (ERM) 2022
3. NYSDEC Wetlands: NYSDEC 2006
4. Streets: NYS GIS Program Office 2022
5. Basemap: Bing Maps

LaBella
Powered by partnership.

South Avenue,
City of Poughkeepsie,
Dutchess Co., New York

South Avenue
ARGO Development

LaBella Project No: 2222201
Date: 11/15/2022

NYSDEC Environmental Resource Map

FIGURE 4

1 PREDEVELOPMENT WATERSHED MAP
FIG 5 SCALE: 1" = 30'

11/29/2022 1:13:01 PM
Z:\2022Projects\ARGO\2222201 - South Ave Multi Family Dev\06_Drawings\Civil\FIGS_2222201_PRE_DEV_MAP.dwg

LaBella
Powered by partnership.

21 Fox Street
Poughkeepsie, NY 12601
(845) 454-3980

labellapc.com

It is a violation of New York Education Law Article 145 Sec.7209, for any person, unless acting under the direction of a licensed architect, professional engineer, or land surveyor, to alter an item in any way. If an item bearing the seal of an architect, engineer, or land surveyor is altered; the altering architect, engineer, or land surveyor shall affix to the item their seal and notation "altered by" followed by their signature and date of such alteration, and a specific description of the alteration.

© 2022 LaBella Associates

APPLICANT NAME & ADDRESS:

ARGO DEVELOPMENT
95 CHESTNUT RIDGE ROAD
MONTVALE, NJ 07645

PROJECT NAME & LOCATION:

SOUTH AVE
MULTI-FAMILY DEVELOPMENT
SOUTH AVENUE
CITY OF POUGHKEEPSIE, NY 12601

NO:	DATE:	DESCRIPTION:
Revisions		

PROJECT NUMBER: 2222201
DRAWN BY:
REVIEWED BY: CPL
ISSUED FOR: PLANNING BOARD REVIEW
DATE: 11/28/2022
DRAWING NAME:

PREDEVELOPMENT WATERSHED MAP

DRAWING NUMBER:

FIG 5

1 FIG 6 POSTDEVELOPMENT WATERSHED MAP

SCALE: 1" = 30'

LaBella
Powered by partnership.

21 Fox Street
Poughkeepsie, NY 12601
(845) 454-3980

labellapc.com

It is a violation of New York Education Law Article 145 Sec.7209, for any person, unless acting under the direction of a licensed architect, professional engineer, or land surveyor, to alter an item in any way. If an item bearing the seal of an architect, engineer, or land surveyor is altered; the altering architect, engineer, or land surveyor shall affix to the item their seal and notation "altered by" followed by their signature and date of such alteration, and a specific description of the alteration.

© 2022 LaBella Associates

APPLICANT NAME & ADDRESS:

ARGO DEVELOPMENT
95 CHESTNUT RIDGE ROAD
MONTVALE, NJ 07645

PROJECT NAME & LOCATION:

SOUTH AVE
MULTI-FAMILY DEVELOPMENT
SOUTH AVENUE
CITY OF POUGHKEEPSIE, NY 12601

NO:	DATE:	DESCRIPTION:
Revisions		

PROJECT NUMBER: 2222201

DRAWN BY:

REVIEWED BY: CPL

ISSUED FOR: PLANNING BOARD REVIEW

DATE: 11/28/2022

DRAWING NAME:

POSTDEVELOPMENT WATERSHED MAP

DRAWING NUMBER:

FIG 6

11/29/2022 1:19:26 PM
Z:\2022Projects\ARGO\2222201 - South Ave Multi Family Dev\05_Drawings\Civil\FIG6_2222201_POST_DEV_MAP.dwg

APPENDIX B:
FORMS

Notice of Intent
MS4 SWPPP Acceptance Form
Contractor and Subcontractor Certification Forms
Notice of Termination (NOT)

LaBella
Powered by partnership.

This Page Intentionally Left Blank

0644089821

NOTICE OF INTENT

New York State Department of Environmental Conservation
Division of Water
625 Broadway, 4th Floor
Albany, New York 12233-3505

NYR _____
(for DEC use only)

Stormwater Discharges Associated with Construction Activity Under State Pollutant Discharge Elimination System (SPDES) General Permit # GP-0-15-002

All sections must be completed unless otherwise noted. Failure to complete all items may result in this form being returned to you, thereby delaying your coverage under this General Permit. Applicants must read and understand the conditions of the permit and prepare a Stormwater Pollution Prevention Plan prior to submitting this NOI. Applicants are responsible for identifying and obtaining other DEC permits that may be required.

-IMPORTANT-
RETURN THIS FORM TO THE ADDRESS ABOVE

OWNER/OPERATOR MUST SIGN FORM

Owner/Operator Information

Owner/Operator (Company Name/Private Owner Name/Municipality Name)
ARGO Development

Owner/Operator Contact Person Last Name (NOT CONSULTANT)
Abuladze

Owner/Operator Contact Person First Name
Michael

Owner/Operator Mailing Address
95 Chestnut Ridge Rd

City
Montvale

State
NJ

Zip
07645-____

Phone (Owner/Operator)
201-549-9090

Fax (Owner/Operator)
___-___-____

Email (Owner/Operator)
mike@argodev.com

FED TAX ID
__-_____ (not required for individuals)

Project Site Information

Project/Site Name
South Ave Multi-Family Development

Street Address (NOT P.O. BOX)
South Ave

Side of Street
○ **North** ○ **South** ○ **East** ● **West**

City/Town/Village (THAT ISSUES BUILDING PERMIT)
City of Poughkeepsie

State: NY
Zip: 12601-5584
County: Dutchess
DEC Region: 3

Name of Nearest Cross Street
Academy Street

Distance to Nearest Cross Street (Feet)
450

Project In Relation to Cross Street
○ **North** ● **South** ○ **East** ○ **West**

Tax Map Numbers
Section-Block-Parcel
6061-52-937583

Tax Map Numbers

1. Provide the Geographic Coordinates for the project site in NYTM Units. To do this you **must** go to the NYSDEC Stormwater Interactive Map on the DEC website at:

www.dec.ny.gov/imsmaps/stormwater/viewer.htm

Zoom into your Project Location such that you can accurately click on the centroid of your site. Once you have located your project site, go to the tool boxes on the top and choose "i"(identify). Then click on the center of your site and a new window containing the X, Y coordinates in UTM will pop up. Transcribe these coordinates into the boxes below. For problems with the interactive map use the help function.

X Coordinates (Easting): 588863

Y Coordinates (Northing): 4615867

2. What is the nature of this construction project?

● **New Construction**

○ **Redevelopment with increase in impervious area**

○ **Redevelopment with no increase in impervious area**

3. Select the predominant land use for both pre and post development conditions.
SELECT ONLY ONE CHOICE FOR EACH

Pre-Development Existing Land Use

- ● FOREST
- ○ PASTURE/OPEN LAND
- ○ CULTIVATED LAND
- ○ SINGLE FAMILY HOME
- ○ SINGLE FAMILY SUBDIVISION
- ○ TOWN HOME RESIDENTIAL
- ○ MULTIFAMILY RESIDENTIAL
- ○ INSTITUTIONAL/SCHOOL
- ○ INDUSTRIAL
- ○ COMMERCIAL
- ○ ROAD/HIGHWAY
- ○ RECREATIONAL/SPORTS FIELD
- ○ BIKE PATH/TRAIL
- ○ LINEAR UTILITY
- ○ PARKING LOT
- ○ OTHER

Post-Development Future Land Use

Number of Lots

- ○ SINGLE FAMILY HOME
- ○ SINGLE FAMILY SUBDIVISION
- ○ TOWN HOME RESIDENTIAL
- ● MULTIFAMILY RESIDENTIAL
- ○ INSTITUTIONAL/SCHOOL
- ○ INDUSTRIAL
- ○ COMMERCIAL
- ○ MUNICIPAL
- ○ ROAD/HIGHWAY
- ○ RECREATIONAL/SPORTS FIELD
- ○ BIKE PATH/TRAIL
- ○ LINEAR UTILITY (water, sewer, gas, etc.)
- ○ PARKING LOT
- ○ CLEARING/GRADING ONLY
- ○ DEMOLITION, NO REDEVELOPMENT
- ○ WELL DRILLING ACTIVITY *(Oil, Gas, etc.)
- ○ OTHER

***Note**: for gas well drilling, non-high volume hydraulic fractured wells only

4. In accordance with the larger common plan of development or sale, enter the total project site area; the total area to be disturbed; existing impervious area to be disturbed (for redevelopment activities); and the future impervious area constructed within the disturbed area. (Round to the nearest tenth of an acre.)

Total Site Area	Total Area To Be Disturbed	Existing Impervious Area To Be Disturbed	Future Impervious Area Within Disturbed Area
2.8	2.5	0.0	1.5

5. Do you plan to disturb more than 5 acres of soil at any one time? ○ **Yes** ● **No**

6. Indicate the percentage of each Hydrologic Soil Group(HSG) at the site.

A	B	C	D
97 %	0 %	0 %	3 %

7. Is this a phased project? ○ **Yes** ● **No**

8. Enter the planned start and end dates of the disturbance activities.

Start Date 07/01/2023 - **End Date** 07/01/2024

9. Identify the nearest surface waterbody(ies) to which construction site runoff will discharge.

Name

Hudson River

9a. Type of waterbody identified in Question 9?

- ○ Wetland / State Jurisdiction On Site (Answer 9b)
- ○ Wetland / State Jurisdiction Off Site
- ○ Wetland / Federal Jurisdiction On Site (Answer 9b)
- ○ Wetland / Federal Jurisdiction Off Site
- ○ Stream / Creek On Site
- ○ Stream / Creek Off Site
- ○ River On Site
- ● River Off Site
- ○ Lake On Site
- ○ Lake Off Site
- ○ Other Type On Site
- ○ Other Type Off Site

9b. How was the wetland identified?

- ● Regulatory Map
- ○ Delineated by Consultant
- ○ Delineated by Army Corps of Engineers
- ○ Other (identify)

10. Has the surface waterbody(ies) in question 9 been identified as a 303(d) segment in Appendix E of GP-0-15-002? ○ **Yes** ● **No**

11. Is this project located in one of the Watersheds identified in Appendix C of GP-0-15-002? ○ **Yes** ● **No**

12. Is the project located in one of the watershed areas associated with AA and AA-S classified waters? ○ **Yes** ● **No**
If no, skip question 13.

13. Does this construction activity disturb land with no existing impervious cover and where the Soil Slope Phase is identified as an E or F on the USDA Soil Survey? ○ **Yes** ● **No**
If Yes, what is the acreage to be disturbed?

.

14. Will the project disturb soils within a State regulated wetland or the protected 100 foot adjacent area? ○ **Yes** ● **No**

15. Does the site runoff enter a separate storm sewer system (including roadside drains, swales, ditches, culverts, etc)? ◉ Yes ○ No ○ Unknown

16. What is the name of the municipality/entity that owns the separate storm sewer system?

NYS Dept of Transportation

17. Does any runoff from the site enter a sewer classified as a Combined Sewer? ○ Yes ◉ No ○ Unknown

18. Will future use of this site be an agricultural property as defined by the NYS Agriculture and Markets Law? ○ Yes ◉ No

19. Is this property owned by a state authority, state agency, federal government or local government? ○ Yes ◉ No

20. Is this a remediation project being done under a Department approved work plan? (i.e. CERCLA, RCRA, Voluntary Cleanup Agreement, etc.) ○ Yes ◉ No

21. Has the required Erosion and Sediment Control component of the SWPPP been developed in conformance with the current NYS Standards and Specifications for Erosion and Sediment Control (aka Blue Book)? ◉ Yes ○ No

22. Does this construction activity require the development of a SWPPP that includes the post-construction stormwater management practice component (i.e. Runoff Reduction, Water Quality and Quantity Control practices/techniques)? ◉ Yes ○ No
If No, skip questions 23 and 27-39.

23. Has the post-construction stormwater management practice component of the SWPPP been developed in conformance with the current NYS Stormwater Management Design Manual? ◉ Yes ○ No

24. The Stormwater Pollution Prevention Plan (SWPPP) was prepared by:

- ● **Professional Engineer (P.E.)**
- ○ **Soil and Water Conservation District (SWCD)**
- ○ **Registered Landscape Architect (R.L.A)**
- ○ **Certified Professional in Erosion and Sediment Control (CPESC)**
- ○ **Owner/Operator**
- ○ **Other**

SWPPP Preparer
LaBella Associates

Contact Name (Last, Space, First)
Lapine, Christopher

Mailing Address
21 Fox Street

City
Poughkeepsie

State Zip
NY 12601-4724

Phone
845-454-3980

Fax

Email
clapine@labellapc.com

SWPPP Preparer Certification

I hereby certify that the Stormwater Pollution Prevention Plan (SWPPP) for this project has been prepared in accordance with the terms and conditions of the GP-0-15-002. Furthermore, I understand that certifying false, incorrect or inaccurate information is a violation of this permit and the laws of the State of New York and could subject me to criminal, civil and/or administrative proceedings.

First Name
Christopher

MI
P

Last Name
Lapine

Signature

Date
/ /

25. Has a construction sequence schedule for the planned management practices been prepared? ● Yes ○ No

26. Select **all** of the erosion and sediment control practices that will be employed on the project site:

Temporary Structural

- ○ Check Dams
- ○ Construction Road Stabilization
- ◪ Dust Control
- ○ Earth Dike
- ○ Level Spreader
- ○ Perimeter Dike/Swale
- ○ Pipe Slope Drain
- ○ Portable Sediment Tank
- ○ Rock Dam
- ○ Sediment Basin
- ○ Sediment Traps
- ◪ Silt Fence
- ◪ Stabilized Construction Entrance
- ◪ Storm Drain Inlet Protection
- ○ Straw/Hay Bale Dike
- ○ Temporary Access Waterway Crossing
- ○ Temporary Stormdrain Diversion
- ○ Temporary Swale
- ○ Turbidity Curtain
- ○ Water bars

Biotechnical

- ○ Brush Matting
- ○ Wattling

Vegetative Measures

- ○ Brush Matting
- ○ Dune Stabilization
- ○ Grassed Waterway
- ○ Mulching
- ● Protecting Vegetation
- ○ Recreation Area Improvement
- ● Seeding
- ○ Sodding
- ● Straw/Hay Bale Dike
- ○ Streambank Protection
- ○ Temporary Swale
- ● Topsoiling
- ○ Vegetating Waterways

Permanent Structural

- ○ Debris Basin
- ○ Diversion
- ○ Grade Stabilization Structure
- ● Land Grading
- ○ Lined Waterway (Rock)
- ○ Paved Channel (Concrete)
- ○ Paved Flume
- ● Retaining Wall
- ○ Riprap Slope Protection
- ● Rock Outlet Protection
- ○ Streambank Protection

Other

Post-construction Stormwater Management Practice (SMP) Requirements

Important: Completion of Questions 27-39 is not required if response to Question 22 is No.

27. Identify all site planning practices that were used to prepare the final site plan/layout for the project.

- ○ **Preservation of Undisturbed Areas**
- ○ **Preservation of Buffers**
- ○ **Reduction of Clearing and Grading**
- ○ **Locating Development in Less Sensitive Areas**
- ○ **Roadway Reduction**
- ○ **Sidewalk Reduction**
- ○ **Driveway Reduction**
- ○ **Cul-de-sac Reduction**
- ○ **Building Footprint Reduction**
- ○ **Parking Reduction**

27a. Indicate which of the following soil restoration criteria was used to address the requirements in Section 5.1.6("Soil Restoration") of the Design Manual (2010 version).

- ● All disturbed areas will be restored in accordance with the Soil Restoration requirements in Table 5.3 of the Design Manual (see page 5-22).
- ○ Compacted areas were considered as impervious cover when calculating the **WQv Required**, and the compacted areas were assigned a post-construction Hydrologic Soil Group (HSG) designation that is one level less permeable than existing conditions for the hydrology analysis.

28. Provide the total Water Quality Volume (WQv) required for this project (based on final site plan/layout).

Total WQv Required

0.170 **acre-feet**

29. Identify the RR techniques (Area Reduction), RR techniques(Volume Reduction) and Standard SMPs with RRv Capacity in Table 1 (See Page 9) that were used to reduce the Total WQv Required(#28).

Also, provide in Table 1 the total impervious area that contributes runoff to each technique/practice selected. For the Area Reduction Techniques, provide the total contributing area (includes pervious area) and, if applicable, the total impervious area that contributes runoff to the technique/practice.

Note: Redevelopment projects shall use Tables 1 and 2 to identify the SMPs used to treat and/or reduce the WQv required. If runoff reduction techniques will not be used to reduce the required WQv, skip to question 33a after identifying the SMPs.

Table 1 - Runoff Reduction (RR) Techniques and Standard Stormwater Management Practices (SMPs)

	Total Contributing Area (acres)		Total Contributing Impervious Area(acres)
RR Techniques (Area Reduction)			
○ Conservation of Natural Areas (RR-1)		and/or	
○ Sheetflow to Riparian Buffers/Filters Strips (RR-2)		and/or	
○ Tree Planting/Tree Pit (RR-3)		and/or	
○ Disconnection of Rooftop Runoff (RR-4)		and/or	
RR Techniques (Volume Reduction)			
○ Vegetated Swale (RR-5)			
○ Rain Garden (RR-6)			
○ Stormwater Planter (RR-7)			
○ Rain Barrel/Cistern (RR-8)			
○ Porous Pavement (RR-9)			
○ Green Roof (RR-10)			
Standard SMPs with RRv Capacity			
○ Infiltration Trench (I-1)			
○ Infiltration Basin (I-2)			
○ Dry Well (I-3)			
✓ Underground Infiltration System (I-4)			1.26
✓ Bioretention (F-5)			0.26
○ Dry Swale (O-1)			
Standard SMPs			
○ Micropool Extended Detention (P-1)			
○ Wet Pond (P-2)			
○ Wet Extended Detention (P-3)			
○ Multiple Pond System (P-4)			
○ Pocket Pond (P-5)			
○ Surface Sand Filter (F-1)			
○ Underground Sand Filter (F-2)			
○ Perimeter Sand Filter (F-3)			
○ Organic Filter (F-4)			
○ Shallow Wetland (W-1)			
○ Extended Detention Wetland (W-2)			
○ Pond/Wetland System (W-3)			
○ Pocket Wetland (W-4)			
○ Wet Swale (O-2)			

Table 2 - Alternative SMPs (DO NOT INCLUDE PRACTICES BEING USED FOR PRETREATMENT ONLY)

Alternative SMP	Total Contributing Impervious Area(acres)
○ **Hydrodynamic**	
○ **Wet Vault**	
○ **Media Filter**	
○ **Other**	

Provide the name and manufacturer of the Alternative SMPs (i.e. proprietary practice(s)) being used for WQv treatment.

Name

Manufacturer

Note: Redevelopment projects which do not use RR techniques, shall use questions 28, 29, 33 and 33a to provide SMPs used, total WQv required and total WQv provided for the project.

30. Indicate the Total RRv provided by the RR techniques (Area/Volume Reduction) and Standard SMPs with RRv capacity identified in question 29.

Total RRv provided

0.165 **acre-feet**

31. Is the Total RRv provided (#30) greater than or equal to the total WQv required (#28).

○ **Yes** ● **No**

If Yes, go to question 36.
If No, go to question 32.

32. Provide the Minimum RRv required based on HSG.
[Minimum RRv Required = (P)(0.95)(Ai)/12, Ai=(S)(Aic)]

Minimum RRv Required

0.089 **acre-feet**

32a. Is the Total RRv provided (#30) greater than or equal to the Minimum RRv Required (#32)?

● **Yes** ○ **No**

If Yes, go to question 33.
Note: Use the space provided in question #39 to summarize the specific site limitations and justification for not reducing 100% of WQv required (#28). A detailed evaluation of the specific site limitations and justification for not reducing 100% of the WQv required (#28) must also be included in the SWPPP.
If No, sizing criteria has not been met, so NOI can not be processed. SWPPP preparer must modify design to meet sizing criteria.

33. Identify the Standard SMPs in Table 1 and, if applicable, the Alternative SMPs in Table 2 that were used to treat the remaining total WQv(=Total WQv Required in 28 - Total RRv Provided in 30).

Also, provide in Table 1 and 2 the total impervious area that contributes runoff to each practice selected.

Note: Use Tables 1 and 2 to identify the SMPs used on Redevelopment projects.

33a. Indicate the Total WQv provided (i.e. WQv treated) by the SMPs identified in question #33 and Standard SMPs with RRv Capacity identified in question 29.

WQv Provided

0.176 **acre-feet**

Note: For the standard SMPs with RRv capacity, the WQv provided by each practice = the WQv calculated using the contributing drainage area to the practice - RRv provided by the practice. (See Table 3.5 in Design Manual)

34. Provide the sum of the Total RRv provided (#30) and the WQv provided (#33a). 0.341

35. Is the sum of the RRv provided (#30) and the WQv provided (#33a) greater than or equal to the total WQv required (#28)? ● **Yes** ○ **No**

If Yes, go to question 36.
If No, sizing criteria has not been met, so NOI can not be processed. SWPPP preparer must modify design to meet sizing criteria.

36. Provide the total Channel Protection Storage Volume (CPv) required and provided or select waiver (36a), if applicable.

CPv Required

0.00 **acre-feet**

CPv Provided

0.00 **acre-feet**

36a. The need to provide channel protection has been waived because:

○ Site discharges directly to tidal waters or a fifth order or larger stream.

● Reduction of the total CPv is achieved on site through runoff reduction techniques or infiltration systems.

37. Provide the Overbank Flood (Qp) and Extreme Flood (Qf) control criteria or select waiver (37a), if applicable.

Total Overbank Flood Control Criteria (Qp)

Pre-Development

0.02 **CFS**

Post-development

0.00 **CFS**

Total Extreme Flood Control Criteria (Qf)

Pre-Development

1.38 **CFS**

Post-development

1.36 **CFS**

37a. The need to meet the Qp and Qf criteria has been waived because:

- ○ Site discharges directly to tidal waters or a fifth order or larger stream.
- ○ Downstream analysis reveals that the Qp and Qf controls are not required

38. Has a long term Operation and Maintenance Plan for the post-construction stormwater management practice(s) been developed? ● **Yes** ○ **No**

If Yes, Identify the entity responsible for the long term Operation and Maintenance

ARGO Development

39. Use this space to summarize the specific site limitations and justification for not reducing 100% of WQv required(#28). (See question 32a) This space can also be used for other pertinent project information.

40. Identify other DEC permits, existing and new, that are required for this project/facility.

- ○ Air Pollution Control
- ○ Coastal Erosion
- ○ Hazardous Waste
- ○ Long Island Wells
- ○ Mined Land Reclamation
- ○ Solid Waste
- ○ Navigable Waters Protection / Article 15
- ○ Water Quality Certificate
- ○ Dam Safety
- ○ Water Supply
- ○ Freshwater Wetlands/Article 24
- ○ Tidal Wetlands
- ○ Wild, Scenic and Recreational Rivers
- ○ Stream Bed or Bank Protection / Article 15
- ○ Endangered or Threatened Species(Incidental Take Permit)
- ○ Individual SPDES
- ○ SPDES Multi-Sector GP | N | Y | R | 2 | 0 | A | 1 | 9 | 8 |
- ○ Other | | | | | | | | | | | | | | | | | | | | | | | |
- ○ None

41. Does this project require a US Army Corps of Engineers Wetland Permit? ○ **Yes** ◉ **No**
If Yes, Indicate Size of Impact. | | | | | | . |

42. Is this project subject to the requirements of a regulated, traditional land use control MS4? ◉ **Yes** ○ **No**
(If No, skip question 43)

43. Has the "MS4 SWPPP Acceptance" form been signed by the principal executive officer or ranking elected official and submitted along with this NOI? ◉ **Yes** ○ **No**

44. If this NOI is being submitted for the purpose of continuing or transferring coverage under a general permit for stormwater runoff from construction activities, please indicate the former SPDES number assigned. | N | Y | R | 2 | 0 | A | 1 | 9 | 8 |

Owner/Operator Certification

I have read or been advised of the permit conditions and believe that I understand them. I also understand that, under the terms of the permit, there may be reporting requirements. I hereby certify that this document and the corresponding documents were prepared under my direction or supervision. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment for knowing violations. I further understand that coverage under the general permit will be identified in the acknowledgment that I will receive as a result of submitting this NOI and can be as long as sixty (60) business days as provided for in the general permit. I also understand that, by submitting this NOI, I am acknowledging that the SWPPP has been developed and will be implemented as the first element of construction, and agreeing to comply with all the terms and conditions of the general permit for which this NOI is being submitted.

Print First Name

Michael

MI

Print Last Name

Abuladze

Owner/Operator Signature

Date

/ /

NYS Department of Environmental Conservation
Division of Water
625 Broadway, 4th Floor
Albany, New York 12233-3505

MS4 Stormwater Pollution Prevention Plan (SWPPP) Acceptance Form

for

Construction Activities Seeking Authorization Under SPDES General Permit

*(NOTE: Attach Completed Form to Notice Of Intent and Submit to Address Above)

I. Project Owner/Operator Information	
1. Owner/Operator Name:	ARGO Development
2. Contact Person:	Michael Abuladze
3. Street Address:	95 Chestnut Ridge Rd
4. City/State/Zip:	Montvale, NJ 07645
II. Project Site Information	
5. Project/Site Name:	South Ave Multi-Family Development
6. Street Address:	South Ave
7. City/State/Zip:	Poughkeepsie, NY 12601
III. Stormwater Pollution Prevention Plan (SWPPP) Review and Acceptance Information	
8. SWPPP Reviewed by:	Christopher Lapine
9. Title/Position:	Regional Leader
10. Date Final SWPPP Reviewed and Accepted:	
IV. Regulated MS4 Information	
11. Name of MS4:	City of Poughkeepsie
12. MS4 SPDES Permit Identification Number: NYR20A	
13. Contact Person:	Rich DuPike
14. Street Address:	62 Civic Center Plaza
15. City/State/Zip:	Poughkeepsie, NY 12601
16. Telephone Number:	845-451-4192

MS4 SWPPP Acceptance Form - continued

V. Certification Statement - MS4 Official (principal executive officer or ranking elected official) or Duly Authorized Representative

I hereby certify that the final Stormwater Pollution Prevention Plan (SWPPP) for the construction project identified in question 5 has been reviewed and meets the substantive requirements in the SPDES General Permit For Stormwater Discharges from Municipal Separate Storm Sewer Systems (MS4s). Note: The MS4, through the acceptance of the SWPPP, assumes no responsibility for the accuracy and adequacy of the design included in the SWPPP. In addition, review and acceptance of the SWPPP by the MS4 does not relieve the owner/operator or their SWPPP preparer of responsibility or liability for errors or omissions in the plan.

Printed Name:

Title/Position:

Signature:

Date:

VI. Additional Information

(NYS DEC - MS4 SWPPP Acceptance Form - January 2015)

Stormwater Pollution Prevention Plan
Contractor Certification Statement
(Responsible for overall SWPPP Compliance)

South Ave Multi-Family Development
City of Poughkeepsie, Dutchess County, New York

This is to certify that the following contracting firm will be responsible for installing, constructing, repairing, inspecting and/or maintaining the erosion and sediment control practices and post-construction stormwater management control practices required by the SWPPP.

Contracting Firm Information

Name: _____

Address: _____

Telephone & Fax: _____

Trained Contractor(s)[1] Responsible for SWPPP Implementation (Provide name, title, and date of last training)

_____

_____

Prior to commencement of construction activity, the following certification shall be issued:

I hereby certify under penalty of law that I understand and agree to comply with the terms and conditions of the SWPPP and agree to implement any corrective actions identified by the *qualified inspector* during a site inspection. I also understand that the *owner or operator* must comply with the terms and conditions of the most current version of the New York State Pollutant Discharge Elimination System ("SPDES") general permit for stormwater *discharges* from *construction activities* and that it is unlawful for any person to cause or contribute to a violation of *water quality standards*. Furthermore, I am aware that there are significant penalties for submitting false information, that I do not believe to be true, including the possibility of fine and imprisonment for knowing violations.

Printed Name: _____

Title/Position: _____

Signature: _____ Date: _____

Upon completion of construction activities, the following certification shall be issued, prior to issuance of the NOT:

I hereby certify that that all permanent stormwater management practices required by the SWPPP have been installed in accordance with the contract documents. I further certify that all temporary erosion and sediment control measures have been removed from the site, and that the on-site soils disturbed by construction activity have been restored in accordance with the SWPPP and the NYSDEC Division of Water's publication "Deep-Ripping and Decompaction".

Printed Name: _____

Title/Position: _____

Signature: _____ Date: _____

[1] "Trained Contractor" means an employee from a contracting (construction) company that has received four (4) hours of Department endorsed training in proper erosion and sediment control principles from a Soil and Water Conservation District, or other Department endorsed entity. After receiving the initial training, the "trained contractor" shall receive four (4) hours of training every three (3) years. It can also mean an employee from the contracting (construction) company that meets the "qualified inspector" qualifications (e.g. licensed Professional Engineer, Certified Professional in Erosion and Sediment Control (CPESC), Registered Landscape Architect, New York State Erosion and Sediment Control Certificate Program holder, or someone working under the direct supervision of, and at the same company as, the licensed Professional Engineer or Registered Landscape Architect, provided they have received four (4) hours of Department endorsed training in proper erosion and sediment control principles from a Soil and Water Conservation District, or other Department endorsed entity). The "Trained Contractor" will be responsible for the day to day implementation of the SWPPP.

[2] Signatory Requirements:

a. For a corporation, this form shall be signed by (i) a president, secretary, treasurer, or vice-president of the corporation in charge of a principle business function, or any other person who performs similar policy or decision-making functions for the corporation; or (ii) the manager of one or more manufacturing, production or operating facilities, provided the manager is authorized to make management decisions which govern the operation of the regulated facility including having the explicit or implicit duty of making major capital investment recommendations, and initiating and directing other comprehensive measures to assure long term environmental compliance with environmental laws and regulations; the manager can ensure that the necessary systems are established or actions taken to gather complete and accurate information for permit application requirements; and where authority to sign documents has been assigned or delegated to the manager in accordance with corporate procedures.

b. For a partnership or sole proprietorship, this form shall be signed by a general partner or the proprietor, respectively.

c. For a municipality, State, Federal, or other public agency, this form shall be signed by either a principal executive officer or ranking elected official. For purposes of this section, a principal executive officer of a Federal agency includes (i) the chief executive officer of the agency, or (ii) a senior executive officer having responsibility for the overall operations of a principal geographic unit of the agency (e.g. Regional Administrators of EPA).

Stormwater Pollution Prevention Plan
Subcontractor Certification Statement
(whose work involves soil disturbance)

South Ave Multi-Family Development
City of Poughkeepsie, Dutchess County, New York

Each Subcontractor whose work will involve soil disturbance of any kind is required to complete and sign this Certification Statement before commencing any construction activity at the site. This completed Certification Statement(s) shall be maintained at the construction site in the Site Log Book.

Subcontracting Firm Information

Name: _____

Address: _____

_____

Telephone & Fax: _____

Trained Contractor(s)[2] Responsible for SWPPP Implementation (Provide name, title, and date of last training)

_____

_____

Prior to commencement of construction activities, the following certification shall be issued:

I hereby certify under penalty of law that I understand and agree to comply with the terms and conditions of the SWPPP and agree to implement any corrective actions identified by the *qualified inspector* during a site inspection. I also understand that the *owner or operator* must comply with the terms and conditions of the most current version of the New York State Pollutant Discharge Elimination System ("SPDES") general permit for stormwater *discharges* from *construction activities* and that it is unlawful for any person to cause or contribute to a violation of *water quality standards*. Furthermore, I am aware that there are significant penalties for submitting false information, that I do not believe to be true, including the possibility of fine and imprisonment for knowing violations.

Printed Name: _____

Title/Position: _____

Signature: _____ Date: _____

[2] "Trained Contractor" means an employee from a contracting (construction) company that has received four (4) hours of Department endorsed training in proper erosion and sediment control principles from a Soil and Water Conservation District, or other Department endorsed entity. After receiving the initial training, the "trained contractor" shall receive four (4) hours of training every three (3) years. It can also mean an employee from the contracting (construction) company that meets the "qualified inspector" qualifications (e.g. licensed Professional Engineer, Certified Professional in Erosion and Sediment Control (CPESC), Registered Landscape Architect, New York State Erosion and Sediment Control Certificate Program holder, or someone working under the direct supervision of, and at the same company as, the licensed Professional Engineer or Registered Landscape Architect, provided they have received four (4) hours of Department endorsed training in proper erosion and sediment control principles from a Soil and Water Conservation District, or other Department endorsed entity). The "Trained Contractor" will be responsible for the day to day implementation of the SWPPP.

[2] Signatory Requirements:

a. For a corporation, this form shall be signed by (i) a president, secretary, treasurer, or vice-president of the corporation in charge of a principle business function, or any other person who performs similar policy or decision-making functions for the corporation; or (ii) the manager of one or more manufacturing, production or operating facilities, provided the manager is authorized to make management decisions which govern the operation of the regulated facility including having the explicit or implicit duty of making major capital investment recommendations, and initiating and directing other comprehensive measures to assure long term environmental compliance with environmental laws and regulations; the manager can ensure that the necessary systems are established or actions taken to gather complete and accurate information for permit application requirements; and where authority to sign documents has been assigned or delegated to the manager in accordance with corporate procedures.

b. For a partnership or sole proprietorship, this form shall be signed by a general partner or the proprietor, respectively.

c. For a municipality, State, Federal, or other public agency, this form shall be signed by either a principal executive officer or ranking elected official. For purposes of this section, a principal executive officer of a Federal agency includes (i) the chief executive officer of the agency, or (ii) a senior executive officer having responsibility for the overall operations of a principal geographic unit of the agency (e.g. Regional Administrators of EPA).

New York State Department of Environmental Conservation
Division of Water
625 Broadway, 4th Floor
Albany, New York 12233-3505
(NOTE: Submit completed form to address above)

NOTICE OF TERMINATION for Storm Water Discharges Authorized under the SPDES General Permit for Construction Activity

Please indicate your permit identification number: NYR ___ ___ ___ ___ ___ ___

I. Owner or Operator Information

1. Owner/Operator Name: ARGO Development

2. Street Address: 95 Chestnut Ridge Rd

3. City/State/Zip: Montvale, NJ 07645

4. Contact Person: Michael Abuladze | 4a. Telephone:

4b. Contact Person E-Mail:

II. Project Site Information

5. Project/Site Name: South Ave Multi-Family Development

6. Street Address: South Ave

7. City/Zip: Poughkeepsie, NY 12601

8. County: Dutchess

III. Reason for Termination

9a. □ All disturbed areas have achieved final stabilization in accordance with the general permit and SWPPP. ***Date final stabilization completed** (month/year): _____

9b. □ Permit coverage has been transferred to new owner/operator. Indicate new owner/operator's permit identification number: NYR ___ ___ ___ ___ ___ ___
(Note: Permit coverage can not be terminated by owner identified in I.1. above until new owner/operator obtains coverage under the general permit)

9c. □ Other (Explain on Page 2)

IV. Final Site Information:

10a. Did this construction activity require the development of a SWPPP that includes post-construction stormwater management practices? □ yes □ no (If no, go to question 10f.)

10b. Have all post-construction stormwater management practices included in the final SWPPP been constructed? □ yes □ no (If no, explain on Page 2)

10c. Identify the entity responsible for long-term operation and maintenance of practice(s)?

_____

NOTICE OF TERMINATION for Storm Water Discharges Authorized under the SPDES General Permit for Construction Activity - continued

10d. Has the entity responsible for long-term operation and maintenance been given a copy of the operation and maintenance plan required by the general permit? □ yes □ no

10e. Indicate the method used to ensure long-term operation and maintenance of the post-construction stormwater management practice(s):

□ Post-construction stormwater management practice(s) and any right-of-way(s) needed to maintain practice(s) have been deeded to the municipality.

□ Executed maintenance agreement is in place with the municipality that will maintain the post-construction stormwater management practice(s).

□ For post-construction stormwater management practices that are privately owned, a mechanism is in place that requires operation and maintenance of the practice(s) in accordance with the operation and maintenance plan, such as a deed covenant in the owner or operator's deed of record.

□ For post-construction stormwater management practices that are owned by a public or private institution (e.g. school, university or hospital), government agency or authority, or public utility; policy and procedures are in place that ensures operation and maintenance of the practice(s) in accordance with the operation and maintenance plan.

10f. Provide the total area of impervious surface (i.e. roof, pavement, concrete, gravel, etc.) constructed within the disturbance area? _____ (acres)

11. Is this project subject to the requirements of a regulated, traditional land use control MS4? □ yes □ no

(If Yes, complete section VI - "MS4 Acceptance" statement

V. Additional Information/Explanation:

(Use this section to answer questions 9c. and 10b., if applicable)

VI. MS4 Acceptance - MS4 Official (principal executive officer or ranking elected official) or Duly Authorized Representative (Note: Not required when 9b. is checked -transfer of coverage)

I have determined that it is acceptable for the owner or operator of the construction project identified in question 5 to submit the Notice of Termination at this time.

Printed Name:	
Title/Position:	
Signature:	Date:

NOTICE OF TERMINATION for Storm Water Discharges Authorized under the SPDES General Permit for Construction Activity - continued

VII. Qualified Inspector Certification - Final Stabilization:

I hereby certify that all disturbed areas have achieved final stabilization as defined in the current version of the general permit, and that all temporary, structural erosion and sediment control measures have been removed. Furthermore, I understand that certifying false, incorrect or inaccurate information is a violation of the referenced permit and the laws of the State of New York and could subject me to criminal, civil and/or administrative proceedings.

Printed Name:	
Title/Position:	
Signature:	Date:

VIII. Qualified Inspector Certification - Post-construction Stormwater Management Practice(s):

I hereby certify that all post-construction stormwater management practices have been constructed in conformance with the SWPPP. Furthermore, I understand that certifying false, incorrect or inaccurate information is a violation of the referenced permit and the laws of the State of New York and could subject me to criminal, civil and/or administrative proceedings.

Printed Name:	
Title/Position:	
Signature:	Date:

IX. Owner or Operator Certification

I hereby certify that this document was prepared by me or under my direction or supervision. My determination, based upon my inquiry of the person(s) who managed the construction activity, or those persons directly responsible for gathering the information, is that the information provided in this document is true, accurate and complete. Furthermore, I understand that certifying false, incorrect or inaccurate information is a violation of the referenced permit and the laws of the State of New York and could subject me to criminal, civil and/or administrative proceedings.

Printed Name:	
Title/Position:	
Signature:	Date:

(NYS DEC Notice of Termination - January 2015)

This Page Intentionally Left Blank

APPENDIX C:
PROJECT EVALUATION AND DESIGN CALCULATIONS

LaBella
Powered by partnership.

This Page Intentionally Left Blank

Appendix C - Table A
Step 1 - Evaluation of Green Infrastructure Planning Measures

Group	Practice	Description	Applicable	Project Specific Evaluation
Preservation of Natural Resources	**Preservation of Undisturbed Areas**	Delineate and place into permanent conservation undisturbed forests, native vegetated areas, riparian corridors, wetlands, and natural terrain.	No	The project does not propose permanent conservation of this area at this time.
	Preservation of Buffers	Define, delineate and preserve naturally vegetated buffers along perennial streams, rivers, shorelines and wetlands.	NA	There are no perennial streams, rivers, shorelines, or wetlands on or adjacent to the project site. As such, this green planning measure does not apply.
	Reduction of Clearing and Grading	Limit clearing and grading to the minimum amount needed for roads, driveways, foundations, utilities and stormwater management facilities.	No	This project proposes tree clearing.
	Locating Development in Less Sensitive Areas	Avoid sensitive resource areas such as floodplains, steep slopes, erodible soils, wetlands, mature forests and critical habitats by locating development to fit the terrain in areas that will create the least impact.	Yes	The site layout has been designed to avoid sensitive resource areas to the greatest extent practical. The site layout will avoid disturbance of steep slopes located on the project site.
	Open Space Design	Use clustering, conservation design or open space design to reduce impervious cover, preserve more open space and protect water resources.	No	The site layout has been designed to maximize open space to the greatest possible extent.
	Soil Restoration	Restore the original properties and porosity of the soil by deep till and amendment with compost to reduce the generation of runoff and enhance the runoff reduction performance of practices such as downspout disconnections, grass channels, filter strips, and tree clusters.	Yes	Full soil restoration is proposed for all areas of disturbance that will not become hardscape. All areas will be stabilized with seed & mulch, and landscaped areas will be provided.
Reduction of Impervious Cover	**Roadway Reduction**	Minimize roadway widths and lengths to reduce site impervious area	NA	No new roadways are proposed as part of this project.
	Sidewalk Reduction	Minimize sidewalk lengths and widths to reduce site impervious area	Yes	Sidewalk widths and lengths have been minimized to the greatest extent practical.
	Driveway Reduction	Minimize driveway lengths and widths to reduce site impervious area	Yes	Driveway widths and lengths have been minimized to the greatest extent practical.
	Cul-de-sac Reduction	Minimize the number of cul-de-sacs and incorporate landscaped areas to reduce their impervious cover.	NA	No cul-de-sacs are proposed as part of this project.
	Building Footprint Reduction	Reduce the impervious footprint of residences and commercial buildings by using alternate or taller buildings while maintaining the same floor to area ratio.	No	This project proposes a new building.
	Parking Reduction	Reduce imperviousness on parking lots by eliminating unneeded spaces, providing compact car spaces and efficient parking lanes, minimizing stall dimensions, using porous pavement surfaces in overflow parking areas, and using multi-storied parking decks where appropriate.	Yes	On-site parking has been allocated to provide a sufficient number of spaces for the intended use.

Appendix K - Table B
Step 2 - Determine Water Quality Treatment Volume (WQv)

Determine Pre- and Post-Development Impervious Cover Areas				
Watershed Pre-Development Impervious Area:	1,482	sf =	0.03	ac
Watershed Post-Development Impervious Area:	66,076	sf =	1.52	ac
Total Area Within Work Limits:	122,856	sf =	2.82	ac
Existing Disturbed Impervious Area:	0	sf =	0.00	ac
Additional Runoff From Trib. Areas Not Within the Disturbed, Impervious Area:	1,482	sf =	0.03	ac
New Development Impervious Area:	64,594	sf =	**1.48**	**ac**
Redevelopment Impervious % (based on proposed treatment practice)	0	%		
Redevelopment Impervious Area:	0	sf =	**0.00**	**ac**

Determine the Initial Water Quality Volume (WQv)				
WQv(acre-feet) = [(P)(Rv)(A)] /12				
Rv = 0.05+0.009(I)				
I = Impervious Cover (%)				
P=	1.38	*inch*		
I=	53%			
Rv=	0.523			
Initial WQv=	**7,392**	cf =	**0.170**	**ac-ft**

Appendix C - Table C
Step 3 - Evaluation of Runoff Reduction Techniques and Standard SMPs with RRv Capacity

Design Variant	Practice	Description	Applicable	Project Specific Evaluation/Justification
RR-1	**Conservation of Natural Areas**	Retain the pre-development hydrologic and water quality characteristics of undisturbed natural areas, stream and wetland buffers by restoring and/or permanently conserving these areas on a site.	No	The project does not propose permanent conservation of these areas at this time.
RR-2	**Sheet flow to Riparian Buffers or Filter Strips**	Undisturbed natural areas such as forested conservation areas and stream buffers or vegetated filter strips and riparian buffers can be used to treat and control stormwater runoff from portions of development.	No	Riparian buffers or filter strips are not proposed.
RR-3	**Tree Planting/ Tree Pit**	Plant or conserve trees to reduce stormwater runoff, increase nutrient uptake, and provide bank stabilization. Trees can be used for applications such as landscaping, stormwater management practice areas, and conservation areas.	No	The project proposes the preservation of existing mature trees, as well as the planting of numerous trees throughout the site, in order to reduce stormwater runoff, increase nutrient uptake, and provide bank stabilization. However, credit for these trees will not be taken toward an area reduction in the RRv calculations.
RR-4	**Disconnection of Rooftop Runoff**	Direct runoff from residential rooftop areas and upland overland runoff flow to designated pervious areas to reduce runoff volumes and rates.	No	Rooftop disconnect is not applicable, since this is a commercial building project.
RR-5	**Vegetated Swale**	The natural drainage paths, or properly designed vegetated channels, can be used instead of constructing underground storm sewers or concrete open channels to increase time of concentration, reduce the peak discharge, and provide infiltration.	No	Swales are not proposed on this site.
RR-6	**Rain Garden**	Manage and treat small volumes of stormwater runoff using a conditioned planting soil bed and planting materials to filter runoff stored within a shallow depression.	No	Due to the limited tributary area to rain gardens (≤ 1,000SF), a bioretention facility will be implemented instead of rain gardens.
RR-7	**Stormwater Planter**	Small landscaped stormwater treatment devices that can be designed as infiltration or filtering practices. Stormwater planters use soil infiltration and biogeochemical processes to decrease stormwater quantity and improve water quality.	Yes	A stormwater planter is proposed on the south side of the proposed building, and will capture a portion of the new roof area.
RR-8	**Rain Barrels/ Cisterns**	Capture and store stormwater runoff to be used for irrigation systems or filtered and reused for non-contact activities.	No	Rain Barrels/Cisterns are not proposed on-site due to the need for active management/maintenance and initial capital cost.
RR-9	**Porous Pavement**	Pervious types of pavements that provide an alternative to conventional paved surfaces, designed to infiltrate rainfall through the surface, thereby reducing stormwater runoff from a site and providing some pollutant uptake in the underlying soils.	No	Porous pavement is not proposed as part of this project due to low permeability of on-site soils, as well as concerns regarding winter maintenance.
RR-10	**Green Roof**	Capture runoff by a layer of vegetation and soil installed on top of a conventional flat or sloped roof. The rooftop vegetation allows evaporation and evapotranspiration processes to reduce volume and discharge rate of runoff entering conveyance system.	No	A green roof is not proposed on-site due to significant structural, insurance, and maintenance considerations.
	Stream Daylighting	Stream Daylight previously-culverted/piped streams to restore natural habitats, better attenuate runoff by increasing the storage size, promoting infiltration, and help reduce pollutant loads.	No	No stream daylighting opportunities are present on this site.

I-1	**Infiltration Trench**	Excavated, stone-filled trenches designed to capture and temporarily store runoff in the stone reservoir to promote infiltration. Can be constructed as sheet flow to a ground surface depression or piped flow discharged directly into the trench.	No	Infiltration is not proposed due to poor draining soils.
I-2	**Infiltration Basin**	Vegetated excavations designed to capture and infiltrate the WQv. Can be designed off-line to bypass larger flows to downstream flood control facilities or as combined infiltration/flood control facilities by providing temporary detention ponding.	No	Infiltration is not proposed due to poor draining soils.
I-3	**Dry Wells**	Underground structures designed to capture, treat, and infiltrate runoff from small drainage areas (rooftop only) that have low sediment or pollutant loadings. Larger stormwater volumes can be bypassed directly to a flood control facility.	No	Infiltration is not proposed due to poor draining soils.
I-4	**Underground Infiltration Systems**	Underground, proprietary systems designed to capture and infiltrate the WQv, reduce runoff, remove fine sediment and associated pollutants, recharge groundwater, and attenuate peak flows.	No	Infiltration is not proposed due to poor draining soils.
F-5	**Bioretention**	Shallow landscaped depressions where stormwater flows into the practice, ponds at the surface, and gradually filters through the media to remove pollutants. Filtered runoff can either infiltrate into the surrounding soil, or be collected by an underdrain system and discharged to the storm sewer system or directly to receiving waters.	Yes	Bioretention has been applied to this project.
O-1	**Dry Swale**	Designed to temporarily hold the WQv in a pool or series of pools created by permanent check dams. The soil bed consists of native soils or highly permeable fill material, underlain by an underdrain system. Pollutants are removed through sedimentation, nutrient uptake, and infiltration.	No	Dry swales are not proposed because they are intended for use with roads, highways, or residential development.

Appendix C - Table D

Step 4 - Determine Minimum Runoff Reduction Volume (RRv) Required

Section 4.3 of the NYSDEC Stormwater Management Design Manual describes the equation for minimum Runoff Reduction Volume as:

$$RRv_{min} = (P \times \bar{R}v \times Aic \times S) / 12$$

where: RRv_{min} = Minimum Runoff Reduction Volume Required (acre-feet)
P = 90% Rainfall Event Number (inches) (interpolated from Design Manual Fig
$\bar{R}v$ = 0.05 + 0.009 (I), where I is 100% impervious = 0.95 constant
Aic = Total area of new impervious cover (acres)
S = Hydrologic Soil Group (HSG) Specific Reduction Factor

HSG A=	0.55	HSG C=	0.30
HSG B=	0.40	HSG D=	0.20

Enter the Soils Data for the site

Soil Group	Acres	S
A	2.71	0.55
B	0.00	0.40
C	0.00	0.30
D	0.11	0.20
Total Area	2.82	acres

Calculate the Minimum RRv

S =	**0.54**	
Impervious	1.52	*acre*
Precipitation	1.38	*in*
Rv	0.95	
Minimum RRv	**3,868**	ft^3
	0.089	af

Appendix C - Table E

Summary Table: Runoff Reduction Volume and Treated volumes

	Runoff Reduction Techiques/Standard SMPs		Total Contributing Area	Total Contributing Impervious Area	WQv Reduced (RRv)	WQv Treated
			(acres)	(acres)	cf	cf
Area/Volume Reduction	Conservation of Natural Areas	RR-1	0.00	0.00		
	Sheetflow to Riparian Buffers/Filter Strips	RR-2	0.00	0.00		
	Tree Planting/Tree Pit	RR-3	0.00	0.00		
	Disconnection of Rooftop Runoff	RR-4	0.00	0.00		
	Vegetated Swale	RR-5	0.00	0.00	0	
	Rain Garden	RR-6	0.00	0.00	0	
	Stormwater Planter	RR-7	0.00	0.00	0	
	Rain Barrel/Cistern	RR-8	0.00	0.00	0	
	Porous Pavement	RR-9	0.00	0.00	0	
	Green Roof (Intensive & Extensive)	RR-10	0.00	0.00	0	
Standard SMPs w/RRv Capacity	Infiltration Trench	I-1	0.00	0.00	0	0
	Infiltration Basins	I-2	0.00	0.00	0	
	Dry Well	I-3	0.00	0.00	0	0
	Underground Infiltration System	I-4	2.42	1.26	6,299	6,299
	Bioretention	F-5	0.40	0.26	907	1,360
	Dry Swale	O-1	0.00	0.00	0	0
Standard SMPs	Micropool Extended Detention (P-1)	P-1	0.00	0.00		0
	Wet Pond (P-2)	P-2	0.00	0.00		0
	Wet Extended Detention (P-3)	P-3	0.00	0.00		0
	Multiple Pond System (P-4)	P-4	0.00	0.00		0
	Pocket Pond (P-5)	P-5	0.00	0.00		0
	Surface Sand Filter (F-1)	F-1	0.00	0.00		0
	Underground Sand Filter (F-2)	F-2	0.00	0.00		0
	Perimeter Sand Filter (F-3)	F-3	0.00	0.00		0
	Organic Filter (F-4)	F-4	0.00	0.00		0
	Shallow Wetland (W-1)	W-1	0.00	0.00		0
	Extended Detention Wetland (W-2)	W-2	0.00	0.00		0
	Pond/Wetland System (W-3)	W-3	0.00	0.00		0
	Pocket Wetland (W-4)	W-4	0.00	0.00		0
	Wet Swale (O-2)	O-2	0.00	0.00		0
Alternative Practices	Hydrodynamic Separator		0.00	0.00		0
	Filterra Bioretention System		0.00	0.00		0
	Wet Vault		0.00	0.00		0
	Media Filter		0.00	0.00		0
Totals by Area Reduction →			0.00	0.00	0	
Totals by Volume Reduction →			0.00	0.00	0	
Totals by Standard SMP w/RRV →			2.82	1.52	7,206	7,659
Totals by Standard SMP →			0.00	0.00		0
Totals by Alternative Practices →			0.00	0.00		0
Totals (Area + Volume + all SMPs) →			2.82	1.52	**7,206**	**7,659**

Appendix C - Table F
Practice Specific Sizing Calculation Worksheet

BIORETENTION NO. 1 (2P)

Practice Proposed?	Yes

Enter Site Data For Drainage Area to be Treated by Practice

Catchment Number	Total Area (Acres)	Impervious Area (Acres)	Percent Impervious %	Rv	WQv (ft^3)	Precipitation (in)	Description
PS4,5	0.10	0.09	85%	0.81	423	1.38	Bioretention
Enter Impervious Area Reduced by Disconnection of Rooftops Within this Catchment:		0.00	85%	0.81	423	<<WQv after adjusting for Disconnected Rooftops	
Reduced by Tree Planting:	0.00	0.00	85%	0.81	423	<<WQv after adjusting for Tree Planting	
Enter the portion of the WQv that is not reduced for all practices routed to this practice:					0	ft^3	

Determine Required Water Quality Volume

WQv = (P/12) * Rv * A

where: WQv = Water Quality Volume (acre-feet)
P = 1-year 24-hour design storm (inches)
Rv = 0.05 + 0.009 (I); min Rv = 0.2
I = Impervious Cover (%) within the drainage area contributing to the SWM practice
A = Drainage area (square feet) contributing to the SWM practice

WQv =	423	CF

**Value taken from Appendix K - Table B*

Calculate Required Filter Bed Area

Af=(WQv)*(df)/[(k)*(hf+df)*(tf)]

where: Af = Surface area of filter bed (SF)
WQv = Required Water Quality Volume (CF)
df = Filter bed depth (ft)
k = Coefficient of permeability of filter media (ft/day)
hf = Average height of water above filter bed (ft)
tf = Design filter bed drain time (days)

SMP ID	WQv (cubic feet)	df (feet)	k (ft/day)	hf (feet)	tf (days)	Minimum Af (sq-ft)	Provided Af (sq-ft)
BIO-1	423	2.5	0.5	0.5	2.0	352	515

Calculate Provided Water Quality Volume

WQv Provided Within Practice = Total volumes of soil media, mulch, and ponding

$WQv = V_{SM} + V_M + Vpond$

V_{SM} =	Af * df * P_{SM}	=	258	cf.
V_M =	Af * dm * P_M	=	52	cf.
V_{POND} =	(Af * hf * 2) + (2 * S * hf^2 * Pf)	=	638	cf.

where:

P_{SM} =	Porosity of soil media - 0.20	0.20	
P_M =	Porosity of mulch - 0.40	0.40	
S =	Bioretention Side Slopes	3.00	:1
Pf =	Bioretention Perimeter	82	LF

WQv =	947	CF

Calculate Provided Runoff Reduction Volume

Using Underdrains?	Yes	
RRv =	379	CF
RRv Applied =	379	CF

This is 40% of the storage provided or WQv, whichever is less.

BIORETENTION NO. 2 (6P)

Practice Proposed?	Yes

Enter Site Data For Drainage Area to be Treated by Practice

Catchment Number	Total Area (Acres)	Impervious Area (Acres)	Percent Impervious %	Rv	WQv (ft^3)	Precipitation (in)	Description
PS6A	0.29	0.17	59%	0.58	857	1.38	Bioretention
Enter Impervious Area Reduced by Disconnection of Rooftops Within this Catchment:		0.00	59%	0.58	857	<<WQv after adjusting for Disconnected Rooftops	
Reduced by Tree Planting:	0.00	0.00	59%	0.58	857	<<WQv after adjusting for Tree Planting	
Enter the portion of the WQv that is not reduced for all practices routed to this practice:					0	ft^3	

Determine Required Water Quality Volume

WQv = (P/12) * Rv * A

where: WQv = Water Quality Volume (acre-feet)
P = 1-year 24-hour design storm (inches)
Rv = 0.05 + 0.009 (I); min Rv = 0.2
I = Impervious Cover (%) within the drainage area contributing to the SWM practice
A = Drainage area (square feet) contributing to the SWM practice

WQv =	857	CF

**Value taken from Appendix K - Table B*

Calculate Required Filter Bed Area

Af=(WQv)*(df)/[(k)*(hf+df)*(tf)]

where: Af = Surface area of filter bed (SF)
WQv = Required Water Quality Volume (CF)
df = Filter bed depth (ft)
k = Coefficient of permeability of filter media (ft/day)
hf = Average height of water above filter bed (ft)
tf = Design filter bed drain time (days)

SMP ID	WQv (cubic feet)	df (feet)	k (ft/day)	hf (feet)	tf (days)	Minimum Af (sq-ft)	Provided Af (sq-ft)
BIO-1	857	2.5	0.5	0.5	2.0	715	720

Calculate Provided Water Quality Volume

WQv Provided Within Practice = Total volumes of soil media, mulch, and ponding

$WQv = V_{SM} + V_M + Vpond$

V_{SM} =	$Af * df * P_{SM}$	=	360	cf.
V_M =	$Af * dm * P_M$	=	72	cf.
V_{POND} =	$(Af * hf * 2) + (2 * S * hf^2 * Pf)$	=	888	cf.

where:

P_{SM} =	Porosity of soil media - 0.20	0.20	
P_M =	Porosity of mulch - 0.40	0.40	
S =	Bioretention Side Slopes	3.00	:1
Pf =	Bioretention Perimeter	112	LF

WQv =	1,320	CF

Calculate Provided Runoff Reduction Volume

Using Underdrains? Yes

RRv =	528	CF
RRv Applied =	**528**	**CF**

This is 40% of the storage provided or WQv, whichever is less.

Appendix C - Table G
Practice Specific Sizing Calculation Worksheet

INFILTRATION CHAMBER NO. 1 (8P)

Practice Proposed?	Yes

Enter Site Data For Drainage Area to be Treated by Practice

Catchment Number	Total Area *(Acres)*	Impervious Area *(Acres)*	Percent Impervious %	Rv	WQv *(ft^3)*	Precipitation *(in)*	
PS1,2,3,6B,7	2.42	1.26	52%	0.52	6,265	1.38	
Enter Impervious Area Reduced by Disconnection of Rooftops Within this Catchment:		0.00	52%	0.52	6,265	<<WQv after adjusting for Disconnected Rooftops	
Enter the portion of the WQv that is not reduced for all practices routed to this practice:					0	ft^3	

Determine Pretreatment Volume

Infiltration Rate:	0.5	in/hour	
Pretreatment Sizing:	25	% WQv	25% minimum; 50% if > 2 in/hr; 100% if > 5 in/hr
Pretreatment Required Volume:	1,566	ft^3	
Pretreatment Provided:	1,566	ft^3	
Pretreatment Techniques Utilized:	Hydro		

Size Infiltration Basin

Design Volume	6,265	ft^3	WQv
Volume Provided	6,299	ft^3	Per HydroCAD model at specified elevation below overflow pipe

Calculate Provided Runoff Reduction Volume

RRv Applied =	6,299	CF

Appendix K - Table H
Practice Specific Sizing Calculation Worksheet

HYDRODYNAMIC SEPARATOR NO. 1 (3P)

Practice Proposed?	Yes
Treatment (Redevelopment)?	No

Enter Site Data For Drainage Area to be Treated by Practice

Catchment Number	Total Area *(Acres)*	Impervious Area *(Acres)*	Percent Impervious %	Rv	WQv *(ft^3)*	Precipitation *(in)*	Description
PS1,2,3,6C	1.44	1.06	74%	0.72	5,159	1.38	Hydrodynamic Separator

Compute Peak Water Quality Discharge

Qp = qu * A * WQv

where: qu = the unit peak discharge, in cfs/mi^2/inch
A = Drainage area (square miles) contributing to the SMP
WQv = Water Quality Volume (inches)

The unit peak discharge qu is obtained from TR-55 Exhibits 4-I through 4-III, depending on the NRCS rainfall distribution type. It is based on the time of concentration (Tc) in hours, the initial abstraction (Ia) in inches, and the precipitation (P) in inches. The initial abstraction (Ia) is obtained from TR-55 Table 4-1, and is based on the equivalent Curve Number for the water quality volume.

The equivalent Curve Number is calculated using the following equation:

CN = 1000 / [10 + 5P + 10Q - 10 * (Q^2 + 1.25QP)^0.5]

where: CN = Equivalent Curve Number
P = 90% Rainfall Event Number (inches) = 1.38 in
Q = Water Quality Volume (inches)

The following table presents the Water Quality Peak Flow calculations for each of the proposed stormwater management practices (SMPs):

SMP ID	A (ac)	WQv (cf)	Q (inches)	Tc (hours)	CN	Ia (inches)	Ia/P	qu (cfs/sq.mi.-inch)	Qp (cfs)
PS1,2,3,6C	1.44	5,159	0.99	0.10	96.1	0.081	0.059	700	**1.60**

Size Flow Diversion Structure

Orifice Equation: $Qp = CA(2gh)^{0.5}$

where: C = Orifice coefficient
A = Area of WQv orifice (sf)
g = acceleration due to gravity (feet/$second^2$)
h = depth of water to center of orifice (ft)
d = minimum diameter of WQv orifice
y = distance of overflow bipass above invert of water quality pipe (ft)

The following table presents the minimum diameter of the WQv orifice and distance of the overflow bipass above the invert of the

SMP ID	C	A (ft^2)	g (ft/sec^2)	h (ft)	d (ft)	d (in)	y (ft)
PS1,2,3,6C	0.60		32.2				

WQv Overflow Calc

Practice Proposed?	No
Treatment (Redevelopment)?	No

Hide worksheet and do not provide in SWPPP Calculations

Enter Site Data For Drainage Area to be Treated by Practice

Catchment	Total Area	Impervious Area	Percent	Rv	WQv	Precipitation	Description
PS1	0.54	0.40	74%	0.72	1,931	1.38	

Compute Peak Water Quality Discharge

Qp = qu * A * WQv

where: qu = the unit peak discharge, in cfs/mi^2/inch
A = Drainage area (square miles) contributing to the SMP
WQv = Water Quality Volume (inches)

The unit peak discharge qu is obtained from TR-55 Exhibits 4-I through 4-III, depending on the NRCS rainfall distribution type. It is
The equivalent Curve Number is calculated using the following equation:

CN = 1000 / [10 + 5P + 10Q - 10 * (Q^2 + 1.25QP)^0.5]

where: CN = Equivalent Curve Number
P = 90% Rainfall Event Number (inches) = 0.00 in
Q = Water Quality Volume (inches)

The following table presents the Water Quality Peak Flow calculations for each of the proposed stormwater management practices

SMP ID	A	WQv	Q	Tc	CN	Ia	Ia/P	qu	Qp
	(ac)	(cf)	(inches)	(hours)		(inches)		(cfs/sq.mi.-inch)	(cfs)
PS1	0.54	1,931	0.99	0.10	96.1	0.081	0.059	700	**0.60**

Size Flow Diversion Structure

Orifice Equation: Qp = CA(2gh)$^{0.5}$

where: C = Orifice coefficient
A = Area of WQv orifice (sf)
g = acceleration due to gravity (feet/second^2)
h = depth of water to center of orifice (ft)
d = minimum diameter of WQv orifice
y = distance of overflow bipass above invert of water quality pipe (ft)

The following table presents the minimum diameter of the WQv orifice and distance of the overflow bipass above the invert of the

SMP ID	C	A	g	h	d	d	y
		(ft^2)	(ft/sec^2)	(ft)	(ft)	(in)	(ft)
PS1	0.60	0.2	32.2	0.55	0.46	6	0.80

WQv Overflow Calc

Practice Proposed?	No
Treatment (Redevelopment)?	No

Hide worksheet and do not provide in SWPPP Calculations

Enter Site Data For Drainage Area to be Treated by Practice

Catchment Number	Total Area *(Acres)*	Impervious Area *(Acres)*	Percent Impervious *%*	Rv	WQv *(ft^3)*	Precipitation *(in)*	Description
PS2, 3, 6C	0.90	0.67	74%	0.71	3,230	1.38	

Compute Peak Water Quality Discharge

Qp = qu * A * WQv

where: qu = the unit peak discharge, in cfs/mi^2/inch
A = Drainage area (square miles) contributing to the SMP
WQv = Water Quality Volume (inches)

The unit peak discharge qu is obtained from TR-55 Exhibits 4-I through 4-III, depending on the NRCS rainfall distribution type. It is
The equivalent Curve Number is calculated using the following equation:

CN = 1000 / [10 + 5P + 10Q - 10 * (Q^2 + 1.25QP)^0.5]

where: CN = Equivalent Curve Number
P = 90% Rainfall Event Number (inches) = 0.00 in
Q = Water Quality Volume (inches)

The following table presents the Water Quality Peak Flow calculations for each of the proposed stormwater management practices

SMP ID	A	WQv	Q	Tc	CN	Ia	Ia/P	qu	Qp
	(ac)	(cf)	(inches)	(hours)		(inches)		(cfs/sq.mi.-inch)	(cfs)
PS2, 3, 6C	0.90	3,230	0.98	0.10	96.0	0.083	0.060	700	**1.00**

Size Flow Diversion Structure

Orifice Equation: $Qp = CA(2gh)^{0.5}$

where:
C = Orifice coefficient
A = Area of WQv orifice (sf)
g = acceleration due to gravity (feet/$second^2$)
h = depth of water to center of orifice (ft)
d = minimum diameter of WQv orifice
y = distance of overflow bipass above invert of water quality pipe (ft)

The following table presents the minimum diameter of the WQv orifice and distance of the overflow bipass above the invert of the

SMP ID	C	A	g	h	d	d	y
		(ft^2)	(ft/sec^2)	(ft)	(ft)	(in)	(ft)
PS2, 3, 6C	0.60	0.3	32.2	0.55	0.60	8	0.88

APPENDIX D:
PRE-DEVELOPMENT STORMWATER MODELING

LaBella
Powered by partnership.

This Page Intentionally Left Blank


ES1
ES2
ES3
1P
2P
EXISTING POND
EXISTING POND
AP1
Subcat
Reach
Pond
Link
Routing Diagram for HydroCAD_PreDev_2222201
Prepared by The Chazen Companies, Printed 11/29/2022
HydroCAD® 10.00-21 s/n 00927 © 2018 HydroCAD Software Solutions LLC

This Page Intentionally Left Blank

Summary for Subcatchment ES1:

Runoff = 0.03 cfs @ 12.43 hrs, Volume= 0.009 af, Depth> 0.16"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
Type III 24-hr 1-yr Rainfall=2.61"

Area (sf)	CN	Description
24,695	57	Woods/grass comb., Poor, HSG A
3,441	68	<50% Grass cover, Poor, HSG A
28,136	58	Weighted Average
28,136		100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
4.3	50	0.1000	0.19		**Sheet Flow, 50' sheet flow grass** Grass: Dense n= 0.240 P2= 3.17"
3.1	28	0.2000	0.15		**Sheet Flow, 28' sheet flow woods** Woods: Light underbrush n= 0.400 P2= 3.17"
1.5	100	0.0488	1.10		**Shallow Concentrated Flow, 100' shallow concentrated woods** Woodland Kv= 5.0 fps
8.9	178	Total			

Subcatchment ES1:



Summary for Subcatchment ES2:

Runoff = 0.09 cfs @ 12.41 hrs, Volume= 0.022 af, Depth> 0.16"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
Type III 24-hr 1-yr Rainfall=2.61"

Area (sf)	CN	Description
67,702	57	Woods/grass comb., Poor, HSG A
0	86	Woods/grass comb., Poor, HSG D
3,703	68	<50% Grass cover, Poor, HSG A
985	89	<50% Grass cover, Poor, HSG D
363	98	Paved parking, HSG D
72,753	58	Weighted Average
72,390		99.50% Pervious Area
363		0.50% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
2.4	21	0.2100	0.14		**Sheet Flow, 21' sheet woods** Woods: Light underbrush n= 0.400 P2= 3.17"
5.1	290	0.0360	0.95		**Shallow Concentrated Flow, 290' of shallow concentrated** Woodland Kv= 5.0 fps
7.5	311	Total			

Subcatchment ES2:



Summary for Subcatchment ES3:

Runoff = 0.04 cfs @ 12.49 hrs, Volume= 0.008 af, Depth> 0.20"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
Type III 24-hr 1-yr Rainfall=2.61"

Area (sf)	CN	Description
18,346	57	Woods/grass comb., Poor, HSG A
1,098	86	Woods/grass comb., Poor, HSG D
0	68	<50% Grass cover, Poor, HSG A
1,005	89	<50% Grass cover, Poor, HSG D
20,449	60	Weighted Average
20,449		100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.5	40	0.0350	0.12		**Sheet Flow, 40' sheet flow grass** Grass: Dense n= 0.240 P2= 3.17"
11.0	60	0.0390	0.09		**Sheet Flow, 60' sheet flow woods** Woods: Light underbrush n= 0.400 P2= 3.17"
0.1	15	0.1333	1.83		**Shallow Concentrated Flow, 15' shallow concentrated woods** Woodland Kv= 5.0 fps
16.6	115	Total			

Subcatchment ES3:



Summary for Reach AP1:

Inflow Area = 2.786 ac, 0.30% Impervious, Inflow Depth > 0.10" for 1-yr event
Inflow = 0.09 cfs @ 12.41 hrs, Volume= 0.022 af
Outflow = 0.09 cfs @ 12.41 hrs, Volume= 0.022 af, Atten= 0%, Lag= 0.0 min

Routing by Dyn-Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs / 3

Reach AP1:



Summary for Pond 1P: EXISTING POND

Inflow Area = 0.646 ac, 0.00% Impervious, Inflow Depth > 0.16" for 1-yr event
Inflow = 0.03 cfs @ 12.43 hrs, Volume= 0.009 af
Outflow = 0.00 cfs @ 0.00 hrs, Volume= 0.000 af, Atten= 100%, Lag= 0.0 min
Primary = 0.00 cfs @ 0.00 hrs, Volume= 0.000 af

Routing by Dyn-Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs / 3
Peak Elev= 78.47' @ 24.00 hrs Surf.Area= 1,054 sf Storage= 375 cf
Flood Elev= 79.00' Surf.Area= 1,630 sf Storage= 1,090 cf

Plug-Flow detention time= (not calculated: initial storage exceeds outflow)
Center-of-Mass det. time= (not calculated: no outflow)

Volume	Invert	Avail.Storage	Storage Description
#1	78.00'	1,090 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
78.00	550	0	0
79.00	1,630	1,090	1,090

Device	Routing	Invert	Outlet Devices
#1	Primary	78.50'	**35.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s)

Primary OutFlow Max=0.00 cfs @ 0.00 hrs HW=78.00' TW=0.00' (Dynamic Tailwater)
↑—**1=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)

Pond 1P: EXISTING POND



Summary for Pond 2P: EXISTING POND

Inflow Area = 0.469 ac, 0.00% Impervious, Inflow Depth > 0.20" for 1-yr event
Inflow = 0.04 cfs @ 12.49 hrs, Volume= 0.008 af
Outflow = 0.00 cfs @ 0.00 hrs, Volume= 0.000 af, Atten= 100%, Lag= 0.0 min
Primary = 0.00 cfs @ 0.00 hrs, Volume= 0.000 af

Routing by Dyn-Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs / 3
Peak Elev= 78.66' @ 24.00 hrs Surf.Area= 764 sf Storage= 347 cf

Plug-Flow detention time= (not calculated: initial storage exceeds outflow)
Center-of-Mass det. time= (not calculated: no outflow)

Volume	Invert	Avail.Storage	Storage Description
#1	78.00'	5,855 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
78.00	288	0	0
79.00	1,010	649	649
80.00	2,071	1,541	2,190
81.00	5,260	3,666	5,855

Device	Routing	Invert	Outlet Devices
#1	Primary	80.90'	**40.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s)

Primary OutFlow Max=0.00 cfs @ 0.00 hrs HW=78.00' TW=0.00' (Dynamic Tailwater)
↑—**1=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)

Pond 2P: EXISTING POND



Summary for Subcatchment ES1:

Runoff = 0.56 cfs @ 12.15 hrs, Volume= 0.053 af, Depth> 0.99"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
Type III 24-hr 10-yr Rainfall=4.67"

Area (sf)	CN	Description
24,695	57	Woods/grass comb., Poor, HSG A
3,441	68	<50% Grass cover, Poor, HSG A
28,136	58	Weighted Average
28,136		100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
4.3	50	0.1000	0.19		**Sheet Flow, 50' sheet flow grass** Grass: Dense n= 0.240 P2= 3.17"
3.1	28	0.2000	0.15		**Sheet Flow, 28' sheet flow woods** Woods: Light underbrush n= 0.400 P2= 3.17"
1.5	100	0.0488	1.10		**Shallow Concentrated Flow, 100' shallow concentrated woods** Woodland Kv= 5.0 fps
8.9	178	Total			

Subcatchment ES1:



Summary for Subcatchment ES2:

Runoff = 1.52 cfs @ 12.13 hrs, Volume= 0.138 af, Depth> 0.99"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
Type III 24-hr 10-yr Rainfall=4.67"

Area (sf)	CN	Description
67,702	57	Woods/grass comb., Poor, HSG A
0	86	Woods/grass comb., Poor, HSG D
3,703	68	<50% Grass cover, Poor, HSG A
985	89	<50% Grass cover, Poor, HSG D
363	98	Paved parking, HSG D
72,753	58	Weighted Average
72,390		99.50% Pervious Area
363		0.50% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
2.4	21	0.2100	0.14		**Sheet Flow, 21' sheet woods** Woods: Light underbrush n= 0.400 P2= 3.17"
5.1	290	0.0360	0.95		**Shallow Concentrated Flow, 290' of shallow concentrated** Woodland Kv= 5.0 fps
7.5	311	Total			

Subcatchment ES2:



Summary for Subcatchment ES3:

Runoff = 0.38 cfs @ 12.26 hrs, Volume= 0.043 af, Depth> 1.11"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
Type III 24-hr 10-yr Rainfall=4.67"

Area (sf)	CN	Description
18,346	57	Woods/grass comb., Poor, HSG A
1,098	86	Woods/grass comb., Poor, HSG D
0	68	<50% Grass cover, Poor, HSG A
1,005	89	<50% Grass cover, Poor, HSG D
20,449	60	Weighted Average
20,449		100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.5	40	0.0350	0.12		**Sheet Flow, 40' sheet flow grass** Grass: Dense n= 0.240 P2= 3.17"
11.0	60	0.0390	0.09		**Sheet Flow, 60' sheet flow woods** Woods: Light underbrush n= 0.400 P2= 3.17"
0.1	15	0.1333	1.83		**Shallow Concentrated Flow, 15' shallow concentrated woods** Woodland Kv= 5.0 fps
16.6	115	Total			

Subcatchment ES3:



Summary for Reach AP1:

Inflow Area = 2.786 ac, 0.30% Impervious, Inflow Depth > 0.78" for 10-yr event
Inflow = 1.52 cfs @ 12.13 hrs, Volume= 0.182 af
Outflow = 1.52 cfs @ 12.13 hrs, Volume= 0.182 af, Atten= 0%, Lag= 0.0 min

Routing by Dyn-Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs / 3

Reach AP1:



Summary for Pond 1P: EXISTING POND

Inflow Area = 0.646 ac, 0.00% Impervious, Inflow Depth > 0.99" for 10-yr event
Inflow = 0.56 cfs @ 12.15 hrs, Volume= 0.053 af
Outflow = 0.42 cfs @ 12.27 hrs, Volume= 0.044 af, Atten= 25%, Lag= 7.6 min
Primary = 0.42 cfs @ 12.27 hrs, Volume= 0.044 af

Routing by Dyn-Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs / 3
Peak Elev= 78.52' @ 12.27 hrs Surf.Area= 1,116 sf Storage= 436 cf
Flood Elev= 79.00' Surf.Area= 1,630 sf Storage= 1,090 cf

Plug-Flow detention time= 112.2 min calculated for 0.044 af (82% of inflow)
Center-of-Mass det. time= 36.3 min (925.1 - 888.8)

Volume	Invert	Avail.Storage	Storage Description
#1	78.00'	1,090 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
78.00	550	0	0
79.00	1,630	1,090	1,090

Device	Routing	Invert	Outlet Devices
#1	Primary	78.50'	**35.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s)

Primary OutFlow Max=0.42 cfs @ 12.27 hrs HW=78.52' TW=0.00' (Dynamic Tailwater)
↑—**1=Sharp-Crested Rectangular Weir** (Weir Controls 0.42 cfs @ 0.50 fps)

Pond 1P: EXISTING POND



Summary for Pond 2P: EXISTING POND

Inflow Area = 0.469 ac, 0.00% Impervious, Inflow Depth > 1.11" for 10-yr event
Inflow = 0.38 cfs @ 12.26 hrs, Volume= 0.043 af
Outflow = 0.00 cfs @ 0.00 hrs, Volume= 0.000 af, Atten= 100%, Lag= 0.0 min
Primary = 0.00 cfs @ 0.00 hrs, Volume= 0.000 af

Routing by Dyn-Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs / 3
Peak Elev= 79.85' @ 24.00 hrs Surf.Area= 1,910 sf Storage= 1,887 cf

Plug-Flow detention time= (not calculated: initial storage exceeds outflow)
Center-of-Mass det. time= (not calculated: no outflow)

Volume	Invert	Avail.Storage	Storage Description
#1	78.00'	5,855 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
78.00	288	0	0
79.00	1,010	649	649
80.00	2,071	1,541	2,190
81.00	5,260	3,666	5,855

Device	Routing	Invert	Outlet Devices
#1	Primary	80.90'	**40.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s)

Primary OutFlow Max=0.00 cfs @ 0.00 hrs HW=78.00' TW=0.00' (Dynamic Tailwater)
1=Sharp-Crested Rectangular Weir (Controls 0.00 cfs)

Pond 2P: EXISTING POND



Summary for Subcatchment ES1:

Runoff = 2.18 cfs @ 12.13 hrs, Volume= 0.175 af, Depth> 3.25"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
Type III 24-hr 100-yr Rainfall=8.20"

Area (sf)	CN	Description
24,695	57	Woods/grass comb., Poor, HSG A
3,441	68	<50% Grass cover, Poor, HSG A
28,136	58	Weighted Average
28,136		100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
4.3	50	0.1000	0.19		**Sheet Flow, 50' sheet flow grass** Grass: Dense n= 0.240 P2= 3.17"
3.1	28	0.2000	0.15		**Sheet Flow, 28' sheet flow woods** Woods: Light underbrush n= 0.400 P2= 3.17"
1.5	100	0.0488	1.10		**Shallow Concentrated Flow, 100' shallow concentrated woods** Woodland Kv= 5.0 fps
8.9	178	Total			

Subcatchment ES1:



Summary for Subcatchment ES2:

Runoff = 5.92 cfs @ 12.11 hrs, Volume= 0.453 af, Depth> 3.25"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
Type III 24-hr 100-yr Rainfall=8.20"

Area (sf)	CN	Description
67,702	57	Woods/grass comb., Poor, HSG A
0	86	Woods/grass comb., Poor, HSG D
3,703	68	<50% Grass cover, Poor, HSG A
985	89	<50% Grass cover, Poor, HSG D
363	98	Paved parking, HSG D
72,753	58	Weighted Average
72,390		99.50% Pervious Area
363		0.50% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
2.4	21	0.2100	0.14		**Sheet Flow, 21' sheet woods** Woods: Light underbrush n= 0.400 P2= 3.17"
5.1	290	0.0360	0.95		**Shallow Concentrated Flow, 290' of shallow concentrated** Woodland Kv= 5.0 fps
7.5	311	Total			

Subcatchment ES2:



Summary for Subcatchment ES3:

Runoff = 1.37 cfs @ 12.23 hrs, Volume= 0.136 af, Depth> 3.47"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
Type III 24-hr 100-yr Rainfall=8.20"

Area (sf)	CN	Description
18,346	57	Woods/grass comb., Poor, HSG A
1,098	86	Woods/grass comb., Poor, HSG D
0	68	<50% Grass cover, Poor, HSG A
1,005	89	<50% Grass cover, Poor, HSG D
20,449	60	Weighted Average
20,449		100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.5	40	0.0350	0.12		**Sheet Flow, 40' sheet flow grass** Grass: Dense n= 0.240 P2= 3.17"
11.0	60	0.0390	0.09		**Sheet Flow, 60' sheet flow woods** Woods: Light underbrush n= 0.400 P2= 3.17"
0.1	15	0.1333	1.83		**Shallow Concentrated Flow, 15' shallow concentrated woods** Woodland Kv= 5.0 fps
16.6	115	Total			

Subcatchment ES3:



Summary for Reach AP1:

Inflow Area = 2.786 ac, 0.30% Impervious, Inflow Depth > 2.72" for 100-yr event
Inflow = 8.04 cfs @ 12.12 hrs, Volume= 0.631 af
Outflow = 8.04 cfs @ 12.12 hrs, Volume= 0.631 af, Atten= 0%, Lag= 0.0 min

Routing by Dyn-Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs / 3

Reach AP1:



Summary for Pond 1P: EXISTING POND

Inflow Area = 0.646 ac, 0.00% Impervious, Inflow Depth > 3.25" for 100-yr event
Inflow = 2.18 cfs @ 12.13 hrs, Volume= 0.175 af
Outflow = 2.18 cfs @ 12.14 hrs, Volume= 0.165 af, Atten= 0%, Lag= 0.4 min
Primary = 2.18 cfs @ 12.14 hrs, Volume= 0.165 af

Routing by Dyn-Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs / 3
Peak Elev= 78.57' @ 12.14 hrs Surf.Area= 1,167 sf Storage= 490 cf
Flood Elev= 79.00' Surf.Area= 1,630 sf Storage= 1,090 cf

Plug-Flow detention time= 39.1 min calculated for 0.165 af (95% of inflow)
Center-of-Mass det. time= 10.5 min (861.2 - 850.7)

Volume	Invert	Avail.Storage	Storage Description
#1	78.00'	1,090 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
78.00	550	0	0
79.00	1,630	1,090	1,090

Device	Routing	Invert	Outlet Devices
#1	Primary	78.50'	**35.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s)

Primary OutFlow Max=2.17 cfs @ 12.14 hrs HW=78.57' TW=0.00' (Dynamic Tailwater)
↑**1=Sharp-Crested Rectangular Weir** (Weir Controls 2.17 cfs @ 0.87 fps)

Pond 1P: EXISTING POND



Summary for Pond 2P: EXISTING POND

Inflow Area = 0.469 ac, 0.00% Impervious, Inflow Depth > 3.47" for 100-yr event
Inflow = 1.37 cfs @ 12.23 hrs, Volume= 0.136 af
Outflow = 0.04 cfs @ 19.81 hrs, Volume= 0.013 af, Atten= 97%, Lag= 454.9 min
Primary = 0.04 cfs @ 19.81 hrs, Volume= 0.013 af

Routing by Dyn-Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs / 3
Peak Elev= 80.90' @ 19.81 hrs Surf.Area= 4,955 sf Storage= 5,367 cf

Plug-Flow detention time= 599.2 min calculated for 0.013 af (9% of inflow)
Center-of-Mass det. time= 440.2 min (1,292.6 - 852.3)

Volume	Invert	Avail.Storage	Storage Description
#1	78.00'	5,855 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
78.00	288	0	0
79.00	1,010	649	649
80.00	2,071	1,541	2,190
81.00	5,260	3,666	5,855

Device	Routing	Invert	Outlet Devices
#1	Primary	80.90'	**40.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s)

Primary OutFlow Max=0.04 cfs @ 19.81 hrs HW=80.90' TW=0.00' (Dynamic Tailwater)
↑—**1=Sharp-Crested Rectangular Weir** (Weir Controls 0.04 cfs @ 0.22 fps)

Pond 2P: EXISTING POND



APPENDIX E:
POST DEVELOPMENT STORMWATER MODELING

LaBella
Powered by partnership.

This Page Intentionally Left Blank



Subcat Reach Pond Link

Routing Diagram for HydroCAD_PostDev_2222201
Prepared by The Chazen Companies, Printed 11/29/2022
HydroCAD® 10.00-21 s/n 00927 © 2018 HydroCAD Software Solutions LLC

Summary for Subcatchment PS1: ENTRANCE

Runoff = 0.71 cfs @ 12.12 hrs, Volume= 0.057 af, Depth> 1.27"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.10 hrs
Type III 24-hr 1-yr Rainfall=2.61"

Area (sf)	CN	Description
17,360	98	Paved parking, HSG A
5,995	49	50-75% Grass cover, Fair, HSG A
23,355	85	Weighted Average
5,995		25.67% Pervious Area
17,360		74.33% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
7.5	100	0.0400	0.22		**Sheet Flow, 100' sheet flow grass** Grass: Short n= 0.150 P2= 3.17"
0.4	102	0.0350	3.80		**Shallow Concentrated Flow, 102' Shallow concentrated paveme** Paved Kv= 20.3 fps
7.9	202	Total			

Subcatchment PS1: ENTRANCE



Summary for Subcatchment PS2: MID PARKING

Runoff = 0.53 cfs @ 12.12 hrs, Volume= 0.042 af, Depth> 1.20"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.10 hrs
Type III 24-hr 1-yr Rainfall=2.61"

Area (sf)	CN	Description
12,975	98	Paved parking, HSG A
5,375	49	50-75% Grass cover, Fair, HSG A
18,350	84	Weighted Average
5,375		29.29% Pervious Area
12,975		70.71% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
7.1	100	0.0450	0.23		**Sheet Flow, 100' sheet flow grass** Grass: Short n= 0.150 P2= 3.17"
0.6	118	0.0260	3.27		**Shallow Concentrated Flow, 118' paved shallow concentration** Paved Kv= 20.3 fps
7.7	218	Total			

Subcatchment PS2: MID PARKING



Summary for Subcatchment PS3: W PARKING

Runoff = 0.25 cfs @ 12.11 hrs, Volume= 0.019 af, Depth> 0.91"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.10 hrs
Type III 24-hr 1-yr Rainfall=2.61"

Area (sf)	CN	Description
6,240	98	Paved parking, HSG A
1,755	49	50-75% Grass cover, Fair, HSG A
3,070	57	Woods/grass comb., Poor, HSG A
11,065	79	Weighted Average
4,825		43.61% Pervious Area
6,240		56.39% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
3.2	63	0.1349	0.33		**Sheet Flow, 63' grass sheet flow** Grass: Short n= 0.150 P2= 3.17"
0.9	167	0.0239	3.14		**Shallow Concentrated Flow, 167' paved** Paved Kv= 20.3 fps
4.1	230	Total, Increased to minimum Tc = 6.0 min			

Subcatchment PS3: W PARKING



Summary for Subcatchment PS4: EXIT GARAGE

Runoff = 0.03 cfs @ 12.11 hrs, Volume= 0.002 af, Depth> 0.81"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.10 hrs
Type III 24-hr 1-yr Rainfall=2.61"

Area (sf)	CN	Description
892	98	Paved parking, HSG A
686	49	50-75% Grass cover, Fair, HSG A
0	84	50-75% Grass cover, Fair, HSG D
1,578	77	Weighted Average
686		43.47% Pervious Area
892		56.53% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					**Direct Entry, Minimum**

Subcatchment PS4: EXIT GARAGE



Summary for Subcatchment PS5: ENTRANCE GARAGE

Runoff = 0.10 cfs @ 12.11 hrs, Volume= 0.008 af, Depth> 0.81"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.10 hrs
Type III 24-hr 1-yr Rainfall=2.61"

Area (sf)	CN	Description
2,942	98	Paved parking, HSG A
2,292	49	50-75% Grass cover, Fair, HSG A
0	84	50-75% Grass cover, Fair, HSG D
5,234	77	Weighted Average
2,292		43.79% Pervious Area
2,942		56.21% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					**Direct Entry, MINIMUM**

Subcatchment PS5: ENTRANCE GARAGE



Summary for Subcatchment PS6A: BUILDING

Runoff = 0.27 cfs @ 12.11 hrs, Volume= 0.021 af, Depth> 0.86"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.10 hrs
Type III 24-hr 1-yr Rainfall=2.61"

Area (sf)	CN	Description
7,572	98	Paved parking, HSG A
5,258	49	50-75% Grass cover, Fair, HSG A
0	84	50-75% Grass cover, Fair, HSG D
12,830	78	Weighted Average
5,258		40.98% Pervious Area
7,572		59.02% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					**Direct Entry, roof**

Subcatchment PS6A: BUILDING



Summary for Subcatchment PS6B: BUILDING

Runoff = 0.89 cfs @ 12.09 hrs, Volume= 0.076 af, Depth> 2.38"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.10 hrs
Type III 24-hr 1-yr Rainfall=2.61"

Area (sf)	CN	Description
16,600	98	Paved parking, HSG A
0	49	50-75% Grass cover, Fair, HSG A
0	84	50-75% Grass cover, Fair, HSG D
16,600	98	Weighted Average
16,600		100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					**Direct Entry, roof**

Subcatchment PS6B: BUILDING



Summary for Subcatchment PS7: GRASS

Runoff = 0.00 cfs @ 15.76 hrs, Volume= 0.002 af, Depth> 0.03"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.10 hrs
Type III 24-hr 1-yr Rainfall=2.61"

Area (sf)	CN	Description
0	98	Paved parking, HSG A
32,076	49	50-75% Grass cover, Fair, HSG A
0	84	50-75% Grass cover, Fair, HSG D
32,076	49	Weighted Average
32,076		100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
7.9	100	0.0350	0.21		**Sheet Flow, 100' grass sheet flow** Grass: Short n= 0.150 P2= 3.17"
1.1	75	0.0286	1.18		**Shallow Concentrated Flow, 75' grass** Short Grass Pasture Kv= 7.0 fps
9.0	175	Total			

Subcatchment PS7: GRASS



Summary for Reach AP1: DP1

Inflow Area = 2.780 ac, 53.33% Impervious, Inflow Depth > 0.05" for 1-yr event
Inflow = 0.02 cfs @ 16.52 hrs, Volume= 0.012 af
Outflow = 0.02 cfs @ 16.52 hrs, Volume= 0.012 af, Atten= 0%, Lag= 0.0 min

Routing by Dyn-Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.10 hrs / 3

Reach AP1: DP1



Summary for Pond 1P: DETENTION

Inflow Area = 2.780 ac, 53.33% Impervious, Inflow Depth > 0.08" for 1-yr event
Inflow = 0.40 cfs @ 12.11 hrs, Volume= 0.019 af
Outflow = 0.02 cfs @ 16.52 hrs, Volume= 0.012 af, Atten= 96%, Lag= 264.8 min
Primary = 0.02 cfs @ 16.52 hrs, Volume= 0.012 af

Routing by Dyn-Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.10 hrs / 3
Peak Elev= 71.08' @ 16.52 hrs Surf.Area= 5,172 sf Storage= 405 cf
Flood Elev= 74.00' Surf.Area= 9,613 sf Storage= 21,879 cf

Plug-Flow detention time= 304.7 min calculated for 0.012 af (61% of inflow)
Center-of-Mass det. time= 170.8 min (1,092.9 - 922.1)

Volume	Invert	Avail.Storage	Storage Description
#1	71.00'	21,879 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
71.00	5,057	0	0
72.00	6,512	5,785	5,785
73.00	8,032	7,272	13,057
74.00	9,613	8,823	21,879

Device	Routing	Invert	Outlet Devices
#1	Primary	67.00'	**6.0" Round Culvert** L= 26.0' CPP, square edge headwall, Ke= 0.500 Inlet / Outlet Invert= 67.00' / 66.60' S= 0.0154 '/' Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.20 sf
#2	Device 1	73.55'	**12.0" x 12.0" Horiz. Orifice/Grate** C= 0.600 Limited to weir flow at low heads
#3	Device 1	71.00'	**4.0" Vert. Orifice/Grate** C= 0.600

Primary OutFlow Max=0.02 cfs @ 16.52 hrs HW=71.08' TW=0.00' (Dynamic Tailwater)
└─**1=Culvert** (Passes 0.02 cfs of 1.67 cfs potential flow)
  ├─**2=Orifice/Grate** (Controls 0.00 cfs)
  └─**3=Orifice/Grate** (Orifice Controls 0.02 cfs @ 0.96 fps)

Pond 1P: DETENTION



Summary for Pond 2P: BIO (S)

Inflow Area = 0.156 ac, 56.28% Impervious, Inflow Depth > 0.33" for 1-yr event
Inflow = 0.02 cfs @ 13.70 hrs, Volume= 0.004 af
Outflow = 0.00 cfs @ 0.00 hrs, Volume= 0.000 af, Atten= 100%, Lag= 0.0 min
Primary = 0.00 cfs @ 0.00 hrs, Volume= 0.000 af
Secondary = 0.00 cfs @ 0.00 hrs, Volume= 0.000 af

Routing by Dyn-Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.10 hrs / 3
Peak Elev= 73.34' @ 24.00 hrs Surf.Area= 607 sf Storage= 190 cf
Flood Elev= 74.00' Surf.Area= 788 sf Storage= 651 cf

Plug-Flow detention time= (not calculated: initial storage exceeds outflow)
Center-of-Mass det. time= (not calculated: no outflow)

Volume	Invert	Avail.Storage	Storage Description
#1	73.00'	651 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
73.00	514	0	0
74.00	788	651	651

Device	Routing	Invert	Outlet Devices
#1	Primary	73.50'	**5.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s)
#2	Secondary	68.45'	**6.0" Round Culvert** L= 42.0' CPP, square edge headwall, Ke= 0.500 Inlet / Outlet Invert= 68.45' / 67.00' S= 0.0345 '/' Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.20 sf
#3	Device 2	73.90'	**12.0" x 12.0" Horiz. Orifice/Grate** C= 0.600 Limited to weir flow at low heads

Primary OutFlow Max=0.00 cfs @ 0.00 hrs HW=73.00' TW=71.00' (Dynamic Tailwater)
└─**1=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)

Secondary OutFlow Max=0.00 cfs @ 0.00 hrs HW=73.00' TW=0.00' (Dynamic Tailwater)
└─**2=Culvert** (Passes 0.00 cfs of 1.68 cfs potential flow)
└─**3=Orifice/Grate** (Controls 0.00 cfs)

Pond 2P: BIO (S)


Hydrograph
Inflow Area=0.156 ac
Peak Elev=73.34'
Storage=190 cf
0.02 cfs
0.00 cfs
0.00 cfs
0.00 cfs
Inflow
Outflow
Primary
Secondary
Flow (cfs)
0.024
0.022
0.02
0.018
0.016
0.014
0.012
0.01
0.008
0.006
0.004
0.002
0
0 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24
Time (hours)

Summary for Pond 3P: HYDRO

Inflow Area = 1.056 ac, 77.83% Impervious, Inflow Depth > 1.51" for 1-yr event
Inflow = 1.28 cfs @ 12.10 hrs, Volume= 0.133 af
Outflow = 1.28 cfs @ 12.10 hrs, Volume= 0.133 af, Atten= 0%, Lag= 0.0 min
Primary = 1.28 cfs @ 12.10 hrs, Volume= 0.133 af

Routing by Dyn-Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.10 hrs / 3
Peak Elev= 75.92' @ 12.10 hrs
Flood Elev= 79.85'

Device	Routing	Invert	Outlet Devices
#1	Primary	75.00'	**8.0" Round Culvert** L= 10.5' CPP, square edge headwall, Ke= 0.500 Inlet / Outlet Invert= 75.00' / 74.58' S= 0.0400 '/' Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.35 sf

Primary OutFlow Max=1.28 cfs @ 12.10 hrs HW=75.91' TW=72.30' (Dynamic Tailwater)
1=Culvert (Inlet Controls 1.28 cfs @ 3.66 fps)

Pond 3P: HYDRO



Summary for Pond 4P: PRETREAT PIPE

Inflow Area = 0.156 ac, 56.28% Impervious, Inflow Depth > 0.81" for 1-yr event
Inflow = 0.13 cfs @ 12.11 hrs, Volume= 0.011 af
Outflow = 0.02 cfs @ 13.70 hrs, Volume= 0.004 af, Atten= 83%, Lag= 95.4 min
Primary = 0.02 cfs @ 13.70 hrs, Volume= 0.004 af

Routing by Dyn-Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.10 hrs / 3
Peak Elev= 75.02' @ 13.70 hrs Surf.Area= 0 sf Storage= 269 cf
Flood Elev= 75.62' Surf.Area= 0 sf Storage= 269 cf

Plug-Flow detention time= 309.0 min calculated for 0.004 af (41% of inflow)
Center-of-Mass det. time= 173.1 min (1,037.4 - 864.3)

Volume	Invert	Avail.Storage	Storage Description
#1	71.12'	269 cf	**42.0" Round Pipe Storage** L= 28.0'

Device	Routing	Invert	Outlet Devices
#1	Primary	74.95'	**10.0" Round Culvert** L= 4.0' CPP, square edge headwall, Ke= 0.500 Inlet / Outlet Invert= 74.95' / 74.50' S= 0.1125 '/' Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.55 sf

Primary OutFlow Max=0.02 cfs @ 13.70 hrs HW=75.02' TW=73.01' (Dynamic Tailwater)
1=Culvert (Inlet Controls 0.02 cfs @ 0.93 fps)

Pond 4P: PRETREAT PIPE



Summary for Pond 5P: MH1

Inflow Area = 1.056 ac, 77.83% Impervious, Inflow Depth > 1.56" for 1-yr event
Inflow = 1.66 cfs @ 12.10 hrs, Volume= 0.137 af
Outflow = 1.66 cfs @ 12.10 hrs, Volume= 0.137 af, Atten= 0%, Lag= 0.0 min
Primary = 1.28 cfs @ 12.10 hrs, Volume= 0.133 af
Secondary = 0.38 cfs @ 12.10 hrs, Volume= 0.004 af

Routing by Dyn-Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.10 hrs / 3
Peak Elev= 76.39' @ 12.11 hrs
Flood Elev= 80.50'

Device	Routing	Invert	Outlet Devices
#1	Primary	75.20'	**8.0" Round Culvert** L= 9.0' CPP, square edge headwall, Ke= 0.500 Inlet / Outlet Invert= 75.20' / 75.03' S= 0.0189 '/' Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.35 sf
#2	Secondary	76.08'	**12.0" Round Culvert** L= 21.0' CPP, square edge headwall, Ke= 0.500 Inlet / Outlet Invert= 76.08' / 74.90' S= 0.0562 '/' Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.79 sf

Primary OutFlow Max=1.15 cfs @ 12.10 hrs HW=76.38' TW=75.91' (Dynamic Tailwater)
└**1=Culvert** (Inlet Controls 1.15 cfs @ 3.29 fps)

Secondary OutFlow Max=0.36 cfs @ 12.10 hrs HW=76.38' TW=71.02' (Dynamic Tailwater)
└**2=Culvert** (Inlet Controls 0.36 cfs @ 1.85 fps)

Pond 5P: MH1



Summary for Pond 6P: BIO (NW)

Inflow Area = 0.295 ac, 59.02% Impervious, Inflow Depth > 0.86" for 1-yr event
Inflow = 0.27 cfs @ 12.11 hrs, Volume= 0.021 af
Outflow = 0.04 cfs @ 12.81 hrs, Volume= 0.012 af, Atten= 84%, Lag= 42.3 min
Primary = 0.04 cfs @ 12.81 hrs, Volume= 0.012 af

Routing by Dyn-Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.10 hrs / 3
Peak Elev= 80.52' @ 12.81 hrs Surf.Area= 910 sf Storage= 425 cf
Flood Elev= 81.00' Surf.Area= 1,085 sf Storage= 903 cf

Plug-Flow detention time= 236.3 min calculated for 0.012 af (55% of inflow)
Center-of-Mass det. time= 113.0 min (973.7 - 860.6)

Volume	Invert	Avail.Storage	Storage Description
#1	80.00'	903 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
80.00	720	0	0
81.00	1,085	903	903

Device	Routing	Invert	Outlet Devices
#1	Primary	76.50'	**6.0" Round Culvert** L= 14.0' CPP, square edge headwall, Ke= 0.500 Inlet / Outlet Invert= 76.50' / 76.25' S= 0.0179 '/' Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.20 sf
#2	Device 1	80.50'	**12.0" x 12.0" Horiz. Orifice/Grate** C= 0.600 Limited to weir flow at low heads

Primary OutFlow Max=0.04 cfs @ 12.81 hrs HW=80.52' TW=75.36' (Dynamic Tailwater)
↑**1=Culvert** (Passes 0.04 cfs of 1.84 cfs potential flow)
↑**2=Orifice/Grate** (Weir Controls 0.04 cfs @ 0.48 fps)

Pond 6P: BIO (NW)



Summary for Pond 7P: CB1

Inflow Area = 0.536 ac, 74.33% Impervious, Inflow Depth > 1.27" for 1-yr event
Inflow = 0.71 cfs @ 12.12 hrs, Volume= 0.057 af
Outflow = 0.71 cfs @ 12.12 hrs, Volume= 0.057 af, Atten= 0%, Lag= 0.0 min
Primary = 0.50 cfs @ 12.14 hrs, Volume= 0.054 af
Secondary = 0.21 cfs @ 12.11 hrs, Volume= 0.002 af

Routing by Dyn-Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.10 hrs / 3
Peak Elev= 77.28' @ 12.13 hrs
Flood Elev= 80.50'

Device	Routing	Invert	Outlet Devices
#1	Primary	76.50'	**6.0" Round Culvert** L= 187.5' CPP, square edge headwall, Ke= 0.500 Inlet / Outlet Invert= 76.50' / 75.20' S= 0.0069 '/' Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.20 sf
#2	Secondary	77.05'	**15.0" Round Culvert** L= 65.0' CPP, square edge headwall, Ke= 0.500 Inlet / Outlet Invert= 77.05' / 76.55' S= 0.0077 '/' Cc= 0.900 n= 0.012 Corrugated PP, smooth interior, Flow Area= 1.23 sf

Primary OutFlow Max=0.48 cfs @ 12.14 hrs HW=77.24' TW=75.63' (Dynamic Tailwater)
└**1=Culvert** (Barrel Controls 0.48 cfs @ 2.46 fps)

Secondary OutFlow Max=0.19 cfs @ 12.11 hrs HW=77.26' TW=75.48' (Dynamic Tailwater)
└**2=Culvert** (Barrel Controls 0.19 cfs @ 2.16 fps)

Pond 7P: CB1



Summary for Pond 8P: PIPE INFILTRATORS

Inflow Area = 1.593 ac, 76.65% Impervious, Inflow Depth > 1.35" for 1-yr event
Inflow = 1.93 cfs @ 12.11 hrs, Volume= 0.179 af
Outflow = 0.11 cfs @ 19.69 hrs, Volume= 0.121 af, Atten= 95%, Lag= 454.7 min
Discarded = 0.11 cfs @ 19.69 hrs, Volume= 0.121 af
Primary = 0.00 cfs @ 0.00 hrs, Volume= 0.000 af

Routing by Dyn-Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.10 hrs / 3
Peak Elev= 73.50' @ 15.66 hrs Surf.Area= 2,254 sf Storage= 4,142 cf
Flood Elev= 75.25' Surf.Area= 0 sf Storage= 7,138 cf

Plug-Flow detention time= 297.4 min calculated for 0.121 af (67% of inflow)
Center-of-Mass det. time= 190.6 min (1,009.5 - 818.9)

Volume	Invert	Avail.Storage	Storage Description
#1	71.25'	7,138 cf	**48.0" Round Pipe Storage** x 4 L= 142.0'

Device	Routing	Invert	Outlet Devices
#1	Discarded	71.25'	**2.000 in/hr Exfiltration over Surface area**
#2	Primary	74.25'	**12.0" Round Culvert** L= 35.0' CPP, square edge headwall, Ke= 0.500 Inlet / Outlet Invert= 74.25' / 73.00' S= 0.0357 '/' Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.79 sf

Discarded OutFlow Max=0.11 cfs @ 19.69 hrs HW=73.25' (Free Discharge)
↑**1=Exfiltration** (Exfiltration Controls 0.11 cfs)

Primary OutFlow Max=0.00 cfs @ 0.00 hrs HW=71.25' TW=71.00' (Dynamic Tailwater)
↑**2=Culvert** (Controls 0.00 cfs)

Pond 8P: PIPE INFILTRATORS



Summary for Pond 9P: MH3

Inflow Area = 0.295 ac, 59.02% Impervious, Inflow Depth > 0.58" for 1-yr event
Inflow = 0.21 cfs @ 12.11 hrs, Volume= 0.014 af
Outflow = 0.21 cfs @ 12.11 hrs, Volume= 0.014 af, Atten= 0%, Lag= 0.0 min
Primary = 0.21 cfs @ 12.11 hrs, Volume= 0.014 af

Routing by Dyn-Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.10 hrs / 3
Peak Elev= 75.50' @ 12.12 hrs
Flood Elev= 83.00'

Device	Routing	Invert	Outlet Devices
#1	Primary	75.25'	**24.0" Round Culvert** L= 264.0' CPP, square edge headwall, Ke= 0.500 Inlet / Outlet Invert= 75.25' / 74.50' S= 0.0028 '/' Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 3.14 sf

Primary OutFlow Max=0.19 cfs @ 12.11 hrs HW=75.48' TW=73.17' (Dynamic Tailwater)
1=Culvert (Barrel Controls 0.19 cfs @ 1.42 fps)

Pond 9P: MH3



Summary for Pond 10P: PIPE DETENTION

Inflow Area = 0.295 ac, 59.02% Impervious, Inflow Depth > 0.58" for 1-yr event
Inflow = 0.21 cfs @ 12.11 hrs, Volume= 0.014 af
Outflow = 0.06 cfs @ 12.24 hrs, Volume= 0.014 af, Atten= 70%, Lag= 7.4 min
Primary = 0.06 cfs @ 12.24 hrs, Volume= 0.014 af

Routing by Dyn-Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.10 hrs / 3
Peak Elev= 73.24' @ 12.24 hrs Surf.Area= 592 sf Storage= 75 cf
Flood Elev= 76.55' Surf.Area= 0 sf Storage= 3,608 cf

Plug-Flow detention time= 26.9 min calculated for 0.014 af (98% of inflow)
Center-of-Mass det. time= 17.9 min (949.2 - 931.3)

Volume	Invert	Avail.Storage	Storage Description
#1	73.05'	3,608 cf	**42.0" Round Pipe Storage** x 3 L= 125.0'

Device	Routing	Invert	Outlet Devices
#1	Primary	73.05'	**6.0" Round Culvert** L= 11.0' CPP, square edge headwall, Ke= 0.500 Inlet / Outlet Invert= 73.05' / 73.00' S= 0.0045 '/' Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.20 sf

Primary OutFlow Max=0.06 cfs @ 12.24 hrs HW=73.23' TW=71.03' (Dynamic Tailwater)
↑**1=Culvert** (Barrel Controls 0.06 cfs @ 1.39 fps)

Pond 10P: PIPE DETENTION



Summary for Pond 11P: PRETREAT PIPE

Inflow Area = 0.536 ac, 74.33% Impervious, Inflow Depth > 1.21" for 1-yr event
Inflow = 0.50 cfs @ 12.14 hrs, Volume= 0.054 af
Outflow = 0.65 cfs @ 12.11 hrs, Volume= 0.046 af, Atten= 0%, Lag= 0.0 min
Primary = 0.65 cfs @ 12.11 hrs, Volume= 0.046 af

Routing by Dyn-Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.10 hrs / 3
Peak Elev= 75.69' @ 12.12 hrs Surf.Area= 18 sf Storage= 404 cf
Flood Elev= 75.70' Surf.Area= 0 sf Storage= 404 cf

Plug-Flow detention time= 98.7 min calculated for 0.046 af (84% of inflow)
Center-of-Mass det. time= 30.8 min (872.4 - 841.6)

Volume	Invert	Avail.Storage	Storage Description
#1	72.20'	404 cf	**42.0" Round Pipe Storage** L= 42.0'

Device	Routing	Invert	Outlet Devices
#1	Primary	75.20'	**8.0" Round Culvert** L= 14.0' CPP, square edge headwall, Ke= 0.500 Inlet / Outlet Invert= 75.20' / 74.58' S= 0.0443 '/' Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.35 sf

Primary OutFlow Max=0.60 cfs @ 12.11 hrs HW=75.66' TW=72.33' (Dynamic Tailwater)
1=Culvert (Inlet Controls 0.60 cfs @ 2.32 fps)

Pond 11P: PRETREAT PIPE



Summary for Subcatchment PS1: ENTRANCE

Runoff = 1.70 cfs @ 12.11 hrs, Volume= 0.137 af, Depth> 3.06"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.10 hrs
Type III 24-hr 10-yr Rainfall=4.67"

Area (sf)	CN	Description
17,360	98	Paved parking, HSG A
5,995	49	50-75% Grass cover, Fair, HSG A
23,355	85	Weighted Average
5,995		25.67% Pervious Area
17,360		74.33% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
7.5	100	0.0400	0.22		**Sheet Flow, 100' sheet flow grass** Grass: Short n= 0.150 P2= 3.17"
0.4	102	0.0350	3.80		**Shallow Concentrated Flow, 102' Shallow concentrated paveme** Paved Kv= 20.3 fps
7.9	202	Total			

Subcatchment PS1: ENTRANCE



Summary for Subcatchment PS2: MID PARKING

Runoff = 1.31 cfs @ 12.11 hrs, Volume= 0.104 af, Depth> 2.97"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.10 hrs
Type III 24-hr 10-yr Rainfall=4.67"

Area (sf)	CN	Description
12,975	98	Paved parking, HSG A
5,375	49	50-75% Grass cover, Fair, HSG A
18,350	84	Weighted Average
5,375		29.29% Pervious Area
12,975		70.71% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
7.1	100	0.0450	0.23		**Sheet Flow, 100' sheet flow grass** Grass: Short n= 0.150 P2= 3.17"
0.6	118	0.0260	3.27		**Shallow Concentrated Flow, 118' paved shallow concentration** Paved Kv= 20.3 fps
7.7	218	Total			

Subcatchment PS2: MID PARKING



Summary for Subcatchment PS3: W PARKING

Runoff = 0.70 cfs @ 12.10 hrs, Volume= 0.053 af, Depth> 2.52"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.10 hrs
Type III 24-hr 10-yr Rainfall=4.67"

Area (sf)	CN	Description
6,240	98	Paved parking, HSG A
1,755	49	50-75% Grass cover, Fair, HSG A
3,070	57	Woods/grass comb., Poor, HSG A
11,065	79	Weighted Average
4,825		43.61% Pervious Area
6,240		56.39% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
3.2	63	0.1349	0.33		**Sheet Flow, 63' grass sheet flow** Grass: Short n= 0.150 P2= 3.17"
0.9	167	0.0239	3.14		**Shallow Concentrated Flow, 167' paved** Paved Kv= 20.3 fps
4.1	230	Total, Increased to minimum Tc = 6.0 min			

Subcatchment PS3: W PARKING



Summary for Subcatchment PS4: EXIT GARAGE

Runoff = 0.09 cfs @ 12.10 hrs, Volume= 0.007 af, Depth> 2.35"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.10 hrs
Type III 24-hr 10-yr Rainfall=4.67"

Area (sf)	CN	Description
892	98	Paved parking, HSG A
686	49	50-75% Grass cover, Fair, HSG A
0	84	50-75% Grass cover, Fair, HSG D
1,578	77	Weighted Average
686		43.47% Pervious Area
892		56.53% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					**Direct Entry, Minimum**

Subcatchment PS4: EXIT GARAGE



Summary for Subcatchment PS5: ENTRANCE GARAGE

Runoff = 0.31 cfs @ 12.10 hrs, Volume= 0.024 af, Depth> 2.35"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.10 hrs
Type III 24-hr 10-yr Rainfall=4.67"

Area (sf)	CN	Description
2,942	98	Paved parking, HSG A
2,292	49	50-75% Grass cover, Fair, HSG A
0	84	50-75% Grass cover, Fair, HSG D
5,234	77	Weighted Average
2,292		43.79% Pervious Area
2,942		56.21% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					**Direct Entry, MINIMUM**

Subcatchment PS5: ENTRANCE GARAGE



Summary for Subcatchment PS6A: BUILDING

Runoff = 0.79 cfs @ 12.10 hrs, Volume= 0.060 af, Depth> 2.43"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.10 hrs
Type III 24-hr 10-yr Rainfall=4.67"

Area (sf)	CN	Description
7,572	98	Paved parking, HSG A
5,258	49	50-75% Grass cover, Fair, HSG A
0	84	50-75% Grass cover, Fair, HSG D
12,830	78	Weighted Average
5,258		40.98% Pervious Area
7,572		59.02% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					**Direct Entry, roof**

Subcatchment PS6A: BUILDING



Summary for Subcatchment PS6B: BUILDING

Runoff = 1.62 cfs @ 12.09 hrs, Volume= 0.141 af, Depth> 4.43"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.10 hrs
Type III 24-hr 10-yr Rainfall=4.67"

Area (sf)	CN	Description
16,600	98	Paved parking, HSG A
0	49	50-75% Grass cover, Fair, HSG A
0	84	50-75% Grass cover, Fair, HSG D
16,600	98	Weighted Average
16,600		100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					**Direct Entry, roof**

Subcatchment PS6B: BUILDING



Summary for Subcatchment PS7: GRASS

Runoff = 0.19 cfs @ 12.26 hrs, Volume= 0.032 af, Depth> 0.51"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.10 hrs
Type III 24-hr 10-yr Rainfall=4.67"

Area (sf)	CN	Description
0	98	Paved parking, HSG A
32,076	49	50-75% Grass cover, Fair, HSG A
0	84	50-75% Grass cover, Fair, HSG D
32,076	49	Weighted Average
32,076		100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
7.9	100	0.0350	0.21		**Sheet Flow, 100' grass sheet flow** Grass: Short n= 0.150 P2= 3.17"
1.1	75	0.0286	1.18		**Shallow Concentrated Flow, 75' grass** Short Grass Pasture Kv= 7.0 fps
9.0	175	Total			

Subcatchment PS7: GRASS



Summary for Reach AP1: DP1

Inflow Area = 2.780 ac, 53.33% Impervious, Inflow Depth > 1.12" for 10-yr event
Inflow = 0.38 cfs @ 14.34 hrs, Volume= 0.259 af
Outflow = 0.38 cfs @ 14.34 hrs, Volume= 0.259 af, Atten= 0%, Lag= 0.0 min

Routing by Dyn-Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.10 hrs / 3

Reach AP1: DP1



Summary for Pond 1P: DETENTION

Inflow Area = 2.780 ac, 53.33% Impervious, Inflow Depth > 1.21" for 10-yr event
Inflow = 2.76 cfs @ 12.12 hrs, Volume= 0.280 af
Outflow = 0.38 cfs @ 14.34 hrs, Volume= 0.259 af, Atten= 86%, Lag= 133.0 min
Primary = 0.38 cfs @ 14.34 hrs, Volume= 0.259 af

Routing by Dyn-Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.10 hrs / 3
Peak Elev= 71.99' @ 14.34 hrs Surf.Area= 6,502 sf Storage= 5,739 cf
Flood Elev= 74.00' Surf.Area= 9,613 sf Storage= 21,879 cf

Plug-Flow detention time= 201.8 min calculated for 0.259 af (92% of inflow)
Center-of-Mass det. time= 169.7 min (1,014.5 - 844.9)

Volume	Invert	Avail.Storage	Storage Description
#1	71.00'	21,879 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
71.00	5,057	0	0
72.00	6,512	5,785	5,785
73.00	8,032	7,272	13,057
74.00	9,613	8,823	21,879

Device	Routing	Invert	Outlet Devices
#1	Primary	67.00'	**6.0" Round Culvert** L= 26.0' CPP, square edge headwall, Ke= 0.500 Inlet / Outlet Invert= 67.00' / 66.60' S= 0.0154 '/' Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.20 sf
#2	Device 1	73.55'	**12.0" x 12.0" Horiz. Orifice/Grate** C= 0.600 Limited to weir flow at low heads
#3	Device 1	71.00'	**4.0" Vert. Orifice/Grate** C= 0.600

Primary OutFlow Max=0.38 cfs @ 14.34 hrs HW=71.99' TW=0.00' (Dynamic Tailwater)
└─**1=Culvert** (Passes 0.38 cfs of 1.85 cfs potential flow)
  ├─**2=Orifice/Grate** (Controls 0.00 cfs)
  └─**3=Orifice/Grate** (Orifice Controls 0.38 cfs @ 4.38 fps)

Pond 1P: DETENTION



Summary for Pond 2P: BIO (S)

Inflow Area = 0.156 ac, 56.28% Impervious, Inflow Depth > 1.87" for 10-yr event
Inflow = 0.60 cfs @ 12.10 hrs, Volume= 0.024 af
Outflow = 0.21 cfs @ 12.41 hrs, Volume= 0.018 af, Atten= 65%, Lag= 18.3 min
Primary = 0.21 cfs @ 12.41 hrs, Volume= 0.018 af
Secondary = 0.00 cfs @ 0.00 hrs, Volume= 0.000 af

Routing by Dyn-Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.10 hrs / 3
Peak Elev= 73.56' @ 12.41 hrs Surf.Area= 666 sf Storage= 328 cf
Flood Elev= 74.00' Surf.Area= 788 sf Storage= 651 cf

Plug-Flow detention time= 154.9 min calculated for 0.018 af (72% of inflow)
Center-of-Mass det. time= 57.3 min (925.4 - 868.1)

Volume	Invert	Avail.Storage	Storage Description
#1	73.00'	651 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
73.00	514	0	0
74.00	788	651	651

Device	Routing	Invert	Outlet Devices
#1	Primary	73.50'	**5.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s)
#2	Secondary	68.45'	**6.0" Round Culvert** L= 42.0' CPP, square edge headwall, Ke= 0.500 Inlet / Outlet Invert= 68.45' / 67.00' S= 0.0345 '/' Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.20 sf
#3	Device 2	73.90'	**12.0" x 12.0" Horiz. Orifice/Grate** C= 0.600 Limited to weir flow at low heads

Primary OutFlow Max=0.20 cfs @ 12.41 hrs HW=73.55' TW=71.52' (Dynamic Tailwater)
└**1=Sharp-Crested Rectangular Weir** (Weir Controls 0.20 cfs @ 0.75 fps)

Secondary OutFlow Max=0.00 cfs @ 0.00 hrs HW=73.00' TW=0.00' (Dynamic Tailwater)
└**2=Culvert** (Passes 0.00 cfs of 1.68 cfs potential flow)
└**3=Orifice/Grate** (Controls 0.00 cfs)

Pond 2P: BIO (S)


Hydrograph
Inflow Area=0.156 ac
Peak Elev=73.56'
Storage=328 cf
Inflow
Outflow
Primary
Secondary
0.60 cfs
0.21 cfs
0.21 cfs
0.00 cfs
Flow (cfs)
Time (hours)

Summary for Pond 3P: HYDRO

Inflow Area = 1.056 ac, 77.83% Impervious, Inflow Depth > 2.91" for 10-yr event
Inflow = 1.54 cfs @ 12.08 hrs, Volume= 0.256 af
Outflow = 1.54 cfs @ 12.08 hrs, Volume= 0.256 af, Atten= 0%, Lag= 0.0 min
Primary = 1.54 cfs @ 12.08 hrs, Volume= 0.256 af

Routing by Dyn-Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.10 hrs / 3
Peak Elev= 76.17' @ 12.09 hrs
Flood Elev= 79.85'

Device	Routing	Invert	Outlet Devices
#1	Primary	75.00'	**8.0" Round Culvert** L= 10.5' CPP, square edge headwall, Ke= 0.500 Inlet / Outlet Invert= 75.00' / 74.58' S= 0.0400 '/' Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.35 sf

Primary OutFlow Max=1.51 cfs @ 12.08 hrs HW=76.14' TW=73.40' (Dynamic Tailwater)
1=Culvert (Inlet Controls 1.51 cfs @ 4.34 fps)

Pond 3P: HYDRO



Summary for Pond 4P: PRETREAT PIPE

Inflow Area = 0.156 ac, 56.28% Impervious, Inflow Depth > 2.35" for 10-yr event
Inflow = 0.40 cfs @ 12.10 hrs, Volume= 0.031 af
Outflow = 0.60 cfs @ 12.10 hrs, Volume= 0.024 af, Atten= 0%, Lag= 0.1 min
Primary = 0.60 cfs @ 12.10 hrs, Volume= 0.024 af

Routing by Dyn-Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.10 hrs / 3
Peak Elev= 75.37' @ 12.10 hrs Surf.Area= 0 sf Storage= 269 cf
Flood Elev= 75.62' Surf.Area= 0 sf Storage= 269 cf

Plug-Flow detention time= 114.1 min calculated for 0.024 af (80% of inflow)
Center-of-Mass det. time= 35.5 min (868.1 - 832.5)

Volume	Invert	Avail.Storage	Storage Description
#1	71.12'	269 cf	**42.0" Round Pipe Storage** L= 28.0'

Device	Routing	Invert	Outlet Devices
#1	Primary	74.95'	**10.0" Round Culvert** L= 4.0' CPP, square edge headwall, Ke= 0.500 Inlet / Outlet Invert= 74.95' / 74.50' S= 0.1125 '/' Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.55 sf

Primary OutFlow Max=0.57 cfs @ 12.10 hrs HW=75.36' TW=73.21' (Dynamic Tailwater)
1=Culvert (Inlet Controls 0.57 cfs @ 2.17 fps)

Pond 4P: PRETREAT PIPE



Summary for Pond 5P: MH1

Inflow Area = 1.056 ac, 77.83% Impervious, Inflow Depth > 3.39" for 10-yr event
Inflow = 3.63 cfs @ 12.10 hrs, Volume= 0.298 af
Outflow = 3.63 cfs @ 12.10 hrs, Volume= 0.298 af, Atten= 0%, Lag= 0.0 min
Primary = 1.54 cfs @ 12.08 hrs, Volume= 0.256 af
Secondary = 2.09 cfs @ 12.11 hrs, Volume= 0.042 af

Routing by Dyn-Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.10 hrs / 3
Peak Elev= 76.89' @ 12.11 hrs
Flood Elev= 80.50'

Device	Routing	Invert	Outlet Devices
#1	Primary	75.20'	**8.0" Round Culvert** L= 9.0' CPP, square edge headwall, Ke= 0.500 Inlet / Outlet Invert= 75.20' / 75.03' S= 0.0189 '/' Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.35 sf
#2	Secondary	76.08'	**12.0" Round Culvert** L= 21.0' CPP, square edge headwall, Ke= 0.500 Inlet / Outlet Invert= 76.08' / 74.90' S= 0.0562 '/' Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.79 sf

Primary OutFlow Max=1.40 cfs @ 12.08 hrs HW=76.84' TW=76.14' (Dynamic Tailwater)
└**1=Culvert** (Inlet Controls 1.40 cfs @ 4.02 fps)

Secondary OutFlow Max=2.04 cfs @ 12.11 hrs HW=76.88' TW=71.19' (Dynamic Tailwater)
└**2=Culvert** (Inlet Controls 2.04 cfs @ 3.04 fps)

Pond 5P: MH1



Summary for Pond 6P: BIO (NW)

Inflow Area = 0.295 ac, 59.02% Impervious, Inflow Depth > 2.43" for 10-yr event
Inflow = 0.79 cfs @ 12.10 hrs, Volume= 0.060 af
Outflow = 0.72 cfs @ 12.14 hrs, Volume= 0.050 af, Atten= 9%, Lag= 2.5 min
Primary = 0.72 cfs @ 12.14 hrs, Volume= 0.050 af

Routing by Dyn-Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.10 hrs / 3
Peak Elev= 80.65' @ 12.14 hrs Surf.Area= 956 sf Storage= 541 cf
Flood Elev= 81.00' Surf.Area= 1,085 sf Storage= 903 cf

Plug-Flow detention time= 99.5 min calculated for 0.050 af (84% of inflow)
Center-of-Mass det. time= 32.4 min (862.2 - 829.9)

Volume	Invert	Avail.Storage	Storage Description
#1	80.00'	903 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
80.00	720	0	0
81.00	1,085	903	903

Device	Routing	Invert	Outlet Devices
#1	Primary	76.50'	**6.0" Round Culvert** L= 14.0' CPP, square edge headwall, Ke= 0.500 Inlet / Outlet Invert= 76.50' / 76.25' S= 0.0179 '/' Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.20 sf
#2	Device 1	80.50'	**12.0" x 12.0" Horiz. Orifice/Grate** C= 0.600 Limited to weir flow at low heads

Primary OutFlow Max=0.67 cfs @ 12.14 hrs HW=80.64' TW=75.92' (Dynamic Tailwater)
↑**1=Culvert** (Passes 0.67 cfs of 1.86 cfs potential flow)
↑**2=Orifice/Grate** (Weir Controls 0.67 cfs @ 1.21 fps)

Pond 6P: BIO (NW)



Summary for Pond 7P: CB1

Inflow Area = 0.536 ac, 74.33% Impervious, Inflow Depth > 3.06" for 10-yr event
Inflow = 1.70 cfs @ 12.11 hrs, Volume= 0.137 af
Outflow = 1.70 cfs @ 12.11 hrs, Volume= 0.137 af, Atten= 0%, Lag= 0.0 min
Primary = 0.54 cfs @ 12.12 hrs, Volume= 0.111 af
Secondary = 1.17 cfs @ 12.11 hrs, Volume= 0.026 af

Routing by Dyn-Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.10 hrs / 3
Peak Elev= 77.59' @ 12.12 hrs
Flood Elev= 80.50'

Device	Routing	Invert	Outlet Devices
#1	Primary	76.50'	**6.0" Round Culvert** L= 187.5' CPP, square edge headwall, Ke= 0.500 Inlet / Outlet Invert= 76.50' / 75.20' S= 0.0069 '/' Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.20 sf
#2	Secondary	77.05'	**15.0" Round Culvert** L= 65.0' CPP, square edge headwall, Ke= 0.500 Inlet / Outlet Invert= 77.05' / 76.55' S= 0.0077 '/' Cc= 0.900 n= 0.012 Corrugated PP, smooth interior, Flow Area= 1.23 sf

Primary OutFlow Max=0.53 cfs @ 12.12 hrs HW=77.57' TW=75.63' (Dynamic Tailwater)
└**1=Culvert** (Barrel Controls 0.53 cfs @ 2.71 fps)

Secondary OutFlow Max=1.10 cfs @ 12.11 hrs HW=77.57' TW=75.94' (Dynamic Tailwater)
└**2=Culvert** (Barrel Controls 1.10 cfs @ 3.38 fps)

Pond 7P: CB1



Summary for Pond 8P: PIPE INFILTRATORS

Inflow Area = 1.593 ac, 76.65% Impervious, Inflow Depth > 2.70" for 10-yr event
Inflow = 2.08 cfs @ 12.09 hrs, Volume= 0.358 af
Outflow = 0.80 cfs @ 12.70 hrs, Volume= 0.230 af, Atten= 61%, Lag= 36.6 min
Discarded = 0.11 cfs @ 12.03 hrs, Volume= 0.118 af
Primary = 0.73 cfs @ 12.70 hrs, Volume= 0.113 af

Routing by Dyn-Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.10 hrs / 3
Peak Elev= 74.68' @ 12.70 hrs Surf.Area= 1,585 sf Storage= 6,519 cf
Flood Elev= 75.25' Surf.Area= 0 sf Storage= 7,138 cf

Plug-Flow detention time= 205.2 min calculated for 0.229 af (64% of inflow)
Center-of-Mass det. time= 91.0 min (902.9 - 811.9)

Volume	Invert	Avail.Storage	Storage Description
#1	71.25'	7,138 cf	**48.0" Round Pipe Storage** x 4 L= 142.0'

Device	Routing	Invert	Outlet Devices
#1	Discarded	71.25'	**2.000 in/hr Exfiltration over Surface area**
#2	Primary	74.25'	**12.0" Round Culvert** L= 35.0' CPP, square edge headwall, Ke= 0.500 Inlet / Outlet Invert= 74.25' / 73.00' S= 0.0357 '/' Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.79 sf

Discarded OutFlow Max=0.11 cfs @ 12.03 hrs HW=73.24' (Free Discharge)
↑**1=Exfiltration** (Exfiltration Controls 0.11 cfs)

Primary OutFlow Max=0.73 cfs @ 12.70 hrs HW=74.68' TW=71.72' (Dynamic Tailwater)
↑**2=Culvert** (Inlet Controls 0.73 cfs @ 2.24 fps)

Pond 8P: PIPE INFILTRATORS



Summary for Pond 9P: MH3

Inflow Area = 0.295 ac, 59.02% Impervious, Inflow Depth > 3.11" for 10-yr event
Inflow = 1.88 cfs @ 12.12 hrs, Volume= 0.076 af
Outflow = 1.88 cfs @ 12.12 hrs, Volume= 0.076 af, Atten= 0%, Lag= 0.0 min
Primary = 1.88 cfs @ 12.12 hrs, Volume= 0.076 af

Routing by Dyn-Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.10 hrs / 3
Peak Elev= 75.97' @ 12.13 hrs
Flood Elev= 83.00'

Device	Routing	Invert	Outlet Devices
#1	Primary	75.25'	**24.0" Round Culvert** L= 264.0' CPP, square edge headwall, Ke= 0.500 Inlet / Outlet Invert= 75.25' / 74.50' S= 0.0028 '/' Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 3.14 sf

Primary OutFlow Max=1.74 cfs @ 12.12 hrs HW=75.94' TW=73.82' (Dynamic Tailwater)
1=Culvert (Barrel Controls 1.74 cfs @ 2.73 fps)

Pond 9P: MH3



Summary for Pond 10P: PIPE DETENTION

Inflow Area = 0.295 ac, 59.02% Impervious, Inflow Depth > 3.11" for 10-yr event
Inflow = 1.88 cfs @ 12.12 hrs, Volume= 0.076 af
Outflow = 0.83 cfs @ 12.32 hrs, Volume= 0.076 af, Atten= 56%, Lag= 11.8 min
Primary = 0.83 cfs @ 12.32 hrs, Volume= 0.076 af

Routing by Dyn-Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.10 hrs / 3
Peak Elev= 74.16' @ 12.32 hrs Surf.Area= 1,223 sf Storage= 988 cf
Flood Elev= 76.55' Surf.Area= 0 sf Storage= 3,608 cf

Plug-Flow detention time= 19.2 min calculated for 0.076 af (99% of inflow)
Center-of-Mass det. time= 15.6 min (832.1 - 816.4)

Volume	Invert	Avail.Storage	Storage Description
#1	73.05'	3,608 cf	**42.0" Round Pipe Storage** x 3 L= 125.0'

Device	Routing	Invert	Outlet Devices
#1	Primary	73.05'	**6.0" Round Culvert** L= 11.0' CPP, square edge headwall, Ke= 0.500 Inlet / Outlet Invert= 73.05' / 73.00' S= 0.0045 '/' Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.20 sf

Primary OutFlow Max=0.83 cfs @ 12.32 hrs HW=74.15' TW=71.46' (Dynamic Tailwater)
1=Culvert (Barrel Controls 0.83 cfs @ 4.21 fps)

Pond 10P: PIPE DETENTION



Summary for Pond 11P: PRETREAT PIPE

Inflow Area = 0.536 ac, 74.33% Impervious, Inflow Depth > 2.47" for 10-yr event
Inflow = 0.54 cfs @ 12.12 hrs, Volume= 0.111 af
Outflow = 0.54 cfs @ 12.12 hrs, Volume= 0.102 af, Atten= 0%, Lag= 0.1 min
Primary = 0.54 cfs @ 12.12 hrs, Volume= 0.102 af

Routing by Dyn-Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.10 hrs / 3
Peak Elev= 75.63' @ 12.12 hrs Surf.Area= 40 sf Storage= 402 cf
Flood Elev= 75.70' Surf.Area= 0 sf Storage= 404 cf

Plug-Flow detention time= 62.8 min calculated for 0.102 af (92% of inflow)
Center-of-Mass det. time= 22.7 min (853.8 - 831.1)

Volume	Invert	Avail.Storage	Storage Description
#1	72.20'	404 cf	**42.0" Round Pipe Storage** L= 42.0'

Device	Routing	Invert	Outlet Devices
#1	Primary	75.20'	**8.0" Round Culvert** L= 14.0' CPP, square edge headwall, Ke= 0.500 Inlet / Outlet Invert= 75.20' / 74.58' S= 0.0443 '/' Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.35 sf

Primary OutFlow Max=0.53 cfs @ 12.12 hrs HW=75.63' TW=73.51' (Dynamic Tailwater)
1=Culvert (Inlet Controls 0.53 cfs @ 2.24 fps)

Pond 11P: PRETREAT PIPE



Summary for Subcatchment PS1: ENTRANCE

Runoff = 3.46 cfs @ 12.11 hrs, Volume= 0.286 af, Depth> 6.40"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.10 hrs
Type III 24-hr 100-yr Rainfall=8.20"

Area (sf)	CN	Description
17,360	98	Paved parking, HSG A
5,995	49	50-75% Grass cover, Fair, HSG A
23,355	85	Weighted Average
5,995		25.67% Pervious Area
17,360		74.33% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
7.5	100	0.0400	0.22		**Sheet Flow, 100' sheet flow grass** Grass: Short n= 0.150 P2= 3.17"
0.4	102	0.0350	3.80		**Shallow Concentrated Flow, 102' Shallow concentrated paveme** Paved Kv= 20.3 fps
7.9	202	Total			

Subcatchment PS1: ENTRANCE



Summary for Subcatchment PS2: MID PARKING

Runoff = 2.70 cfs @ 12.11 hrs, Volume= 0.221 af, Depth> 6.28"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.10 hrs
Type III 24-hr 100-yr Rainfall=8.20"

Area (sf)	CN	Description
12,975	98	Paved parking, HSG A
5,375	49	50-75% Grass cover, Fair, HSG A
18,350	84	Weighted Average
5,375		29.29% Pervious Area
12,975		70.71% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
7.1	100	0.0450	0.23		**Sheet Flow, 100' sheet flow grass** Grass: Short n= 0.150 P2= 3.17"
0.6	118	0.0260	3.27		**Shallow Concentrated Flow, 118' paved shallow concentration** Paved Kv= 20.3 fps
7.7	218	Total			

Subcatchment PS2: MID PARKING



Summary for Subcatchment PS3: W PARKING

Runoff = 1.56 cfs @ 12.10 hrs, Volume= 0.120 af, Depth> 5.69"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.10 hrs
Type III 24-hr 100-yr Rainfall=8.20"

Area (sf)	CN	Description
6,240	98	Paved parking, HSG A
1,755	49	50-75% Grass cover, Fair, HSG A
3,070	57	Woods/grass comb., Poor, HSG A
11,065	79	Weighted Average
4,825		43.61% Pervious Area
6,240		56.39% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
3.2	63	0.1349	0.33		**Sheet Flow, 63' grass sheet flow** Grass: Short n= 0.150 P2= 3.17"
0.9	167	0.0239	3.14		**Shallow Concentrated Flow, 167' paved** Paved Kv= 20.3 fps
4.1	230	Total, Increased to minimum Tc = 6.0 min			

Subcatchment PS3: W PARKING



Summary for Subcatchment PS4: EXIT GARAGE

Runoff = 0.21 cfs @ 12.10 hrs, Volume= 0.016 af, Depth> 5.46"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.10 hrs
Type III 24-hr 100-yr Rainfall=8.20"

Area (sf)	CN	Description
892	98	Paved parking, HSG A
686	49	50-75% Grass cover, Fair, HSG A
0	84	50-75% Grass cover, Fair, HSG D
1,578	77	Weighted Average
686		43.47% Pervious Area
892		56.53% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					**Direct Entry, Minimum**

Subcatchment PS4: EXIT GARAGE



Summary for Subcatchment PS5: ENTRANCE GARAGE

Runoff = 0.71 cfs @ 12.10 hrs, Volume= 0.055 af, Depth> 5.46"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.10 hrs
Type III 24-hr 100-yr Rainfall=8.20"

Area (sf)	CN	Description
2,942	98	Paved parking, HSG A
2,292	49	50-75% Grass cover, Fair, HSG A
0	84	50-75% Grass cover, Fair, HSG D
5,234	77	Weighted Average
2,292		43.79% Pervious Area
2,942		56.21% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					**Direct Entry, MINIMUM**

Subcatchment PS5: ENTRANCE GARAGE



Summary for Subcatchment PS6A: BUILDING

Runoff = 1.78 cfs @ 12.10 hrs, Volume= 0.137 af, Depth> 5.57"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.10 hrs
Type III 24-hr 100-yr Rainfall=8.20"

Area (sf)	CN	Description
7,572	98	Paved parking, HSG A
5,258	49	50-75% Grass cover, Fair, HSG A
0	84	50-75% Grass cover, Fair, HSG D
12,830	78	Weighted Average
5,258		40.98% Pervious Area
7,572		59.02% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					**Direct Entry, roof**

Subcatchment PS6A: BUILDING



Summary for Subcatchment PS6B: BUILDING

Runoff = 2.86 cfs @ 12.09 hrs, Volume= 0.253 af, Depth> 7.96"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.10 hrs
Type III 24-hr 100-yr Rainfall=8.20"

Area (sf)	CN	Description
16,600	98	Paved parking, HSG A
0	49	50-75% Grass cover, Fair, HSG A
0	84	50-75% Grass cover, Fair, HSG D
16,600	98	Weighted Average
16,600		100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					**Direct Entry, roof**

Subcatchment PS6B: BUILDING



Summary for Subcatchment PS7: GRASS

Runoff = 1.50 cfs @ 12.15 hrs, Volume= 0.139 af, Depth> 2.26"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.10 hrs
Type III 24-hr 100-yr Rainfall=8.20"

Area (sf)	CN	Description
0	98	Paved parking, HSG A
32,076	49	50-75% Grass cover, Fair, HSG A
0	84	50-75% Grass cover, Fair, HSG D
32,076	49	Weighted Average
32,076		100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
7.9	100	0.0350	0.21		**Sheet Flow, 100' grass sheet flow** Grass: Short n= 0.150 P2= 3.17"
1.1	75	0.0286	1.18		**Shallow Concentrated Flow, 75' grass** Short Grass Pasture Kv= 7.0 fps
9.0	175	Total			

Subcatchment PS7: GRASS



Summary for Reach AP1: DP1

Inflow Area = 2.780 ac, 53.33% Impervious, Inflow Depth > 3.25" for 100-yr event
Inflow = 2.13 cfs @ 13.11 hrs, Volume= 0.752 af
Outflow = 2.13 cfs @ 13.11 hrs, Volume= 0.752 af, Atten= 0%, Lag= 0.0 min

Routing by Dyn-Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.10 hrs / 3

Reach AP1: DP1



Summary for Pond 1P: DETENTION

Inflow Area = 2.780 ac, 53.33% Impervious, Inflow Depth > 4.02" for 100-yr event
Inflow = 10.86 cfs @ 12.12 hrs, Volume= 0.932 af
Outflow = 2.13 cfs @ 13.11 hrs, Volume= 0.752 af, Atten= 80%, Lag= 59.5 min
Primary = 2.13 cfs @ 13.11 hrs, Volume= 0.752 af

Routing by Dyn-Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.10 hrs / 3
Peak Elev= 73.78' @ 13.11 hrs Surf.Area= 9,266 sf Storage= 19,807 cf
Flood Elev= 74.00' Surf.Area= 9,613 sf Storage= 21,879 cf

Plug-Flow detention time= 243.2 min calculated for 0.752 af (81% of inflow)
Center-of-Mass det. time= 178.5 min (1,009.0 - 830.4)

Volume	Invert	Avail.Storage	Storage Description
#1	71.00'	21,879 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
71.00	5,057	0	0
72.00	6,512	5,785	5,785
73.00	8,032	7,272	13,057
74.00	9,613	8,823	21,879

Device	Routing	Invert	Outlet Devices
#1	Primary	67.00'	**6.0" Round Culvert** L= 26.0' CPP, square edge headwall, Ke= 0.500 Inlet / Outlet Invert= 67.00' / 66.60' S= 0.0154 '/' Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.20 sf
#2	Device 1	73.55'	**12.0" x 12.0" Horiz. Orifice/Grate** C= 0.600 Limited to weir flow at low heads
#3	Device 1	71.00'	**4.0" Vert. Orifice/Grate** C= 0.600

Primary OutFlow Max=2.12 cfs @ 13.11 hrs HW=73.78' TW=0.00' (Dynamic Tailwater)
└─**1=Culvert** (Passes 2.12 cfs of 2.16 cfs potential flow)
  ├─**2=Orifice/Grate** (Weir Controls 1.44 cfs @ 1.57 fps)
  └─**3=Orifice/Grate** (Orifice Controls 0.68 cfs @ 7.78 fps)

Pond 1P: DETENTION



Summary for Pond 2P: BIO (S)

Inflow Area = 0.156 ac, 56.28% Impervious, Inflow Depth > 4.98" for 100-yr event
Inflow = 0.89 cfs @ 12.10 hrs, Volume= 0.065 af
Outflow = 0.86 cfs @ 12.12 hrs, Volume= 0.058 af, Atten= 3%, Lag= 1.3 min
Primary = 0.86 cfs @ 12.12 hrs, Volume= 0.060 af
Secondary = 0.00 cfs @ 0.00 hrs, Volume= 0.000 af

Routing by Dyn-Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.10 hrs / 3
Peak Elev= 73.78' @ 13.13 hrs Surf.Area= 728 sf Storage= 485 cf
Flood Elev= 74.00' Surf.Area= 788 sf Storage= 651 cf

Plug-Flow detention time= 73.8 min calculated for 0.058 af (89% of inflow)
Center-of-Mass det. time= 25.2 min (854.7 - 829.4)

Volume	Invert	Avail.Storage	Storage Description
#1	73.00'	651 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
73.00	514	0	0
74.00	788	651	651

Device	Routing	Invert	Outlet Devices
#1	Primary	73.50'	**5.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s)
#2	Secondary	68.45'	**6.0" Round Culvert** L= 42.0' CPP, square edge headwall, Ke= 0.500 Inlet / Outlet Invert= 68.45' / 67.00' S= 0.0345 '/' Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.20 sf
#3	Device 2	73.90'	**12.0" x 12.0" Horiz. Orifice/Grate** C= 0.600 Limited to weir flow at low heads

Primary OutFlow Max=0.83 cfs @ 12.12 hrs HW=73.64' TW=72.22' (Dynamic Tailwater)
└─**1=Sharp-Crested Rectangular Weir** (Weir Controls 0.83 cfs @ 1.21 fps)

Secondary OutFlow Max=0.00 cfs @ 0.00 hrs HW=73.00' TW=0.00' (Dynamic Tailwater)
└─**2=Culvert** (Passes 0.00 cfs of 1.68 cfs potential flow)
└─**3=Orifice/Grate** (Controls 0.00 cfs)

Pond 2P: BIO (S)


Hydrograph
Inflow Area=0.156
Peak Elev=73.78'
Storage=485 cf
0.89 cfs
0.86 cfs
0.86 cfs
0.00 cfs
Inflow
Outflow
Primary
Secondary
Flow (cfs)
Time (hours)

Summary for Pond 3P: HYDRO

Inflow Area = 1.056 ac, 77.83% Impervious, Inflow Depth > 5.12" for 100-yr event
Inflow = 2.17 cfs @ 12.09 hrs, Volume= 0.451 af
Outflow = 2.17 cfs @ 12.09 hrs, Volume= 0.451 af, Atten= 0%, Lag= 0.0 min
Primary = 2.17 cfs @ 12.09 hrs, Volume= 0.451 af

Routing by Dyn-Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.10 hrs / 3
Peak Elev= 77.00' @ 12.09 hrs
Flood Elev= 79.85'

Device	Routing	Invert	Outlet Devices
#1	Primary	75.00'	**8.0" Round Culvert** L= 10.5' CPP, square edge headwall, Ke= 0.500 Inlet / Outlet Invert= 75.00' / 74.58' S= 0.0400 '/' Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.35 sf

Primary OutFlow Max=2.12 cfs @ 12.09 hrs HW=76.92' TW=75.11' (Dynamic Tailwater)
1=Culvert (Inlet Controls 2.12 cfs @ 6.06 fps)

Pond 3P: HYDRO



Summary for Pond 4P: PRETREAT PIPE

Inflow Area = 0.156 ac, 56.28% Impervious, Inflow Depth > 5.46" for 100-yr event
Inflow = 0.93 cfs @ 12.10 hrs, Volume= 0.071 af
Outflow = 0.89 cfs @ 12.10 hrs, Volume= 0.065 af, Atten= 4%, Lag= 0.0 min
Primary = 0.89 cfs @ 12.10 hrs, Volume= 0.065 af

Routing by Dyn-Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.10 hrs / 3
Peak Elev= 75.47' @ 12.10 hrs Surf.Area= 0 sf Storage= 269 cf
Flood Elev= 75.62' Surf.Area= 0 sf Storage= 269 cf

Plug-Flow detention time= 63.8 min calculated for 0.065 af (91% of inflow)
Center-of-Mass det. time= 21.0 min (829.4 - 808.4)

Volume	Invert	Avail.Storage	Storage Description
#1	71.12'	269 cf	**42.0" Round Pipe Storage** L= 28.0'

Device	Routing	Invert	Outlet Devices
#1	Primary	74.95'	**10.0" Round Culvert** L= 4.0' CPP, square edge headwall, Ke= 0.500 Inlet / Outlet Invert= 74.95' / 74.50' S= 0.1125 '/' Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.55 sf

Primary OutFlow Max=0.88 cfs @ 12.10 hrs HW=75.47' TW=73.64' (Dynamic Tailwater)
1=Culvert (Inlet Controls 0.88 cfs @ 2.46 fps)

Pond 4P: PRETREAT PIPE



Summary for Pond 5P: MH1

Inflow Area = 1.056 ac, 77.83% Impervious, Inflow Depth > 6.74" for 100-yr event
Inflow = 7.11 cfs @ 12.10 hrs, Volume= 0.594 af
Outflow = 7.11 cfs @ 12.10 hrs, Volume= 0.594 af, Atten= 0%, Lag= 0.0 min
Primary = 2.17 cfs @ 12.09 hrs, Volume= 0.451 af
Secondary = 4.94 cfs @ 12.11 hrs, Volume= 0.143 af

Routing by Dyn-Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.10 hrs / 3
Peak Elev= 78.29' @ 12.10 hrs
Flood Elev= 80.50'

Device	Routing	Invert	Outlet Devices
#1	Primary	75.20'	**8.0" Round Culvert** L= 9.0' CPP, square edge headwall, Ke= 0.500 Inlet / Outlet Invert= 75.20' / 75.03' S= 0.0189 '/' Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.35 sf
#2	Secondary	76.08'	**12.0" Round Culvert** L= 21.0' CPP, square edge headwall, Ke= 0.500 Inlet / Outlet Invert= 76.08' / 74.90' S= 0.0562 '/' Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.79 sf

Primary OutFlow Max=1.87 cfs @ 12.09 hrs HW=78.15' TW=76.92' (Dynamic Tailwater)
└**1=Culvert** (Inlet Controls 1.87 cfs @ 5.35 fps)

Secondary OutFlow Max=4.87 cfs @ 12.11 hrs HW=78.24' TW=72.15' (Dynamic Tailwater)
└**2=Culvert** (Inlet Controls 4.87 cfs @ 6.20 fps)

Pond 5P: MH1



Summary for Pond 6P: BIO (NW)

Inflow Area = 0.295 ac, 59.02% Impervious, Inflow Depth > 5.57" for 100-yr event
Inflow = 1.78 cfs @ 12.10 hrs, Volume= 0.137 af
Outflow = 1.63 cfs @ 12.13 hrs, Volume= 0.127 af, Atten= 8%, Lag= 1.7 min
Primary = 1.63 cfs @ 12.13 hrs, Volume= 0.127 af

Routing by Dyn-Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.10 hrs / 3
Peak Elev= 80.75' @ 12.13 hrs Surf.Area= 994 sf Storage= 643 cf
Flood Elev= 81.00' Surf.Area= 1,085 sf Storage= 903 cf

Plug-Flow detention time= 57.1 min calculated for 0.127 af (93% of inflow)
Center-of-Mass det. time= 20.9 min (827.1 - 806.2)

Volume	Invert	Avail.Storage	Storage Description
#1	80.00'	903 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
80.00	720	0	0
81.00	1,085	903	903

Device	Routing	Invert	Outlet Devices
#1	Primary	76.50'	**6.0" Round Culvert** L= 14.0' CPP, square edge headwall, Ke= 0.500 Inlet / Outlet Invert= 76.50' / 76.25' S= 0.0179 '/' Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.20 sf
#2	Device 1	80.50'	**12.0" x 12.0" Horiz. Orifice/Grate** C= 0.600 Limited to weir flow at low heads

Primary OutFlow Max=1.55 cfs @ 12.13 hrs HW=80.74' TW=76.37' (Dynamic Tailwater)
↑**1=Culvert** (Passes 1.55 cfs of 1.89 cfs potential flow)
↑**2=Orifice/Grate** (Weir Controls 1.55 cfs @ 1.61 fps)

Pond 6P: BIO (NW)



Summary for Pond 7P: CB1

Inflow Area = 0.536 ac, 74.33% Impervious, Inflow Depth > 6.40" for 100-yr event
Inflow = 3.46 cfs @ 12.11 hrs, Volume= 0.286 af
Outflow = 3.46 cfs @ 12.11 hrs, Volume= 0.286 af, Atten= 0%, Lag= 0.0 min
Primary = 0.59 cfs @ 12.11 hrs, Volume= 0.199 af
Secondary = 2.87 cfs @ 12.11 hrs, Volume= 0.087 af

Routing by Dyn-Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.10 hrs / 3
Peak Elev= 77.96' @ 12.11 hrs
Flood Elev= 80.50'

Device	Routing	Invert	Outlet Devices
#1	Primary	76.50'	**6.0" Round Culvert** L= 187.5' CPP, square edge headwall, Ke= 0.500 Inlet / Outlet Invert= 76.50' / 75.20' S= 0.0069 '/' Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.20 sf
#2	Secondary	77.05'	**15.0" Round Culvert** L= 65.0' CPP, square edge headwall, Ke= 0.500 Inlet / Outlet Invert= 77.05' / 76.55' S= 0.0077 '/' Cc= 0.900 n= 0.012 Corrugated PP, smooth interior, Flow Area= 1.23 sf

Primary OutFlow Max=0.58 cfs @ 12.11 hrs HW=77.94' TW=75.66' (Dynamic Tailwater)
└**1=Culvert** (Barrel Controls 0.58 cfs @ 2.97 fps)

Secondary OutFlow Max=2.76 cfs @ 12.11 hrs HW=77.94' TW=76.37' (Dynamic Tailwater)
└**2=Culvert** (Barrel Controls 2.76 cfs @ 4.13 fps)

Pond 7P: CB1



Summary for Pond 8P: PIPE INFILTRATORS

Inflow Area = 1.593 ac, 76.65% Impervious, Inflow Depth > 4.83" for 100-yr event
Inflow = 2.76 cfs @ 12.09 hrs, Volume= 0.641 af
Outflow = 2.40 cfs @ 12.15 hrs, Volume= 0.505 af, Atten= 13%, Lag= 3.8 min
Discarded = 0.11 cfs @ 11.07 hrs, Volume= 0.129 af
Primary = 2.37 cfs @ 12.15 hrs, Volume= 0.376 af

Routing by Dyn-Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.10 hrs / 3
Peak Elev= 75.14' @ 12.15 hrs Surf.Area= 752 sf Storage= 7,081 cf
Flood Elev= 75.25' Surf.Area= 0 sf Storage= 7,138 cf

Plug-Flow detention time= 148.8 min calculated for 0.505 af (79% of inflow)
Center-of-Mass det. time= 58.7 min (860.9 - 802.2)

Volume	Invert	Avail.Storage	Storage Description
#1	71.25'	7,138 cf	**48.0" Round Pipe Storage** x 4 L= 142.0'

Device	Routing	Invert	Outlet Devices
#1	Discarded	71.25'	**2.000 in/hr Exfiltration over Surface area**
#2	Primary	74.25'	**12.0" Round Culvert** L= 35.0' CPP, square edge headwall, Ke= 0.500 Inlet / Outlet Invert= 74.25' / 73.00' S= 0.0357 '/' Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.79 sf

Discarded OutFlow Max=0.11 cfs @ 11.07 hrs HW=73.25' (Free Discharge)
↑**1=Exfiltration** (Exfiltration Controls 0.11 cfs)

Primary OutFlow Max=2.32 cfs @ 12.15 hrs HW=75.13' TW=72.38' (Dynamic Tailwater)
↑**2=Culvert** (Inlet Controls 2.32 cfs @ 3.19 fps)

Pond 8P: PIPE INFILTRATORS



Summary for Pond 9P: MH3

Inflow Area = 0.295 ac, 59.02% Impervious, Inflow Depth > 8.75" for 100-yr event
Inflow = 4.50 cfs @ 12.12 hrs, Volume= 0.215 af
Outflow = 4.50 cfs @ 12.12 hrs, Volume= 0.215 af, Atten= 0%, Lag= 0.0 min
Primary = 4.50 cfs @ 12.12 hrs, Volume= 0.215 af

Routing by Dyn-Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.10 hrs / 3
Peak Elev= 76.40' @ 12.14 hrs
Flood Elev= 83.00'

Device	Routing	Invert	Outlet Devices
#1	Primary	75.25'	**24.0" Round Culvert** L= 264.0' CPP, square edge headwall, Ke= 0.500 Inlet / Outlet Invert= 75.25' / 74.50' S= 0.0028 '/' Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 3.14 sf

Primary OutFlow Max=4.43 cfs @ 12.12 hrs HW=76.37' TW=75.03' (Dynamic Tailwater)
1=Culvert (Barrel Controls 4.43 cfs @ 3.52 fps)

Pond 9P: MH3



Summary for Pond 10P: PIPE DETENTION

Inflow Area = 0.295 ac, 59.02% Impervious, Inflow Depth > 8.75" for 100-yr event
Inflow = 4.50 cfs @ 12.12 hrs, Volume= 0.215 af
Outflow = 1.61 cfs @ 12.37 hrs, Volume= 0.214 af, Atten= 64%, Lag= 15.4 min
Primary = 1.61 cfs @ 12.37 hrs, Volume= 0.214 af

Routing by Dyn-Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.10 hrs / 3
Peak Elev= 76.19' @ 12.38 hrs Surf.Area= 798 sf Storage= 3,412 cf
Flood Elev= 76.55' Surf.Area= 0 sf Storage= 3,608 cf

Plug-Flow detention time= 34.5 min calculated for 0.214 af (100% of inflow)
Center-of-Mass det. time= 32.3 min (819.1 - 786.8)

Volume	Invert	Avail.Storage	Storage Description
#1	73.05'	3,608 cf	**42.0" Round Pipe Storage** x 3 L= 125.0'

Device	Routing	Invert	Outlet Devices
#1	Primary	73.05'	**6.0" Round Culvert** L= 11.0' CPP, square edge headwall, Ke= 0.500 Inlet / Outlet Invert= 73.05' / 73.00' S= 0.0045 '/' Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.20 sf

Primary OutFlow Max=1.60 cfs @ 12.37 hrs HW=76.17' TW=73.14' (Dynamic Tailwater)
↑**1=Culvert** (Inlet Controls 1.60 cfs @ 8.15 fps)

Pond 10P: PIPE DETENTION



Summary for Pond 11P: PRETREAT PIPE

Inflow Area = 0.536 ac, 74.33% Impervious, Inflow Depth > 4.44" for 100-yr event
Inflow = 0.59 cfs @ 12.11 hrs, Volume= 0.199 af
Outflow = 0.59 cfs @ 12.12 hrs, Volume= 0.190 af, Atten= 0%, Lag= 0.3 min
Primary = 0.59 cfs @ 12.12 hrs, Volume= 0.190 af

Routing by Dyn-Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.10 hrs / 3
Peak Elev= 75.66' @ 12.12 hrs Surf.Area= 32 sf Storage= 403 cf
Flood Elev= 75.70' Surf.Area= 0 sf Storage= 404 cf

Plug-Flow detention time= 42.4 min calculated for 0.189 af (95% of inflow)
Center-of-Mass det. time= 18.3 min (836.8 - 818.5)

Volume	Invert	Avail.Storage	Storage Description
#1	72.20'	404 cf	**42.0" Round Pipe Storage** L= 42.0'

Device	Routing	Invert	Outlet Devices
#1	Primary	75.20'	**8.0" Round Culvert** L= 14.0' CPP, square edge headwall, Ke= 0.500 Inlet / Outlet Invert= 75.20' / 74.58' S= 0.0443 '/' Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.35 sf

Primary OutFlow Max=0.58 cfs @ 12.12 hrs HW=75.65' TW=75.13' (Dynamic Tailwater)
1=Culvert (Inlet Controls 0.58 cfs @ 2.30 fps)

Pond 11P: PRETREAT PIPE



This Page Intentionally Left Blank

APPENDIX F:
SWPPP INSPECTION REPORT
(SAMPLE FORM)

LaBella
Powered by partnership.

This Page Intentionally Left Blank

Prepared by:
LaBella Associates
21 Fox Street
Poughkeepsie, NY 12601
(845) 454-3980

SWPPP INSPECTION REPORT NUMBER XX
ARGO DEVELOPMENT
SOUTH AVE MULTI-FAMILY DEVELOPMENT
SOUTH AVE, CITY OF POUGHKEEPSIE, DUTCHESS COUNTY, NY



Performed: 9/29/2021 @ 12:00 AM
Report Issued: 9/29/2021

Status: POTENTIAL CLEAN WATER ACT VIOLATION (Contractor must begin repairs within one (1) business day. Overdue corrective actions may result in fines from the NYSDEC in the amount of $37,500/day/violation)

Qualified Inspector (name and title)	Qualified Professional (name and title)
Date	Date
Signature	Signature

NYSDEC Documentation and SWPPP Forms

NYSDEC Issued Permit Identification Number: NYRXXXXXX

5-Acre Waiver: N/A (No 5-acre waiver for this project - Contractor not authorized to disturb >5 acres)

303d Status: Project does not directly discharge to a 303d impaired waterbody

Number of Inspections required: 1 / week

Location of SWPPP and Site Log Book on-site:

YES	NO	N/A	CONTAINED IN SITE LOG BOOK?
☐	☐	☐	Preconstruction Assessment
☐	☐	☐	NOI Acknowledgement letter
☐	☐	☐	Copy of eNOI
☐	☐	☐	Owner / Operator Certification
☐	☐	☐	SWPPP Preparer Certification
☐	☐	☐	MS4 SWPPP Acceptance Form
☐	☐	☐	Contractor and Subcontractor Certifications
☐	☐	☐	SPDES General Permit
☐	☐	☐	5 Acre Waiver
☐	☐	☐	NOT

Comments:

Site Conditions

Approximate Disturbed Area at Time of Inspection: XX Acres			
Allowable Disturbed Area Per NOI and/or 5-acre waiver: XX Acres			
Current Status of Construction: Description			
Weather Conditions: Conditions		**Temperature:** XX ºF	**Soil Conditions:** Choose an item.

Description of Discharge Point/Natural Surface Waterbody	Condition of Runoff	Sediment Discharge Noted Y / N	Corrective Action

Erosion and Sediment Control Deficiencies and Corrective Actions

SWPPP Component	Functional Y / N / NA	Deficiency (See Checklist and/or note)	Deficiency Location	Initial Date	Corrective Action	Corrected Y / N
General Site Conditions						
Silt Fence						
Stabilized Construction Access						
Compost Filter Sock						
Inlet Protection						
Soil Stockpiles						
Temporary Stabilization						
Permanent Stabilization						
Dewatering Operations						
Stone Check Dams						
Rock Outlet Protection						
Sediment Traps and Basins						
Temporary Stream Crossing						
Pavement Sweeping						
Concrete Washout						
Filter Strips						
Slope Protection Measures						
Temporary Swales and Berms						
Temporary Parking Areas						
Fiber Roll						
Permanent Turf Reinforcement						
Water Bars						
Flow Diffusers						
Other:						

SWPPP Inspection Checklist and Deficiency Numbers

1	General Site Conditions
1A	Adjoining properties are not protected from erosion and sediment deposition
1B	Downstream waterways are not protected from erosion and sediment deposition
1C	All E&SC measures have not been constructed as detailed in the SWPPP
1D	Dust is not adequately controlled
1E	Storage areas contain spills, leaks, or harmful materials
1F	Garbage and waste building materials are not being managed properly
1G	Temporary control measures that are no longer needed have not been removed
1H	Permanent SWM practices not constructed per plans

2	Silt Fence
2A	Silt fence not installed on contour
2B	Silt fence not across conveyance channels
2C	Silt fence not at least 10 feet from toe of slope
2D	Silt fence not at appropriate spacing intervals based on slope
2E	Silt fence ends are not wrapped for continuous support
2F	Silt fence fabric is loose or contains rips or frayed areas
2G	Silt fence posts are unstable
2H	Silt fence is not buried 6 inches minimum
2I	Silt fence contains bulges or material buildup

3	Stabilized Construction Access
3A	Temporary construction access not installed or not per NYS standards
3B	Other access areas have not been stabilized immediately as work takes place
3C	Sediment has tracked onto public streets and is not being cleaned daily
3D	Stone is not clean enough to effectively remove mud from vehicles
3E	Adequate drainage not provided to prevent ponding

4	Compost Filter Sock
4A	Filter sock not installed on contour
4B	Filter sock terminal ends do not extended 8' upslope at 45˚ angle
4C	Inappropriate diameter based on slope steepness and slope length
4D	Filter sock not anchored at 10' intervals
4E	More than 50% sediment has built up

5	Inlet Protection
5A	Inlet protection not installed or installation is not per SWPPP or Blue Book specifications
5B	Incorrect type(s) of inlet control installed or is inappropriate for location
5C	Drainage area for inlet protection is greater than 1 acre
5D	Sediment has not been removed when 50% of storage volume has been achieved
5E	A 2" x 4" wood frame and wood posts has not been installed
5F	Filter fabric is not buried a minimum of 1 foot below ground or secured to frame/posts
5G	Posts are unstable, fabric is loose, and contains rips or frayed areas
5H	Post spacing exceeds maximum 3' spacing

6	Soil Stockpiles
6A	No sediment controls at downhill slope

7	Temporary Stabilization
7A	Areas inactive for 14 days or more have not been stabilized (If <5 acres disturbed)
7B	Areas inactive for 7 days or more have not been stabilized (If >5 acres disturbed or 303d)
7C	Soil preparation has not been applied as specified in the SWPPP or the Blue Book
7D	Rolled EC products specified for steep slopes or channels have not been installed

8	Permanent Stabilization
8A	Lawn in disturbed areas has not been established to 80% germination
8B	Soil preparation has not been applied as specified in the SWPPP or the Blue Book
8C	Rolled EC products specified for steep slopes or channels have not been installed

9	Dewatering Operations
9A	Upstream and downstream berms are not installed or functioning poorly
9B	Clean water from upstream pool is not being pumped to the downstream pool
9C	Sediment laden water from work area is not being discharged to a silt-trapping device
9D	Groundwater from excavations managed improperly (No sumps/sediment control)

10	Stone Check Dam
10A	Not installed per standards
10B	Channel is unstable (flow is eroding soil underneath or around the structure)
10C	Check dam in poor condition (rocks not in place or lack of geotextile fabric)
10D	Sediment needs to be removed

11	Rock Outlet Protection
11A	Rock outlet protection not installed per plan or Blue Book
11B	Rock outlet protection not installed concurrently with pipe installation

12	Sediment Traps and Basins
12A	Outlet structure constructed improperly
12B	Geotextile fabric has not been placed beneath rock fill
12C	Depth of sediment in basin has exceeded allowable threshold
12D	Basin and outlet structure not constructed per the approved plan
12E	Basin side slopes are not stabilized with seed/mulch
12F	More than 50% capacity has built up

13	Temporary Stream Crossing
13A	Construction crossings at concentrated flow areas have not been culverted

14	Pavement Sweeping
14A	Pavement has not been swept daily and sediment has traveled into road

Stormwater Management Practice Deficiencies and Corrective Actions

Practice	Sign Y / N	Current Phase of Construction	Items Not in Conformance with SWPPP	Deficiency Location	Initial Date	Corrective Action	Corrected Y / N
Practice 1:							
Practice 2:							
Practice 3:							
Practice 4:							
Practice 5:							
Practice 6:							

Photo Log

Photo 1 *Date – Item in need of repair or maintenance:*	***Photo 1A*** *Date – Corrected Action:*
Photo 2 *Date – Item in need of repair or maintenance:*	***Photo 2A*** *Date – Corrected Action:*
Photo 3 *Date – Item in need of repair or maintenance:*	***Photo 3A*** *Date – Corrected Action:*

Photo Log (continued)

Photo 4	***Photo 4A***
Date – Item in need of repair or maintenance:	*Date – Corrected Action:*
Photo 5	***Photo 5A***
Date – Item in need of repair or maintenance:	*Date – Corrected Action:*
Photo 6	***Photo 6A***
Date – Item in need of repair or maintenance:	*Date – Corrected Action:*

Disturbance / Photo Location Map

Replace this page to include an 11x17 erosion control plan sketch to scale showing:

1. Areas with active soil disturbance activity
2. Areas that have been disturbed but are inactive at the time of the inspection
3. Areas that have been stabilized (temporary and/or final) since the last inspection
4. Limit of disturbance line per the SWPPP and the grading plan
5. Photo locations

Use Bluebeam template with standard colors to indicate limits

APPENDIX G:
POST-CONSTRUCTION INSPECTIONS AND MAINTENANCE

LaBella
Powered by partnership.

This Page Intentionally Left Blank

POST CONSTRUCTION INSPECTIONS AND MAINTENANCE

1. SITE COVER

a. Inspections

Site cover and associated structures and embankments should be inspected periodically for the first few months following construction and then on a biannual basis. Site inspections should also be performed following all major storm events. Items to check for include (but are not limited to):

i. Differential settlement of embankments, cracking or erosion.

ii. Lack of vigor and density of grass turf.

iii. Accumulation of sediments or litter on lawn areas, paved areas, or within catch basin sumps.

iv. Accumulation of pollutants, including oils or grease, in catch basin sumps.

v. Damage or fatigue of storm sewer structures or associated components.

b. Mowing and Sweeping

Vegetated areas and landscaping should be maintained to promote vigorous and dense growth. Lawn areas should be mowed at least three times a year (more frequent mowing may be desired for aesthetic reasons). Resultant yard waste shall be collected and disposed of off-site.

Paved areas should be swept at least twice a year. Additional sweeping may be appropriate in the early spring for removal of deicing materials

c. Debris and Litter Removal

Accumulation of litter and debris should be removed during each mowing or sweep operation.

d. Structural Repair or Replacement

Components of the system which require repair or replacement should be addressed immediately following identification.

e. Catch Basins

The frequency for cleanout of catch basin sumps will depend on the efficiency of mowing, sweeping, and debris and litter removal. Sumps should be cleaned when accumulation of sediments are within six inches of the catch basin outlet pipe.

Disposal of material from catch basins sumps, drainage manholes, and trench drains shall be in accordance with local, state, and federal guidelines.

f. Rip-rap Dissipation structures

Riprap used to dissipate energy from pipe outfalls shall be cleaned or replaced when it becomes overburdened with silt or sediment.

g. Winter Maintenance

To prevent impacts to storm water management facilities, the following winter maintenance limitations, restrictions, or requirements are recommended:

i. Remove snow and ice from inlet structures, basin inlet and outlet structures and away from culvert end sections.

ii. Snow removed from paved areas should not be piled at inlets/outlets of the storm water management basin.

iii. Use of deicing materials should be limited to sand and "environmentally friendly" chemical products. Use of salt mixtures should be kept to a minimum.

iv. Sand used for deicing should be clean, course material free of fines, silt, and clay.

v. Materials used for deicing should be removed during the early spring by sweeping and/ or vacuuming.

2. BIORETENTION FILTERS

a. Inspection Schedule

Bioretention filters should be inspected periodically for the first few months after construction and then on a monthly basis. Bioretention filters should be inspected after all major storm events.

b. Inspection of Uphill Drainage Area

Inspect areas that are uphill from the Bioretention filter.

i. Bare soil and/or erosion of the ground should be seeded and mulches to establish vegetation. Areas of erosion should be filled with soil, compacted, and seeded and strawed to establish vegetation.

ii. If a small channel(s) is forming, try to redirect water flowing to this area by creating a small berm or adding topsoil to areas that are heavily compacted.

iii. Piles of grass clippings, mulch, dirt, salt or other materials should be removed.

iv. Open containers of oil, grease, paint, or other substances should be covered and properly disposed of.

c. Inspection of Inlets

Stand in the Bioretention filter itself and inspect each location where water flows in.

i. Inlets should have a clear pathway for water to flow into the filter. Grit and debris or grass/weeds should be removed at curb inlets or openings.

ii. Clumps of growing grass or weeds and the associated soil or grit should be removed.

iii. Grass clippings, leaves, sticks, and other debris collecting at inlets should be removed.

iv. For pipes and ditches, sediment and debris partially blocking the pipe or ditch opening into the Bioretention filter should be removed.

v. All materials removed should be properly disposed in such a way that it may not re-enter the Bioretention filter.

vi. Small areas of erosion should be smoothed out and rock or stone applied to prevent further erosion. Reseeding and applying erosion-control matting can be used to prevent further erosion.

d. Inspection of Ponding Area

Examine the entire Bioretention surface and side slopes:

i. In areas where the mulch layer has decomposed or is less than 1-inch thick, new mulch should be added to a total depth of 2 to 3 inches. The mulch should be a shredded hardwood mulch that is less likely to float away during rainstorms. Avoid adding too much mulch so that inlets are obstructed, or certain areas become higher than the rest of the Bioretention surface.

ii. Excess sediment, grit, trash, or other debris that has accumulated on the bottom should be removed and disposed of in such a way that it cannot re-enter the Bioretention filter. If removing the material creates a hole or low area, fill in with a soil mix that matches the original mix and cover with mulch to create a flat surface.

iii. Eroded areas in the bottom or on the side slopes should be filled with clean topsoil or sand and covered with mulch. If the problem reoccurs, stone can be used to fill in the areas. If the erosion is on a side slope, fill in with clay that can be compacted and seed and mulch the area.

iv. The bottom of the Bioretention filter should be flat. The surface should be raked or mulch added to low spots to create a more level surface.

e. Inspection of Vegetation

Examine all Bioretention filter vegetation:

i. Weeds and dead and/or diseased plants should be removed and the mulch surrounding these replaced. Plants should be added to fill in areas that are not well vegetated.

ii. If bioretention filter utilized a vegetated seed mix, then grass areas shall be mowed to ensure that grass height does not exceed 6-inches.

iii. Undesirable trees and shrubs should be removed. Resultant yard wastes shall be collected and disposed of off-site

f. Inspection of Outlets

Examine the outlets that release water out of the Bioretention filter:

i. Stone should be added in areas of erosion at the outlet to reduce the impact from the water flowing out of the outlet pipe or weir during storms.

ii. Outlet obstructions should be removed and disposed of where it cannot re-enter the Bioretention filter.

g. Debris, Trash and Litter Control

Removal of debris and litter shall be accomplished during mowing operations. Inlet structures should be cleared of all debris and litter.

h. Structural Repairs and Replacement

Components of the bioretention filter, which require repair or replacement, should be addressed immediately following identification. This includes treating and or replacing diseased trees and shrub, fertilizing as necessary, replacing tree stakes and wires, replacing mulch where bare spots appear, replacing clogged underdrains, filter beds, and pea gravel diaphragm.

i. Erosion and Sediment Control

Sources of sedimentation, specifically eroded areas in upland drainage areas, should be stabilized immediately upon identification. Stabilization should be with vegetative practices or other erosion control practices when vegetative measures do not prove effective.

Soil slumpage, erosion of the embankments or around inlets/outlets, and cracking should be stabilized and repaired immediately upon identification.

j. Sediment Removal

Sediments that accumulate in the bioretention filter should be removed annually to prevent clogging of inlet or outlet structures. Disposal of material removed from bioretention filter shall be in accordance with local, state, and federal guidelines.

3. UNDERGROUND INFILTRATION SYSTEM

a. Inspection Schedule

Underground infiltration systems should be inspected periodically for the first few months after construction and then on an annual basis. Underground infiltration systems should be inspected after major storm events to ensure inlets and outlets remain clear.

b. Inspection Items

Items to check for include (but are not limited to):

i. Measure the sediment buildup at each riser.

ii. Inspect each header, all laterals, inlets, and outlet pipes for sediment build up, obstructions or other problems. Cracking, erosion or seepage through embankments.

c. Debris and Litter Control

Inlet and outlet structures should be cleared of all debris and litter.

d. Structural repairs and Replacement

Components of the underground infiltration system, which require repair or replacement, should be addressed immediately following identification.

e. Sedimentation Control

Sources of sedimentation, specifically eroded areas in upland drainage areas, should be stabilized immediately upon identification. Stabilization should be with vegetative practices or other erosion control practices when vegetative measures do not prove effective.

f. Sediment removal

Sediments, which accumulate in the underground infiltration system, should be removed when it reaches 4% of the pipe diameter to prevent clogging of the outlet. A typical clean-out cycle should be between 5 to 10 years with more frequent cleanings near inlet and outlet structures. The unit may require cleaning in the event of a spill of a toxic or foreign substance. Disposal of material from the underground infiltration systems shall be in accordance with local, state, and federal guidelines.

Underground infiltration systems are confined space environment and only properly trained personnel possessing the necessary safety equipment should enter the systems to perform maintenance or inspection.

4. HYDRODYNAMIC DEVICE

The hydrodynamic device is a confined space environment and only properly trained personnel possessing the necessary safety equipment should enter the unit to perform maintenance or inspection.

a. Inspection Schedule

The hydrodynamic device shall be inspected every four months.

b. Inspection Items

The unit's internal components should be inspected for any signs of damage or any loosening of the bolts used to fasten the various components to the manhole structure and to each other.

Refer to attached Operations and Maintenance Guidelines, for the CS-4 Cascade Hydrodynamic Device, and CDS Guide Operation, Design, Performance and Maintenance Manual for the manufacturer's detailed inspection and maintenance requirements.

c. Debris, Trash and Litter Control

The screen shall be power washed for the inspection. The floatables shall be removed and the sump cleaned when it has reached 50% capacity. The unit may require cleaning in the event of a spill of a toxic or foreign substance. At a minimum, the hydrodynamic device shall be pumped out at least once a year if the sump does not reach its 50% capacity.

d. Sediment removal

Disposal of material from the hydrodynamic device shall be in accordance with local, state, and federal guidelines.

5. SURFACE DETENTION BASINS

a. Inspection Schedule

Detention Basins should be inspected periodically for the first few months after construction and then on an annual basis. Detention Basins should be inspected after major storm events to ensure inlets and outlets remain clear.

b. Inspection Items

Items to check for include (but are not limited to):

i. Differential settlement of embankments.

ii. Cracking, erosion, or seepage through embankments.

iii. Evidence of clogging at inlets or outlets.

iv. Erosion of the flow path through the detention basin.

v. Brush, shrub, or tree growth on embankments.

vi. Condition of the overflow spillway.

vii. Lack of vigor and density of grass turf on the basin embankments.

c. Mowing

The side slopes, embankments, inlets, and overflow spillways of the detention basins should be mowed at least three times a year and resultant yard wastes collected and disposed of off-site.

d. Debris and Litter Control

Removal of debris and litter should be accomplished during mowing operations. Inlet and outlet structures should be cleared of all debris and litter.

e. Structural repairs and Replacement

Components of the detention basin, which require repair or replacement, should be addressed immediately following identification.

f. Erosion Control

Sources of sedimentation, specifically eroded areas in upland drainage areas, should be stabilized immediately upon identification. Stabilization should be with vegetative practices or other erosion control practices when vegetative measures do not prove effective.

Soil slumpage, erosion of the basin embankment or around inlets/outlets, and cracking should be stabilized and repaired immediately upon identification. Repair, replacement, or addition of rip-rap aprons, channels or embankments should be pursued as required.

g. Sediment removal

Sediments, which accumulate in the detention basin, should be removed periodically to prevent clogging of inlet or outlet structures. A typical clean-out cycle should be between 5 to 10 years with more frequent cleanings near inlet and outlet structures.

APPENDIX H:
NYSDEC "DEEP-RIPPING AND DECOMPACTION," APRIL 2008

LaBella
Powered by partnership.

This Page Intentionally Left Blank

New York State
DEPARTMENT OF ENVIRONMENTAL CONSERVATION

Division of Water

Deep-Ripping and Decompaction

April 2008

Document Prepared by:

John E. Lacey,
Land Resource Consultant and Environmental Compliance Monitor
(Formerly with the Division of Agricultural Protection and Development Services,
NYS Dept. of Agriculture & Markets)

New York State
Department of Environmental Conservation

Alternative Stormwater Management
Deep-Ripping and Decompaction

Description

The two-phase practice of 1) “Deep Ripping;” and 2) “Decompaction” (deep subsoiling), of the soil material as a step in the cleanup and restoration/landscaping of a construction site, helps mitigate the physically induced impacts of soil compression; i.e.: soil compaction or the substantial increase in the bulk density of the soil material.

Deep Ripping and Decompaction are key factors which help in restoring soil pore space and permeability for water infiltration. Conversely, the physical actions of cut-and-fill work, land grading, the ongoing movement of construction equipment and the transport of building materials throughout a site alter the architecture and structure of the soil, resulting in: the mixing of layers (horizons) of soil materials, compression of those materials and diminished soil porosity which, if left unchecked, severely impairs the soil’s water holding capacity and vertical drainage (rainfall infiltration), from the surface downward.

In a humid climate region, compaction damage on a site is virtually guaranteed over the duration of a project. Soil in very moist to wet condition when compacted, will have severely reduced permeability. Figure 1 displays the early stage of the deep-ripping phase (Note that all topsoil was stripped prior to construction access, and it remains stockpiled until the next phase – decompaction – is complete). A heavy-duty tractor is pulling a three-shank ripper on the first of several series of incrementally deepening passes through the construction access corridor's densely compressed subsoil material. Figure 2 illustrates the approximate volumetric composition of a loam surface soil when conditions are good for plant growth, with adequate natural pore space for fluctuating moisture conditions.

Fig. 1. A typical deep ripping phase of this practice, during the first in a series of progressively deeper “rips” through severely compressed subsoil.



Fig. 2. About 50% of the volume of undisturbed loam surface soil is pore space, when soil is in good condition for plant growth. Brady, 2002.

Recommended Application of Practice

The objective of Deep Ripping and Decompaction is to effectively fracture (vertically and laterallly) through the thickness of the physically compressed subsoil material (see Figure 3), restoring soil porosity and permeability and aiding infiltration to help reduce runoff. Together with topsoil stripping, the “two-phase” practice of Deep Ripping and Decompaction first became established as a “best management practice” through ongoing success on commercial farmlands affected by heavy utility construction right-of-way projects (transmission pipelines and large power lines).

Fig. 3. Construction site with significant compaction of the deep basal till subsoil extends 24 inches below this exposed cut-and-fill work surface.

Soil permeability, soil drainage and cropland productivity were restored. For broader construction application, the two-phase practice of Deep Ripping and Decompaction is best adapted to areas impacted with significant soil compaction, on contiguous open portions of large construction sites and inside long, open construction corridors used as temporary access over the duration of construction. Each mitigation area should have minimal above-and-below-ground obstructions for the easy avoidance and maneuvering of a large tractor and ripping/decompacting implements. Conversely, the complete two-phase practice is not recommended in congested or obstructed areas due to the limitations on tractor and implement movement.

Benefits

Aggressive “deep ripping” through the compressed thickness of exposed subsoil before the replacement/respreading of the topsoil layer, followed by “decompaction,” i.e.: “sub-soiling,” through the restored topsoil layer down into the subsoil, offers the following benefits:

- Increases the project (larger size) area’s direct surface infiltration of rainfall by providing the open site’s mitigated soil condition and lowers the demand on concentrated runoff control structures
- Enhances direct groundwater recharge through greater dispersion across and through a broader surface than afforded by some runoff-control structural measures
- Decreases runoff volume generated and provides hydrologic source control
- May be planned for application in feasible open locations either alone or in

conjunction with plans for structural practices (e.g., subsurface drain line or infiltration basin) serving the same or contiguous areas

- Promotes successful long-term revegetation by restoring soil permeability, drainage and water holding capacity for healthy (rather than restricted) root-system development of trees, shrubs and deep rooted ground cover, minimizing plant drowning during wet periods and burnout during dry periods.

Feasibility/Limitations

The effectiveness of Deep Ripping and Decompaction is governed mostly by site factors such as: the original (undisturbed) soil's hydrologic characteristics; the general slope; local weather/timing (soil moisture) for implementation; the space-related freedom of equipment/implement maneuverability (noted above in **Recommended Application of Practice**), and by the proper selection and operation of tractor and implements (explained below in **Design Guidance**). The more notable site-related factors include:

Soil
In the undisturbed condition, each identified soil type comprising a site is grouped into one of four categories of soil hydrology, Hydrologic Soil Group A, B, C or D, determined primarily by a range of characteristics including soil texture, drainage capability when thoroughly wet, and depth to water table. The natural rates of infiltration and transmission of soil-water through the undisturbed soil layers for Group A is "high" with a low runoff potential while soils in Group B are moderate in infiltration and the transmission of soil-water with a moderate runoff potential, depending somewhat on slope. Soils in Group C have slow rates of infiltration and transmission of soil-water and a moderately high runoff potential influenced by soil texture and slope; while soils in Group D have exceptionally slow rates of infiltration and transmission of soil-water, and high runoff potential.

In Figure 4, the profile displays the undisturbed horizons of a soil in Hydrologic Soil Group C and the naturally slow rate of infiltration through the subsoil. The slow rate of infiltration begins immediately below the topsoil horizon (30 cm), due to the limited amount of macro pores, e.g.: natural subsoil fractures, worm holes and root channels. Infiltration after the construction-induced mixing and compression of such subsoil material is virtually absent; but can be restored back to this natural level with the two-phase practice of deep ripping and decompaction, followed by the permanent establishment of an appropriate, deep taproot



Fig. 4. Profile (in centimeters) displaying the infiltration test result of the natural undisturbed horizons of a soil in Hydrologic Soil Group C.

lawn/ground cover to help maintain the restored subsoil structure. Infiltration after construction-induced mixing and compression of such subsoil material can be notably rehabilitated with the Deep Ripping and Decompaction practice, which prepares the site for the appropriate long-term lawn/ground cover mix including deep taproot plants such as clover, fescue or trefoil, etc. needed for all rehabilitated soils.

Generally, soils in Hydrologic Soil Groups A and B, which respectively may include deep, well-drained, sandy-gravelly materials or deep, moderately well-drained basal till materials, are among the easier ones to restore permeability and infiltration, by deep ripping and decompaction. Among the many different soils in Hydrologic Soil Group C are those unique glacial tills having a natural fragipan zone, beginning about 12 to 18 inches (30 – 45cm), below surface. Although soils in Hydrologic Soil Group C do require a somewhat more carefully applied level of the Deep Ripping and Decompaction practice, it can greatly benefit such affected areas by reducing the runoff and fostering infiltration to a level equal to that of pre-disturbance.

Soils in Hydrologic Soil Group D typically have a permanent high water table close to the surface, influenced by a clay or other highly impervious layer of material. In many locations with clay subsoil material, the bulk density is so naturally high that heavy trafficking has little or no added impact on infiltration; and structural runoff control practices rather than Deep Ripping and Decompaction should be considered.

The information about Hydrologic Soil Groups is merely a general guideline. Site-specific data such as limited depths of cut-and-fill grading with minimal removal or translocation of the inherent subsoil materials (as analyzed in the county soil survey) or, conversely, the excavation and translocation of deeper, unconsolidated substratum or consolidated bedrock materials (unlike the analyzed subsoil horizons' materials referred to in the county soil survey) should always be taken into account.

Sites made up with significant quantities of large rocks, or having a very shallow depth to bedrock, are not conducive to deep ripping and decompation (subsoiling); and other measures may be more practical.

Slope
The two-phase application of 1) deep ripping and 2) decompaction (deep subsoiling), is most practical on flat, gentle and moderate slopes. In some situations, such as but not limited to temporary construction access corridors, inclusion areas that are moderately steep along a project's otherwise gentle or moderate slope may also be deep ripped and decompacted. For limited instances of moderate steepness on other projects, however, the post-construction land use and the relative alignment of the potential ripping and decompaction work in relation to the lay of the slope should be reviewed for safety and practicality. In broad construction areas predominated by moderately steep or steep slopes, the practice is generally not used.

Local Weather/Timing/Soil Moisture
Effective fracturing of compressed subsoil material from the exposed work surface, laterally and vertically down through the affected zone is achieved only when the soil material is moderately dry to moderately moist. Neither one of the two-phases, deep ripping nor decompaction (deep

subsoiling), can be effectively conducted when the soil material (subsoil or replaced topsoil) is in either a “plastic” or “liquid” state of soil consistency. Pulling the respective implements legs through the soil when it is overly moist only results in the “slicing and smearing” of the material or added “squeezing and compression” instead of the necessary fracturing. Ample drying time is needed for a “rippable” soil condition not merely in the material close to the surface, but throughout the material located down to the bottom of the physically compressed zone of the subsoil.

The “poor man’s Atterberg field test” for soil plasticity is a simple “hand-roll” method used for quick, on-site determination of whether or not the moisture level of the affected soil material is low enough for: effective deep ripping of subsoil; respreading of topsoil in a friable state; and final decompaction (deep subsoiling). Using a sample of soil material obtained from the planned bottom depth of ripping, e.g.: 20 - 24 inches below exposed subsoil surface, the sample is hand rolled between the palms down to a 1/8-inch diameter thread. (Use the same test for stored topsoil material before respreading on the site.) If the respective soil sample crumbles apart in segments no greater than 3/8 of an inch long, by the time it is rolled down to 1/8 inch diameter, it is low enough in moisture for deep ripping (or topsoil replacement), and decompaction. Conversely, as shown in Figure 5, if the rolled sample stretches out in increments greater than 3/8 of an inch long before crumbling, it is in a “plastic” state of soil consistency and is too wet for subsoil ripping (as well as topsoil replacement) and final decompaction.

Fig. 5. Augered from a depth of 19 inches below the surface of the replaced topsoil, this subsoil sample was hand rolled to a 1/8-inch diameter. The test shows the soil at this site stretches out too far without crumbling; it indicates the material is in a plastic state of consistence, too wet for final decompaction (deep subsoiling) at this time.

Design Guidance

Beyond the above-noted site factors, a vital requirement for the effective Deep Ripping and Decompaction (deep subsoiling), is implementing the practice in its distinct, two-phase process:

1) Deep rip the affected thickness of exposed subsoil material (see Figure 10 and 11), aggressively fracturing it before the protected topsoil is reapplied on the site (see Figure 12); and

2) Decompact (deep subsoil), simultaneously through the restored topsoil layer and the upper half of the affected subsoil (Figure 13). The second phase, “decompaction,” mitigates the partial recompaction which occurs during the heavy process of topsoil spreading/grading. Prior to deep ripping and decompacting the site, all construction activity, including construction equipment and material storage, site cleanup and trafficking (Figure 14), should be finished; and the site closed off to further disturbance. Likewise, once the practice is underway and the area’s soil permeability and

rainfall infiltration are being restored, a policy limiting all further traffic to permanent travel lanes is maintained.

The other critical elements, outlined below, are: using the proper implements (deep, heavy-duty rippers and subsoilers), and ample pulling-power equipment (tractors); and conducting the practice at the appropriate speed, depth and pattern(s) of movement.

Note that an appropriate plan for the separate practice of establishing a healthy perennial ground cover, with deep rooting to help maintain the restored soil structure, should be developed in advance. This may require the assistance of an agronomist or landscape horticulturist.

Implements

Avoid the use of all undersize implements. The small-to-medium, light-duty tool will, at best, only “scarify” the uppermost surface portion of the mass of compacted subsoil material. The term “chisel plow” is commonly but incorrectly applied to a broad range of implements. While a few may be adapted for the moderate subsoiling of non-impacted soils, the majority are less durable and used for only lighter land-fitting (see Figure 6).

Fig. 6. A light duty chisel implement, not adequate for either the deep ripping or decompaction (deep subsoiling) phase.

Fig. 7. One of several variations of an agricultural ripper. This unit has long, rugged shanks mounted on a steel V-frame for deep, aggressive fracturing through Phase 1.

Use a “heavy duty” agricultural-grade, deep ripper (see Figures 7,9,10 and 11) for the first phase: the lateral and vertical fracturing of the mass of exposed and compressed subsoil, down and through, to the bottom of impact, prior to the replacement of the topsoil layer. (Any oversize rocks which are uplifted to the subsoil surface during the deep ripping phase are picked and removed.) Like the heavy-duty class of implement for the first phase, the decompaction (deep subsoiling) of Phase 2 is conducted with the heavy-duty version of the deep subsoiler. More preferable is the angled-leg variety of deep subsoiler (shown in Figures 8 and 13). It minimizes the inversion of the subsoil and topsoil layers while laterally and vertically fracturing the upper half of the previously ripped subsoil layer and all of the topsoil layer by delivering a momentary, wave-like “lifting and shattering” action up through the soil layers as it is pulled.

Pulling-Power of Equipment
Use the following rule of thumb for tractor horsepower (hp) whenever deep ripping and decompacting a significantly impacted site: For both types of implement, have at least 40 hp of tractor pull available for each mounted shank/ leg.

Using the examples of a 3-shank and a 5-shank implement, the respective tractors should have 120 and 200 hp available for fracturing down to the final depth of 20-to-24 inches per phase. Final depth for the deep ripping in Phase 1 is achieved incrementally by a progressive series of passes (see Depth and Patterns of Movement, below); while for Phase 2, the full operating depth of the deep subsoiler is applied from the beginning.

The operating speed for pulling both types of implement should not exceed 2 to 3 mph. At this slow and managed rate of operating speed, maximum functional performance is sustained by the tractor and the implement performing the soil fracturing. Referring to Figure 8, the implement is the 6-leg version of the deep angled-leg subsoiler. Its two outside legs are "chained up" so that only four legs will be engaged (at the maximum depth), requiring no less than 160 hp, (rather than 240 hp) of pull. The 4-wheel drive, articulated-frame tractor in Figure 8 is 174 hp. It will be decompacting this unobstructed, former construction access area simultaneously through 11 inches of replaced topsoil and the upper 12 inches of the previously deep-ripped subsoil. In constricted areas of Phase 1) Deep Ripping, a medium-size tractor with adequate hp, such as the one in Figure 9 pulling a 3-shank deep ripper, may be more maneuverable.

Fig. 8. A deep, angled-leg subsoiler, ideal for Phase 2 decompaction of after the topsoil layer is graded on top of the ripped subsoil.

Fig. 9. This medium tractor is pulling a 3-shank deep ripper. The severely compacted construction access corridor is narrow, and the 120 hp tractor is more maneuverable for Phase 1 deep ripping (subsoil fracturing), here.

Some industrial-grade variations of ripping implements are attached to power graders and bulldozers. Although highly durable, they are generally not recommended. Typically, the shanks or "teeth" of these rippers are too short and stout; and they are mounted too far apart to achieve the well-distributed type of lateral and vertical fracturing of the soil materials necessary to restore soil permeability and infiltration. In addition, the power graders and bulldozers, as pullers, are far less maneuverable for turns and patterns than the tractor.

Depth and Patterns of Movement
As previously noted both Phase 1 Deep Ripping through significantly compressed, exposed subsoil and Phase 2 Decompaction (deep subsoiling) through the replaced topsoil and upper subsoil need to be performed at maximum capable depth of each implement. With an implement's guide wheels attached, some have a "normal" maximum operating depth of 18 inches, while others may go deeper. In many situations, however, the tractor/implement operator must first remove the guide wheels and other non essential elements from the implement. This adapts the ripper or the deep subsoiler for skillful pulling with its frame only a few inches above surface, while the shanks or legs, fracture the soil material 20-to-24 inches deep.

There may be construction sites where the depth of the exposed subsoil's compression is moderate, e.g.: 12 inches, rather than deep. This can be verified by using a ¾ inch cone penetrometer and a shovel to test the subsoil for its level of compaction, incrementally, every three inches of increasing depth. Once the full thickness of the subsoil's compacted zone is finally "pieced" and there is a significant drop in the psi measurements of the soil penetrometer, the depth/thickness of compaction is determined. This is repeated at several representative locations of the construction site. If the thickness of the site's subsoil compaction is verified as, for example, ten inches, then the Phase 1 Deep Ripping can be correspondingly reduced to the implement's minimum operable depth of 12 inches. However, the Phase 2 simultaneous Decompation (subsoiling) of an 11 inch thick layer of replaced topsoil and the upper subsoil should run at the subsoiling implements full operating depth.

Fig. 10. An early pass with a 3-shank deep ripper penetrating only 8 inches into this worksite's severely compressed subsoil.

Fig. 11. A repeat run of the 3-shank ripper along the same patterned pass area as Fig. 9; here, incrementally reaching 18 of the needed 22 inches of subsoil fracture.

Typically, three separate series (patterns) are used for both the Phase 1 Deep Ripping and the Phase 2 Decompaction on significantly compacted sites. For Phase 1, each series begins with a moderate depth of rip and, by repeat-pass, continues until full depth is reached. Phase 2 applies the full depth of Decompation (subsoiling), from the beginning.

Every separate series (pattern) consists of parallel, forward-and-return runs, with each progressive

pass of the implement's legs or shanks evenly staggered between those from the previous pass. This compensates for the shank or leg-spacing on the implement, e.g., with 24-to-30 inches between each shank or leg. The staggered return pass ensures lateral and vertical fracturing actuated every 12 to 15 inches across the densely compressed soil mass.

Large, Unobstructed Areas
For larger easy areas, use the standard patterns of movement:

- The first series (pattern) of passes is applied lengthwise, parallel with the longest spread of the site; gradually progressing across the site's width, with each successive pass.

- The second series runs obliquely, crossing the first series at an angle of about 45 degrees.

- The third series runs at right angle (or 90 degrees), to the first series to complete the fracturing and shattering on severely compacted sites, and avoid leaving large unbroken blocks of compressed soil material. (In certain instances, the third series may be optional, depending on how thoroughly the first two series loosen the material and eliminate large chunks/blocks of material as verified by tests with a ¾-inch cone penetrometer.)

Fig. 12. Moderately dry topsoil is being replaced on the affected site now that Phase 1 deep ripping of the compressed subsoil is complete.

Fig. 13. The same deep, angled-leg subsoiler shown in Fig. 7 is engaged at maximum depth for Phase 2, decompaction (deep soiling), of the replaced topsoil and the upper subsoil materials.

Corridors
In long corridors of limited width and less maneuverability than larger sites, e.g.: along compacted areas used as temporary construction access, a modified series of pattern passes are used.

- First, apply the same initial lengthwise, parallel series of passes described above.

- A second series of passes makes a broad "S" shaped pattern of rips, continually and gradually alternating the "S" curves between opposite edges inside the compacted corridor.

- The third and final series again uses the broad, alternating S pattern, but it is "flip-flopped" to continually cross the previous S pattern along the corridor's centerline. This final series of the S pattern curves back along the edge areas skipped by the second series.

Maintenance and Cost

Once the two-phase practice of Deep Ripping and Decompation is completed, two items are essential for maintaining a site's soil porosity and permeability for infiltration. They are: planting and maintaining the appropriate ground cover with deep roots to maintain the soil structure (see Figure 15); and keeping the site free of traffic or other weight loads.

Note that site-specific choice of an appropriate vegetative ground-cover seed mix, including the proper seeding ratio of one or more perennial species with a deep taproot system and the proper amount of lime and soil nutrients (fertilizer mix) adapted to the soil-needs, are basic to the final practice of landscaping, i.e: surface tillage, seeding/planting/fertilizing and culti-packing or mulching is applied. The "maintenance" of an effectively deep-ripped and decompacted area is generally limited to the successful perennial (long-term) landscape ground cover; as long as no weight-bearing force of soil compaction is applied.

Fig. 14. The severely compacted soil of a temporary construction yard used daily by heavy equipment for four months; shown before deep ripping, topsoil replacement, and decompaction.

Fig. 15. The same site as Fig. 14 after deep ripping of the exposed subsoil, topsoil replacement, decompaction through the topsoil and upper subsoil and final surface tillage and revegetation to maintain soil permeability and infiltration.

The Deep Ripping and Decompaction practice is, by necessity, more extensive than periodic subsoiling of farmland.The cost of deep ripping and decompacting (deep subsoiling), will vary according to the depth and severity of soil-material compression and the relative amount of tractor and implement time that is required. In some instances, depending on open maneuverability, two-to-three acres of compacted project area may be deep-ripped in one day. In other situations of more severe compaction and - or less maneuverability, as little as one acre may be fully ripped in a day. Generally, if the Phase 1) Deep Ripping is fully effective, the Phase 2) Decompaction should be completed in 2/3 to 3/4 of the time required for Phase 1.

Using the example of two acres of Phase 1) Deep Ripping in one day, at $1800 per day, the net cost is $900 per acre. If the Phase 2) Decompacting or deep subsoiling takes 3/4 the time as Phase 1, it costs $675 per acre for a combined total of $1575 per acre to complete the practice (these figures do not include the cost of the separate practice of topsoil stripping and replacement). Due to the many variables, it must be recognized that cost will be determined by the specific conditions or constraints of the site and the availability of proper equipment.

Resources

Publications:

- American Society of Agricultural Engineers. 1971. *Compaction of Agricultural Soils.* ASAE.
- Brady, N.C., and R.R. Weil. 2002. *The Nature and Properties of Soils. 13th ed.* Pearson Education, Inc.
- Baver, L.D. 1948. *Soil Physics.* John Wiley & Sons.
- Carpachi, N. 1987 (1995 fifth printing). *Excavation and Grading Handbook, Revised. 2nd ed.* Craftsman Book Company
- Ellis, B. (Editor). 1997. Safe & Easy Lawn Care: The Complete Guide to Organic Low Maintenance Lawn. Houghton Mifflin.
- Harpstead, M.I., T.J. Sauer, and W.F. Bennett. 2001. *Soil Science Simplified. 4th ed.* Iowa State University Press.
- Magdoff, F., and H. van Es. 2000. *Building Soils for Better Crops. 2nd ed.* Sustainable Agricultural Networks
- McCarthy, D.F. 1993. *Essentials of Soil Mechanics and Foundations, Basic Geotechnics 4th ed.* Regents/Prentice Hall.
- Plaster, E.J. 1992. *Soil Science & Management. 3rd ed.* Delmar Publishers.
- Union Gas Limited, Ontario, Canada. 1984. *Rehabilitation of Agricultural Lands, Dawn-Kerwood Loop Pipeline; Technical Report.* Ecological Services for Planning, Ltd.; Robinson, Merritt & Devries, Ltd. and Smith, Hoffman Associates, Ltd.
- US Department of Agriculture in cooperation with Cornell University Agricultural Experiment Station. Various years. *Soil Survey of (various names) County, New York.* USDA.

Internet Access:

- Examples of implements:

V-Rippers. Access by internet search of *John Deere Ag -New Equipment for 915* (larger-frame model) *V-Rippe*; and, *for 913* (smaller-frame model) *V-Ripper*. Deep, angled-leg subsoiler. Access by internet search of: B*igham Brothers Shear Bolt Paratill-Subsoiler.* http://salesmanual.deere.com/sales/salesmanual/en_NA/primary_tillage/2008/feature/rippers/915v_pattern_frame.html?sbu=ag&link=prodcat Last visited March 08.

- Soils data of USDA Natural Resources Conservation Service. *NRCS Web Soil Survey.* http://websoilsurvey.nrcs.usda.gov/app/ and *USDA-NRCS Official Soil Series Descriptions; View by Name.* http://ortho.ftw.nrcs.usda.gov/cgi-bin/osd/osdname.cgi . *Last visited Jan. 08.*
- Soil penetrometer information. Access by internet searches of: *Diagnosing Soil Compaction using a Penetrometer (soil compaction tester), PSU Extension;* as well as *Dickey-john Soil Compaction Tester.* http://www.dickey-johnproducts.com/pdf/SoilCompactionTest.pdf and http://cropsoil.psu.edu/Extension/Facts/uc178pdf Last visited Sept. 07

This Page Intentionally Left Blank

APPENDIX I:
LABELLA CERTIFYING PROFESSIONALS LETTER

LaBella
Powered by partnership.

This Page Intentionally Left Blank

February 17, 2022

RE: LaBella Certifying Professionals for NYSDEC SPDES GP-20-001

To Whom it May Concern:

In accordance with the NYSDEC SPDES General Permit GP 0-20-001, part VII.H.2, the New York State licensed Professional Engineers employed by LaBella Associates and listed on the attachment to this letter are duly authorized to sign and seal Stormwater Pollution Prevention Plans (SWPPPs), NOIs, and NOTs prepared under their direct supervision.

Respectfully submitted,

LaBella Associates



Steven P. Metzger, PE
Chief Executive Officer

LaBella Professional Engineers duly authorized to sign and seal SWPPPs, NOIs, and NOTs:

Name:	Title:	Signature:	Date:
Kyle Ahearn, PE	Senior Civil Engineer		2/9/22
Jody Allen, PE	Senior Civil Engineer		2/24/2022
Anthony Bernardi, PE	Senior Civil Engineer		
Christian Bertram, PE	Senior Civil Engineer		2/9/2022
Brendan Bystrak, PE	Vice President		
Steven Calocerinos, PE	Senior Civil Engineer		2/9/2022
Sean Doty, PE	Senior Civil Engineer		2/24/2022
Jason Ebbs, PE	Municipal Group Leader		
Michael Flanagan, PE	Senior Civil Engineer		2/10/22
Don Hoefler, PE	Senior Project Engineer		
Reuben Hull, PE	Senior Civil Engineer		2/9/2002
Eric Johnson, PE	Senior Civil Engineer		2/9/2002
Roger Keating, PE	Senior Civil Engineer		2/8/2022
Walter Kubow, PE	Senior Civil Engineer		2/9/2022
Christopher Lapine, PE	Senior Civil Engineer		2/9/22
Joseph Lanaro, PE	Vice President		2/9/2022
Michael Mishook, PE	Vice President		2/10/22
Lauren Rodriquez, PE	Civil Engineer		2/9/2022
Jonathan Spurr, PE	Civil Engineer		2/10/22
Mary Steblein, PE	Senior Civil Engineer		2/9/2022
Robert Steehler, PE	Vice President		2/9/2022
Timothy Webber, PE	Vice President		2/9/2022
Kristopher Winkler, PE	Senior Civil Engineer		2/14/2022

APPENDIX J:
NYSDEC SPDES GENERAL PERMIT GP-0-20-001

LaBella
Powered by partnership.

This Page Intentionally Left Blank

NEW YORK STATE OF OPPORTUNITY | Department of Environmental Conservation

NEW YORK STATE
DEPARTMENT OF ENVIRONMENTAL CONSERVATION

SPDES GENERAL PERMIT
FOR STORMWATER DISCHARGES

From

CONSTRUCTION ACTIVITY

Permit No. GP- 0-20-001

Issued Pursuant to Article 17, Titles 7, 8 and Article 70

of the Environmental Conservation Law

Effective Date: January 29, 2020 Expiration Date: January 28, 2025

John J. Ferguson

Chief Permit Administrator

1-23-20

Authorized Signature Date

Address: NYS DEC
Division of Environmental Permits
625 Broadway, 4th Floor
Albany, N.Y. 12233-1750

PREFACE

Pursuant to Section 402 of the Clean Water Act ("CWA"), stormwater *discharges* from certain *construction activities* are unlawful unless they are authorized by a *National Pollutant Discharge Elimination System ("NPDES")* permit or by a state permit program. New York administers the approved State Pollutant Discharge Elimination System (SPDES) program with permits issued in accordance with the New York State Environmental Conservation Law (ECL) Article 17, Titles 7, 8 and Article 70.

An *owner or operator* of a *construction activity* that is eligible for coverage under this permit must obtain coverage prior to the *commencement of construction activity*. Activities that fit the definition of "*construction activity*", as defined under 40 CFR 122.26(b)(14)(x), (15)(i), and (15)(ii), constitute construction of a *point source* and therefore, pursuant to ECL section 17-0505 and 17-0701, the *owner or operator* must have coverage under a SPDES permit prior to *commencing construction activity*. The *owner or operator* cannot wait until there is an actual *discharge* from the *construction site* to obtain permit coverage.

***Note: The italicized words/phrases within this permit are defined in Appendix A.**

NEW YORK STATE DEPARTMENT OF ENVIRONMENTAL CONSERVATION
SPDES GENERAL PERMIT FOR STORMWATER DISCHARGES FROM CONSTRUCTION ACTIVITIES

Table of Contents

Part 1. PERMIT COVERAGE AND LIMITATIONS 1
A. Permit Application 1
B. Effluent Limitations Applicable to Discharges from Construction Activities 1
C. Post-construction Stormwater Management Practice Requirements 4
D. Maintaining Water Quality 8
E. Eligibility Under This General Permit 9
F. Activities Which Are Ineligible for Coverage Under This General Permit 9
Part II. PERMIT COVERAGE 12
A. How to Obtain Coverage 12
B. Notice of Intent (NOI) Submittal 13
C. Permit Authorization 13
D. General Requirements For Owners or Operators With Permit Coverage 15
E. Permit Coverage for Discharges Authorized Under GP-0-15-002 17
F. Change of Owner or Operator 17
Part III. STORMWATER POLLUTION PREVENTION PLAN (SWPPP) 18
A. General SWPPP Requirements 18
B. Required SWPPP Contents 20
C. Required SWPPP Components by Project Type 24
Part IV. INSPECTION AND MAINTENANCE REQUIREMENTS 24
A. General Construction Site Inspection and Maintenance Requirements 24
B. Contractor Maintenance Inspection Requirements 24
C. Qualified Inspector Inspection Requirements 25
Part V. TERMINATION OF PERMIT COVERAGE 29
A. Termination of Permit Coverage 29
Part VI. REPORTING AND RETENTION RECORDS 31
A. Record Retention 31
B. Addresses 31
Part VII. STANDARD PERMIT CONDITIONS 31
A. Duty to Comply 31
B. Continuation of the Expired General Permit 32
C. Enforcement 32
D. Need to Halt or Reduce Activity Not a Defense 32
E. Duty to Mitigate 33
F. Duty to Provide Information 33
G. Other Information 33
H. Signatory Requirements 33
I. Property Rights 35
J. Severability 35
K. Requirement to Obtain Coverage Under an Alternative Permit 35
L. Proper Operation and Maintenance 36
M. Inspection and Entry 36
N. Permit Actions 37
O. Definitions 37
P. Re-Opener Clause 37
Q. Penalties for Falsification of Forms and Reports 37
R. Other Permits 38
APPENDIX A – Acronyms and Definitions 39
Acronyms 39
Definitions 40
APPENDIX B – Required SWPPP Components by Project Type 48
Table 1 48
Table 2 50
APPENDIX C – Watersheds Requiring Enhanced Phosphorus Removal 52
APPENDIX D – Watersheds with Lower Disturbance Threshold 58
APPENDIX E – 303(d) Segments Impaired by Construction Related Pollutant(s) 59
APPENDIX F – List of NYS DEC Regional Offices 65

Part 1. PERMIT COVERAGE AND LIMITATIONS

A. Permit Application

This permit authorizes stormwater *discharges* to *surface waters of the State* from the following *construction activities* identified within 40 CFR Parts 122.26(b)(14)(x), 122.26(b)(15)(i) and 122.26(b)(15)(ii), provided all of the eligibility provisions of this permit are met:

1. *Construction activities* involving soil disturbances of one (1) or more acres; including disturbances of less than one acre that are part of a *larger common plan of development or sale* that will ultimately disturb one or more acres of land; excluding *routine maintenance activity* that is performed to maintain the original line and grade, hydraulic capacity or original purpose of a facility;

2. *Construction activities* involving soil disturbances of less than one (1) acre where the Department has determined that a *SPDES* permit is required for stormwater *discharges* based on the potential for contribution to a violation of a *water quality standard* or for significant contribution of *pollutants* to *surface waters of the State.*

3. *Construction activities* located in the watershed(s) identified in Appendix D that involve soil disturbances between five thousand (5,000) square feet and one (1) acre of land.

B. Effluent Limitations Applicable to Discharges from Construction Activities

*Discharge*s authorized by this permit must achieve, at a minimum, the effluent limitations in Part I.B.1. (a) – (f) of this permit. These limitations represent the degree of effluent reduction attainable by the application of best practicable technology currently available.

1. Erosion and Sediment Control Requirements - The *owner or operator* must select, design, install, implement and maintain control measures to *minimize* the *discharge* of *pollutants* and prevent a violation of the *water quality standards*. The selection, design, installation, implementation, and maintenance of these control measures must meet the non-numeric effluent limitations in Part I.B.1.(a) – (f) of this permit and be in accordance with the New York State Standards and Specifications for Erosion and Sediment Control, dated November 2016, using sound engineering judgment. Where control measures are not designed in conformance with the design criteria included in the technical standard, the *owner or operator* must include in the *Stormwater Pollution Prevention Plan* (“SWPPP”) the reason(s) for the

deviation or alternative design and provide information which demonstrates that the deviation or alternative design is *equivalent* to the technical standard.

a. **Erosion and Sediment Controls.** Design, install and maintain effective erosion and sediment controls to *minimize* the *discharge* of *pollutants* and prevent a violation of the *water quality standards*. At a minimum, such controls must be designed, installed and maintained to:

   (i) *Minimize* soil erosion through application of runoff control and soil stabilization control measure to *minimize pollutant discharge*s;

   (ii) Control stormwater *discharge*s, including both peak flowrates and total stormwater volume, to *minimize* channel and *streambank* erosion and scour in the immediate vicinity of the *discharge* points;

   (iii) *Minimize* the amount of soil exposed during *construction activity*;

   (iv) *Minimize* the disturbance of *steep slopes*;

   (v) *Minimize* sediment *discharge*s from the site;

   (vi) Provide and maintain *natural buffer*s around surface waters, direct stormwater to vegetated areas and maximize stormwater infiltration to reduce *pollutant discharge*s, unless *infeasible*;

   (vii) *Minimize* soil compaction. Minimizing soil compaction is not required where the intended function of a specific area of the site dictates that it be compacted;

   (viii) Unless *infeasible*, preserve a sufficient amount of topsoil to complete soil restoration and establish a uniform, dense vegetative cover; and

   (ix) *Minimize* dust. On areas of exposed soil, *minimize* dust through the appropriate application of water or other dust suppression techniques to control the generation of pollutants that could be discharged from the site.

b. **Soil Stabilization**. In areas where soil disturbance activity has temporarily or permanently ceased, the application of soil stabilization measures must be initiated by the end of the next business day and completed within fourteen (14) days from the date the current soil disturbance activity ceased. For construction sites that *directly discharge* to one of the 303(d) segments

listed in Appendix E or is located in one of the watersheds listed in Appendix C, the application of soil stabilization measures must be initiated by the end of the next business day and completed within seven (7) days from the date the current soil disturbance activity ceased. See Appendix A for definition of *Temporarily Ceased*.

c. **Dewatering**. *Discharge*s from *dewatering* activities, including *discharge*s from *dewatering* of trenches and excavations, must be managed by appropriate control measures.

d. **Pollution Prevention Measures**. Design, install, implement, and maintain effective pollution prevention measures to *minimize* the *discharge* of *pollutants* and prevent a violation of the *water quality standards*. At a minimum, such measures must be designed, installed, implemented and maintained to:

(i) *Minimize* the *discharge* of *pollutants* from equipment and vehicle washing, wheel wash water, and other wash waters. This applies to washing operations that use clean water only. Soaps, detergents and solvents cannot be used;

(ii) *Minimize* the exposure of building materials, building products, construction wastes, trash, landscape materials, fertilizers, pesticides, herbicides, detergents, sanitary waste, hazardous and toxic waste, and other materials present on the site to precipitation and to stormwater. Minimization of exposure is not required in cases where the exposure to precipitation and to stormwater will not result in a *discharge* of *pollutants*, or where exposure of a specific material or product poses little risk of stormwater contamination (such as final products and materials intended for outdoor use) ; and

(iii) Prevent the *discharge* of *pollutants* from spills and leaks and implement chemical spill and leak prevention and response procedures.

e. **Prohibited *Discharge*s.** The following *discharge*s are prohibited:

(i) Wastewater from washout of concrete;

(ii) Wastewater from washout and cleanout of stucco, paint, form release oils, curing compounds and other construction materials;

(iii) Fuels, oils, or other *pollutants* used in vehicle and equipment operation and maintenance;

(iv) Soaps or solvents used in vehicle and equipment washing; and

(v) Toxic or hazardous substances from a spill or other release.

f. Surface Outlets. When discharging from basins and impoundments, the outlets shall be designed, constructed and maintained in such a manner that sediment does not leave the basin or impoundment and that erosion at or below the outlet does not occur.

C. Post-construction Stormwater Management Practice Requirements

1. The *owner or operator* of a *construction activity* that requires post-construction stormwater management practices pursuant to Part III.C. of this permit must select, design, install, and maintain the practices to meet the *performance criteria* in the New York State Stormwater Management Design Manual ("Design Manual"), dated January 2015, using sound engineering judgment. Where post-construction stormwater management practices ("SMPs") are not designed in conformance with the *performance criteria* in the Design Manual, the *owner or operator* must include in the SWPPP the reason(s) for the deviation or alternative design and provide information which demonstrates that the deviation or alternative design is *equivalent* to the technical standard.

2. The *owner or operator* of a *construction activity* that requires post-construction stormwater management practices pursuant to Part III.C. of this permit must design the practices to meet the applicable *sizing criteria* in Part I.C.2.a., b., c. or d. of this permit.

a. Sizing Criteria for New Development

(i) Runoff Reduction Volume ("RRv"): Reduce the total Water Quality Volume ("WQv") by application of RR techniques and standard SMPs with RRv capacity. The total WQv shall be calculated in accordance with the criteria in Section 4.2 of the Design Manual.

(ii) Minimum RRv and Treatment of Remaining Total WQv: Construction activities that cannot meet the criteria in Part I.C.2.a.(i) of this permit due to site limitations shall direct runoff from all newly constructed impervious areas to a RR technique or standard SMP with RRv capacity unless infeasible. The specific site limitations that prevent the reduction of 100% of the WQv shall be documented in the SWPPP.

For each impervious area that is not directed to a RR technique or standard SMP with RRv capacity, the SWPPP must include documentation which demonstrates that all options were considered and for each option explains why it is considered infeasible.

In no case shall the runoff reduction achieved from the newly constructed impervious areas be less than the Minimum RRv as calculated using the criteria in Section 4.3 of the Design Manual. The remaining portion of the total WQv that cannot be reduced shall be treated by application of standard SMPs.

(iii) Channel Protection Volume ("Cpv"): Provide 24 hour extended detention of the post-developed 1-year, 24-hour storm event; remaining after runoff reduction. The Cpv requirement does not apply when:
(1) Reduction of the entire Cpv is achieved by application of runoff reduction techniques or infiltration systems, or
(2) The site discharges directly to tidal waters, or fifth order or larger streams.

(iv) *Overbank* Flood Control Criteria ("Qp"): Requires storage to attenuate the post-development 10-year, 24-hour peak discharge rate (Qp) to predevelopment rates. The Qp requirement does not apply when:
(1) the site discharges directly to tidal waters or fifth order or larger streams, or
(2) A downstream analysis reveals that *overbank* control is not required.

(v) Extreme Flood Control Criteria ("Qf"): Requires storage to attenuate the post-development 100-year, 24-hour peak discharge rate (Qf) to predevelopment rates. The Qf requirement does not apply when:
(1) the site discharges directly to tidal waters or fifth order or larger streams, or
(2) A downstream analysis reveals that *overbank* control is not required.

b. *Sizing Criteria* for *New Development* in Enhanced Phosphorus Removal Watershed

(i) Runoff Reduction Volume (RRv): Reduce the total Water Quality Volume (WQv) by application of RR techniques and standard SMPs with RRv capacity. The total WQv is the runoff volume from the 1-year, 24 hour design storm over the post-developed watershed and shall be

calculated in accordance with the criteria in Section 10.3 of the Design Manual.

(ii) Minimum RRv and Treatment of Remaining Total WQv: *Construction activities* that cannot meet the criteria in Part I.C.2.b.(i) of this permit due to *site limitations* shall direct runoff from all newly constructed *impervious areas* to a RR technique or standard SMP with RRv capacity unless *infeasible*. The specific *site limitations* that prevent the reduction of 100% of the WQv shall be documented in the SWPPP. For each *impervious area* that is not directed to a RR technique or standard SMP with RRv capacity, the SWPPP must include documentation which demonstrates that all options were considered and for each option explains why it is considered *infeasible.*

In no case shall the runoff reduction achieved from the newly constructed *impervious areas* be less than the Minimum RRv as calculated using the criteria in Section 10.3 of the Design Manual. The remaining portion of the total WQv that cannot be reduced shall be treated by application of standard SMPs.

(iii) Channel Protection Volume (Cpv): Provide 24 hour extended detention of the post-developed 1-year, 24-hour storm event; remaining after runoff reduction. The Cpv requirement does not apply when:
(1) Reduction of the entire Cpv is achieved by application of runoff reduction techniques or infiltration systems, or
(2) The site *discharge*s directly to tidal waters, or fifth order or larger streams.

(iv) *Overbank* Flood Control Criteria (Qp): Requires storage to attenuate the post-development 10-year, 24-hour peak *discharge* rate (Qp) to predevelopment rates. The Qp requirement does not apply when:
(1) the site *discharge*s directly to tidal waters or fifth order or larger streams, or
(2) A downstream analysis reveals that *overbank* control is not required.

(v) Extreme Flood Control Criteria (Qf): Requires storage to attenuate the post-development 100-year, 24-hour peak *discharge* rate (Qf) to predevelopment rates. The Qf requirement does not apply when:
(1) the site *discharge*s directly to tidal waters or fifth order or larger streams, or
(2) A downstream analysis reveals that *overbank* control is not required.

c. Sizing Criteria for Redevelopment Activity

(i) Water Quality Volume (WQv): The WQv treatment objective for *redevelopment activity* shall be addressed by one of the following options. *Redevelopment activities* located in an Enhanced Phosphorus Removal Watershed (see Part III.B.3. and Appendix C of this permit) shall calculate the WQv in accordance with Section 10.3 of the Design Manual. All other *redevelopment activities* shall calculate the WQv in accordance with Section 4.2 of the Design Manual.

(1) Reduce the existing *impervious cover* by a minimum of 25% of the total disturbed, *impervious area*. The Soil Restoration criteria in Section 5.1.6 of the Design Manual must be applied to all newly created pervious areas, or

(2) Capture and treat a minimum of 25% of the WQv from the disturbed, *impervious area* by the application of standard SMPs; or reduce 25% of the WQv from the disturbed, *impervious area* by the application of RR techniques or standard SMPs with RRv capacity., or

(3) Capture and treat a minimum of 75% of the WQv from the disturbed, *impervious area* as well as any additional runoff from tributary areas by application of the alternative practices discussed in Sections 9.3 and 9.4 of the Design Manual., or

(4) Application of a combination of 1, 2 and 3 above that provide a weighted average of at least two of the above methods. Application of this method shall be in accordance with the criteria in Section 9.2.1(B) (IV) of the Design Manual.

If there is an existing post-construction stormwater management practice located on the site that captures and treats runoff from the *impervious area* that is being disturbed, the WQv treatment option selected must, at a minimum, provide treatment equal to the treatment that was being provided by the existing practice(s) if that treatment is greater than the treatment required by options 1 – 4 above.

(ii) Channel Protection Volume (Cpv): Not required if there are no changes to hydrology that increase the *discharge* rate from the project site.

(iii) *Overbank* Flood Control Criteria (Qp): Not required if there are no changes to hydrology that increase the *discharge* rate from the project site.

(iv) Extreme Flood Control Criteria (Qf): Not required if there are no changes to hydrology that increase the *discharge* rate from the project site

d. Sizing Criteria for Combination of Redevelopment Activity and New Development

Construction projects that include both New Development and Redevelopment Activity shall provide post-construction stormwater management controls that meet the sizing criteria calculated as an aggregate of the Sizing Criteria in Part I.C.2.a. or b. of this permit for the New Development portion of the project and Part I.C.2.c of this permit for Redevelopment Activity portion of the project.

D. Maintaining Water Quality

The Department expects that compliance with the conditions of this permit will control *discharge*s necessary to meet applicable *water quality standards*. It shall be a violation of the *ECL* for any discharge to either cause or contribute to a violation of *water quality standards* as contained in Parts 700 through 705 of Title 6 of the Official Compilation of Codes, Rules and Regulations of the State of New York, such as:

1. There shall be no increase in turbidity that will cause a substantial visible contrast to natural conditions;

2. There shall be no increase in suspended, colloidal or settleable solids that will cause deposition or impair the waters for their best usages; and

3. There shall be no residue from oil and floating substances, nor visible oil film, nor globules of grease.

If there is evidence indicating that the stormwater *discharge*s authorized by this permit are causing, have the reasonable potential to cause, or are contributing to a violation of the *water quality standards*; the *owner or operator* must take appropriate corrective action in accordance with Part IV.C.5. of this general permit and document in accordance with Part IV.C.4. of this general permit. To address the *water quality standard* violation the *owner or operator* may need to provide additional information, include and implement appropriate controls in the SWPPP to correct the problem, or obtain an individual SPDES permit.

If there is evidence indicating that despite compliance with the terms and conditions of this general permit it is demonstrated that the stormwater *discharge*s authorized by this permit are causing or contributing to a violation of *water quality standards*, or if the Department determines that a modification of the permit is necessary to prevent a violation of *water quality standards*, the authorized *discharge*s will no longer be eligible for coverage under this permit. The Department may require the *owner or operator* to obtain an individual SPDES permit to continue discharging.

E. Eligibility Under This General Permit

1. This permit may authorize all *discharges* of stormwater from *construction activity* to *surface waters of the State* and *groundwaters* except for ineligible *discharges* identified under subparagraph F. of this Part.

2. Except for non-stormwater *discharges* explicitly listed in the next paragraph, this permit only authorizes stormwater *discharge*s; including stormwater runoff, snowmelt runoff, and surface runoff and drainage, from *construction activities*.

3. Notwithstanding paragraphs E.1 and E.2 above, the following non-stormwater discharges are authorized by this permit: those listed in 6 NYCRR 750-1.2(a)(29)(vi), with the following exception: "Discharges from firefighting activities are authorized only when the firefighting activities are emergencies/unplanned"; waters to which other components have not been added that are used to control dust in accordance with the SWPPP; and uncontaminated *discharge*s from *construction site* de-watering operations. All non-stormwater discharges must be identified in the SWPPP. Under all circumstances, the *owner or operator* must still comply with *water quality standards* in Part I.D of this permit.

4. The *owner or operator* must maintain permit eligibility to *discharge* under this permit. Any *discharges* that are not compliant with the eligibility conditions of this permit are not authorized by the permit and the *owner or operator* must either apply for a separate permit to cover those ineligible *discharges* or take steps necessary to make the *discharge* eligible for coverage.

F. Activities Which Are Ineligible for Coverage Under This General Permit

All of the following are **not** authorized by this permit:

1. *Discharge*s after *construction activities* have been completed and the site has undergone *final stabilization*;

2. *Discharge*s that are mixed with sources of non-stormwater other than those expressly authorized under subsection E.3. of this Part and identified in the SWPPP required by this permit;

3. *Discharges* that are required to obtain an individual SPDES permit or another SPDES general permit pursuant to Part VII.K. of this permit;

4. *Construction activities* or *discharges* from *construction activities* that may adversely affect an *endangered or threatened species* unless the *owner or*

operator has obtained a permit issued pursuant to 6 NYCRR Part 182 for the project or the Department has issued a letter of non-jurisdiction for the project. All documentation necessary to demonstrate eligibility shall be maintained on site in accordance with Part II.D.2 of this permit;

5. *Discharges* which either cause or contribute to a violation of *water quality standards* adopted pursuant to the *ECL* and its accompanying regulations;

6. *Construction activities* for residential, commercial and institutional projects:

   a. Where the *discharge*s from the *construction activities* are tributary to waters of the state classified as AA or AA-s; and

   b. Which are undertaken on land with no existing *impervious cover*; and

   c. Which disturb one (1) or more acres of land designated on the current United States Department of Agriculture ("USDA") Soil Survey as Soil Slope Phase "D", (provided the map unit name is inclusive of slopes greater than 25%), or Soil Slope Phase "E" or "F" (regardless of the map unit name), or a combination of the three designations.

7. *Construction activities* for linear transportation projects and linear utility projects:

   a. Where the *discharge*s from the *construction activities* are tributary to waters of the state classified as AA or AA-s; and

   b. Which are undertaken on land with no existing *impervious cover*; and

   c. Which disturb two (2) or more acres of land designated on the current USDA Soil Survey as Soil Slope Phase "D" (provided the map unit name is inclusive of slopes greater than 25%), or Soil Slope Phase "E" or "F" (regardless of the map unit name), or a combination of the three designations.

8. *Construction activities* that have the potential to affect an *historic property*, unless there is documentation that such impacts have been resolved. The following documentation necessary to demonstrate eligibility with this requirement shall be maintained on site in accordance with Part II.D.2 of this permit and made available to the Department in accordance with Part VII.F of this permit:

   a. Documentation that the *construction activity* is not within an archeologically sensitive area indicated on the sensitivity map, and that the *construction activity* is not located on or immediately adjacent to a property listed or determined to be eligible for listing on the National or State Registers of Historic Places, and that there is no new permanent building on the *construction site* within the following distances from a building, structure, or object that is more than 50 years old, or if there is such a new permanent building on the *construction site* within those parameters that NYS Office of Parks, Recreation and Historic Preservation (OPRHP), a Historic Preservation Commission of a Certified Local Government, or a qualified preservation professional has determined that the building, structure, or object more than 50 years old is not historically/archeologically significant.

      - 1-5 acres of disturbance - 20 feet
      - 5-20 acres of disturbance - 50 feet
      - 20+ acres of disturbance - 100 feet, or

   b. DEC consultation form sent to OPRHP, and copied to the NYS DEC Agency Historic Preservation Officer (APO), and
      (i) the State Environmental Quality Review (SEQR) Environmental Assessment Form (EAF) with a negative declaration or the Findings Statement, with documentation of OPRHP's agreement with the resolution; or
      (ii) documentation from OPRHP that the *construction activity* will result in No Impact; or
      (iii) documentation from OPRHP providing a determination of No Adverse Impact; or
      (iv) a Letter of Resolution signed by the owner/operator, OPRHP and the DEC APO which allows for this *construction activity* to be eligible for coverage under the general permit in terms of the State Historic Preservation Act (SHPA); or

   c. Documentation of satisfactory compliance with Section 106 of the National Historic Preservation Act for a coterminous project area:

      (i) No Affect
      (ii) No Adverse Affect
      (iii) Executed Memorandum of Agreement, or

   d. Documentation that:

      (i) SHPA Section 14.09 has been completed by NYS DEC or another state agency.

9. *Discharge*s from *construction activities* that are subject to an existing SPDES individual or general permit where a SPDES permit for *construction activity* has been terminated or denied; or where the *owner or operator* has failed to renew an expired individual permit.

Part II. PERMIT COVERAGE

A. How to Obtain Coverage

1. An *owner or operator* of a *construction activity* that is not subject to the requirements of a regulated, traditional land use control MS4 must first prepare a SWPPP in accordance with all applicable requirements of this permit and then submit a completed Notice of Intent (NOI) to the Department to be authorized to discharge under this permit.

2. An *owner or operator* of a *construction activity* that is subject to the requirements of a *regulated, traditional land use control MS4* must first prepare a SWPPP in accordance with all applicable requirements of this permit and then have the SWPPP reviewed and accepted by the *regulated, traditional land use control MS4* prior to submitting the NOI to the Department. The *owner or operator* shall have the "MS4 SWPPP Acceptance" form signed in accordance with Part VII.H., and then submit that form along with a completed NOI to the Department.

3. The requirement for an *owner or operator* to have its SWPPP reviewed and accepted by the *regulated, traditional land use control MS4* prior to submitting the NOI to the Department does not apply to an *owner or operator* that is obtaining permit coverage in accordance with the requirements in Part II.F. (Change of *Owner or Operator*) or where the *owner or operator* of the *construction activity* is the *regulated, traditional land use control MS4* . This exemption does not apply to *construction activities* subject to the New York City Administrative Code.

B. Notice of Intent (NOI) Submittal

1. Prior to December 21, 2020, an owner or operator shall use either the electronic (eNOI) or paper version of the NOI that the Department prepared. Both versions of the NOI are located on the Department's website (http://www.dec.ny.gov/). The paper version of the NOI shall be signed in accordance with Part VII.H. of this permit and submitted to the following address:

   NOTICE OF INTENT
   NYS DEC, Bureau of Water Permits
   625 Broadway, 4th Floor
   Albany, New York 12233-3505

2. Beginning December 21, 2020 and in accordance with EPA's 2015 NPDES Electronic Reporting Rule (40 CFR Part 127), the *owner or operator* must submit the NOI electronically using the *Department's* online NOI.

3. The *owner or operator* shall have the SWPPP preparer sign the "SWPPP Preparer Certification" statement on the NOI prior to submitting the form to the Department.

4. As of the date the NOI is submitted to the Department, the *owner or operator* shall make the NOI and SWPPP available for review and copying in accordance with the requirements in Part VII.F. of this permit.

C. Permit Authorization

1. An *owner or operator* shall not *commence construction activity* until their authorization to *discharge* under this permit goes into effect.

2. Authorization to *discharge* under this permit will be effective when the *owner or operator* has satisfied all of the following criteria:

   a. project review pursuant to the State Environmental Quality Review Act ("SEQRA") have been satisfied, when SEQRA is applicable. See the Department's website (http://www.dec.ny.gov/) for more information,

   b. where required, all necessary Department permits subject to the *Uniform Procedures Act ("UPA")* (see 6 NYCRR Part 621), or the equivalent from another New York State agency, have been obtained, unless otherwise notified by the Department pursuant to 6 NYCRR 621.3(a)(4). *Owners or operators* of *construction activities* that are required to obtain *UPA* permits

must submit a preliminary SWPPP to the appropriate DEC Permit Administrator at the Regional Office listed in Appendix F at the time all other necessary *UPA* permit applications are submitted. The preliminary SWPPP must include sufficient information to demonstrate that the *construction activity* qualifies for authorization under this permit,

   c. the final SWPPP has been prepared, and

   d. a complete NOI has been submitted to the Department in accordance with the requirements of this permit.

3. An *owner or operator* that has satisfied the requirements of Part II.C.2 above will be authorized to *discharge* stormwater from their *construction activity* in accordance with the following schedule:

   a. For *construction activities* that are not subject to the requirements of a *regulated, traditional land use control MS4*:

      (i) Five (5) business days from the date the Department receives a complete electronic version of the NOI (eNOI) for *construction activities* with a SWPPP that has been prepared in conformance with the design criteria in the technical standard referenced in Part III.B.1 and the *performance criteria* in the technical standard referenced in Parts III.B., 2 or 3, for *construction activities* that require post-construction stormwater management practices pursuant to Part III.C.; or

      (ii) Sixty (60) business days from the date the Department receives a complete NOI (electronic or paper version) for *construction activities* with a SWPPP that has not been prepared in conformance with the design criteria in technical standard referenced in Part III.B.1. or, for *construction activities* that require post-construction stormwater management practices pursuant to Part III.C., the *performance criteria* in the technical standard referenced in Parts III.B., 2 or 3, or;

      (iii) Ten (10) business days from the date the Department receives a complete paper version of the NOI for *construction activities* with a SWPPP that has been prepared in conformance with the design criteria in the technical standard referenced in Part III.B.1 and the *performance criteria* in the technical standard referenced in Parts III.B., 2 or 3, for *construction activities* that require post-construction stormwater management practices pursuant to Part III.C.

b. For *construction activities* that are subject to the requirements of a *regulated, traditional land use control MS4*:

(i) Five (5) business days from the date the Department receives both a complete electronic version of the NOI (eNOI) and signed "*MS4* SWPPP Acceptance" form, or

(ii) Ten (10) business days from the date the Department receives both a complete paper version of the NOI and signed "MS4 SWPPP Acceptance" form.

4. Coverage under this permit authorizes stormwater *discharges* from only those areas of disturbance that are identified in the NOI. If an *owner or operator* wishes to have stormwater *discharges* from future or additional areas of disturbance authorized, they must submit a new NOI that addresses that phase of the development, unless otherwise notified by the Department. The *owner or operator* shall not *commence construction activity* on the future or additional areas until their authorization to *discharge* under this permit goes into effect in accordance with Part II.C. of this permit.

D. General Requirements For Owners or Operators With Permit Coverage

1. The *owner or operator* shall ensure that the provisions of the SWPPP are implemented from the *commencement of construction activity* until all areas of disturbance have achieved *final stabilization* and the Notice of Termination ("NOT") has been submitted to the Department in accordance with Part V. of this permit. This includes any changes made to the SWPPP pursuant to Part III.A.4. of this permit.

2. The *owner or operator* shall maintain a copy of the General Permit (GP-0-20-001), NOI, *NOI Acknowledgment Letter*, SWPPP, MS4 SWPPP Acceptance form, inspection reports, responsible contractor's or subcontractor's certification statement (see Part III.A.6.), and all documentation necessary to demonstrate eligibility with this permit at the *construction site* until all disturbed areas have achieved *final stabilization* and the NOT has been submitted to the Department. The documents must be maintained in a secure location, such as a job trailer, on-site construction office, or mailbox with lock. The secure location must be accessible during normal business hours to an individual performing a compliance inspection.

3. The *owner or operator* of a *construction activity* shall not disturb greater than five (5) acres of soil at any one time without prior written authorization from the Department or, in areas under the jurisdiction of a *regulated, traditional land*

use control MS4, the *regulated, traditional land use control MS4* (provided the *regulated, traditional land use control MS4* is not the *owner or operator* of the *construction activity*). At a minimum, the *owner or operator* must comply with the following requirements in order to be authorized to disturb greater than five (5) acres of soil at any one time:

a. The *owner or operator* shall have a *qualified inspector* conduct **at least** two (2) site inspections in accordance with Part IV.C. of this permit every seven (7) calendar days, for as long as greater than five (5) acres of soil remain disturbed. The two (2) inspections shall be separated by a minimum of two (2) full calendar days.

b. In areas where soil disturbance activity has temporarily or permanently ceased, the application of soil stabilization measures must be initiated by the end of the next business day and completed within seven (7) days from the date the current soil disturbance activity ceased. The soil stabilization measures selected shall be in conformance with the technical standard, New York State Standards and Specifications for Erosion and Sediment Control, dated November 2016.

c. The *owner or operator* shall prepare a phasing plan that defines maximum disturbed area per phase and shows required cuts and fills.

d. The *owner or operator* shall install any additional site-specific practices needed to protect water quality.

e. The *owner or operator* shall include the requirements above in their SWPPP.

4. In accordance with statute, regulations, and the terms and conditions of this permit, the Department may suspend or revoke an *owner's or operator's* coverage under this permit at any time if the Department determines that the SWPPP does not meet the permit requirements or consistent with Part VII.K..

5. Upon a finding of significant non-compliance with the practices described in the SWPPP or violation of this permit, the Department may order an immediate stop to all activity at the site until the non-compliance is remedied. The stop work order shall be in writing, describe the non-compliance in detail, and be sent to the *owner or operator*.

6. For *construction activities* that are subject to the requirements of a *regulated, traditional land use control MS4*, the *owner or operator* shall notify the

regulated, traditional land use control MS4 in writing of any planned amendments or modifications to the post-construction stormwater management practice component of the SWPPP required by Part III.A. 4. and 5. of this permit. Unless otherwise notified by the *regulated, traditional land use control MS4*, the *owner or operator* shall have the SWPPP amendments or modifications reviewed and accepted by the *regulated, traditional land use control MS4* prior to commencing construction of the post-construction stormwater management practice.

E. Permit Coverage for Discharges Authorized Under GP-0-15-002

1. Upon renewal of SPDES General Permit for Stormwater Discharges from *Construction Activity* (Permit No. GP-0-15-002), an *owner or operator* of *a construction activity* with coverage under GP-0-15-002, as of the effective date of GP- 0-20-001, shall be authorized to *discharge* in accordance with GP- 0-20-001, unless otherwise notified by the Department.

   An *owner or operator* may continue to implement the technical/design components of the post-construction stormwater management controls provided that such design was done in conformance with the technical standards in place at the time of initial project authorization. However, they must comply with the other, non-design provisions of GP-0-20-001.

F. Change of Owner or Operator

1. When property ownership changes or when there is a change in operational control over the construction plans and specifications, the original *owner or operator* must notify the new *owner or operator*, in writing, of the requirement to obtain permit coverage by submitting a NOI with the Department. For *construction activities* subject to the requirements of a *regulated, traditional land use control MS4,* the original *owner or operator* must also notify the MS4, in writing, of the change in ownership at least 30 calendar days prior to the change in ownership.

2. Once the new *owner or operator* obtains permit coverage, the original *owner or operator* shall then submit a completed NOT with the name and permit identification number of the new *owner or operator* to the Department at the address in Part II.B.1. of this permit. If the original *owner or operator* maintains ownership of a portion of the *construction activity* and will disturb soil, they must maintain their coverage under the permit.

3. Permit coverage for the new *owner or operator* will be effective as of the date the Department receives a complete NOI, provided the original *owner or*

operator was not subject to a sixty (60) business day authorization period that has not expired as of the date the Department receives the NOI from the new *owner or operator*.

Part III. STORMWATER POLLUTION PREVENTION PLAN (SWPPP)

A. General SWPPP Requirements

1. A SWPPP shall be prepared and implemented by the *owner or operator* of each *construction activity* covered by this permit. The SWPPP must document the selection, design, installation, implementation and maintenance of the control measures and practices that will be used to meet the effluent limitations in Part I.B. of this permit and where applicable, the post-construction stormwater management practice requirements in Part I.C. of this permit. The SWPPP shall be prepared prior to the submittal of the NOI. The NOI shall be submitted to the Department prior to the *commencement of construction activity*. A copy of the completed, final NOI shall be included in the SWPPP.

2. The SWPPP shall describe the erosion and sediment control practices and where required, post-construction stormwater management practices that will be used and/or constructed to reduce the *pollutants* in stormwater *discharges* and to assure compliance with the terms and conditions of this permit. In addition, the SWPPP shall identify potential sources of pollution which may reasonably be expected to affect the quality of stormwater *discharges*.

3. All SWPPPs that require the post-construction stormwater management practice component shall be prepared by a *qualified professional* that is knowledgeable in the principles and practices of stormwater management and treatment.

4. The *owner or operator* must keep the SWPPP current so that it at all times accurately documents the erosion and sediment controls practices that are being used or will be used during construction, and all post-construction stormwater management practices that will be constructed on the site. At a minimum, the *owner or operator* shall amend the SWPPP, including construction drawings:

   a. whenever the current provisions prove to be ineffective in minimizing *pollutants* in stormwater *discharges* from the site;

b. whenever there is a change in design, construction, or operation at the *construction site* that has or could have an effect on the *discharge* of *pollutants*;

c. to address issues or deficiencies identified during an inspection by the *qualified inspector,* the Department or other regulatory authority; and

d. to document the final construction conditions.

5. The Department may notify the *owner or operator* at any time that the SWPPP does not meet one or more of the minimum requirements of this permit. The notification shall be in writing and identify the provisions of the SWPPP that require modification. Within fourteen (14) calendar days of such notification, or as otherwise indicated by the Department, the *owner or operator* shall make the required changes to the SWPPP and submit written notification to the Department that the changes have been made. If the *owner or operator* does not respond to the Department's comments in the specified time frame, the Department may suspend the *owner's or operator's* coverage under this permit or require the *owner or operator* to obtain coverage under an individual SPDES permit in accordance with Part II.D.4. of this permit.

6. Prior to the *commencement of construction activity*, the *owner or operator* must identify the contractor(s) and subcontractor(s) that will be responsible for installing, constructing, repairing, replacing, inspecting and maintaining the erosion and sediment control practices included in the SWPPP; and the contractor(s) and subcontractor(s) that will be responsible for constructing the post-construction stormwater management practices included in the SWPPP. The *owner or operator* shall have each of the contractors and subcontractors identify at least one person from their company that will be responsible for implementation of the SWPPP. This person shall be known as the *trained contractor.* The *owner or operator* shall ensure that at least one *trained contractor* is on site on a daily basis when soil disturbance activities are being performed.

   The *owner or operator* shall have each of the contractors and subcontractors identified above sign a copy of the following certification statement below before they commence any *construction activity*:

   "I hereby certify under penalty of law that I understand and agree to comply with the terms and conditions of the SWPPP and agree to implement any corrective actions identified by the *qualified inspector* during a site inspection. I also understand that the *owner or operator* must comply with

the terms and conditions of the most current version of the New York State Pollutant Discharge Elimination System ("SPDES") general permit for stormwater *discharge*s from *construction activities* and that it is unlawful for any person to cause or contribute to a violation of *water quality standards*. Furthermore, I am aware that there are significant penalties for submitting false information, that I do not believe to be true, including the possibility of fine and imprisonment for knowing violations"

In addition to providing the certification statement above, the certification page must also identify the specific elements of the SWPPP that each contractor and subcontractor will be responsible for and include the name and title of the person providing the signature; the name and title of the *trained contractor* responsible for SWPPP implementation; the name, address and telephone number of the contracting firm; the address (or other identifying description) of the site; and the date the certification statement is signed. The *owner or operator* shall attach the certification statement(s) to the copy of the SWPPP that is maintained at the *construction site*. If new or additional contractors are hired to implement measures identified in the SWPPP after construction has commenced, they must also sign the certification statement and provide the information listed above.

7. For projects where the Department requests a copy of the SWPPP or inspection reports, the *owner or operator* shall submit the documents in both electronic (PDF only) and paper format within five (5) business days, unless otherwise notified by the Department.

B. Required SWPPP Contents

1. Erosion and sediment control component - All SWPPPs prepared pursuant to this permit shall include erosion and sediment control practices designed in conformance with the technical standard, New York State Standards and Specifications for Erosion and Sediment Control, dated November 2016. Where erosion and sediment control practices are not designed in conformance with the design criteria included in the technical standard, the *owner or operator* must demonstrate *equivalence* to the technical standard. At a minimum, the erosion and sediment control component of the SWPPP shall include the following:

   a. Background information about the scope of the project, including the location, type and size of project

b. A site map/construction drawing(s) for the project, including a general location map. At a minimum, the site map shall show the total site area; all improvements; areas of disturbance; areas that will not be disturbed; existing vegetation; on-site and adjacent off-site surface water(s); floodplain/floodway boundaries; wetlands and drainage patterns that could be affected by the *construction activity*; existing and final contours ; locations of different soil types with boundaries; material, waste, borrow or equipment storage areas located on adjacent properties; and location(s) of the stormwater *discharge*(s);

c. A description of the soil(s) present at the site, including an identification of the Hydrologic Soil Group (HSG);

d. A construction phasing plan and sequence of operations describing the intended order of *construction activities*, including clearing and grubbing, excavation and grading, utility and infrastructure installation and any other activity at the site that results in soil disturbance;

e. A description of the minimum erosion and sediment control practices to be installed or implemented for each *construction activity* that will result in soil disturbance. Include a schedule that identifies the timing of initial placement or implementation of each erosion and sediment control practice and the minimum time frames that each practice should remain in place or be implemented;

f. A temporary and permanent soil stabilization plan that meets the requirements of this general permit and the technical standard, New York State Standards and Specifications for Erosion and Sediment Control, dated November 2016, for each stage of the project, including initial land clearing and grubbing to project completion and achievement of *final stabilization*;

g. A site map/construction drawing(s) showing the specific location(s), size(s), and length(s) of each erosion and sediment control practice;

h. The dimensions, material specifications, installation details, and operation and maintenance requirements for all erosion and sediment control practices. Include the location and sizing of any temporary sediment basins and structural practices that will be used to divert flows from exposed soils;

i. A maintenance inspection schedule for the contractor(s) identified in Part III.A.6. of this permit, to ensure continuous and effective operation of the erosion and sediment control practices. The maintenance inspection

schedule shall be in accordance with the requirements in the technical standard, New York State Standards and Specifications for Erosion and Sediment Control, dated November 2016;

j. A description of the pollution prevention measures that will be used to control litter, construction chemicals and construction debris from becoming a *pollutant* source in the stormwater *discharges*;

k. A description and location of any stormwater *discharges* associated with industrial activity other than construction at the site, including, but not limited to, stormwater *discharges* from asphalt plants and concrete plants located on the *construction site*; and

l. Identification of any elements of the design that are not in conformance with the design criteria in the technical standard, New York State Standards and Specifications for Erosion and Sediment Control, dated November 2016. Include the reason for the deviation or alternative design and provide information which demonstrates that the deviation or alternative design is *equivalent* to the technical standard.

2. Post-construction stormwater management practice component – The *owner or operator* of any construction project identified in Table 2 of Appendix B as needing post-construction stormwater management practices shall prepare a SWPPP that includes practices designed in conformance with the applicable *sizing criteria* in Part I.C.2.a., c. or d. of this permit and the *performance criteria* in the technical standard, New York State Stormwater Management Design Manual dated January 2015

   Where post-construction stormwater management practices are not designed in conformance with the *performance criteria* in the technical standard, the *owner or operator* must include in the SWPPP the reason(s) for the deviation or alternative design and provide information which demonstrates that the deviation or alternative design is *equivalent* to the technical standard.

   The post-construction stormwater management practice component of the SWPPP shall include the following:

   a. Identification of all post-construction stormwater management practices to be constructed as part of the project. Include the dimensions, material specifications and installation details for each post-construction stormwater management practice;

b. A site map/construction drawing(s) showing the specific location and size of each post-construction stormwater management practice;

c. A Stormwater Modeling and Analysis Report that includes:
   (i) Map(s) showing pre-development conditions, including watershed/subcatchments boundaries, flow paths/routing, and design points;

   (ii) Map(s) showing post-development conditions, including watershed/subcatchments boundaries, flow paths/routing, design points and post-construction stormwater management practices;

   (iii) Results of stormwater modeling (i.e. hydrology and hydraulic analysis) for the required storm events. Include supporting calculations (model runs), methodology, and a summary table that compares pre and post-development runoff rates and volumes for the different storm events;

   (iv) Summary table, with supporting calculations, which demonstrates that each post-construction stormwater management practice has been designed in conformance with the *sizing criteria* included in the Design Manual;

   (v) Identification of any *sizing criteria* that is not required based on the requirements included in Part I.C. of this permit; and

   (vi) Identification of any elements of the design that are not in conformance with the *performance criteria* in the Design Manual. Include the reason(s) for the deviation or alternative design and provide information which demonstrates that the deviation or alternative design is *equivalent* to the Design Manual;

d. Soil testing results and locations (test pits, borings);

e. Infiltration test results, when required; and

f. An operations and maintenance plan that includes inspection and maintenance schedules and actions to ensure continuous and effective operation of each post-construction stormwater management practice. The plan shall identify the entity that will be responsible for the long term operation and maintenance of each practice.

3. Enhanced Phosphorus Removal Standards - All construction projects identified in Table 2 of Appendix B that are located in the watersheds identified in Appendix C shall prepare a SWPPP that includes post-construction stormwater management practices designed in conformance with the applicable *sizing criteria* in Part I.C.2. b., c. or d. of this permit and the *performance criteria,* Enhanced Phosphorus Removal Standards included in the Design Manual. At a minimum, the post-construction stormwater management practice component of the SWPPP shall include items 2.a - 2.f. above.

C. Required SWPPP Components by Project Type

Unless otherwise notified by the Department, *owners or operators* of *construction activities* identified in Table 1 of Appendix B are required to prepare a SWPPP that only includes erosion and sediment control practices designed in conformance with Part III.B.1 of this permit. *Owners or operators* of the *construction activities* identified in Table 2 of Appendix B shall prepare a SWPPP that also includes post-construction stormwater management practices designed in conformance with Part III.B.2 or 3 of this permit.

Part IV. INSPECTION AND MAINTENANCE REQUIREMENTS

A. General Construction Site Inspection and Maintenance Requirements

1. The *owner or operator* must ensure that all erosion and sediment control practices (including pollution prevention measures) and all post-construction stormwater management practices identified in the SWPPP are inspected and maintained in accordance with Part IV.B. and C. of this permit.

2. The terms of this permit shall not be construed to prohibit the State of New York from exercising any authority pursuant to the ECL, common law or federal law, or prohibit New York State from taking any measures, whether civil or criminal, to prevent violations of the laws of the State of New York or protect the public health and safety and/or the environment.

B. Contractor Maintenance Inspection Requirements

1. The *owner or operator* of each *construction activity* identified in Tables 1 and 2 of Appendix B shall have a *trained contractor* inspect the erosion and sediment control practices and pollution prevention measures being implemented within the active work area daily to ensure that they are being maintained in effective operating condition at all times. If deficiencies are identified, the contractor shall

begin implementing corrective actions within one business day and shall complete the corrective actions in a reasonable time frame.

2. For construction sites where soil disturbance activities have been temporarily suspended (e.g. winter shutdown) and *temporary stabilization* measures have been applied to all disturbed areas, the *trained contractor* can stop conducting the maintenance inspections. The *trained contractor* shall begin conducting the maintenance inspections in accordance with Part IV.B.1. of this permit as soon as soil disturbance activities resume.

3. For construction sites where soil disturbance activities have been shut down with partial project completion, the *trained contractor* can stop conducting the maintenance inspections if all areas disturbed as of the project shutdown date have achieved *final stabilization* and all post-construction stormwater management practices required for the completed portion of the project have been constructed in conformance with the SWPPP and are operational.

C. Qualified Inspector Inspection Requirements

The *owner or operator* shall have a *qualified inspector* conduct site inspections in conformance with the following requirements:

[Note: The *trained contractor* identified in Part III.A.6. and IV.B. of this permit **cannot** conduct the *qualified inspector* site inspections unless they meet the *qualified inspector* qualifications included in Appendix A. In order to perform these inspections, the *trained contractor* would have to be a:

- licensed Professional Engineer,
- Certified Professional in Erosion and Sediment Control (CPESC),
- New York State Erosion and Sediment Control Certificate Program holder
- Registered Landscape Architect, or
- someone working under the direct supervision of, and at the same company as, the licensed Professional Engineer or Registered Landscape Architect, provided they have received four (4) hours of Department endorsed training in proper erosion and sediment control principles from a Soil and Water Conservation District, or other Department endorsed entity].

1. A *qualified inspector* shall conduct site inspections for all *construction activities* identified in Tables 1 and 2 of Appendix B, with the exception of:

   a. the construction of a single family residential subdivision with 25% or less *impervious cover* at total site build-out that involves a soil disturbance of one (1) or more acres of land but less than five (5) acres and is not located

in one of the watersheds listed in Appendix C and not directly discharging to one of the 303(d) segments listed in Appendix E;

   b. the construction of a single family home that involves a soil disturbance of one (1) or more acres of land but less than five (5) acres and is not located in one of the watersheds listed in Appendix C and not directly discharging to one of the 303(d) segments listed in Appendix E;

   c. construction on agricultural property that involves a soil disturbance of one (1) or more acres of land but less than five (5) acres; and

   d. *construction activities* located in the watersheds identified in Appendix D that involve soil disturbances between five thousand (5,000) square feet and one (1) acre of land.

2. Unless otherwise notified by the Department, the *qualified inspector* shall conduct site inspections in accordance with the following timetable:

   a. For construction sites where soil disturbance activities are on-going, the *qualified inspector* shall conduct a site inspection at least once every seven (7) calendar days.

   b. For construction sites where soil disturbance activities are on-going and the *owner or operator* has received authorization in accordance with Part II.D.3 to disturb greater than five (5) acres of soil at any one time, the *qualified inspector* shall conduct at least two (2) site inspections every seven (7) calendar days. The two (2) inspections shall be separated by a minimum of two (2) full calendar days.

   c. For construction sites where soil disturbance activities have been temporarily suspended (e.g. winter shutdown) and *temporary stabilization* measures have been applied to all disturbed areas, the *qualified inspector* shall conduct a site inspection at least once every thirty (30) calendar days. The *owner or operator* shall notify the DOW Water (SPDES) Program contact at the Regional Office (see contact information in Appendix F) or, in areas under the jurisdiction of a *regulated, traditional land use control MS4,* the *regulated, traditional land use control MS4* (provided the *regulated, traditional land use control MS4* is not the *owner or operator* of the *construction activity*) in writing prior to reducing the frequency of inspections.

d. For construction sites where soil disturbance activities have been shut down with partial project completion, the *qualified inspector* can stop conducting inspections if all areas disturbed as of the project shutdown date have achieved *final stabilization* and all post-construction stormwater management practices required for the completed portion of the project have been constructed in conformance with the SWPPP and are operational. The *owner or operator* shall notify the DOW Water (SPDES) Program contact at the Regional Office (see contact information in Appendix F) or, in areas under the jurisdiction of a *regulated, traditional land use control MS4,* the *regulated, traditional land use control MS4* (provided the *regulated, traditional land use control MS4* is not the *owner or operator* of the *construction activity*) in writing prior to the shutdown. If soil disturbance activities are not resumed within 2 years from the date of shutdown, the *owner or operator* shall have the *qualified inspector* perform a final inspection and certify that all disturbed areas have achieved *final stabilization,* and all temporary, structural erosion and sediment control measures have been removed*;* and that all post-construction stormwater management practices have been constructed in conformance with the SWPPP by signing the "*Final Stabilization*" and "Post-Construction Stormwater Management Practice" certification statements on the NOT. The *owner or operator* shall then submit the completed NOT form to the address in Part II.B.1 of this permit.

e. For construction sites that directly *discharge* to one of the 303(d) segments listed in Appendix E or is located in one of the watersheds listed in Appendix C, the *qualified inspector* shall conduct at least two (2) site inspections every seven (7) calendar days. The two (2) inspections shall be separated by a minimum of two (2) full calendar days.

3. At a minimum, the *qualified inspector* shall inspect all erosion and sediment control practices and pollution prevention measures to ensure integrity and effectiveness, all post-construction stormwater management practices under construction to ensure that they are constructed in conformance with the SWPPP, all areas of disturbance that have not achieved *final stabilization,* all points of *discharge* to natural surface waterbodies located within, or immediately adjacent to, the property boundaries of the *construction site*, and all points of *discharge* from the *construction site*.

4. The *qualified inspector* shall prepare an inspection report subsequent to each and every inspection. At a minimum, the inspection report shall include and/or address the following:

a. Date and time of inspection;

b. Name and title of person(s) performing inspection;

c. A description of the weather and soil conditions (e.g. dry, wet, saturated) at the time of the inspection;

d. A description of the condition of the runoff at all points of *discharge* from the *construction site*. This shall include identification of any *discharges* of sediment from the *construction site*. Include *discharges* from conveyance systems (i.e. pipes, culverts, ditches, etc.) and overland flow;

e. A description of the condition of all natural surface waterbodies located within, or immediately adjacent to, the property boundaries of the *construction site* which receive runoff from disturbed areas. This shall include identification of any *discharges* of sediment to the surface waterbody;

f. Identification of all erosion and sediment control practices and pollution prevention measures that need repair or maintenance;

g. Identification of all erosion and sediment control practices and pollution prevention measures that were not installed properly or are not functioning as designed and need to be reinstalled or replaced;

h. Description and sketch of areas with active soil disturbance activity, areas that have been disturbed but are inactive at the time of the inspection, and areas that have been stabilized (temporary and/or final) since the last inspection;

i. Current phase of construction of all post-construction stormwater management practices and identification of all construction that is not in conformance with the SWPPP and technical standards;

j. Corrective action(s) that must be taken to install, repair, replace or maintain erosion and sediment control practices and pollution prevention measures; and to correct deficiencies identified with the construction of the post-construction stormwater management practice(s);

k. Identification and status of all corrective actions that were required by previous inspection; and

l. Digital photographs, with date stamp, that clearly show the condition of all practices that have been identified as needing corrective actions. The *qualified inspector* shall attach paper color copies of the digital photographs to the inspection report being maintained onsite within seven (7) calendar days of the date of the inspection. The *qualified inspector* shall also take digital photographs, with date stamp, that clearly show the condition of the practice(s) after the corrective action has been completed. The *qualified inspector* shall attach paper color copies of the digital photographs to the inspection report that documents the completion of the corrective action work within seven (7) calendar days of that inspection.

5. Within one business day of the completion of an inspection, the *qualified inspector* shall notify the *owner or operator* and appropriate contractor or subcontractor identified in Part III.A.6. of this permit of any corrective actions that need to be taken. The contractor or subcontractor shall begin implementing the corrective actions within one business day of this notification and shall complete the corrective actions in a reasonable time frame.

6. All inspection reports shall be signed by the *qualified inspector.* Pursuant to Part II.D.2. of this permit, the inspection reports shall be maintained on site with the SWPPP.

Part V. TERMINATION OF PERMIT COVERAGE

A. Termination of Permit Coverage

1. An *owner or operator* that is eligible to terminate coverage under this permit must submit a completed NOT form to the address in Part II.B.1 of this permit. The NOT form shall be one which is associated with this permit, signed in accordance with Part VII.H of this permit.

2. An *owner or operator* may terminate coverage when one or more the following conditions have been met:

   a. Total project completion - All *construction activity* identified in the SWPPP has been completed; and all areas of disturbance have achieved *final stabilization*; and all temporary, structural erosion and sediment control measures have been removed; and all post-construction stormwater management practices have been constructed in conformance with the SWPPP and are operational;

   b. Planned shutdown with partial project completion - All soil disturbance activities have ceased; and all areas disturbed as of the project shutdown date have achieved *final stabilization*; and all temporary, structural erosion and sediment control measures have been removed; and all post-construction stormwater management practices required for the completed portion of the project have been constructed in conformance with the SWPPP and are operational;

   c. A new *owner or operator* has obtained coverage under this permit in accordance with Part II.F. of this permit.

   d. The *owner or operator* obtains coverage under an alternative SPDES general permit or an individual SPDES permit.

3. For *construction activities* meeting subdivision 2a. or 2b. of this Part, the *owner or operator* shall have the *qualified inspector* perform a final site inspection prior to submitting the NOT. The *qualified inspector* shall, by signing the "*Final Stabilization*" and "Post-Construction Stormwater Management Practice certification statements on the NOT, certify that all the requirements in Part V.A.2.a. or b. of this permit have been achieved.

4. For *construction activities* that are subject to the requirements of a *regulated, traditional land use control MS4* and meet subdivision 2a. or 2b. of this Part, the *owner or operator* shall have the *regulated, traditional land use control MS4* sign the "MS4 Acceptance" statement on the NOT in accordance with the requirements in Part VII.H. of this permit. The *regulated, traditional land use control MS4* official, by signing this statement, has determined that it is acceptable for the *owner or operator* to submit the NOT in accordance with the requirements of this Part. The *regulated, traditional land use control MS4* can make this determination by performing a final site inspection themselves or by accepting the *qualified inspector*'s final site inspection certification(s) required in Part V.A.3. of this permit.

5. For *construction activities* that require post-construction stormwater management practices and meet subdivision 2a. of this Part, the *owner or operator* must, prior to submitting the NOT, ensure one of the following:

   a. the post-construction stormwater management practice(s) and any right-of-way(s) needed to maintain such practice(s) have been deeded to the municipality in which the practice(s) is located,

b. an executed maintenance agreement is in place with the municipality that will maintain the post-construction stormwater management practice(s),

c. for post-construction stormwater management practices that are privately owned, the *owner or operator* has a mechanism in place that requires operation and maintenance of the practice(s) in accordance with the operation and maintenance plan, such as a deed covenant in the *owner or operator's* deed of record,

d. for post-construction stormwater management practices that are owned by a public or private institution (e.g. school, university, hospital), government agency or authority, or public utility; the *owner or operator* has policy and procedures in place that ensures operation and maintenance of the practices in accordance with the operation and maintenance plan.

Part VI. REPORTING AND RETENTION RECORDS

A. Record Retention

The *owner or operator* shall retain a copy of the NOI, NOI Acknowledgment Letter, SWPPP, MS4 SWPPP Acceptance form and any inspection reports that were prepared in conjunction with this permit for a period of at least five (5) years from the date that the Department receives a complete NOT submitted in accordance with Part V. of this general permit.

B. Addresses

With the exception of the NOI, NOT, and MS4 SWPPP Acceptance form (which must be submitted to the address referenced in Part II.B.1 of this permit), all written correspondence requested by the Department, including individual permit applications, shall be sent to the address of the appropriate DOW Water (SPDES) Program contact at the Regional Office listed in Appendix F.

Part VII. STANDARD PERMIT CONDITIONS

A. Duty to Comply

The *owner or operator* must comply with all conditions of this permit. All contractors and subcontractors associated with the project must comply with the terms of the SWPPP. Any non-compliance with this permit constitutes a violation of the Clean Water

Act (CWA) and the ECL and is grounds for an enforcement action against the *owner or operator* and/or the contractor/subcontractor; permit revocation, suspension or modification; or denial of a permit renewal application. Upon a finding of significant non-compliance with this permit or the applicable SWPPP, the Department may order an immediate stop to all *construction activity* at the site until the non-compliance is remedied. The stop work order shall be in writing, shall describe the non-compliance in detail, and shall be sent to the *owner or operator*.

If any human remains or archaeological remains are encountered during excavation, the *owner or operator* must immediately cease, or cause to cease, all *construction activity* in the area of the remains and notify the appropriate Regional Water Engineer (RWE). *Construction activity* shall not resume until written permission to do so has been received from the RWE.

B. Continuation of the Expired General Permit

This permit expires five (5) years from the effective date. If a new general permit is not issued prior to the expiration of this general permit, an *owner or operator* with coverage under this permit may continue to operate and *discharge* in accordance with the terms and conditions of this general permit, if it is extended pursuant to the State Administrative Procedure Act and 6 NYCRR Part 621, until a new general permit is issued.

C. Enforcement

Failure of the *owner or operator,* its contractors, subcontractors, agents and/or assigns to strictly adhere to any of the permit requirements contained herein shall constitute a violation of this permit. There are substantial criminal, civil, and administrative penalties associated with violating the provisions of this permit. Fines of up to $37,500 per day for each violation and imprisonment for up to fifteen (15) years may be assessed depending upon the nature and degree of the offense.

D. Need to Halt or Reduce Activity Not a Defense

It shall not be a defense for an *owner or operator* in an enforcement action that it would have been necessary to halt or reduce the *construction activity* in order to maintain compliance with the conditions of this permit.

E. Duty to Mitigate

The *owner or operator* and its contractors and subcontractors shall take all reasonable steps to *minimize* or prevent any *discharge* in violation of this permit which has a reasonable likelihood of adversely affecting human health or the environment.

F. Duty to Provide Information

The *owner or operator* shall furnish to the Department, within a reasonable specified time period of a written request, all documentation necessary to demonstrate eligibility and any information to determine compliance with this permit or to determine whether cause exists for modifying or revoking this permit, or suspending or denying coverage under this permit, in accordance with the terms and conditions of this permit. The NOI, SWPPP and inspection reports required by this permit are public documents that the *owner or operator* must make available for review and copying by any person within five (5) business days of the *owner or operator* receiving a written request by any such person to review these documents. Copying of documents will be done at the requester's expense.

G. Other Information

When the *owner or operator* becomes aware that they failed to submit any relevant facts, or submitted incorrect information in the NOI or in any of the documents required by this permit , or have made substantive revisions to the SWPPP (e.g. the scope of the project changes significantly, the type of post-construction stormwater management practice(s) changes, there is a reduction in the sizing of the post-construction stormwater management practice, or there is an increase in the disturbance area or *impervious area*), which were not reflected in the original NOI submitted to the Department, they shall promptly submit such facts or information to the Department using the contact information in Part II.A. of this permit. Failure of the *owner or operator* to correct or supplement any relevant facts within five (5) business days of becoming aware of the deficiency shall constitute a violation of this permit.

H. Signatory Requirements

1. All NOIs and NOTs shall be signed as follows:

    a. For a corporation these forms shall be signed by a responsible corporate officer. For the purpose of this section, a responsible corporate officer means:

(i) a president, secretary, treasurer, or vice-president of the corporation in charge of a principal business function, or any other person who performs similar policy or decision-making functions for the corporation; or

(ii) the manager of one or more manufacturing, production or operating facilities, provided the manager is authorized to make management decisions which govern the operation of the regulated facility including having the explicit or implicit duty of making major capital investment recommendations, and initiating and directing other comprehensive measures to assure long term environmental compliance with environmental laws and regulations; the manager can ensure that the necessary systems are established or actions taken to gather complete and accurate information for permit application requirements; and where authority to sign documents has been assigned or delegated to the manager in accordance with corporate procedures;

b. For a partnership or sole proprietorship these forms shall be signed by a general partner or the proprietor, respectively; or

c. For a municipality, State, Federal, or other public agency these forms shall be signed by either a principal executive officer or ranking elected official. For purposes of this section, a principal executive officer of a Federal agency includes:

(i) the chief executive officer of the agency, or

(ii) a senior executive officer having responsibility for the overall operations of a principal geographic unit of the agency (e.g., Regional Administrators of EPA).

2. The SWPPP and other information requested by the Department shall be signed by a person described in Part VII.H.1. of this permit or by a duly authorized representative of that person. A person is a duly authorized representative only if:

    a. The authorization is made in writing by a person described in Part VII.H.1. of this permit;

    b. The authorization specifies either an individual or a position having responsibility for the overall operation of the regulated facility or activity, such as the position of plant manager, operator of a well or a well field,

superintendent, position of *equivalent* responsibility, or an individual or position having overall responsibility for environmental matters for the company. (A duly authorized representative may thus be either a named individual or any individual occupying a named position) and,

c. The written authorization shall include the name, title and signature of the authorized representative and be attached to the SWPPP.

3. All inspection reports shall be signed by the *qualified inspector* that performs the inspection.

4. The MS4 SWPPP Acceptance form shall be signed by the principal executive officer or ranking elected official from the *regulated, traditional land use control MS4,* or by a duly authorized representative of that person.

   It shall constitute a permit violation if an incorrect and/or improper signatory authorizes any required forms, SWPPP and/or inspection reports.

I. Property Rights

The issuance of this permit does not convey any property rights of any sort, nor any exclusive privileges, nor does it authorize any injury to private property nor any invasion of personal rights, nor any infringement of Federal, State or local laws or regulations. *Owners or operators* must obtain any applicable conveyances, easements, licenses and/or access to real property prior to *commencing construction activity*.

J. Severability

The provisions of this permit are severable, and if any provision of this permit, or the application of any provision of this permit to any circumstance, is held invalid, the application of such provision to other circumstances, and the remainder of this permit shall not be affected thereby.

K. Requirement to Obtain Coverage Under an Alternative Permit

1. The Department may require any owner or operator authorized by this permit to apply for and/or obtain either an individual SPDES permit or another SPDES general permit. When the Department requires any discharger authorized by a general permit to apply for an individual SPDES permit, it shall notify the discharger in writing that a permit application is required. This notice shall

include a brief statement of the reasons for this decision, an application form, a statement setting a time frame for the owner or operator to file the application for an individual SPDES permit, and a deadline, not sooner than 180 days from owner or operator receipt of the notification letter, whereby the authorization to discharge under this general permit shall be terminated. Applications must be submitted to the appropriate Permit Administrator at the Regional Office. The Department may grant additional time upon demonstration, to the satisfaction of the Department, that additional time to apply for an alternative authorization is necessary or where the Department has not provided a permit determination in accordance with Part 621 of this Title.

2. When an individual SPDES permit is issued to a discharger authorized to *discharge* under a general SPDES permit for the same *discharge*(s), the general permit authorization for outfalls authorized under the individual SPDES permit is automatically terminated on the effective date of the individual permit unless termination is earlier in accordance with 6 NYCRR Part 750.

L. Proper Operation and Maintenance

The *owner or operator* shall at all times properly operate and maintain all facilities and systems of treatment and control (and related appurtenances) which are installed or used by the *owner or operator* to achieve compliance with the conditions of this permit and with the requirements of the SWPPP.

M. Inspection and Entry

The *owner or operator* shall allow an authorized representative of the Department, EPA, applicable county health department, or, in the case of a *construction site* which *discharges* through an *MS4*, an authorized representative of the *MS4* receiving the discharge, upon the presentation of credentials and other documents as may be required by law, to:

1. Enter upon the owner's or operator's premises where a regulated facility or activity is located or conducted or where records must be kept under the conditions of this permit;

2. Have access to and copy at reasonable times, any records that must be kept under the conditions of this permit; and

3. Inspect at reasonable times any facilities or equipment (including monitoring and control equipment), practices or operations regulated or required by this permit.

4. Sample or monitor at reasonable times, for purposes of assuring permit compliance or as otherwise authorized by the Act or ECL, any substances or parameters at any location.

N. Permit Actions

This permit may, at any time, be modified, suspended, revoked, or renewed by the Department in accordance with 6 NYCRR Part 621. The filing of a request by the *owner or operator* for a permit modification, revocation and reissuance, termination, a notification of planned changes or anticipated noncompliance does not limit, diminish and/or stay compliance with any terms of this permit.

O. Definitions

Definitions of key terms are included in Appendix A of this permit.

P. Re-Opener Clause

1. If there is evidence indicating potential or realized impacts on water quality due to any stormwater discharge associated with construction activity covered by this permit, the owner or operator of such discharge may be required to obtain an individual permit or alternative general permit in accordance with Part VII.K. of this permit or the permit may be modified to include different limitations and/or requirements.

2. Any Department initiated permit modification, suspension or revocation will be conducted in accordance with 6 NYCRR Part 621, 6 NYCRR 750-1.18, and 6 NYCRR 750-1.20.

Q. Penalties for Falsification of Forms and Reports

In accordance with 6NYCRR Part 750-2.4 and 750-2.5, any person who knowingly makes any false material statement, representation, or certification in any application, record, report or other document filed or required to be maintained under this permit, including reports of compliance or noncompliance shall, upon conviction, be punished in accordance with ECL §71-1933 and or Articles 175 and 210 of the New York State Penal Law.

R. Other Permits

Nothing in this permit relieves the *owner or operator* from a requirement to obtain any other permits required by law.

APPENDIX A – Acronyms and Definitions

Acronyms

APO – Agency Preservation Officer
BMP – Best Management Practice
CPESC – Certified Professional in Erosion and Sediment Control
Cpv – Channel Protection Volume
CWA – Clean Water Act (or the Federal Water Pollution Control Act, 33 U.S.C. §1251 et seq)
DOW – Division of Water
EAF – Environmental Assessment Form
ECL - Environmental Conservation Law
EPA – U. S. Environmental Protection Agency
HSG – Hydrologic Soil Group
MS4 – Municipal Separate Storm Sewer System
NOI – Notice of Intent
NOT – Notice of Termination
NPDES – National Pollutant Discharge Elimination System
OPRHP – Office of Parks, Recreation and Historic Places
Qf – Extreme Flood
Qp – Overbank Flood
RRv – Runoff Reduction Volume
RWE – Regional Water Engineer
SEQR – State Environmental Quality Review
SEQRA - State Environmental Quality Review Act
SHPA – State Historic Preservation Act
SPDES – State Pollutant Discharge Elimination System
SWPPP – Stormwater Pollution Prevention Plan
TMDL – Total Maximum Daily Load
UPA – Uniform Procedures Act
USDA – United States Department of Agriculture
WQv – Water Quality Volume

Definitions

All definitions in this section are solely for the purposes of this permit.

Agricultural Building – a structure designed and constructed to house farm implements, hay, grain, poultry, livestock or other horticultural products; excluding any structure designed, constructed or used, in whole or in part, for human habitation, as a place of employment where agricultural products are processed, treated or packaged, or as a place used by the public.

Agricultural Property –means the land for construction of a barn, *agricultural building*, silo, stockyard, pen or other structural practices identified in Table II in the "Agricultural Management Practices Catalog for Nonpoint Source Pollution in New York State" prepared by the Department in cooperation with agencies of New York Nonpoint Source Coordinating Committee (dated June 2007).

Alter Hydrology from Pre to Post-Development Conditions - means the post-development peak flow rate(s) has increased by more than 5% of the pre-developed condition for the design storm of interest (e.g. 10 yr and 100 yr).

Combined Sewer - means a sewer that is designed to collect and convey both "sewage" and "stormwater".

Commence (Commencement of) Construction Activities - means the initial disturbance of soils associated with clearing, grading or excavation activities; or other construction related activities that disturb or expose soils such as demolition, stockpiling of fill material, and the initial installation of erosion and sediment control practices required in the SWPPP. See definition for "*Construction Activity(ies)*" also.

Construction Activity(ies) - means any clearing, grading, excavation, filling, demolition or stockpiling activities that result in soil disturbance. Clearing activities can include, but are not limited to, logging equipment operation, the cutting and skidding of trees, stump removal and/or brush root removal. Construction activity does not include routine maintenance that is performed to maintain the original line and grade, hydraulic capacity, or original purpose of a facility.

Construction Site – means the land area where *construction activity(ies)* will occur. See definition for "*Commence (Commencement of) Construction Activities"* and "*Larger Common Plan of Development or Sale" also.*

Dewatering – means the act of draining rainwater and/or groundwater from building foundations, vaults or excavations/trenches.

Direct Discharge (to a specific surface waterbody) - means that runoff flows from a *construction site* by overland flow and the first point of discharge is the specific surface waterbody, or runoff flows from a *construction site* to a separate storm sewer system

and the first point of discharge from the separate storm sewer system is the specific surface waterbody.

Discharge(s) - means any addition of any pollutant to waters of the State through an outlet or *point source*.

Embankment –means an earthen or rock slope that supports a road/highway.

Endangered or Threatened Species – see 6 NYCRR Part 182 of the Department's rules and regulations for definition of terms and requirements.

Environmental Conservation Law (ECL) - means chapter 43-B of the Consolidated Laws of the State of New York, entitled the Environmental Conservation Law.

Equivalent (Equivalence) – means that the practice or measure meets all the performance, longevity, maintenance, and safety objectives of the technical standard and will provide an equal or greater degree of water quality protection.

Final Stabilization - means that all soil disturbance activities have ceased and a uniform, perennial vegetative cover with a density of eighty (80) percent over the entire pervious surface has been established; or other equivalent stabilization measures, such as permanent landscape mulches, rock rip-rap or washed/crushed stone have been applied on all disturbed areas that are not covered by permanent structures, concrete or pavement.

General SPDES permit - means a SPDES permit issued pursuant to 6 NYCRR Part 750-1.21 and Section 70-0117 of the ECL authorizing a category of discharges.

Groundwater(s) - means waters in the saturated zone. The saturated zone is a subsurface zone in which all the interstices are filled with water under pressure greater than that of the atmosphere. Although the zone may contain gas-filled interstices or interstices filled with fluids other than water, it is still considered saturated.

Historic Property – means any building, structure, site, object or district that is listed on the State or National Registers of Historic Places or is determined to be eligible for listing on the State or National Registers of Historic Places.

Impervious Area (Cover) - means all impermeable surfaces that cannot effectively infiltrate rainfall. This includes paved, concrete and gravel surfaces (i.e. parking lots, driveways, roads, runways and sidewalks); building rooftops and miscellaneous impermeable structures such as patios, pools, and sheds.

Infeasible – means not technologically possible, or not economically practicable and achievable in light of best industry practices.

Larger Common Plan of Development or Sale - means a contiguous area where multiple separate and distinct *construction activities* are occurring, or will occur, under one plan. The term "plan" in "larger common plan of development or sale" is broadly defined as any announcement or piece of documentation (including a sign, public notice or hearing, marketing plan, advertisement, drawing, permit application, State Environmental Quality Review Act (SEQRA) environmental assessment form or other documents, zoning request, computer design, etc.) or physical demarcation (including boundary signs, lot stakes, surveyor markings, etc.) indicating that *construction activities* may occur on a specific plot.

For discrete construction projects that are located within a larger common plan of development or sale that are at least 1/4 mile apart, each project can be treated as a separate plan of development or sale provided any interconnecting road, pipeline or utility project that is part of the same "common plan" is not concurrently being disturbed.

Minimize – means reduce and/or eliminate to the extent achievable using control measures (including best management practices) that are technologically available and economically practicable and achievable in light of best industry practices.

Municipal Separate Storm Sewer (MS4) - a conveyance or system of conveyances (including roads with drainage systems, municipal streets, catch basins, curbs, gutters, ditches, man-made channels, or storm drains):

(i) Owned or operated by a State, city, town, borough, county, parish, district, association, or other public body (created by or pursuant to State law) having jurisdiction over disposal of sewage, industrial wastes, stormwater, or other wastes, including special districts under State law such as a sewer district, flood control district or drainage district, or similar entity, or an Indian tribe or an authorized Indian tribal organization, or a designated and approved management agency under section 208 of the CWA that discharges to surface waters of the State*;*
(ii) Designed or used for collecting or conveying stormwater;
(iii) Which is not a *combined sewer*; and
(iv) Which is not part of a Publicly Owned Treatment Works (POTW) as defined at 40 CFR 122.2.

National Pollutant Discharge Elimination System (NPDES) - means the national system for the issuance of wastewater and stormwater permits under the Federal Water Pollution Control Act (Clean Water Act).

Natural Buffer –means an undisturbed area with natural cover running along a surface water (e.g. wetland, stream, river, lake, etc.).

New Development – means any land disturbance that does not meet the definition of Redevelopment Activity included in this appendix.

New York State Erosion and Sediment Control Certificate Program – a certificate program that establishes and maintains a process to identify and recognize individuals who are capable of developing, designing, inspecting and maintaining erosion and sediment control plans on projects that disturb soils in New York State. The certificate program is administered by the New York State Conservation District Employees Association.

NOI Acknowledgment Letter - means the letter that the Department sends to an owner or operator to acknowledge the Department's receipt and acceptance of a complete Notice of Intent. This letter documents the owner's or operator's authorization to discharge in accordance with the general permit for stormwater discharges from *construction activity.*

Nonpoint Source - means any source of water pollution or pollutants which is not a discrete conveyance or *point source* permitted pursuant to Title 7 or 8 of Article 17 of the Environmental Conservation Law (see ECL Section 17-1403).

Overbank –means flow events that exceed the capacity of the stream channel and spill out into the adjacent floodplain.

Owner or Operator - means the person, persons or legal entity which owns or leases the property on which the *construction activity* is occurring; an entity that has operational control over the construction plans and specifications, including the ability to make modifications to the plans and specifications; and/or an entity that has day-to-day operational control of those activities at a project that are necessary to ensure compliance with the permit conditions.

Performance Criteria – means the design criteria listed under the "Required Elements" sections in Chapters 5, 6 and 10 of the technical standard, New York State Stormwater Management Design Manual, dated January 2015. It does not include the Sizing Criteria (i.e. WQv, RRv, Cpv, Qp and Qf) in Part I.C.2. of the permit.

Point Source - means any discernible, confined and discrete conveyance, including but not limited to any pipe, ditch, channel, tunnel, conduit, well, discrete fissure, container, rolling stock, concentrated animal feeding operation, vessel or other floating craft, or landfill leachate collection system from which *pollutants* are or may be discharged.

Pollutant - means dredged spoil, filter backwash, solid waste, incinerator residue, sewage, garbage, sewage sludge, munitions, chemical wastes, biological materials, radioactive materials, heat, wrecked or discarded equipment, rock, sand and industrial, municipal, agricultural waste and ballast discharged into water; which may cause or might reasonably be expected to cause pollution of the waters of the state in contravention of the standards or guidance values adopted as provided in 6 NYCRR Parts 700 et seq .

Qualified Inspector - means a person that is knowledgeable in the principles and practices of erosion and sediment control, such as a licensed Professional Engineer, Certified Professional in Erosion and Sediment Control (CPESC), Registered Landscape Architect, New York State Erosion and Sediment Control Certificate Program holder or other Department endorsed individual(s).

It can also mean someone working under the direct supervision of, and at the same company as, the licensed Professional Engineer or Registered Landscape Architect, provided that person has training in the principles and practices of erosion and sediment control. Training in the principles and practices of erosion and sediment control means that the individual working under the direct supervision of the licensed Professional Engineer or Registered Landscape Architect has received four (4) hours of Department endorsed training in proper erosion and sediment control principles from a Soil and Water Conservation District, or other Department endorsed entity. After receiving the initial training, the individual working under the direct supervision of the licensed Professional Engineer or Registered Landscape Architect shall receive four (4) hours of training every three (3) years.

It can also mean a person that meets the *Qualified Professional* qualifications in addition to the *Qualified Inspector* qualifications.

Note: Inspections of any post-construction stormwater management practices that include structural components, such as a dam for an impoundment, shall be performed by a licensed Professional Engineer.

Qualified Professional - means a person that is knowledgeable in the principles and practices of stormwater management and treatment, such as a licensed Professional Engineer, Registered Landscape Architect or other Department endorsed individual(s). Individuals preparing SWPPPs that require the post-construction stormwater management practice component must have an understanding of the principles of hydrology, water quality management practice design, water quantity control design, and, in many cases, the principles of hydraulics. All components of the SWPPP that involve the practice of engineering, as defined by the NYS Education Law (see Article 145), shall be prepared by, or under the direct supervision of, a professional engineer licensed to practice in the State of New York.

Redevelopment Activity(ies) – means the disturbance and reconstruction of existing impervious area, including impervious areas that were removed from a project site within five (5) years of preliminary project plan submission to the local government (i.e. site plan, subdivision, etc.).

Regulated, Traditional Land Use Control MS4 - means a city, town or village with land use control authority that is authorized to discharge under New York State DEC's

SPDES General Permit For Stormwater Discharges from Municipal Separate Stormwater Sewer Systems (MS4s) or the City of New York's Individual SPDES Permit for their Municipal Separate Storm Sewer Systems (NY-0287890).

Routine Maintenance Activity - means *construction activity* that is performed to maintain the original line and grade, hydraulic capacity, or original purpose of a facility, including, but not limited to:

- Re-grading of gravel roads or parking lots,
- Cleaning and shaping of existing roadside ditches and culverts that maintains the approximate original line and grade, and hydraulic capacity of the ditch,
- Cleaning and shaping of existing roadside ditches that does not maintain the approximate original grade, hydraulic capacity and purpose of the ditch if the changes to the line and grade, hydraulic capacity or purpose of the ditch are installed to improve water quality and quantity controls (e.g. installing grass lined ditch),
- Placement of aggregate shoulder backing that stabilizes the transition between the road shoulder and the ditch or *embankment*,
- Full depth milling and filling of existing asphalt pavements, replacement of concrete pavement slabs, and similar work that does not expose soil or disturb the bottom six (6) inches of subbase material,
- Long-term use of equipment storage areas at or near highway maintenance facilities,
- Removal of sediment from the edge of the highway to restore a previously existing sheet-flow drainage connection from the highway surface to the highway ditch or *embankment*,
- Existing use of Canal Corp owned upland disposal sites for the canal, and
- Replacement of curbs, gutters, sidewalks and guide rail posts.

Site limitations – means site conditions that prevent the use of an infiltration technique and or infiltration of the total WQv. Typical site limitations include: seasonal high groundwater, shallow depth to bedrock, and soils with an infiltration rate less than 0.5 inches/hour. The existence of site limitations shall be confirmed and documented using actual field testing (i.e. test pits, soil borings, and infiltration test) or using information from the most current United States Department of Agriculture (USDA) Soil Survey for the County where the project is located.

Sizing Criteria – means the criteria included in Part I.C.2 of the permit that are used to size post-construction stormwater management control practices. The criteria include; Water Quality Volume (WQv), Runoff Reduction Volume (RRv), Channel Protection Volume (Cpv), *Overbank* Flood (Qp), and Extreme Flood (Qf).

State Pollutant Discharge Elimination System (SPDES) - means the system established pursuant to Article 17 of the ECL and 6 NYCRR Part 750 for issuance of permits authorizing discharges to the waters of the state.

Steep Slope – means land area designated on the current United States Department of Agriculture ("USDA") Soil Survey as Soil Slope Phase "D", (provided the map unit name is inclusive of slopes greater than 25%) , or Soil Slope Phase E or F, (regardless of the map unit name), or a combination of the three designations.

Streambank – as used in this permit, means the terrain alongside the bed of a creek or stream. The bank consists of the sides of the channel, between which the flow is confined.

Stormwater Pollution Prevention Plan (SWPPP) – means a project specific report, including construction drawings, that among other things: describes the construction activity(ies), identifies the potential sources of pollution at the *construction site*; describes and shows the stormwater controls that will be used to control the pollutants (i.e. erosion and sediment controls; for many projects, includes post-construction stormwater management controls); and identifies procedures the *owner or operator* will implement to comply with the terms and conditions of the permit. See Part III of the permit for a complete description of the information that must be included in the SWPPP.

Surface Waters of the State - shall be construed to include lakes, bays, sounds, ponds, impounding reservoirs, springs, rivers, streams, creeks, estuaries, marshes, inlets, canals, the Atlantic ocean within the territorial seas of the state of New York and all other bodies of surface water, natural or artificial, inland or coastal, fresh or salt, public or private (except those private waters that do not combine or effect a junction with natural surface waters), which are wholly or partially within or bordering the state or within its jurisdiction. Waters of the state are further defined in 6 NYCRR Parts 800 to 941.

Temporarily Ceased – means that an existing disturbed area will not be disturbed again within 14 calendar days of the previous soil disturbance.

Temporary Stabilization - means that exposed soil has been covered with material(s) as set forth in the technical standard, New York Standards and Specifications for Erosion and Sediment Control, to prevent the exposed soil from eroding. The materials can include, but are not limited to, mulch, seed and mulch, and erosion control mats (e.g. jute twisted yarn, excelsior wood fiber mats).

Total Maximum Daily Loads (TMDLs) - A TMDL is the sum of the allowable loads of a single pollutant from all contributing point and *nonpoint source*s. It is a calculation of the maximum amount of a pollutant that a waterbody can receive on a daily basis and still meet *water quality standard*s, and an allocation of that amount to the pollutant's sources. A TMDL stipulates wasteload allocations (WLAs) for *point source* discharges, load allocations (LAs) for *nonpoint source*s, and a margin of safety (MOS).

Trained Contractor - means an employee from the contracting (construction) company, identified in Part III.A.6., that has received four (4) hours of Department endorsed

training in proper erosion and sediment control principles from a Soil and Water Conservation District, or other Department endorsed entity. After receiving the initial training, the *trained contractor* shall receive four (4) hours of training every three (3) years.

It can also mean an employee from the contracting (construction) company, identified in Part III.A.6., that meets the *qualified inspector* qualifications (e.g. licensed Professional Engineer, Certified Professional in Erosion and Sediment Control (CPESC), Registered Landscape Architect, New York State Erosion and Sediment Control Certificate Program holder, or someone working under the direct supervision of, and at the same company as, the licensed Professional Engineer or Registered Landscape Architect, provided they have received four (4) hours of Department endorsed training in proper erosion and sediment control principles from a Soil and Water Conservation District, or other Department endorsed entity).

The *trained contractor* is responsible for the day to day implementation of the SWPPP.

Uniform Procedures Act (UPA) Permit - means a permit required under 6 NYCRR Part 621 of the Environmental Conservation Law (ECL), Article 70.

Water Quality Standard - means such measures of purity or quality for any waters in relation to their reasonable and necessary use as promulgated in 6 NYCRR Part 700 et seq.

APPENDIX B – Required SWPPP Components by Project Type

Table 1
Construction Activities that Require the Preparation of a SWPPP That Only Includes Erosion and Sediment Controls

The following construction activities that involve soil disturbances of one (1) or more acres of land, but less than five (5) acres: • Single family home <u>not</u> located in one of the watersheds listed in Appendix C or <u>not</u> *directly discharging* to one of the 303(d) segments listed in Appendix E • Single family residential subdivisions with 25% or less impervious cover at total site build-out and <u>not</u> located in one of the watersheds listed in Appendix C and <u>not</u> directly discharging to one of the 303(d) segments listed in Appendix E • Construction of a barn or other *agricultural building*, silo, stock yard or pen.
The following construction activities that involve soil disturbances between five thousand (5000) square feet and one (1) acre of land: All construction activities located in the watersheds identified in Appendix D that involve soil disturbances between five thousand (5,000) square feet and one (1) acre of land.
The following construction activities that involve soil disturbances of one (1) or more acres of land: • Installation of underground, linear utilities; such as gas lines, fiber-optic cable, cable TV, electric, telephone, sewer mains, and water mains • Environmental enhancement projects, such as wetland mitigation projects, stormwater retrofits and stream restoration projects • Pond construction • Linear bike paths running through areas with vegetative cover, including bike paths surfaced with an impervious cover • Cross-country ski trails and walking/hiking trails • Sidewalk, bike path or walking path projects, surfaced with an impervious cover, that are not part of residential, commercial or institutional development; • Sidewalk, bike path or walking path projects, surfaced with an impervious cover, that include incidental shoulder or curb work along an existing highway to support construction of the sidewalk, bike path or walking path. • Slope stabilization projects • Slope flattening that changes the grade of the site, but does not significantly change the runoff characteristics

Table 1 (Continued) CONSTRUCTION ACTIVITIES THAT REQUIRE THE PREPARATION OF A SWPPP THAT ONLY INCLUDES EROSION AND SEDIMENT CONTROLS

The following construction activities that involve soil disturbances of one (1) or more acres of land:

- Spoil areas that will be covered with vegetation
- Vegetated open space projects (i.e. recreational parks, lawns, meadows, fields, downhill ski trails) excluding projects that *alter hydrology from pre to post development* conditions,
- Athletic fields (natural grass) that do not include the construction or reconstruction of *impervious area* and do not *alter hydrology from pre to post development* conditions
- Demolition project where vegetation will be established, and no redevelopment is planned
- Overhead electric transmission line project that does not include the construction of permanent access roads or parking areas surfaced with *impervious cover*
- Structural practices as identified in Table II in the "Agricultural Management Practices Catalog for Nonpoint Source Pollution in New York State", excluding projects that involve soil disturbances of greater than five acres and construction activities that include the construction or reconstruction of impervious area
- Temporary access roads, median crossovers, detour roads, lanes, or other temporary impervious areas that will be restored to pre-construction conditions once the construction activity is complete

Table 2
CONSTRUCTION ACTIVITIES THAT REQUIRE THE PREPARATION OF A SWPPP THAT INCLUDES POST-CONSTRUCTION STORMWATER MANAGEMENT PRACTICES

The following construction activities that involve soil disturbances of one (1) or more acres of land:

- Single family home located in one of the watersheds listed in Appendix C or *directly discharging* to one of the 303(d) segments listed in Appendix E
- Single family home that disturbs five (5) or more acres of land
- Single family residential subdivisions located in one of the watersheds listed in Appendix C or *directly discharging* to one of the 303(d) segments listed in Appendix E
- Single family residential subdivisions that involve soil disturbances of between one (1) and five (5) acres of land with greater than 25% impervious cover at total site build-out
- Single family residential subdivisions that involve soil disturbances of five (5) or more acres of land, and single family residential subdivisions that involve soil disturbances of less than five (5) acres that are part of a larger common plan of development or sale that will ultimately disturb five or more acres of land
- Multi-family residential developments; includes duplexes, townhomes, condominiums, senior housing complexes, apartment complexes, and mobile home parks
- Airports
- Amusement parks
- Breweries, cideries, and wineries, including establishments constructed on agricultural land
- Campgrounds
- Cemeteries that include the construction or reconstruction of impervious area (>5% of disturbed area) or *alter the hydrology from pre to post development* conditions
- Commercial developments
- Churches and other places of worship
- Construction of a barn or other *agricultural building* (e.g. silo) and structural practices as identified in Table II in the "Agricultural Management Practices Catalog for Nonpoint Source Pollution in New York State" that include the construction or reconstruction of *impervious area*, excluding projects that involve soil disturbances of less than five acres.
- Golf courses
- Institutional development; includes hospitals, prisons, schools and colleges
- Industrial facilities; includes industrial parks
- Landfills
- Municipal facilities; includes highway garages, transfer stations, office buildings, POTW's, water treatment plants, and water storage tanks
- Office complexes
- Playgrounds that include the construction or reconstruction of impervious area
- Sports complexes
- Racetracks; includes racetracks with earthen (dirt) surface
- Road construction or reconstruction, including roads constructed as part of the construction activities listed in Table 1

Table 2 (Continued)

CONSTRUCTION ACTIVITIES THAT REQUIRE THE PREPARATION OF A SWPPP THAT INCLUDES POST-CONSTRUCTION STORMWATER MANAGEMENT PRACTICES

The following construction activities that involve soil disturbances of one (1) or more acres of land:

- Parking lot construction or reconstruction, including parking lots constructed as part of the construction activities listed in Table 1
- Athletic fields (natural grass) that include the construction or reconstruction of impervious area (>5% of disturbed area) or *alter the hydrology from pre to post development* conditions
- Athletic fields with artificial turf
- Permanent access roads, parking areas, substations, compressor stations and well drilling pads, surfaced with *impervious cover,* and constructed as part of an over-head electric transmission line project, wind-power project, cell tower project, oil or gas well drilling project, sewer or water main project or other linear utility project
- Sidewalk, bike path or walking path projects, surfaced with an impervious cover, that are part of a residential, commercial or institutional development
- Sidewalk, bike path or walking path projects, surfaced with an impervious cover, that are part of a highway construction or reconstruction project
- All other construction activities that include the construction or reconstruction of *impervious area* or *alter the hydrology from pre to post development* conditions, and are not listed in Table 1

APPENDIX C – Watersheds Requiring Enhanced Phosphorus Removal

Watersheds where *owners or operators* of construction activities identified in Table 2 of Appendix B must prepare a SWPPP that includes post-construction stormwater management practices designed in conformance with the Enhanced Phosphorus Removal Standards included in the technical standard, New York State Stormwater Management Design Manual ("Design Manual").

- Entire New York City Watershed located east of the Hudson River - Figure 1
- Onondaga Lake Watershed - Figure 2
- Greenwood Lake Watershed -Figure 3
- Oscawana Lake Watershed – Figure 4
- Kinderhook Lake Watershed – Figure 5

Figure 1 - New York City Watershed East of the Hudson



Figure 2 - Onondaga Lake Watershed

Figure 3 - Greenwood Lake Watershed



Figure 4 - Oscawana Lake Watershed



Figure 5 - Kinderhook Lake Watershed



APPENDIX D – Watersheds with Lower Disturbance Threshold

Watersheds where *owners or operators* of construction activities that involve soil disturbances between five thousand (5000) square feet and one (1) acre of land must obtain coverage under this permit.

Entire New York City Watershed that is located east of the Hudson River - See Figure 1 in Appendix C

APPENDIX E – 303(d) Segments Impaired by Construction Related Pollutant(s)

List of 303(d) segments impaired by pollutants related to *construction activity* (e.g. silt, sediment or nutrients). The list was developed using "The Final New York State 2016 Section 303(d) List of Impaired Waters Requiring a TMDL/Other Strategy" dated November 2016. *Owners or operators* of single family home and single family residential subdivisions with 25% or less total impervious cover at total site build-out that involve soil disturbances of one or more acres of land, but less than 5 acres, and *directly discharge* to one of the listed segments below shall prepare a SWPPP that includes post-construction stormwater management practices designed in conformance with the New York State Stormwater Management Design Manual ("Design Manual"), dated January 2015.

COUNTY	WATERBODY	POLLUTANT
Albany	Ann Lee (Shakers) Pond, Stump Pond	Nutrients
Albany	Basic Creek Reservoir	Nutrients
Allegany	Amity Lake, Saunders Pond	Nutrients
Bronx	Long Island Sound, Bronx	Nutrients
Bronx	Van Cortlandt Lake	Nutrients
Broome	Fly Pond, Deer Lake, Sky Lake	Nutrients
Broome	Minor Tribs to Lower Susquehanna (north)	Nutrients
Broome	Whitney Point Lake/Reservoir	Nutrients
Cattaraugus	Allegheny River/Reservoir	Nutrients
Cattaraugus	Beaver (Alma) Lake	Nutrients
Cattaraugus	Case Lake	Nutrients
Cattaraugus	Linlyco/Club Pond	Nutrients
Cayuga	Duck Lake	Nutrients
Cayuga	Little Sodus Bay	Nutrients
Chautauqua	Bear Lake	Nutrients
Chautauqua	Chadakoin River and tribs	Nutrients
Chautauqua	Chautauqua Lake, North	Nutrients
Chautauqua	Chautauqua Lake, South	Nutrients
Chautauqua	Findley Lake	Nutrients
Chautauqua	Hulburt/Clymer Pond	Nutrients
Clinton	Great Chazy River, Lower, Main Stem	Silt/Sediment
Clinton	Lake Champlain, Main Lake, Middle	Nutrients
Clinton	Lake Champlain, Main Lake, North	Nutrients
Columbia	Kinderhook Lake	Nutrients
Columbia	Robinson Pond	Nutrients
Cortland	Dean Pond	Nutrients

Dutchess	Fall Kill and tribs	Nutrients
Dutchess	Hillside Lake	Nutrients
Dutchess	Wappingers Lake	Nutrients
Dutchess	Wappingers Lake	Silt/Sediment
Erie	Beeman Creek and tribs	Nutrients
Erie	Ellicott Creek, Lower, and tribs	Silt/Sediment
Erie	Ellicott Creek, Lower, and tribs	Nutrients
Erie	Green Lake	Nutrients
Erie	Little Sister Creek, Lower, and tribs	Nutrients
Erie	Murder Creek, Lower, and tribs	Nutrients
Erie	Rush Creek and tribs	Nutrients
Erie	Scajaquada Creek, Lower, and tribs	Nutrients
Erie	Scajaquada Creek, Middle, and tribs	Nutrients
Erie	Scajaquada Creek, Upper, and tribs	Nutrients
Erie	South Branch Smoke Cr, Lower, and tribs	Silt/Sediment
Erie	South Branch Smoke Cr, Lower, and tribs	Nutrients
Essex	Lake Champlain, Main Lake, South	Nutrients
Essex	Lake Champlain, South Lake	Nutrients
Essex	Willsboro Bay	Nutrients
Genesee	Bigelow Creek and tribs	Nutrients
Genesee	Black Creek, Middle, and minor tribs	Nutrients
Genesee	Black Creek, Upper, and minor tribs	Nutrients
Genesee	Bowen Brook and tribs	Nutrients
Genesee	LeRoy Reservoir	Nutrients
Genesee	Oak Orchard Cr, Upper, and tribs	Nutrients
Genesee	Tonawanda Creek, Middle, Main Stem	Nutrients
Greene	Schoharie Reservoir	Silt/Sediment
Greene	Sleepy Hollow Lake	Silt/Sediment
Herkimer	Steele Creek tribs	Silt/Sediment
Herkimer	Steele Creek tribs	Nutrients
Jefferson	Moon Lake	Nutrients
Kings	Hendrix Creek	Nutrients
Kings	Prospect Park Lake	Nutrients
Lewis	Mill Creek/South Branch, and tribs	Nutrients
Livingston	Christie Creek and tribs	Nutrients
Livingston	Conesus Lake	Nutrients
Livingston	Mill Creek and minor tribs	Silt/Sediment
Monroe	Black Creek, Lower, and minor tribs	Nutrients
Monroe	Buck Pond	Nutrients
Monroe	Cranberry Pond	Nutrients

Monroe	Lake Ontario Shoreline, Western	Nutrients
Monroe	Long Pond	Nutrients
Monroe	Mill Creek and tribs	Nutrients
Monroe	Mill Creek/Blue Pond Outlet and tribs	Nutrients
Monroe	Minor Tribs to Irondequoit Bay	Nutrients
Monroe	Rochester Embayment - East	Nutrients
Monroe	Rochester Embayment - West	Nutrients
Monroe	Shipbuilders Creek and tribs	Nutrients
Monroe	Thomas Creek/White Brook and tribs	Nutrients
Nassau	Beaver Lake	Nutrients
Nassau	Camaans Pond	Nutrients
Nassau	East Meadow Brook, Upper, and tribs	Silt/Sediment
Nassau	East Rockaway Channel	Nutrients
Nassau	Grant Park Pond	Nutrients
Nassau	Hempstead Bay	Nutrients
Nassau	Hempstead Lake	Nutrients
Nassau	Hewlett Bay	Nutrients
Nassau	Hog Island Channel	Nutrients
Nassau	Long Island Sound, Nassau County Waters	Nutrients
Nassau	Massapequa Creek and tribs	Nutrients
Nassau	Milburn/Parsonage Creeks, Upp, and tribs	Nutrients
Nassau	Reynolds Channel, west	Nutrients
Nassau	Tidal Tribs to Hempstead Bay	Nutrients
Nassau	Tribs (fresh) to East Bay	Nutrients
Nassau	Tribs (fresh) to East Bay	Silt/Sediment
Nassau	Tribs to Smith/Halls Ponds	Nutrients
Nassau	Woodmere Channel	Nutrients
New York	Harlem Meer	Nutrients
New York	The Lake in Central Park	Nutrients
Niagara	Bergholtz Creek and tribs	Nutrients
Niagara	Hyde Park Lake	Nutrients
Niagara	Lake Ontario Shoreline, Western	Nutrients
Niagara	Lake Ontario Shoreline, Western	Nutrients
Oneida	Ballou, Nail Creeks and tribs	Nutrients
Onondaga	Harbor Brook, Lower, and tribs	Nutrients
Onondaga	Ley Creek and tribs	Nutrients
Onondaga	Minor Tribs to Onondaga Lake	Nutrients
Onondaga	Ninemile Creek, Lower, and tribs	Nutrients
Onondaga	Onondaga Creek, Lower, and tribs	Nutrients
Onondaga	Onondaga Creek, Middle, and tribs	Nutrients

Onondaga	Onondaga Lake, northern end	Nutrients
Onondaga	Onondaga Lake, southern end	Nutrients
Ontario	Great Brook and minor tribs	Silt/Sediment
Ontario	Great Brook and minor tribs	Nutrients
Ontario	Hemlock Lake Outlet and minor tribs	Nutrients
Ontario	Honeoye Lake	Nutrients
Orange	Greenwood Lake	Nutrients
Orange	Monhagen Brook and tribs	Nutrients
Orange	Orange Lake	Nutrients
Orleans	Lake Ontario Shoreline, Western	Nutrients
Orleans	Lake Ontario Shoreline, Western	Nutrients
Oswego	Lake Neatahwanta	Nutrients
Oswego	Pleasant Lake	Nutrients
Putnam	Bog Brook Reservoir	Nutrients
Putnam	Boyd Corners Reservoir	Nutrients
Putnam	Croton Falls Reservoir	Nutrients
Putnam	Diverting Reservoir	Nutrients
Putnam	East Branch Reservoir	Nutrients
Putnam	Lake Carmel	Nutrients
Putnam	Middle Branch Reservoir	Nutrients
Putnam	Oscawana Lake	Nutrients
Putnam	Palmer Lake	Nutrients
Putnam	West Branch Reservoir	Nutrients
Queens	Bergen Basin	Nutrients
Queens	Flushing Creek/Bay	Nutrients
Queens	Jamaica Bay, Eastern, and tribs (Queens)	Nutrients
Queens	Kissena Lake	Nutrients
Queens	Meadow Lake	Nutrients
Queens	Willow Lake	Nutrients
Rensselaer	Nassau Lake	Nutrients
Rensselaer	Snyders Lake	Nutrients
Richmond	Grasmere Lake/Bradys Pond	Nutrients
Rockland	Congers Lake, Swartout Lake	Nutrients
Rockland	Rockland Lake	Nutrients
Saratoga	Ballston Lake	Nutrients
Saratoga	Dwaas Kill and tribs	Silt/Sediment
Saratoga	Dwaas Kill and tribs	Nutrients
Saratoga	Lake Lonely	Nutrients
Saratoga	Round Lake	Nutrients
Saratoga	Tribs to Lake Lonely	Nutrients

Schenectady	Collins Lake	Nutrients
Schenectady	Duane Lake	Nutrients
Schenectady	Mariaville Lake	Nutrients
Schoharie	Engleville Pond	Nutrients
Schoharie	Summit Lake	Nutrients
Seneca	Reeder Creek and tribs	Nutrients
St.Lawrence	Black Lake Outlet/Black Lake	Nutrients
St.Lawrence	Fish Creek and minor tribs	Nutrients
Steuben	Smith Pond	Nutrients
Suffolk	Agawam Lake	Nutrients
Suffolk	Big/Little Fresh Ponds	Nutrients
Suffolk	Canaan Lake	Silt/Sediment
Suffolk	Canaan Lake	Nutrients
Suffolk	Flanders Bay, West/Lower Sawmill Creek	Nutrients
Suffolk	Fresh Pond	Nutrients
Suffolk	Great South Bay, East	Nutrients
Suffolk	Great South Bay, Middle	Nutrients
Suffolk	Great South Bay, West	Nutrients
Suffolk	Lake Ronkonkoma	Nutrients
Suffolk	Long Island Sound, Suffolk County, West	Nutrients
Suffolk	Mattituck (Marratooka) Pond	Nutrients
Suffolk	Meetinghouse/Terrys Creeks and tribs	Nutrients
Suffolk	Mill and Seven Ponds	Nutrients
Suffolk	Millers Pond	Nutrients
Suffolk	Moriches Bay, East	Nutrients
Suffolk	Moriches Bay, West	Nutrients
Suffolk	Peconic River, Lower, and tidal tribs	Nutrients
Suffolk	Quantuck Bay	Nutrients
Suffolk	Shinnecock Bay and Inlet	Nutrients
Suffolk	Tidal tribs to West Moriches Bay	Nutrients
Sullivan	Bodine, Montgomery Lakes	Nutrients
Sullivan	Davies Lake	Nutrients
Sullivan	Evens Lake	Nutrients
Sullivan	Pleasure Lake	Nutrients
Tompkins	Cayuga Lake, Southern End	Nutrients
Tompkins	Cayuga Lake, Southern End	Silt/Sediment
Tompkins	Owasco Inlet, Upper, and tribs	Nutrients
Ulster	Ashokan Reservoir	Silt/Sediment
Ulster	Esopus Creek, Upper, and minor tribs	Silt/Sediment
Warren	Hague Brook and tribs	Silt/Sediment

Warren	Huddle/Finkle Brooks and tribs	Silt/Sediment
Warren	Indian Brook and tribs	Silt/Sediment
Warren	Lake George	Silt/Sediment
Warren	Tribs to L.George, Village of L George	Silt/Sediment
Washington	Cossayuna Lake	Nutrients
Washington	Lake Champlain, South Bay	Nutrients
Washington	Tribs to L.George, East Shore	Silt/Sediment
Washington	Wood Cr/Champlain Canal and minor tribs	Nutrients
Wayne	Port Bay	Nutrients
Westchester	Amawalk Reservoir	Nutrients
Westchester	Blind Brook, Upper, and tribs	Silt/Sediment
Westchester	Cross River Reservoir	Nutrients
Westchester	Lake Katonah	Nutrients
Westchester	Lake Lincolndale	Nutrients
Westchester	Lake Meahagh	Nutrients
Westchester	Lake Mohegan	Nutrients
Westchester	Lake Shenorock	Nutrients
Westchester	Long Island Sound, Westchester (East)	Nutrients
Westchester	Mamaroneck River, Lower	Silt/Sediment
Westchester	Mamaroneck River, Upper, and minor tribs	Silt/Sediment
Westchester	Muscoot/Upper New Croton Reservoir	Nutrients
Westchester	New Croton Reservoir	Nutrients
Westchester	Peach Lake	Nutrients
Westchester	Reservoir No.1 (Lake Isle)	Nutrients
Westchester	Saw Mill River, Lower, and tribs	Nutrients
Westchester	Saw Mill River, Middle, and tribs	Nutrients
Westchester	Sheldrake River and tribs	Silt/Sediment
Westchester	Sheldrake River and tribs	Nutrients
Westchester	Silver Lake	Nutrients
Westchester	Teatown Lake	Nutrients
Westchester	Titicus Reservoir	Nutrients
Westchester	Truesdale Lake	Nutrients
Westchester	Wallace Pond	Nutrients
Wyoming	Java Lake	Nutrients
Wyoming	Silver Lake	Nutrients

APPENDIX F – List of NYS DEC Regional Offices

Region	Covering the following counties:	DIVISION OF ENVIRONMENTAL PERMITS (DEP) Permit Administrators	DIVISION OF WATER (DOW) Water (SPDES) Program
1	Nassau and Suffolk	50 Circle Road Stony Brook, NY 11790 Tel. (631) 444-0365	50 Circle Road Stony Brook, NY 11790-3409 Tel. (631) 444-0405
2	Bronx, Kings, New York, Queens and Richmond	1 Hunters Point Plaza, 47-40 21st St. Long Island City, NY 11101-5407 Tel. (718) 482-4997	1 Hunters Point Plaza, 47-40 21st St. Long Island City, NY 11101-5407 Tel. (718) 482-4933
3	Dutchess, Orange, Putnam, Rockland, Sullivan, Ulster and Westchester	21 South Putt Corners Road New Paltz, NY 12561-1696 Tel. (845) 256-3059	100 Hillside Avenue, Suite 1w White Plains, NY 10603 Tel. (914) 428 - 2505
4	Albany, Columbia, Delaware, Greene, Montgomery, Otsego, Rensselaer, Schenectady and Schoharie	1150 North Westcott Road Schenectady, NY 12306-2014 Tel. (518) 357-2069	1130 North Westcott Road Schenectady, NY 12306-2014 Tel. (518) 357-2045
5	Clinton, Essex, Franklin, Fulton, Hamilton, Saratoga, Warren and Washington	1115 State Route 86, Po Box 296 Ray Brook, NY 12977-0296 Tel. (518) 897-1234	232 Golf Course Road Warrensburg, NY 12885-1172 Tel. (518) 623-1200
6	HERKIMER, JEFFERSON, LEWIS, ONEIDA AND ST. LAWRENCE	STATE OFFICE BUILDING 317 WASHINGTON STREET WATERTOWN, NY 13601-3787 TEL. (315) 785-2245	STATE OFFICE BUILDING 207 GENESEE STREET UTICA, NY 13501-2885 TEL. (315) 793-2554
7	BROOME, CAYUGA, CHENANGO, CORTLAND, MADISON, ONONDAGA, OSWEGO, TIOGA AND TOMPKINS	615 ERIE BLVD. WEST SYRACUSE, NY 13204-2400 TEL. (315) 426-7438	615 ERIE BLVD. WEST SYRACUSE, NY 13204-2400 TEL. (315) 426-7500
8	CHEMUNG, GENESEE, LIVINGSTON, MONROE, ONTARIO, ORLEANS, SCHUYLER, SENECA, STEUBEN, WAYNE AND YATES	6274 EAST AVON-LIMA ROADAVON, NY 14414-9519 TEL. (585) 226-2466	6274 EAST AVON-LIMA RD. AVON, NY 14414-9519 TEL. (585) 226-2466
9	ALLEGANY, CATTARAUGUS, CHAUTAUQUA, ERIE, NIAGARA AND WYOMING	270 MICHIGAN AVENUE BUFFALO, NY 14203-2999 TEL. (716) 851-7165	270 MICHIGAN AVENUE BUFFALO, NY 14203-2999 TEL. (716) 851-7070

Poughkeepsie Natural Resource Inventory
Conservation Analysis
South Avenue Multi-Family Development
South Avenue
City of Poughkeepsie
Dutchess County, New York

Issued: November 29, 2022
Revised January 27, 2023
Revised March 7, 2023

Prepared for:
ARGO Development
95 Chestnut Ridge Road
Montvale, NJ 07645

Prepared by:
LaBella Associates
21 Fox Street Suite 201
Poughkeepsie, NY 12601
845-486-1541

TABLE OF CONTENTS

1.0 INTRODUCTION 1
1.1 Project Summary 1
1.2 Background 1
1.3 Site and Surrounding Area Description 1
1.4 Approvals, Consultations and Referrals 2

2.0 CONSERVATION ANALYSIS 2
2.1 Geology and Soils 2
2.2 Water Resources 3
2.3 Habitat 3
2.4 Land Use 4
2.5 Historic and Archaeological Resources 5
2.6 Recreational Resources 5
2.7 Conclusion 5

LIST OF TABLES

Table 1: Anticipated Approvals and Permits 2
Table 2: Characteristics of Anticipated Soil Types within Project Site 3

FIGURES

Figure 1: Geology and Soils
Figure 2: Water Resources
Figure 3: Habitats
Figure 4: NYSDEC Environmental Resource Map
Figure 5: Land Use Map
Figure 6: Historic Resources
Figure 7: Recreation Resources
Figure 8: Pollinator Pathway

1.0 INTRODUCTION

1.1 Project Summary

The Applicant, ARGO Development is seeking site plan approval from the City of Poughkeepsie, to develop an 87-unit, mid-rise multifamily residential development with underground and surface-level parking. The proposed action will be located on an approximately 2.76-acre parcel on the west side of South Avenue (Tax Lot 937583) in the City of Poughkeepsie. The proposed action includes construction of a five-story building with 87, one-bedroom, apartments located over one level of underground parking (60 spaces), and 55 off-street surface parking spaces. The parcel is currently a wooded lot. The parcel is located within the R-D, Research and Development District. Residential development is a permitted use within the R-D zone, subject to the requirements of the High-Density R-5 District Permitted Uses [Section 19-3.16(2)], and further subject to all other requirements applicable to High-Density R-5 District residential development. Primary access will be provided via South Avenue. Municipal water and sanitary sewer connections are available in South Road. The proposed ground disturbance is approximately 2.5 acres. Since the site will have more than 1 acre of ground disturbance, the proposed action will also require a SPDES General Permit for stormwater.

1.2 Background

The total project site area is comprised of approximately 2.76 acres and is zoned Research and Development (R-D). The project site is comprised of one parcel, identified as follows:

- Tax parcel 6061-52-937583 (South Avenue, approximately 2.76 ac.)

Residential development is classified as a permitted use within the R-D zone, subject to the requirements of the High-Density R-5 District Permitted Uses and all other requirements applicable to High-Density R-5 District residential development. Per ZS 19-3.16(2)(a)(4), multifamily dwellings are classified as permitted uses within the R-5 District. The proposed project will comply with all of the lot, bulk, and design requirements and standards included in ZS 19-3.16(4), ZS 19-3.16(5), and ZS 19-3.16(6).

1.3 Site and Surrounding Area Description

The site is currently undeveloped and wooded. The land uses located within 1,000 feet of the project site are characterized by commercial (office buildings with associated parking), vacant (wooded areas), public services (Central Hudson Gas & Electric), and single-family residential properties. The site abuts vacant and commercial area (Poughkeepsie Imported Car Parts) to the south, New York State Route 9 to the west, commercial (office) and residential land to the north and east, and South Avenue to the east.

The project site is not located within a floodway, 100-year floodplain, or 500-year floodplain. The project site is also not located over an aquifer.

1.4 Approvals, Consultations and Referrals

Table 1 provides a list of the approvals/permits that are anticipated for the project.

Table 1: Anticipated Approvals and Permits

Agency	Approval/Permit
City of Poughkeepsie Planning Board	Site plan
City of Poughkeepsie Zoning Board of Appeals	Area variance (parking)
City of Poughkeepsie Department of Public Works (DPW)	Highway Work Permit; Water and Sewer Hook-ups
Dutchess County Department of Planning and Development	GML 239m referral
NYS Department of Environmental Conservation	SPDES General Permit GP-0-020-001
NYS Department of Transportation	Drainage connection
NYS Office of Parks, Recreation, and Historic Preservation (OPRHP)	SHPO Consult

2.0 CONSERVATION ANALYSIS

The project has been evaluated according to the Natural Resources Inventory (NRI) for the City of Poughkeepsie as discussed in the following sections.

2.1 Geology and Soils

According to the NRI Report, Figure 1, the project site's bedrock geology is Taconic melange (Otm), which is considered permeable in the City of Poughkeepsie. The surficial geology of the site is described in the report as featuring glacial till, which is described in the NRI as having a variable texture (boulders to silt).[1] Table 2 provides characteristics of soil types expected to be found on site according to the NRI, Dutchess County Soil Survey information available in GIS, and the Natural Resource Conservation Service website.

[1] The Environmental Cooperative at Vassar Barns. *Natural Resources Inventory for the City of Poughkeepsie.* 2019. Map 2.2 Surficial Geology. Page 27.

Table 2: Characteristics of Anticipated Soil Types within Project Site

% of SITE	SOIL SYMBOL	SOIL TYPE	FARMLAND CLASSIFICATION	SLOPES	DRAINAGE	DEPTH TO WATER TABLE	DEPTH TO BEDROCK
98.2	Ud	Udorthents, smoothed	Not prime farmland	0-8%	Well drained	~36 to 72 inches	>80 inches
1.8	Ur	Urban Land	Not prime farmland				

The site is almost entirely comprised of Udorthents, smoothed soil (Ud). The Udorthents, smoothed soils are well drained soils and have a depth to water table of about 3 to 6 feet.

Groundwater encountered during the construction will be pumped from the open excavations and discharged to approved sediment trapping devices in accordance with NYSDEC guidelines.

2.2 Water Resources

According to Figure 2, which is drawn from the NRI mapping service, the project site includes three wetlands. However, according to NYSDEC Wetland and Stream information available through GIS, and the EAF Mapper, there are no wetlands or other waterbodies on or near the project site. There was no standing water observed during the site walk with the City of Poughkeepsie on January 24, 2023. This is indicative of the well-drained on-site soils consistent with the Udorthents soil type. Soils supporting wetlands would be hydric in nature (saturated). Also there was no evidence of wetland vegetation in the slight depressions on-site.

The project development will involve greater than one acre of ground disturbance; therefore, coverage under the State Pollutant Discharge Elimination System (SPDES) General Permit for Stormwater Discharges from Construction Activities will be sought. A Stormwater Pollution Prevention Plan (SWPPP) will be prepared in conformance with the most current New York State Stormwater Management Design Manual and New York State Standards and Specifications for Erosion and Sediment Control. With the implementation of the SWPPP, no significant adverse impacts to wetlands and watercourses located off site will occur.

2.3 Habitat

The NRI maps significant habitats in Map 4.1, page 70. This map indicates that the project site is comprised of hardwood swamps and upland hardwood forest land uses. The parcel is currently a wooded, undeveloped lot.

According to the NRI online mapping tool, the same parts of the project site are characterized by hardwood swamps and upland hardwood forest (see Figure 3). The upland hardwood forest habitat is characterized by closed (forested) area with wetlands underneath.

Map 4.4 on page 76 identifies Habitat Envelopes and Potential Corridors, with Significant Habitat Areas identified. In this map, the project site is identified as Significant Habitat Area.

According to the NYSDEC Environmental Resource Mapper (Figure 6), there are known occurrences of the atlantic sturgeon, shortnose sturgeon, and bald eagle on or in the vicinity of the project site.

According to the United States Fish and Wildlife Service (USFWS) Information for Planning and Consultation (IPaC), the project lies within the range of records for indiana bat (endangered) and the monarch butterfly, a candidate species. Candidate species are not regulated by the USFWS (See Attachment A). The IPaC also states that there are no critical habitats at the project location.

The proposed project will require clearing of the entire wooded site (2.5 acres) for construction of the proposed apartment building. To avoid direct or indirect take of bat species, it is recommended that any forest clearing take place between October 30 and March 31, as during this time, the bats would be hibernating and not present onsite.

The atlantic sturgeon and shortnose sturgeon are aquatic species and are found within the Hudson River or immediately adjacent tributaries. The Hudson River is approximately 1,450 feet away from the project site, and therefore the proposed project will not result in any adverse impacts to these species.

An information request has been submitted to NYSDEC for further information regarding the bald eagle. However, based on the NYSDEC Environmental Resource Mapper, the centroid for the bald eagle element occurrence record appears to lie in the vicinity of the Poughkeepsie Rural Cemetery. The heavily traveled NYS Route 9 and the offices for Central Hudson Gas & Electric, lie between the project site and the element occurrence record.

Based on Google Earth, the area within 330 feet of the southern edge of the property is dominated by the heavily traveled NYS Route 9 and the northern portion of the Central Hudson Gas & Electric offices. From 330 to 660 feet from the southern property boundary, the area is dominated by the parking lots for Central Hudson Gas & Electric offices. From 660 to approximately 2,795 feet, the area is dominated by the Poughkeepsie Rural Cemetery. A pond, in the center of the Poughkeepsie Rural Cemetery, which may be close to the location of the bald eagle nest, is more than a ½ mile (2,795 feet) from the southern limits of the project area. Given the intervening highway and commercial land use, and the ½ mile distance from the project area, it is unlikely that the construction or operation of the proposed project will have adverse impacts on the bald eagle. LaBella is making an inquiry to NYSDEC Region 3 to determine the location of the nest and to consult on the bald eagle as necessary.

The project site lies in the vicinity of a significant natural community as shown by the crosshatched pattern on figure 6. This significant natural community is the Hudson River Estuary. The project site lies approximately 1,450 feet away from the Hudson River, and thus is not expected to have any effect on the significant natural community.

2.4 Land Use

The project site is located in the Research and Development District (R&D). It is not located on agriculturally farmed land and is not within the County's Agricultural District. The project site is currently wooded and undeveloped.

According to City Zoning Section (ZS) 19-3.16(1), the City of Poughkeepsie created the R&D District to provide areas for intense residential development accessible to all commercial, cultural and community services and major transportation facilities and to provide opportunity for limited nonresidential activity that will enrich the urban environment.

The land uses located within 1,000 feet of the project site are characterized by commercial, residential, public and community services, vacant and wooded areas (see Figure 5). The site abuts vacant and commercial area (Poughkeepsie Imported Car Parts) to the south, New York State Route 9 to the west, commercial (office) and residential land to the north and east, and South Avenue to the east.

The proposed use, as an 87-unit, mid-rise multifamily residential development with underground and surface-level parking, is a permitted use within the R&D zone, subject to the requirements of the High-Density R-5 District Permitted Uses [Section 19-3.16(2)], and further subject to all other requirements applicable to High-Density R-5 District residential development.

Per ZS 19-3.16(2)(a)(4), multifamily dwellings are classified as permitted uses within the R-5 District. And, per ZS 19-3.16(3)(a), off-street parking is classified as an accessory use within the R-5 District. The proposed project will require an area variance from the Zoning Board of Appeals for parking.

2.5 Historic and Archaeological Resources

According to the NRI (Figure 6), the project site does not contain and is not substantially contiguous to any Local, National or State Historic Register site nor is it within a historic district.

According to the NYS Office of Parks, Recreation, and Historic Preservation (NYSOPRHP) Cultural Resource Information System (CRIS) mapping (Figure 7), there are no National or State Historic Register sites on or substantially contiguous to the project site.

The project site is located within a known archaeologically sensitive area. Therefore, a consultation request will be submitted to NYSOPRHP.

2.6 Recreational Resources

The site does not abut any recreational resources. The project site is located on privately-owned land that is not currently used by the public for recreation (see Figure 7).

2.7 Conclusion

The project site is identified in the NRI Report as a site that includes hardwood swamps and upland hardwood forest. The proposed project involves the development of a 2.76-acre wooded and undeveloped site, into an 87-unit, 5-story mid-rise multifamily residential

development with underground and surface-level parking. The site is zoned for the proposed use and has been modified from its natural condition by the construction of the adjoining uses and roadways and historic development as far back as 1936. The site does not contain wetlands or watercourses and the NYSDEC has been consulted with regard to the bald eagle concern. A consultation with NYSOPRHP will also be undertaken. For these reasons, the proposed project is consistent with the policy objectives of the Natural Resources Inventory for the City of Poughkeepsie.

FIGURES

South Avenue ARGO Development: Geology and Soils



11/16/2022, 1:41:38 PM

City of Poughkeepsie Boundary

Parcel Boundaries

Soils

Bedrock Geology

Graywacke, shale (Oag)

Taconic melange (Otm)

Water

1:2,257

0 0.02 0.04 0.08 mi

0 0.03 0.07 0.13 km

Esri Community Maps Contributors, © OpenStreetMap, Microsoft, Esri, HERE, Garmin, SafeGraph, GeoTechnologies, Inc, METI/NASA, USGS, EPA, NPS, US Census Bureau, USDA, New York State, Maxar,

Applicant

New York State, Maxar, Microsoft | NYS Museum | Esri Community Maps Contributors, © OpenStreetMap, Microsoft, Esri, HERE, Garmin, SafeGraph, GeoTechnologies, Inc, METI/NASA, USGS, EPA, NPS, US Census Bureau, USDA |

South Avenue ARGO Development: Water Resources



11/16/2022, 1:48:08 PM

Parcel Boundaries

City of Poughkeepsie Boundary

Wetlands

Streams

Intermittennt

Watershed

Hudson River Direct Drainage E

1:2,257

0 0.02 0.04 0.08 mi

0 0.03 0.07 0.13 km

Esri Community Maps Contributors, © OpenStreetMap, Microsoft, Esri, HERE, Garmin, SafeGraph, GeoTechnologies, Inc, METI/NASA, USGS, EPA, NPS, US Census Bureau, USDA, New York State, Maxar,

Applicant

New York State, Maxar, Microsoft | New York Natural Heritage Program | Esri Community Maps Contributors, © OpenStreetMap, Microsoft, Esri, HERE, Garmin, SafeGraph, GeoTechnologies, Inc, METI/NASA, USGS, EPA, NPS, US Census Bureau, USDA |

South Avenue ARGO Development: Habitats



11/16/2022, 1:51:50 PM

Parcel Boundaries
City of Poughkeepsie Boundary
Wetlands

Hudsonia Streams
Intermittennt
Hudsonia Habitats
Developed
Cultural
Hardwood swamp
Upland shrubland
Wet meadow
Upland meadow
Upland hardwood forest
Upland conifer forest

1:2,257

0 0.02 0.04 0.08 mi
0 0.03 0.07 0.13 km

Esri Community Maps Contributors, © OpenStreetMap, Microsoft, Esri, HERE, Garmin, SafeGraph, GeoTechnologies, Inc, METI/NASA, USGS, EPA, NPS, US Census Bureau, USDA, New York State, Maxar,

Applicant

New York State, Maxar, Microsoft | Esri Community Maps Contributors, © OpenStreetMap, Microsoft, Esri, HERE, Garmin, SafeGraph, GeoTechnologies, Inc, METI/NASA, USGS, EPA, NPS, US Census Bureau, USDA |



Sources:

1. Rare Plants or Animals and Significant Natural Communities: NYSDEC Environmental Resource Mapper (ERM) 2022

LaBella
Powered by partnership

South Avenue
Poughkeepsie, NY
12601

South Avenue
ARGO Development

LaBella Project No: 2222201
Date: 11/29/2022

NYSDEC Environmental Resource Map

FIGURE 4

South Avenue ARGO Development: Land Use



11/16/2022, 1:56:37 PM

City of Poughkeepsie Boundary

Land Use by Parcel

Commercial

Community Services

Public Services

Residential

Vacant Land

1:2,257

0 0.02 0.04 0.08 mi

0 0.03 0.07 0.13 km

Esri Community Maps Contributors, © OpenStreetMap, Microsoft, Esri, HERE, Garmin, SafeGraph, GeoTechnologies, Inc, METI/NASA, USGS, EPA, NPS, US Census Bureau, USDA, New York State, Maxar,

ArcGIS Web AppBuilder

New York State, Maxar, Microsoft | Esri Community Maps Contributors, © OpenStreetMap, Microsoft, Esri, HERE, Garmin, SafeGraph, GeoTechnologies, Inc, METI/NASA, USGS, EPA, NPS, US Census Bureau, USDA |

South Avenue ARGO Development: Historic Resources



11/16/2022, 2:00:16 PM

Parcel Boundaries

Historic Sites (2021)

Local, State, and National

City of Poughkeepsie Boundary

1:2,257

0 0.02 0.04 0.08 mi

0 0.03 0.07 0.13 km

Esri Community Maps Contributors, © OpenStreetMap, Microsoft, Esri, HERE, Garmin, SafeGraph, GeoTechnologies, Inc, METI/NASA, USGS, EPA, NPS, US Census Bureau, USDA, Sources: Esri, Airbus DS,

ArcGIS Web AppBuilder

Esri Community Maps Contributors, © OpenStreetMap, Microsoft, Esri, HERE, Garmin, SafeGraph, GeoTechnologies, Inc, METI/NASA, USGS, EPA, NPS, US Census Bureau, USDA |

South Avenue ARGO Development: Recreational Resources

11/16/2022, 2:02:27 PM

Parcel Boundaries

City of Poughkeepsie Boundary

Trails

Parks and Open Spaces

1:2,257

0 0.02 0.04 0.08 mi

0 0.03 0.07 0.13 km

Esri Community Maps Contributors, © OpenStreetMap, Microsoft, Esri, HERE, Garmin, SafeGraph, GeoTechnologies, Inc, METI/NASA, USGS, EPA, NPS, US Census Bureau, USDA, New York State, Maxar,

Applicant

New York State, Maxar, Microsoft | Esri Community Maps Contributors, © OpenStreetMap, Microsoft, Esri, HERE, Garmin, SafeGraph, GeoTechnologies, Inc, METI/NASA, USGS, EPA, NPS, US Census Bureau, USDA |

South Avenue ARGO Development: Pollinator Pathway



11/16/2022, 2:04:53 PM

Poughkeepsie Greenspace
Overlapping Parcels
Not Subject to Site Review
Subject to Site Review
Potential Pathway
Poughkeepsie Boundary
Dutchess County Parks

1:4,514

0 0.04 0.09 0.17 mi

0 0.05 0.1 0.2 km

New York State, Maxar

ArcGIS Web AppBuilder
New York State, Maxar |

William F.X. O'Neil
County Executive

Eoin Wrafter, AICP
Commissioner

County of Dutchess

Department of Planning and development

March 15, 2023

To: Planning Board, City of Poughkeepsie
Re: ZR23-043, South Avenue Residential Building – Site Plan and Special Use Permit
Lot: 937583, South Avenue and US 9

The Dutchess County Department of Planning and Development has reviewed the subject referral within the framework of General Municipal Law (Article 12B, §239-l/m).

Action

The applicant is seeking site plan and special use permit approval for the construction of a 5-story multifamily residential building to include 87 one-bedroom units and related parking, landscaping, and lighting.

Comments

Upon review of the materials submitted to our office, we offer the following comments:

- Additional landscaping, especially shade trees, could be added along the south side of the building to buffer the residences from the neighboring non-residential use, and to provide some buffering between the building and nearby Route 9.
- The applicant could consider incorporating green design techniques by adding appropriate plantings such as native grasses, wildflowers, or other herbaceous vegetation to the proposed retention basin along the southwest wall of the building. This could enhance both the functionality and aesthetic of the area, transforming it from an engineered basin to an environmental and visual amenity for the many residences overlooking the area.
- There are four parking spaces, shown between the refuse enclosure and the entrance to the underbuilding parking, which do not benefit from a direct connection to the courtyard entrance to the building. A pedestrian connection could be added, perhaps via stairs through the retaining wall opposite the spaces, to give people parked there a more direct and safe route to access the main building entrance.

Recommendation

The Department recommends that the Board rely upon its own study of the facts in the case with due consideration of the above comments.

Eoin Wrafter, AICP, Commissioner
By

Heather M. LaVarnway, CNU-A
Senior Planner

Dutchess County Department of Planning and Development

Fax Info Only		
	To	Date #pgs
	Co./Dept.	From
	Fax #	Phone #

239 Planning/Zoning Referral - Exemption Communities

Please Fill in this section

Municipality: **City of Poughkeepsie**

Referring Agency: **Planning Board**

Tax Parcel Numbers(s): **9375830000**

Project Name: **South Avenue #937583**

Applicant: **ARGO Development**

Address of Property: **South Ave, Poughkeepsie, NY 12601**

Exempt Actions:*
239 Review is NOT Required

- Administrative Amendments (fees, procedures, penalties, etc.)
- Special Permits for residential uses (accessory apts, home occupations, etc.)
- Use Variances for residential uses
- Area Variances for residential uses
- Renewals/Extension of Site Plans or Special Permits that have no changes from previous approvals

No Authority to review these Actions

- Subdivisions / Lot Line Adjustments
- Interpretations

☐ Exempt Action submitted for informal review

Actions Requiring 239 Review

- ☐ Comprehensive/Master Plans
- ☐ Zoning Amendments (standards, uses, definitions, district regulations, etc.)
- ☐ Other Local Laws associated with zoning (wetlands, historic preservation, affordable housing, architectural review, etc.)
- ☐ Rezonings involving all map changes
- ☐ Architectural Review
- ☑ Site Plans (all)
- ☐ Special Permits for all non-residential uses
- ☐ Use Variances for all non-residential uses
- ☐ Area Variances for all non-residential uses
- ☐ Other (Describe):

Parcels within 500 feet of:

- ☑ State Road: **Rt 9**
- ☐ County Road:
- ☐ State Property (with recreation area or public building)
- ☐ County Property (with recreation area or public building)
- ☐ Municipal Boundary
- ☐ Farm operation in an Agricultural District

Date Response Requested:

Entered By: **Garcia, Lori**

These actions are only exempt in municipalities that signed an intermunicipal agreemment with Dutchess County to that effect.

For County Office Use Only

Response From Dutchess County Department of Planning and Development

No Comments:

- ☐ Matter of Local Concern
- ☐ No Jurisdiction
- ☐ No Authority
- ☐ Withdrawn
- ☐ Incomplete - municipality must resubmit to County
- ☐ Exempt from 239 Review
- ☐ None

Comments Attached:

- ☑ Local Concern with Comments
- ☐ Conditional
- ☐ Denial
- ☐ Incomplete with Comments- municipality must resubmit to County
- ☐ Informal Comments Only (Action Exempt from 239 Review)

Date Submitted: **2/14/2023**	Notes:	☑ Major Project
Date Received: **2/14/2023**		Referral #: **ZR23-043**
Date Requested:		
Date Required: **3/15/2023**	☐ Also mailed hard copy	Reviewer: Heather M. LaV
Date Transmitted: **3/15/2023**		

THE CITY OF POUGHKEEPSIE
FIRE DEPARTMENT
505 MAIN STREET
POUGHKEEPSIE, NY 12601
TEL: 845-451-4079 FAX: 845-451-4191
FIRE CHIEF JOSEPH FRANCO
JFRANCO@CITYOFPOUGHKEEPSIE.COM

SITE PLAN REVIEW FORM

TO: Planning Board

Site Plan Dated 4/4/23

FROM: Fire Chief Joseph Franco

DATE: April 5, 2023

ADDRESS: South Ave. Grid # 6061-52-937583

The site plan is acceptable and will be signed without conditions.

__x__ The site plan is acceptable and will be signed without conditions:

1. *Upon completion of the installation of the fire sprinkler and standpipe system, the Fire Department will perform a flow test to verify required flow is obtained as stated in the hydraulic calculations. If it is found the water volume is not sufficient, developer will need to increase volume of water to required floe demand.*

2. *Upon construction completion, Fire Department will do a performance test verifying the clearance of tower ladder 2 accessing and exiting the property.*

Joseph Franco, Fire Chief

4/5/2023
Date

February 20, 2023

City of Poughkeepsie Planning Board
Attn: Anne Saylor, Chairperson
63 Civic Center Plaza
Poughkeepsie, NY 12601

cc: Natalie Quinn, Development Director

RE: 2022-055: SOUTH AVENUE LOT

MASS DESIGN GROUP

1 Chandler Street Suite 101
Boston, MA 02116

289 Main Street Suite 101
Poughkeepsie, NY 12601

hello@massdesigngroup.org
+1 857 233 5788
+1 845 473 4003

massdesigngroup.org

Dear City of Poughkeepsie Planning Board,

We are in the receipt of the site plan and elevation drawings forwarded to our office on January 30. The applicant and design team convened with Chris Kroner, Natalie Quinn and Lori Garcia on February 9th, 2023 to discuss their proposed project on South Avenue. Attendees from the design team included: Michael Abuladez, CEO, Argo Development; Christopher Lapine, P.E., LEED AP, LaBella Associates, Mike McCormick of LMV Architects. The discussion was a preliminary workshop in nature, and they gave an introduction to the project, its intent and constraints to which MASS elevated some clarifying questions for further consideration. They presented their chic, contemporary aesthetic, as in dialogue with the context of nearby commercial buildings. As this is a large-scale housing building near a gateway point into the city of Poughkeepsie off of Route 9, we are hoping that this project will capture the attention of the public.

Drawings/Elevations
In the conversation the development team shared example renderings that were evolving the design; these renderings have key differences to the elevations, especially as it pertains to the scale of the entrance volumes. *We would encourage coordinating renderings and elevations for better clarity in subsequent review, or adding notations as to which document governs.*

Exterior Staircase
The project hopes to activate the streetscape sidewalk with both a ramped sidewalk and exterior staircase near the South Avenue entrance. The sidewalk as currently drawn while it may meet minimum requirements however feels small in comparison with the building. *We recommend widening the staircase to be grander in scale with the width of the entry volume of the building, or a similar study by the design team.*

Exterior Windows/Balconies
We understand that the operation of the windows will be fixed picture windows above with awning (pull-in) windows below. Through discussion with the design team, we see that this choice mates well with the architectural intent.

MASS appreciates the inclusion of balconies, understanding the importance of

outdoor space in a post-pandemic development that looks not just for fresh air intake, but access to fresh air. *We see the balustrades on the included rendered images as an opportunity to consider patterns, material and/or craft of the region as the basis for a fabricated railing that helps to land this new project in an existing context.*

Parking Lot Apertures
Discussion was held regarding the ground floor and subsurface parking lots, and how the fresh air intakes would be treated in the building wall. *This has been the discussion of previous applicants, and we would ask the design team to elaborate on the intent there (louvers, metal mesh, vine supporting grids, etc.)*

Roof
Roof plan needs clarification as we understand there will be Rooftop Mechanical Units, but *we want to understand any proposed Bulkheads, Openspace, MEP Areas, Screening, etc for another review.*

Generator
Please clarify the generator location, fuel source and utility runs associated for the planning board to understand.

Materials
In the workshop we heard that the applicant is considering Cement Board Paneling vs Sheet Metals. Alternative Metal Sheeting approaches such as Zinc, and different shingling strategies such as at the Lace Mill Factory in Kingston were discussed. *Please submit a materials sheet and/or physical samples for the planning board to review.*

Exterior Lighting
Discussion was held regarding lighting, and which lighting approach would be most appropriate on the facade. Given the contemporary look of the design, *we encourage the design team to revise their wall mounted and parking lamp pole luminaires with something in the same spirit as the design building.*

Benches, Tables, Site Features
Similar to the lighting, the current detail for the benches appears to be a stock historical bench, and *we would encourage them to specify a bench more compatible with the contemporary architecture design. Are these the same benches that are shown in the seating area with crushed stone on the Northwest corner of the site?*
Please clarify the proposed picnic table specification (material/style).
Please clarify the field stone planter with a bench in the center of the pedestrian circle near the back entry with a drawing or precedent image.

MASS DESIGN GROUP

1 Chandler Street Suite 101
Boston, MA 02116

289 Main Street Suite 101
Poughkeepsie, NY 12601

hello@massdesigngroup.org
+1 857 233 5788
+1 845 473 4003

massdesigngroup.org

Landscaping
We are encouraged that the siting of the building provides some screening of the surface parking lot behind, and *encourage additional density of tree plantings to add screening.*
We notice the shrubline along South Avenue, and while that is an encouraging buffer zone, *we would ask the applicant to consider adding street trees (especially deciduous) along South Avenue to help enliven the streetscape further.*

Given the scale and location, we look forward to seeing this important anchor project for the south side of Poughkeepsie evolve through public participation in collaboration with community partners.

Sincerely,
Chris Kroner



Principal
ckroner@mass-group.org

MASS DESIGN GROUP

334 Boylston Street #400
Boston, MA 02118

337 Main Street #3F
Poughkeepsie, NY 12601

hello@massdesigngroup.org
+1 857 233 5788
+1 845 473 4003

massdesigngroup.org

THE CITY OF POUGHKEEPSIE

DEPARTMENT OF PUBLIC WORKS & ENGINEERING

SITE PLAN REVIEW
Form #1

1. Date: February 17, 2023
2. Name of Site Plan: South Avenue – Multi Family Development
3. Address or Location: South Avenue (Grid #6061-52-937583)
4. Owner: South Avenue Real Estate Associates LLC
5. Engineer/ Architect: LaBella
6. Yes ☐ No ☐ The site plan as forwarded by the Planning Department is acceptable and will be signed off on with no condition(s).
7. Yes ☐ No ☐ The site plan as forwarded by the Planning Department is acceptable and has been signed off on with no condition(s).
8. Yes ☒ No ☐ The applicant should be notified that the Dept. of Public Works/Engineering requires the following comment(s) be addressed:

1. Verify and demonstrate available water utility is sufficient for proposed development for both domestic and fire suppression. Any fire suppression requirements to be discussed with City Fire Department and must demonstrate what is being requested is achieved.
2. Provide utility report demonstrating available sanitary sewer utility is sufficient for proposed development. Include discussion of water utility for domestic and fire suppression requirements.
3. Indicate location of all proposed backflow devices. Coordinate with City Building Department on type that meets requirements per code.
4. Provide City Standard details for, Curbs, Sidewalk, Driveway Aprons, Pipe Trench, Water TS&V etc. for work within City ROW.
5. Sheet C160 and C560 indicates Mueller Hydrant. Provide and indicate on Site Plan City Standard Hydrant – American Darling B-62-B. No equivalent or exceptions.
6. Indicate and show on Sheet C160 and C560 water tapping sleeve and valve and redundant valve on back side of the curb. Both valves to be Red Top, Right Open.
7. Provide design, stability calculations and certification by NYS Licensed PE for retaining walls greater than 5 feet in height.
8. The engineer shall certify that the native soils are acceptable for use as an infiltration practice for the development. In the event the proposed infiltration practice cannot be used, an alternative means to handle site stormwater will need to be developed and implemented for the project. Any alternative must be approved by the City Engineer.
9. Proposed development indicates 2.5 acres of disturbance. Provide SWPPP for review.
10. Proposed development indicates storm sewer discharge to NYSDOT owned storm sewer. Any work within or adjacent to NYSDOT ROW or Utility Easements must be reviewed and approved by the respective agency. Provide copies of correspondence and/ or approvals.
11. Any food prep areas within development requires properly sized and designed grease trap. Provide size, location and maintenance schedule on site plan, if applicable.

12. Show on Site Plan maintenance and protection of traffic for work within City ROW.
13. Provide an estimate of costs for site work.

Joseph T. Kane, P.E.
Assistant Civil Engineer

Note: If #6 or #7 above are checked "yes" there is no need to go on to Form #2.

THE CITY OF POUGHKEEPSIE
FIRE DEPARTMENT

505 MAIN STREET
POUGHKEEPSIE, NY 12601
TEL: 845-451-4079 FAX: 845-451-4191
FIRE CHIEF JOSEPH FRANCO
JFRANCO@CITYOFPOUGHKEEPSIE.COM

SITE PLAN REVIEW FORM

TO: Planning Board

FROM: Fire Chief Joseph Franco

DATE: February, 16th 2023

ADDRESS: South Ave Grid # 6061-52-937583

Site Plan Submittal Date 1/27/23

____ The site plan is acceptable and will be signed without conditions.

__X__ The site plan is acceptable and will be signed with the following conditions:

1. *Upon completion of the installation of fire sprinkler and standpipe system, the fire department will perform a flow test to verify required flow is obtained as stated in hydraulic calculations. If it is found the water volume is not sufficient, developer will need to increase volume of water to required flow demand*

2. *Upon construction completion, fire department will do a performance test verifying the clearance of TL-2 accessing and exiting property as discussed*

Joseph Franco, Fire Chief

2-16-23
Date

New York State
Parks, Recreation and
Historic Preservation

KATHY HOCHUL
Governor

ERIK KULLESEID
Commissioner

February 28, 2023

Brittany Micheline
LaBella Associates
21 Fox Street
Poughkeepsie, NY 12480

Re: DEC
South Avenue Multi-Family Development
City of Poughkeepsie, Dutchess County, NY
23PR00880

Dear Brittany Micheline:

Thank you for requesting the comments of the Office of Parks, Recreation and Historic Preservation (OPRHP). We have reviewed the project in accordance with the New York State Historic Preservation Act of 1980 (Section 14.09 of the New York Parks, Recreation and Historic Preservation Law). These comments are those of the OPRHP and relate only to Historic/Cultural resources. They do not include potential environmental impacts to New York State Parkland that may be involved in or near your project. Such impacts must be considered as part of the environmental review of the project pursuant to the State Environmental Quality Review Act (New York Environmental Conservation Law Article 8) and its implementing regulations (6 NYCRR Part 617).

Based upon this review, it is the opinion of OPRHP that no properties, including archaeological and/or historic resources, listed in or eligible for the New York State and National Registers of Historic Places will be impacted by this project.

If further correspondence is required regarding this project, please be sure to refer to the OPRHP Project Review (PR) number noted above.

Sincerely,

R. Daniel Mackay

Deputy Commissioner for Historic Preservation
Division for Historic Preservation

rev: J. Carter

BUILDING DEPARTMENT

CITY OF POUGHKEEPSIE
62 CIVIC CENTER PLAZA, 2ND FLOOR
POUGHKEEPSIE, NY 12601
Phone: (845) 451-4007 Fax: (845) 451-4006

Eric Philipp
Building Inspector

SITE PLAN REVIEW

DATE: 1-30-23

PROJECT ADDRESS: South Ave #937583

PROJECT NAME: South Avenue Multi-family Development

OWNER: ARGO Development

ENGINEER/ARCHITECT:

☑ **The site plan is acceptable and will be signed with no conditions.**

☐ **The site plan cannot be approved as submitted. The following comments must be addressed or conditions satisfied:**

_____

_____

_____

_____

_____

_____

Eric Philipp
Building Inspector

CITY OF POUGHKEEPSIE POLICE DEPARTMENT

SITE PLAN REVIEW

DATE: 02/04/2023

PROJECT NAME: South Avenue #937583

PROJECT ADDRESS: South Avenue #937583

☒ **THE SITE PLAN IS ACCEPTABLE AND WILL BE SIGNED WITH NO CONDITIONS**

☐ **THE SITE PLAN IS UNACCEPTABLE.**

CONDITIONS:

APPROVED BY CHIEF THOMAS PAPE OR AGENT:	DATE:
Sgt #112 SGT. E. ACKEN #112	02/04/2023

THE CITY OF POUGHKEEPSIE
NEW YORK
DEVELOPMENT DEPARTMENT
62 CIVIC CENTER PLAZA, 2ND FLOOR
POUGHKEEPSIE, NY 12601
Phone: (845) 451-4623 Fax: (845) 451-4006

Resolution of the City of Poughkeepsie Planning Board
DRAFT Negative Declaration of Environmental Significance
April 18, 2023

WHEREAS, the Planning Board has received an application for South Avenue lot of record #6061-52-937583 for construction of 87-unit, 5-story mid-rise multifamily residential development with 60 underground and 84 surface-level parking spaces.

WHEREAS, the application was accompanied by additional materials, including Elevations with Landscaping, Garage Site Plan, Roof Level Site Plan with a date of 4/4/23, prepared by Chris Lapine and supplemental materials; and,

WHEREAS, a public hearing will be held on the application on April 18, 2023; and,

WHEREAS, this application is considered to be an Unlisted Action under SEQR; and,

WHEREAS, on February 22, 2023 the Planning Board declared itself lead agency for SEQR; and,

WHEREAS, on April 11, 2023 the Zoning Board of Appeals received notice of the Planning Board's intent to be lead agency for the purposes of SEQR; and,

WHEREAS, the action is more fully detailed in the Full Environmental Assessment Form with a revision date of 1/27/23, prepared by LaBella Associates, and the application and plans outlined above; and,

WHEREAS, the Board has compared the impacts that are likely to result from the action against those in 617.7(c)(1)(i) through (xii), as noted in the EAF, and has determined that there will be no significant adverse environmental impacts and therefore, a draft environmental impact statement will not be prepared:

NOW THEREFORE BE IT RESOLVED that the Board hereby adopts a Negative Declaration subject to the provision of:

Motion:
Second:
Carried:

APPLICATION TO THE PLANNING BOARD
CITY OF POUGHKEEPSIE, NEW YORK

Application for Site Plan, Special Permit & Facade Approval

OFFICE USE ONLY

CODE: PLSF

ID #RB2022-020

FEE: _____
Total, from:
$500, plus
$_____
($150 per 1000 square feet of floor area), plus
$_____
($35 per number of required parking spaces), plus
$_____
($500 for special permit, if applicable)

I. **PROPERTY ADDRESS:** 117 N. Hamilton Strreet

II. **PROPERTY OWNER:** See Attachment A
ADDRESS: _____

_____

_____ (state and zip code)

PHONE NUMBER: _____ (include area code)

III. **NAME OF APPLICANT:** Baxter Development Corp. Attn: Eric Baxter

ADDRESS: 278 Mill Street, Suite 100

Poughkeepsie

NY 12601 (state and zip code)

PHONE NUMBER: 845-471-1047 (include area code)

EMAIL ADDRESS: Eric@Baxterbuilt.com

(If applicant is NOT the owner, proof of owner's consent to the application MUST be provided.)

IV. **CONSULTANT:** Rohde, Soyka & Andrews, Consulting Engineers, PC

ADDRESS: 40 Garden Street

Poughkeepsie

NY 12601 (state and zip code)

PHONE NUMBER: 845-452-7515 (include area code)

V. **PROPOSED USE or FAÇADE CHANGE** (Summarize proposed use or uses):_____

Wholesale storage, warehousing, manufacturing, creative, retail, contracting businesses

VI. **ZONING DISTRICT:** I-1

(Proceed to XVII for special permit & façade approval only)

RECEIVED

JUN – 6 2022

Revised January 2018: Previous Editions Obsolete

APPLICATION TO THE PLANNING BOARD
CITY OF POUGHKEEPSIE, NEW YORK

Application for Site Plan, Special Permit & Façade Approval
Attachment A

OWNERSHIP:

- PARCEL: 266293
  117 N Hamilton, LLC
  186 Cottage Street
  Poughkeepsie, 12601
  Size: 0.43 Acres
  Telephone : 845-465-0207
  Email: truforminc@verizon.net

- PARCEL: 271278
  North Hamilton Parcel, LLC
  278 Mill St., Suite 100
  Poughkeepsie, NY 12601
  Size: 1.20 Acres
  Telephone: 845-471-1047
  Email: eric@baxterbuilt.com

PROJECT INFORMATION

New construction: X (yes)_____ (no)

Change of use:_____ (yes) _____ (no)

Expansion/addition:_____ (yes) _____ (no)

Alteration:_____ (yes) _____ (no)

Cost of Construction: $_____

LOT AND BULK INFORMATION:

Lot area: 1.63 (acres) 71,003 (square feet)

Building Footprint: 19,957 (proposed square feet for new construction)

_____ (existing square feet for change of use/expansion)

_____ (additional proposed square feet for expansion)

_____ (total building footprint, square feet)

Lot Coverage: 28 (percentage, building coverage only)

Gross Floor Area: 23,422 (proposed square feet for new construction)

_____ (existing square feet for change of use/expansion)

_____ (additional proposed square feet for expansion)

_____ (total gross floor area, square feet)

Building Height: 1 (stories) 32 (feet)

Floor Area Ratio: 0.33 (ratio of gross floor area divided by lot area)

VIII. PROJECT PARKING INFORMATION

A) Number of Off-Street Parking Spaces required: 24

B) Number of Off-Street Parking Spaces provided: _____

C) Waiver Requested: _____ (Yes) X (No)

Is municipal parking available within 600 feet? _____ (Yes) X (No)

If yes, name all such municipal facilities: _____

_____

_____

(If a waiver is requested based on proximity to municipal facilities, a written request for such waiver, addressed to the City Planning Staff and the Chairman of the Planning Board, must be submitted with the application.)

If a private parking facility is to be utilized, is such facility within 600 feet?

_____ (Yes) _____ (No)

If yes, provide the address of the facility, name of the property owner, number of spaces in the lot, number of spaces available for lease, and length of lease. Attach copy of lease. Additional information may be required by the Planning Board):

_____

_____

_____

_____

IX. RESIDENTIAL PROPOSALS

A) Type of Development: _____
(Townhouse, condominium, multiple residence rental, etc.)

B) Unit Breakdown:

Number of efficiency or "studio" units: _____

Number of one (1) bedroom units: _____

Number of two (2) bedroom unit's _____

Number with three or more bedrooms: _____

Total number of units: _____

C) Is funding public? ____ Yes ____ No

If yes, describe funding source: _____

X. OFFICE PROPOSALS (____ Medical/Dental ____ Professional ____ Business)

A) Number of Employees: _____

B) Number of doctors/dentists/medical practitioners: _____

C) Days/Hours of Operation: _____

XI. SERVICE BUSINESS PROPOSALS

A) Specify Business: _____
(e.g., laundromat, drycleaner, beauty parlor, travel agency, banks)

B) Number of Employees: _____

C) Number of Washing Machines (for laundromat): _____

D) Days/Hours of Operation: _____

XII. MERCANTILE PROPOSALS (Retail _____ Wholesale _____)

A) Type of Mercantile (specify): _____

B) Number of Employees: _____

C) Days/Hours of Operation: _____

XIII. STANDARD RESTAURANT/FAST FOOD RESTAURANT/COFFEE SHOP/DONUT SHOP/NIGHTCLUB/DISCOTHEQUE/BAR PROPOSALS

A) Specify Use: _____

B) Number of seats (excluding bar stools and outdoor seating):_____

C) Meals served (i.e., breakfast, lunch, dinner): _____

D) Type of Menu: _____

E) Days/Hours of Operation: _____

F) Entertainment (live and/or recorded):_____

G) Will the restaurant contain a bar/lounge?: _____ Yes _____ No

H) If yes, how many seats at the bar? _____

I) Is a drive-through window proposed? _____

J) Is a walk-up window proposed? _____

K) Is an outdoor seating area proposed? _____

L) If yes, how many seats are proposed? _____

M) If yes, is outdoor cooking proposed? _____

XIV. INDUSTRIAL/COMMERCIAL PROPOSALS (Automobile repair, taxi, motor vehicle sales, warehouse, manufacturing, animal hospital, research facilities, etc.)

A) Specify Use: WAREHOUSE

B) Number of shifts (if any): ONE

C) Number of employees: _____
(If shifts are proposed, list number of employees per shift)

E) Number of work bays (if automobile repair): NA - NOT APPLICABLE

F) Days/Hours of operation: 6 DAYS PER WEEK - 8-10 HOURS PER DAY 7a-5p

XV. EDUCATIONAL/INSTITUTIONAL/RECREATIONAL PROPOSALS (e.g., Museums, Theatres, Conference Centers, Hotels, Motels, Hospitals, Nursing Homes, Assisted Living Facilities, Nursery Schools, Private Schools, Day Care Centers, Places of Worship, Marinas, Membership Clubs, etc.)

A) Specify: _____

B) Number of shifts (if any): _____

C) Number of employees: _____
(If shifts are proposed, list number of employees per shift)

D) Number of beds (hospitals, nursing homes, etc): _____

E) Number of seats in largest assembly space: _____

F) Number of classrooms (schools): _____

G) Number of rental units (hotels, motels, etc.) _____

H) Number of boat slips/courts (e.g., tennis, handball, etc.), alleys: _____

I) Days/Hours of Operation: _____

XVI. PROPOSALS NOT MENTIONED ABOVE (Please be specific):

_____

_____

_____

_____

_____

XVII. APPLICANT CERTIFICATION

I, _____, certify that the this application has addressed the objectives outlined in the Zoning Ordinance with consideration given to the public health, safety and welfare; the comfort and convenience of the public in general or the residents or users of the proposed development and of the immediate neighborhood.

The applicant certifies that all information contained herein is accurate and complete as of the date of this application.

_____ 6/1/22

Signature of Applicant Date

DocuSign Envelope ID: 7CBFC9CC-6AB4-4EB2-86F6-CA26F4710EE7

BAXTER

DEVELOPMENT

March 7, 2023

The City of Poughkeepsie New York Planning & Zoning
62 Civic Center Plaza, 2nd Floor
Poughkeepsie, NY 12601

Re: 117 North Hamilton Street

To Whom it may concern,

We write to you regarding our upcoming project at 117 North Hamilton Street and in response to the questions and comments posed by the Planning Board at the last meeting in Fall 2022. Attached, you will find the Planning Board application, in addition to the following materials & responses for the Planning Board:

- SWPPP has been completed.
- Updated site plan, inclusive of the below feedback:
  - Fire inspection comments
  - HVAC unit
  - Details with utilities, eg placement for gas meters
- SEQRA has been updated.
- Pervious pavement has been incorporated into the stormwater management design rather than permeable pavers. (We prefer the use of the pervious pavement rather than the permeable pavers from a snow removal and maintenance perspective. This is also a warehouse facility, and the areas of use are located in areas not readily visible. The location and nature of the area of use does not require the aesthetic benefit afforded by pavers.)
- The black fence will be used with black vinyl and black posts.
- Planting choices have been made that are hardy, salt tolerant and have a viable life span.
- Flood Plain Permit:
  - Our understanding is that the Flood Plain Permit is issued by the Building Inspector. Earlier discussions with the Building Inspector led us to understand that such an application is made when site plan approval has been received. We are prepared to make such an application when the project has reached that point. The requirement for that permit has been acknowledged in the submitted documentation.
  - However, we would like to note that the building is sitting above the flood plain (the highest adjacent grade is 166, and the finished flood must be at 169, which is where we're at).

If anything still remains unclear after your review of the submitted materials, please let us know.

Thank you,

Eric Baxter
Vice President
Baxter Development Corp.

DocuSigned by:
349600D2A8354D6...



1 C100 EXISTING CONDITIONS
1" = 20'

BUILDING PARCELS

TAX PARCEL NOS. 6162-03-266293, 271278
ACREAGE 0.43 AC / 1.20 AC - TOTAL COMBINED 1.63 AC
OWNER 117 N Hamilton, LLC , North Hamilton Parcel, LLC
APPLICANT BAXTER DEVELOPMENT CORP
WATER DISTRICT = CITY OF POUGHKEEPSIE WATER SERVICE AREA
SEWER DISTRICT = CITY OF POUGHKEEPSIE
SCHOOL DISTRICT = POUGHKEEPSIE CITY SCHOOL DISTRICT
FIRE DISTRICT = CITY OF POUGHKEEPSIE FIRE DEPRTMENT
ZONING DISTRICT(S) I-1 - LIGHT INDUSTRIAL DISTRICT
FLOOD ZONE = ZONE A - NO BASE FLOOD ELEVATION (FIRM MAP NO. 36027C0358E)

LOT DATA TABLE - LIGHT INDUSTRIAL DISTRICT (I-1)

	LOT AREA (SF)	LOT WIDTH (FT)	LOT FRONTAGE (FT)	FRONT SETBACK (FT)	SIDE SETBACK (FT)		REAR SETBACK (FT)	MAX BLDG HGT (FT)	LOT COVERAGE (%)	FLOOR AREA RATIO
					EACH (FT)	TOTAL (FT)				
REQUIRED	NONE		50	20	10	20	25		60	1.0
PROVIDED (OVERALL)	71003	212	206						28.0	0.33
WAREHOUSE 1		212	206	20	38/41	79	98	32	17.0	0.22
WAREHOUSE 2		212	206	218	10/31.5	41.5	25	32	11.0	0.11
										-

PARKING : USE - WHOLESALE BUSINESSES, WAREHOUSES BUILDING, PLUMBING AND ELECTRICAL CONTRACTORS INCLUDING STORAGE RELATED THERETO.

BEST FIT PARKING CATEGORY - INDUSTRIAL AND HEAVY COMMERCIAL USES:

- WHOLESALE, STORAGE, AND WAREHOUSING - 1 SPACE FOR EACH 1000 SQUARE FEET OF GROSS FLOOR AREA OR 1 SPACE PER EMPLOYEE ON THE LARGEST SHIFT , WHICHEVER IS GREATER
- TOTAL GROSS SQUARE FEET, ALL BUILDINGS - 23422 SF - 23.4 SAY 24 SPACES REQUIRED
- MAX EMPLOYEES (7 INDIVIDUAL UNITS - 3 EMPLOYEES EACH) - 21 SPACES

1A G-1 VICINITY MAP
SCALE: 1" = 150'
(DUTCHESS COUNTY PARCEL ACCESS)

ADJACENT PROPERY OWNERS

PARCEL NO.	PARCEL ADDRESS	OWNER NAME	OWNER ADDRESS	TOWN	ST	ZIP
6162-63-290274	112 N. Clinton St	Senon Antonio Galvan	112 N. Clinton St	Poughkeepsie	NY	12601
6162-63-288281	114 N. Clinton St	Senon Antonio Galvan	112 N. Clinton St	Poughkeepsie	NY	12601
6162-63-286286	118 N. Clinton St	Christine McNair	118 N. Clinton St	Poughkeepsie	NY	12601
6162-62-233288	N. Hamilton St	County of Dutchess	22 Market St	Poughkeepsie	NY	12601
6162-62-247286	N. Hamilton St	Highway Displays	404 Maple St	Poughkeepsie	NY	12601
6162-62-238330	150 N. Hamilton St	Dutchess County	22 Market St	Poughkeepsie	NY	12601
6162-63-322264	103 N. Clinton St	Carl J. Grabala, Jr.	533 Salt Point Tpke	Poughkeepsie	NY	12601
6162-63-308267	N. Clinton St	Mary Williams	533 Salt Point Tpke	Poughkeepsie	NY	12601
6162-63-309270	107 N. Clinton St	Hudson River Housing	313 Mill St	Poughkeepsie	NY	12601
6162-63-287290	122 N. Clinton St	Aurelio Cruz	122 N. Clinton St	Poughkeepsie	NY	12601
6162-63-288295	N. Clinton St	Aurelio Cruz	122 N. Clinton St	Poughkeepsie	NY	12601
6162-63-267298	119 N. Hamilton St	William Hockler	2139 New Hackensack Rd	Poughkeepsie	NY	12603

LEGEND

- EX. FLOOD ZONE LIMIT
- EX. PROPERTY LINE
- EX. ADJACENT PROPERTY LINE
- EX. MINOR CONTOUR
- 190 EX. MAJOR CONTOUR
- EX. RETAINING WALL
- EX. FENCE
- EX. ASPHALT LIMIT
- EX. GRAVEL LIMIT
- EX. CONCRETE LIMIT
- EX. CONCRETE CURB
- UTP EX. OVERHEAD WIRES WITH UTILITY POLE
- SMH EX. SANITARY SEWER LINE & MANHOLE
- DMH EX. STORMWATER LINE & DRAINAGE MANHOLE
- G EX. GAS LINE WITH GAS VALVE
- LTP EX. LIGHT POLE
- MB EX. MAILBOX
- HYD EX. HYDRANT
- CB EX. CATCH BASIN
- SIGN EX. SIGN

CITY PLANNING BOARD
CITY OF POUGHKEEPSIE, NEW YORK
SITE PLAN APPROVAL
FILE NO:
PROJECT NAME:
PROJECT LOCATION:
APPLICANT:
OFFICIALLY APPROVED at the Planning Board meeting held the ____ day of _____ 2____
PLANNING CHAIR:
DESIGNEE:
DATE SIGNED:
CONDITION(S):

SURVEY NOTE:
BASE MAP TAKEN FROM BOUNDARY AND TOPOGRAPHIC SURVEY BY JOHNSON SURVEYING. FIELD SURVEY COMPLETED ON OCT. 30, 2020. BEARINGS AND NORTH ARROW SHOWN ARE REFERENCED TO NAD 83 - NY EAST USING NYSNET RTN GPS. CONTOUR INTERVAL IS ONE FOOT. ELEVATIONS SHOWN ARE REFERENCED TO NAVD 88 USING NYSNET RTN GIS.

LIST OF DRAWINGS:

SHEET NO.	DRAWING NO.	TITLE
1	C100	EXISTING CONDITIONS & NOTES
2	C101	SITE PLAN
3	C102	GRADING PLAN
4	C103	UTILITY PLAN
5	C104	EROSION CONTROL PLAN
6	C105	TRUCK TURNING PLAN
7	C500	DETAILS #1
8	C501	DETAILS #2
9	C502	ESC DETAILS
10	C503	LANDSCAPING PLAN

FIRE DEPARTMENT NOTES

1. LOCATION OF KNOX BOX ENTRY SYSTEM WILL BE PROVIDED BY THE APPLICANT WITH A QUANTITY AND LOCATION APPROVED BY THE FIRE OFFICIAL. A MASTER KEY SYSTEM SHALL BE PROVIDED AND KEYS SUPPLIED ON COMPLETION OF CONSTRUCTION.
2. IF A STANDPIPE/SPRINKLER SYSYEM IS REQUIRED, THE LOCATION OF THE FIRE DEPARTMENT CONNECTION SHALL BE NOTED, AND VERIFICATION THAT THE EXISTING WATER SUPPLY CAN MEET THE SYSTEM DEMAND PROVIDED.
3. AN APPROVED RAPID ENTRY SYSTEM SHALL BE INSTALLED TO OPEN AY GATES.
4. IF A FIRE ALARM SYSTEM IS REQUIRED, THE LOCATION OF THE ANNUNCIATOR PANEL SHALL BE NOTED ON THE CONSTRUCTION DRAWING AT THE LOCATION APPROVED BY THE FIRE OFFICIAL.
5. 911 ADDRESS TO BE NOTED ON FAÇADE, A MINIMUM OF 6" IN HEIGHT IN CONTRASTING COLORS.

Fire Chief

Police Chief

Building Inspector

City Engineer

Commissioner of Public Works

NO.	DATE	REVISION	BY
2	9/7/22	PER COMMENTS / SITE CHANGE	JVA
1	5/5/22	PER COMMENTS	JVA

NORTH ARROW

• Alteration of this drawing, except by a licensed Professional Engineer or Architect is illegal. Any alteration by a Professional Engineer or Architect shall bear their name, signature and date of alteration.
• The user of this drawing shall verify all dimensions shown hereon and shall report any discrepancies.
• This line is one inch long

DRAWN BY:	KMC	SCALE:	1" = 20'
CHECKED BY:	JVA		
DATE:	JUNE 2021		

ROHDE, SOYKA & ANDREWS
Consulting Engineers PC
40 Garden Street Poughkeepsie, N.Y. 12601
(845) 452-7515
Fax: (845) 452-8356

NORTH HAMILTON PARCEL, LLC
NORTH HAMILTON STREET
CITY OF POUGHKEEPSIE
DUTCHESS COUNTY, NEW YORK

EXISTING CONDITIONS & NOTES

PROJECT NUMBER: 21-786-01

DRAWING NUMBER: C100
1 OF 10



1 / C101 SITE PLAN
1" = 20'

NO.	DATE	REVISION	BY
5	2/28/23	Misc Additions for SWPPP	JVA
4	9/2/22	PER COMMENTS/ SITE CHANGE	JVA
3	7/26/22	PER COMMENTS	JVA
2	7/5/22	PER CITY COMMENTS	JVA
1	5/3/22	PER COMMENTS	JVA

NORTH ARROW

© Alteration of this drawing, except by a Licensed Professional Engineer or Architect in the furtherance of his duties, is illegal. Any alteration by a Professional Engineer or Architect is illegal unless he shall affix his signature and date of alteration.
• The user of this drawing shall verify all dimensions shown hereon and shall report any discrepancies to the author of this drawing.
• This line is one inch long

DRAWN BY:	KMC
CHECKED BY:	JVA
DATE:	JULY 22, 2022
SCALE:	1" = 20'

ROHDE, SOYKA & ANDREWS
Consulting Engineers PC
40 Garden Street
Poughkeepsie, N.Y. 12601
(845) 452-7515
Fax: (845) 452-6525

117 NORTH HAMILTON
NORTH HAMILTON STREET
CITY OF POUGHKEEPSIE
DUTCHESS COUNTY, NEW YORK

SITE PLAN

PROJECT NUMBER: 21-786-01

DRAWING NUMBER: C101

2 OF 10

North Hamilton Street

Now or Formerly Decker 6162-63-267298

Now or Formerly Cruz 6162-63-288295

Now or Formerly Cruz 6162-63-287290

Now or Formerly McNair 6162-63-286286

Now or Formerly Colvon 6162-63-288281

Now or Formerly Decker 6162-63-290274

Now or Formerly County of Dutchess 6162-62-233288

LIMITS OF AREA OF SPECIAL FLOOD HAZARD

S80°38'27"E 210.00'

N80°38'27"W 209.73'

S9°21'33"W 35.18'

S80°12'15"E 110.17'

S9°21'45"W 91.05'

S79°54'15"E 99.89'

S8°41'55"W 52.10'

N80°00'05"W 210.52'

N80°38'27"W 218.90'

N9°21'33"E 90.00'

S9°21'45"W 90.00'

(BUILDING 1)
F.F.E.: 169

(BUILDING 2)
F.F.E.: 169.8

MEZZ. OFFICE 755 S.F.
WAREHOUSE 1 1588 S.F.
WAREHOUSE 2 1588 S.F.
WAREHOUSE 3 1588 S.F.
WAREHOUSE 4 1588 S.F.
WAREHOUSE 5 1588 S.F.
WAREHOUSE 1 3827 S.F.
WAREHOUSE 2 3827 S.F.
OUTDOOR 1 YARD 630 S.F.
OUTDOOR 2 YARD 630 S.F.
OUTDOOR 3 YARD 630 S.F.
OUTDOOR 4 YARD 630 S.F.
OUTDOOR 4 YARD 293 S.F.
OOR YARD
MECHANICAL ROOM
CONDENSER PAD
CURBED AREA
HANDICAP PARKING
PAINTED PAVEMENT MARKINGS (TYP.)
STEP
CONCRETE CURBING
STONE STRONG RETAINING WALL
UNILOCK OR APPROVED EQUAL RETAINING WALL
CONCRETE RETAINING WALL W/CLADDING TO MATCH BLDG

WALL TW: 168.5
WALL TW: 169.5
WALL TW: 170.5
WALL TW: 172.0 BW: 169.5
WALL TW: 174.0 BW: 169.5
WALL TW: 172.0 BW: 169.5
WALL TW: 174.0 BW: 169.6
WALL TW: 176.8 BW: 169.4
WALL TW: 172.0 BW: 169.2
WALL TW: 174.0 BW: 169.4
WALL TW: 176.0 BW: 171.0

UTP WOH1
UTP WOH2
UTP WOH1WOH2
LTP
MHS
HYD
INV IN 161.84
Catch Basin
North Clinton Street

20 10 0 20 40
SCALE IN FEET

1 C102 GRADING PLAN 1" = 20'

NO.	DATE	REVISION	BY
2	9/2/22	PER COMMENTS/ SITE CHANGE	JVA
1	5/5/22	PER COMMENTS	JVA

NORTH ARROW

- Alteration of this drawing, except by a Licensed Professional Engineer or Architect in illegal AND violation of law. If altered, the altering Engineer or Architect shall affix to the drawing their signature and date of alteration.
- The user of this drawing shall verify all dimensions shown thereon and the size of the drawing.
- This line is one inch long

DRAWN BY: KMC
CHECKED BY: JVA
DATE: MARCH 2022
SCALE: 1" = 20'

ROHDE, SOYKA & ANDREWS
Consulting Engineers PC
40 Garden Street
Poughkeepsie, N.Y. 12601
(845) 452-7515
Fax (845) 452-2553

117 NORTH HAMILTON
NORTH HAMILTON STREET
CITY OF POUGHKEEPSIE
DUTCHESS COUNTY, NEW YORK

GRADING PLAN

PROJECT NUMBER: 21-786-01

DRAWING NUMBER: C102

3 OF 10

NOTE: LOCATE AND PROPERLY ABANDON FORMER WATER AND SEWER SERVICES TO THE EXISTING PROPERTIES. WATER SERVICE TO BE ABANDONED AT MAIN PER CITY OF POUGHKEEPSIE REQUIREMENTS.

North Hamilton Street

Now or Formerly Decker 6162-63-267298

Now or Formerly Cruz 6162-63-288295

Now or Formerly Cruz 6162-63-287290

Now or Formerly McNair 6162-63-286286

Now or Formerly Colvan 6162-63-288281

Now or Formerly Decker 6162-63-290274

Now or Formerly County of Dutchess 6162-62-233288

(BUILDING 1) F.F.E.: 169

(BUILDING 2) F.F.E.: 169.8

23' X 53' UNDERGROUND FILTRATION SYSTEM

PERVIOUS PAVEMENT

S80°38'27"E 210.00'

N80°38'27"W 209.73'

S9°21'33"W 35.18'

S80°12'15"E 110.17'

S9°21'45"W 90.00'

S9°45'45"W 92.65'

S79°54'15"E 99.89'

S8°41'55"W 52.10'

N80°00'05"W 210.52'

N64°00'17"W 218.90'

N9°21'33"E 90.00'

112 L.F. 6" @ 1%

132 L.F. 4" @ 2%

15" ø HDPE

6" D.I. WATERMAIN

1.5" H.D.P.E. GAS

8X6 REDUCER

DOUBLE C.O.

INV 165.5

INV 164.75

M.H. INV IN - 163.2 INV IN - 164.4 INV OUT - 163.1

INV IN 161.84

DOG HOUSE M.H.

WET TAP 16 X 8"

CONCRETE RETAINING WALL W/CLADDING TO MATCH BLDG

UNILOCK OR APPROVED EQUAL RETAINING WALL

8' HIGH CHAIN LINK FENCE BLACK, MESH AND POLES

6' HIGH VINYL PRIVACY FENCE COLOR AND STYLE BY OWNER

TERMINATE FENCE AT BASE OF SLOPE

HANDICAP PARKING

ONE WAY EXIT ONLY

CURBED ISLAND

CONCRETE CURBING

GATE DOUBLE LEAF 15' BETWEEN POSTS

FUTURE SUBDIVISION LINE

STONE STRONG RETAINING WALL

MECHANICAL ROOM

CONDENSER PAD

CURBED AREA

WAREHOUSE 1 1588 S.F.

WAREHOUSE 2 1588 S.F.

WAREHOUSE 3 1588 S.F.

WAREHOUSE 4 1588 S.F.

WAREHOUSE 5 1588 S.F.

MEZZ. OFFICE 755 S.F.

WAREHOUSE 1 3827 S.F.

WAREHOUSE 2 3827 S.F.

OUTDOOR 1 YARD 630 S.F.

OUTDOOR 2 YARD 630 S.F.

OUTDOOR 3 YARD 630 S.F.

OUTDOOR 4 YARD 630 S.F.

OUTDOOR 5 YARD 630 S.F.

OUTDOOR 6 YARD 1693 S.F.

WALL TW: 168.5

WALL TW: 169.5

WALL TW: 170.5

WALL TW: 172.0 BW: 169.5

WALL TW: 174.0 BW: 169.5

WALL TW: 172.0 BW: 169.5

WALL TW: 174.0 BW: 169.6

WALL TW: 176.8 BW: 169.4

WALL TW: 172.0 BW: 169.2

WALL TW: 174.0 BW: 169.4

WALL TW: 176.0 BW: 171.0

UTP WOH1

UTP WOH2

UTP WOH1WOH2

LTP

HYD

MHS

DMH

STEP

Catch Basin

SCALE IN FEET 20 10 0 20 40

1 C103 UTILITY PLAN 1" = 20'

NO.	DATE	REVISION	BY
2	2/28/23	Misc Additions for SWPPP	JVA
1	6/5/22	PER COMMENTS	JVA

NORTH ARROW

- Alteration of this drawing, except by a Licensed Professional Engineer or Architect is illegal. If an item bearing the stamp of a Professional Engineer or Architect is altered, the altering engineer shall affix to the drawing his or her seal and the notation "altered" followed by his or her signature and date of alteration.
- The user of this drawing shall verify all dimensions shown thereon to the work of this drawing.
- This line is one inch long

DRAWN BY:	KMC
CHECKED BY:	JVA
DATE:	MARCH 2022
SCALE:	1" = 20'

ROHDE, SOYKA & ANDREWS
Consulting Engineers PC
40 Garden Street Poughkeepsie, N.Y. 12601
(845) 452-7515
Fax: (845) 452-8539

117 NORTH HAMILTON
NORTH HAMILTON STREET
CITY OF POUGHKEEPSIE
DUTCHESS COUNTY, NEW YORK

UTILITY PLAN

PROJECT NUMBER: 21-786-01

DRAWING NUMBER: C103



20 10 0 20 40
SCALE IN FEET

SURVEY NOTE:
BASE MAP TAKEN FROM BOUNDARY & TOPOGRAPHIC SURVEY BY JOHNSON SURVEYING. FIELD SURVEY COMPLETED ON OCT. 30, 2020. BEARINGS & NORTH ARROW SHOWN ARE REFERENCED TO NAD 83 -NY EAST USING NYSNET RTN GPS. CONTOUR INTERVAL IS ONE FOOT. ELEVATIONS SHOWN ARE REFERENCED TO NAVD 88 USING NYSNET RTN GIS.

1 / C104 EROSION CONTROL PLAN
1" = 20'

LEGEND

- EX. FLOOD ZONE LIMIT
- EX. PROPERTY LINE
- EX. ADJACENT PROPERTY LINE
- EX. MINOR CONTOUR
- EX. MAJOR CONTOUR
- EX. RETAINING WALL
- EX. FENCE
- EX. ASPHALT LIMIT
- EX. GRAVEL LIMIT
- EX. CONCRETE LIMIT
- EX. CONCRETE CURB
- EX. OVERHEAD WIRES WITH UTILITY POLE
- EX. SANITARY SEWER LINE & MANHOLE
- EX. STORMWATER LINE & DRAINAGE MANHOLE
- EX. GAS LINE WITH GAS VALVE
- EX. WATER LINE
- EX. LIGHT POLE
- EX. MAILBOX
- EX. HYDRANT
- EX. CATCH BASIN
- EX. SIGN
- SILTSOXX (TM)
- SILT FENCE
- SOIL STOCKPILE
- 15' WIDE X 50' LONG STABILIZED CONSTRUCTION ENTRANCE



NOTES: 1. CHOKER COURSE AND FILTER LAYER STONE TO BE DOUBLE WASHED AND CLEAN AND FREE OF ALL FINES.

2. PERMEABLE PAVEMENT/POROUS ASPHALT IS NOT TO BE USED FOR HANDICAPPED ACCESSIBLE PARKING SPACES.

2 / C104 PERMEABLE PAVEMENT
FOR SPECIFIED PARKING SPACES — NO SCALE

EROSION AND SEDIMENT CONTROL NOTES

1. THE OWNER IS TO COORDINATE AND BE RESPONSIBLE FOR SITE EROSION AND SEDIMENT CONTROL. THE OWNER MAY DELEGATE EROSION AND SEDIMENT CONTROL DUTIES TO CONTRACTORS OR SUBCONTRACTORS BASED UPON THE FIRM WITH THE APPROPRIATE EQUIPMENT OR WHO IS RESPONSIBLE FOR CREATING A VIOLATION (IE SEDIMENT TRACKING, KNOCKING DOWN SILT FENCE, BY-PASSING STABILIZED CONSTRUCTION ENTRANCE, ETC). THE OWNER IS RESPONSIBLE FOR THE DAY TO DAY IMPLEMENTATION OF THE SWPPP AND PREVENTING SEDIMENT-LADEN DISCHARGES FROM THE CONSTRUCTION SITE.
2. ALL EROSION AND SEDIMENT CONTROL PRACTICES ARE TO BE INSTALLED PRIOR TO SOIL DISTURBANCE, OR IN THEIR PROPER SEQUENCE, AND MAINTAINED UNTIL PERMANENT PROTECTION OR STABILIZATION IS ESTABLISHED. VEGETATED AREAS ARE CONSIDERED TO HAVE ACHIEVED FINAL STABILIZATION ONCE 80% COVERAGE DENSITY HAS BEEN ACHIEVED.
3. ANY DISTURBED AREAS THAT WILL BE LEFT EXPOSED MORE THAN TEN (10) DAYS, AND NOT SUBJECT TO CONSTRUCTION TRAFFIC, WILL IMMEDIATELY RECEIVE A TEMPORARY SEEDING AND MULCHED WITH STRAW OR EQUIVALENT MATERIAL AT A RATE OF TWO (2) TONS PER ACRE, ACCORDING TO STATE STANDARDS.
4. PERMANENT VEGETATION TO BE SEEDED OR SODDED ON ALL EXPOSED AREAS WITHIN TEN (10) DAYS AFTER FINAL GRADING. MULCHING IS REQUIRED ON ALL SEEDING. WHEN HYDROSEEDING, REFER TO MANUFACTURER'S INSTRUCTIONS.
5. ALL WORK IS TO BE DONE IN ACCORDANCE WITH THE "NEW YORK STANDARDS AND SPECIFICATIONS FOR EROSION AND SEDIMENT CONTROL," LATEST EDITION.
6. IMMEDIATELY FOLLOWING INITIAL DISTURBANCE OR ROUGH GRADING, ALL CRITICAL AREAS SUBJECT TO EROSION (I.E., STEEP SLOPES) WILL RECEIVE A TEMPORARY SEEDING IN COMBINATION WITH STRAW MULCH OR A SUITABLE EQUIVALENT, AT A RATE OF TWO (2) TONS PER ACRE, ACCORDING TO STATE STANDARDS OR EROSION CONTROL MATTING.
7. SHOULD THE CONTROL OF DUST AT THE SITE BE NECESSARY, THE SITE WILL BE SPRINKLED UNTIL THE SURFACE IS WET. TEMPORARY VEGETATIVE COVER SHALL BE ESTABLISHED OR MULCH SHALL BE APPLIED IN ACCORDANCE WITH STATE STANDARDS FOR EROSION CONTROL.
8. ALL SOIL WASHED, DROPPED, SPILLED, OR TRACKED OUTSIDE THE LIMIT OF DISTURBANCE OR ONTO LOCAL ROADS, PARKING LOTS, SIDEWALKS OR PUBLIC RIGHTS-OF-WAY SHALL BE REMOVED IMMEDIATELY.
9. THE PROPERTY OWNER SHALL BE RESPONSIBLE FOR ANY EROSION AND SEDIMENTATION THAT MAY OCCUR OFF-SITE AS A RESULT OF CONSTRUCTION OF THE PROJECT.
10. STOCKPILE AND STAGING LOCATIONS DETERMINED IN THE FIELD SHALL BE PLACED WITHIN THE LIMITS OF DISTURBANCE ACCORDING TO THE CERTIFIED PLAN. STAGING AND STOCKPILES NOT LOCATED WITHIN THE LIMITS OF DISTURBANCE WILL REQUIRE A REVISED EROSION AND SEDIMENT CONTROL PLAN. THE OWNER RESERVES THE RIGHT TO DETERMINE WHEN A NEW AND SEPARATE EROSION AND SEDIMENT CONTROL PLAN WILL BE REQUIRED FOR THESE ACTIVITIES.
11. ALL SOIL STOCKPILES ARE TO BE TEMPORARILY STABILIZED IN ACCORDANCE WITH THE EROSION AND SEDIMENT CONTROL PLAN. SURROUND THE SOIL STOCKPILE WITH A RING OF SILT FENCE. DO NOT LOCATE A STOCKPILE AREA WITHIN 100 FEET OF A WETLAND BOUNDARY. DO NOT LOCATE A STOCKPILE AREA CLOSER THAN 20 FEET TO THE TOP OF A STEEP SLOPE. TEMPORARILY SEED OR COVER THE SOIL STOCKPILE IF IT WILL NOT BE DISTURBED FOR TEN (10) DAYS.
12. PAVEMENT AREAS ARE TO BE KEPT CLEAN AT ALL TIMES. ALL ROADS/DRIVEWAYS ARE TO BE SWEPT CLEAN AT THE END OF EACH WORKDAY OR AS MAY OTHERWISE BE DICTATED BY THE WORK BEING PERFORMED. ALL CAMPUS ROADS, PARKING LOTS, AND ACTIVE PEDESTRIAN WALKS ARE TO BE KEPT CLEAN ON A CONTINUOUS BASIS WHICH MAY REQUIRE MORE FREQUENT SWEEPING.
13. DURING IMPORTATION OF FILL, ANY ADDITIONAL CONTROL MEASURES AS DEEMED NECESSARY TO PREVENT EROSION OR CONTROL SEDIMENT BEYOND THOSE MEASURES SHOWN ON THE APPROVED PLAN SHALL BE INSTALLED OR EMPLOYED AT THE DIRECTION OF THE ENGINEER, THE PROJECT MANAGER, OR THE OWNER.

EROSION & SEDIMENT MAINTENANCE REQUIREMENTS

MEASURE	FREQUENCY	REQUIRED MAINTENANCE
SILT FENCE	ONCE PER WEEK OR AFTER A STORM EVENT	REMOVE ACCUMULATED SEDIMENT. REPAIR/RESET WHEN TORN OR KNOCKED DOWN
SILTSOXX	ONCE PER WEEK OR AFTER A STORM EVENT	REMOVE ACCUMULATED SEDIMENT. RESET /STABILIZE. REPLACE TORN OR DAMAGED SECTIONS. DISPOSE OF PER MANUFACTURERS RECOMMENDATION
SOIL STOCKPILE	ONCE PER WEEK OR AFTER A STORM EVENT	RESEED/MULCH VISIBLE BARE SPOTS. REMOVE ACCUMULATED SEDIMENT FROM SILT FENCE. REPAIR/RESET WHEN SILT FENCE IS TORN OR KNOCKED DOWN
DUST CONTROL	AS NEEDED	SWEEP SURFACES. WET AFFECTED AREA

CONSTRUCTION SEQUENCE

1. CLEAN AND PREPARE SITE – REMOVE LITTER AND DEBRIS, CLEAN CONCRETE SURFACE.
2. INSTALL REQUIRED EROSION AND SEDIMENT CONTROL MEASURES.
3. STABILIZE STOCKPILE AND SITE ANYTIME THE IMPORTATION OF FILL OR GRADING CEASES FOR ONE WEEK (7 CONSECUTIVE DAYS) AND UPON COMPLETION OF THE IMPORT OF FILL AND/OR GRADING.

NO.	DATE	REVISION	BY
3	3/2/23	PER FINAL SWPP CHANGES	JVA
2	9/2/22	PER COMMENTS / SITE CHANGE	JVA
1	6/3/22	PER COMMENTS	JVA

NORTH ARROW

- Alteration of this drawing, except by a Licensed Professional Engineer or Architect in limited accordance with Section 7209 of the NYS Education Law, is illegal.
- The user of this drawing shall indemnify and hold harmless the Engineer or Architect from any and all claims arising from the unauthorized alteration or misuse of this drawing.
- The user of this drawing shall verify all dimensions shown on this drawing prior to the start of construction.
- This line is one inch long

DRAWN BY: AGL
CHECKED BY: JVA
DATE: JUNE 2021
SCALE: 1" = 20'

ROHDE, SOYKA & ANDREWS
Consulting Engineers PC
40 Garden Street Poughkeepsie, N.Y. 12601
(845) 452-7515
Fax: (845) 452-8255

117 NORTH HAMILTON
NORTH HAMILTON STREET
CITY OF BEACON
DUTCHESS COUNTY, NEW YORK

GRADING/EROSION CONTROL PLAN

PROJECT NUMBER: 21-786-01

DRAWING NUMBER: C104

5 OF 10



1 C105 TRUCK TURNING – CITY OF POUGHKEEPSIE LADDER TRUCK
1" = 20'

THE CITY OF POUGHKEEPSIE FIRE DEPARTMENT

505 MAIN STREET
POUGHKEEPSIE, NY 12601
TEL: 845-451-4079 FAX: 845-451-4191
FIRE CHIEF JOSEPH FRANCO

Date: September 7, 2022

To: All project designers

Subj: City of Poughkeepsie Fire Department Tower Ladder 2 turning specs and dimensions.

These specs are for our 2018 Spartan/Smeal mid-ship 100' Tower Ladder. These are the only dimensions to be used on projects concerning entrance opening and exits, and inside radius turns.

Whenever possible, low profile "rolled" curbing shall be used on inside turn areas to prevent jack scraping and damage.

R,

Fire Chief Joseph Franco

- Length of truck:
  - Body (bumper to bumper) 526" Front bumper of chassis to rear bumper of body.
  - Front axle to rear axle 244" WB
  - Overhang Rear Bumper to rear edge of platform: 35" at rear. Q2B siren adds 6" to length at the front.
  - Ground load on jacks is 120psi when outriggers are set up.

Operational Set-up: Outrigger to outrigger is 18'width deployed. With jack distribution plates it is 22'. Optimal angle is cab away from building at 15 degrees, this accounts for a 27' set up area. Ground must be solid & level, free of obstructions: curbing, storm drains, bollards etc.



The turn radius is a worthwhile guide for reference only. Each model needs to depend on the type, speed, weight distribution, alignment, mfg. & tire manufacturer, steering settings, etc. The chassis is used between inches on tires as to the accuracy of the test.

NO.	DATE	REVISION	BY
1	12/1/22	PER FD COMMENTS	JVA

NORTH ARROW

● Alteration of this drawing, except by a Licensed Professional Engineer or Architect in illegal and subject to penalties. Engineer or Architect making alterations must add their name, signature and date of alteration.
● The user of this drawing shall verify all dimensions shown hereon and the exact location of all lines and grades.
● This line is one inch long ■

DRAWN BY:	KMC
CHECKED BY:	JVA
DATE:	SEPTEMBER 2, 2022
SCALE:	1" = 20'

ROHDE, SOYKA & ANDREWS
Consulting Engineers PC
40 Garden Street Poughkeepsie, N.Y. 12601
(845) 452-7515
Fax: (845) 452-6353

117 NORTH HAMILTON
NORTH HAMILTON STREET
CITY OF POUGHKEEPSIE
DUTCHESS COUNTY, NEW YORK

TRUCK TURNING

PROJECT NUMBER: 21-786-01

DRAWING NUMBER: C105

6 OF 10



NOTES:

1. ALL CONCRETE SHALL BE MINIMUM 4,000 PSI.

DRIVEWAY RAMPS & ADA RAMP

CITY OF POUGHKEEPSIE ENGINEERING DEPARTMENT 62 CIVIC CENTER PLAZA POUGHKEEPSIE, NY 12601	FILE NO.: 001-DET	DRIVEWAY RAMPS & ADA RAMP DETAIL	1
	DATE: 3-8-00		
	SCALE: AS NOTED		
	DRAWN BY: JP		PAGE NO.



NOTE: PAVEMENT MARKINGS ARE TO CONFORM TO THE LATEST EDITION OF NYS MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES (MUTCD).

2 C500 PAINTED PAVEMENT MARKINGS
NO SCALE



3 C500 STOP SIGN
NO SCALE



4 C500 HANDICAP SIGN
NO SCALE



5 C500 NO PARKING SIGN
NO SCALE



1. SCORING PATTERN AND EDGE TOOLING TO MATCH CAMPUS STANDARD. SCORED JOINTS EVERY 10' O.C., UNLESS NOTED OTHERWISE. CAULKED JOINTS EVERY 2nd JOINT
2. ALL COLD JOINTS TO BE DOWELED WITH #4 BAR AT 12" ON CENTER.

6 C500 HEAVY DUTY CONCRETE WALK
NO SCALE



7 C500 CURB RAMP AT END OF SIDEWALK
NO SCALE

GENERAL NOTES:
1. THE DIMENSIONS AND SLOPES PRESENTED IN THE DETAILS ARE THE MINIMUM REQUIREMENTS TO MEET THE NEW YORK STATE DOT STANDARDS.
2. CURB RAMPS, LANDINGS AND BLENDED TRANSITIONS MAY REQUIRE THE USE OF DETECTABLE WARNINGS. REFER TO DETECTABLE WARNING DETAIL AND SITE PLAN LOCATIONS.

CURB RAMP NOTES:
4. THE RUNNING SLOPE FOR SIDEWALK CURB RAMPS IS 5'-0". REFER TO SITE PLAN FOR SIDEWALK WIDTHS.
5. THE RUNNING SLOPE OF A CURB RAMP SHALL BE 1:20 (5%) MINIMUM AND 1:12 (8.33%) MAXIMUM. (SEE NOTE 8)
6. WHERE THE SLOPE OF THE ROADWAY EXCEEDS 8.33% THE CURB RAMP LENGTH IS THE LENGTH NECESSARY TO MEET THE EXISTING SIDEWALK. IT IS RECOMMENDED THAT THE RAMP LENGTH NOT EXCEED 15'-0".
7. THE CROSS SLOPE OF THE CURB RAMPS SHOULD BE AS FLAT AS POSSIBLE, NOT TO EXCEED 1:50 (2%). THE CROSS SLOPE AT MIDBLOCK CROSSINGS MAY BE THE ROADWAY SLOPE (SEE NOTE 5).
8. THE VERTICAL ALIGNMENT OF CURB RAMP, EXCLUDING THE FLARES, SHALL BE PLANAR. GRADE BREAKS SHALL BE FLUSH AND PERPENDICULAR TO THE DIRECTION OF THE RUNNING SLOPE.
9. RAMP TRANSITIONS BETWEEN WALKS, LANDINGS, GUTTERS, OR STREETS SHALL BE FLUSH AND FREE OF ABRUPT VERTICAL CHANGES (1/4" MAX).
10. WHERE AN ACCESSIBLE PEDESTRIAN PATH CROSSES THE CURB RAMP, FLARED SIDES WITH A SLOPE OF 1:10 (10%) MAXIMUM, MEASURED PARALLEL TO THE CURB LINE, SHALL BE PROVIDED.

LANDING NOTES:
10. LANDINGS SHALL HAVE A MINIMUM CLEAR DIMENSION OF 5'-0"x5'-0" EXCEPT AT CURB RAMPS.
11. THE RUNNING AND CROSS SLOPES ON LANDINGS AT INTERSECTIONS IS 1:50 (2%) MAXIMUM. THE RUNNING AND CROSS SLOPES AT MIDBLOCK CROSSINGS MAY BE WARPED TO MEET STREET GRADE.



8 C500 CURB RAMP FOR CONTINUING SIDEWALK
NO SCALE



NOTE #1. 5" CONCRETE WALK PER DETAIL 14/C500
8" CONCRETE WALK PER DETAIL 6/C500

9 C500 CONCRETE CURB AND SIDEWALK
NO SCALE



Minimum Convex Radius			
Wall Height (ft)	Total # of Courses	Min. Radius at First Course	
6	3	10'-0"	
9	4	10'-0"	
12	5	10'-0"	
15	6	10'-0"	
18	7	10'-0"	
21	8	44'-0"	
24	9	56'-0"	

NOTES:
1. SEE FACE AND WEB MESH DETAILS FOR REINFORCEMENT GRID.
2. CHISELED GRANITE STYLE HAS A DIFFERENT FACE PATTERN ON 24-42 BLOCKS. INSTALL A, B, C, & D PATTERNS AT RANDOM IN WALL.

NOTES:
1. SEE FACE AND WEB MESH DETAILS FOR REINFORCEMENT GRID.
2. CHISELED GRANITE STYLE HAS A DIFFERENT FACE PATTERN ON 24-66 BLOCKS. INSTALL A, B, C, & D PATTERNS AT RANDOM IN WALL.

FINAL WALL DESIGN AND DETAILED CALCULATIONS PREPARED BY A LICENSED PROFESSIONAL ENGINEER SHALL BE SUBMITTED PRIOR TO ISSUANCE OF A BUILDING PERMIT.

NO.	DATE	REVISION	BY
2	9/2/22	PER COMMENTS / SITE CHANGE	JVA
1	5/3/22	PER COMMENTS	JVA

NORTH ARROW

© Alteration of this drawing, except by a Licensed Professional Engineer or Architect in limited alteration as to his own work, is illegal. Additions must be identified with his name and signature and date of alteration.
• The user of this drawing shall verify all dimensions shown on the drawing.
• This line is one inch long

DRAWN BY:	KMC	
CHECKED BY:	JVA	
DATE:	FEB 2022	
SCALE:	AS NOTED	



10 C500 SAWCUT
NO SCALE



11 C500 CAULKED EXPANSION JOINT
NO SCALE



12 C500 CURB END
NO SCALE



NOTE:
JOINT SEALANT STRIP SHALL BE "QUIKJOINT", MANUFACTURED BY QUIKPAVE PRODUCTS, INC. OR APPROVED EQUAL.

13 C500 PAVEMENT KEY
NO SCALE



NOTES:
1. ALL CONCRETE SHALL BE MINIMUM 4,000 PSI.
2. WHERE MATERIAL IS NOT USED THE CITY OF POUGHKEEPSIE WILL BE CREDITED IN AREAS WHERE MORE THAN THE SPECIFIED AMOUNT OF MATERIAL IS USED. MAJOR GRADE CHANGES WILL BE APROVED BY THE CITY ENGINEERING DEPT. AND WILL BE PAID UNDER APPROPRIATE ITEMS.
3. UPON COMPLETION OF CURING ALL CONCRETE SURFACES SHALL BE COATED WITH SODIUM CHLORIDE INHIBITING SEALER AS REQ'D.

SIDEWALK DETAIL REPLACE & NEW

CITY OF POUGHKEEPSIE ENGINEERING DEPARTMENT 62 CIVIC CENTER PLAZA POUGHKEEPSIE, NY 12601	PROJECT: 001-DET	SIDEWALK DETAIL	
	DATE: 5-16-06		
	SCALE: AS NOTED		
	DRAWN BY: JP		

15 C500 BITUMINOUS CONCRETE PAVEMENT
NO SCALE



16 C500 ADA 12" PAVER
NO SCALE



NOTE:
1. CONCRETE SHALL BE MINIMUM 4,000 PSI

FORMED CURB DETAIL

CITY OF POUGHKEEPSIE ENGINEERING DEPARTMENT 62 CIVIC CENTER PLAZA POUGHKEEPSIE, NY 12601	FILE NO.: 001-DET	FORMED CURB DETIAL	1
	DATE: 3-8-00		
	SCALE: AS NOTED		
	DRAWN BY: JP		PAGE NO.

18 C500 ADA PAVER INSTALLATION DETAIL
NO SCALE



NOTE: ALONG CURB RAMPS, SLOPE OF DROP CURB TO MATCH CURB RAMP.

19 C500 DROP CURB
NO SCALE



'H'	'A'	'B'
3'-6"	1'-0"	2'-6"
4'-6"	1'-6"	3'-0"
5'-6"	2'-6"	3'-6"

NOTE:
1. SITTING WALLS ARE NOT STRUCTURALLY CONNECTED TO THE BUILDING FOUNDATION.
2. 4" DIAMETER SCUPPERS AS REQUIRED BY SITE PLAN OR AS OTHERWISE INDICATED BY THE ENGINEER.
3. LIGHTING – AS REQUIRED BY SITE PLAN OR OTHERWISE INDICATED BY THE ARCHITECT.

20 C500 SITTING WALL
NO SCALE



21 C500 ASPHALT SIDEWALK
NO SCALE



GENERAL NOTES:

DITCH WIDTH SHALL EXTEND A MINIMUM OF ONE AND ONE-HALF FT. (1 1/2') FROM THE EDGES.

REPLACED BASE MATERIAL OVER TRENCH SHALL BE TWICE THE THICKNESS OF THE BASE. (MINIMUM THICKNESS OF 8 INCHES).

BASE MATERIAL SHALL BE PLACED IN TWO OR THREE LAYERS AND EACH LAYER THOROUGHLY ROLLED OR TAMPED.

ASPHALTIC CONCRETE PAVEMENT JOINTS SHALL BE MECHANICALLY SAWED.

ALL JOINTS TO BE SQUARED TO THE EXISTING EDGE OF CURB AND/ OR PAVEMENT, AND TACK COATED PER DETAIL.

TOP COURSE SURFACE REPLACEMENT SHALL EXTEND A MINIMUM OF ONE FOOT (1') FROM THE EDGES OF THE OPEN CUT ONTO THE ROAD BASE..

TOP COURSE REPLACEMENT SHALL BE MINIMUM OF TWO INCHES (2") OF ASPHALTIC CONCRETE.

FLEXIBLE PAVEMENT AND TRENCH LIMITS DETAIL
SCALE: N.T.S.

CITY OF POUGHKEEPSIE ENGINEERING DEPARTMENT 62 CIVIC CENTER PLAZA POUGHKEEPSIE, NY 12601	FILE NO.: 001-DET	FLEXIBILE PAVEMENT DETAIL	1
	DATE: 2-27-12		
	SCALE: AS NOTED		
	DRAWN BY: JP		PAGE NO.



NOTE:
CONTRACTOR TO PROVIDE ALL NECESSARY PLATING TO FACILITATE CONCRETE CURING OPERATIONS

RIGID PAVEMENT AND TRENCH LIMITS DETAIL
SCALE: N.T.S.

CITY OF POUGHKEEPSIE ENGINEERING DEPARTMENT 62 CIVIC CENTER PLAZA POUGHKEEPSIE, NY 12601	FILE NO.: 001-DET	RIGID PAVEMENT DETAIL	1
	DATE: 5-16-06		
	SCALE: AS NOTED		
	DRAWN BY: JP		PAGE NO.

ROHDE, SOYKA & ANDREWS
Consulting Engineers PC
Poughkeepsie, N.Y. 12601
(845) 452-7515
Fax: (845) 452-8353
40 Garden Street

117 NORTH HAMILTON
NORTH HAMILTON STREET
CITY OF POUGHKEEPSIE
DUTCHESS COUNTY, NEW YORK

DETAILS #1

PROJECT NUMBER: 21-786-01

DRAWING NUMBER: C500

6 OF 9



NOTES:

1. EXISTING SANITARY LINE TO BE EXCAVATED TO A DEPTH OF 14-INCHES +/- BELOW PIPE.
2. 7-FT X 7-FT CONCRETE SLAB SHALL BE POURED AND CENTERED BENEATH PIPE. CONCRETE SHALL BE 4000 PSI FIBER REINFORCED. FIBERS TO BE POLY PROPYLENE FIBERS FOR CONCRETE AT NOT LESS THAN 1.0 LB/CY
3. DOGHOUSE SECTION SHALL BE LOWERED IN PLACE OVER THE EXISTING 8" SANITARY LINE.
4. CONCRETE SHALL BE POURED TO A DEPTH OF 6-INCHES AND THE FORMING OF THE CHANNEL FOR THE PROPOSED 10-INCH SANITARY LINE SHALL BE COMPLETED.
5. THE INLET AND OUTLET OF THE DOGHOUSE SHALL BE CEMENTED AND TAR COATED TO INSURE WATER TIGHTNESS.
6. THE MANHOLE WILL THEN BE HYDROSTATICALLY OR VACUUM TESTED PRIOR TO BACKFILLING TO ENSURE WATER TIGHTNESS.
7. THE EXISTING 8-INCH MAIN WILL BE REMOVED FOR THE COMPLETION OF THE CHANNEL WITH ADDITIONAL CONCRETE

(3/C501) DOGHOUSE MANHOLE
NO SCALE



NEW MANHOLE DETAIL
NOT TO SCALE
REMOVE AND REPLACE EXISTING MANHOLE WITH MANHOLE SECTIONS.

CITY OF POUGHKEEPSIE ENGINEERING DEPARTMENT 62 CIVIC CENTER PLAZA POUGHKEEPSIE, NY 12601	FILE NO.: MANHOLE	TYPICAL MANHOLE DETAIL	1
	DATE: 7-2-02		
	SCALE: N.T.S.		
	DRAWN BY: JP		PAGE NO.

GENERAL NOTES

1. WATER LINES CROSSING OVER SANITARY OR STORM SEWERS SHALL HAVE A MINIMUM VERTICAL SEPARATION OF 18 INCHES FROM TOP OF SEWER TO BOTTOM OF WATER LINE.
2. WATER LINES RUNNING PARALLEL TO SANITARY SEWERS SHALL MAINTAIN A VERTICAL SEPARATION OF 18 INCHES ABOVE THE SEWER AND A HORIZON- TAL SEPARATION OF 10 FEET FROM THE SEWER. SANITARY SEWERS LOCAT- ED NEARER THAN THIS MINIMUM SEPARATION REQUIREMENT SHALL BE DUCTILE IRON, CLASS 52, CEMENT LINED, MECHANICAL JOINT PRESSURE PIPE.
3. WATER LINES CROSSING UNDER SANITARY OR STORM SEWERS SHALL HAVE:
   A. A MINIMUM VERTICAL SEPARATION OF 18" FROM TOP OF WATER LINE TO BOTTOM OF SEWER (UNLESS SHOWN OTHERWISE).
   B. ADDITIONAL STRUCTURAL SUPPORT FOR THE SEWER TO PREVENT DEFLECTION.
   C. THE 18 FOOT LENGTH OF WATER PIPE SHALL BE CENTERED AT THE POINT OF CROSSING SUCH THAT THE JOINTS WILL BE EQUIDISTANT FROM THE SEWER.



(5/C501) WATER AND SEWER SEPARATION DISTANCES
NO SCALE



(6/C501) SECTION ALONG MANHOLE TROUGH
NO SCALE



(7/C501) SECTION THRU MANHOLE TROUGH
NO SCALE



(8/C501) FLEXIBLE CONNECTION AT MANHOLE
FOR PIPES 4" TO 16"
NO SCALE





DRAINBASIN STANDARD GRATE
FOR MH-1 USE SOLID COVER

NOTE:
BACK-FILL MATERIAL FOR THE SIDES OF THE STRUCTURE SHALL BE NATIVE MATERIAL IF SUITABLE, (NO PARTICLES LARGER THAN 4" IN DIAMETER). BACK-FILL SHALL BE PLACED UNIFORMLY IN 12" LIFTS AND COMPACTED TO A MINIMUM OF 90%.

(9/C501) DRAINBASIN – GRASSED AREAS
NO SCALE

NOTES
1. ALL BASINS ARE TO BE PRECAST CONCRETE DESIGNED FOR H-20 HIGHWAY LOADING PLUS PLUS 25% IMPACT.
2. ALL COMPONENTS TO CONFORM TO NYSDOT NYSDOT SPECIFICATIONS, LATEST EDITION.
3. SLOPE ADJACENT GRADES 2% MINIMUM TO ALL BASINS OR AS SHOWN.



(14/C501) CURBLESS TYPE CATCHBASIN
(ROADS AND PARKING AREAS)
NO SCALE



(10/C501) MANHOLE LID & FRAME
NO SCALE



TAPPING SLEEVE & VALVE
SCALE: N.T.S.

CITY OF POUGHKEEPSIE ENGINEERING DEPARTMENT 62 CIVIC CENTER PLAZA POUGHKEEPSIE, NY 12601	TAPPING SLEEVE & VALVE	DATE: 9/15/2014



STANDARD DROP CONNECTION
NTS

CITY OF POUGHKEEPSIE ENGINEERING DEPARTMENT 62 CIVIC CENTER PLAZA POUGHKEEPSIE, NY 12601	FILE NO.: 001-DET	STANDARD DROP CONNECTION	1
	DATE: 3-15-07		
	SCALE: AS NOTED		
	DRAWN BY: JAC		PAGE NO.



REFUSE ENCLOSURE WALL SECTION
NO SCALE



REFUSE ENCLOSURE GATE POST
NO SCALE



REFUSE ENCLOSURE PLAN
NO SCALE

(15/C500) REFUSE ENCLOSURE
NO SCALE



(11/C501) PLASTIC MANHOLE STEP
NO SCALE



UTILITY TRENCH DETAIL IN PUBLIC R.O.W.
SCALE: 1/4" =1'-0"

NOTES:
1. DITCH WIDTH SHALL EXTEND A MINIMUM OF ONE AND ONE-HALF FT. FROM THE EDGES OF THE TRENCH.
2. REPLACED BASE MATERIAL OVER TRENCH SHALL BE ITEM 4 COMPACTED IN 12" LIFTS.
3. PIPE BEDDING SHALL BE A MINIMUM OF 6" ABOVE AND BELOW PIPE
4. ALL JOINTS SHALL BE MECHANICALLY SAWED.
5. ALL JOINTS SHALL BE SQUARED TO THE EXISTING EDGE OF CURB AND/OR PAVEMENT, AND TACK COATED PER DETAIL.
6. ROAD SURFACE REPLACEMENT SHALL BE MINIMUM OF SIX INCHES OF ASPHALIC CONCRETE.
7. BINDER COURSE ASPHALT PAVEMENT TO BE PLACED IN TWO LIFTS.

CITY OF POUGHKEEPSIE ENGINEERING DEPARTMENT 62 CIVIC CENTER PLAZA POUGHKEEPSIE, NY 12601	PROJECT: LSRP	TRENCH AND PAVEMENT DETAIL	4
	DATE: 10-30-2018		
	SCALE: NTS		
	DRAWN BY: JAC		PAGE NO.



RESIDENTIAL CLEAN-OUT DETAIL
SCALE: 3/4"-1'-0"

CITY OF POUGHKEEPSIE ENGINEERING DEPARTMENT 62 CIVIC CENTER PLAZA POUGHKEEPSIE, NY 12601	RESIDENTIAL SANITARY CLEAN-OUT	DATE: 9/22/2014



NOTES:
1. WHEN THE ELEVATION OF THE SEWER CAN NOT BE VARIED TO MEET THE ABOVE REQUIREMENTS, THE WATERMAIN SHALL BE RELOCATED TO PROVIDE THIS REQUIRED SEPARATION OR RECONSTRUCTED WITH MECHANICAL JOINT PIPE FOR A DISTANCE OF TEN (10) FEET ON EACH SIDE OF THE SEWER. ONE FULL, UNCUT LENGTH OF WATERMAIN SHALL BE CENTERED OVER THE SEWER SO THAT BOTH JOINTS WILL BE AS FAR AWAY FROM THE SEWER AS POSSIBLE.
2. WHEN IT IS IMPOSSIBLE TO OBTAIN VERTICAL SEPARATION AS STIPULATED ABOVE, BOTH THE WATERMAIN AND THE SEWERMAIN SHALL BE CONSTRUCTED OF SLIP ON OR OF MECHANICAL PIPE JOINTS, CAST IRON PIPE OR SDR 26 PVC COMPLYING WITH PUBLIC WATER SUPPLY DESIGN STANDARDS OF THE AGENCY AND BE PRESSURE TESTED TO 150 PSI TO ASSURE WATER TIGHTNESS.

WATERLINE OFFSET DETAIL
SCALE: N.T.S.

CITY OF POUGHKEEPSIE ENGINEERING DEPARTMENT 62 CIVIC CENTER PLAZA POUGHKEEPSIE, NY 12601	FILE NO.: 001-DET	WATERLINE OFFSET	1
	DATE: 3-6-00		
	SCALE: AS NOTED		
	DRAWN BY: JP		PAGE NO.

NOTES
1. ALL BASINS ARE TO BE PRECAST CONCRETE DESIGNED FOR H-20 HIGHWAY LOADING PLUS PLUS 25% IMPACT.
2. ALL COMPONENTS TO CONFORM TO NYSDOT NYSDOT SPECIFICATIONS, LATEST EDITION.
3. SLOPE ADJACENT GRADES 2% MINIMUM TO ALL BASINS OR AS SHOWN.



(15/C501) CURB TYPE CATCHBASIN
NO SCALE



NOTES:
1. ALL FITTINGS SHALL BE GASKETED.
2. CLEAN OUTS SHALL BE SAME DIAMETER (D) AS SERVICE LINE.

(16/C501) DOUBLE CLEANOUT
NO SCALE



NOTES:
1. FOR PIPE GREATER THAN 15" ALL PIPE JOINTS SHALL BE CONSTRUCTED BY MEDTHODS APPROVED BY THE CITY ENGINEER.

TYPICAL SANITARY SEWER PIPE REPAIR OR WYE INSTALLATION DETAIL
SCALE: N.T.S.

FILE: *.DWG	TYPICAL SANITARY SEWER PIPE REPAIR OR WYE INSTALLATION DETAIL	CITY OF POUGHKEEPSIE ENGINEERING DEPARTMENT 62 CIVIC CENTER PLAZA POUGHKEEPSIE, NY 12601	1
DATE: 03-02-2009			
SCALE: AS NOTED			
DRAWN BY: JTK			PAGE NO.



NOTE
1. REMOVE ALL ROCKS GREATER THAN 2" IN ANY DIMENSION FROM IN-SITU MATERIAL PRIOR TO BACKFILLING AND COMPACTING.
2. 5'-0" MIN COVER FROM TOP OF PIPE TO FINISHED GRADE FOR WATER. 4'-6" MIN COVER FROM TOP OF PIPE TO FINISHED GRADE FOR SEWER.
3. PLACE MAGNETIC LOCATOR TAPE 12" BELOW FINISHED GRADE FOR WATER AND SEWER.
4. BEDDING, PIPE ZONE MATERIAL AND TRENCH BACKFILL TO CONFORM TO TOWN OF POUGHKEEPSIE WATER NOTE #18 FOR WATER AND SANITARY AND SEWER NOTE #10 FOR SEWER. TOWN OF POUGHKEEPSIE NOTES ARE LOCATED ON C-4.
5. IF REQUIRED AND AUTHORIZED BY THE ENGINEER OR THE TOWN, INSULATION SHALL BE INSTALLED PER THIS NOTE AND DETAIL. INSULATION SHALL BE CENTERED ON THE PIPE AND EXTEND THE WIDTH OF THE TRENCH OR 2' MINIMUM WHICHEVER IS LESS.

(13/C501) TRENCHING
NO SCALE

NO.	DATE	REVISION	BY

NORTH ARROW

- Alteration of this drawing, except by a Licensed Professional Engineer or Architect is illegal. Any alteration by a Professional Engineer or Architect must be indicated and bear his/her seal, signature and date of alteration.
- The user of this drawing shall verify all dimensions shown hereon and the scale of this drawing.
- This line is one inch long.

DRAWN BY:	KMC
CHECKED BY:	JVA
DATE:	FEB 2022
SCALE:	AS NOTED

ROHDE, SOYKA & ANDREWS
Consulting Engineers PC
40 Garden Street Poughkeepsie, N.Y. 12601 (845) 452-7515 Fax: (845) 452-8335

117 NORTH HAMILTON
NORTH HAMILTON STREET
CITY OF POUGHKEEPSIE
DUTCHESS COUNTY, NEW YORK

DETAILS #2

PROJECT NUMBER: 21-786-01

DRAWING NUMBER: C501
7 OF 9

1 STABILIZED CONSTRUCTION ENTRANCE (C502) — NO SCALE



CONSTRUCTION SPECIFICATIONS

1. Stone Size – Use 2" stone, or reclaimed or recycled concrete equivilent.
2. Length – As required, but not less than 50 feet (except on a single residence lot where a 30 foot minimum length would apply).
3. Thickness – Not less than six (6) inches.
4. Width – Ten (10) foot minimum, but not less than the full width at points where ingress or egress occurs.
5. Filter Cloth – Will be placed over the entire area prior to placing of stone. Filter will not be required on a single family residence lot.
6. Surface Water – All surface water flowing or diverted toward construction entrances shall be piped across the entrance. If piping is impractical, a mountable berm with 5:1 slopes will be permitted.
7. Maintenance – The entrance shall be maintained in a condition which will prevent tracking or flowing of sediment onto public rights-of-way. This may require periodic top dressing with additional stone as conditions demand and repair and/or cleanout of any measures used to trap sediment. All sediment spilled, dropped, washed or tracked onto public rights-of-way must be removed immediately.
8. Washing – Wheels shall be cleaned to remove sediment prior to entrance onto public rights-of-way. When washing is required, it shall be done on an area stabilized with stone and which drains into an approved sediment trapping device.
9. Periodic inspection and needed maintenance shall be provided after each rain.

STABILIZED CONSTRUCTION ENTRANCE

CITY OF POUGHKEEPSIE ENGINEERING DEPARTMENT 62 CIVIC CENTER PLAZA POUGHKEEPSIE, NY 12601	FILE NO.: 001-DET DATE: 3-6-00 SCALE: AS NOTED DRAWN BY: JP	STABILIZED CONSTRUCTION ENTRANCE	1 PAGE NO.

2 STABILIZED CONSTRUCTION ROAD AND PARKING AREAS (C502) — NO SCALE



NOTE:

1. STONE–SIZE: USE NYS DOT SUB–BASE TYPES 1,2,3,4 OR EQUIVALENT AS SPECIFIED. LARGER STONE CAN BE USED IN AREAS WITH HEAVY CONSTRUCTION EQUIPMENT TRAFFIC.
2. THICKNESS: NOT LESS THAN SIX (6) INCHES.
3. WIDTH: 24' MINIMUM.
4. DRAINAGE: PROVIDE SURFACE DRAINAGE AND DIVERT EXCESS RUNOFF TO STABILIZED AREAS.
5. ROAD GRADE: A MAXIMUM OF 12% IS RECOMMENDED, ALTHOUGH GRADES OF UP TO 15% ARE POSSIBLE FOR SHORT DISTANCES.
6. MAINTENANCE: INSPECT CONSTRUCTION ROADS PERIODICALLY. TOP DRESS WITH NEW GRAVEL AS NEEDED.

3 SILT FENCE (C502) — NO SCALE



CONSTRUCTION SPECIFICATIONS

1. WOVEN WIRE FENCE TO BE FASTENED SECURELY TO FENCE POSTS WITH WIRE TIES OR STAPLES. POSTS SHALL BE STEEL EITHER "T" OR "U" TYPE OR HARDWOOD.
2. FILTER CLOTH TO BE TO BE FASTENED SECURELY TO WOVEN WIRE FENCE WITH TIES SPACED EVERY 24" AT TOP AND MID SECTION. FENCE SHALL BE WOVEN WIRE, 12 1/2 GAUGE, 6" MAXIMUM MESH OPENING.
3. WHEN TWO SECTIONS OF FILTER CLOTH ADJOIN EACH OTHER THEY SHALL BE OVER-LAPPED BY SIX INCHES AND FOLDED. FILTER CLOTH SHALL BE EITHER FILTER X, MIRAFI 100X, STABILINKA T140N, OR APPROVED EQUIVALENT.
4. PREFABRICATED UNITS SHALL BE GEOFAB, ENVIROFENCE, OR APPROVED EQUIVALENT.
5. MAINTENANCE SHALL BE PERFORMED AS NEEDED AND MATERIAL REMOVED WHEN "BULGES" DEVELOP IN THE SILT FENCE.

CITY OF POUGHKEEPSIE ENGINEERING DEPARTMENT 62 CIVIC CENTER PLAZA POUGHKEEPSIE, NY 12601	SILT FENCE	DATE: 9/18/2014

EROSION AND SEDIMENT CONTROL NOTES

1. THE CONSTRUCTION MANAGER IS TO COORDINATE AND BE RESPONSIBLE FOR SITE EROSION AND SEDIMENT CONTROL. THE CONSTRUCTION MANAGER MAY DELEGATE EROSION AND SEDIMENT CONTROL DUTIES TO CONTRACTORS OR SUBCONTRACTORS BASED UPON THE FIRM WITH THE APPROPRIATE EQUIPMENT OR WHO IS RESPONSIBLE FOR CREATING A VIOLATION (IE SEDIMENT TRACKING, KNOCKING DOWN SILT FENCE, BY–PASSING STABILIZED CONSTRUCTION ENTRANCE, ETC). THE CONSTRUCTION MANAGER IS RESPONSIBLE FOR THE DAY TO DAY IMPLEMENTATION OF THE SWPPP AND PREVENTING SEDIMENT–LADEN DISCHARGES FROM THE CONSTRUCTION SITE.
2. ALL EROSION AND SEDIMENT CONTROL PRACTICES ARE TO BE INSTALLED PRIOR TO SOIL DISTURBANCE, OR IN THEIR PROPER SEQUENCE, AND MAINTAINED UNTIL PERMANENT PROTECTION OR STABILIZATION IS ESTABLISHED. VEGETATED AREAS ARE CONSIDERED TO HAVE ACHIEVED FINAL STABILIZATION ONCE 80% COVERAGE DENSITY HAS BEEN ACHIEVED.
3. ANY DISTURBED AREAS THAT WILL BE LEFT EXPOSED MORE THAN TEN (10) DAYS, AND NOT SUBJECT TO CONSTRUCTION TRAFFIC, WILL IMMEDIATELY RECEIVE A TEMPORARY SEEDING AND MULCHED WITH STRAW OR EQUIVALENT MATERIAL AT A RATE OF TWO (2) TONS PER ACRE, ACCORDING TO STATE STANDARDS.
4. PERMANENT VEGETATION TO BE SEEDED OR SODDED ON ALL EXPOSED AREAS WITHIN TEN (10) DAYS AFTER FINAL GRADING. MULCHING IS REQUIRED ON ALL SEEDING. WHEN HYDROSEEDING, REFER TO MANUFACTURER'S INSTRUCTIONS.
5. ALL WORK IS TO BE DONE IN ACCORDANCE WITH THE "NEW YORK STANDARDS AND SPECIFICATIONS FOR EROSION AND SEDIMENT CONTROL," LATEST EDITION.
6. IMMEDIATELY FOLLOWING INITIAL DISTURBANCE OR ROUGH GRADING, ALL CRITICAL AREAS SUBJECT TO EROSION (I.E., STEEP SLOPES) WILL RECEIVE A TEMPORARY SEEDING IN COMBINATION WITH STRAW MULCH OR A SUITABLE EQUIVALENT, AT A RATE OF TWO (2) TONS PER ACRE, ACCORDING TO STATE STANDARDS OR EROSION CONTROL MATTING.
7. THE STANDARD FOR STABILIZED CONSTRUCTION ENTRANCE REQUIRES THE INSTALLATION OF A STONE PAD OF 2" STONE A MINIMUM OF 6" THICK, AT ALL CONSTRUCTION DRIVEWAYS, PRIOR TO INITIAL SITE DISTURBANCE. THE OWNER IS TO PROVIDE THE LOCATION OF THE STABILIZED CONSTRUCTION ENTRANCE. THE OWNER SHALL DESIGNATE AN AREA OR AREAS FOR CONSTRUCTION VEHICLE PARKING.
8. AT THE TIME THE SITE PREPARATION FOR PERMANENT VEGETATIVE STABILIZATION IS GOING TO BE ACCOMPLISHED, ANY SOIL THAT WILL NOT PROVIDE A SUITABLE ENVIRONMENT TO SUPPORT ADEQUATE VEGETATIVE GROUND COVER, SHALL BE REMOVED OR TREATED IN SUCH A WAY THAT IT WILL PERMANENTLY ADJUST THE SOIL CONDITIONS AND RENDER IT SUITABLE FOR VEGETATIVE GROUND COVER. IF THE REMOVAL OR TREATMENT OF THE SOIL WILL NOT PROVIDE SUITABLE CONDITIONS, NONVEGETATIVE MEANS OF PERMANENT GROUND STABILIZATION WILL HAVE TO BE EMPLOYED.
9. UNFILTERED DEWATERING IS NOT PERMITTED. TAKE ALL NECESSARY PRECAUTIONS DURING ALL DEWATERING OPERATIONS TO MINIMIZE SEDIMENT TRANSFER. ANY DEWATERING METHODS USED MUST BE IN ACCORDANCE WITH STATE STANDARDS. DO NOT DISCHARGE DOWN STEEP SLOPES.
10. SHOULD THE CONTROL OF DUST AT THE SITE BE NECESSARY, THE SITE WILL BE SPRINKLED UNTIL THE SURFACE IS WET, TEMPORARY VEGETATIVE COVER SHALL BE ESTABLISHED OR MULCH SHALL BE APPLIED IN ACCORDANCE WITH STATE STANDARDS FOR EROSION CONTROL.
11. ALL SOIL WASHED, DROPPED, SPILLED, OR TRACKED OUTSIDE THE LIMIT OF DISTURBANCE OR ONTO PARKING LOTS, SIDEWALKS OR PUBLIC RIGHTS–OF–WAY SHALL BE REMOVED IMMEDIATELY.
12. THE PROPERTY OWNER SHALL BE RESPONSIBLE FOR ANY EROSION AND SEDIMENTATION THAT MAY OCCUR OFF–SITE AS A RESULT OF CONSTRUCTION OF THE PROJECT.
13. STOCKPILE AND STAGING LOCATIONS DETERMINED IN THE FIELD SHALL BE PLACED WITHIN THE LIMITS OF DISTURBANCE ACCORDING TO THE CERTIFIED PLAN. STAGING AND STOCKPILES NOT LOCATED WITHIN THE LIMITS OF DISTURBANCE WILL REQUIRE A REVISED EROSION AND SEDIMENT CONTROL PLAN. THE OWNER RESERVES THE RIGHT TO DETERMINE WHEN A NEW AND SEPARATE EROSION AND SEDIMENT CONTROL PLAN WILL BE REQUIRED FOR THESE ACTIVITIES.
14. ALL SOIL STOCKPILES ARE TO BE TEMPORARILY STABILIZED IN ACCORDANCE WITH THE EROSION AND SEDIMENT CONTROL PLAN. SURROUND THE SOIL STOCKPILE WITH A RING OF SILT FENCE. DO NOT LOCATE A STOCKPILE AREA WITHIN 100 FEET OF A WETLAND BOUNDARY. DO NOT LOCATE A STOCKPILE AREA CLOSER THAN 20 FEET TO THE TOP OF A STEEP SLOPE. TEMPORARILY SEED OR COVER THE SOIL STOCKPILE IF IT WILL NOT BE DISTURBED FOR TEN (10) DAYS.
15. ALL PERMANENT EROSION AND SEDIMENT CONTROL MEASURES SHALL BE MAINTAINED BY THE PROPERTY OWNER, AND SHALL BECOME THEIR RESPONSIBILITY.
16. PAVEMENT AREAS ARE TO BE KEPT CLEAN AT ALL TIMES. ALL ROADS/DRIVEWAYS ARE TO BE SWEPT CLEAN AT THE END OF EACH WORKDAY OR AS MAY OTHERWISE BE DICTATED BY THE WORK BEING PERFORMED. PLEASE ALSO SEE NOTE 11. ALL PARKING LOTS, AND ACTIVE PEDESTRIAN WALKS ARE TO BE KEPT CLEAN ON A CONTINUOUS BASIS WHICH MAY REQUIRE MORE FREQUENT SWEEPING.
17. DURING CONSTRUCTION, ANY ADDITIONAL CONTROL MEASURES AS DEEMED NECESSARY TO PREVENT EROSION OR CONTROL SEDIMENT BEYOND THOSE MEASURES SHOWN ON THE APPROVED PLAN SHALL BE INSTALLED OR EMPLOYED AT THE DIRECTION OF THE ENGINEER, THE OWNER, THE PROJECT MANAGER OR THE CONSTRUCTION MANAGER.
18. AFTER CONSTRUCTION IS COMPLETE AND FINAL STABILIZATION HAS BEEN ACHIEVED, REMOVE ALL TEMPORARY EROSION AND SEDIMENT CONTROL PRACTICES. INSPECT ALL PREVIOUSLY SEEDED GRASS/LAWN AREAS FOR BARE OR THIN SPOTS AND RE–SEED AND MULCH AS NEEDED.
19. IN ACCORDANCE WITH GP–0–20–001, A FINAL STABILIZATION INSPECTION AND SIGN–OFF BY THE LOCAL MS4 IS REQUIRED BEFORE THE NOTICE OF TERMINATION (NOT) CAN BE FILED WITH NYSDEC.

CONSTRUCTION SEQUENCE

1. PRE–CONSTRUCTION

A. PRE–CONSTRUCTION MEETING

1. CONSTRUCTION MANAGERS, CONTRACTORS AND SUBCONTRACTORS PERFORMING EARTH–DISTURBING ACTIVITIES MUST ATTEND PRE–CONSTRUCTION MEETING. THE MEETING IS TO BE COORDINATED BY THE CONSTRUCTION MANAGERS.

2. CONSTRUCTION MANAGERS, CONTRACTORS, AND SUBCONTRACTORS PERFORMING EARTH DISTURBING ACTIVITIES MUST PROVIDE SIGNED CONTRACTOR CERTIFICATIONS AND IDENTIFY THE 'TRAINED CONTRACTOR' WHO WILL BE ON–SITE ON A DAILY BASIS IN ACCORDANCE WITH NYSDEC SPDES GENERAL PERMIT FOR STORMWATER DISCHARGES FROM CONSTRUCTION ACTIVITIES, GP–0–20–001. THE TRAINING CERTIFICATE NUMBER FOR THE 'TRAINED CONTRACTOR' MUST BE PROVIDED IN ACCORDANCE WITH CITY OF POUGHKEEPSIE.

3. IN ADDITION, THE 'QUALIFIED INSPECTOR,' SWPPP PREPARER, MS4 EROSION & SEDIMENT CONTROL INSPECTOR, AND OWNER'S REPRESENTATIVE MUST ATTEND THE PRE–CONSTRUCTION MEETING.

B. MARK LIMITS OF DISTURBANCE

C. DIVERT OFF–SITE, CLEAN RUNOFF FROM ENTERING AREAS TO BE DISTURBED.

D. ESTABLISH CONSTRUCTION ENTRANCE(S)

1. ANY SEDIMENT TRACKED ONTO PUBLIC OR PRIVATE ROADWAYS, PARKING LOTS OR SIDEWALKS OUTSIDE THE CONSTRUCTION AREA IS TO BE CLEANED/REMOVED ON A DAILY BASIS.
2. PRESERVE EXISTING ASPHALT WHERE POSSIBLE FOR USE AS CONSTRUCTION ENTRANCES AND CONSTRUCTION ROUTES.

E. ESTABLISH CONTRACTOR PARKING AND STAGING AREAS, IN ACCORDANCE WITH OWNER'S PREFERENCES. PROVIDE CONTRACTOR PARKING AND STAGING AREA STABILIZATION PRIOR TO USE.

F. INSTALL EROSION CONTROL MEASURES, SUCH AS SILT FENCE AND CATCHBASIN INLET PROTECTION, BEFORE LAND GRADING BEGINS.
1. SILT FENCE IS TO BE INSTALLED PARALLEL TO CONTOURS

G. INSTALL TREE PROTECTION FENCING.

2. CONSTRUCTION

A. LIMIT INITIAL GRADING TO AREAS THAT ARE NEEDED FOR EROSION AND SEDIMENT CONTROL.

B. STOCKPILE TOPSOIL AWAY FROM DRAINAGE PATHS, WATERBODIES AND THE TOP OF STEEP SLOPES. STABILIZE AS SOON AS POSSIBLE.

C. AVOID DISTURBANCE OF STEEP SLOPES
1. IF DISTURBANCE ON STEEP SLOPES IS REQUIRED, MINIMIZE AREA TO BE DISTURBED AND AMOUNT OF TIME AREA WILL BE DISTURBED. PLAN STEEP SLOPE DISTURBANCE DURING DRY WEATHER AND WHEN SOILS ARE NOT SATURATED. STABILIZE STEEP SLOPE DISTURBANCE AT THE END OF EACH WORKDAY. PROVIDE FINAL STABILIZATION AS SOON AS WORK ON THE STEEP SLOPE IS COMPLETED.

D. COMMENCE GENERAL SITE CONSTRUCTION

E. STABILIZE EXPOSED SOIL AS SOON AS POSSIBLE. IN AREAS WHERE SOIL DISTURBANCE ACTIVITY HAS BEEN TEMPORARILY OR PERMANENTLY CEASED, TEMPORARY AND/OR PERMANENT SOIL STABILIZATION MEASURES SHALL BE INSTALLED AND/OR IMPLEMENTED WITHIN TEN (10) DAYS FROM THE DATE THE SOIL DISTURBANCE ACTIVITY CEASED.

F. DIRECT ANY SEDIMENT RUNOFF INTO SEDIMENTATION TRAPS. IF THERE IS A SEDIMENTATION PROBLEM IN AN AREA WHERE THERE IS NO SEDIMENTATION TRAP CALLED FOR ON THE PLAN, CREATE A SEDIMENTATION TRAP AND NOTE ITS LOCATION ON THE STORMWATER DRAWING.

G. PREVENT SEDIMENT FROM BEING TRANSPORTED OFF–SITE.

H. ANY SEDIMENT TRACKED ONTO ROADS, PARKING LOTS, OR ACTIVE PEDESTRIAN WALKS SHALL BE SWEPT, AS NEEDED, BUT NOT LESS THAN ONE (1) TIME PER DAY.

3. MAINTENANCE AND INSPECTION DURING CONSTRUCTION

A. ALL EROSION AND SEDIMENT CONTROL MEASURES MUST BE MAINTAINED ON A REGULAR SCHEDULE DURING CONSTRUCTION.

B. INSPECTIONS MUST BE PERFORMED AT LEAST ONCE EVERY SEVEN (7) CALENDAR DAYS BY QUALIFIED PROFESSIONAL AS OUTLINED IN GP–0–20–001.

C. CONTRACTORS RESPONSIBLE FOR EROSION AND SEDIMENT CONTROL ARE TO INSPECT ALL PRACTICES AT LEAST ONCE A WEEK AND AFTER EVERY RAIN EVENT.

D. ENSURE THAT ALL PRACTICES ARE OPERATING AS DESIGNED.

E. ENSURE THAT NO SEDIMENT IS BEING TRANSPORTED OFF–SITE OR IS ENTERING THE DRAINAGE SYSTEM.

F. LOOK FOR EVIDENCE OF EROSION IN DISTURBED PORTIONS OF THE SITE.

G. ENSURE THAT SEDIMENT IS NOT BEING TRACKED ONTO PUBLIC OR PRIVATE ROADS, PARKING LOTS OR SIDEWALKS OUTSIDE THE CONSTRUCTION AREA.

H. RETAIN COPIES OF INSPECTION REPORTS ON–SITE WITH THE SWPPP. CONSTRUCTION MANAGER IS TO MAINTAIN SWPPP AND INSPECTION REPORTS ON–SITE.

4. FINAL GRADING & LANDSCAPING

A. ONCE CONSTRUCTION IS NEARING COMPLETION, IDENTIFY THE FINAL GRADING AND STABILIZATION PLAN.

B. ALL BARE AREAS MUST RECEIVE COVER. PERMANENT TOPSOIL AND VEGETATION SHOULD BE PLACED WHERE APPROPRIATE. REFER TO LANDSCAPING PLANS.

C. AREAS USED FOR CONSTRUCTION STAGING AND AREAS THAT WERE PREVIOUSLY IMPERVIOUS AND ARE NOW LAWN AREA ARE TO BE DE–COMPACTED PRIOR TO SPREADING OF TOPSOIL, SEED AND MULCH. REFER TO SWPPP FOR ADDITIONAL INFORMATION ON DE–COMPACTION.

D. OTHER AREAS SHALL RECEIVE COVER, SUCH AS STONE, MULCH OR RIPRAP, AS APPROPRIATE.

E. STABILIZATION MUST BE UNDERTAKEN NO LATER THAN 10 DAYS AFTER CONSTRUCTION ACTIVITY HAS CEASED.

F. FINAL PLANTING SCHEDULE TO BE DETERMINED BY LANDSCAPE ARCHITECT. IF CONSTRUCTION IS NEARING COMPLETION AT A TIME OF YEAR WHEN PLANTING IS NOT RECOMMENDED, PROVIDE TEMPORARY SEED AND MULCH IN PLACE OF LANDSCAPING UNTIL CONDITIONS ARE APPROPRIATE FOR FINAL PLANTING.

G. REMOVE TEMPORARY EROSION CONTROL MEASURES THAT WILL INTERFERE WITH FINAL GRADING AND LANDSCAPING.

5. POST–CONSTRUCTION

A. ENSURE THAT THE PERMANENT PRACTICES UTILIZED DURING CONSTRUCTION ARE SUITABLE TO FIT POST–CONSTRUCTION SITE CONDITIONS.

B. MINIMIZE THE RISK OF CONCENTRATED FLOW AND EROSION.

C. CLEAN AND PREPARE PERMANENT PRACTICES TO BE TURNED OVER TO THE OWNER/OPERATOR. PREPARE MANUAL AND DISCUSS OPERATION AND MAINTENANCE OF THE PERMANENT PRACTICE WITH THE OWNER/OPERATOR OR REPRESENTATIVE.

D. REMOVE TEMPORARY EROSION AND SEDIMENT CONTROL PRACTICES, SUCH AS SILT FENCE.

E. INSPECT PREVIOUSLY SEEDED GRASS/LAWN AREAS FOR BARE OR THIN SPOTS. RE–SEED AND MULCH AS NEEDED. WITH REMOVAL OF TEMPORARY E&SC PRACTICES, SUCH AS SILT FENCE, SEED AND MULCH AS NEEDED.

F. IN ACCORDANCE WITH GP–0–20–001, A FINAL STABILIZATION INSPECTION AND SIGN–OFF BY THE LOCAL MS4 IS REQUIRED BEFORE THE NOTICE OF TERMINATION (NOT) CAN BE FILED WITH NYSDEC.

4 TEMPORARY ORANGE CONSTRUCTION FENCE (C502) — NO SCALE



NOTES:

1. TEMPORARY ORANGE CONSTRUCTION FENCES SHALL BE USED TO SEPARATE CONSTRUCTION ACTIVITIES FROM PEDESTRIANS.
2. ALL TEMPORARY ORANGE CONSTRUCTION FENCING SHALL BE PLASTIC, 48" MINIMUM HEIGHT AND ORANGE IN COLOR.
3. TEMPORARY ORANGE CONSTRUCTION FENCE USED TO SEPARATE SIDEWALKS FROM CONSTRUCTION ACTIVITIES SHALL HAVE MINIMUM ENCROACHMENT TO THE SIDEWALK.
4. CONTRACTOR TO PROVIDE ANCHORAGE (I.E. SANDBAGS) FOR FENCE IF REQUIRED BY SITE CONDITIONS.

5 TEMPORARY CHAIN LINK PANEL FENCE DURING CONSTRUCTION (C502) — NO SCALE



NOTES:

1. TOP AND BOTTOM SELVAGE ON WIRE MESH SHALL BE KNUCKLED.
2. CONTRACTOR TO PROVIDE ANCHORAGE (I.E. SANDBAGS) FOR FENCE IF REQUIRED BY SITE CONDITIONS.
3. ATTACH OPAQUE SCREEN TO FENCE; MINIMUM 2–FT GAP BETWEEN GROUND SURFACE AND BOTTOM OF OPAQUE SCREEN.

6 STONE AND BLOCK DROP INLET PROTECTION (C502) — NO SCALE



CONSTRUCTION SPECIFICATIONS

1. LAY ONE BLOCK ON EACH SIDE OF THE STRUCTURE ON ITS SIDE FOR DEWATERING. FOUNDATION SHALL BE 2 INCHES MINIMUM BELOW REST OF INLET AND BLOCKS SHALL BE PLACED AGAINST INLET FOR SUPPORT.
2. HARDWARE CLOTH OR 1/2" WIRE MESH SHALL BE PLACED OVER BLOCK OPENINGS TO SUPPORT STONE.
3. USE CLEAN STONE OR GRAVEL 1/2–3/4 INCH IN DIAMETER PLACED 2 INCHES BELOW TOP OF THE BLOCK ON A 2:1 SLOPE OR FLATTER.
4. FOR STONE STRUCTURES ONLY, A 1 FOOT THICK LAYER OF THE FILTER STONE WILL BE PLACED AGAINST THE 3 INCH STONE AS SHOWN ON THE DRAWINGS.
5. MAXIMUM DRAINAGE AREA 1 ACRE.
6. PROTECT INLET PROTECTION FROM DAMAGE BY CONSTRUCTION TRAFFIC; SURROUND WITH TEMPORARY ORANGE CONSTRUCTION FENCE.
7. IN PAVED AREAS, ELIMINATE CONCRETE BLOCK FOR DEWATERING. USE STONE/GRAVEL FILTER.

7 STONE OUTLET SEDIMENT TRAP (C502) — NO SCALE



CONSTRUCTION SPECIFICATIONS

1. AREA UNDER EMBANKMENT SHALL BE CLEARED, GRUBBED, AND STRIPPED OF ANY VEGETATION AND ROOT MATERIAL. THE TRAP AREA SHALL BE CLEARED.
2. THE FILL MATERIAL FOR THE EMBANKMENT SHALL BE FREE OF ROOTS OR OTHER WOODY VEGETATION AS WELL AS OVERSIZED STONES, ROCKS, ORGANIC MATERIAL OR OTHER QUESTIONABLE MATERIAL. THE EMBANKMENT SHALL BE COMPACTED BY TRAVERSING WITH EQUIPMENT WHILE IT IS BEING CONSTRUCTED.
3. SEDIMENT SHALL BE REMOVED AND TRAP RESTORED TO ITS ORIGINAL DIMENSION WHEN THE SEDIMENT HAS ACCUMULATED TO 1/2 THE DESIGN DEPTH OF THE TRAP. REMOVED SEDIMENT SHALL BE DEPOSITED IN A SUITABLE AREA AND IN SUCH A MANNER THAT IT WILL NOT ERODE.
4. THE STRUCTURE SHALL BE INSPECTED AFTER EACH RAIN AND REPAIRS MADE AS NECESSARY.
5. CONSTRUCTION OPERATIONS SHALL BE CARRIED OUT IN SUCH A MANNER THAT EROSION AND WATER POLLUTION IS MINIMIZED.
6. THE STRUCTURE SHALL BE REMOVED AND THE AREA STABILIZED WHEN THE DRAINAGE AREA HAS BEEN PROPERLY STABILIZED.
7. ALL CUT AND FILL SLOPES SHALL BE 2 ON 1 OR FLATTER.
8. THE CRUSHED STONE USED IN THE OUTLET SHALL MEET AASHTO DESIGNATION M43, SIZE NO. 2. OR 24 OR ITS EQUIVALENT SUCH AS MSHA NO. 2 GRAVEL MEET-ING THE ABOVE GRADATION MAY BE USED IF CRUSHED STONE IS NOT AVAILABLE. CRUSHER RUN IS NOT ACCEPTABLE.

8 SILTSOXX (tm) SEDIMENT CONTROL ON PAVEMENT (C502) — NO SCALE



9 SOIL STOCKPILE (C502) — NO SCALE



10 FLARED END SECTION AND RIPRAP OUTLET PROTECTION (C502) — NO SCALE



11 ABOVE GRADE WASHOUT STRUCTURE (C502) — NO SCALE



GENERAL NOTES:

1. ACTUAL LOCATION DETERMINED IN THE FIELD.
2. CONCRETE WASHOUT STRUCTURE NEEDS TO BE CLEARLY MARKED WITH SIGNAGE NOTING DEVICE.

WASHOUT NOTES

1. ALL CONCRETE WASHOUT FACILITIES SHALL BE INSPECTED DAILY. DAMAGED OR LEAKING FACILITIES SHALL BE DE–ACTIVATED & REPAIRED, OR REPLACED IMMEDIATELY. EXCESS RAINWATER THAT HAS ACCUMULATED OVER HARDENED CONCRETE SHALL BE PUMPED TO A STABILIZED AREA, SUCH AS A GRASS FILTER STRIP.
2. ACCUMULATED MATERIAL SHALL BE REMOVED WHEN 75% OF THE STORAGE CAPACITY OF THE STRUCTURE IS FILLED. ANY EXCESS WASH WATER SHALL BE PUMPED INTO A CONTAINMENT VESSEL AND PROPERLY DISPOSED OF OFF–SITE.
3. DISPOSE OF ALL HARDENED MATERIAL OFF–SITE IN A CONSTRUCTION/DEMOLITION LANDFILL. ON–SITE DISPOSAL MAY BE ALLOWED IF THIS HAS BEEN APPROVED & ACCEPTED AS PART OF THE PROJECTS SWPPP. IN THAT CASE, THE MATERIAL SHOULD BE RECYCLED AS SPECIFIED, OR BURIED & COVERED WITH A MINIMUM OF TWO (2) FEET OF CLEAN COMPACTED EARTH–FILL THAT IS PERMANENTLY STABILIZED TO PREVENT EROSION.
4. THE PLASTIC LINER SHALL BE REPLACED WITH EACH CLEANING OF THE WASHOUT FACILITY.
5. INSPECT THE PROJECT SITE FREQUENTLY TO ENSURE THAT NO CONCRETE DISCHARGES ARE TAKING PLACE IN NON–DESIGNATED AREAS.
6. AS AN ALTERNATIVE, A LINED ROLL–OFF CONTAINER CAN BE USED FOR THE WASHOUT FACILITY.
7. THE CONCRETE WASHOUT FACILITY SHALL BE LOCATED A MINIMUM OF 100 FEET FROM DRAINAGE SWALES, WETLANDS, STREAMS, AND OTHER WATER BODIES. THE FACILITY SHALL BE LOCATED DOWN HILL OF ANY STORM DRAINAGE INLET OR OTHERWISE 100 FEET MINIMUM FROM SUCH STRUCTURES.

12 STORMTECH MC 3500 STORMWATER CHAMBER (C502) — NO SCALE

PERIMETER STONE MUST ALWAYS BE BROUGHT UP EVENLY WITH BACKFILL OF BED. PERIMETER STONE MUST EXTEND HORIZONTALLY TO THE EXCAVATION WALL FOR BOTH STRAIGHT OR SLOPED SIDEWALLS.



THE INSTALLED CHAMBER SYSTEM SHALL PROVIDE THE LOAD FACTORS SPECIFIED IN THE AASHTO LRFD BRIDGE DESIGN SPECIFICATIONS SECTION 12.12 FOR EARTH AND LIVE LOADS, WITH CONSIDERATION FOR IMPACT AND MULTIPLE VEHICLE PRESENCES.

NOTES:

1. INSPECTION PORTS MAY BE CONNECTED THROUGH ANY OF (6) CHAMBER CORRUGATION VALLEYS
2. ALL SCHEDULE 40 FITTINGS TO BE SOLVENT CEMENTED.









NO.	DATE	REVISION	BY
2	3/2/23	PER FINAL SWPP CHANGES	JVA
1	5/31/22	PER COMMENTS	JVA

NORTH ARROW

- Alteration of this drawing, except by a Licensed Professional Engineer or Architect is illegal. Any alteration by a Professional Engineer or Architect must be indicated and bear his/her seal, signature and date of alteration.
- The user of this drawing shall verify all dimensions shown hereon and the scale of this drawing.
- This line is one inch long.

DRAWN BY:	KMC
CHECKED BY:	JVA
DATE:	FEB 2022
SCALE:	AS NOTED

ROHDE, SOYKA & ANDREWS
Consulting Engineers PC
40 Garden Street Poughkeepsie, N.Y. 12601 (845) 452-7515 Fax: (845) 452-8335

117 NORTH HAMILTON
NORTH HAMILTON STREET
CITY OF POUGHKEEPSIE
DUTCHESS COUNTY, NEW YORK

ESC DETAILS

PROJECT NUMBER: 21–786–01

DRAWING NUMBER: C502

8 OF 9



1 L100 LANDSCAPE PLAN
1" = 20'

20 10 0 20 40
SCALE IN FEET



2 L100 GROUNDCOVER PLANTING
NO SCALE



3 L100 PLANTING
NO SCALE



4 L100 SHRUB PLANTING
NO SCALE



5 L100 STONE DIAPHRAGM
NO SCALE

NOTES

1. PROTECT ALL EXISTING VEGETATION TO REMAIN FROM DAMAGE DURING CONSTRUCTION.
2. USE EXTREME CAUTION TO PROTECT UTILITIES.
3. ALL PLANT MATERIAL SHALL BE NURSERY GROWN UNLESS OTHERWISE NOTED.
4. QUANTITIES GIVEN ON THE PLANTING LIST ARE FOR REFERENCE ONLY. THE CONTRACTOR SHALL VERIFY ALL QUANTITIES SHOWN ON THE LIST AND SHALL BE RESPONSIBLE FOR FURNISHING ALL MATERIALS REQUIRED TO COMPLETE THE PLANS.
5. THE CONTRACTOR SHALL VERIFY ALL GRADES, DIMENSIONS AND EXISTING CONDITIONS, AND REPORT ANY DISCREPANCIES TO THE ENGINEER.
6. ALL BEDS AND TREE SAUCERS AND OTHER AREAS NOTED SHALL RECEIVE 2 INCHES (MINIMUM) OF APPROVED MULCH (SHREDDED CEDAR).
7. CONTRACTOR SHALL GUARANTEE ALL PLANT MATERIAL FOR ONE YEAR FROM TIME OF ENGINEER'S FINAL WRITTEN APPROVAL.
8. TOP SOIL MIX SHALL INCLUDE:
   - 3 PARTS SCREENED TOPSOIL
   - 1PART SAND
   - 1 PART HUMUS
   - 5 LBS. SUPERPHOSPHATE PER CU. YD. OF MIX
9. CONTRACTOR TO COORDINATE PLANTING, SEEDING AND TREE WORK WITH OTHER TRADES.
10. CONTRACTOR IS RESPONSIBLE FOR RESTORING ALL AREAS DISTURBED DUE TO PLANTING OPERATIONS.

LEGEND

- EXISTING TREE
- PROPOSED TREE
- PROPOSED SHRUB
- PROPOSED GRASSES
- PROPOSED PERENNIALS

PLANT LIST

QTY	KEY	BOTANICAL NAME	COMMON NAME	SIZE	COMMENTS
Trees					
10	ERC	*Juniperus virginiana*	Eastern Red Cedar	5-6'	B&B
3	RM	*Acer rubrum*	Red Maple	2-2.5" C	B&B
Shrubs					
3	RTD	*Cornus alba* "siberica"	Red Twig Dogwood	3 – 5' Hgt	1 Gal
8	H	*Hydrangea paniculata* "little quick fire"	Hydrangea	3 – 5' Hgt	1 Gal
Grasses					
50	SG	*Panicum virgatum* "Shenandoah"	Switch Grass	1 Gal	18" O.C.
32	PD	*Sporobolus heteroepis*	Prairie Dropseed	1 Gal	18" O.C.
6	LBS	*Carex sprengelii*	Long Beaked Sedge	1 Gal	18" O.C.
Perennials					
12	PCF	*Echineacea purpurea*	Purple Cone Flower	2 Gal	
14	HM	*Agastache* "Summer Sky"	Hummingbird Mint	2 Gal	
15	S	*Sedum herbstfreude* "autumn joy"	Stonecrop	2 Gal	

ALL AREAS NOT OTHERWISE COVERED BY ASPHALT, BUILDINGS OR LANDSCAPE PLANTINGS, SHALL BE TOPSOILED, SEEDED WITH LAWN (GRASS) PLANTED.

NO.	DATE	REVISION	BY
4	9/8/22	PER COMMENTS	JVA
3	9/2/22	PER COMMENTS/ SITE CHANGE	JVA
2	7/5/22	PER CITY COMMENT	JVA
1	5/27/22	PER OWNER COMMENT	JVA

NORTH ARROW

- Alteration of this drawing, except by a Licensed Professional Engineer or Architect in illegal and a violation of law. Licensed Professional Engineer or Architect who has altered this drawing shall affix to the drawing his seal, the notation "altered by" followed by his signature and date of alteration.
- The user of this drawing shall verify all dimensions shown thereon and shall report any discrepancies to the Engineer.
- This line is one inch long

DRAWN BY: KMC
CHECKED BY: JVA
DATE: APRIL 2022
SCALE: 1" = 20'

ROHDE, SOYKA & ANDREWS
Consulting Engineers PC
40 Garden Street Poughkeepsie, N.Y. 12601
(845) 452-7515
Fax (845) 452-8535

117 NORTH HAMILTON
NORTH HAMILTON STREET
CITY OF POUGHKEEPSIE
DUTCHESS COUNTY, NEW YORK

LANDSCAPE PLAN

PROJECT NUMBER: 21-786-01

DRAWING NUMBER: L100
10 OF 10



1 C101 SITE PLAN
1" = 20'

NO.	DATE	REVISION	BY
4	9/2/22	PER COMMENTS/ SITE CHANGE	JVA
3	7/6/22	PER COMMENTS	JVA
2	7/5/22	PER CITY COMMENTS	JVA
1	5/3/22	PER COMMENTS	JVA

NORTH ARROW

© Alteration of this drawing, except by a Licensed Professional Engineer or Architect is illegal. Add alterer's Engineer or Architect is illegal. Add alterer's signature and date of alteration.
• The user of this drawing shall verify all dimensions shown hereon and shall report any discrepancies to the author of this drawing.
• This line is one inch long

DRAWN BY: KMC
CHECKED BY: JVA
DATE: JULY 22, 2022
SCALE: 1" = 20'

ROHDE, SOYKA & ANDREWS
Consulting Engineers PC
40 Garden Street Poughkeepsie, N.Y. 12601
(845) 452-7515
Fax: (845) 452-8535

117 NORTH HAMILTON
NORTH HAMILTON STREET
CITY OF POUGHKEEPSIE
DUTCHESS COUNTY, NEW YORK

SITE PLAN

PROJECT NUMBER: 21-786-01

DRAWING NUMBER: C101
2 OF 10

DEVELOPMENT

June 1, 2022

City of Poughkeepsie Planning Board
62 Civic Center Plaza
2nd Floor
Poughkeepsie, NY 12601

Re: 117 North Hamilton Street

To Whom it may concern,

We write to you regarding our upcoming project at 117 N Hamilton Street and in response to the questions and comments posed by the Planning Board.

Attached are the updated drawings to reflect our responses to the comments and questions from the planning board.

Thank you,

Eric Baxter
Vice President
Baxter Development Corp.



Plan View
Scale - 1" = 30ft

HOLOPHANE
LEADER IN LIGHTING SOLUTIONS

Catalog Number
Notes
Type

HLWPC2
Wallpack® Full Cutoff LED

Mechanical
- Heavy grade A360 cast aluminum (aluminum with < 1% copper)
- Exterior parts are protected by a zinc-infused Super Durable TGIC thermoset powder coat finish that provides superior resistance to corrosion and weathering
- Mounts to a standard junction box
- Swivel kit for pendant mount applications mounts to 4" square electrical box
- Wet location listed
- IP65 rated housing, down light only
- ¾" painted threaded entry(¾" - 14 NPT) on each side and on top, accepts ¾" and ½" condiut
- ¾" threaded plugs are painted on each side
- Vibe rating for surface mount: 3G
- Viberating for pendant mount: 3G at 1.5', excludes swivel kit
- Bird shroud for pendant mount

Electrical
- Certified by UL or CSA
- Rated for -40°C (-40°F) minimum ambient
- A programmable electronic driver with 0-10V control leads
- Available in: 120-277V 50/60 Hz and 347-480V 50/60 Hz,
- Standard LEDs shall have a minimum of 70 CRI available in 3000K, 4000K and 5000K CCT
- Optional LEDs shall have a minimum of 80 CRI available in 3000K, 4000K and 5000K CCT
- Amber LED option shall limited wavelength amber and no phosphor corrected amber (8 week lead-time)
- Internally mounted emergency battery backup for operation in an ambient temperature ranging from -20°C (-4°F) to 30°C (86°F), available with P10 thru P40 performance packages, non CEC compliant
- The electrical system for a single circuit shall be designed to meets ANSI/IEEE C62.41.2 and includes a 20kV/10kA (standard) with an optional 10kV/5kA surge protection

Optical
The light engine housing is IP66 rated. The acrylic optical system consist of the following I.E.S. distributions:
- Typ V: E (entry), M (medium), R (rectangle) & W (wide)
- Asymmetric

Controls
- Field adjustable output (AO)
- Button style photocontrol (PE)
- Motion sensor & ambient photocontrol combination for mounting low (8-15') (MASL) and high (15-30') (MASH) mounting heights

Certification and Standards
- Luminaire shall be UL or CSA listed per CSA luminaire standard CSA
- Suitable for operation in an ambient temperature up to 40°C/104°F per UL or CSA certification
- Design lights Consortium® (DLC) qualified product. Not all versions of this product may be DLC qualified. Please check the DLC Qualified Products List at www.designlights.org/QPL to confirm which versions are qualified.
- LM-79 compliant
- The projected LED Lumen Maintenance shall be based only on IES LM-80-08 and TM-21

Warranty
5-year limited warranty. Complete warranty terms located at: www.acuitybrands.com/CustomerResources/Terms_and_Conditions.aspx.

Note: Actual performance may differ as a result of end-user environment and application.
All values are design or typical values, measured under laboratory conditions at 25°C.
Specifications subject to change without notice.

15.54
2 LEM CONFIGURATION
3/4" THREADED PAINTED PLUG (3/4"-14 NPT)
11.53
.77
2.38
4.76
BACK BOX
1 LEM CONFIGURATION

Note: Maximum weight 22 lbs.

AcuityBrands. | Holophane | 3825 Columbus Rd., Granville, OH 43023 | Phone: 866-HOLOPHANE | www.holophane.com
© 2014-2018 Acuity Brands Lighting, Inc. All rights reserved. Rev. 05/01/19 Specifications are subject to change without notice.
HLWPC2
Page 1 of 8

Note

Please note this analysis does not comply with IESNA RP-8-18 levels for parking and pedestrian safety. Acuity Brands Lighting will not be liable for any issues that may arise from the installation of this design. An alternative design can be provided if requested through your acuity Agent.

Note

Background Image Disclaimer
Please note this design utilizes an image format or converted image such as a PDF or JPEG formats for the background shown. These types of formats can vary in accuracy and possibly resulting in deficiencies of actual readings in the field. Acuity Brands strongly suggest the use of Auto Cad formats for all design request.

Note

1. Readings shown are based on a total LLF of as shown at grade. Data references
the extrapolated performance projections in a 25c ambient based on 10,000 hrs of
LED testing (per IESNA LM-80-08 and projected per IESNA TM-21-11).
2. Please refer to the "luminaire locations" table for mounting heights.
3. Product information can be obtained at www.Acuity Brands.com

Luminaire Locations

		Location					
No.	Label	X	Y	Z	MH	Orientation	Tilt
1	A	89.00	-13.00	20.00	20.00	186.34	0.00
2	A	110.00	121.00	8.00	8.00	9.46	0.00
3	A	59.00	130.00	8.00	8.00	5.19	0.00
1	B	194.00	-52.00	20.00	20.00	282.26	0.00
2	B	93.00	-6.00	20.00	20.00	101.31	0.00
3	B	109.00	89.00	20.00	20.00	101.31	0.00

Statistics

Description	Symbol	Avg	Max	Min	Max/Min	Avg/Min
PARKING LOT	⚹	0.4 fc	5.2 fc	0.0 fc	N/A	N/A
PROPERTY LINE	⚹	0.0 fc	0.0 fc	0.0 fc	N/A	N/A
SITE CALCULATIONS	+	0.4 fc	5.6 fc	0.0 fc	N/A	N/A

Schedule

Symbol	Label	QTY	Catalog Number	Description	Number Lamps	Lumens per Lamp	LLF	Wattage
	A	3	HLWPC2 P10 40K XX T2M	Wallpack Full Cutoff LED, LED Performance Package P10, 4000 series CCT, Voltage, Type II Medium	1	3110	0.9	28
	B	3	HLWPC2 P10 40K XX TFTM	Wallpack Full Cutoff LED, LED Performance Package P10, 4000 series CCT, Voltage, Forward Throw Medium	1	3209	0.9	28

Note

Acuity Brands Lighting Inc. This document contains confidential and proprietary information of Acuity Brands Lighting. This document may only be used by or for the benifit of Acuity Brands Lighting's representitives and Customers.
This application design is not a professional engineering drawing and the design, including reported data and calulated results, is provided for informational purposes only,without any warrenty as to accuracy, completeness, safety or otherwise. The design is the result of calculations made using Visual lighting application software, photometric/radiometric data measured in a labrarory, and certian computational and modeling assumptions.
Far-field photometric/radiometric data may have been used to perform one or more calculations. Photometric/radiometric data is typically collected under far-field measurement conditions;far-field data is generally not representitive of near-field geometric conditions. When using the far-field photometric/rodiometric data, the Visual software applies certian generallizing assuptions to approximate near-field performance.. These assumptions may result in significant inaccuracies in individual calculated luminous and/or radiant power quantities in areas where a source is in close proximity to a particular surface or pont.
The modeling of radiant flux exchange used in the Visual software requires a uniform exitance accross each reflecting surface. The Visual software approximates the uniform surface exitance condition by adaptively subdividing surfaces with non-uniform exitance into subsurfaces with sufficently uniform exitance gradiant. Practical restrictions, due to computer hardware limitations, may prevent the subdivision procedure from subdividing surfaces with high exitance gradients into subsurfaces with sufficiently uniform exitance gradients, introducing potential discretization error into the calculated values.
Calulations performed by Visual softwarw assume that all reflected flux is reflected in a perfectly diffuse(Lambertian) and spectrally uniform manner accross the spectral range being analyzed. If actual reflectance characteristics differ from these assumptions, observed luminous and/or radiant power quantities may differ from the predicted quantities.
As a result of the computional limitations and simplifying modeling assumptions described above,and/or variations in actual product performance from tested product samples, the accuracy of calculated outut values identifying expected radiometric quantities and any resulting derived radiation dose calculation may be adversely affected.
In addition, the accuracy of the application design may be adversely affected if information about the physical space provided to Acuity Brands Lighting is incomplete, inaccurate, outdated or not in the required format (includiing but not limited to floor plans, space layout, reflected ceiling plans, physical structures, electrical design or specifications) if incorrect assumptions are made because of because such are not appropriate for the space. Furthermore, actual actual field performance may differ from performance calculated using laboratory measurement as a result of miscalculations related to defiiciencies in the information provided about the physical space, degregation factors in the end-user enviroment(including, but not limited to, voltage variation and dirt accumulation), or other possible variations in field conditions. Finially, lamp lumen depriciation and/or depriciation in lamp radiant intensity may result in performance over time that differs performance calculated using a new lamp. Light loss factors may have been used in the application design to estimate such depreciation, but flaws in these estimates may also result in performance over time that differ from the calculated performance.
It is the obligation of the end-user to consult with appropriately qualified Proffesional Engineer (s) to determine whether this application design meets the applicable requirements for performance,code compliance, safety,suitabilty and effectiveness for use in a particular application. In no event will Acuity Brands Lighting be responsible for any loss resulting from any use of this design.

ACUITY DESIGN SERVICES
LIGHTINGDESIGN@ACUITYBRANDS.COM

117 NORTH HAMILTON STREET
POUGHKEEPSIE, NY 12601

Designer
R.A. MCILRATH
Date
6/1/2022
Scale
As Shown
Drawing No.
206527-1 A1
Summary

1 of 1



1 BUILDING 1 FLOOR PLAN
1/8" = 1'-0"

CONSTRUCTION NOTES

NOTE: NOT ALL NOTES MAY BE USED ON THIS DRAWING.

WINDOW / DOOR NOTES:

1. ALL WINDOWS ARE BASED UPON USING ANDERSEN 200 SERIES W/ DUAL PANE HIGH PERFORMANCE LOW E, GLAZING WINDOWS AND DOOR ASSEMBLIES SHALL BE LABELLED AND CERTIFIED BY THE MANUFACTURER NOT TO EXCEED 0.3 CFM/SF AND SWINGING DOORS SHALL HAVE NO MORE THAN 0.5 CFM PER SQUARE FOOT OF LEAKAGE.
2. G.C. TO CONFIRM ALL DOOR AND WINDOW ROUGH OPENING SIZES PRIOR TO ORDERING.
3. CONFIRM HEAD HEIGHT AND SILL HEIGHT W/ OWNER IN FIELD TO DETERMINE SPECIAL CONDITIONS IN KITCHEN AND ON 2ND FLOOR.
4. GLAZING W/ IN 18" W/ FLOOR REQUIRED TO BE TEMPERED.

NOTES:

ALL BATHROOMS # LAVS. NOT HAVING OPERABLE WINDOWS OR HAVING LESS THAN 1.5 S.F. OF WINDOW VENT SPACE SHALL BE MECHANICAL VENTED TO THE EXTERIOR AND TERMINATE USING A WEATHERPROOF BAFFLE DEVICE. (SEE FOLLOWING CFM REQUIREMENTS) INTERMITTENT VENTILATION REQUIRES A MIN. OF 50 CFM (23.6 LIS) WHILE CONTINUOUS VENTILATION REQUIRES 20 CFM (9.4 LIS).

WALL NOTES:

1. ALL MTL. STUD WALLS, PROVIDE COLD ROLLED CHANNEL @ EV. 4'-0" VERT.
2. ALL MTL STUD WALLS OVER 12'-0" # ALL BEARING WALLS, INSTALL DIAGONAL X-BEARING AT 45° ANGLE @ CORNER # ENDS. USE 2". 16 G.A. GALVANIZED STRAPS W/ (4) #10 TEK SCREWS @ ENDS # ONE @ EACH STUD INSTALL COLD ROLLED CHANNEL @ 4' AND 8'.
3. ALL DIMENSIONS ARE TO ROUGH FRAMING.
4. CLOSED CELL SPRAY FOAM INSUL. MAY BE SUBSTITUTED FOR BATT INSULATION GIVEN THAT AN IGNITION BARRIER IS PROVIDED.
5. STRUCTURAL SPECIFICATION OF METAL FRAMING MEMBERS/GAUGES AND ANY BRACING SUPERSEDE THE ARCHITECTURAL DRAWINGS.

PROJECT

PROJECT

N O R T H

KEY PLAN

AREA OF CONSTRUCTION

CONSTRUCTION DOCUMENT

REVISIONS:

NUM.	DATE	DESCRIPTION

ANDERSON DESIGN GROUP

ARCHITECTURE
PLANNING
INTERIORS

25 WALLKILL AVE ● MONTGOMERY ● NY 12549
O. 845. 294.2724 | F.888.305.6442

WWW.ADGARCHITECT.COM
CONTACT@ADGARCHITECT.COM

Project: BAXTER 117 N HAMILTON
117 NORTH HAMILTON ST., CITY OF POUGHKEEPSIE
COUNTRY OF DUTCHESS, NEWYORK

Drawing Name: BUILDING 1 FLOOR PLAN

Drawn: IDEA | Scale: AS NOTED | Project: 22102 | Date: 03/02/22

DRAFT - NOT FOR CONSTRUCTION

Drawing Number: A-201

Copyright © all rights reserved - Jason T. Anderson Architect, P.C. / DBA / Anderson Design Group - Architecture - Planning - Interiors / Unauthorized addition or alteration of this document is a violation of the State Education Law.



1 BUILDING 2 FLOOR PLAN
1/8" = 1'-0"

CONSTRUCTION NOTES

NOTE: NOT ALL NOTES MAY BE USED ON THIS DRAWING

WINDOW / DOOR NOTES:

1. ALL WINDOWS ARE BASED UPON USING ANDERSEN 200 SERIES W/ DUAL PANE HIGH PERFORMANCE LOW E, GLAZING WINDOWS AND DOOR ASSEMBLIES SHALL BE LABELLED AND CERTIFIED BY THE MANUFACTURER NOT TO EXCEED 0.3 CFM/SF AND SWINGING DOORS SHALL HAVE NO MORE THAN 0.5 CFM PER SQUARE FOOT OF LEAKAGE.
2. G.C. TO CONFIRM ALL DOOR AND WINDOW ROUGH OPENING SIZES PRIOR TO ORDERING.
3. CONFIRM HEAD HEIGHT AND SILL HEIGHT W/ OWNER IN FIELD TO DETERMINE SPECIAL CONDITIONS IN KITCHEN AND ON 2ND FLOOR.
4. GLAZING W/ IN 18" W/ FLOOR REQUIRED TO BE TEMPERED.

NOTES:

ALL BATHROOMS 4 LAVS. NOT HAVING OPERABLE WINDOWS OR HAVING LESS THAN 1.5 S.F. OF WINDOW VENT SPACE SHALL BE MECHANICAL VENTED TO THE EXTERIOR AND TERMINATE USING A WEATHERPROOF BAFFLE DEVICE. (SEE FOLLOWING CFM REQUIREMENTS) INTERMITTENT VENTILATION REQUIRES A MIN. OF 50 CFM (23.6 L/S) WHILE CONTINUOUS VENTILATION REQUIRES 20 CFM (9.4 L/S).

WALL NOTES:

1. ALL MTL. STUD WALLS, PROVIDE COLD ROLLED CHANNEL @ EV. 4'-0" VERT.
2. ALL MTL STUD WALLS OVER 12'-0" ¢ ALL BEARING WALLS, INSTALL DIAGONAL K-BEARING AT 45° ANGLE @ CORNER ¢ ENDS. USE 2", 16 G.A. GALVANIZED STRAPS W/ (4) #10 TEK SCREWS @ ENDS ¢ ONE @ EACH STUD INSTALL COLD ROLLED CHANNEL @ 4' AND 8'.
3. ALL DIMENSIONS ARE TO ROUGH FRAMING.
4. CLOSED CELL SPRAY FOAM INSUL. MAY BE SUBSTITUTED FOR BATT INSULATION GIVEN THAT AN IGNITION BARRIER IS PROVIDED.
5. STRUCTURAL SPECIFICATION OF METAL FRAMING MEMBERS/GAUGES AND ANY BRACING SUPERSEDE THE ARCHITECTURAL DRAWINGS.

PROJECT

NORTH

KEY PLAN

AREA OF CONSTRUCTION

CONSTRUCTION DOCUMENT

REVISIONS:

NUM.	DATE	DESCRIPTION

ANDERSON DESIGN GROUP

ARCHITECTURE
PLANNING
INTERIORS

25 WALKILL AVE ● MONTGOMERY ● NY 12549
O. 845. 294.2724 | F.888.305.6442

WWW.ADGARCHITECT.COM
CONTACT@ADGARCHITECT.COM

Project: BAXTER 117 N HAMILTON
117 NORTH HAMILTON ST., CITY OF POUGHKEEPSIE
COUNTRY OF DUTCHESS, NEWYORK

Drawing Name: BUILDING 2 FLOOR PLAN

Drawn: IDEA | Scale: AS NOTED | Project: 22102 | Date: 03/02/22

DRAFT - NOT FOR CONSTRUCTION

Drawing Number: A-202

Copyright © all rights reserved - Jason T. Anderson Architect, P.C. / DBA / Anderson Design Group - Architecture - Planning - Interiors / Unauthorized addition or alteration of this document is a violation of the State Education Law.





1 SOUTH ELEVATION
1/8" = 1'-0"





2 NORTH ELEVATION
1/8" = 1'-0"

Copyright © all rights reserved - Jason T. Anderson Architect, P.C. / DBA / Anderson Design Group - Architecture - Planning - Interiors / Unauthorized addition or alteration of this document is a violation of the State Education Law.

CONSTRUCTION NOTES

NOTE: NOT ALL NOTES MAY BE USED ON THIS DRAWING

PROJECT

NORTH



100% **SCHEMATIC DESIGN**

REVISIONS:

NUM.	DATE	DESCRIPTION

ANDERSON DESIGN GROUP
ARCHITECTURE
PLANNING
INTERIORS
25 WALLKILL AVE ● MONTGOMERY ● NY 12549
O. 845. 294-2724 | F. 888.305.6442
WWW.ADGARCHITECT.COM
CONTACT@ADGARCHITECT.COM

Project: 117 NORTH HAMILTON
117 NORTH HAMILTON ST., POUGHKEEPSIE, NY 12601

Drawing Name: BUILDING 1 EXTERIOR ELEVATIONS

Drawn: IDEA | Scale: AS NOTED | Project: 22102 | Date: 05/31/22

REGISTERED ARCHITECT JASON T. ANDERSON 05-31-2022 033127 STATE OF NEW YORK

Drawing Number: A-300-PB





1 EAST ELEVATION
1/8" = 1'-0"





2 WEST ELEVATION
1/8" = 1'-0"

CONSTRUCTION NOTES

NOTE: NOT ALL NOTES MAY BE USED ON THIS DRAWING

PROJECT

N O R T H



100% **SCHEMATIC DESIGN**

REVISIONS:

NUM.	DATE	DESCRIPTION

ANDERSON DESIGN GROUP

ARCHITECTURE
PLANNING
INTERIORS

25 WALLKILL AVE ● MONTGOMERY ● NY 12549
O. 845. 294.2724 | F.888.305.6442

WWW.ADGARCHITECT.COM
CONTACT@ADGARCHITECT.COM

Project: 117 NORTH HAMILTON
117 NORTH HAMILTON ST., POUGHKEEPSIE, NY 12601

Drawing Name: BUILDING 1 EXTERIOR ELEVATIONS

Drawn: IDEA | Scale: AS NOTED | Project: 22102 | Date: 05/31/22

JASON T. ANDERSON REGISTERED ARCHITECT 033127 STATE OF NEW YORK
05.31.2022

Drawing Number: A-301-PB

Copyright © all rights reserved - Jason T. Anderson Architect, P.C. / DBA / Anderson Design Group - Architecture - Planning - Interiors / Unauthorized addition or alteration of this document is a violation of the State Education Law.





1 SOUTH ELEVATION
1/8" = 1'-0"





2 NORTH ELEVATION
1/8" = 1'-0"

CONSTRUCTION NOTES

NOTE: NOT ALL NOTES MAY BE USED ON THIS DRAWING

PROJECT

N O R T H



KEY PLAN

AREA OF CONSTRUCTION

100% **SCHEMATIC DESIGN**

REVISIONS:

NUM.	DATE	DESCRIPTION

ANDERSON DESIGN GROUP

ARCHITECTURE
PLANNING
INTERIORS

25 WALLKILL AVE • MONTGOMERY • NY 12549
O. 845. 294.2724 | F. 888.305.6442

WWW.ADGARCHITECT.COM
CONTACT@ADGARCHITECT.COM

Project: 117 NORTH HAMILTON
117 NORTH HAMILTON ST., POUGHKEEPSIE, NY 12601

Drawing Name: BUILDING 2 EXTERIOR ELEVATIONS

Drawn: IDEA | Scale: AS NOTED | Project: 22102 | Date: 05/31/22

REGISTERED ARCHITECT
JASON T. ANDERSON
033127
STATE OF NEW YORK
05.31.2022

Drawing Number: A-302-PB

Copyright © all rights reserved - Jason T. Anderson Architect, P.C. / DBA / Anderson Design Group - Architecture - Planning - Interiors / Unauthorized addition or alteration of this document is a violation of the State Education Law.





1 EAST EELEVATION
1/8" = 1'-0"





2 WEST ELAVATION
1/8" = 1'-0"

Copyright © all rights reserved - Jason T. Anderson Architect, P.C. / DBA / Anderson Design Group - Architecture - Planning - Interiors / Unauthorized addition or alteration of this document is a violation of the State Education Law.

CONSTRUCTION NOTES

NOTE: NOT ALL NOTES MAY BE USED ON THIS DRAWING

PROJECT

PROJECT

N O R T H



KEY PLAN

AREA OF CONSTRUCTION

100% **SCHEMATIC DESIGN**

REVISIONS:

NUM.	DATE	DESCRIPTION

ANDERSON DESIGN GROUP

ARCHITECTURE
PLANNING
INTERIORS

25 WALLKILL AVE • MONTGOMERY • NY 12549
O. 845. 294.2724 | F. 888.305.6442

WWW.ADGARCHITECT.COM
CONTACT@ADGARCHITECT.COM

Project: 117 NORTH HAMILTON
117 NORTH HAMILTON ST., POUGHKEEPSIE, NY 12601

Drawing Name: BUILDING 2 EXTERIOR ELEVATIONS

Drawn: IDEA | Scale: AS NOTED | Project: 22102 | Date: 05/31/22

REGISTERED ARCHITECT
JASON T. ANDERSON
03912
STATE OF NEW YORK
05-31-2022

Drawing Number: A-303-PB

1 EXTERIOR RENDERING

2 EXTERIOR RENDERING

Copyright © all rights reserved - Jason T. Anderson Architect, P.C. / DBA / Anderson Design Group - Architecture - Planning - Interiors / Unauthorized addition or alteration of this document is a violation of the State Education Law.

CONSTRUCTION NOTES

NOTE: NOT ALL NOTES MAY BE USED ON THIS DRAWING



PROJECT NORTH



100% **SCHEMATIC DESIGN**

REVISIONS:

NUM.	DATE	DESCRIPTION

ANDERSON DESIGN GROUP
ARCHITECTURE
PLANNING
INTERIORS
25 WALKILL AVE ● MONTGOMERY ● NY 12549
O. 845. 294.2724 | F.888.305.6442
WWW.ADGARCHITECT.COM
CONTACT@ADGARCHITECT.COM

Project: 117 NORTH HAMILTON
117 NORTH HAMILTON ST., POUGHKEEPSIE, NY 12601

Drawing Name: EXTERIOR RENDERING

Drawn: IDEA | Scale: AS NOTED | Project: 22102 | Date: 05/31/22

Drawing Number: A-902-PB





1 EAST ELEVATION
1/8" = 1'-0"



2 WEST ELEVATION
1/8" = 1'-0"

CONSTRUCTION NOTES

NOTE: NOT ALL NOTES MAY BE USED ON THIS DRAWING

PROJECT

NORTH



100% **SCHEMATIC DESIGN**

REVISIONS:

NUM.	DATE	DESCRIPTION

ANDERSON DESIGN GROUP

ARCHITECTURE
PLANNING
INTERIORS

25 WALLKILL AVE • MONTGOMERY • NY 12549
O. 845. 294.2724 | F.888.305.6442

WWW.ADGARCHITECT.COM
CONTACT@ADGARCHITECT.COM

Project: 117 NORTH HAMILTON
117 NORTH HAMILTON ST., POUGHKEEPSIE, NY 12601

Drawing Name: BUILDING 1 EXTERIOR ELEVATIONS

Drawn:	Scale:	Project:	Date:
IDEA	AS NOTED	22102	05/31/22

Drawing Number: A-301-PB

Copyright © all rights reserved - Jason T. Anderson Architect, P.C. / DBA / Anderson Design Group - Architecture - Planning - Interiors / Unauthorized addition or alteration of this document is a violation of the State Education Law.





1 SOUTH ELEVATION
1/8" = 1'-0"





2 NORTH ELEVATION
1/8" = 1'-0"

Copyright © all rights reserved - Jason T. Anderson Architect, P.C. / DBA / Anderson Design Group - Architecture - Planning - Interiors / Unauthorized addition or alteration of this document is a violation of the State Education Law.

CONSTRUCTION NOTES

NOTE: NOT ALL NOTES MAY BE USED ON THIS DRAWING

PROJECT

PROJECT NORTH

N O R T H



100% **SCHEMATIC DESIGN**

REVISIONS:

NUM.	DATE	DESCRIPTION

ANDERSON DESIGN GROUP
ARCHITECTURE
PLANNING
INTERIORS
25 WALLKILL AVE ● MONTGOMERY ● NY 12549
O. 845. 294-2724 | F.888.305.6442
WWW.ADGARCHITECT.COM
CONTACT@ADGARCHITECT.COM

Project: 117 NORTH HAMILTON
117 NORTH HAMILTON ST., POUGHKEEPSIE, NY 12601

Drawing Name: BUILDING 1 EXTERIOR ELEVATIONS

Drawn:	Scale:	Project:	Date:
IDEA	AS NOTED	22102	05/31/22

Drawing Number: A-300-PB





1 SOUTH ELEVATION
1/8" = 1'-0"





2 NORTH ELEVATION
1/8" = 1'-0"

Copyright © all rights reserved - Jason T. Anderson Architect, P.C. / DBA / Anderson Design Group - Architecture - Planning - Interiors / Unauthorized addition or alteration of this document is a violation of the State Education Law.

CONSTRUCTION NOTES

NOTE: NOT ALL NOTES MAY BE USED ON THIS DRAWING

PROJECT

N O R T H



100% **SCHEMATIC DESIGN**

REVISIONS:

NUM.	DATE	DESCRIPTION

ANDERSON DESIGN GROUP
ARCHITECTURE
PLANNING
INTERIORS
25 WALLKILL AVE • MONTGOMERY • NY 12549
O. 845. 294.2724 | F. 888.305.6442
WWW.ADGARCHITECT.COM
CONTACT@ADGARCHITECT.COM

Project: 117 NORTH HAMILTON
117 NORTH HAMILTON ST., POUGHKEEPSIE, NY 12601

Drawing Name: BUILDING 2 EXTERIOR ELEVATIONS

Drawn:	Scale:	Project:	Date:
IDEA	AS NOTED	22102	05/31/22

Drawing Number: A-302-PB





1 EAST EELEVATION
1/8" = 1'-0"





2 WEST ELAVATION
1/8" = 1'-0"

Copyright © all rights reserved - Jason T. Anderson Architect, P.C. / DBA / Anderson Design Group - Architecture - Planning - Interiors / Unauthorized addition or alteration of this document is a violation of the State Education Law.

CONSTRUCTION NOTES

NOTE: NOT ALL NOTES MAY BE USED ON THIS DRAWING

PROJECT

PROJECT

N O R T H



KEY PLAN

100% **SCHEMATIC DESIGN**

REVISIONS:

NUM.	DATE	DESCRIPTION

ANDERSON DESIGN GROUP

ARCHITECTURE
PLANNING
INTERIORS

25 WALLKILL AVE • MONTGOMERY • NY 12549
O. 845. 294.2724 | F. 888.305.6442

WWW.ADGARCHITECT.COM
CONTACT@ADGARCHITECT.COM

Project: 117 NORTH HAMILTON
117 NORTH HAMILTON ST., POUGHKEEPSIE, NY 12601

Drawing Name: BUILDING 2 EXTERIOR ELEVATIONS

Drawn:	Scale:	Project:	Date:
IDEA	AS NOTED	22102	05/31/22

Drawing Number: A-303-PB

DocuSign Envelope ID: E8F79ECF-3084-4722-BDBB-3AD22CB97E25

Instructions for Completing Part 1

Part 1 is to be completed by the applicant or project sponsor. Responses become part of the application for approval or funding, are subject to public review, and may be subject to further verification.

Complete Part 1 based on information currently available. If additional research or investigation would be needed to fully respond to any item, please answer as thoroughly as possible based on current information; indicate whether missing information does not exist, or is not reasonably available to the sponsor; and, when possible, generally describe work or studies which would be necessary to update or fully develop that information.

Applicants/sponsors must complete all items in Sections A & B. In Sections C, D & E, most items contain an initial question that must be answered either "Yes" or "No". If the answer to the initial question is "Yes", complete the sub-questions that follow. If the answer to the initial question is "No", proceed to the next question. Section F allows the project sponsor to identify and attach any additional information. Section G requires the name and signature of the applicant or project sponsor to verify that the information contained in Part 1is accurate and complete.

A. Project and Applicant/Sponsor Information.

Name of Action or Project: 117 N Hamilton		
Project Location (describe, and attach a general location map): 117 N Hamilton Street, City of Poughkeepsie, Dutchess County, - easterly side of N Hamilton St., approx. 250' north of its intersection with High St.		
Brief Description of Proposed Action (include purpose or need): The action involves Site Plan approval for the redevelopment of vacant land with construction of two (2), one tall story, multi-tenant warehouse facilities, 15,712 and 7710 square feet, to be connected to existing City water and sewer facilities, including outdoor access-controlled storage areas with landscaping, paved parking and maneuvering areas involving two (2) existing lots of record which are to be combined into one lot totaling 1.63 acres . Portions of the site are in an area of special flood hazard with no identified base flood elevation which requires a flood plain development permit and for which structures are required to be elevated 3'0" above the highest adjacent grade.		
Name of Applicant/Sponsor: Baxter Development Corp., Attn: Eric Baxter	Telephone: 845-471-1047 E-Mail: eric@baxterbuilt.com	
Address: 278 Mill Street, Suite 100		
City/PO: Poughkeepsie	State: NY	Zip Code: 12601
Project Contact (if not same as sponsor; give name and title/role):	Telephone: E-Mail:	
Address:		
City/PO:	State:	Zip Code:
Property Owner (if not same as sponsor): SEE ATTACHED ADDITIONAL INFORMATION	Telephone: E-Mail:	
Address:		
City/PO:	State:	Zip Code:

B. Government Approvals

B. Government Approvals, Funding, or Sponsorship. ("Funding" includes grants, loans, tax relief, and any other forms of financial assistance.)

Government Entity	If Yes: Identify Agency and Approval(s) Required	Application Date (Actual or projected)
a. City Counsel, Town Board, or Village Board of Trustees ☒Yes ☐No	City Counsel - Rezone Tax parcel 266293	12.20.2022 Approved
b. City, Town or Village Planning Board or Commission ☒Yes ☐No	City Planning Board- Site Plan	
c. City, Town or Village Zoning Board of Appeals ☒Yes ☐No	City Zoning Board - Variance	08.09.2022 Granted
d. Other local agencies ☒Yes ☐No	Building Inspector - Flood Plain Development Permit	
e. County agencies ☐Yes ☐No		
f. Regional agencies ☐Yes ☐No		
g. State agencies ☐Yes ☐No		
h. Federal agencies ☐Yes ☐No		

i. Coastal Resources.

i. Is the project site within a Coastal Area, or the waterfront area of a Designated Inland Waterway? ☐Yes ☒No

ii. Is the project site located in a community with an approved Local Waterfront Revitalization Program? ☐Yes ☒No

iii. Is the project site within a Coastal Erosion Hazard Area? ☐Yes ☒No

C. Planning and Zoning

C.1. Planning and zoning actions.

Will administrative or legislative adoption, or amendment of a plan, local law, ordinance, rule or regulation be the only approval(s) which must be granted to enable the proposed action to proceed? ☐Yes ☒No

- **If Yes,** complete sections C, F and G.
- **If No,** proceed to question C.2 and complete all remaining sections and questions in Part 1

C.2. Adopted land use plans.

a. Do any municipally- adopted (city, town, village or county) comprehensive land use plan(s) include the site where the proposed action would be located? ☒Yes ☐No

If Yes, does the comprehensive plan include specific recommendations for the site where the proposed action would be located? ☐Yes ☒No

b. Is the site of the proposed action within any local or regional special planning district (for example: Greenway; Brownfield Opportunity Area (BOA); designated State or Federal heritage area; watershed management plan; or other?) ☐Yes ☒No

If Yes, identify the plan(s):

_____

_____

_____

c. Is the proposed action located wholly or partially within an area listed in an adopted municipal open space plan, or an adopted municipal farmland protection plan? ☐Yes ☒No

If Yes, identify the plan(s):

_____

_____

_____

C.3. Zoning

a. Is the site of the proposed action located in a municipality with an adopted zoning law or ordinance. ☒ Yes ☐ No
If Yes, what is the zoning classification(s) including any applicable overlay district?
Light Industrial - I-1

b. Is the use permitted or allowed by a special or conditional use permit? ☐ Yes ☒ No

c. Is a zoning change requested as part of the proposed action? ☒ Yes ☐ No
If Yes,
i. What is the proposed new zoning for the site? Previously approved I-1 for Tax Parcel 266293

C.4. Existing community services.

a. In what school district is the project site located? City of Poughkeepsie City School District

b. What police or other public protection forces serve the project site?
City of Poughkeepsie Police Depratment

c. Which fire protection and emergency medical services serve the project site?
City of Poughkeepsie Fire Department

d. What parks serve the project site?
All City of Poughkeepsie Park Facilities

D. Project Details

D.1. Proposed and Potential Development

a. What is the general nature of the proposed action (e.g., residential, industrial, commercial, recreational; if mixed, include all components)? commercial - warehousing, contractor storage

b. a. Total acreage of the site of the proposed action? 1.63 acres
b. Total acreage to be physically disturbed? 1.63 acres
c. Total acreage (project site and any contiguous properties) owned or controlled by the applicant or project sponsor? 1.63 acres

c. Is the proposed action an expansion of an existing project or use? ☐ Yes ☒ No
i. If Yes, what is the approximate percentage of the proposed expansion and identify the units (e.g., acres, miles, housing units, square feet)? % _____ Units: _____

d. Is the proposed action a subdivision, or does it include a subdivision? ☐ Yes ☒ No
If Yes,
i. Purpose or type of subdivision? (e.g., residential, industrial, commercial; if mixed, specify types)
ii. Is a cluster/conservation layout proposed? ☐ Yes ☐ No
iii. Number of lots proposed? _____
iv. Minimum and maximum proposed lot sizes? Minimum _____ Maximum _____

e. Will the proposed action be constructed in multiple phases? ☐ Yes ☒ No
i. If No, anticipated period of construction: 6 months
ii. If Yes:
- Total number of phases anticipated _____
- Anticipated commencement date of phase 1 (including demolition) _____ month _____ year
- Anticipated completion date of final phase _____ month _____year
- Generally describe connections or relationships among phases, including any contingencies where progress of one phase may determine timing or duration of future phases: _____

f. Does the project include new residential uses? ☐ Yes ☒ No

If Yes, show numbers of units proposed.

	One Family	Two Family	Three Family	Multiple Family (four or more)
Initial Phase				
At completion of all phases				

g. Does the proposed action include new non-residential construction (including expansions)? ☒ Yes ☐ No

If Yes,

i. Total number of structures 2

ii. Dimensions (in feet) of largest proposed structure: 32' height; 92.125' width; and 131.17' length

iii. Approximate extent of building space to be heated or cooled: 23,422 gross square feet

h. Does the proposed action include construction or other activities that will result in the impoundment of any liquids, such as creation of a water supply, reservoir, pond, lake, waste lagoon or other storage? ☐ Yes ☒ No

If Yes,

i. Purpose of the impoundment: _____

ii. If a water impoundment, the principal source of the water: ☐ Ground water ☐ Surface water streams ☐ Other specify:

_____

iii. If other than water, identify the type of impounded/contained liquids and their source.

_____

iv. Approximate size of the proposed impoundment. Volume: _____ million gallons; surface area: _____ acres

v. Dimensions of the proposed dam or impounding structure: _____ height; _____ length

vi. Construction method/materials for the proposed dam or impounding structure (e.g., earth fill, rock, wood, concrete):

_____

D.2. Project Operations

a. Does the proposed action include any excavation, mining, or dredging, during construction, operations, or both? ☐ Yes ☒ No
(Not including general site preparation, grading or installation of utilities or foundations where all excavated materials will remain onsite)

If Yes:

i .What is the purpose of the excavation or dredging? _____

ii. How much material (including rock, earth, sediments, etc.) is proposed to be removed from the site?

- Volume (specify tons or cubic yards): _____
- Over what duration of time? _____

iii. Describe nature and characteristics of materials to be excavated or dredged, and plans to use, manage or dispose of them.

_____

_____

i*v.* Will there be onsite dewatering or processing of excavated materials? ☐ Yes ☐ No
If yes, describe. _____

_____

v. What is the total area to be dredged or excavated? _____acres

vi. What is the maximum area to be worked at any one time? _____ acres

vii. What would be the maximum depth of excavation or dredging? _____ feet

viii. Will the excavation require blasting? ☐ Yes ☐ No

ix. Summarize site reclamation goals and plan: _____

_____

_____

b. Would the proposed action cause or result in alteration of, increase or decrease in size of, or encroachment into any existing wetland, waterbody, shoreline, beach or adjacent area? ☐ Yes ☒ No

If Yes:

i. Identify the wetland or waterbody which would be affected (by name, water index number, wetland map number or geographic description): _____

_____

DocuSign Envelope ID: E8F79ECF-3084-4722-BDBB-3AD22CB97E25

ii. Describe how the proposed action would affect that waterbody or wetland, e.g. excavation, fill, placement of structures, or alteration of channels, banks and shorelines. Indicate extent of activities, alterations and additions in square feet or acres: _____

iii. Will the proposed action cause or result in disturbance to bottom sediments? ☐ Yes ☐ No
If Yes, describe: _____

iv. Will the proposed action cause or result in the destruction or removal of aquatic vegetation? ☐ Yes ☐ No
If Yes:

- acres of aquatic vegetation proposed to be removed: _____
- expected acreage of aquatic vegetation remaining after project completion: _____
- purpose of proposed removal (e.g. beach clearing, invasive species control, boat access): _____
- proposed method of plant removal: _____
- if chemical/herbicide treatment will be used, specify product(s): _____

v. Describe any proposed reclamation/mitigation following disturbance: _____

c. Will the proposed action use, or create a new demand for water? ☒ Yes ☐ No
If Yes: 7 units at 4 employees per unit times 15 gpd per employee

i. Total anticipated water usage/demand per day: 420 gallons/day

ii. Will the proposed action obtain water from an existing public water supply? ☒ Yes ☐ No
If Yes:

- Name of district or service area: City of Poughkeepsie Water Service Area
- Does the existing public water supply have capacity to serve the proposal? ☒ Yes ☐ No
- Is the project site in the existing district? ☒ Yes ☐ No
- Is expansion of the district needed? ☐ Yes ☒ No
- Do existing lines serve the project site? ☒ Yes ☐ No

iii. Will line extension within an existing district be necessary to supply the project? ☐ Yes ☒ No
If Yes:

- Describe extensions or capacity expansions proposed to serve this project: _____
- Source(s) of supply for the district: _____

iv. Is a new water supply district or service area proposed to be formed to serve the project site? ☐ Yes ☐ No
If, Yes:

- Applicant/sponsor for new district: _____
- Date application submitted or anticipated: _____
- Proposed source(s) of supply for new district: _____

v. If a public water supply will not be used, describe plans to provide water supply for the project: _____

vi. If water supply will be from wells (public or private), what is the maximum pumping capacity: _____ gallons/minute.

d. Will the proposed action generate liquid wastes? ☒ Yes ☐ No
If Yes: 7 units at 4 employees per unit times 15 gpd per employee

i. Total anticipated liquid waste generation per day: 420 gallons/day

ii. Nature of liquid wastes to be generated (e.g., sanitary wastewater, industrial; if combination, describe all components and approximate volumes or proportions of each): Sanitary Wastewater

iii. Will the proposed action use any existing public wastewater treatment facilities? ☒ Yes ☐ No
If Yes:

- Name of wastewater treatment plant to be used: Joint City/Town wastewater treatment facility
- Name of district: City of Poughkeepsie
- Does the existing wastewater treatment plant have capacity to serve the project? ☒ Yes ☐ No
- Is the project site in the existing district? ☒ Yes ☐ No
- Is expansion of the district needed? ☐ Yes ☒ No

DocuSign Envelope ID: E8F79ECF-3084-4722-BDBB-3AD22CB97E25

- Do existing sewer lines serve the project site? ☒ Yes ☐ No
- Will a line extension within an existing district be necessary to serve the project? ☐ Yes ☒ No

If Yes:

- Describe extensions or capacity expansions proposed to serve this project: _____

iv. Will a new wastewater (sewage) treatment district be formed to serve the project site? ☐ Yes ☒ No

If Yes:

- Applicant/sponsor for new district: _____
- Date application submitted or anticipated: _____
- What is the receiving water for the wastewater discharge? _____

v. If public facilities will not be used, describe plans to provide wastewater treatment for the project, including specifying proposed receiving water (name and classification if surface discharge or describe subsurface disposal plans):

_____

vi. Describe any plans or designs to capture, recycle or reuse liquid waste: _____

e. Will the proposed action disturb more than one acre and create stormwater runoff, either from new point sources (i.e. ditches, pipes, swales, curbs, gutters or other concentrated flows of stormwater) or non-point source (i.e. sheet flow) during construction or post construction? ☒ Yes ☐ No

If Yes:

i. How much impervious surface will the project create in relation to total size of project parcel?

_____ Square feet or 1.25 acres (impervious surface) 0.60 IMPERVIOUS EXISTING TO BE REDEVELOPED

_____ Square feet or 1.63 acres (parcel size)

ii. Describe types of new point sources. _____

iii. Where will the stormwater runoff be directed (i.e. on-site stormwater management facility/structures, adjacent properties, groundwater, on-site surface water or off-site surface waters)?

ON-SITE STORMWATER MANGAMENT FACILITIES DISCHARGE TO GROUND WATER

- If to surface waters, identify receiving water bodies or wetlands: _____
- Will stormwater runoff flow to adjacent properties? ☐ Yes ☒ No

iv. Does the proposed plan minimize impervious surfaces, use pervious materials or collect and re-use stormwater? ☒ Yes ☐ No

f. Does the proposed action include, or will it use on-site, one or more sources of air emissions, including fuel combustion, waste incineration, or other processes or operations? ☐ Yes ☒ No

If Yes, identify:

i. Mobile sources during project operations (e.g., heavy equipment, fleet or delivery vehicles)

ii. Stationary sources during construction (e.g., power generation, structural heating, batch plant, crushers)

iii. Stationary sources during operations (e.g., process emissions, large boilers, electric generation)

g. Will any air emission sources named in D.2.f (above), require a NY State Air Registration, Air Facility Permit, or Federal Clean Air Act Title IV or Title V Permit? ☐ Yes ☒ No

If Yes:

i. Is the project site located in an Air quality non-attainment area? (Area routinely or periodically fails to meet ambient air quality standards for all or some parts of the year) ☐ Yes ☐ No

ii. In addition to emissions as calculated in the application, the project will generate:

- _____Tons/year (short tons) of Carbon Dioxide (CO_2)
- _____Tons/year (short tons) of Nitrous Oxide (N_2O)
- _____Tons/year (short tons) of Perfluorocarbons (PFCs)
- _____Tons/year (short tons) of Sulfur Hexafluoride (SF_6)
- _____Tons/year (short tons) of Carbon Dioxide equivalent of Hydroflourocarbons (HFCs)
- _____Tons/year (short tons) of Hazardous Air Pollutants (HAPs)

h. Will the proposed action generate or emit methane (including, but not limited to, sewage treatment plants, landfills, composting facilities)? ☐Yes ☒No

If Yes:

i. Estimate methane generation in tons/year (metric): _____

ii. Describe any methane capture, control or elimination measures included in project design (e.g., combustion to generate heat or electricity, flaring): _____

i. Will the proposed action result in the release of air pollutants from open-air operations or processes, such as quarry or landfill operations? ☐Yes ☒No

If Yes: Describe operations and nature of emissions (e.g., diesel exhaust, rock particulates/dust):

j. Will the proposed action result in a substantial increase in traffic above present levels or generate substantial new demand for transportation facilities or services? ☐Yes ☒No

If Yes:

i. When is the peak traffic expected (Check all that apply): ☐ Morning ☐ Evening ☐Weekend ☐ Randomly between hours of _____ to _____.

ii. For commercial activities only, projected number of truck trips/day and type (e.g., semi trailers and dump trucks): _____

iii. Parking spaces: Existing _____ Proposed _____ Net increase/decrease _____

iv. Does the proposed action include any shared use parking? ☐Yes ☐No

v. If the proposed action includes any modification of existing roads, creation of new roads or change in existing access, describe:

vi. Are public/private transportation service(s) or facilities available within ½ mile of the proposed site? ☒Yes ☐No

vii Will the proposed action include access to public transportation or accommodations for use of hybrid, electric or other alternative fueled vehicles? ☐Yes ☒No

viii. Will the proposed action include plans for pedestrian or bicycle accommodations for connections to existing pedestrian or bicycle routes? ☐Yes ☒No

k. Will the proposed action (for commercial or industrial projects only) generate new or additional demand for energy? ☒Yes ☐No

If Yes:

i. Estimate annual electricity demand during operation of the proposed action: _____

customary electric usage

ii. Anticipated sources/suppliers of electricity for the project (e.g., on-site combustion, on-site renewable, via grid/local utility, or other):

connection to existing CHGE grid

iii. Will the proposed action require a new, or an upgrade, to an existing substation? ☐Yes ☒No

l. Hours of operation. Answer all items which apply.

i. During Construction:

- Monday - Friday: 7 am - 4:30 pm
- Saturday: 7 am - 4:30 pm (possible)
- Sunday: _____
- Holidays: _____

ii. During Operations:

- Monday - Friday: 7 am - 5 pm
- Saturday: 7 am - 5 pm (possible)
- Sunday: _____
- Holidays: _____

m. Will the proposed action produce noise that will exceed existing ambient noise levels during construction, operation, or both? ☒ Yes ☐ No

If yes:

i. Provide details including sources, time of day and duration:

DURING CONSTRCUTION ONLY - DURING WORKING HOURS ONLY

ii. Will the proposed action remove existing natural barriers that could act as a noise barrier or screen? ☐ Yes ☒ No

Describe: _____

n. Will the proposed action have outdoor lighting? ☒ Yes ☐ No

If yes:

i. Describe source(s), location(s), height of fixture(s), direction/aim, and proximity to nearest occupied structures:

Building mounted LED lighting aimed downward - greater than 50' to nearest occupied structure

ii. Will proposed action remove existing natural barriers that could act as a light barrier or screen? ☐ Yes ☒ No

Describe: _____

o. Does the proposed action have the potential to produce odors for more than one hour per day? ☐ Yes ☒ No

If Yes, describe possible sources, potential frequency and duration of odor emissions, and proximity to nearest occupied structures: _____

p. Will the proposed action include any bulk storage of petroleum (combined capacity of over 1,100 gallons) or chemical products 185 gallons in above ground storage or any amount in underground storage? ☐ Yes ☒ No

If Yes:

i. Product(s) to be stored _____

ii. Volume(s) _____ per unit time _____ (e.g., month, year)

iii. Generally, describe the proposed storage facilities: _____

q. Will the proposed action (commercial, industrial and recreational projects only) use pesticides (i.e., herbicides, insecticides) during construction or operation? ☐ Yes ☒ No

If Yes:

i. Describe proposed treatment(s):

ii. Will the proposed action use Integrated Pest Management Practices? ☐ Yes ☐ No

r. Will the proposed action (commercial or industrial projects only) involve or require the management or disposal of solid waste (excluding hazardous materials)? ☒ Yes ☐ No

If Yes:

i. Describe any solid waste(s) to be generated during construction or operation of the facility:

- Construction: _____ tons per _____ (unit of time)
- Operation : _____ tons per _____ (unit of time)

ii. Describe any proposals for on-site minimization, recycling or reuse of materials to avoid disposal as solid waste:

- Construction: recycling existing concrete to be removed
- Operation: _____

iii. Proposed disposal methods/facilities for solid waste generated on-site:

- Construction: Royal Carting
- Operation: Royal Carting

s. Does the proposed action include construction or modification of a solid waste management facility? ☐ Yes ☒ No

If Yes:

i. Type of management or handling of waste proposed for the site (e.g., recycling or transfer station, composting, landfill, or other disposal activities): _____

ii. Anticipated rate of disposal/processing:

- _____ Tons/month, if transfer or other non-combustion/thermal treatment, or
- _____ Tons/hour, if combustion or thermal treatment

iii. If landfill, anticipated site life: _____ years

t. Will the proposed action at the site involve the commercial generation, treatment, storage, or disposal of hazardous waste? ☐ Yes ☒ No

If Yes:

i. Name(s) of all hazardous wastes or constituents to be generated, handled or managed at facility: _____

ii. Generally describe processes or activities involving hazardous wastes or constituents: _____

iii. Specify amount to be handled or generated _____ tons/month

iv. Describe any proposals for on-site minimization, recycling or reuse of hazardous constituents: _____

v. Will any hazardous wastes be disposed at an existing offsite hazardous waste facility? ☐ Yes ☐ No

If Yes: provide name and location of facility: _____

If No: describe proposed management of any hazardous wastes which will not be sent to a hazardous waste facility:

E. Site and Setting of Proposed Action

E.1. Land uses on and surrounding the project site

a. Existing land uses.

i. Check all uses that occur on, adjoining and near the project site.

☒ Urban ☐ Industrial ☒ Commercial ☐ Residential (suburban) ☐ Rural (non-farm)
☐ Forest ☐ Agriculture ☐ Aquatic ☒ Other (specify): Dutchess County Jail facility

ii. If mix of uses, generally describe:

some surrounding residential - mixed uses single and multifamily

b. Land uses and covertypes on the project site.

Land use or Covertype	Current Acreage	Acreage After Project Completion	Change (Acres +/-)
• Roads, buildings, and other paved or impervious surfaces	0.60	1.25	+0.65
• Forested	0.58	0.15	-0.43
• Meadows, grasslands or brushlands (non-agricultural, including abandoned agricultural)	0.21	0	-0.21
• Agricultural (includes active orchards, field, greenhouse etc.)			
• Surface water features (lakes, ponds, streams, rivers, etc.)			
• Wetlands (freshwater or tidal)			
• Non-vegetated (bare rock, earth or fill)	0.24	0	-0.24
• Other Describe: Lawn/Landscaping		0.28	+0.28

c. Is the project site presently used by members of the community for public recreation? ☐ Yes ☒ No

i. If Yes: explain: _____

d. Are there any facilities serving children, the elderly, people with disabilities (e.g., schools, hospitals, licensed day care centers, or group homes) within 1500 feet of the project site? ☒ Yes ☐ No

If Yes,

i. Identify Facilities:

Inner City Parcels - Several Poughkeepsie City Schools, numerous churches, and the Dutchess County Jail

e. Does the project site contain an existing dam? ☐ Yes ☒ No

If Yes:

i. Dimensions of the dam and impoundment:

- Dam height: _____ feet
- Dam length: _____ feet
- Surface area: _____ acres
- Volume impounded: _____ gallons OR acre-feet

ii. Dam's existing hazard classification: _____

iii. Provide date and summarize results of last inspection:

f. Has the project site ever been used as a municipal, commercial or industrial solid waste management facility, or does the project site adjoin property which is now, or was at one time, used as a solid waste management facility? ☐ Yes ☒ No

If Yes:

i. Has the facility been formally closed? ☐ Yes ☐ No

- If yes, cite sources/documentation: _____

ii. Describe the location of the project site relative to the boundaries of the solid waste management facility:

iii. Describe any development constraints due to the prior solid waste activities: _____

g. Have hazardous wastes been generated, treated and/or disposed of at the site, or does the project site adjoin property which is now or was at one time used to commercially treat, store and/or dispose of hazardous waste? ☐ Yes ☒ No

If Yes:

i. Describe waste(s) handled and waste management activities, including approximate time when activities occurred:

h. Potential contamination history. Has there been a reported spill at the proposed project site, or have any remedial actions been conducted at or adjacent to the proposed site? ☒ Yes ☐ No

If Yes:

i. Is any portion of the site listed on the NYSDEC Spills Incidents database or Environmental Site Remediation database? Check all that apply: ☐ Yes ☒ No

☐ Yes – Spills Incidents database Provide DEC ID number(s): _____

☐ Yes – Environmental Site Remediation database Provide DEC ID number(s): _____

☐ Neither database

ii. If site has been subject of RCRA corrective activities, describe control measures: _____

iii. Is the project within 2000 feet of any site in the NYSDEC Environmental Site Remediation database? ☒ Yes ☐ No

If yes, provide DEC ID number(s): B00036, C314130, C314131, C314134, B00020, 3141...

iv. If yes to (i), (ii) or (iii) above, describe current status of site(s):

See Attachments for current status of each involved site.

v. Is the project site subject to an institutional control limiting property uses? ☐ Yes ☒ No

- If yes, DEC site ID number: _____
- Describe the type of institutional control (e.g., deed restriction or easement): _____
- Describe any use limitations: _____
- Describe any engineering controls: _____
- Will the project affect the institutional or engineering controls in place? ☐ Yes ☐ No
- Explain: _____

E.2. Natural Resources On or Near Project Site

a. What is the average depth to bedrock on the project site? 5.0+/- feet

b. Are there bedrock outcroppings on the project site? ☐ Yes ☒ No
If Yes, what proportion of the site is comprised of bedrock outcroppings? _____%

c. Predominant soil type(s) present on project site:

DxB-Dutchess Cardigan Urban	81 %
BeC-Bernardston silt loam	18 %
Ur-Urban land	1 %

d. What is the average depth to the water table on the project site? Average: 5.0+/- feet

e. Drainage status of project site soils:
☒ Well Drained: 100 % of site
☐ Moderately Well Drained: _____% of site
☐ Poorly Drained _____% of site

f. Approximate proportion of proposed action site with slopes:
☒ 0-10%: _____% of site
☐ 10-15%: _____% of site
☐ 15% or greater: _____% of site

g. Are there any unique geologic features on the project site? ☐ Yes ☒ No
If Yes, describe: _____

h. Surface water features.

i. Does any portion of the project site contain wetlands or other waterbodies (including streams, rivers, ponds or lakes)? ☐ Yes ☒ No

ii. Do any wetlands or other waterbodies adjoin the project site? ☒ Yes ☐ No

If Yes to either *i* or *ii*, continue. If No, skip to E.2.i.

iii. Are any of the wetlands or waterbodies within or adjoining the project site regulated by any federal, state or local agency? ☒ Yes ☐ No

iv. For each identified regulated wetland and waterbody on the project site, provide the following information:

- Streams: Name _____ Classification _____
- Lakes or Ponds: Name _____ Classification _____
- Wetlands: Name Fall Kill Approximate Size _____
- Wetland No. (if regulated by DEC) _____

v. Are any of the above water bodies listed in the most recent compilation of NYS water quality-impaired waterbodies? ☐ Yes ☒ No

If yes, name of impaired water body/bodies and basis for listing as impaired: _____

i. Is the project site in a designated Floodway? ☐ Yes ☒ No

j. Is the project site in the 100-year Floodplain? ☒ Yes ☐ No

k. Is the project site in the 500-year Floodplain? ☐ Yes ☒ No

l. Is the project site located over, or immediately adjoining, a primary, principal or sole source aquifer? ☐ Yes ☒ No
If Yes:

i. Name of aquifer: _____

DocuSign Envelope ID: E8F79ECF-3084-4722-BDBB-3AD22CB97E25

m. Identify the predominant wildlife species that occupy or use the project site: _____

_____ _____ _____

_____ _____ _____

n. Does the project site contain a designated significant natural community? ☐ Yes ☒ No

If Yes:

i. Describe the habitat/community (composition, function, and basis for designation): _____

_____

ii. Source(s) of description or evaluation: _____

iii. Extent of community/habitat:

- Currently: _____ acres
- Following completion of project as proposed: _____ acres
- Gain or loss (indicate + or -): _____ acres

o. Does project site contain any species of plant or animal that is listed by the federal government or NYS as endangered or threatened, or does it contain any areas identified as habitat for an endangered or threatened species? ☐ Yes ☒ No

If Yes:

i. Species and listing (endangered or threatened): _____

_____

_____

p. Does the project site contain any species of plant or animal that is listed by NYS as rare, or as a species of special concern? ☐ Yes ☒ No

If Yes:

i. Species and listing: _____

_____

q. Is the project site or adjoining area currently used for hunting, trapping, fishing or shell fishing? ☐ Yes ☒ No

If yes, give a brief description of how the proposed action may affect that use: _____

_____

E.3. Designated Public Resources On or Near Project Site

a. Is the project site, or any portion of it, located in a designated agricultural district certified pursuant to Agriculture and Markets Law, Article 25-AA, Section 303 and 304? ☐ Yes ☒ No

If Yes, provide county plus district name/number: _____

b. Are agricultural lands consisting of highly productive soils present? ☐ Yes ☒ No

i. If Yes: acreage(s) on project site? _____

ii. Source(s) of soil rating(s): _____

c. Does the project site contain all or part of, or is it substantially contiguous to, a registered National Natural Landmark? ☐ Yes ☒ No

If Yes:

i. Nature of the natural landmark: ☐ Biological Community ☐ Geological Feature

ii. Provide brief description of landmark, including values behind designation and approximate size/extent: _____

_____

_____

d. Is the project site located in or does it adjoin a state listed Critical Environmental Area? ☐ Yes ☒ No

If Yes:

i. CEA name: _____

ii. Basis for designation: _____

iii. Designating agency and date: _____

e. Does the project site contain, or is it substantially contiguous to, a building, archaeological site, or district which is listed on the National or State Register of Historic Places, or that has been determined by the Commissioner of the NYS Office of Parks, Recreation and Historic Preservation to be eligible for listing on the State Register of Historic Places? ☐ Yes ☒ No

If Yes:

i. Nature of historic/archaeological resource: ☐ Archaeological Site ☐ Historic Building or District

ii. Name: _____

iii. Brief description of attributes on which listing is based:

_____

f. Is the project site, or any portion of it, located in or adjacent to an area designated as sensitive for archaeological sites on the NY State Historic Preservation Office (SHPO) archaeological site inventory? ☐ Yes ☒ No

g. Have additional archaeological or historic site(s) or resources been identified on the project site? ☐ Yes ☒ No

If Yes:

i. Describe possible resource(s): _____

ii. Basis for identification: _____

h. Is the project site within fives miles of any officially designated and publicly accessible federal, state, or local scenic or aesthetic resource? ☐ Yes ☒ No

If Yes:

i. Identify resource: _____

ii. Nature of, or basis for, designation (e.g., established highway overlook, state or local park, state historic trail or scenic byway, etc.): _____

iii. Distance between project and resource: _____ miles.

i. Is the project site located within a designated river corridor under the Wild, Scenic and Recreational Rivers Program 6 NYCRR 666? ☐ Yes ☒ No

If Yes:

i. Identify the name of the river and its designation: _____

ii. Is the activity consistent with development restrictions contained in 6NYCRR Part 666? ☐ Yes ☐ No

F. Additional Information

Attach any additional information which may be needed to clarify your project.

If you have identified any adverse impacts which could be associated with your proposal, please describe those impacts plus any measures which you propose to avoid or minimize them.

G. Verification

I certify that the information provided is true to the best of my knowledge.

Applicant/Sponsor Name Baxter Development Corp. Date 3.29.2022//Revised 3.03.23

Signature _____ Title _____

DocuSigned by:

349600D2A8354D6...

PRINT FORM

EAF Mapper Summary Report

Wednesday, February 16, 2022 9:22 AM



Disclaimer: The EAF Mapper is a screening tool intended to assist project sponsors and reviewing agencies in preparing an environmental assessment form (EAF). Not all questions asked in the EAF are answered by the EAF Mapper. Additional information on any EAF question can be obtained by consulting the EAF Workbooks. Although the EAF Mapper provides the most up-to-date digital data available to DEC, you may also need to contact local or other data sources in order to obtain data not provided by the Mapper. Digital data is not a substitute for agency determinations.

B.i.i [Coastal or Waterfront Area]	No
B.i.ii [Local Waterfront Revitalization Area]	No
C.2.b. [Special Planning District]	Digital mapping data are not available or are incomplete. Refer to EAF Workbook.
E.1.h [DEC Spills or Remediation Site - Potential Contamination History]	Digital mapping data are not available or are incomplete. Refer to EAF Workbook.
E.1.h.i [DEC Spills or Remediation Site - Listed]	Digital mapping data are not available or are incomplete. Refer to EAF Workbook.
E.1.h.i [DEC Spills or Remediation Site - Environmental Site Remediation Database]	Digital mapping data are not available or are incomplete. Refer to EAF Workbook.
E.1.h.iii [Within 2,000' of DEC Remediation Site]	Yes
E.1.h.iii [Within 2,000' of DEC Remediation Site - DEC ID]	B00036, C314130, C314131, C314134, B00020, 314122, 314074
E.2.g [Unique Geologic Features]	No
E.2.h.i [Surface Water Features]	No
E.2.h.ii [Surface Water Features]	Yes
E.2.h.iii [Surface Water Features]	Yes - Digital mapping information on local and federal wetlands and waterbodies is known to be incomplete. Refer to EAF Workbook.
E.2.h.v [Impaired Water Bodies]	No
E.2.i. [Floodway]	No
E.2.j. [100 Year Floodplain]	Yes
E.2.k. [500 Year Floodplain]	No
E.2.l. [Aquifers]	No
E.2.n. [Natural Communities]	No
E.2.o. [Endangered or Threatened Species]	No

DocuSign Envelope ID: E8F79ECF-3084-4722-BDBB-3AD22CB97E25

E.3.n. [Rare Plants or Animals]	No
E.3.a. [Agricultural District]	No
E.3.c. [National Natural Landmark]	No
E.3.d [Critical Environmental Area]	No
E.3.e. [National or State Register of Historic Places or State Eligible Sites]	Digital mapping data are not available or are incomplete. Refer to EAF Workbook.
E.3.f. [Archeological Sites]	No
E.3.i. [Designated River Corridor]	No

STORMWATER POLLUTION PREVENTION PLAN (SWPPP)

117 NORTH HAMILTON
NORTH HAMILTON STREET, City of Poughkeepsie

City of Poughkeepsie • Dutchess County • New York

Dated: February 2023

PREPARED BY:

ROHDE, SOYKA & ANDREWS
Consulting Engineers, P.C.
40 Garden Street
Poughkeepsie, NY 12601
(845) 452-7515 phone
(845) 452-8335 fax

John V. Andrews, Jr., P.E.
NYS License No. 065955
RSA Project No. 21-786-01

It is a violation of Article 145 Title VIII of the State Education Law to alter this report except by a Professional Engineer. If this report is to be altered, the altering Engineer shall affix hereon his/her seal and the notation "altered by" followed by his/her signature and the date of such alteration, and a specific description of the alteration.

TABLE OF CONTENTS

SWPPP Narrative	Pages 1-20
Appendices: Notice of Intent (NOI)	Appendix A (Not Included at this time)
MS4 Stormwater Pollution Prevention Plan Acceptance Form	Appendix B (Not Included at this time)
Site Data Vicinity Map Soils Information – Web Soil Survey	Appendix C
Documentation for No Impact to Historic & Cultural Resources	Appendix D
Water Quality Treatment Water Quality Volume (WQv) Porous Pavement Underground Infiltration Chambers	Appendix E
Soil Restoration Section 5.1.6 'Soil Restoration' from NYS Stormwater Management Design Manual, (NYS SMDM) January 2015	Appendix F (Not Included at this time)
Hydrocad Report	Appendix G
Soil Stabilization Temporary Seed Mix	Appendix H
NYSDEC Spill Reporting & Initial Notification Requirements	Appendix I (Not Included at this time)
Construction Site Log Book Table of Contents Contractor Certification Form Erosion & Sediment Control Weekly Inspection Report	Appendix J

11" X 17" Drawings Reduced Size Drawings – Not to Scale

SPDES General Permit for Stormwater Discharges from Construction Activity – (GP-0-20-001)	Not included at this time

1.0 PROJECT BACKGROUND

The project area, identified as 117 North Hamilton Street, is comprised of two lots; a northern 0.43 acre vacant residential parcel and a 1.20 vacant industrial parcel to the south. Total project area will be 1.63 acres.

The project involves the redevelopment of vacant land with construction of two (2), one tall story, multi-tenant warehouse facilities, 15,712 and 7710 square feet in size, to be connected to existing City water and sewer facilities, including outdoor access-controlled storage areas with landscaping, paved parking, and maneuvering areas. The project includes two (2) existing lots of record which are to be combined into one lot totaling 1.63 acres. The involved parcels were both previously developed. The existing structures have been demolished but elements of those structures remain in place including the concrete slab on grade, loading area and asphalt maneuvering areas for the prior structures. Portions of the site are in an area of special flood hazard with no identified base flood elevation which requires a flood plain development permit and for which structures are required to be elevated 3'0" above the highest adjacent grade.

The existing facilities are to be removed with the site to be filled to achieve the required 3'0" in elevation for the proposed new structures within the area of special flood hazard. Site access will match the existing grade at the road. Site grading will accommodate the elevation change required for the structures without impacting adjacent parcels. All proposed grades will match to existing grades along the property perimeter.

The area of disturbance is estimated to be **1.63 acres**. Because the area of disturbance will be greater than one acre, the project will require coverage under New York State Department of Environmental Conservation (NYSDEC) State Pollutant Discharge Elimination System (SPDES) General Permit for Stormwater Discharges from Construction Activity, Permit No. GP-0-20-001, effective date January 29, 2020, expiration date January 28, 2025.

This project requires erosion and sediment control measures, and water quality and water quantity control in accordance with NYSDEC SPDES General Permit for Stormwater Discharges from Construction Activity, Permit No GP-0-20-001, *New York Standards and Specifications for Erosion and Sediment Control*, November 2016 and *New York State Stormwater Management Design Manual*, January 2015 (SMDM).

Refer to the drawing set for existing and proposed conditions.

2.0 SOILS

The soils within the proposed area of disturbance are underlain by Graywacke, shale bedrock. The site's surficial geology is of glacial till soils, specifically DxB-Dutchess-Cardigan Dutchess-Cardigan-Urban land complex, undulating, rocky and BeC-Bernardston silt loam. The geology and surface soils are typical for the area and there are no unique geologic features on the site.

According to the USDA Web Soil Survey, the parcel has the following breakdown of soil units:

Map Unit Legend (North Hamilton Parcel)

Map Unit Symbol	Map Unit Name	Acres in AOI	Percent of AOI
BeC	Bernardston silt loam, 8 to 15 percent slopes	0.3	18.4%
DxB	Dutchess-Cardigan-Urban land complex, undulating, rocky	1.3	81.6%
Totals for Area of Interest		1.6	100.0%

As seen in the table above, the majority of the disturbance is within the DxB soil unit. According to the Soil Survey of Dutchess County, "Typically, the urban land consists of areas covered by buildings, streets, parking lots, and other impervious surfaces which obscure soil identification. The natural soil layers have been altered or mixed with non-soil material such as bricks, broken concrete, or cinders." This description is consistent with the project's location in an industrial/urban area.

According to the USDA Web Soil Survey, the soil unit has the following Hydrologic Soil Group (HSG) classification.

Report—Hydrologic Soil Group and Surface Runoff (North Hamilton Parcel)

Absence of an entry indicates that the data were not estimated. The dash indicates no documented presence.

Hydrologic Soil Group and Surface Runoff–Dutchess County, New York			
Map symbol and soil name	**Pct. of map unit**	**Surface Runoff**	**Hydrologic Soil Group**
BeC—Bernardston silt loam, 8 to 15 percent slopes			
Bernardston	80	—	C/D
DxB—Dutchess-Cardigan-Urban land complex, undulating, rocky			
Dutchess	30	—	B
Cardigan	25	—	C
Urban land	20	—	—

For the purposes of hydrologic design, a HSG classification of C is used for pre and post development conditions.

Refer to Appendix C for Soils Map.

3.0 HISTORIC ASSESSMENT

In accordance with SPDES General Permit for Stormwater Discharges from Construction Activity, GP-0-20-001, documentation regarding possible impacts to historic or cultural resources by the construction activities must be provided.

According to the Natural Resources Inventory Historic Resources Map, the nearest historic sites are the Guilford Dudley Memorial at College Hill Park and St. Paul's Episcopal Church on Mansion Street. Both lie roughly 0.15 miles distant. The site is not located within or immediately adjacent to any historic districts, buildings or archeological sites.

Refer to Appendix D for documentation.

4.0 CONSTRUCTION PHASING AND SEQUENCE OF OPERATIONS

Construction is proposed to occur in one phase. It is proposed to prep the site, install the utilities and then begin building construction. There is some basic demolition and removal work involving the existing concrete slabs that will be undertaken.

The total estimated area of disturbance for all phases is **1.63 acres**. This is less than the 5.0 acre maximum threshold for area of disturbance. Therefore, construction phasing is not required for stormwater purposes.

The site contains a substantial concrete slab area, asphalt area and compacted gravel. These existing impervious surfaces will need to be removed to raise the site to meet special flood hazard area requirements.

Areas not scheduled for immediate construction are to be left undisturbed for as long as possible. Areas disturbed outside the main construction area will be temporarily stabilized with seed and mulch or other stabilization measure as appropriate.

The Construction Manager is to coordinate and take responsibility for site erosion and sediment control. The Construction Manager may delegate E&SC duties to subcontractors based upon the subcontractor with the appropriate equipment or the subcontractor who is responsible for creating a violation (i.e., sediment tracking, knocked down silt fence, by-passing stabilized construction entrance, etc). The Construction Manager is ultimately responsible for the day to day implementation of the SWPPP and preventing sediment-laden discharges from the site.

Sequence of Operations:

A. Pre-construction meeting to be attended by Construction Manager, contractor(s) or subcontractor(s) involved in earth disturbing activities, Qualified Inspector and City E&SC inspector

B. Install temporary chain link fence, erosion control measures, the office trailer and other related staging areas as shown on the plans. Keep equipment, vehicles and material stockpiles within designated staging areas or on pavement or concrete surfaces.

C. Install stabilized construction entrance(s) adjacent to the existing asphalt or concrete as shown on the plans.

D. Begin to bring in acceptable fill to raise the elevation in accordance with the special flood hazard area requirements.

E. Begin excavation for foundation.

F. Complete construction of the buildings.

G. Install curb, sidewalks and pavement

H. Clean and remove all construction-related debris and excess material.

I. Final grade around completed buildings and adjacent landscape areas.

J. Spread topsoil. Seed and mulch as construction is completed.

K. For areas used for construction staging to be restored to lawn and areas that were previously impervious and now lawn areas, provide de-compaction prior to spreading topsoil, seed and mulch. Refer to 'Soil Restoration' below and Appendix F.

L. Stabilize all permanent stormwater management and erosion control measures to remain.

M. Complete final grading of disturbed areas. In non-paved areas, topsoil and permanently vegetate, landscape and mulch.

N. Clear drainage pipes and structures of any sediment which may have accumulated.

O. Maintain all seeded and planted areas to insure a viable stabilized vegetative cover.

P. All erosion and sediment control practices to be inspected weekly and after rainfall events. Necessary repairs are to be made immediately following each inspection.

Q. After site is stabilized*, remove all temporary E&SC measures. Restore areas that may be disturbed by removal of temporary E&SC measures.

R. Additional erosion and sediment control measures shall be installed, as may be required and requested by authorities, to prevent the incidental discharge of sediment-laden runoff from entering a water course, a drainage system, or adjacent property.

S. The general permit for stormwater discharges from construction activities states that it is unlawful for any person to cause or contribute to a violation of water quality standards.

* Stabilization means covering or maintaining an existing cover over soil. Cover can be vegetative (e.g. grass, trees, seed and mulch, shrubs or turf) or non-vegetative (e.g. geotextiles, riprap, gabions, pavement, or crushed stone) per SPDES General Permit for Stormwater Runoff from Construction Activities, GP-0-20-001.

5.0 Erosion and Sediment Control Plan

Erosion and sedimentation control measures have been incorporated into the project design. Erosion and sedimentation control measures have been developed in accordance with applicable guidelines, specifically *New York State Standards and Specifications for Erosion and Sediment Control*, dated November 2016.

All disturbed areas will be stabilized as soon as conditions allow. In areas where soil disturbance has been temporarily or permanently ceased, temporary and/or permanent soil stabilization measures shall be installed and/or implemented within ten (10) days from the date the soil disturbance activity ceased. Total estimated area of disturbance is 1.63 acres.

Erosion and sediment control measures will be installed and in place prior to the start of any site disturbance. Temporary measures will remain in place and in good repair until permanent measures are implemented, are viable and function adequately.

Refer to the construction plans and details for more specific information on the dimensions, materials and installation of erosion and sediment control measures.

5.1 Temporary erosion and sediment control measures

Temporary erosion and sediment control measures to be used during the construction of the project include, but are not limited to, the following:

A. Silt fence will be installed along the downslope sides of all cleared areas to control deposition of transported sediment and reduce runoff velocity. This is of particular importance at boundaries with adjacent properties and at the top of existing slopes. Runoff must be directed away from the existing slope. Silt fence is to be installed parallel to contours (not up and down a slope).

B. A stabilized construction entrance will be installed prior to the start of construction. The stabilized construction entrance will be used to reduce sediment tracked by construction vehicle tires when exiting the disturbed area. Any sediment tracked onto the existing paved roadway will be cleared as necessary.

C. Storm drain inlet protection will be installed around each catch basin inlet to the existing storm drainage system to prevent sediment laden water from entering the system through the catch basin.

D. Stabilized temporary construction staging and parking areas will be provided for construction vehicles.

E. Topsoil stockpiles will be used to protect any topsoil that is removed. The stockpiles can be vegetated or covered with plastic sheeting to prevent erosion and preserve for future use.

F. Contractor will be required to provide dust control if necessary on a regular basis to eliminate the migration of airborne soil particles. This is to be achieved by sprinkling with water.

G. Contractor shall provide a designated 'concrete truck wash-out' area. The designated area is to be located to prevent wash-out water from entering waterways, wetlands or adjacent property and away from the slope.

5.2 Permanent erosion and sediment control measures

Permanent erosion and sediment control measures are incorporated into the final project design. All disturbed areas will receive buildings, pavement or suitable vegetative cover as soon as practical upon the completion of construction. Each area shall be re-vegetated and landscaped as the project progresses.

Permanent erosion and sediment control measures to be installed during the construction of the project include, but are not limited to, the following:

A. Establishment of lawn areas.

Refer to the Landscape Plans for additional information on permanent erosion and sediment control measures.

5.3 Soil Stabilization

Disturbed areas are to be stabilized as soon as practical, but no longer than ten (10) days since last disturbance. Seeding and mulching, either temporary or permanent is an inexpensive, quick and easy way to reduce erosion. Minimize the amount of exposed soil to minimize the erosion potential.

Stabilization measures shall include the following:

- Preservation and protection of existing trees and mature vegetation.
- Preservation of existing vegetation cover as long as possible (Do not remove all of the vegetative cover within the area of disturbance if some areas are not scheduled for work for a few weeks.)
- Protection of trees along the area of disturbance boundaries;
- Temporary seeding;
- Permanent seeding;
- Permanent plantings;
- Mulching;
- Geotextiles;
- Gravel or crushed stone surfaces; and
- Pavements (asphalt or concrete)

Refer to Appendix H for temporary seed mixtures. Refer to the Landscape Plans permanent seed mixtures.

Fertilizer use is discouraged, except as specifically required by the Landscape Architect. If fertilizer is requested, have a sample of topsoil tested to determine the correct fertilizer formula to use. Per NYS Dishwasher Detergent and Nutrient Runoff Law, effective August 14, 2010:

- Use of fertilizer containing phosphorus on non-agricultural lawns and turf is restricted.
- Application of any fertilizer for non-farm use is prohibited between December 1st and April 1st.
- Application of any fertilizer within 20 feet of a water body or on paved surfaces is restricted.
- Retailers must display fertilizer that contains phosphorous separately from phosphorus-free fertilizer and must post signs notifying customers of the terms of the law.

5.4 Maintenance of temporary erosion and sediment control measures

A. All erosion and sedimentation control practices shall be checked for stability and operation following every runoff-producing rainfall, but in no case less than once every week by the contractor, in addition to inspections by the Qualified Inspector. Necessary repairs shall be made immediately to maintain all practices as designed and installed.

B. The temporary stabilized construction entrance/exit shall be maintained in a condition which shall prevent tracking or flowing of sediment onto adjacent private or public roadways. If there is evidence of sediment-tracking onto public or campus roads, the sediment must be removed immediately and the stabilized construction entrance must receive a fresh layer of crushed stone immediately.

C. Sediment shall be removed from behind the silt fence when it becomes 6-inches deep at the fence. The silt fence shall be repaired as necessary to maintain an effective barrier.

D. All seeded areas are to be reseeded as necessary and mulched according to the specifications as depicted on the approved plans. Fertilizer use is discouraged, except as specifically required by the Landscape Architect. If fertilizer is requested by another party, have a sample of topsoil tested to determine the correct fertilizer formula to use.

5.5 Pollution Prevention Measures

A. Contractor shall provide litter control for all debris and trash generated from construction activity. This includes waste paper, wrappers, containers, packaging and similar trash generated by the work and workers. Contractor will control collection of this material with the use of covered trash receptacles. Debris and trash shall be collected and removed by the contractor on a daily basis.

1. Construction Manager to ensure that all contractors are using the

provided trash receptacles. Construction Manager to provide additional trash receptacles if necessary to encourage contractors to use them.

B. Do not store construction material or construction waste receptacles near waterways, wetlands or adjacent to the top of steep slopes.

C. All oils, grease, solvents and other fluids necessary for the maintenance and operation of equipment used for the work are to be handled properly, contained and collected for use or disposal at the appropriate recycling center or collection site.

D. Contractor to have a 'spill kit' on-site in case of a chemical spill. Contractor shall be familiar with NYS DEC spill reporting requirements. Refer to Appendix I.

6.0 POST-CONSTRUCTION STORMWATER MANAGEMENT

In accordance with the general permit GP-0-20-001, and Chapter 9 "Redevelopment Activity" of *New York State Stormwater Management Design Manual*, January 2015 (SMDM); this project is considered a redevelopment activity in that it includes the disturbance and reconstruction of existing impervious surfaces. Requirements for the installation of post construction stormwater management controls for water quality apply for construction projects including redevelopment activities.

Per *New York State Stormwater Management Design Manual*, January 2015, Chapter 9, Section 9.2, "The provision of stormwater management practices during redevelopment activities should follow an approach to balance between 1) maximizing improvements in site design that can reduce the impacts of stormwater runoff, and 2) providing a maximum level of on-site treatment that is feasible given then site constraints present where the redevelopment activities are occurring."

This area of North Hamilton St has been developed in some fashion for decades.

The area of disturbance associated with this current project is **1.63 acres**. Within this **1.63 acre** area of disturbance, there is approximately 0.6 acres of existing impervious surfaces consisting of the existing concrete slabs, parking areas and compacted gravel. The project proposes to remove the existing impervious areas and replace them with the buildings, parking and sidewalks. Upon completion of the project there will be approximately 1.25 acres of impervious surfaces, a net increase in impervious area of 0.65 acres. The remainder of the project area will be pervious surfaces either in the form of lawn area or landscaping.

6.1 Water Quality Volume (WQv)

The plan proposes that a minimum of 25% of the water quality volume from the existing disturbed impervious area is captured and treated by a standard stormwater management practice as well as 100% of the new impervious area.

Refer to Table 1, below, for existing and post-construction impervious surface areas within the **1.63** acre area of disturbance. Due to site topography and the site development, there are no areas outside of the area of disturbance that will contribute stormwater runoff. Stormwater sizing does not have to include any 'run-on' areas.

Table 1– Impervious Areas for Existing and Post-Construction Conditions within Area of Disturbance

	Impervious Area (ac)	Impervious Area to be Treated (%)	Impervious Area to be Treated (ac)
Existing	0.60	25	0.15
Additional Post-Construction	0.65	100	0.65
Total Post-Construction	1.25		0.80

The water quality volume necessary for treatment is determined by the equation provided in the NYS Stormwater Management Design Manual, January 2015:
$WQv = [(P)(Rv)(A)]/12,$ (pg 4-2)

Where:

WQv = Water Quality Volume in acre feet
P = 90% Rainfall Event Number, 1.4 inches for this site
I = Impervious Cover
Rv = 0.05+0.009(I), Minimum Rv = 0.28
A = site area in acres.

The proposed disturbed area is **1.63 acres**.

The water quality volume is 4069 cubic feet (ft3). Based upon the *NYS Stormwater Management Design Manual*, January 2015, water quality treatment can be achieved by runoff reduction methods and green infrastructure techniques.

6.2 Runoff Reduction Volume (RRv)

According to the *NYS Stormwater Management Design Manual*, January 2015, Chapter 4, the Runoff Reduction Volume (RRv) is the "reduction of the total WQv by application of green infrastructure techniques and SMPs to replicate pre-development hydrology."

Per Chapter 9, Section 9.2, Scope and applicability "Although encouraged, meeting the Runoff Reduction Volume (RRv) sizing criteria is not required for the redevelopment

activity portion of the project." For this project, runoff reduction methods will be implemented.

As noted herein this is a redevelopment activity. Runoff reduction and green infrastructure practices were evaluated and incorporated into the project to the maximum extent practicable. The runoff reduction and green infrastructure practices detailed in Chapter 5 of the SMDM were evaluated within the context of this proposal. Those elements which could feasibly and reasonably be incorporated into the project have been. The incorporated elements are further described below.

6.2.1 **Soil Restoration**

According to *NYS Stormwater Management Design Manual*, January 2015, Chapter 5, Section 5.1.6, "Soil Restoration is a required practice applied across areas of a development site where soils have been disturbed and will be vegetated in order to recover the original properties and porosity of the soil." Furthermore, "Soil Restoration is applied in the cleanup, restoration, and landscaping phase of construction followed by the permanent establishment of an appropriate, deep-rooted ground cover to help maintain the restored soil structure. Soil Restoration includes mechanical decompaction, compost amendment or both."

Per SMDM Table 5.3 "Soil Restoration Requirements," full soil restoration, including decompaction and compost enhancement, is required in "heavy traffic areas on site (especially in a zone 5-25 feet around buildings, but not within a 5 foot perimeter around foundation walls)," and for "redevelopment projects in areas where existing impervious area will be converted to pervious area."

For this project, soil restoration will be required in limited areas where existing impervious surface is replaced with landscaping.

Refer to Appendix F for additional information.

6.2.2 **Pervious Pavement**

According to *NYS Stormwater Management Design Manual*, January 2015, Chapter 5, Section 5.3.11, "Permeable paving provides an alternative to conventional asphalt and concrete surfaces and are designed to convey rainfall through the surface into an underlying reservoir where it can infiltrate, thereby reducing stormwater runoff from a site. In addition, permeable paving reduces impacts of impervious cover by augmenting the recharge of groundwater through infiltration, and providing some pollutant uptake in the underlying soils."

Per the Stormwater Manual, "The basic equation for sizing the required porous surface area is as follows:

Ap = Vw/(n x dt), (pg 5-111)

Where:
Ap = the required porous pavement surface area (square feet)
Vw = the design volume (cubic feet)
n = porosity of gravel bed/reservoir (assume 0.4)
dt = depth of gravel bed/reservoir (maximum of four feet, and separated by at least three feet from seasonally high groundwater) (feet)

"Design volume Vw may include WQv and CPv from contributing area."

There is 4900 SF of surface area to be porous pavement. The required WQv for that surface area is 543 cubic feet. 4900 SF of surface area with 1 foot of gravel bed/reservoir provides 1960 cubic feet of treatment. The excess treated volume can be applied to CPv.

6.2.3 **Combined Effect of Runoff Reduction & Green Infrastructure**

The benefits of the green infrastructure practices Green Roof and Bioretention Area can be combined to benefit the overall project site and meet the project's water quality and runoff reduction requirements.

Table 4 – Combined Benefits of Runoff Reduction and Green Infrastructure

WQv Calculation	Required WQv (ft^3)	Provided WQv (ft^3)	Provided RRv (ft^3)
Standard Calculation for WQv	4069		
WQv Treated by Porous Pavement		543	543
WQv Treated by underground infiltration chambers		3888	3888
Total	4069	4431	4431

The green infrastructure practices of Porous Pavement and standard practice of infiltration with underground infiltration chambers provide 4431 cubic feet of water quality treatment and 4431 cubic feet of runoff reduction volume. This exceeds the minimum required water quality volume of 4069 cubic feet.

The requirements for water quality treatment (WQv) and runoff reduction (RRv) have been achieved through green infrastructure practices and standard practices as outlined in Chapter 5 of the *NYS Stormwater Management Design Manual*, January 2015.

6.3 Channel Protection Volume (Cpv)

According to *NYS Stormwater Management Design Manual*, January 2015, Chapter 4, Table 4.1, Cpv is the "24 hour extended detention of post-developed 1-year, 24-hour storm event; remaining after runoff reduction. Where site conditions allow, runoff reduction of total Cpv is encouraged."

6.3.1 Channel Protection Volume (Cpv) for Redevelopment

According to *NYS Stormwater Management Design Manual*, January 2015, Chapter 9 Redevelopment Projects, Section 9.2.1 Sizing Criteria, A(II) "Channel protection for redevelopment activities is not required if there are no changes to hydrology that increase the discharge rate from the project site." This same section states " If the hydrology and the hydraulic analysis for the project site shows that the post construction 1-year 24 hour discharge rate and velocity are less than or equal the preconstruction discharge rate, providing 24 hour detention of the 1 year storm to meet the channel protection criteria is not required."

This is a redevelopment project. The hydrology and the hydraulic analysis for the project indicate that the post construction 1 year 24 hour peak discharge rate is less than or equal to the pre-construction discharge rate with the use of the underground infiltration chambers. A simple pre versus post analysis yields a reduced discharge rate for the post-construction condition. The project does not otherwise modify the hydrology of the project area. No new point discharges have been established. Therefore use of the underground infiltration chambers as water quantity control is sufficient, including channel protection volume, Cpv.

6.4 Water Quantity (10 & 100 Year Storms)

According to *NYS Stormwater Management Design Manual*, January 2015, Chapter 9 Redevelopment Projects, Section 9.3.2 Sizing Criteria, A(I) "[i]f redevelopment activities result in no change to hydrology that increases the discharge rate from the site the ten-year and 100-year criteria do not apply."

The analysis prepared for the project indicates that the post development discharges is less than the pre development discharge. There is no identifiable change in the hydrology of the area. Therefore no water quantity controls are required beyond the use of the underground infiltration chambers design for water quality volume.

Refer to Appendix G for Hydrocad report.

6.5 Deviation from Standards

As required in SPDES General Permit for Stormwater Discharges from Construction Activity, Permit No. GP-0-20-001, Part III.B.2.d, any elements of design that are not in conformance with the Design Manual (SMDM, January 2015) must be identified.

This project is in conformance with the *NYS Stormwater Management Design Manual,* January 2015.

7.0 LONG TERM MAINTENANCE AND OPERATION OF PERMANENT POST-CONSTRUCTION MANAGEMENT PRACTICE

Long-term maintenance and operation will be the responsibility of the property owner(s). This includes:

7.1 Soil Restoration

7.1.1 First Year Maintenance

7.1.1.1 Initial inspections for the first six (6) months, including after each storm greater than half-inch of rainfall.

7.1.1.2 Reseeding to repair bare or eroding areas to assure grass stabilization

7.1.1.3 Water once every three days for first month, and then provide a half inch of water per week during the first year. Irrigation plan may be adjusted according to the rain event

7.1.1.4 Fertilization may be needed in the fall after the first growing season to increase plant vigor. Avoid over-fertilization.

7.1.2 Ongoing Maintenance

7.1.2.1 Keep site free of vehicular traffic or other weight loads

7.1.2.2 Inspect lawn area after winter for damage from plowing operations; re-seed as necessary.

7.1.2.3 Inspect lawn area after major campus events for bare spots; re-seed as necessary.

7.2 Porous Pavement

7.2.1 Ensure that paving area is clean of debris (Monthly)

7.2.2 Ensure that paving dewaters between storms (Monthly and after storms greater than 0.5 inches)

7.2.3 Ensure that the area is clean of sediments (Monthly)

7.2.4 Mow upland and adjacent areas and seed bare areas (As needed)

7.2.5 Vacuum sweep frequently to keep surface free of sediments (Typically 3 to 4 times per year)

7.2.6 Inspect the surface for deterioration or spalling (Annually)

7.3 **Underground Infiltration Chambers**

7.3.1 Refer to manufacturer's requirements.

7.4 **General Maintenance Requirements**

7.4.1 Signage - According to *NYS Stormwater Management Design Manual*, January 2015, Chapter 3, Section 3.5, an "owner of a post-construction stormwater management practice…shall erect or post, in the immediate vicinity of the stormwater management practice, a conspicuous and legible sign of not less than 18 inches by 24 inches."

7.4.1.1 Stormwater management practices that require signage: Green Roof.

7.4.1.2 Example Sign

STORMWATER MANAGEMENT PRACTICE -	Green Roof
Project Identification -	SPDES NYR #
Must be maintained in accordance with O&M Plan	
DO NOT REMOVE OR ALTER	

7.4.2 Responsible Entity – The property owner(s) is the entity responsible for long term operation and maintenance of the stormwater management practices.

7.4.3 Schematics of Practice – Design drawings for the stormwater management practices are included in this SWPPP as 11" x 17" reduced size drawings. Property owner(s) will be provided with full size copies for O&M purposes.

7.4.4 List of Maintenance Requirements – Refer to maintenance requirements outlined above in Sections 7.1 to 7.4.

8.0 ENHANCED PHOSPHORUS REMOVAL STANDARDS

This project is not located in a watershed identified in Appendix C of GP-0-15-002. Therefore enhanced phosphorus removal standards are not applicable to this project.

9.0 SWPPP SITE INSPECTIONS

According to SPDES General Permit for Stormwater Discharges from Construction Activity, Permit No. GP-0-20-0021 Part IV. A. 1 "The owner or operator must ensure that all erosion and sediment control practices and all post-construction stormwater management practices identified in the SWPPP are maintained in effective operating condition at all times."

A 'qualified inspector' must conduct the SWPPP site inspections. Per GP-0-15-002, Part IV. C. qualified inspector must be:

- Licensed Professional Engineer (PE)
- Certified Professional in Erosion and Sediment Control (CPESC)
- Registered Landscape Architect (RLA)

- Someone working under the direct supervision of, and at the same company as, the licensed PE or RLA, provided they have received four (4) hours of NYSDEC endorsed training in proper erosion and sediment control principles from a Soil and Water Conservation District or other NYSDEC endorsed entity.

A 'Qualified Inspector' must conduct site inspections at least once every seven (7) calendar days. Inspections are to include verifying that all erosion & sediment control practices are operational and maintained, inspection of construction of post-construction management practices, looking for evidence of soil erosion on the site, looking for evidence of pollutants entering the drainage system and all points of discharge to natural surface waterbodies located within, or immediately adjacent to, the property boundaries of the construction site, and all points of discharge from the construction site.

Refer to GP-0-20-001, Part IV. C. 4 for a complete description of what must be included in the site inspection report. To summarize; the inspection report must include the date and time of inspection, name and title of person performing the inspection, description of weather and soil conditions, description of the condition of runoff at all points of discharge, description of condition of and all points of discharge to natural surface waterbodies located within, or immediately adjacent to, the property boundaries of the construction site, and all points of discharge from the construction site. Report must also include identification of all erosion and sediment control practices that need maintenance, repair, or were not installed properly, description and sketch of areas disturbed at time of inspection and areas that have been stabilized since last inspection. Report must also include the current phase of construction of any post-construction stormwater management practices. Any corrective actions that must be taken to install, repair, replace or maintain E&SC practices and any deficiencies identified with the post-construction stormwater management practices must be included in the report. Additionally, digital photographs, with date stamp showing the condition of all practices identified as needing corrective action. The qualified inspector must take digital photographs that show the practice after corrective action work has taken place.

10.0 TRAINED CONTRACTOR

According to SPDES General Permit for Stormwater Discharges from Construction Activity, Permit No. GP-0-20-001, Part III. A. 6. "Prior to the commencement of construction activity, the owner or operator must identify the contractor(s) and subcontractor(s) that will be responsible for installing, construction, repairing, replacing, inspecting, and maintaining the erosion and sediment control practices included in the SWPPP; and the contractor(s) and subcontractor(s) that will be responsible for constructing the post-construction stormwater management practices included in the SWPPP." Additionally, "the owner or operator shall ensure that at least one trained contractor is on site on a daily basis when soil disturbance activities are being performed."

According to SPDES General Permit for Stormwater Discharges from Construction Activity, Permit No. GP-0-20-001, Appendix A 'Definitions,' a Trained Contractor is "an employee from the contracting (construction) company,...that has received four (4) hours of Department endorsed training in proper erosion and sediment control principles from a Soil and Water Conservation District, or other Department endorsed entity. After receiving the initial training, the trained contractor shall receive four (4) hours of training every three (3) years... The trained contractor will be responsible for the day to day implementation of the SWPPP."

Any contractors or sub-contractors performing earth-disturbing activities, that are responsible for maintaining erosion & sediment control measures, and/or constructing the post-construction management practices must sign the "Contractor's Certification." The contractor or subcontractors must designate a 'trained contractor.' A copy of the "Contractor's Certification" is included in Appendix J.

The "Contractor Certification" forms must be maintained at the construction site until all disturbed areas have achieved final stabilization and the Notice of Termination (NOT) has been filled out, signed by the MS4 (City of Poughkeepsie) and submitted to NYSDEC.

11.0 CONSTRUCTION SITE LOG BOOK

A Construction Site Log Book must be maintained at the construction site. This book must be readily available for inspection by any federal, state, county, local or Owner/Operator appointed inspector. The Construction Site Log Book must contain at a minimum, the following:

1.0 NYS DEC General Permit GP-0-20-001
2.0 Notice of Intent (NOI)
3.0 MS4 Acceptance Form
4.0 Letter of Acknowledgment from NYS DEC
5.0 SWPPP
    5.1 SWPPP Updates or Modifications
6.0 Contractor Certification Forms
7.0 Inspection Reports

A sample "Construction Site Log Book" table of contents and sample forms are provided in Appendix J of this report.

12.0 DUTY TO PROVIDE INFORMATION

According to SPDES General Permit for Stormwater Discharges from Construction Activity, Permit No. GP-0-20-001, Part III. A. 7, "For project where the Department [NYSDEC] requests a copy of the SWPPP or inspection reports, the owner or operator

shall submit the documents in both electronic (PDF only) and paper format within five (5) business days, unless otherwise notified by the Department."

According to SPDES General Permit for Stormwater Discharges from Construction Activity, Permit No. GP-0-20-001, Part VII. F.:

"The owner or operator shall make available to the Department [NYSDEC] for review and copying or furnish to the Department within five (5) business days of receipt of a Department request for such information, any information requested for the purpose of determining compliance with this permit. This can include, but is not limited to, the NOI, NOI Acknowledgment Letter, SWPPP, MS4 SWPPP Acceptance form, executed maintenance agreement, and inspection reports. Failure to provide information requested by the Department within the request timeframe shall be a violation of this permit.

The NOI, SWPPP and inspection reports required by this permit are public documents that the owner or operator must make available for review and copying by any person within five (5) business days of the owner or operator receiving a written request by any such person to review the NOI, SWPPP or inspection reports. Copying of documents will be done at the requester's expense."

13.0 RECORD RETENTION

It is recognized that stormwater pollution prevention efforts can be enhanced by retaining records in an orderly manner at one location for reference. Provisions of GP-0-20-001 also require the retention of certain records. Therefore, records regarding stormwater pollution prevention activities shall be maintained at the construction site. The records shall be retained and maintained by the Owner for a period of at least five (5) years after the filing of the Notice of Termination (NOT) for General Permit coverage. Records to be retained shall include the following:

- The SWPPP and all revisions.
- All NOI's to discharge to waters of the United States under authorization of the Construction General Permit as well as all data used to determine Permit eligibility.
- MS4 SWPPP Acceptance Form(s)
- NYS DEC NOI Acknowledgment letter(s)
- Certifications required by the SWPPP
  - Contractor Certification Forms
- All inspection reports.
- Construction activity records indicating dates of construction milestones and stormwater management and pollution prevention control installations.
- All spill reports/notifications.
- All NOT's

14.0 REVISION OF THE SWPPP

The SWPPP must be amended whenever:

1. There is a change in design, construction, operation or maintenance which will have a significant effect on the potential for the discharge of pollutants to waters of the United States;

2. The SWPPP proves to be ineffective in eliminating or significantly minimizing pollutants from the sources; or

3. The SWPPP is proven to be ineffective in achieving the general objectives of controlling pollutants from the construction site's stormwater discharges. Plan certifications shall also be made whenever Permittees change for the described project.

Additionally, the MS4 must be notified. According to SPDES General Permit for Stormwater Discharges from Construction Activity, Permit No. GP-0-20-001, Part II.C.5 "For construction activities that are subject to the requirements of a regulated, traditional land use control MS4, the owner or operator shall notify the MS4 in writing of any planned amendments or modifications to the post-construction stormwater management practice component of the SWPPP…"

15.0 TERMINATION OF COVERAGE

According to SPDES General Permit for Stormwater Discharges from Construction Activity, Permit No. GP-0-20-001, Part V. A., coverage under GP-0-20-001 can be terminated by the owner or operator by filing the Notice of Termination (NOT) with NYSDEC. The owner or operator may terminate coverage when one or more of the following conditions have been met:

a. Total project completion
b. Planned shutdown with partial project completion
c. New owner or operator

The qualified inspector must complete a final inspection, unless the NOT is filed for change of owner.

Additionally, the MS4 must be notified. According to SPDES General Permit for Stormwater Discharges from Construction Activity, Permit No. GP-0-20-001, Part V.A. 4 "For construction activities that are subject to the requirements of a regulated traditional land use control MS4 and" have achieved total project completion or planned shutdown with partial completion "the owner or operator shall also have the MS4 sign the "MS4 Acceptance" statement on the NOT."

Projects that have post-construction stormwater management practices must ensure there are policies and procedures in place to ensure operation and maintenance of the practices in accordance with the SWPPP.

16.0 CONCLUSION

The purpose of the project is to redevelop previously developed area within the City of Poughkeepsie that has been vacant for some time. The project meets this goal with little to no impacts on drainage. The project substantially preserves pre-development area hydrology.

This project is in substantial compliance with the requirements of New York State Department of Environmental Conservation, NYS DEC, as stated in the SPDES General Permit for Stormwater Discharges from Construction Activity, GP-0-20-001, "*New York State Stormwater Management Design Manual*," January 2015 and the *"New York State Standards and Specifications for Erosion and Sediment Control,"* November 2016 (Blue Book).

With the above outlined stormwater pollution prevention plan, including runoff reduction methods and green infrastructure practices, this project will not negatively impact the environment or adjacent property owners.

Refer to the appendices and construction drawings for more detailed calculations and information.

APPENDIX A

NOTICE OF INTENT (NOI)

(Not included at this time)

APPENDIX B

MS4 SWPPP ACCEPTANCE FORM

(Not included at this time)

APPENDIX C

SITE DATA

VICINITY MAP
SOILS INFORMATION – WEB SOIL SURVEY

Dutchess County
New York

117 North Hamilton

Dutchess County, NY

Printed By:
ParcelAccess

N

ParcelAccess
3/2/2023



Dutchess County
New York

117 North Hamilton

Dutchess County, NY

Printed By:
ParcelAccess

N

ParcelAccess
3/2/2023

National Flood Hazard Layer FIRMette

FEMA

73°55'33"W 41°42'45"N

73°54'55"W 41°42'18"N

0 250 500 1,000 1,500 2,000 Feet

1:6,000

Legend

SEE FIS REPORT FOR DETAILED LEGEND AND INDEX MAP FOR FIRM PANEL LAYOUT

SPECIAL FLOOD HAZARD AREAS
- Without Base Flood Elevation (BFE) *Zone A, V, A99*
- With BFE or Depth *Zone AE, AO, AH, VE, AR*
- Regulatory Floodway

OTHER AREAS OF FLOOD HAZARD
- 0.2% Annual Chance Flood Hazard, Area of 1% annual chance flood with average depth less than one foot or with drainag areas of less than one square mile *Zone*
- Future Conditions 1% Annual Chance Flood Hazard *Zone X*
- Area with Reduced Flood Risk due to Levee. See Notes. *Zone X*
- Area with Flood Risk due to Levee *Zone D*

OTHER AREAS
- NO SCREEN Area of Minimal Flood Hazard *Zone X*
- Effective LOMRs
- Area of Undetermined Flood Hazard *Zone*

GENERAL STRUCTURES
- Channel, Culvert, or Storm Sewer
- Levee, Dike, or Floodwall

OTHER FEATURES
- 20.2 / 17.5 Cross Sections with 1% Annual Chance Water Surface Elevation
- Coastal Transect
- Base Flood Elevation Line (BFE)
- Limit of Study
- Jurisdiction Boundary
- Coastal Transect Baseline
- Profile Baseline
- Hydrographic Feature

MAP PANELS
- Digital Data Available
- No Digital Data Available
- Unmapped

N

The pin displayed on the map is an approximate point selected by the user and does not represe an authoritative property location.

This map complies with FEMA's standards for the use of digital flood maps if it is not void as described below. The basemap shown complies with FEMA's basemap accuracy standards

The flood hazard information is derived directly from the authoritative NFHL web services provided by FEMA. This map was exported on 2/23/2023 at 11:42 AM and does not reflect changes or amendments subsequent to this date and time. The NFHL and effective information may change or become superseded by new data over time.

This map image is void if the one or more of the following map elements do not appear: basemap imagery, flood zone labels, legend, scale bar, map creation date, community identifiers, FIRM panel number, and FIRM effective date. Map images for unmapped and unmodernized areas cannot be used for regulatory purposes.

Stormwater Interactive Map



The coordinates of the point you clicked on are:

UTM 18	**Easting:**	589808.819	**Northing:**	4618007.449
Longitude/Latitude	**Latitude:**	41.709	**Longitude:**	-73.921

The approximate address of the point you clicked on is:
97 N Hamilton St, Poughkeepsie, New York, 12601

County: Dutchess
City: Poughkeepsie
USGS Quad: POUGHKEEPSIE

DEC Administrative Boundaries

Region 3:
(Lower Hudson Valley) Dutchess, Orange, Putnam, Rockland, Sullivan, Ulster and Westchester counties. For more information visit http://www.dec.ny.gov/about/607.html.

Impaired Streams for MSGP

PWL ID: undefined
Waterbody Name: undefined
Waterbody Type: undefined
Applicable Sectors: undefined
Pollutant: undefined

Impaired Estuaries for MSGP

PWL ID: undefined
Waterbody Name: undefined
Waterbody Type: undefined
Applicable Sectors: undefined
Pollutant: undefined

USDA United States Department of Agriculture

NRCS Natural Resources Conservation Service

A product of the National Cooperative Soil Survey, a joint effort of the United States Department of Agriculture and other Federal agencies, State agencies including the Agricultural Experiment Stations, and local participants

Custom Soil Resource Report for Dutchess County, New York

North Hamilton Parcel LLC

Preface

Soil surveys contain information that affects land use planning in survey areas. They highlight soil limitations that affect various land uses and provide information about the properties of the soils in the survey areas. Soil surveys are designed for many different users, including farmers, ranchers, foresters, agronomists, urban planners, community officials, engineers, developers, builders, and home buyers. Also, conservationists, teachers, students, and specialists in recreation, waste disposal, and pollution control can use the surveys to help them understand, protect, or enhance the environment.

Various land use regulations of Federal, State, and local governments may impose special restrictions on land use or land treatment. Soil surveys identify soil properties that are used in making various land use or land treatment decisions. The information is intended to help the land users identify and reduce the effects of soil limitations on various land uses. The landowner or user is responsible for identifying and complying with existing laws and regulations.

Although soil survey information can be used for general farm, local, and wider area planning, onsite investigation is needed to supplement this information in some cases. Examples include soil quality assessments (http://www.nrcs.usda.gov/wps/portal/nrcs/main/soils/health/) and certain conservation and engineering applications. For more detailed information, contact your local USDA Service Center (https://offices.sc.egov.usda.gov/locator/app?agency=nrcs) or your NRCS State Soil Scientist (http://www.nrcs.usda.gov/wps/portal/nrcs/detail/soils/contactus/?cid=nrcs142p2_053951).

Great differences in soil properties can occur within short distances. Some soils are seasonally wet or subject to flooding. Some are too unstable to be used as a foundation for buildings or roads. Clayey or wet soils are poorly suited to use as septic tank absorption fields. A high water table makes a soil poorly suited to basements or underground installations.

The National Cooperative Soil Survey is a joint effort of the United States Department of Agriculture and other Federal agencies, State agencies including the Agricultural Experiment Stations, and local agencies. The Natural Resources Conservation Service (NRCS) has leadership for the Federal part of the National Cooperative Soil Survey.

Information about soils is updated periodically. Updated information is available through the NRCS Web Soil Survey, the site for official soil survey information.

The U.S. Department of Agriculture (USDA) prohibits discrimination in all its programs and activities on the basis of race, color, national origin, age, disability, and where applicable, sex, marital status, familial status, parental status, religion, sexual orientation, genetic information, political beliefs, reprisal, or because all or a part of an individual's income is derived from any public assistance program. (Not all prohibited bases apply to all programs.) Persons with disabilities who require

alternative means for communication of program information (Braille, large print, audiotape, etc.) should contact USDA's TARGET Center at (202) 720-2600 (voice and TDD). To file a complaint of discrimination, write to USDA, Director, Office of Civil Rights, 1400 Independence Avenue, S.W., Washington, D.C. 20250-9410 or call (800) 795-3272 (voice) or (202) 720-6382 (TDD). USDA is an equal opportunity provider and employer.

Contents

Preface 2
How Soil Surveys Are Made 5
Soil Map 8
Soil Map (North Hamilton Parcel) 9
Legend 10
Map Unit Legend (North Hamilton Parcel) 11
Map Unit Descriptions (North Hamilton Parcel) 11
Dutchess County, New York 13
BeC—Bernardston silt loam, 8 to 15 percent slopes 13
DxB—Dutchess-Cardigan-Urban land complex, undulating, rocky 14
Soil Information for All Uses 17
Soil Reports 17
Water Features 17
Hydrologic Soil Group and Surface Runoff (North Hamilton Parcel) 17
References 19

How Soil Surveys Are Made

Soil surveys are made to provide information about the soils and miscellaneous areas in a specific area. They include a description of the soils and miscellaneous areas and their location on the landscape and tables that show soil properties and limitations affecting various uses. Soil scientists observed the steepness, length, and shape of the slopes; the general pattern of drainage; the kinds of crops and native plants; and the kinds of bedrock. They observed and described many soil profiles. A soil profile is the sequence of natural layers, or horizons, in a soil. The profile extends from the surface down into the unconsolidated material in which the soil formed or from the surface down to bedrock. The unconsolidated material is devoid of roots and other living organisms and has not been changed by other biological activity.

Currently, soils are mapped according to the boundaries of major land resource areas (MLRAs). MLRAs are geographically associated land resource units that share common characteristics related to physiography, geology, climate, water resources, soils, biological resources, and land uses (USDA, 2006). Soil survey areas typically consist of parts of one or more MLRA.

The soils and miscellaneous areas in a survey area occur in an orderly pattern that is related to the geology, landforms, relief, climate, and natural vegetation of the area. Each kind of soil and miscellaneous area is associated with a particular kind of landform or with a segment of the landform. By observing the soils and miscellaneous areas in the survey area and relating their position to specific segments of the landform, a soil scientist develops a concept, or model, of how they were formed. Thus, during mapping, this model enables the soil scientist to predict with a considerable degree of accuracy the kind of soil or miscellaneous area at a specific location on the landscape.

Commonly, individual soils on the landscape merge into one another as their characteristics gradually change. To construct an accurate soil map, however, soil scientists must determine the boundaries between the soils. They can observe only a limited number of soil profiles. Nevertheless, these observations, supplemented by an understanding of the soil-vegetation-landscape relationship, are sufficient to verify predictions of the kinds of soil in an area and to determine the boundaries.

Soil scientists recorded the characteristics of the soil profiles that they studied. They noted soil color, texture, size and shape of soil aggregates, kind and amount of rock fragments, distribution of plant roots, reaction, and other features that enable them to identify soils. After describing the soils in the survey area and determining their properties, the soil scientists assigned the soils to taxonomic classes (units). Taxonomic classes are concepts. Each taxonomic class has a set of soil characteristics with precisely defined limits. The classes are used as a basis for comparison to classify soils systematically. Soil taxonomy, the system of taxonomic classification used in the United States, is based mainly on the kind and character of soil properties and the arrangement of horizons within the profile. After the soil

scientists classified and named the soils in the survey area, they compared the individual soils with similar soils in the same taxonomic class in other areas so that they could confirm data and assemble additional data based on experience and research.

The objective of soil mapping is not to delineate pure map unit components; the objective is to separate the landscape into landforms or landform segments that have similar use and management requirements. Each map unit is defined by a unique combination of soil components and/or miscellaneous areas in predictable proportions. Some components may be highly contrasting to the other components of the map unit. The presence of minor components in a map unit in no way diminishes the usefulness or accuracy of the data. The delineation of such landforms and landform segments on the map provides sufficient information for the development of resource plans. If intensive use of small areas is planned, onsite investigation is needed to define and locate the soils and miscellaneous areas.

Soil scientists make many field observations in the process of producing a soil map. The frequency of observation is dependent upon several factors, including scale of mapping, intensity of mapping, design of map units, complexity of the landscape, and experience of the soil scientist. Observations are made to test and refine the soil-landscape model and predictions and to verify the classification of the soils at specific locations. Once the soil-landscape model is refined, a significantly smaller number of measurements of individual soil properties are made and recorded. These measurements may include field measurements, such as those for color, depth to bedrock, and texture, and laboratory measurements, such as those for content of sand, silt, clay, salt, and other components. Properties of each soil typically vary from one point to another across the landscape.

Observations for map unit components are aggregated to develop ranges of characteristics for the components. The aggregated values are presented. Direct measurements do not exist for every property presented for every map unit component. Values for some properties are estimated from combinations of other properties.

While a soil survey is in progress, samples of some of the soils in the area generally are collected for laboratory analyses and for engineering tests. Soil scientists interpret the data from these analyses and tests as well as the field-observed characteristics and the soil properties to determine the expected behavior of the soils under different uses. Interpretations for all of the soils are field tested through observation of the soils in different uses and under different levels of management. Some interpretations are modified to fit local conditions, and some new interpretations are developed to meet local needs. Data are assembled from other sources, such as research information, production records, and field experience of specialists. For example, data on crop yields under defined levels of management are assembled from farm records and from field or plot experiments on the same kinds of soil.

Predictions about soil behavior are based not only on soil properties but also on such variables as climate and biological activity. Soil conditions are predictable over long periods of time, but they are not predictable from year to year. For example, soil scientists can predict with a fairly high degree of accuracy that a given soil will have a high water table within certain depths in most years, but they cannot predict that a high water table will always be at a specific level in the soil on a specific date.

After soil scientists located and identified the significant natural bodies of soil in the survey area, they drew the boundaries of these bodies on aerial photographs and

identified each as a specific map unit. Aerial photographs show trees, buildings, fields, roads, and rivers, all of which help in locating boundaries accurately.

Soil Map

The soil map section includes the soil map for the defined area of interest, a list of soil map units on the map and extent of each map unit, and cartographic symbols displayed on the map. Also presented are various metadata about data used to produce the map, and a description of each soil map unit.

Custom Soil Resource Report
Soil Map (North Hamilton Parcel)



Map Scale: 1:873 if printed on A landscape (11" x 8.5") sheet.

N

Meters: 0 10 20 40 60

Feet: 0 40 80 160 240

Map projection: Web Mercator Corner coordinates: WGS84 Edge tics: UTM Zone 18N WGS84

MAP LEGEND

Area of Interest (AOI)
- Area of Interest (AOI)

Soils
- Soil Map Unit Polygons
- Soil Map Unit Lines
- Soil Map Unit Points

Special Point Features
- Blowout
- Borrow Pit
- Clay Spot
- Closed Depression
- Gravel Pit
- Gravelly Spot
- Landfill
- Lava Flow
- Marsh or swamp
- Mine or Quarry
- Miscellaneous Water
- Perennial Water
- Rock Outcrop
- Saline Spot
- Sandy Spot
- Severely Eroded Spot
- Sinkhole
- Slide or Slip
- Sodic Spot
- Spoil Area
- Stony Spot
- Very Stony Spot
- Wet Spot
- Other
- Special Line Features

Water Features
- Streams and Canals

Transportation
- Rails
- Interstate Highways
- US Routes
- Major Roads
- Local Roads

Background
- Aerial Photography

MAP INFORMATION

The soil surveys that comprise your AOI were mapped at 1:24,000.

Warning: Soil Map may not be valid at this scale.

Enlargement of maps beyond the scale of mapping can cause misunderstanding of the detail of mapping and accuracy of soil line placement. The maps do not show the small areas of contrasting soils that could have been shown at a more detailed scale.

Please rely on the bar scale on each map sheet for map measurements.

Source of Map: Natural Resources Conservation Service
Web Soil Survey URL:
Coordinate System: Web Mercator (EPSG:3857)

Maps from the Web Soil Survey are based on the Web Mercator projection, which preserves direction and shape but distorts distance and area. A projection that preserves area, such as the Albers equal-area conic projection, should be used if more accurate calculations of distance or area are required.

This product is generated from the USDA-NRCS certified data as of the version date(s) listed below.

Soil Survey Area: Dutchess County, New York
Survey Area Data: Version 19, Sep 10, 2022

Soil map units are labeled (as space allows) for map scales 1:50,000 or larger.

Date(s) aerial images were photographed: Oct 8, 2020—Oct 14, 2020

The orthophoto or other base map on which the soil lines were compiled and digitized probably differs from the background imagery displayed on these maps. As a result, some minor shifting of map unit boundaries may be evident.

Map Unit Legend (North Hamilton Parcel)

Map Unit Symbol	Map Unit Name	Acres in AOI	Percent of AOI
BeC	Bernardston silt loam, 8 to 15 percent slopes	0.3	18.4%
DxB	Dutchess-Cardigan-Urban land complex, undulating, rocky	1.3	81.6%
Totals for Area of Interest		**1.6**	**100.0%**

Map Unit Descriptions (North Hamilton Parcel)

The map units delineated on the detailed soil maps in a soil survey represent the soils or miscellaneous areas in the survey area. The map unit descriptions, along with the maps, can be used to determine the composition and properties of a unit.

A map unit delineation on a soil map represents an area dominated by one or more major kinds of soil or miscellaneous areas. A map unit is identified and named according to the taxonomic classification of the dominant soils. Within a taxonomic class there are precisely defined limits for the properties of the soils. On the landscape, however, the soils are natural phenomena, and they have the characteristic variability of all natural phenomena. Thus, the range of some observed properties may extend beyond the limits defined for a taxonomic class. Areas of soils of a single taxonomic class rarely, if ever, can be mapped without including areas of other taxonomic classes. Consequently, every map unit is made up of the soils or miscellaneous areas for which it is named and some minor components that belong to taxonomic classes other than those of the major soils.

Most minor soils have properties similar to those of the dominant soil or soils in the map unit, and thus they do not affect use and management. These are called noncontrasting, or similar, components. They may or may not be mentioned in a particular map unit description. Other minor components, however, have properties and behavioral characteristics divergent enough to affect use or to require different management. These are called contrasting, or dissimilar, components. They generally are in small areas and could not be mapped separately because of the scale used. Some small areas of strongly contrasting soils or miscellaneous areas are identified by a special symbol on the maps. If included in the database for a given area, the contrasting minor components are identified in the map unit descriptions along with some characteristics of each. A few areas of minor components may not have been observed, and consequently they are not mentioned in the descriptions, especially where the pattern was so complex that it was impractical to make enough observations to identify all the soils and miscellaneous areas on the landscape.

The presence of minor components in a map unit in no way diminishes the usefulness or accuracy of the data. The objective of mapping is not to delineate pure taxonomic classes but rather to separate the landscape into landforms or landform segments that have similar use and management requirements. The

delineation of such segments on the map provides sufficient information for the development of resource plans. If intensive use of small areas is planned, however, onsite investigation is needed to define and locate the soils and miscellaneous areas.

An identifying symbol precedes the map unit name in the map unit descriptions. Each description includes general facts about the unit and gives important soil properties and qualities.

Soils that have profiles that are almost alike make up a *soil series*. Except for differences in texture of the surface layer, all the soils of a series have major horizons that are similar in composition, thickness, and arrangement.

Soils of one series can differ in texture of the surface layer, slope, stoniness, salinity, degree of erosion, and other characteristics that affect their use. On the basis of such differences, a soil series is divided into *soil phases*. Most of the areas shown on the detailed soil maps are phases of soil series. The name of a soil phase commonly indicates a feature that affects use or management. For example, Alpha silt loam, 0 to 2 percent slopes, is a phase of the Alpha series.

Some map units are made up of two or more major soils or miscellaneous areas. These map units are complexes, associations, or undifferentiated groups.

A *complex* consists of two or more soils or miscellaneous areas in such an intricate pattern or in such small areas that they cannot be shown separately on the maps. The pattern and proportion of the soils or miscellaneous areas are somewhat similar in all areas. Alpha-Beta complex, 0 to 6 percent slopes, is an example.

An *association* is made up of two or more geographically associated soils or miscellaneous areas that are shown as one unit on the maps. Because of present or anticipated uses of the map units in the survey area, it was not considered practical or necessary to map the soils or miscellaneous areas separately. The pattern and relative proportion of the soils or miscellaneous areas are somewhat similar. Alpha-Beta association, 0 to 2 percent slopes, is an example.

An *undifferentiated group* is made up of two or more soils or miscellaneous areas that could be mapped individually but are mapped as one unit because similar interpretations can be made for use and management. The pattern and proportion of the soils or miscellaneous areas in a mapped area are not uniform. An area can be made up of only one of the major soils or miscellaneous areas, or it can be made up of all of them. Alpha and Beta soils, 0 to 2 percent slopes, is an example.

Some surveys include *miscellaneous areas*. Such areas have little or no soil material and support little or no vegetation. Rock outcrop is an example.

Dutchess County, New York

BeC—Bernardston silt loam, 8 to 15 percent slopes

Map Unit Setting

National map unit symbol: 9rdn
Elevation: 0 to 1,000 feet
Mean annual precipitation: 41 to 47 inches
Mean annual air temperature: 45 to 50 degrees F
Frost-free period: 115 to 195 days
Farmland classification: Farmland of statewide importance

Map Unit Composition

Bernardston and similar soils: 80 percent
Minor components: 20 percent
Estimates are based on observations, descriptions, and transects of the mapunit.

Description of Bernardston

Setting

Landform: Till plains, hills, drumlinoid ridges
Landform position (two-dimensional): Shoulder
Landform position (three-dimensional): Crest
Down-slope shape: Convex
Across-slope shape: Convex
Parent material: Loamy, acid, dense till derived mainly from phyllite, shale, slate, and schist

Typical profile

H1 - 0 to 8 inches: silt loam
H2 - 8 to 27 inches: silt loam
H3 - 27 to 80 inches: silt loam

Properties and qualities

Slope: 8 to 15 percent
Depth to restrictive feature: 15 to 30 inches to densic material
Drainage class: Well drained
Capacity of the most limiting layer to transmit water (Ksat): Moderately low to moderately high (0.06 to 0.20 in/hr)
Depth to water table: About 18 to 24 inches
Frequency of flooding: None
Frequency of ponding: None
Available water supply, 0 to 60 inches: Low (about 4.8 inches)

Interpretive groups

Land capability classification (irrigated): None specified
Land capability classification (nonirrigated): 3e
Hydrologic Soil Group: C/D
Ecological site: F144AY007CT - Well Drained Dense Till Uplands
Hydric soil rating: No

Minor Components

Stockbridge

Percent of map unit: 5 percent
Hydric soil rating: No

Pittstown
Percent of map unit: 5 percent
Hydric soil rating: No

Punsit
Percent of map unit: 5 percent
Hydric soil rating: No

Unnamed soils, fine-loamy
Percent of map unit: 3 percent
Hydric soil rating: No

Sun
Percent of map unit: 1 percent
Landform: Depressions
Hydric soil rating: Yes

Canandaigua
Percent of map unit: 1 percent
Landform: Depressions
Hydric soil rating: Yes

DxB—Dutchess-Cardigan-Urban land complex, undulating, rocky

Map Unit Setting
National map unit symbol: 9rfr
Elevation: 20 to 1,000 feet
Mean annual precipitation: 41 to 47 inches
Mean annual air temperature: 45 to 50 degrees F
Frost-free period: 115 to 195 days
Farmland classification: Not prime farmland

Map Unit Composition
Dutchess and similar soils: 30 percent
Cardigan and similar soils: 25 percent
Urban land: 20 percent
Minor components: 25 percent
Estimates are based on observations, descriptions, and transects of the mapunit.

Description of Dutchess

Setting
Landform: Ridges, hills
Landform position (two-dimensional): Summit
Landform position (three-dimensional): Crest
Down-slope shape: Convex
Across-slope shape: Convex
Parent material: Loamy till derived mainly from phyllite, slate, schist, and shale

Typical profile
H1 - 0 to 8 inches: silt loam

H2 - 8 to 28 inches: silt loam
H3 - 28 to 86 inches: channery silt loam

Properties and qualities

Slope: 1 to 6 percent
Depth to restrictive feature: More than 80 inches
Drainage class: Well drained
Capacity of the most limiting layer to transmit water (Ksat): Moderately high to high (0.57 to 1.98 in/hr)
Depth to water table: More than 80 inches
Frequency of flooding: None
Frequency of ponding: None
Available water supply, 0 to 60 inches: High (about 9.6 inches)

Interpretive groups

Land capability classification (irrigated): None specified
Land capability classification (nonirrigated): 2e
Hydrologic Soil Group: B
Ecological site: F144AY034CT - Well Drained Till Uplands
Hydric soil rating: No

Description of Cardigan

Setting

Landform: Ridges, hills
Landform position (two-dimensional): Summit
Landform position (three-dimensional): Crest
Down-slope shape: Convex
Across-slope shape: Convex
Parent material: Loamy till or colluvium derived from phyllite, slate, shale, and schist

Typical profile

H1 - 0 to 8 inches: channery silt loam
H2 - 8 to 20 inches: channery loam
H3 - 20 to 30 inches: channery silt loam
H4 - 30 to 34 inches: unweathered bedrock

Properties and qualities

Slope: 1 to 6 percent
Depth to restrictive feature: 20 to 40 inches to lithic bedrock
Drainage class: Well drained
Capacity of the most limiting layer to transmit water (Ksat): Low to moderately low (0.00 to 0.06 in/hr)
Depth to water table: More than 80 inches
Frequency of flooding: None
Frequency of ponding: None
Available water supply, 0 to 60 inches: Low (about 4.1 inches)

Interpretive groups

Land capability classification (irrigated): None specified
Land capability classification (nonirrigated): 2e
Hydrologic Soil Group: C
Ecological site: F144AY034CT - Well Drained Till Uplands
Hydric soil rating: No

Description of Urban Land

Typical profile

H1 - 0 to 6 inches: variable

Interpretive groups

Land capability classification (irrigated): None specified
Land capability classification (nonirrigated): 8s
Hydric soil rating: Unranked

Minor Components

Udorthents

Percent of map unit: 10 percent
Hydric soil rating: No

Georgia

Percent of map unit: 5 percent
Hydric soil rating: No

Nassau

Percent of map unit: 5 percent
Hydric soil rating: No

Massena

Percent of map unit: 4 percent
Hydric soil rating: No

Sun

Percent of map unit: 1 percent
Landform: Depressions
Hydric soil rating: Yes

Soil Information for All Uses

Soil Reports

The Soil Reports section includes various formatted tabular and narrative reports (tables) containing data for each selected soil map unit and each component of each unit. No aggregation of data has occurred as is done in reports in the Soil Properties and Qualities and Suitabilities and Limitations sections.

The reports contain soil interpretive information as well as basic soil properties and qualities. A description of each report (table) is included.

Water Features

This folder contains tabular reports that present soil hydrology information. The reports (tables) include all selected map units and components for each map unit. Water Features include ponding frequency, flooding frequency, and depth to water table.

Hydrologic Soil Group and Surface Runoff (North Hamilton Parcel)

This table gives estimates of various soil water features. The estimates are used in land use planning that involves engineering considerations.

Hydrologic soil groups are based on estimates of runoff potential. Soils are assigned to one of four groups according to the rate of water infiltration when the soils are not protected by vegetation, are thoroughly wet, and receive precipitation from long-duration storms.

The four hydrologic soil groups are:

Group A. Soils having a high infiltration rate (low runoff potential) when thoroughly wet. These consist mainly of deep, well drained to excessively drained sands or gravelly sands. These soils have a high rate of water transmission.

Group B. Soils having a moderate infiltration rate when thoroughly wet. These consist chiefly of moderately deep or deep, moderately well drained or well drained soils that have moderately fine texture to moderately coarse texture. These soils have a moderate rate of water transmission.

Group C. Soils having a slow infiltration rate when thoroughly wet. These consist chiefly of soils having a layer that impedes the downward movement of water or soils of moderately fine texture or fine texture. These soils have a slow rate of water transmission.

Group D. Soils having a very slow infiltration rate (high runoff potential) when thoroughly wet. These consist chiefly of clays that have a high shrink-swell potential, soils that have a high water table, soils that have a claypan or clay layer at or near the surface, and soils that are shallow over nearly impervious material. These soils have a very slow rate of water transmission.

If a soil is assigned to a dual hydrologic group (A/D, B/D, or C/D), the first letter is for drained areas and the second is for undrained areas.

Surface runoff refers to the loss of water from an area by flow over the land surface. Surface runoff classes are based on slope, climate, and vegetative cover. The concept indicates relative runoff for very specific conditions. It is assumed that the surface of the soil is bare and that the retention of surface water resulting from irregularities in the ground surface is minimal. The classes are negligible, very low, low, medium, high, and very high.

Report—Hydrologic Soil Group and Surface Runoff (North Hamilton Parcel)

Absence of an entry indicates that the data were not estimated. The dash indicates no documented presence.

Hydrologic Soil Group and Surface Runoff–Dutchess County, New York			
Map symbol and soil name	**Pct. of map unit**	**Surface Runoff**	**Hydrologic Soil Group**
BeC—Bernardston silt loam, 8 to 15 percent slopes			
Bernardston	80	—	C/D
DxB—Dutchess-Cardigan-Urban land complex, undulating, rocky			
Dutchess	30	—	B
Cardigan	25	—	C
Urban land	20	—	—

References

American Association of State Highway and Transportation Officials (AASHTO). 2004. Standard specifications for transportation materials and methods of sampling and testing. 24th edition.

American Society for Testing and Materials (ASTM). 2005. Standard classification of soils for engineering purposes. ASTM Standard D2487-00.

Cowardin, L.M., V. Carter, F.C. Golet, and E.T. LaRoe. 1979. Classification of wetlands and deep-water habitats of the United States. U.S. Fish and Wildlife Service FWS/OBS-79/31.

Federal Register. July 13, 1994. Changes in hydric soils of the United States.

Federal Register. September 18, 2002. Hydric soils of the United States.

Hurt, G.W., and L.M. Vasilas, editors. Version 6.0, 2006. Field indicators of hydric soils in the United States.

National Research Council. 1995. Wetlands: Characteristics and boundaries.

Soil Survey Division Staff. 1993. Soil survey manual. Soil Conservation Service. U.S. Department of Agriculture Handbook 18. http://www.nrcs.usda.gov/wps/portal/nrcs/detail/national/soils/?cid=nrcs142p2_054262

Soil Survey Staff. 1999. Soil taxonomy: A basic system of soil classification for making and interpreting soil surveys. 2nd edition. Natural Resources Conservation Service, U.S. Department of Agriculture Handbook 436. http://www.nrcs.usda.gov/wps/portal/nrcs/detail/national/soils/?cid=nrcs142p2_053577

Soil Survey Staff. 2010. Keys to soil taxonomy. 11th edition. U.S. Department of Agriculture, Natural Resources Conservation Service. http://www.nrcs.usda.gov/wps/portal/nrcs/detail/national/soils/?cid=nrcs142p2_053580

Tiner, R.W., Jr. 1985. Wetlands of Delaware. U.S. Fish and Wildlife Service and Delaware Department of Natural Resources and Environmental Control, Wetlands Section.

United States Army Corps of Engineers, Environmental Laboratory. 1987. Corps of Engineers wetlands delineation manual. Waterways Experiment Station Technical Report Y-87-1.

United States Department of Agriculture, Natural Resources Conservation Service. National forestry manual. http://www.nrcs.usda.gov/wps/portal/nrcs/detail/soils/home/?cid=nrcs142p2_053374

United States Department of Agriculture, Natural Resources Conservation Service. National range and pasture handbook. http://www.nrcs.usda.gov/wps/portal/nrcs/detail/national/landuse/rangepasture/?cid=stelprdb1043084

United States Department of Agriculture, Natural Resources Conservation Service. National soil survey handbook, title 430-VI. http://www.nrcs.usda.gov/wps/portal/nrcs/detail/soils/scientists/?cid=nrcs142p2_054242

United States Department of Agriculture, Natural Resources Conservation Service. 2006. Land resource regions and major land resource areas of the United States, the Caribbean, and the Pacific Basin. U.S. Department of Agriculture Handbook 296. http://www.nrcs.usda.gov/wps/portal/nrcs/detail/national/soils/?cid=nrcs142p2_053624

United States Department of Agriculture, Soil Conservation Service. 1961. Land capability classification. U.S. Department of Agriculture Handbook 210. http://www.nrcs.usda.gov/Internet/FSE_DOCUMENTS/nrcs142p2_052290.pdf

APPENDIX D

DOCUMENTATION FOR NO IMPACT TO HISTORIC & CULTURAL RESOURCES

117 N HAMILTON
City of Poughkeepsie, Duchess County, New York
July 5, 2022

POUGHKEEPSIE NATURAL RESOURCE INVENTORY NARRATIVE

The project site, identified as 117 N Hamilton Street, is comprised of two existing lots of record: Tax Parcel No. 6162-63-266293, 0.43 acre and Tax Parcel No. 6162-63-271278, 1.20 acres. The two (2) existing lots are to be combined into one lot totaling 1.63 acres.

Geology and Soils

According to the Geology and Soils map, the site is underlain by Graywacke, shale bedrock. The site's surficial geology is of glacial till soils, specifically DxB-Dutchess-Cardigan (urban land complex) and BeC-Bernardston silt loam. The geology and surface soils are typical for the area and there are no unique geologic features on the site.

Water Resources

According to the Water Resources map, the front portion of the site lies within the Flood Hazard Area of the Fall Kill. The Fall Kill and its identified riparian buffer in this area are situated west of the former rail bed, which is located just south of the site. No aquatic resources are situated on or immediately adjacent the subject parcels.

Habitats

The sites which make up 117 North Hamilton are highly disturbed urban lots with no habitat of any significance. According to the NRI Habitat Map, much of the site, specifically the bulk of the larger parcel, is identified as waste ground. The rear portion of the same parcel is identified as upland hardwood forest; however, no trees are found in the bulk of this on-site designation. A number of trees will be removed, particularly along the easterly edge in the building footprint. Most of the trees at the rear of the sites nearest the North Clinton Street residential lots will be maintained. No specimen or high value trees exist on site.

Land Use

The NRI Land Use Map indicates the larger lot to be vacant and the smaller to be residential. Both appear to have been historically developed and now lie vacant. No structures exist on either parcel. The site is surrounded predominantly by mixed residential and commercial. The Dutchess County Jail facility lies east and northeast of the site and the former railbed, also identified as vacant land, forms the site's southern boundary.

Historic Resources

According to the NRI Historic Resources Map, the nearest historic sites are the Guilford Dudley Memorial at College Hill Park and St. Paul's Episcopal Church on Mansion Street. Both lie roughly 0.15 miles distant. The site is not located within or immediately adjacent to any historic districts, buildings, or archeological sites.

Recreational Resources

The site is situated several blocks (approximately 0.15 miles) distant the Malcolm X Park (southeast), Earline Patrice Park (south), and College Hill Park (northeast). The project will have no impact upon these resources. The site is also bound to the south by the former railbed. Improvement of the subject parcel would be beneficial with regard to development of the adjacent rail trail linear park.

Pollinator Pathway

According to the NRI Pollinator Pathway map, 117 North Hamilton Street is not located within any greenspace or any potential pathway. No pollinator gardens are in the immediate vicinity of the site nor are any potential future gardens in this area. The map shows pollinator pathways closely match the recreational resources in this area.

Poughkeepsie NRI Map - Historic Resources 117 North Hamilton Street



6/28/2022, 10:40:09 AM

Parcel Boundaries

Historic Sites (2021)

Local

City of Poughkeepsie Boundary

1:2,257

0 0.02 0.04 0.08 mi

0 0.03 0.07 0.13 km

Esri Community Maps Contributors, © OpenStreetMap, Microsoft, Esri, HERE, Garmin, SafeGraph, GeoTechnologies, Inc, METI/NASA, USGS, EPA, NPS, US Census Bureau, USDA, Sources: Esri, Airbus DS,

ArcGIS Web AppBuilder

Esri Community Maps Contributors, © OpenStreetMap, Microsoft, Esri, HERE, Garmin, SafeGraph, GeoTechnologies, Inc, METI/NASA, USGS, EPA, NPS, US Census Bureau, USDA |

APPENDIX E

WATER QUALITY TREATMENT

WATER QUALITY VOLUME (WQv)
POROUS PAVEMENT
UNDERGROUND INFILTRATION CHAMBERS

NORTH HAMILTON PARCEL, LLC
City of Poughkeepsie
21-786-01
2/16/20203

Water quality volume (WQv) for redevelopment

Per Chapter 9, Section 9.2.1.B.II, of NYS Stormwater Management Design Manual, January 2015

"The plan proposes that a minimum of 25% of the water quality volume (WQv) from the disturbed, impervious area is captured and treated by the implementation of standard SMP or reduced by application of green infrastructure techniques...If the construction project includes both new development and redevelopment activities, treatment would be required for 25% of the existing, disturbed impervious area, however, the stormwater management practices for the new development portion of the project must be designed in accordance with the sizing criteria in Chapter 4."

	(SF)	(Ac)
Site Area (Contributing Area) (ac)	70969	1.63
Existing Impervious Area	26237	0.60
Proposed Impervious Area	54491	1.25
Proposed NET NEW Impervious Area	28254	0.65

Treatment is required for 25% of the existing, disturbed impervious area plus 100% of the additional impervious area.

Existing Disturbed Impervious Area	26237	0.60
25% of Existing Disturbed Impervious Area	6559	0.15
100% of Proposed NET NEW Impervious Area	28254	0.65
Total Impervious Area to be Treated	34813	0.80

Post Re-development
Water Quality (WQv)
WQv = [(P)(Rv)(A)]/12
Rv=0.05+0.009(I)
I = impervious cover (%)
Min Rv = 0.2
P = 90% Rainfall Event Number (inch) = 1.4
A = site area (acres)

Impervious Area required to be treated (ac) = 34812.91

	A (ac)	Imp Area (ac)	I (%)	Rv	WQv (ac-ft)	WQv (ft^3)
	1.63	0.80	49.1	0.49	0.093	4069

The water quality volume treatment can be achieved through a combination of Runoff Reduction methods, standard practices and alternative/proprietary practices.

WQv Provided:

	WQv Provided (ft^3)		WQv Required (ft^3)
Porous Pavement	543		
Infiltration/StormTech	3888		
Total	4431	>	4069

Water Quality Volume Treatment requirements have been met.

NORTH HAMILTON PARCEL, LLC
City of Poughkeepsie
21-786-01
2/16/2023

Porous Pavement/Permeable Pavers/Grass Pave
Section 5.3.11 of NYS Stormwater Management Design Manual, January 2015

Ap = Vw/(n*dt)
where:

Ap = Area of porous pavement
Vw = Design Volume (ft^3): May include WQv and CPv from Contributing Area
n = porosity of gravel bed/reservoir (assume 0.4)
dt = depth of gravel bed/reservoir (Max of 4 ft, and seperated by at least 3' from water table)

Contributing Areas	Area (SF)	Area (Ac)
Porous Pavement Area	4900	0.11
Concrete Sidewalk	0	0.00
Lawn	0	0.00
Total	4900	0.11

Ap =	4900	SF
dt = depth of gravel bed =	1	ft

WQv treated = 1960 ft^3

Water Quality Volume for Porous Pavement subcatchment

A (ac)	Imp Area (ac)	I (%)	Rv	WQv (ac-ft)	WQv (ft^3)
0.11	0.11	100.0	0.95	0.012	543

WQv Provided by Porous Pavement		WQv Required for Porous Pavement subcatchment
1960 ft^3	>	543 ft^3

Additional treatment volume can be applied to CPv.

User Inputs

Chamber Model:	MC-3500
Outlet Control Structure:	Yes
Project Name:	North Hamilton
Engineer:	Julie Mangarillo
Project Location:	New York
Measurement Type:	Imperial
Required Storage Volume:	3600 cubic ft.
Stone Porosity:	40%
Stone Foundation Depth:	9 in.
Stone Above Chambers:	12 in.
Average Cover Over Chambers:	18 in.
Design Constraint Dimensions:	(25 ft. x 60 ft.)

Results

System Volume and Bed Size

Installed Storage Volume:	3888.85 cubic ft.
Storage Volume Per Chamber:	109.90 cubic ft.
Number Of Chambers Required:	18 3×6
Number Of End Caps Required:	6
Chamber Rows:	3
Maximum Length:	52.68 ft.
Maximum Width:	22.85 ft.
Approx. Bed Size Required:	1203.77 square ft.

System Components

Amount Of Stone Required:	169 cubic yards
Volume Of Excavation (Not Including Fill):	246 cubic yards
Total Non-woven Geotextile Required:	432 square yards
Woven Geotextile Required (excluding Isolator Row):	34 square yards
Woven Geotextile Required (Isolator Row):	55 square yards
Total Woven Geotextile Required:	88 square yards
Impervious Liner Required:	0 square yards



*MINIMUM COVER TO BOTTOM OF FLEXIBLE PAVEMENT. FOR UNPAVED INSTALLATIONS WHERE RUTTING FROM VEHICLES MAY OCCUR, INCREASE COVER TO 24"

APPENDIX F

SOIL RESTORATION

SECTION 5.1.6 "SOIL RESTORATION"
FROM:
NYS STORMWATER MANAGEMENT DESIGN MANUAL
(NYS SMDM) JANUARY 2015

(Not included at this time)

APPENDIX G

HYDROCAD REPORT

Project Notes

Rainfall events imported from "NRCS-Rain.txt" for 7040 NY Dutchess S

Rainfall Events Listing (selected events)

Event#	Event Name	Storm Type	Curve	Mode	Duration (hours)	B/B	Depth (inches)	AMC
1	1-Year	NRCC 24-hr	C	Default	24.00	1	2.64	2
2	10-Year	NRCC 24-hr	C	Default	24.00	1	4.71	2
3	100-Year	NRCC 24-hr	C	Default	24.00	1	8.32	2

Summary for Pond 3P: StormTech MC 3500

Inflow Area = 1.630 ac, 76.69% Impervious, Inflow Depth = 1.82" for 1-Year event
Inflow = 3.54 cfs @ 12.13 hrs, Volume= 0.248 af
Outflow = 3.14 cfs @ 12.16 hrs, Volume= 0.248 af, Atten= 11%, Lag= 2.1 min
Discarded = 0.13 cfs @ 10.65 hrs, Volume= 0.123 af
Primary = 3.01 cfs @ 12.16 hrs, Volume= 0.125 af

Routing by Stor-Ind method, Time Span= 1.00-30.00 hrs, dt= 0.05 hrs
Peak Elev= 1.39' @ 12.16 hrs Surf.Area= 0.025 ac Storage= 0.021 af

Plug-Flow detention time= 10.4 min calculated for 0.247 af (100% of inflow)
Center-of-Mass det. time= 10.4 min (822.6 - 812.1)

Volume	Invert	Avail.Storage	Storage Description
#1A	0.00'	0.037 af	**22.75'W x 48.72'L x 5.50'H Field A** 0.140 af Overall - 0.047 af Embedded = 0.092 af x 40.0% Voids
#2A	0.75'	0.047 af	**ADS_StormTech MC-3500 d +Cap** x 18 Inside #1 Effective Size= 70.4"W x 45.0"H => 15.33 sf x 7.17'L = 110.0 cf Overall Size= 77.0"W x 45.0"H x 7.50'L with 0.33' Overlap 18 Chambers in 3 Rows Cap Storage= 14.9 cf x 2 x 3 rows = 89.4 cf
		0.084 af	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Primary	0.50'	**15.0" Vert. Orifice/Grate** C= 0.600 Limited to weir flow at low heads
#2	Discarded	0.00'	**5.000 in/hr Exfiltration over Surface area**

Discarded OutFlow Max=0.13 cfs @ 10.65 hrs HW=0.06' (Free Discharge)
↑**2=Exfiltration** (Exfiltration Controls 0.13 cfs)

Primary OutFlow Max=2.93 cfs @ 12.16 hrs HW=1.38' (Free Discharge)
↑**1=Orifice/Grate** (Orifice Controls 2.93 cfs @ 3.19 fps)

Pond 3P: StormTech MC 3500 - Chamber Wizard Field A

Chamber Model = ADS_StormTech MC-3500 d +Cap (ADS StormTech® MC-3500 d rev 03/14 with Cap volume)
Effective Size= 70.4"W x 45.0"H => 15.33 sf x 7.17'L = 110.0 cf
Overall Size= 77.0"W x 45.0"H x 7.50'L with 0.33' Overlap
Cap Storage= 14.9 cf x 2 x 3 rows = 89.4 cf

77.0" Wide + 9.0" Spacing = 86.0" C-C Row Spacing

6 Chambers/Row x 7.17' Long +1.85' Cap Length x 2 = 46.72' Row Length +12.0" End Stone x 2 = 48.72' Base Length
3 Rows x 77.0" Wide + 9.0" Spacing x 2 + 12.0" Side Stone x 2 = 22.75' Base Width
9.0" Stone Base + 45.0" Chamber Height + 12.0" Stone Cover = 5.50' Field Height

18 Chambers x 110.0 cf + 14.9 cf Cap Volume x 2 x 3 Rows = 2,068.5 cf Chamber Storage

6,096.1 cf Field - 2,068.5 cf Chambers = 4,027.6 cf Stone x 40.0% Voids = 1,611.0 cf Stone Storage

Chamber Storage + Stone Storage = 3,679.6 cf = 0.084 af
Overall Storage Efficiency = 60.4%
Overall System Size = 48.72' x 22.75' x 5.50'

18 Chambers
225.8 cy Field
149.2 cy Stone



Pond 3P: StormTech MC 3500



Summary for Pond 3P: StormTech MC 3500

Inflow Area = 1.630 ac, 76.69% Impervious, Inflow Depth = 3.81" for 10-Year event
Inflow = 7.08 cfs @ 12.13 hrs, Volume= 0.517 af
Outflow = 5.99 cfs @ 12.17 hrs, Volume= 0.517 af, Atten= 15%, Lag= 2.5 min
Discarded = 0.13 cfs @ 8.55 hrs, Volume= 0.184 af
Primary = 5.86 cfs @ 12.17 hrs, Volume= 0.333 af

Routing by Stor-Ind method, Time Span= 1.00-30.00 hrs, dt= 0.05 hrs
Peak Elev= 2.11' @ 12.17 hrs Surf.Area= 0.025 ac Storage= 0.035 af

Plug-Flow detention time= 10.7 min calculated for 0.516 af (100% of inflow)
Center-of-Mass det. time= 10.7 min (800.2 - 789.5)

Volume	Invert	Avail.Storage	Storage Description
#1A	0.00'	0.037 af	**22.75'W x 48.72'L x 5.50'H Field A** 0.140 af Overall - 0.047 af Embedded = 0.092 af x 40.0% Voids
#2A	0.75'	0.047 af	**ADS_StormTech MC-3500 d +Cap** x 18 Inside #1 Effective Size= 70.4"W x 45.0"H => 15.33 sf x 7.17'L = 110.0 cf Overall Size= 77.0"W x 45.0"H x 7.50'L with 0.33' Overlap 18 Chambers in 3 Rows Cap Storage= 14.9 cf x 2 x 3 rows = 89.4 cf
		0.084 af	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Primary	0.50'	**15.0" Vert. Orifice/Grate** C= 0.600 Limited to weir flow at low heads
#2	Discarded	0.00'	**5.000 in/hr Exfiltration over Surface area**

Discarded OutFlow Max=0.13 cfs @ 8.55 hrs HW=0.06' (Free Discharge)
└**2=Exfiltration** (Exfiltration Controls 0.13 cfs)

Primary OutFlow Max=5.74 cfs @ 12.17 hrs HW=2.07' (Free Discharge)
└**1=Orifice/Grate** (Orifice Controls 5.74 cfs @ 4.68 fps)

Pond 3P: StormTech MC 3500 - Chamber Wizard Field A

Chamber Model = ADS_StormTech MC-3500 d +Cap (ADS StormTech® MC-3500 d rev 03/14 with Cap volume)
Effective Size= 70.4"W x 45.0"H => 15.33 sf x 7.17'L = 110.0 cf
Overall Size= 77.0"W x 45.0"H x 7.50'L with 0.33' Overlap
Cap Storage= 14.9 cf x 2 x 3 rows = 89.4 cf

77.0" Wide + 9.0" Spacing = 86.0" C-C Row Spacing

6 Chambers/Row x 7.17' Long +1.85' Cap Length x 2 = 46.72' Row Length +12.0" End Stone x 2 = 48.72' Base Length
3 Rows x 77.0" Wide + 9.0" Spacing x 2 + 12.0" Side Stone x 2 = 22.75' Base Width
9.0" Stone Base + 45.0" Chamber Height + 12.0" Stone Cover = 5.50' Field Height

18 Chambers x 110.0 cf + 14.9 cf Cap Volume x 2 x 3 Rows = 2,068.5 cf Chamber Storage

6,096.1 cf Field - 2,068.5 cf Chambers = 4,027.6 cf Stone x 40.0% Voids = 1,611.0 cf Stone Storage

Chamber Storage + Stone Storage = 3,679.6 cf = 0.084 af
Overall Storage Efficiency = 60.4%
Overall System Size = 48.72' x 22.75' x 5.50'

18 Chambers
225.8 cy Field
149.2 cy Stone



Pond 3P: StormTech MC 3500



Summary for Pond 3P: StormTech MC 3500

Inflow Area = 1.630 ac, 76.69% Impervious, Inflow Depth = 7.36" for 100-Year event
Inflow = 13.13 cfs @ 12.13 hrs, Volume= 1.000 af
Outflow = 10.34 cfs @ 12.18 hrs, Volume= 1.000 af, Atten= 21%, Lag= 3.3 min
Discarded = 0.13 cfs @ 5.45 hrs, Volume= 0.224 af
Primary = 10.21 cfs @ 12.18 hrs, Volume= 0.776 af

Routing by Stor-Ind method, Time Span= 1.00-30.00 hrs, dt= 0.05 hrs
Peak Elev= 4.11' @ 12.18 hrs Surf.Area= 0.025 ac Storage= 0.070 af

Plug-Flow detention time= 9.6 min calculated for 0.998 af (100% of inflow)
Center-of-Mass det. time= 9.7 min (780.9 - 771.2)

Volume	Invert	Avail.Storage	Storage Description
#1A	0.00'	0.037 af	**22.75'W x 48.72'L x 5.50'H Field A** 0.140 af Overall - 0.047 af Embedded = 0.092 af x 40.0% Voids
#2A	0.75'	0.047 af	**ADS_StormTech MC-3500 d +Cap** x 18 Inside #1 Effective Size= 70.4"W x 45.0"H => 15.33 sf x 7.17'L = 110.0 cf Overall Size= 77.0"W x 45.0"H x 7.50'L with 0.33' Overlap 18 Chambers in 3 Rows Cap Storage= 14.9 cf x 2 x 3 rows = 89.4 cf
		0.084 af	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Primary	0.50'	**15.0" Vert. Orifice/Grate** C= 0.600 Limited to weir flow at low heads
#2	Discarded	0.00'	**5.000 in/hr Exfiltration over Surface area**

Discarded OutFlow Max=0.13 cfs @ 5.45 hrs HW=0.06' (Free Discharge)
↑—**2=Exfiltration** (Exfiltration Controls 0.13 cfs)

Primary OutFlow Max=10.05 cfs @ 12.18 hrs HW=4.02' (Free Discharge)
↑—**1=Orifice/Grate** (Orifice Controls 10.05 cfs @ 8.19 fps)

Pond 3P: StormTech MC 3500 - Chamber Wizard Field A

Chamber Model = ADS_StormTech MC-3500 d +Cap (ADS StormTech® MC-3500 d rev 03/14 with Cap volume)
Effective Size= 70.4"W x 45.0"H => 15.33 sf x 7.17'L = 110.0 cf
Overall Size= 77.0"W x 45.0"H x 7.50'L with 0.33' Overlap
Cap Storage= 14.9 cf x 2 x 3 rows = 89.4 cf

77.0" Wide + 9.0" Spacing = 86.0" C-C Row Spacing

6 Chambers/Row x 7.17' Long +1.85' Cap Length x 2 = 46.72' Row Length +12.0" End Stone x 2 = 48.72' Base Length
3 Rows x 77.0" Wide + 9.0" Spacing x 2 + 12.0" Side Stone x 2 = 22.75' Base Width
9.0" Stone Base + 45.0" Chamber Height + 12.0" Stone Cover = 5.50' Field Height

18 Chambers x 110.0 cf + 14.9 cf Cap Volume x 2 x 3 Rows = 2,068.5 cf Chamber Storage

6,096.1 cf Field - 2,068.5 cf Chambers = 4,027.6 cf Stone x 40.0% Voids = 1,611.0 cf Stone Storage

Chamber Storage + Stone Storage = 3,679.6 cf = 0.084 af
Overall Storage Efficiency = 60.4%
Overall System Size = 48.72' x 22.75' x 5.50'

18 Chambers
225.8 cy Field
149.2 cy Stone



Pond 3P: StormTech MC 3500



APPENDIX H

SOIL STABILIZATION

TEMPORARY SEED MIX

VEGETATIVE MEASURES FOR EROSION AND SEDIMENT CONTROL

Erosion is the gradual wearing away of the land surface as a result of uncontrolled wind and water energy. Sedimentation is the result of transport and delivery of eroded soil particles, deposited at some point. Erosion and sediment control is a complex interaction of soils, engineering water management, agronomic and horticultural practices. Decisions for resolving erosion conditions, both on site and within the upper watershed, are formulated based on surface and subsurface water, soil material, climatic conditions, and anticipated land use. Creating a stable slope is necessary prior to vegetating. Sloughing and slumping are not helpful in establishing a uniform protective cover.

General planning considerations for vegetating a steep slope will include evaluating the soil. Factors such as soil texture and steepness affect the stability of the slope. Texture also influences the permeability and water holding capacity of the soil. Many slopes are stripped of topsoil during the construction phase, leaving an infertile, compacted soil surface, void of valuable organic matter. Topsoil must be reapplied. Overly compacted slopes should be decompacted with appropriate equipment. Soil pH and nutrient level are determined by obtaining a representative soil sample for analysis from an accredited lab. Appropriate plants are selected to meet the final slope and soil conditions for the site.

Liming material sold in New York varies considerably in several ways. The mineral content (calcium and magnesium) of the limestone may be high or low, the fineness or particle sizes vary between suppliers, and the cost varies greatly. Two types of limestone are sold. The most common is limestone high in calcium. Dolomitic limestone contains magnesium (Mg) and calcium (Ca). Limestone sold in NY varies from 0 to 20% Mg while the calcium content of lime varies from 14.7% to 51.5%. Particle size determines how rapidly the calcium and magnesium will react with the acid in the soil. The finer the particle sizes, the quicker the reaction.

When purchasing agricultural limestone, one should state on the order that the amount should be adjusted to 100% effective neutralizing value (ENV). This is the way to compare materials as it adjusts for the reactive Ca and Mg and the particle size. The ENV is stated as the ratio needed to convert a limestone recommendation to 100% ENV. Thus, if the recommendation is 4 tons/acre of 100% ENV lime and the lime being used had an 80% ENV (1/ENV = 1.25), 4 times 1.25 or 5 tons/acre would be required.

The amount of limestone needed can be estimated by using the table below. A soil test is the only way to determine the soil pH. This table is very general, but it is useful for planning.

General lime guidelines (at 100% ENV)

Initial Soil pH	*Sands*	*Sandy Loams*	*Loams and Silt Loams*	*Silty Clay Loams*
		T/A of lime[1]		
4.5	2.5	6.0	9.5	13.0
4.6-4.7	2.5	6.0	9.0	12.5
4.8-4.9	2.5	5.5	8.5	12.0
5.0-5.1	2.0	5.0	7.5	10.5
5.2-5.3	1.5	4.0	6.5	8.5
5.4-5.5	1.0	3.0	4.0	6.0
5.6-5.7	1.0	2.0	3.0	4.5
5.8-5.9	0.7	1.5	2.5	3.5
6.0-6.1	0.6	1.5	2.0	3.0
6.2-6.3	0.4	1.0	1.5	2.0
6.~6.5	0.3	0.7	1.0	1.5
6.6-6.7	0.2	0.5	0.7	1.0

Lime guidelines are in tons per acre and are based on a plow depth of 8.0 inches. Correct rate if plowing to a different depth.

REFERENCE: Cornell Cooperative Extension. 2003 Cornell Guide for Integrated Field Crop Management, Pg. 32.

Fertilizer is sold with an analysis printed on the tag or bag. The first number is the percent of nitrogen (N), the second is phosphorus (P), and the third is potassium (K). Other elements are sometimes included and are listed with these basic three components. For example, a forty pound bag of 5-10-5 contains 2 lbs. N, 4 lbs. P (as P_2O_5), and 2 lbs. of K (as K_20). Select an appropriate analysis to meet the nutrients required for the specific site. Always apply as closely as possible the required amount of fertilizer to meet the requirements of the site. Adding surplus nitrogen may cause pollution of drinking water and saltwater ecosystems. Excessive phosphorus may accelerate the aging process of freshwater ecosystems. Excessive amounts of N and K2O may result in 'burning' the grass and killing it.

Water management on and above potentially eroding sites is extremely important. Large watersheds above a site may require extensive water control measures. Water flow paths must be controlled to allow the safe delivery of the water to an outlet to the side or bottom of the slope. Shallow ditches or diversions across the slope and above the area to be seeded is an effective method of avoiding wash-out of the seed and soil. Diversions may be constructed at a point where surface runoff water is intercepted and carried away from the slope and to a safe outlet. On large slopes,

benching may be necessary for bench drains or future maintenance (see standard for Land Grading). Subsurface drainage is frequently included to prevent long term saturated soil conditions and sloughing.

Conservation plantings need to effectively hold soil and control erosion, and they should enhance and blend with their surroundings. Mature plant size, form, and appearance must be considered along with their functionality to match the anticipated land use. Basic erosion control is accomplished by providing cover to the soil surface utilizing plants and/or mulch. It is the system of seedbed preparation, soil amendments, plant selection, proper timing of planting, and mulching that will optimize the chances of success. Characteristics of grasses such as low growth, horizontal above and below ground stems, leafy growth, and many fine roots for binding soil particles, make them the primary choice for vegetating slopes. Once the grass type is selected, then appropriate forbs, shrubs, or trees may be added to meet site conditions. The use of appropriate mulches will depend on site criteria and should be carefully evaluated. Although some materials are costly, they may prevent the need for more costly reshaping and reseeding.

Selection of proper vegetative materials for site stabilization is critical for environmental success. Species should be selected that are not considered "invasive." A primary list of invasive plants can be found at the website of the Invasive Plant Council of New York State (http://www.ipcnys.org). Any species not on this list but considered suspect should be verified at the appropriate regional or local level for acceptance.

STANDARD AND SPECIFICATIONS FOR TEMPORARY CRITICAL AREA PLANTINGS

Definition

Providing erosion control protection to a critical area for an interim period. A critical area is any disturbed, denuded slope subject to erosion.

Purpose

To provide temporary erosion and sediment control. Temporary control is achieved by covering all bare ground areas that exist as a result of construction or a natural event.

Conditions Where Practice Applies

Temporary seedings may be necessary on construction sites to protect an area, or section, where final grading is complete, when preparing for winter work shutdown, or to provide cover when permanent seedings are likely to fail due to mid-summer heat and drought. The intent is to provide temporary protective cover during temporary shutdown of construction and/or while waiting for optimal planting time.

Criteria

Water management practices must be installed as appropriate for site conditions. The area must be rough graded and slopes physically stable. Large debris and rocks are usually removed. Seedbed must be seeded within 24 hours of disturbance or scarification of the soil surface will be necessary prior to seeding.

Fertilizer or lime are not typically used for temporary seedings.

IF: Spring or summer or early fall, then seed the area with ryegrass (annual or perennial) at 30 lbs. per acre (Approximately 0.7 lb./1000 sq. ft. or use 1 lb./1000 sq. ft.).
IF: Late fall or early winter, then seed Certified 'Aroostook' winter rye (cereal rye) at 100 lbs. per acre (2.5 lbs./1000 sq. ft.).

Any seeding method may be used that will provide uniform application of seed to the area and result in relatively good soil to seed contact.

Mulch the area with hay or straw at 2 tons/acre (approx. 90 lbs./1000 sq. ft. or 2 bales). Quality of hay or straw mulch allowable will be determined based on long term use and visual concerns. Mulch anchoring will be required where wind or areas of concentrated water are of concern. Wood fiber hydromulch or other sprayable products approved for erosion control (nylon web or mesh) may be used if applied according to manufacturers' specification. Caution is advised when using nylon or other synthetic products. They may be difficult to remove prior to final seeding.

STANDARD AND SPECIFICATIONS FOR PERMANENT CRITICAL AREA PLANTINGS

Definition

Establishing grasses with other forbs and/or shrubs to provide perennial vegetative cover on disturbed, denuded, slopes subject to erosion.

Purpose

To reduce erosion and sediment transport.

Conditions Where Practice Applies

This practice applies to all disturbed areas void of, or having insufficient, cover to prevent erosion and sediment transport. See additional standards for special situations such as sand dunes and sand and gravel pits.

Criteria

All water control measures will be installed as needed prior to final grading and seedbed preparation. Any severely compacted sections will require chiseling or disking to provide an adequate rooting zone, to a minimum depth of 12". The seedbed must be prepared to allow good soil to seed contact, with the soil not too soft and not too compact. Adequate soil moisture must be present to accomplish this. If surface is powder dry or sticky wet, postpone operations until moisture changes to a favorable condition. If seeding is accomplished within 24 hours of final grading, additional scarification is generally not needed, especially on ditch or stream banks. Remove all stones and other debris from the surface that are greater than 4 inches, or that will interfere with future mowing or maintenance.

Soil amendments should be incorporated into the upper 2 inches of soil when feasible. **The soil should be tested to determine the amounts of amendments needed.** Apply ground agricultural limestone to attain a pH of 6.0 in the upper 2 inches of soil. If soil must be fertilized before results of a soil test can be obtained to determine fertilizer needs, apply commercial fertilizer at 600 lbs. per acre of 5-10-10 or equivalent. If manure is used, apply a quantity to meet the nutrients of the above fertilizer. This requires an appropriate manure analysis prior to applying to the site. Do not use manure on sites to be planted with birdsfoot trefoil or in the path of concentrated water flow.

Seed mixtures may vary depending on location within the state and time of seeding. Generally, warm season grasses should only be seeded during early spring, April to May. These grasses are primarily used for vegetating excessively drained sands and gravels. See Standard and Specification for Sand and Gravel Mine Reclamation. Other grasses may be seeded any time of the year when the soil is not frozen and is workable. When legumes such as birdsfoot trefoil are included, spring seedings are preferred. See Table 3.1 "Permanent Critical Area Planting Mixture Recommendations" for additional seed mixtures.

General Seed Mix:
[1] add inoculant immediately prior to seeding

	Variety	lbs./acre	lbs/1000 sq. ft.
Birdsfoot trefoil[1] OR	Empire/Pardee	8[2]	0.20
Common white clover[1]	Common	8	0.20
PLUS			
Tall fescue	KY-31/Rebel	20	0.45
PLUS			
Redtop OR	Common	2	0.05
Ryegrass (perennial)	Pennfine/Linn	5	0.10

[2] Mix 4 lbs each of Empire and Pardee OR 4 lbs of Birdsfoot and 4 lbs white clover per acre.

Time of Seeding: The optimum timing for the general seed mixture is early spring. Permanent seedings may be made any time of year if properly mulched and adequate moisture is provided. Late June through early August is not a good time to seed, but may facilitate covering the land without additional disturbance if construction is completed. Portions of the seeding may fail due to drought and heat. These areas may need reseeding in late summer/fall or the following spring.

Method of seeding: Broadcasting, drilling, cultipack type

seeding, or hydroseeding are acceptable methods. Proper soil to seed contact is key to successful seedings.

Mulching: Mulching is essential to obtain a uniform stand of seeded plants. Optimum benefits of mulching new seedings are obtained with the use of small grain straw applied at a rate of 2 tons per acre, and anchored with a netting or tackifier. See the mulch standard and specification for choices and requirements.

Irrigation: Watering may be essential to establish a new seeding when a drought condition occurs shortly after a new seeding emerges. Irrigation is a specialized practice and care must be taken not to exceed the application rate for the soil or subsoil. When disconnecting irrigation pipe, be sure pipes are drained in a safe manor, not creating an erosion concern.

Table 3.1
Permanent Critical Area Planting Mixture Recommendations

Seed mixture	Variety	Rate in lbs. per acre	Rate in lbs. Per 1000 sq. ft.
Mix #1			
Creeping red fescue	Ensylva, Pennlawn, Boreal	10	.25
Perennial ryegrass	Pennfine, Linn	10	.25

*This mix is used extensively for shaded areas.

Mix #2			
Switchgrass	Shelter, Pathfinder, Trailblazer, or Blackwell	20	.5

*This rate is in pure live seed, this would be an excellent choice along the upland edge of a wetland to filter runoff and provide wildlife benefits. In areas where erosion may be a problem, a companion seeding of sand lovegrass should be added to provide quick cover at a rate of 2 lbs. per acre (0.05 lbs. per 1000 sq. ft.).

Mix #3			
Switchgrass	Shelter, Pathfinder, Trailblazer, or Blackwell	4	.1
Big bluestem	Niagara	4	.1
Little bluestem	Aldous or Camper	2	.05
Indiangrass	Rumsey	4	.1
Coastal panicgrass	Atlantic	2	.05
Sideoats grama	El Reno or Trailway	2	.05
Wildflower mix		.5	.01

*This mix has been successful on sand and gravel plantings. It is very difficult to seed without a warm season grass seeder such as a Truax seed drill. Broadcasting this seed is very difficult due to the fluffy nature of some of the seed, such as bluestems and indiangrass.

Mix #4			
Switchgrass	Shelter, Pathfinder Trailblazer, or Blackwell	10	.25
Coastal panicgrass	Atlantic	10	.25

*This mix is salt tolerant, a good choice along the upland edge of tidal areas and roadsides.

Mix #5

Saltmeadow cordgrass (Spartina patens)—This grass is used for tidal shoreline protection and tidal marsh restoration. It is planted by vegetative stem divisions.

'Cape' American beachgrass can be planted for sand dune stabilization above the saltmeadow cordgrass zone.

Mix #6			
Creeping red fescue	Ensylva, Pennlawn, Boreal	20	.45
Tall fescue	KY 31, Rebel	20	.45
Perennial ryegrass	Pennfine, Linn	5	.10
Birdsfoot trefoil	Empire, Pardee	10	.45

*General purpose erosion control mix. Not to be used for a turf planting or play grounds.

APPENDIX I

NYS DEC SPILL REPORTING AND INITIAL NOTIFICATION REQUIREMENTS

(Not included at this time)

APPENDIX J

CONSTRUCTION SITE LOG BOOK

TABLE OF CONTENTS

SAMPLE FORMS

- CONTRACTOR CERTIFICATION FORM
- SAMPLE EROSION & SEDIMENT CONTROL INSPECTION REPORT

CONSTRUCTION SITE LOG BOOK

TABLE OF CONTENTS

1.0 NYS DEC SPDES General Permit for Stormwater Discharges from Construction Activity Permit No. GP-0-20-001

2.0 Notice of Intent (NOI)

3.0 MS4 Stormwater Pollution Prevention Plan Acceptance Form

4.0 Letter of Acknowledgment from NYS DEC

5.0 SWPPP

5.1 SWPPP Updates or Modifications

6.0 Contractor Certification Forms

7.0 Inspection Reports

Contractor's Certification
Stormwater Pollution Prevention Plan

As required by the SPDES General Permit for Stormwater Discharges from Construction Activity, GP-0-20-001, the "owner or operator must identify the contractor(s) and subcontractor(s) that will be responsible for installing, constructing, repairing, replacing, inspecting and maintaining the erosion and sediment control practices included in the SWPPP; and the contractor(s) and subcontractor(s) that will be responsible for constructing the post-construction stormwater management practices included in the SWPPP." Furthermore, the "owner or operator shall ensure that at least one trained contractor* is on site on a daily basis when soil disturbance activities are being performed." (GP-0-20-001 Part III.A.6). All certifications must be maintained with the SWPPP at the construction site.

Certification:

(Note: Certification requirements in Part III.A.6 of the NYSDEC SPDES General Permit GP-0-20-001)

"I hereby certify under penalty of law that I understand and agree to comply with the terms and conditions of the SWPPP and agree to implement any corrective actions identified by the qualified inspector during a site inspection. I also understand that the owner or operator must comply with the terms and conditions of the most current version of the New York State Pollutant Discharge Elimination System ("SPDES") general permit for stormwater discharges from construction activities and that it is unlawful for any person to cause or contribute to a violation of water quality standards. Furthermore, I am aware that there are significant penalties for submitting false information, that I do not believe to be true, including the possibility of fine and imprisonment for knowing violations."

Project Name: _____

Project Location: _____

Owner/Operator Name: _____

Owner/Operator Address: _____

NYSDEC PIN: NYR _____

Contractor: _____

Business Name: _____

Business Address: _____

Telephone No.: _____

Signature: _____

Name of Signatory: _____

Title of Signatory: _____

Date: _____

Contractor's Responsibility: _____

_____

_____

Trained Contractor Name: _____

Trained Contractor Title: _____

Stormwater Training
Certificate #: _____

Signatory Requirements: (Part VII.H.1 of the NYSDEC SPDES General Permit GP-0-20-001)
All NOIs, NOTs, certifications or information required by this permit or submitted pursuant to this permit, shall be signed as follows:

a. For a corporation: by (1) a president, secretary, treasurer, or vice-president of the corporation in charge of a principal business function, or any other person who performs similar policy or decision-making functions for the corporation; or (2) the manager of one or more manufacturing, production or operating facilities, provided the manager is authorized to make management decisions which govern the operation of the regulated facility including having the explicit or implicit duty of making major capital investment recommendations, and initiating and directing other comprehensive measures to assure long term environmental compliance with environmental laws and regulations; the manager can ensure that the necessary systems are established or actions taken to gather complete and accurate information for permit applications requirements; and where authority to sign documents has been assigned or delegated to the manager in accordance with corporate procedures;
b. For a partnership or sole proprietorship these forms shall be signed by a general partner or the proprietor, respectively; or
c. For a municipality, State, Federal, or other public agency these forms shall be signed by either a principal executive officer or ranking elected official. For purposes of this section, a principal executive officer of a Federal agency includes (1) the chief executive officer of the agency, or (2) a senior executive officer having responsibility for the overall operations of a principal geographic unit of the agency (e.g., Regional Administrators of EPA).

ROHDE, SOYKA & ANDREWS
Consulting Engineers, P.C.

40 Garden Street
Poughkeepsie, NY 12601
Phone: (845) 452-7515 Fax: (845) 452-8335
E-Mail Address: *info@rsaengrs.com*

STORMWATER MANAGEMENT AND EROSION CONTROL FACILITIES INSPECTION REPORT

BY: _____ DATE: _____

PROJECT: 117 North Hamilton JOB NO.: _____

CONTRACTOR Construction Manager: Site Contractor: _____

NYSDEC PERMIT IDENTIFICATION NUMBER _____ MUNCIPALITY City of Poughkeepsie

PRESENT AT SITE: _____ _____

_____ _____

_____ _____

WEATHER _____ TEMP _____ @ _____ AM _____ PM

SOIL MOISTURE CONDITIONS: DRY MOIST SATURATED FROZEN

INSPECTION TYPE: √ WEEKLY _____ OTHER

This is to document a field visit conducted by me on the date indicated above. The following was noted:

WORK IN PROCESS:
Attach a sketch showing disturbed areas at time of inspection and areas that have been stabilized since the last inspection.

INSPECTION ITEMS	Good	Fair	Poor	Comment
1. Silt Fence Condition				
2. Temp Chain Link Fence				
3. Catchbasin Inlet Protection				
4. Stabilized Constr Ent				
5. Stabilized Constr Ent				
7. Dust Control				
8. Discharge Points from Site				
9.				
10.				

REQUIRED ACTIONS/MAINTENANCE REQUIRED:

-

COMMENTS/OBSERVATIONS:

-

_____

QUALIFIED INSPECTOR*

PAGE 1 OF 1

cc: Owner, via e-mail
Construction Manager, via e-mail
Site Contractor, via email
City of Poughkeepsie representative, via e-mail

*According to GP-0-20-001

See reverse for additional comments/requirements

FOLLOW-UP FROM LAST REPORT:

- I

REQUIRED ACTIONS/MAINTENANCE REQUIRED; CONTINUED:

-

COMMENTS/OBSERVATIONS; CONTINUED:

-

11" X 17" REDUCED SIZE DRAWINGS

NOT TO SCALE



1 / C100 EXISTING CONDITIONS
1" = 20'

BUILDING PARCELS

TAX PARCEL NOS.	6162-03-290263, 271278
ACREAGE	0.43 AC / 1.20 AC - TOTAL COMBINED 1.63 AC
OWNER	117 N Hamilton, LLC , North Hamilton Parcel, LLC
APPLICANT	BAXTER DEVELOPMENT CORP
WATER DISTRICT =	CITY OF POUGHKEEPSIE WATER SERVICE AREA
SEWER DISTRICT =	CITY OF POUGHKEEPSIE
SCHOOL DISTRICT =	POUGHKEEPSIE CITY SCHOOL DISTRICT
FIRE DISTRICT =	CITY OF POUGHKEEPSIE FIRE DEPTMENT
ZONING DISTRICT(S) =	I-1 - LIGHT INDUSTRIAL DISTRICT
FLOOD ZONE =	ZONE A - NO BASE FLOOD ELEVATION (FIRM MAP NO. 36027C0356E)

LOT DATA TABLE - LIGHT INDUSTRIAL DISTRICT (I-1)

	LOT AREA (SF)	LOT WIDTH (FT)	LOT FRONTAGE (FT)	FRONT SETBACK (FT)	SIDE SETBACK (FT) EACH (FT)	SIDE SETBACK (FT) TOTAL (FT)	REAR SETBACK (FT)	MAX BLDG HGT (FT)	LOT COVERAGE (%)	FLOOR AREA RATIO
REQUIRED	NONE		50	20	10	20	25		60	1.0
PROVIDED (OVERALL)	71,003	212	206						28.9	0.33
WAREHOUSE 1		212	206	20	38/41	79	98	32	17.0	0.22
WAREHOUSE 2		212	206	218	10/33.8	43.8	25	32	11.9	0.11

PARKING : USE - WHOLESALE BUSINESSES, WAREHOUSES BUILDING, PLUMBING AND ELECTRICAL CONTRACTORS INCLUDING STORAGE RELATED THERETO.

BEST FIT PARKING CATEGORY - INDUSTRIAL AND HEAVY COMMERCIAL USES

- WHOLESALE, STORAGE AND WAREHOUSING - 1 SPACE FOR EACH 1000 SQUARE FEET OF GROSS FLOOR AREA OR 1 SPACE PER EMPLOYEE ON THE LARGEST SHIFT, WHICHEVER IS GREATER
- TOTAL GROSS SQUARE FEET, ALL BUILDINGS - 25432 SF - 23.4 SAY 24 SPACES REQUIRED
- MAX EMPLOYEES (7 INDIVIDUAL UNITS - 3 EMPLOYEES EACH) - 21 SPACES

1A / G-1 VICINITY MAP
SCALE: 1" = 150'
(DUTCHESS COUNTY PARCEL ACCESS)

ADJACENT PROPERY OWNERS

PARCEL NO.	PARCEL ADDRESS	OWNER NAME	OWNER ADDRESS	TOWN	ST	ZIP
6162-63-290274	112 N. Clinton St	Senon Antonio Galvan	112 N. Clinton St	Poughkeepsie	NY	12601
6162-63-288281	114 N. Clinton St	Senon Antonio Galvan	112 N. Clinton St	Poughkeepsie	NY	12601
6162-63-286286	118 N. Clinton St	Christine McNair	118 N. Clinton St	Poughkeepsie	NY	12601
6162-62-233288	N. Hamilton St	County of Dutchess	22 Market St	Poughkeepsie	NY	12601
6162-62-247285	N. Hamilton St	Highway Displays	404 Maple St	Poughkeepsie	NY	12601
6162-62-238330	150 N. Hamilton St	Dutchess County	22 Market St	Poughkeepsie	NY	12601
6162-63-322264	103 N. Clinton St	Carl J. Grabata, Jr.	533 Salt Point Tpke	Poughkeepsie	NY	12601
6162-63-308267	N. Clinton St	Mary Williams	533 Salt Point Tpke	Poughkeepsie	NY	12601
6162-63-309270	107 N. Clinton St	Hudson River Housing	313 Mill St	Poughkeepsie	NY	12601
6162-63-287290	122 N. Clinton St	Aurelio Cruz	122 N. Clinton St	Poughkeepsie	NY	12601
6162-63-288295	N. Clinton St	Aurelio Cruz	122 N. Clinton St	Poughkeepsie	NY	12601
6162-63-267298	119 N. Hamilton St	William Hockler	2139 New Hackensack Rd	Poughkeepsie	NY	12603

LEGEND

- EX. FLOOD ZONE LIMIT
- EX. PROPERTY LINE
- EX. ADJACENT PROPERTY LINE
- EX. MINOR CONTOUR
- 190 EX. MAJOR CONTOUR
- EX. RETAINING WALL
- EX. FENCE
- EX. ASPHALT LIMIT
- EX. GRAVEL LIMIT
- EX. CONCRETE LIMIT
- EX. CONCRETE CURB
- UTP SW EX. OVERHEAD WIRES WITH UTILITY POLE
- SMH EX. SANITARY SEWER LINE & MANHOLE
- DMH EX. STORMWATER LINE & DRAINAGE MANHOLE
- G EX. GAS LINE WITH GAS VALVE
- LTP EX. LIGHT POLE
- MB EX. MAILBOX
- HYD EX. HYDRANT
- CB EX. CATCH BASIN
- SIGN EX. SIGN

CITY PLANNING BOARD
CITY OF POUGHKEEPSIE, NEW YORK
SITE PLAN APPROVAL
FILE NO.
PROJECT NAME:
PROJECT LOCATION:
APPLICANT:
OFFICIALLY APPROVED at the Planning Board meeting held the ____ day of _____, 2___
PLANNING CHAIR:
DESIGNEE:
DATE SIGNED:
CONDITION(S):

Fire Chief

Police Chief

Building Inspector

City Engineer

Commissioner of Public Works

SURVEY NOTE:
BASE MAP TAKEN FROM BOUNDARY AND TOPOGRAPHIC SURVEY BY JOHNSON SURVEYING. FIELD SURVEY COMPLETED ON OCT. 30, 2020. BEARINGS AND NORTH ARROW SHOWN ARE REFERENCED TO NAD 83 - NY EAST USING NYSNET RTN GPS. CONTOUR INTERVAL IS ONE FOOT. ELEVATIONS SHOWN ARE REFERENCED TO NAVD 88 USING NYSNET RTN GPS.

LIST OF DRAWINGS:

SHEET NO.	DRAWING NO.	TITLE
1	C100	EXISTING CONDITIONS & NOTES
2	C101	SITE PLAN
3	C102	GRADING PLAN
4	C103	UTILITY PLAN
5	C104	EROSION CONTROL PLAN
6	C105	TRUCK TURNING PLAN
7	C500	DETAILS #1
8	C501	DETAILS #2
9	C502	ESC DETAILS
10	C503	LANDSCAPING PLAN

FIRE DEPARTMENT NOTES

1. LOCATION OF KNOX BOX ENTRY SYSTEM WILL BE PROVIDED BY THE APPLICANT WITH A QUANTITY AND LOCATION APPROVED BY THE FIRE OFFICIAL. A MASTER KEY SYSTEM SHALL BE PROVIDED AND KEYS SUPPLIED ON COMPLETION OF CONSTRUCTION.
2. IF A STANDPIPE/SPRINKLER SYSYEM IS REQUIRED, THE LOCATION OF THE FIRE DEPARTMENT CONNECTION SHALL BE NOTED, AND VERIFICATION THAT THE EXISTING WATER SUPPLY CAN MEET THE SYSTEM DEMAND PROVIDED.
3. AN APPROVED RAPID ENTRY SYSTEM SHALL BE INSTALLED TO OPEN AY GATES.
4. IF A FIRE ALARM SYSTEM IS REQUIRED, THE LOCATION OF THE ANNUNCIATOR PANEL SHALL BE NOTED ON THE CONSTRUCTION DRAWING AT THE LOCATION APPROVED BY THE FIRE OFFICIAL.
5. 911 ADDRESS TO BE NOTED ON FAÇADE, A MINIMUM OF 6" IN HEIGHT IN CONTRASTING COLORS.

NO.	DATE	REVISION	BY
2	9/2/22	PER COMMENTS / SITE CHANGE	JVA
1	5/31/22	PER COMMENTS	JVA

NORTH ARROW

• Alteration of this drawing except by a licensed Professional Engineer or Architect, is illegal. Any alteration by a Professional Engineer or Architect is to be embossed with their signature and date of alteration.
• The name of this drawing shall verify all dimensions shown on this drawing before proceeding with any work.
• This bar is one inch long

DRAWN BY: KMC
CHECKED BY: JVA
DATE: JUNE 2021
SCALE: 1" = 20'

ROHDE, SOYKA & ANDREWS
Consulting Engineers, PC
400 Gardnertown Road, Poughkeepsie, N.Y. 12601
Phone: (845) 452-8555
Fax: (845) 452-8556

NORTH HAMILTON PARCEL, LLC
NORTH HAMILTON STREET
CITY OF POUGHKEEPSIE
DUTCHESS COUNTY, NEW YORK

EXISTING CONDITIONS & NOTES

PROJECT NUMBER: 21-786-01

DRAWING NUMBER: C100
1 OF 10



1 / C101 SITE PLAN 1" = 20'

NO	DATE	REVISION	BY
5	2/28/22	Misc Additions for SWPPP	JVA
4	9/2/22	PER COMMENTS/ SITE CHANGE	JVA
3	7/22/22	PER COMMENTS	JVA
2	7/5/22	PER COMMENTS	JVA
1	6/3/22	PER COMMENTS	JVA

NORTH ARROW

• Acceptance of this drawing, except by a Licensed Professional Engineer or Architect, shall constitute an agreement to indemnify Rhodes, Soyka & Andrews, Professional Engineers, P.C. from all claims, damages, losses and expenses, including attorney's fees, arising out of or resulting from the use of this drawing.
• The user of this drawing shall verify all dimensions shown thereon and the size of line drawing.
• This item is not valid unless sealed.

DRAWN BY: KMC
CHECKED BY: JVA
DATE: JULY 22 2022
SCALE: 1" = 20'

ROHDE, SOYKA & ANDREWS
Professional Engineers, P.C.
Consulting Engineers P.C.
40 Garden Street Poughkeepsie, N.Y. 12601
(845) 452-1510
Fax (845) 452-0689

117 NORTH HAMILTON
NORTH HAMILTON STREET
CITY OF POUGHKEEPSIE
DUTCHESS COUNTY, NEW YORK

SITE PLAN

PROJECT NUMBER: 21-786-01

DRAWING NUMBER: C101
2 OF 10



1 C102 GRADING PLAN 1" = 20'

NO.	DATE	REVISION	BY
2	9/0/22	PER COMMENTS/ SITE CHANGE	JVA
1	5/0/22	PER COMMENTS	JVA

NORTH ARROW

* Alteration of this drawing except by a Licensed Professional Engineer or architect is illegal and a violation of law. Drawings marked with a red seal and signature are original documents and shall not be altered.
* The user of this drawing shall verify all dimensions shown. The user shall report any discrepancies to the engineer.
* This line is one inch long ▬

DRAWN BY: KMC
CHECKED BY: JVA
DATE: MARCH 2022
SCALE: 1" = 20'

ROHDE, SOYKA & ANDREWS
Consulting Engineers PC
45 Garden Street Poughkeepsie, N.Y. 12601
(845) 452-2535
Fax: (845) 452-2538

117 NORTH HAMILTON
NORTH HAMILTON STREET
CITY OF POUGHKEEPSIE
DUTCHESS COUNTY, NEW YORK

GRADING PLAN

PROJECT NUMBER: 21-786-01

DRAWING NUMBER: C102
3 OF 10



1 C103 UTILITY PLAN 1" = 20'

NO.	DATE	REVISION	BY
2	12/28/22	Misc Additions for SWPPP	JVA
1	5/5/22	PER COMMENTS	JVA

NORTH ARROW

* Alteration of this drawing, except by a Licensed Professional Engineer or architect acting under his/her direction, is prohibited and "each" his/her seal.
* The user of this drawing shall verify all dimensions shown hereon and the area of the drawing.
* This item is not item XYZ

DRAWN BY: KMC
CHECKED BY: JVA
DATE: MARCH 2022
SCALE: 1" = 20'

ROHDE, SOYKA & ANDREWS
Consulting Engineers PC
40 Garden Street Poughkeepsie, NY 12601
(845) 452-7825
Fax (845) 452-7826

117 NORTH HAMILTON
NORTH HAMILTON STREET
CITY OF POUGHKEEPSIE
DUTCHESS COUNTY, NEW YORK

UTILITY PLAN

PROJECT NUMBER: 21-706-01

DRAWING NUMBER: C103
4 OF 10



SURVEY NOTE:
BASE MAP TAKEN FROM BOUNDARY & TOPOGRAPHIC SURVEY BY JOHNSON SURVEYING. FIELD SURVEY COMPLETED ON OCT. 30, 2020. BEARINGS & NORTH ARROW SHOWN ARE REFERENCED TO NAD 83 -NY EAST USING NYSNET RTN GPS. CONTOUR INTERVAL IS ONE FOOT. ELEVATIONS SHOWN ARE REFERENCED TO NAVD 88 USING NYSNET RTN GPS

1 / C104 EROSION CONTROL PLAN
1" = 20'

LEGEND

- EX. FLOOD ZONE LIMIT
- EX. PROPERTY LINE
- EX. ADJACENT PROPERTY LINE
- EX. MINOR CONTOUR
- EX. MAJOR CONTOUR
- EX. RETAINING WALL
- EX. FENCE
- EX. ASPHALT LIMIT
- EX. GRAVEL LIMIT
- EX. CONCRETE LIMIT
- EX. CONCRETE CURB
- EX. OVERHEAD WIRES WITH UTILITY POLE
- EX. SANITARY SEWER LINE & MANHOLE
- EX. STORMWATER LINE & DRAINAGE MANHOLE
- EX. GAS LINE WITH GAS VALVE
- EX. WATER LINE
- EX. LIGHT POLE
- EX. MAILBOX
- EX. HYDRANT
- EX. CATCH BASIN
- EX. SIGN
- SILTSOXX (TM)
- SILT FENCE
- SOIL STOCKPILE
- 15' WIDE X 50' LONG STABILIZED CONSTRUCTION ENTRANCE



NOTES: 1. CHOKER COURSE AND FILTER LAYER STONE TO BE DOUBLE WASHED AND CLEAN AND FREE OF ALL FINES.

2. PERMEABLE PAVEMENT/POROUS ASPHALT IS NOT TO BE USED FOR HANDICAPPED ACCESSIBLE PARKING SPACES.

2 / C104 PERMEABLE PAVEMENT
FOR SPECIFIED PARKING SPACES — NO SCALE

EROSION AND SEDIMENT CONTROL NOTES

1. THE OWNER IS TO COORDINATE AND BE RESPONSIBLE FOR SITE EROSION AND SEDIMENT CONTROL. THE OWNER MAY DELEGATE EROSION AND SEDIMENT CONTROL DUTIES TO CONTRACTORS OR SUBCONTRACTORS BASED UPON THE FIRM WITH THE APPROPRIATE EQUIPMENT OR WHO IS RESPONSIBLE FOR CREATING A VIOLATION (IE SEDIMENT TRACKING, KNOCKING DOWN SILT FENCE, BY-PASSING STABILIZED CONSTRUCTION ENTRANCE, ETC). THE OWNER IS RESPONSIBLE FOR THE DAY TO DAY IMPLEMENTATION OF THE SWPPP AND PREVENTING SEDIMENT-LADEN DISCHARGES FROM THE CONSTRUCTION SITE.
2. ALL EROSION AND SEDIMENT CONTROL PRACTICES ARE TO BE INSTALLED PRIOR TO SOIL DISTURBANCE, OR IN THEIR PROPER SEQUENCE, AND MAINTAINED UNTIL PERMANENT PROTECTION OR STABILIZATION IS ESTABLISHED. VEGETATED AREAS ARE CONSIDERED TO HAVE ACHIEVED FINAL STABILIZATION ONCE 80% COVERAGE DENSITY HAS BEEN ACHIEVED.
3. ANY DISTURBED AREAS THAT WILL BE LEFT EXPOSED MORE THAN TEN (10) DAYS, AND NOT SUBJECT TO CONSTRUCTION TRAFFIC, WILL IMMEDIATELY RECEIVE A TEMPORARY SEEDING AND MULCHED WITH STRAW OR EQUIVALENT MATERIAL AT A RATE OF TWO (2) TONS PER ACRE, ACCORDING TO STATE STANDARDS.
4. PERMANENT VEGETATION TO BE SEEDED OR SODDED ON ALL EXPOSED AREAS WITHIN TEN (10) DAYS AFTER FINAL GRADING. MULCHING IS REQUIRED ON ALL SEEDING. WHEN HYDROSEEDING, REFER TO MANUFACTURER'S INSTRUCTIONS.
5. ALL WORK IS TO BE DONE IN ACCORDANCE WITH THE "NEW YORK STANDARDS AND SPECIFICATIONS FOR EROSION AND SEDIMENT CONTROL," LATEST EDITION
6. IMMEDIATELY FOLLOWING INITIAL DISTURBANCE OR ROUGH GRADING, ALL CRITICAL AREAS SUBJECT TO EROSION (I.E., STEEP SLOPES) WILL RECEIVE A TEMPORARY SEEDING IN COMBINATION WITH STRAW MULCH OR A SUITABLE EQUIVALENT, AT A RATE OF TWO (2) TONS PER ACRE, ACCORDING TO STATE STANDARDS OR EROSION CONTROL MATTING.
7. SHOULD THE CONTROL OF DUST AT THE SITE BE NECESSARY, THE SITE WILL BE SPRINKLED UNTIL THE SURFACE IS WET. TEMPORARY VEGETATIVE COVER SHALL BE ESTABLISHED OR MULCH SHALL BE APPLIED IN ACCORDANCE WITH STATE STANDARDS FOR EROSION CONTROL.
8. ALL SOIL WASHED, DROPPED, SPILLED, OR TRACKED OUTSIDE THE LIMIT OF DISTURBANCE OR ONTO LOCAL ROADS, PARKING LOTS, SIDEWALKS OR PUBLIC RIGHTS-OF-WAY SHALL BE REMOVED IMMEDIATELY.
9. THE PROPERTY OWNER SHALL BE RESPONSIBLE FOR ANY EROSION AND SEDIMENTATION THAT MAY OCCUR OFF-SITE AS A RESULT OF CONSTRUCTION OF THE PROJECT.
10. STOCKPILE AND STAGING LOCATIONS DETERMINED IN THE FIELD SHALL BE PLACED WITHIN THE LIMITS OF DISTURBANCE ACCORDING TO THE CERTIFIED PLAN. STAGING AND STOCKPILES NOT LOCATED WITHIN THE LIMITS OF DISTURBANCE WILL REQUIRE A REVISED EROSION AND SEDIMENT CONTROL PLAN. THE OWNER RESERVES THE RIGHT TO DETERMINE WHEN A NEW AND SEPARATE EROSION AND SEDIMENT CONTROL PLAN WILL BE REQUIRED FOR THESE ACTIVITIES
11. ALL SOIL STOCKPILES ARE TO BE TEMPORARILY STABILIZED IN ACCORDANCE WITH THE EROSION AND SEDIMENT CONTROL PLAN. SURROUND THE SOIL STOCKPILE WITH A RING OF SILT FENCE. DO NOT LOCATE A STOCKPILE AREA WITHIN 100 FEET OF A WETLAND BOUNDARY. DO NOT LOCATE A STOCKPILE AREA CLOSER THAN 20 FEET TO THE TOP OF A STEEP SLOPE. TEMPORARILY SEED OR COVER THE SOIL STOCKPILE IF IT WILL NOT BE DISTURBED FOR TEN (10) DAYS
12. PAVEMENT AREAS ARE TO BE KEPT CLEAN AT ALL TIMES. ALL ROADS/DRIVEWAYS ARE TO BE SWEPT CLEAN AT THE END OF EACH WORKDAY OR AS MAY OTHERWISE BE DICTATED BY THE WORK BEING PERFORMED. ALL CAMPUS ROADS, PARKING LOTS, AND ACTIVE PEDESTRIAN WALKS ARE TO BE KEPT CLEAN ON A CONTINUOUS BASIS WHICH MAY REQUIRE MORE FREQUENT SWEEPING.
13. DURING IMPORTATION OF FILL, ANY ADDITIONAL CONTROL MEASURES AS DEEMED NECESSARY TO PREVENT EROSION OR CONTROL SEDIMENT BEYOND THOSE MEASURES SHOWN ON THE APPROVED PLAN SHALL BE INSTALLED OR EMPLOYED AT THE DIRECTION OF THE ENGINEER, THE PROJECT MANAGER, OR THE OWNER.

EROSION & SEDIMENT MAINTENANCE REQUIREMENTS

MEASURE	FREQUENCY	REQUIRED MAINTENANCE
SILT FENCE	ONCE PER WEEK OR AFTER A STORM EVENT	REMOVE ACCUMULATED SEDIMENT. REPAIR/RESET WHEN TORN OR KNOCKED DOWN
SILTSOXX	ONCE PER WEEK OR AFTER A STORM EVENT	REMOVE ACCUMULATED SEDIMENT. RESET /STABILIZE. REPLACE TORN OR DAMAGED SECTIONS. DISPOSE OF PER MANUFACTURERS RECOMMENDATION
SOIL STOCKPILE	ONCE PER WEEK OR AFTER A STORM EVENT	RESEED/MULCH VISIBLE BARE SPOTS. REMOVE ACCUMULATED SEDIMENT FROM SILT FENCE. REPAIR/RESET WHEN SILT FENCE IS TORN OR KNOCKED DOWN
DUST CONTROL	AS NEEDED	SWEEP SURFACES. WET AFFECTED AREA

CONSTRUCTION SEQUENCE

1. CLEAN AND PREPARE SITE – REMOVE LITTER AND DEBRIS. CLEAN CONCRETE SURFACE.
2. INSTALL REQUIRED EROSION AND SEDIMENT CONTROL MEASURES.
3. STABILIZE STOCKPILE AND SITE ANYTIME THE IMPORTATION OF FILL OR GRADING CEASES FOR ONE WEEK (7 CONSECUTIVE DAYS) AND UPON COMPLETION OF THE IMPORT OF FILL AND/OR GRADING.

NO.	DATE	REVISION	BY
3	3/0/21	PER FINAL SWPP CHANGES	JVA
2	9/0/20	PER COMMENTS / SITE CHANGE	JVA
1	8/0/20	PER COMMENTS	JVA

NORTH ARROW

• Elevations of this drawing are in feet and refer to datum as shown hereon. Datum has been established and bear his/her seal, signature, and date of distribution.
• The user of this drawing shall verify all dimensions shown on this drawing before proceeding with any layout or construction work.
• This item is non-scale.

DRAWN BY: AG
CHECKED BY: JVA
DATE: JUNE 2021
SCALE: 1" = 20'

ROHDE, SOYKA & ANDREWS
Consulting Engineers PC
20 Garden Street Poughkeepsie, NY 12601
(845) 452-7510
Fax: (845) 452-2405

117 NORTH HAMILTON
NORTH HAMILTON STREET
CITY OF POUGHKEEPSIE
DUTCHESS COUNTY, NEW YORK

GRADING/EROSION CONTROL PLAN

PROJECT NUMBER: 21-186-01

DRAWING NUMBER: C104

5 OF 10



1 C105 TRUCK TURNING – CITY OF POUGHKEEPSIE LADDER TRUCK
1" = 20'

THE CITY OF POUGHKEEPSIE
FIRE DEPARTMENT
505 MAIN STREET
POUGHKEEPSIE, NY 12601
TEL: 845-451-4079 FAX: 845-451-4191
FIRE CHIEF JOSEPH FRANCO

Date: September 7, 2022

To: All project designers

Subj. City of Poughkeepsie Fire Department Tower Ladder 2 turning specs and dimensions.

These specs are for our 2018 Spartan/Smeal mid-ship 100' Tower Ladder. These are the only dimensions to be used on projects concerning entrance opening and exits, and inside radius turns.

Whenever possible, low profile "rolled" curbing shall be used on inside turn areas to prevent jack scraping and damage.

R,

Fire Chief Joseph Franco

- Length of truck:
  - Body (bumper to bumper) 526" Front bumper of chassis to rear bumper of body.
  - Front axle to rear axle 244" WB
  - Overhang Rear Bumper to rear edge of platform 35" at rear. CJ8 siren adds 8" to length at the front.
  - Ground load on jacks is 120psi when outriggers are set up.

Operational Set-up: Outrigger to outrigger is 16'width deployed. With jack distribution plates it is 22'. Optimal angle is cab away from building at 15 degrees, this accounts for a 27' set up area. Ground must be solid & level, free of obstructions: curbing, storm drains, bollards etc.



NO.	DATE	BY	REVISION
1	12/4/22	JVA	PER FD COMMENTS

NORTH ARROW

DRAWN BY: KMC
CHECKED BY: JVA
DATE: SEPTEMBER 2, 2022
SCALE: 1" = 20'

ROHDE, SOYKA & ANDREWS
Consulting Engineers, P.C.
101 Garden Street Poughkeepsie, N.Y. 12601
Tel: (845) 452-1555 Fax: (845) 452-1535

117 NORTH HAMILTON
NORTH HAMILTON STREET
TAX MAP NO. 6162-83-267293
DUTCHESS COUNTY, NEW YORK

TRUCK TURNING

PROJECT NUMBER
21-785-01

DRAWING NUMBER
C105
6 OF 10

Alteration of this drawing, except by a licensed Professional Engineer or architect in order that it reflects the name and address of the person altering it and the date of alteration.
The users of this drawing shall verify all dimensions shown thereon and shall report any discrepancies to the engineer.
This line is one inch long



DRIVEWAY RAMPS & ADA RAMP

CITY OF POUGHKEEPSIE ENGINEERING DEPARTMENT 62 CIVIC CENTER PLAZA POUGHKEEPSIE, NY 12601	FILE NO.: 001-087	DRIVEWAY RAMP DETAIL	1
	DATE: 3-18-02		
	SCALE: AS NOTED		
	DRAWN BY: JP		



NOTE: PAVEMENT MARKINGS ARE TO CONFORM TO THE LATEST EDITION OF NYS MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES (NUTCD)

2 C500 PAINTED PAVEMENT MARKINGS
NO SCALE



3 C500 STOP SIGN
NO SCALE



4 C500 HANDICAP SIGN
NO SCALE



5 C500 NO PARKING SIGN
NO SCALE



1. SCORING PATTERN AND EDGE TOOLING TO MATCH CAMPUS STANDARD. SCORED JOINTS EVERY 10' O.C., UNLESS NOTED OTHERWISE CAULKED JOINTS EVERY 2nd JOINT
2. ALL COLD JOINTS TO BE DOWELED WITH #4 BAR AT 12" ON CENTER.

HEAVY DUTY CONCRETE WALK
6 C500
NO SCALE



7 C500 CURB RAMP AT END OF SIDEWALK
NO SCALE



8 C500 CURB RAMP FOR CONTINUING SIDEWALK
NO SCALE



NOTE #1: 5" CONCRETE WALK PER DETAIL 14/C500
8" CONCRETE WALK PER DETAIL 6/C500

9 C503 CONCRETE CURB AND SIDEWALK
NO SCALE



NORTH ARROW

NO.	DATE:	REVISION	BY:
2	9/2/22	PER COMMENTS / SITE CHANGE	JVA
1	5/25/22	PER COMMENTS	JVA

Alteration of this drawing, except by a Licensed Professional Engineer or Architect in Charge, is prohibited. Any alteration by a Professional Engineer or Architect shall bear his/her name, signature and date of alteration.
The seal on this drawing shall verify all data contained on all sheets.
Title blocks in error made here.

DRAWN BY: KMC
CHECKED BY: JVA
DATE: 11/1/2022
SCALE: AS NOTED



10 C500 SAWCUT
NO SCALE



11 C500 CAULKED EXPANSION JOINT
NO SCALE



12 C500 CURB END
NO SCALE



NOTE:
JOINT SEALANT STRIP SHALL BE "QUI-JOINT", MANUFACTURED BY QUI-KRAVE PRODUCTS, INC. OR APPROVED EQUAL

13 C500 PAVEMENT KEY
NO SCALE



SIDEWALK DETAIL REPLACE & NEW

CITY OF POUGHKEEPSIE ENGINEERING DEPARTMENT	PROJECT NO.: 001-087	SIDEWALK DETAIL	
	DATE: 3-18-02		
	SCALE: AS NOTED		
	DRAWN BY: JP		



15 C500 BITUMINOUS CONCRETE PAVEMENT
NO SCALE



16 C500 ADA 12" PAVER
NO SCALE



NOTE:
1. CONCRETE SHALL BE MINIMUM 4000 PSI.

FORMED CURB DETAIL

CITY OF POUGHKEEPSIE ENGINEERING DEPARTMENT 62 CIVIC CENTER PLAZA POUGHKEEPSIE, NY 12601	FILE NO.: 001-087	FORMED CURB DETAIL	1
	DATE: 3-18-02		
	SCALE: AS NOTED		
	DRAWN BY: JP		



18 C500 ADA PAVER INSTALLATION DETAIL
NO SCALE



NOTE: ALONG CURB RAMPS, SLOPE OF DROP CURB TO MATCH CURB RAMP

19 C500 DROP CURB
NO SCALE



W	A	B
2'-6"	1'-0"	1'-6"
3'-0"	1'-0"	2'-0"
3'-6"	1'-0"	2'-6"
4'-0"	1'-0"	3'-0"

NOTE
1. SITTING WALLS ARE NOT STRUCTURALLY CONNECTED TO THE BUILDING FOUNDATION
2. AT DIAMETER SOFFITS AS REQUIRED BY SITE PLAN OR AS OTHERWISE INDICATED BY THE ENGINEER
3. LOCATIONS - AS PER PLAN OR AS OTHERWISE INDICATED BY THE ARCHITECT

20 C500 SITTING WALL
NO SCALE



21 C500 ASPHALT SIDEWALK
NO SCALE



CITY OF POUGHKEEPSIE ENGINEERING DEPARTMENT 62 CIVIC CENTER PLAZA POUGHKEEPSIE, NY 12601	FILE NO.: 001-087	FLEXIBLE PAVEMENT DETAIL	1
	DATE: 2-27-12		
	SCALE: AS NOTED		
	DRAWN BY: JP		



RIGID PAVEMENT AND TRENCH LIMITS DETAIL

CITY OF POUGHKEEPSIE ENGINEERING DEPARTMENT 62 CIVIC CENTER PLAZA POUGHKEEPSIE, NY 12601	FILE NO.: 001-087	RIGID PAVEMENT DETAIL	1
	DATE: 5-16-00		
	SCALE: AS NOTED		
	DRAWN BY: JP		

ROHDE, SOYKA & ANDREWS
Consulting Engineers PC
40 Garden Street Poughkeepsie, N.Y. 12601
Tel: (845) 452-4700
Fax: (845) 452-4705

117 NORTH HAMILTON
117 NORTH HAMILTON STREET
POUGHKEEPSIE
DUTCHESS COUNTY, NEW YORK

DETAILS #1

PROJECT NUMBER: 21-786-01

DRAWING NUMBER: C500

6 OF 9

DOGHOUSE MANHOLE (3/C501) — NO SCALE



NOTES:

1. EXISTING SANITARY LINE TO BE EXCAVATED TO A DEPTH OF 14-INCHES +/- BELOW PIPE
2. 7-FT X 7-FT CONCRETE SLAB SHALL BE POURED AND CENTERED BENEATH PIPE. CONCRETE SHALL BE 4000 PSI FIBER REINFORCED. FIBERS TO BE POLY PROPYLENE FIBERS FOR CONCRETE AT NOT LESS THAN 1.0 LB/CY
3. DOGHOUSE SECTION SHALL BE LOWERED IN PLACE OVER THE EXISTING 8" SANITARY LINE.
4. CONCRETE SHALL BE POURED TO A DEPTH OF 6-INCHES AND THE FORMING OF THE CHANNEL FOR THE PROPOSED 10-INCH SANITARY LINE SHALL BE COMPLETED.
5. THE INLET AND OUTLET OF THE DOGHOUSE SHALL BE CEMENTED AND TAR COATED TO INSURE WATER TIGHTNESS.
6. THE MANHOLE WILL THEN BE HYDROSTATICALLY OR VACUUM TESTED PRIOR TO BACKFILLING TO ENSURE WATER TIGHTNESS.
7. THE EXISTING 8-INCH MAIN WILL BE REMOVED FOR THE COMPLETION OF THE CHANNEL WITH ADDITIONAL CONCRETE

NEW MANHOLE DETAIL



CITY OF POUGHKEEPSIE ENGINEERING DEPARTMENT 62 CIVIC CENTER PLAZA POUGHKEEPSIE, NY 12601	FILE NO: MANHOLE DATE: 7-2-02 SCALE: N.T.S. DRAWN BY: JP	TYPICAL MANHOLE DETAIL	1

WATER AND SEWER SEPARATION DISTANCES (5/C501) — NO SCALE

GENERAL NOTES

1. WATER LINES CROSSING OVER SANITARY OR STORM SEWERS SHALL HAVE A MINIMUM VERTICAL SEPARATION OF 18 INCHES FROM TOP OF SEWER TO BOTTOM OF WATER LINE.
2. WATER LINES RUNNING PARALLEL TO SANITARY SEWERS SHALL MAINTAIN A VERTICAL SEPARATION OF 18 INCHES ABOVE THE SEWER AND A HORIZONTAL SEPARATION OF 10 FEET FROM THE SEWER. SANITARY SEWERS LOCATED NEARER THAN THIS MINIMUM SEPARATION REQUIREMENT SHALL BE DUCTILE IRON, CLASS 52, CEMENT LINED, MECHANICAL JOINT PRESSURE PIPE.
3. WATER LINES CROSSING UNDER SANITARY OR STORM SEWERS SHALL HAVE
   A. A MINIMUM VERTICAL SEPARATION OF 18" FROM TOP OF WATER LINE TO BOTTOM OF SEWER (UNLESS SHOWN OTHERWISE)
   B. ADDITIONAL STRUCTURAL SUPPORT FOR THE SEWER TO PREVENT DEFLECTION.
   C. THE 18 FOOT LENGTH OF WATER PIPE SHALL BE CENTERED AT THE POINT OF CROSSING SUCH THAT THE JOINTS WILL BE EQUIDISTANT FROM THE SEWER.



SECTION ALONG MANHOLE TROUGH (6/C501) — NO SCALE



SECTION THRU MANHOLE TROUGH (7/C501) — NO SCALE



FLEXIBLE CONNECTION AT MANHOLE (8/C501) — FOR PIPES 4" TO 15" — NO SCALE



DRAINBASIN – GRASSED AREAS (9/C501) — NO SCALE





DRAINBASIN STANDARD GRATE

FOR MH-1 USE SOLID COVER

NOTE:
BACK-FILL MATERIAL FOR THE SIDES OF THE STRUCTURE SHALL BE NATIVE MATERIAL IF SUITABLE, (NO PARTICLES LARGER THAN 4" IN DIAMETER) BACK-FILL SHALL BE PLACED UNIFORMLY IN 12" LIFTS AND COMPACTED TO A MINIMUM OF 90%

CURBLESS TYPE CATCHBASIN (4/C501) (ROADS AND PARKING AREAS) — NO SCALE

NOTES

1. ALL BASINS ARE TO BE PRECAST CONCRETE DESIGNED FOR H-20 HIGHWAY LOADING PLUS PLUS 25% IMPACT.
2. ALL COMPONENTS TO CONFORM TO NYSDOT NYSDOT SPECIFICATIONS, LATEST EDITION.
3. SLOPE ADJACENT GRADES 2% MINIMUM TO ALL BASINS OR AS SHOWN.



MANHOLE LID & FRAME (10/C501) — NO SCALE



TAPPING SLEEVE & VALVE



CITY OF POUGHKEEPSIE ENGINEERING DEPARTMENT 62 CIVIC CENTER PLAZA POUGHKEEPSIE, NY 12601	TAPPING SLEEVE & VALVE	DATE 9/5/2014

STANDARD DROP CONNECTION



CITY OF POUGHKEEPSIE ENGINEERING DEPARTMENT 62 CIVIC CENTER PLAZA POUGHKEEPSIE, NY 12601	FILE NO.: 05-DET DATE: 3-15-07 SCALE: AS NOTED DRAWN BY: JAC	STANDARD DROP CONNECTION	1

REFUSE ENCLOSURE (15/C500) — NO SCALE



REFUSE ENCLOSURE WALL SECTION



REFUSE ENCLOSURE GATE POST



REFUSE ENCLOSURE PLAN

PLASTIC MANHOLE STEP (1/C501) — NO SCALE



UTILITY TRENCH DETAIL IN PUBLIC R.O.W.



NOTES

1. DITCH WIDTH IS ALL EXTEND A MINIMUM OF ONE AND ONE-HALF FT FROM THE EDGES OF THE TRENCH
2. REPLACED BASE MATERIAL OVER TRENCH SHALL BE ITEM 4 COMPACTED IN 12" LIFTS
3. PIPE BEDDING SHALL BE A MINIMUM OF 6" ABOVE AND BELOW PIPE
4. ALL JOINTS SHALL BE MECHANICALLY SAWED
5. ALL JOINTS SHALL BE SQUARED TO THE EXISTING EDGE OF CURB AND/OR PAVEMENT, AND TACK COATED PER DETAIL
6. ROAD SURFACE REPLACEMENT SHALL BE MINIMUM OF SIX INCHES OF ASPHALT CONCRETE
7. BINDER COURSE ASPHALT PAVEMENT TO BE PLACED IN TWO LIFTS

CITY OF POUGHKEEPSIE ENGINEERING DEPARTMENT 62 CIVIC CENTER PLAZA POUGHKEEPSIE, NY 12601	PROJECT: LSRP DATE: 10-30-2018 SCALE: NTS DRAWN BY: JAC	TRENCH AND PAVEMENT DETAIL	4

RESIDENTIAL CLEAN-OUT DETAIL



CITY OF POUGHKEEPSIE ENGINEERING DEPARTMENT 62 CIVIC CENTER PLAZA POUGHKEEPSIE, NY 12601	RESIDENTIAL SANITARY CLEAN-OUT	DATE: 9/22/2014

WATERLINE OFFSET DETAIL



CITY OF POUGHKEEPSIE ENGINEERING DEPARTMENT 62 CIVIC CENTER PLAZA POUGHKEEPSIE, NY 12601	FILE NO.: 001-DET DATE: 3-6-00 SCALE: AS NOTED DRAWN BY: JP	WATERLINE OFFSET	1

CURB TYPE CATCHBASIN (15/C501) — NO SCALE

NOTES

1. ALL BASINS ARE TO BE PRECAST CONCRETE DESIGNED FOR H-20 HIGHWAY LOADING PLUS PLUS 25% IMPACT.
2. ALL COMPONENTS TO CONFORM TO NYSDOT NYSDOT SPECIFICATIONS, LATEST EDITION.
3. SLOPE ADJACENT GRADES 2% MINIMUM TO ALL BASINS OR AS SHOWN.



DOUBLE CLEANOUT (6/C501) — NO SCALE



NOTES:
1. ALL FITTINGS SHALL BE GASKETED
2. CLEAN OUTS SHALL BE SAME DIAMETER (D) AS SERVICE LINE

TYPICAL SANITARY SEWER PIPE REPAIR OR WYE INSTALLATION DETAIL



NOTES:
1. FOR PIPE GREATER THAN 15" ALL PIPE JOINTS SHALL BE CONSTRUCTED BY METHODS APPROVED BY THE CITY ENGINEER

SCALE: N.T.S.

FILE: +3VS DATE: 02-02-2005 SCALE: AS NOTED DRAWN BY: JTK	TYPICAL SANITARY SEWER PIPE REPAIR OR WYE INSTALLATION DETAIL	CITY OF POUGHKEEPSIE ENGINEERING DEPARTMENT 62 CIVIC CENTER PLAZA POUGHKEEPSIE, NY 12601	1

TRENCHING (13/C501) — NO SCALE



NOTE

1. REMOVE ALL ROCKS GREATER THAN 2" IN ANY DIMENSION FROM IN-SITU MATERIAL PRIOR TO BACKFILLING AND COMPACTING
2. 5'-0" MIN COVER FROM TOP OF PIPE TO FINISHED GRADE FOR WATER 4'-6" MIN COVER FROM TOP OF PIPE TO FINISHED GRADE FOR SEWER.
3. PLACE MAGNETIC LOCATOR TAPE 12" BELOW FINISHED GRADE FOR WATER AND SEWER
4. BEDDING, PIPE ZONE MATERIAL AND TRENCH BACKFILL TO CONFORM TO TOWN OF POUGHKEEPSIE WATER NOTE #15 FOR WATER AND SANITARY AND SEWER NOTE #C FOR SEWER. TOWN OF POUGHKEEPSIE NOTES ARE LOCATED ON C-4
5. IF REQUIRED AND AUTHORIZED BY THE ENGINEER OR THE TOWN, INSULATION SHALL BE INSTALLED PER THIS NOTE AND DETAIL. INSULATION SHALL BE CENTERED ON THE PIPE AND EXTEND THE WIDTH OF THE TRENCH OR 2' MINIMUM WHICHEVER IS LESS

NO.	DATE	REVISION	BY

NORTH ARROW

- Alteration of this drawing, except by a Licensed Professional Engineer or Architect is illegal. Any alteration by a Professional Engineer or Architect must be indicated and bear his/her seal, signature and date of alteration.
- The user of this drawing shall verify all dimensions shown hereon and the scale of this drawing.
- This line is one inch long

DRAWN BY:	KMC
CHECKED BY:	JVA
DATE:	FEB 2022
SCALE:	AS NOTED

ROHDE, SOYKA & ANDREWS
Consulting Engineers PC
40 Garden Street Poughkeepsie, N.Y. 12601 (845) 452 7515 Fax: (845) 452 8335

117 NORTH HAMILTON

NORTH HAMILTON STREET
CITY OF POUGHKEEPSIE
DUTCHESS COUNTY, NEW YORK

DETAILS #2

PROJECT NUMBER: 21-766-01

DRAWING NUMBER C501

7 OF 9



1 C502 STABILIZED CONSTRUCTION ENTRANCE

NO SCALE



NOTE:

1. STONE-SIZE: USE NYS DOT SUB-BASE TYPES 1,2,3,4 OR EQUIVALENT AS SPECIFIED. LARGER STONE CAN BE USED IN AREAS WITH HEAVY CONSTRUCTION EQUIPMENT TRAFFIC.
2. THICKNESS: NOT LESS THAN SIX (6) INCHES.
3. WIDTH: 24' MINIMUM.
4. DRAINAGE: PROVIDE SURFACE DRAINAGE AND DIVERT EXCESS RUNOFF TO STABILIZED AREAS.
5. ROAD GRADE: A MAXIMUM OF 12% IS RECOMMENDED, ALTHOUGH GRADES OF UP TO 15% ARE POSSIBLE FOR SHORT DISTANCES.
6. MAINTENANCE: INSPECT CONSTRUCTION ROADS PERIODICALLY. TOP DRESS WITH NEW GRAVEL AS NEEDED.

2 C502 STABILIZED CONSTRUCTION ROAD AND PARKING AREAS

NO SCALE



CONSTRUCTION SPECIFICATIONS

1. WOVEN WIRE FENCE TO BE FASTENED SECURELY TO FENCE POSTS WITH WIRE TIES OR STAPLES. POSTS SHALL BE STEEL EITHER "T" OR "U" TYPE OR HARDWOOD.
2. FILTER CLOTH TO BE FASTENED SECURELY TO WOVEN WIRE FENCE WITH TIES SPACED EVERY 24" AT TOP AND MID SECTION. FENCE SHALL BE WOVEN WIRE, 12 1/2 GAUGE, 6" MAXIMUM MESH OPENING.
3. WHEN TWO SECTIONS OF FILTER CLOTH ADJOIN EACH OTHER THEY SHALL BE OVER-LAPPED BY SIX INCHES AND FOLDED. FILTER CLOTH SHALL BE EITHER FILTER X, MIRAFI 100X, STABILINKA T140N, OR APPROVED EQUIVALENT.
4. PREFABRICATED UNITS SHALL BE GEOFAB, ENVIROFENCE, OR APPROVED EQUIVALENT.
5. MAINTENANCE SHALL BE PERFORMED AS NEEDED AND MATERIAL REMOVED WHEN "BULGES" DEVELOP IN THE SILT FENCE.

CITY OF POUGHKEEPSIE ENGINEERING DEPARTMENT, 62 CIVIC CENTER PLAZA, POUGHKEEPSIE, NY 12601 | SILT FENCE | DATE: 9/18/2014

3 C502 SILT FENCE

NO SCALE

EROSION AND SEDIMENT CONTROL NOTES

1. THE CONSTRUCTION MANAGER IS TO COORDINATE AND BE RESPONSIBLE FOR SITE EROSION AND SEDIMENT CONTROL. THE CONSTRUCTION MANAGER MAY DELEGATE EROSION AND SEDIMENT CONTROL DUTIES TO CONTRACTORS OR SUBCONTRACTORS BASED UPON THE FIRM WITH THE APPROPRIATE EQUIPMENT OR WHO IS RESPONSIBLE FOR CREATING A VIOLATION (IE SEDIMENT TRACKING, KNOCKING DOWN SILT FENCE, BY-PASSING STABILIZED CONSTRUCTION ENTRANCE, ETC). THE CONSTRUCTION MANAGER IS RESPONSIBLE FOR THE DAY TO DAY IMPLEMENTATION OF THE SWPPP AND PREVENTING SEDIMENT-LADEN DISCHARGES FROM THE CONSTRUCTION SITE.
2. ALL EROSION AND SEDIMENT CONTROL PRACTICES ARE TO BE INSTALLED PRIOR TO SOIL DISTURBANCE, OR IN THEIR PROPER SEQUENCE, AND MAINTAINED UNTIL PERMANENT PROTECTION OR STABILIZATION IS ESTABLISHED. VEGETATED AREAS ARE CONSIDERED TO HAVE ACHIEVED FINAL STABILIZATION ONCE 80% COVERAGE DENSITY HAS BEEN ACHIEVED.
3. ANY DISTURBED AREAS THAT WILL BE LEFT EXPOSED MORE THAN TEN (10) DAYS, AND NOT SUBJECT TO CONSTRUCTION TRAFFIC, WILL IMMEDIATELY RECEIVE A TEMPORARY SEEDING AND MULCHED WITH STRAW OR EQUIVALENT MATERIAL AT A RATE OF TWO (2) TONS PER ACRE, ACCORDING TO STATE STANDARDS.
4. PERMANENT VEGETATION TO BE SEEDED OR SODDED ON ALL EXPOSED AREAS WITHIN TEN (10) DAYS AFTER FINAL GRADING. MULCHING IS REQUIRED ON ALL SEEDING. WHEN HYDROSEEDING, REFER TO MANUFACTURER'S INSTRUCTIONS.
5. ALL WORK IS TO BE DONE IN ACCORDANCE WITH THE "NEW YORK STANDARDS AND SPECIFICATIONS FOR EROSION AND SEDIMENT CONTROL," LATEST EDITION.
6. IMMEDIATELY FOLLOWING INITIAL DISTURBANCE OR ROUGH GRADING, ALL CRITICAL AREAS SUBJECT TO EROSION (I.E., STEEP SLOPES) WILL RECEIVE A TEMPORARY SEEDING IN COMBINATION WITH STRAW MULCH OR A SUITABLE EQUIVALENT, AT A RATE OF TWO (2) TONS PER ACRE, ACCORDING TO STATE STANDARDS OR EROSION CONTROL MATTING.
7. THE STANDARD FOR STABILIZED CONSTRUCTION ENTRANCE REQUIRES THE INSTALLATION OF A STONE PAD OF 2" STONE A MINIMUM OF 6" THICK, AT ALL CONSTRUCTION DRIVEWAYS, PRIOR TO INITIAL SITE DISTURBANCE. THE OWNER IS TO PROVIDE THE LOCATION OF THE STABILIZED CONSTRUCTION ENTRANCE. THE OWNER SHALL DESIGNATE AN AREA OR AREAS FOR CONSTRUCTION VEHICLE PARKING.
8. AT THE TIME THE SITE PREPARATION FOR PERMANENT VEGETATIVE STABILIZATION IS GOING TO BE ACCOMPLISHED, ANY SOIL THAT WILL NOT PROVIDE A SUITABLE ENVIRONMENT TO SUPPORT ADEQUATE VEGETATIVE GROUND COVER, SHALL BE REMOVED OR TREATED IN SUCH A WAY THAT IT WILL PERMANENTLY ADJUST THE SOIL CONDITIONS AND RENDER IT SUITABLE FOR VEGETATIVE GROUND COVER. IF THE REMOVAL OR TREATMENT OF THE SOIL WILL NOT PROVIDE SUITABLE CONDITIONS, NONVEGETATIVE MEANS OF PERMANENT GROUND STABILIZATION WILL HAVE TO BE EMPLOYED.
9. UNFILTERED DEWATERING IS NOT PERMITTED. TAKE ALL NECESSARY PRECAUTIONS DURING ALL DEWATERING OPERATIONS TO MINIMIZE SEDIMENT TRANSFER. ANY DEWATERING METHODS USED MUST BE IN ACCORDANCE WITH STATE STANDARDS. DO NOT DISCHARGE DOWN STEEP SLOPES.
10. SHOULD THE CONTROL OF DUST AT THE SITE BE NECESSARY, THE SITE WILL BE SPRINKLED UNTIL THE SURFACE IS WET, TEMPORARY VEGETATIVE COVER SHALL BE ESTABLISHED OR MULCH SHALL BE APPLIED IN ACCORDANCE WITH STATE STANDARDS FOR EROSION CONTROL.
11. ALL SOIL WASHED, DROPPED, SPILLED, OR TRACKED OUTSIDE THE LIMIT OF DISTURBANCE OR ONTO PARKING LOTS, SIDEWALKS OR PUBLIC RIGHTS-OF-WAY SHALL BE REMOVED IMMEDIATELY.
12. THE PROPERTY OWNER SHALL BE RESPONSIBLE FOR ANY EROSION AND SEDIMENTATION THAT MAY OCCUR OFF-SITE AS A RESULT OF CONSTRUCTION OF THE PROJECT.
13. STOCKPILE AND STAGING LOCATIONS DETERMINED IN THE FIELD SHALL BE PLACED WITHIN THE LIMITS OF DISTURBANCE ACCORDING TO THE CERTIFIED PLAN. STAGING AND STOCKPILES NOT LOCATED WITHIN THE LIMITS OF DISTURBANCE WILL REQUIRE A REVISED EROSION AND SEDIMENT CONTROL PLAN. THE OWNER RESERVES THE RIGHT TO DETERMINE WHEN A NEW AND SEPARATE EROSION AND SEDIMENT CONTROL PLAN WILL BE REQUIRED FOR THESE ACTIVITIES.
14. ALL SOIL STOCKPILES ARE TO BE TEMPORARILY STABILIZED IN ACCORDANCE WITH THE EROSION AND SEDIMENT CONTROL PLAN. SURROUND THE SOIL STOCKPILE WITH A RING OF SILT FENCE. DO NOT LOCATE A STOCKPILE AREA WITHIN 100 FEET OF A WETLAND BOUNDARY. DO NOT LOCATE A STOCKPILE AREA CLOSER THAN 20 FEET TO THE TOP OF A STEEP SLOPE. TEMPORARILY SEED OR COVER THE SOIL STOCKPILE IF IT WILL NOT BE DISTURBED FOR TEN (10) DAYS.
15. ALL PERMANENT EROSION AND SEDIMENT CONTROL MEASURES SHALL BE MAINTAINED BY THE PROPERTY OWNER, AND SHALL BECOME THEIR RESPONSIBILITY.
16. PAVEMENT AREAS ARE TO BE KEPT CLEAN AT ALL TIMES. ALL ROADS/DRIVEWAYS ARE TO BE SWEPT CLEAN AT THE END OF EACH WORKDAY OR AS MAY OTHERWISE BE DICTATED BY THE WORK BEING PERFORMED. PLEASE ALSO SEE NOTE 11. ALL PARKING LOTS, AND ACTIVE PEDESTRIAN WALKS ARE TO BE KEPT CLEAN ON A CONTINUOUS BASIS WHICH MAY REQUIRE MORE FREQUENT SWEEPING.
17. DURING CONSTRUCTION, ANY ADDITIONAL CONTROL MEASURES AS DEEMED NECESSARY TO PREVENT EROSION OR CONTROL SEDIMENT BEYOND THOSE MEASURES SHOWN ON THE APPROVED PLAN SHALL BE INSTALLED OR EMPLOYED AT THE DIRECTION OF THE ENGINEER, THE OWNER, THE PROJECT MANAGER OR THE CONSTRUCTION MANAGER.
18. AFTER CONSTRUCTION IS COMPLETE AND FINAL STABILIZATION HAS BEEN ACHIEVED, REMOVE ALL TEMPORARY EROSION AND SEDIMENT CONTROL PRACTICES. INSPECT ALL PREVIOUSLY SEEDED GRASS/LAWN AREAS FOR BARE OR THIN SPOTS AND RE-SEED AND MULCH AS NEEDED.
19. IN ACCORDANCE WITH GP-0-20-001, A FINAL STABILIZATION INSPECTION AND SIGN-OFF BY THE LOCAL MS4 IS REQUIRED BEFORE THE NOTICE OF TERMINATION (NOT) CAN BE FILED WITH NYSDEC.

CONSTRUCTION SEQUENCE

1. PRE-CONSTRUCTION

A. PRE-CONSTRUCTION MEETING
1. CONSTRUCTION MANAGERS, CONTRACTORS AND SUBCONTRACTORS PERFORMING EARTH-DISTURBING ACTIVITIES MUST ATTEND PRE-CONSTRUCTION MEETING. THE MEETING IS TO BE COORDINATED BY THE CONSTRUCTION MANAGERS.
2. CONSTRUCTION MANAGERS, CONTRACTORS, AND SUBCONTRACTORS PERFORMING EARTH DISTURBING ACTIVITIES MUST PROVIDE SIGNED CONTRACTOR CERTIFICATIONS AND IDENTIFY THE 'TRAINED CONTRACTOR' WHO WILL BE ON-SITE ON A DAILY BASIS IN ACCORDANCE WITH NYSDEC SPDES GENERAL PERMIT FOR STORMWATER DISCHARGES FROM CONSTRUCTION ACTIVITIES, GP-0-20-001. THE TRAINING CERTIFICATE NUMBER FOR THE 'TRAINED CONTRACTOR' MUST BE PROVIDED IN ACCORDANCE WITH CITY OF POUGHKEEPSIE.
3. IN ADDITION, THE 'QUALIFIED INSPECTOR,' SWPPP PREPARER, MS4 EROSION & SEDIMENT CONTROL INSPECTOR, AND OWNER'S REPRESENTATIVE MUST ATTEND THE PRE-CONSTRUCTION MEETING.

B. MARK LIMITS OF DISTURBANCE

C. DIVERT OFF-SITE, CLEAN RUNOFF FROM ENTERING AREAS TO BE DISTURBED.

D. ESTABLISH CONSTRUCTION ENTRANCE(S)
1. ANY SEDIMENT TRACKED ONTO PUBLIC OR PRIVATE ROADWAYS, PARKING LOTS OR SIDEWALKS OUTSIDE THE CONSTRUCTION AREA IS TO BE CLEANED/REMOVED ON A DAILY BASIS.
2. PRESERVE EXISTING ASPHALT WHERE POSSIBLE FOR USE AS CONSTRUCTION ENTRANCES AND CONSTRUCTION ROUTES.

E. ESTABLISH CONTRACTOR PARKING AND STAGING AREAS, IN ACCORDANCE WITH OWNER'S PREFERENCES. PROVIDE CONTRACTOR PARKING AND STAGING AREA STABILIZATION PRIOR TO USE.

F. INSTALL EROSION CONTROL MEASURES, SUCH AS SILT FENCE AND CATCHBASIN INLET PROTECTION, BEFORE LAND GRADING BEGINS.
1. SILT FENCE IS TO BE INSTALLED PARALLEL TO CONTOURS

G. INSTALL TREE PROTECTION FENCING.

2. CONSTRUCTION

A. LIMIT INITIAL GRADING TO AREAS THAT ARE NEEDED FOR EROSION AND SEDIMENT CONTROL.

B. STOCKPILE TOPSOIL AWAY FROM DRAINAGE PATHS, WATERBODIES AND THE TOP OF STEEP SLOPES. STABILIZE AS SOON AS POSSIBLE.

C. AVOID DISTURBANCE OF STEEP SLOPES
1. IF DISTURBANCE ON STEEP SLOPES IS REQUIRED, MINIMIZE AREA TO BE DISTURBED AND AMOUNT OF TIME AREA WILL BE DISTURBED. PLAN STEEP SLOPE DISTURBANCE DURING DRY WEATHER AND WHEN SOILS ARE NOT SATURATED. STABILIZE STEEP SLOPE DISTURBANCE AT THE END OF EACH WORKDAY. PROVIDE FINAL STABILIZATION AS SOON AS WORK ON THE STEEP SLOPE IS COMPLETED.

D. COMMENCE GENERAL SITE CONSTRUCTION

E. STABILIZE EXPOSED SOIL AS SOON AS POSSIBLE. IN AREAS WHERE SOIL DISTURBANCE ACTIVITY HAS BEEN TEMPORARILY OR PERMANENTLY CEASED, TEMPORARY AND/OR PERMANENT SOIL STABILIZATION MEASURES SHALL BE INSTALLED AND/OR IMPLEMENTED WITHIN TEN (10) DAYS FROM THE DATE THE SOIL DISTURBANCE ACTIVITY CEASED.

F. DIRECT ANY SEDIMENT RUNOFF INTO SEDIMENTATION TRAPS. IF THERE IS A SEDIMENTATION PROBLEM IN AN AREA WHERE THERE IS NO SEDIMENTATION TRAP CALLED FOR ON THE PLAN, CREATE A SEDIMENTATION TRAP AND NOTE ITS LOCATION ON THE STORMWATER DRAWING.

G. PREVENT SEDIMENT FROM BEING TRANSPORTED OFF-SITE.

H. ANY SEDIMENT TRACKED ONTO ROADS, PARKING LOTS, OR ACTIVE PEDESTRIAN WALKS SHALL BE SWEPT, AS NEEDED, BUT NOT LESS THAN ONE (1) TIME PER DAY.

3. MAINTENANCE AND INSPECTION DURING CONSTRUCTION

A. ALL EROSION AND SEDIMENT CONTROL MEASURES MUST BE MAINTAINED ON A REGULAR SCHEDULE DURING CONSTRUCTION.

B. INSPECTIONS MUST BE PERFORMED AT LEAST ONCE EVERY SEVEN (7) CALENDAR DAYS BY QUALIFIED PROFESSIONAL AS OUTLINED IN GP-0-20-001.

C. CONTRACTORS RESPONSIBLE FOR EROSION AND SEDIMENT CONTROL ARE TO INSPECT ALL PRACTICES AT LEAST ONCE A WEEK AND AFTER EVERY RAIN EVENT.

D. ENSURE THAT ALL PRACTICES ARE OPERATING AS DESIGNED.

E. ENSURE THAT NO SEDIMENT IS BEING TRANSPORTED OFF-SITE OR IS ENTERING THE DRAINAGE SYSTEM.

F. LOOK FOR EVIDENCE OF EROSION IN DISTURBED PORTIONS OF THE SITE.

G. ENSURE THAT SEDIMENT IS NOT BEING TRACKED ONTO PUBLIC OR PRIVATE ROADS, PARKING LOTS OR SIDEWALKS OUTSIDE THE CONSTRUCTION AREA.

H. RETAIN COPIES OF INSPECTION REPORTS ON-SITE WITH THE SWPPP. CONSTRUCTION MANAGER IS TO MAINTAIN SWPPP AND INSPECTION REPORTS ON-SITE.

4. FINAL GRADING & LANDSCAPING

A. ONCE CONSTRUCTION IS NEARING COMPLETION, IDENTIFY THE FINAL GRADING AND STABILIZATION PLAN.

B. ALL BARE AREAS MUST RECEIVE COVER. PERMANENT TOPSOIL AND VEGETATION SHOULD BE PLACED WHERE APPROPRIATE. REFER TO LANDSCAPING PLANS.

C. AREAS USED FOR CONSTRUCTION STAGING AND AREAS THAT WERE PREVIOUSLY IMPERVIOUS AND ARE NOW LAWN AREA ARE TO BE DE-COMPACTED PRIOR TO SPREADING OF TOPSOIL, SEED AND MULCH. REFER TO SWPPP FOR ADDITIONAL INFORMATION ON DE-COMPACTION.

D. OTHER AREAS SHALL RECEIVE COVER, SUCH AS STONE, MULCH OR RIPRAP, AS APPROPRIATE.

E. STABILIZATION MUST BE UNDERTAKEN NO LATER THAN 10 DAYS AFTER CONSTRUCTION ACTIVITY HAS CEASED.

F. FINAL PLANTING SCHEDULE TO BE DETERMINED BY LANDSCAPE ARCHITECT. IF CONSTRUCTION IS NEARING COMPLETION AT A TIME OF YEAR WHEN PLANTING IS NOT RECOMMENDED, PROVIDE TEMPORARY SEED AND MULCH IN PLACE OF LANDSCAPING UNTIL CONDITIONS ARE APPROPRIATE FOR FINAL PLANTING.

G. REMOVE TEMPORARY EROSION CONTROL MEASURES THAT WILL INTERFERE WITH FINAL GRADING AND LANDSCAPING.

5. POST-CONSTRUCTION

A. ENSURE THAT THE PERMANENT PRACTICES UTILIZED DURING CONSTRUCTION ARE SUITABLE TO FIT POST-CONSTRUCTION SITE CONDITIONS.

B. MINIMIZE THE RISK OF CONCENTRATED FLOW AND EROSION.

C. CLEAN AND PREPARE PERMANENT PRACTICES TO BE TURNED OVER TO THE OWNER/OPERATOR. PREPARE MANUAL AND DISCUSS OPERATION AND MAINTENANCE OF THE PERMANENT PRACTICE WITH THE OWNER/OPERATOR OR REPRESENTATIVE.

D. REMOVE TEMPORARY EROSION AND SEDIMENT CONTROL PRACTICES, SUCH AS SILT FENCE.

E. INSPECT PREVIOUSLY SEEDED GRASS/LAWN AREAS FOR BARE OR THIN SPOTS. RE-SEED AND MULCH AS NEEDED. WITH REMOVAL OF TEMPORARY E&SC PRACTICES, SUCH AS SILT FENCE, SEED AND MULCH AS NEEDED.

F. IN ACCORDANCE WITH GP-0-20-001, A FINAL STABILIZATION INSPECTION AND SIGN-OFF BY THE LOCAL MS4 IS REQUIRED BEFORE THE NOTICE OF TERMINATION (NOT) CAN BE FILED WITH NYSDEC.



NOTES:

1. TEMPORARY ORANGE CONSTRUCTION FENCES SHALL BE USED TO SEPARATE CONSTRUCTION ACTIVITIES FROM PEDESTRIANS.
2. ALL TEMPORARY ORANGE CONSTRUCTION FENCING SHALL BE PLASTIC, 48" MINIMUM HEIGHT AND ORANGE IN COLOR.
3. TEMPORARY ORANGE CONSTRUCTION FENCE USED TO SEPARATE SIDEWALKS FROM CONSTRUCTION ACTIVITIES SHALL HAVE MINIMUM ENCROACHMENT TO THE SIDEWALK.
4. CONTRACTOR TO PROVIDE ANCHORAGE (I.E. SANDBAGS) FOR FENCE IF REQUIRED BY SITE CONDITIONS.

4 C502 TEMPORARY ORANGE CONSTRUCTION FENCE

NO SCALE



NOTES:

1. TOP AND BOTTOM SELVAGE ON WIRE MESH SHALL BE KNUCKLED.
2. CONTRACTOR TO PROVIDE ANCHORAGE (I.E. SANDBAGS) FOR FENCE IF REQUIRED BY SITE CONDITIONS.
3. ATTACH OPAQUE SCREEN TO FENCE; MINIMUM 2-FT GAP BETWEEN GROUND SURFACE AND BOTTOM OF OPAQUE SCREEN.

5 C502 TEMPORARY CHAIN LINK PANEL FENCE DURING CONSTRUCTION

NO SCALE



CONSTRUCTION SPECIFICATIONS

1. LAY ONE BLOCK ON EACH SIDE OF THE STRUCTURE ON ITS SIDE FOR DEWATERING. FOUNDATION SHALL BE 2 INCHES MINIMUM BELOW REST OF INLET AND BLOCKS SHALL BE PLACED AGAINST INLET FOR SUPPORT.
2. HARDWARE CLOTH OR 1/2" WIRE MESH SHALL BE PLACED OVER BLOCK OPENINGS TO SUPPORT STONE.
3. USE CLEAN STONE OR GRAVEL 1/2-3/4 INCH IN DIAMETER PLACED 2 INCHES BELOW TOP OF THE BLOCK ON A 2:1 SLOPE OR FLATTER.
4. FOR STONE STRUCTURES ONLY, A 1 FOOT THICK LAYER OF THE FILTER STONE WILL BE PLACED AGAINST THE 3 INCH STONE AS SHOWN ON THE DRAWINGS.
5. MAXIMUM DRAINAGE AREA 1 ACRE.
6. PROTECT INLET PROTECTION FROM DAMAGE BY CONSTRUCTION TRAFFIC; SURROUND WITH TEMPORARY ORANGE CONSTRUCTION FENCE.
7. IN PAVED AREAS, ELIMINATE CONCRETE BLOCK FOR DEWATERING. USE STONE/GRAVEL FILTER.

6 C502 STONE AND BLOCK DROP INLET PROTECTION

NO SCALE



CONSTRUCTION SPECIFICATIONS

1. AREA UNDER EMBANKMENT SHALL BE CLEARED, GRUBBED, AND STRIPPED OF ANY VEGETATION AND ROOT MATERIAL. THE TRAP AREA SHALL BE CLEARED.
2. THE FILL MATERIAL FOR THE EMBANKMENT SHALL BE FREE OF ROOTS OR OTHER WOODY VEGETATION AS WELL AS OVERSIZED STONES, ROCKS, ORGANIC MATERIAL OR OTHER QUESTIONABLE MATERIAL. THE EMBANKMENT SHALL BE COMPACTED BY TRAVERSING WITH EQUIPMENT WHILE IT IS BEING CONSTRUCTED.
3. SEDIMENT SHALL BE REMOVED AND TRAP RESTORED TO ITS ORIGINAL DIMENSION WHEN THE SEDIMENT HAS ACCUMULATED TO 1/2 THE DESIGN DEPTH OF THE TRAP. REMOVED SEDIMENT SHALL BE DEPOSITED IN A SUITABLE AREA AND IN SUCH A MANNER THAT IT WILL NOT ERODE.
4. THE STRUCTURE SHALL BE INSPECTED AFTER EACH RAIN AND REPAIRS MADE AS NECESSARY.
5. CONSTRUCTION OPERATIONS SHALL BE CARRIED OUT IN SUCH A MANNER THAT EROSION AND WATER POLLUTION IS MINIMIZED.
6. THE STRUCTURE SHALL BE REMOVED AND THE AREA STABILIZED WHEN THE DRAINAGE AREA HAS BEEN PROPERLY STABILIZED.
7. ALL CUT AND FILL SLOPES SHALL BE 2 ON 1 OR FLATTER.
8. THE CRUSHED STONE USED IN THE OUTLET SHALL MEET AASHTO DESIGNATION M43, SIZE NO. 2, OR 24 OR ITS EQUIVALENT SUCH AS MSHA NO. 2 GRAVEL MEETING THE ABOVE GRADATION MAY BE USED IF CRUSHED STONE IS NOT AVAILABLE. CRUSHER RUN IS NOT ACCEPTABLE.

7 C502 STONE OUTLET SEDIMENT TRAP

NO SCALE



8 C502 SILTSOXX (tm) SEDIMENT CONTROL ON PAVEMENT

NO SCALE



9 C502 SOIL STOCKPILE

NO SCALE



10 C502 FLARED END SECTION AND RIPRAP OUTLET PROTECTION

NO SCALE



GENERAL NOTES:

1. ACTUAL LOCATION DETERMINED IN THE FIELD
2. CONCRETE WASHOUT STRUCTURE NEEDS TO BE CLEARLY MARKED WITH SIGNAGE NOTING DEVICE.

11 C502 ABOVE GRADE WASHOUT STRUCTURE

NO SCALE

WASHOUT NOTES

1. ALL CONCRETE WASH-OUT FACILITIES SHALL BE INSPECTED DAILY. DAMAGED OR LEAKING FACILITIES SHALL BE DE-ACTIVATED & REPAIRED, OR REPLACED IMMEDIATELY. EXCESS RAINWATER THAT HAS ACCUMULATED OVER HARDENED CONCRETE SHALL BE PUMPED TO A STABILIZED AREA, SUCH AS A GRASS FILTER STRIP.
2. ACCUMULATED MATERIAL SHALL BE REMOVED WHEN 75% OF THE STORAGE CAPACITY OF THE STRUCTURE IS FILLED. ANY EXCESS WASH WATER SHALL BE PUMPED INTO A CONTAINMENT VESSEL AND PROPERLY DISPOSED OF OFF-SITE.
3. DISPOSE OF ALL HARDENED MATERIAL OFF-SITE IN A CONSTRUCTION/DEMOLITION LANDFILL. ON-SITE DISPOSAL MAY BE ALLOWED IF THIS HAS BEEN APPROVED & ACCEPTED AS PART OF THE PROJECTS SWPPP. IN THAT CASE, THE MATERIAL SHOULD BE RECYCLED AS SPECIFIED, OR BURIED & COVERED WITH A MINIMUM OF TWO (2) FEET OF CLEAN COMPACTED EARTH-FILL THAT IS PERMANENTLY STABILIZED TO PREVENT EROSION.
4. THE PLASTIC LINER SHALL BE REPLACED WITH EACH CLEANING OF THE WASHOUT FACILITY.
5. INSPECT THE PROJECT SITE FREQUENTLY TO ENSURE THAT NO CONCRETE DISCHARGES ARE TAKING PLACE IN NON-DESIGNATED AREAS.
6. AS AN ALTERNATIVE, A LINED ROLL-OFF CONTAINER CAN BE USED FOR THE WASHOUT FACILITY.
7. THE CONCRETE WASHOUT FACILITY SHALL BE LOCATED A MINIMUM OF 100 FEET FROM DRAINAGE SWALES, WETLANDS, STREAMS, AND OTHER WATER BODIES. THE FACILITY SHALL BE LOCATED DOWN HILL OF ANY STORM DRAINAGE INLET OR OTHERWISE 100 FEET MINIMUM FROM SUCH STRUCTURES.

PERIMETER STONE MUST ALWAYS BE BROUGHT UP EVENLY WITH BACKFILL OF BED. PERIMETER STONE MUST EXTEND HORIZONTALLY TO THE EXCAVATION WALL FOR BOTH STRAIGHT OR SLOPED SIDEWALLS.



THE INSTALLED CHAMBER SYSTEM SHALL PROVIDE THE LOAD FACTORS SPECIFIED IN THE AASHTO LRFD BRIDGE DESIGN SPECIFICATIONS SECTION 12.12 FOR EARTH AND LIVE LOADS, WITH CONSIDERATION FOR IMPACT AND MULTIPLE VEHICLE PRESENCES.

NOTES

1. INSPECTION PORTS MAY BE CONNECTED THROUGH ANY OF (6) CHAMBER CORRUGATION VALLEYS.
2. ALL SCHEDULE 40 FITTINGS TO BE SOLVENT CEMENTED.



12 C502 STORMTECH MC 3500 STORMWATER CHAMBER

NO SCALE

NO.	DATE	REVISION	BY
2	3/2/23	PER FINAL SWPP CHANGES	JVA
1	5/31/22	PER COMMENTS	JVA

NORTH ARROW

- Alteration of this drawing, except by a Licensed Professional Engineer or Architect is illegal. Any alteration by a Professional Engineer or Architect must be indicated and bear his/her seal, signature and date of alteration.
- The user of this drawing shall verify all dimensions shown hereon and the scale of this drawing.
- This line is one inch long.

DRAWN BY: KMC
CHECKED BY: JVA
DATE: FEB 2022
SCALE: AS NOTED

ROHDE, SOYKA & ANDREWS
Consulting Engineers PC
40 Garden Street, Poughkeepsie, N.Y. 12601
(845) 452-7515
Fax: (845) 452-8335

117 NORTH HAMILTON
NORTH HAMILTON STREET
CITY OF POUGHKEEPSIE
DUTCHESS COUNTY, NEW YORK

ESC DETAILS

PROJECT NUMBER: 21-786-01

DRAWING NUMBER: C502

8 OF 9



1 L100 LANDSCAPE PLAN
1" = 20'

NOTES

1. PROTECT ALL EXISTING VEGETATION TO REMAIN FROM DAMAGE DURING CONSTRUCTION.
2. USE EXTREME CAUTION TO PROTECT UTILITIES.
3. ALL PLANT MATERIAL SHALL BE NURSERY GROWN UNLESS OTHERWISE NOTED.
4. QUANTITIES GIVEN ON THE PLANTING LIST ARE FOR REFERENCE ONLY. THE CONTRACTOR SHALL VERIFY ALL QUANTITIES SHOWN ON THE LIST AND SHALL BE RESPONSIBLE FOR FURNISHING ALL MATERIALS REQUIRED TO COMPLETE THE PLANS.
5. THE CONTRACTOR SHALL VERIFY ALL GRADES, DIMENSIONS AND EXISTING CONDITIONS, AND REPORT ANY DISCREPANCIES TO THE ENGINEER.
6. ALL BEDS AND TREE SAUCERS AND OTHER AREAS NOTED SHALL RECEIVE 2 INCHES (MINIMUM) OF APPROVED MULCH (SHREDDED CEDAR).
7. CONTRACTOR SHALL GUARANTEE ALL PLANT MATERIAL FOR ONE YEAR FROM TIME OF ENGINEER'S FINAL WRITTEN APPROVAL.
8. TOP SOIL MIX SHALL INCLUDE:
   - 3 PARTS SCREENED TOPSOIL
   - 1PART SAND
   - 1 PART HUMUS
   - 5 LBS. SUPERPHOSPHATE PER CU. YD. OF MIX
9. CONTRACTOR TO COORDINATE PLANTING, SEEDING AND TREE WORK WITH OTHER TRADES.
10. CONTRACTOR IS RESPONSIBLE FOR RESTORING ALL AREAS DISTURBED DUE TO PLANTING OPERATIONS.

LEGEND

- EXISTING TREE
- PROPOSED TREE
- PROPOSED SHRUB
- PROPOSED GRASSES
- PROPOSED PERENNIALS

PLANT LIST

QTY	KEY	BOTANICAL NAME	COMMON NAME	SIZE	COMMENTS
Trees					
10	ERC	*Juniperus virginiana*	Eastern Red Cedar	5-6'	B&B
3	RM	*Acer rubrum*	Red Maple	2-2.5" C	B&B
Shrubs					
3	RTD	*Cornus alba "siberica"*	Red Twig Dogwood	3 – 5' Hgt	3 Gal
8	H	*Hydrangea paniculata "little quick fire"*	Hydrangea	3 – 5' Hgt	3 Gal
Grasses					
50	SG	*Panicum virgatum "Shenandoah"*	Switch Grass	1 Gal	18" O.C.
32	PD	*Sporobolus heterolepis*	Prairie Dropseed	1 Gal	18" O.C.
6	LBS	*Carex sprengelii*	Long Beaked Sedge	1 Gal	18" O.C.
Perennials					
12	PCF	*Echinacea purpurea*	Purple Cone Flower	2 Gal	
14	HM	*Agastache "Summer Sky"*	Hummingbird Mint	2 Gal	
15	S	*Sedum herbstfreude "autumn joy"*	Stonecrop	2 Gal	

ALL AREAS NOT OTHERWISE COVERED BY ASPHALT, BUILDINGS OR LANDSCAPE PLANTINGS, SHALL BE TOPSOILED, SEEDED WITH LAWN (GRASS) PLANTED.

2 L100 GROUNDCOVER PLANTING
NO SCALE



3 L100 PLANTING
NO SCALE



4 L100 SHRUB PLANTING
NO SCALE



6 L100 STONE DIAPHRAGM
NO SCALE

NO	DATE	REVISION	BY
4	9/8/22	PER COMMENTS	JVA
3	9/2/22	PER COMMENTS / SITE CHANGE	JVA
2	7/5/22	PER CITY COMMENT	JVA
1	5/27/22	PER OWNER COMMENT	JVA

NORTH ARROW

- Alteration of this drawing, except by a licensed Professional Engineer or Architect, is illegal, and alteration by a Professional Engineer or Architect requires the affixing of his/her seal, signature and date of alteration.
- The user of this drawing shall verify all dimensions shown on the drawing before proceeding with any layout or fabrication.
- This bar is one inch long

DRAWN BY: KMC
CHECKED BY: JVA
DATE: APRIL 2022
SCALE: 1" = 20'

ROHDE, SOYKA & ANDREWS
Consulting Engineers, PC
49 Garden Street Poughkeepsie, N.Y. 12601
Tel: (845) 452-1555
Fax: (845) 452-2555

117 NORTH HAMILTON
117 NORTH HAMILTON STREET
TAX MAP NUMBER
DUTCHESS COUNTY, NEW YORK

LANDSCAPE PLAN

PROJECT NUMBER:
21-156-01

DRAWING NUMBER:
L100
10 OF 10

SPDES GENERAL PERMIT FOR STORMWATER DISCHARGES FROM CONSTRUCTION ACTIVITY GP-0-20-001

(Not included at this time)



SURVEY NOTE:
BASE MAP TAKEN FROM BOUNDARY & TOPOGRAPHIC SURVEY BY JOHNSON SURVEYING. FIELD SURVEY COMPLETED ON OCT. 30, 2020. BEARINGS & NORTH ARROW SHOWN ARE REFERENCED TO NAD 83 -NY EAST USING NYSNET RTN GPS. CONTOUR INTERVAL IS ONE FOOT. ELEVATIONS SHOWN ARE REFERENCED TO NAVD 88 USING NYSNET RTN GIS.

1 / C104 EROSION CONTROL PLAN
1" = 20'

LEGEND

- EX. FLOOD ZONE LIMIT
- EX. PROPERTY LINE
- EX. ADJACENT PROPERTY LINE
- EX. MINOR CONTOUR
- EX. MAJOR CONTOUR
- EX. RETAINING WALL
- EX. FENCE
- EX. ASPHALT LIMIT
- EX. GRAVEL LIMIT
- EX. CONCRETE LIMIT
- EX. CONCRETE CURB
- EX. OVERHEAD WIRES WITH UTILITY POLE
- EX. SANITARY SEWER LINE & MANHOLE
- EX. STORMWATER LINE & DRAINAGE MANHOLE
- EX. GAS LINE WITH GAS VALVE
- EX. WATER LINE
- EX. LIGHT POLE
- EX. MAILBOX
- EX. HYDRANT
- EX. CATCH BASIN
- EX. SIGN
- SILTSOXX (TM)
- SILT FENCE
- SOIL STOCKPILE
- 15' WIDE X 50' LONG STABILIZED CONSTRUCTION ENTRANCE

EROSION AND SEDIMENT CONTROL NOTES

1. THE OWNER IS TO COORDINATE AND BE RESPONSIBLE FOR SITE EROSION AND SEDIMENT CONTROL. THE OWNER MAY DELEGATE EROSION AND SEDIMENT CONTROL DUTIES TO CONTRACTORS OR SUBCONTRACTORS BASED UPON THE FIRM WITH THE APPROPRIATE EQUIPMENT OR WHO IS RESPONSIBLE FOR CREATING A VIOLATION (IE SEDIMENT TRACKING, KNOCKING DOWN SILT FENCE, BY-PASSING STABILIZED CONSTRUCTION ENTRANCE, ETC). THE OWNER IS RESPONSIBLE FOR THE DAY TO DAY IMPLEMENTATION OF THE SWPPP AND PREVENTING SEDIMENT-LADEN DISCHARGES FROM THE CONSTRUCTION SITE.
2. ALL EROSION AND SEDIMENT CONTROL PRACTICES ARE TO BE INSTALLED PRIOR TO SOIL DISTURBANCE, OR IN THEIR PROPER SEQUENCE, AND MAINTAINED UNTIL PERMANENT PROTECTION OR STABILIZATION IS ESTABLISHED. VEGETATED AREAS ARE CONSIDERED TO HAVE ACHIEVED FINAL STABILIZATION ONCE 80% COVERAGE DENSITY HAS BEEN ACHIEVED.
3. ANY DISTURBED AREAS THAT WILL BE LEFT EXPOSED MORE THAN TEN (10) DAYS, AND NOT SUBJECT TO CONSTRUCTION TRAFFIC, WILL IMMEDIATELY RECEIVE A TEMPORARY SEEDING AND MULCHED WITH STRAW OR EQUIVALENT MATERIAL AT A RATE OF TWO (2) TONS PER ACRE, ACCORDING TO STATE STANDARDS.
4. PERMANENT VEGETATION TO BE SEEDED OR SODDED ON ALL EXPOSED AREAS WITHIN TEN (10) DAYS AFTER FINAL GRADING. MULCHING IS REQUIRED ON ALL SEEDING. WHEN HYDROSEEDING, REFER TO MANUFACTURER'S INSTRUCTIONS.
5. ALL WORK IS TO BE DONE IN ACCORDANCE WITH THE "NEW YORK STANDARDS AND SPECIFICATIONS FOR EROSION AND SEDIMENT CONTROL," LATEST EDITION.
6. IMMEDIATELY FOLLOWING INITIAL DISTURBANCE OR ROUGH GRADING, ALL CRITICAL AREAS SUBJECT TO EROSION (I.E., STEEP SLOPES) WILL RECEIVE A TEMPORARY SEEDING IN COMBINATION WITH STRAW MULCH OR A SUITABLE EQUIVALENT, AT A RATE OF TWO (2) TONS PER ACRE, ACCORDING TO STATE STANDARDS OR EROSION CONTROL MATTING.
7. SHOULD THE CONTROL OF DUST AT THE SITE BE NECESSARY, THE SITE WILL BE SPRINKLED UNTIL THE SURFACE IS WET. TEMPORARY VEGETATIVE COVER SHALL BE ESTABLISHED OR MULCH SHALL BE APPLIED IN ACCORDANCE WITH STATE STANDARDS FOR EROSION CONTROL.
8. ALL SOIL WASHED, DROPPED, SPILLED, OR TRACKED OUTSIDE THE LIMIT OF DISTURBANCE OR ONTO LOCAL ROADS, PARKING LOTS, SIDEWALKS OR PUBLIC RIGHTS-OF-WAY SHALL BE REMOVED IMMEDIATELY.
9. THE PROPERTY OWNER SHALL BE RESPONSIBLE FOR ANY EROSION AND SEDIMENTATION THAT MAY OCCUR OFF-SITE AS A RESULT OF CONSTRUCTION OF THE PROJECT.
10. STOCKPILE AND STAGING LOCATIONS DETERMINED IN THE FIELD SHALL BE PLACED WITHIN THE LIMITS OF DISTURBANCE ACCORDING TO THE CERTIFIED PLAN. STAGING AND STOCKPILES NOT LOCATED WITHIN THE LIMITS OF DISTURBANCE WILL REQUIRE A REVISED EROSION AND SEDIMENT CONTROL PLAN. THE OWNER RESERVES THE RIGHT TO DETERMINE WHEN A NEW AND SEPARATE EROSION AND SEDIMENT CONTROL PLAN WILL BE REQUIRED FOR THESE ACTIVITIES.
11. ALL SOIL STOCKPILES ARE TO BE TEMPORARILY STABILIZED IN ACCORDANCE WITH THE EROSION AND SEDIMENT CONTROL PLAN. SURROUND THE SOIL STOCKPILE WITH A RING OF SILT FENCE. DO NOT LOCATE A STOCKPILE AREA WITHIN 100 FEET OF A WETLAND BOUNDARY. DO NOT LOCATE A STOCKPILE AREA CLOSER THAN 20 FEET TO THE TOP OF A STEEP SLOPE. TEMPORARILY SEED OR COVER THE SOIL STOCKPILE IF IT WILL NOT BE DISTURBED FOR TEN (10) DAYS.
12. PAVEMENT AREAS ARE TO BE KEPT CLEAN AT ALL TIMES. ALL ROADS/DRIVEWAYS ARE TO BE SWEPT CLEAN AT THE END OF EACH WORKDAY OR AS MAY OTHERWISE BE DICTATED BY THE WORK BEING PERFORMED. ALL CAMPUS ROADS, PARKING LOTS, AND ACTIVE PEDESTRIAN WALKS ARE TO BE KEPT CLEAN ON A CONTINUOUS BASIS WHICH MAY REQUIRE MORE FREQUENT SWEEPING.
13. DURING IMPORTATION OF FILL, ANY ADDITIONAL CONTROL MEASURES AS DEEMED NECESSARY TO PREVENT EROSION OR CONTROL SEDIMENT BEYOND THOSE MEASURES SHOWN ON THE APPROVED PLAN SHALL BE INSTALLED OR EMPLOYED AT THE DIRECTION OF THE ENGINEER, THE PROJECT MANAGER, OR THE OWNER.

EROSION & SEDIMENT MAINTENANCE REQUIREMENTS

MEASURE	FREQUENCY	REQUIRED MAINTENANCE
SILT FENCE	ONCE PER WEEK OR AFTER A STORM EVENT	REMOVE ACCUMULATED SEDIMENT. REPAIR/RESET WHEN TORN OR KNOCKED DOWN
SILTSOXX	ONCE PER WEEK OR AFTER A STORM EVENT	REMOVE ACCUMULATED SEDIMENT. RESET /STABILIZE. REPLACE TORN OR DAMAGED SECTIONS. DISPOSE OF PER MANUFACTURERS RECOMMENDATION
SOIL STOCKPILE	ONCE PER WEEK OR AFTER A STORM EVENT	RESEED/MULCH VISIBLE BARE SPOTS. REMOVE ACCUMULATED SEDIMENT FROM SILT FENCE. REPAIR/RESET WHEN SILT FENCE IS TORN OR KNOCKED DOWN
DUST CONTROL	AS NEEDED	SWEEP SURFACES. WET AFFECTED AREA

CONSTRUCTION SEQUENCE

1. CLEAN AND PREPARE SITE – REMOVE LITTER AND DEBRIS, CLEAN CONCRETE SURFACE.
2. INSTALL REQUIRED EROSION AND SEDIMENT CONTROL MEASURES.
3. STABILIZE STOCKPILE AND SITE ANYTIME THE IMPORTATION OF FILL OR GRADING CEASES FOR ONE WEEK (7 CONSECUTIVE DAYS) AND UPON COMPLETION OF THE IMPORT OF FILL AND/OR GRADING.

NO.	DATE	REVISION	BY
2	9/2/22	PER COMMENTS / SITE CHANGE	JVA
1	6/3/22	PER COMMENTS	JVA

NORTH ARROW

• Alteration of this drawing, except by a Licensed Professional Engineer or Architect in limited accordance with Section 7209 of the Education Law, is illegal. Any alteration by a Professional Engineer or Architect must have his/her name, signature and date of alteration, and a specific description of the alteration.
• The user of this drawing shall verify all dimensions shown on the drawing and shall report any discrepancies to the author of the drawing before proceeding with the work.
• This line is one inch long ■

DRAWN BY: AGL
CHECKED BY: JVA
DATE: JUNE 2021
SCALE: 1" = 20'

ROHDE, SOYKA & ANDREWS
Consulting Engineers PC
40 Garden Street Poughkeepsie, N.Y. 12601
(845) 452-7515
Fax: (845) 452-8255

117 NORTH HAMILTON
NORTH HAMILTON STREET
CITY OF POUGHKEEPSIE
DUTCHESS COUNTY, NEW YORK

GRADING/EROSION CONTROL PLAN

PROJECT NUMBER: 21-786-01

DRAWING NUMBER: C104
5 OF 10



1 C103 UTILITY PLAN 1" = 20'

NO.	DATE	REVISION	BY
1	5/5/22	PER COMMENTS	JVA

NORTH ARROW

- Alteration of this drawing, except by a Licensed Professional Engineer or Architect in lieu of his/her professional signature and date of alteration.
- The user of this drawing shall verify all dimensions shown thereon and the scale of this drawing.
- This line is one inch long

DRAWN BY: KMC
CHECKED BY: JVA
DATE: MARCH 2022
SCALE: 1" = 20'

ROHDE, SOYKA & ANDREWS
Consulting Engineers PC
40 Garden Street Poughkeepsie, N.Y. 12601
(845) 452-7515
Fax (845) 454-2038

117 NORTH HAMILTON
NORTH HAMILTON STREET
CITY OF POUGHKEEPSIE
DUTCHESS COUNTY, NEW YORK

UTILITY PLAN

PROJECT NUMBER: 21-786-01

DRAWING NUMBER: C103

4 OF 10



1 L100 LANDSCAPE PLAN
1" = 20'

NOTES

1. PROTECT ALL EXISTING VEGETATION TO REMAIN FROM DAMAGE DURING CONSTRUCTION.
2. USE EXTREME CAUTION TO PROTECT UTILITIES.
3. ALL PLANT MATERIAL SHALL BE NURSERY GROWN UNLESS OTHERWISE NOTED.
4. QUANTITIES GIVEN ON THE PLANTING LIST ARE FOR REFERENCE ONLY. THE CONTRACTOR SHALL VERIFY ALL QUANTITIES SHOWN ON THE LIST AND SHALL BE RESPONSIBLE FOR FURNISHING ALL MATERIALS REQUIRED TO COMPLETE THE PLANS.
5. THE CONTRACTOR SHALL VERIFY ALL GRADES, DIMENSIONS AND EXISTING CONDITIONS, AND REPORT ANY DISCREPANCIES TO THE ENGINEER.
6. ALL BEDS AND TREE SAUCERS AND OTHER AREAS NOTED SHALL RECEIVE 2 INCHES (MINIMUM) OF APPROVED MULCH (SHREDDED CEDAR).
7. CONTRACTOR SHALL GUARANTEE ALL PLANT MATERIAL FOR ONE YEAR FROM TIME OF ENGINEER'S FINAL WRITTEN APPROVAL.
8. TOP SOIL MIX SHALL INCLUDE:
   - 3 PARTS SCREENED TOPSOIL
   - 1PART SAND
   - 1 PART HUMUS
   - 5 LBS. SUPERPHOSPHATE PER CU. YD. OF MIX
9. CONTRACTOR TO COORDINATE PLANTING, SEEDING AND TREE WORK WITH OTHER TRADES.
10. CONTRACTOR IS RESPONSIBLE FOR RESTORING ALL AREAS DISTURBED DUE TO PLANTING OPERATIONS.

LEGEND

- EXISTING TREE
- PROPOSED TREE
- PROPOSED SHRUB
- PROPOSED GRASSES
- PROPOSED PERENNIALS

PLANT LIST

QTY	KEY	BOTANICAL NAME	COMMON NAME	SIZE	COMMENTS
Trees					
10	ERC	*Juniperus virginiana*	Eastern Red Cedar	5-6'	B&B
3	RM	*Acer rubrum*	Red Maple	2-2.5" C	B&B
Shrubs					
2	RTD	*Cornus alba* "siberica"	Red Twig Dogwood	3 – 5' Hgt	1 Gal
5	H	*Hydrangea paniculata* "little quick fire"	Hydrangea	3 – 5' Hgt	1 Gal
Grasses					
50	SG	*Panicum virgatum* "Shenandoah"	Switch Grass	1 Gal	18" O.C.
32	PD	*Sporobolus heteroepis*	Prairie Dropseed	1 Gal	18" O.C.
6	LBS	*Carex sprengelii*	Long Beaked Sedge	1 Gal	18" O.C.
Perennials					
12	PCF	*Echineacea purpurea*	Purple Cone Flower	2 Gal	
14	HM	*Agastache* "Summer Sky"	Hummingbird Mint	2 Gal	
15	S	*Sedum herbstfreude* "autumn joy"	Stonecrop	2 Gal	

ALL AREAS NOT OTHERWISE COVERED BY ASPHALT, BUILDINGS OR LANDSCAPE PLANTINGS, SHALL BE TOPSOILED, SEEDED WITH LAWN (GRASS) PLANTED.



2 L100 GROUNDCOVER PLANTING
NO SCALE



3 L100 PLANTING
NO SCALE



4 L100 SHRUB PLANTING
NO SCALE



5 L100 STONE DIAPHRAGM
NO SCALE

NO.	DATE	REVISION	BY
3	9/2/22	PER COMMENTS/ SITE CHANGE	JVA
2	7/5/22	PER CITY COMMENT	JVA
1	5/27/22	PER OWNER COMMENT	JVA

NORTH ARROW

- Alteration of this drawing, except by a Licensed Professional Engineer or Architect is illegal. Any alteration by a Professional Engineer or Architect is illegal unless they affix their name, signature and date of alteration.
- The user of this drawing shall verify all dimensions shown on the drawing before proceeding with any work.
- This line is one inch long when printed on a full size drawing.

DRAWN BY: KMC
CHECKED BY: JVA
DATE: APRIL 2022
SCALE: 1" = 20'

ROHDE, SOYKA & ANDREWS
Consulting Engineers PC
40 Garden Street Poughkeepsie, N.Y. 12601
(845) 452-7515
Fax: (845) 452-8535

117 NORTH HAMILTON
NORTH HAMILTON STREET
CITY OF POUGHKEEPSIE
DUTCHESS COUNTY, NEW YORK

LANDSCAPE PLAN

PROJECT NUMBER: 21-786-01

DRAWING NUMBER: L100

10 OF 10



1 BUILDING 1 FLOOR PLAN
1" = 10'-0"

CONSTRUCTION NOTES

NOTE: NOT ALL NOTES MAY BE USED ON THIS DRAWING

PROJECT

NORTH

KEY PLAN

AREA OF CONSTRUCTION

100% PLUNNING BOARD SUBMISSION

REVISIONS:

NUM.	DATE	DESCRIPTION

ANDERSON DESIGN GROUP

ARCHITECTURE
PLANNING
INTERIORS

25 WALLKILL AVE • MONTGOMERY • NY 12549
O. 845. 294.2724 | F.888.305.6442

WWW.ADGARCHITECT.COM
CONTACT@ADGARCHITECT.COM

Project: 117 NORTH HAMILTON
117 NORTH HAMILTON ST., POUGHKEEPSIE, NY 12601

Drawing Name: BUILDING 1 FLOOR PLAN

Drawn:	Scale:	Project:	Date:
IDEA	AS NOTED	22102	05/31/22

Drawing Number: A-201-PB

Copyright © all rights reserved - Jason T. Anderson Architect, P.C. / DBA / Anderson Design Group - Architecture - Planning - Interiors / Unauthorized addition or alteration of this document is a violation of the State Education Law.

1 EXTERIOR RENDERING OPTION 3
VIEW 1

2 EXTERIOR RENDERING OPTION 3
VIEW 2

Copyright © all rights reserved - Jason T. Anderson Architect, P.C. / DBA / Anderson Design Group - Architecture - Planning - Interiors / Unauthorized addition or alteration of this document is a violation of the State Education Law.

CONSTRUCTION NOTES

NOTE: NOT ALL NOTES MAY BE USED ON THIS DRAWING



PROJECT NORTH



SCHEMATIC DESIGN

REVISIONS:

NUM.	DATE	DESCRIPTION
1	09-06-22	RESPONSES TO PLANNING BOARD COMMENTS

ANDERSON DESIGN GROUP
ARCHITECTURE
PLANNING
INTERIORS
25 WALLKILL AVE • MONTGOMERY • NY 12549
O. 845. 294.2724 | F. 888.305.6442
WWW.ADGARCHITECT.COM
CONTACT@ADGARCHITECT.COM

Project: 117 NORTH HAMILTON
117 NORTH HAMILTON ST., POUGHKEEPSIE, NY 12601

Drawing Name: EXTERIOR RENDERINGS (OPTION 3)

Drawn:	Scale:	Project:	Date:
IDEA	AS NOTED	22102	08/31/22

Drawing Number: A-903-PB



1 BUILDING 2 FLOOR PLAN
1" = 10'-0"

CONSTRUCTION NOTES

NOTE: NOT ALL NOTES MAY BE USED ON THIS DRAWING

WINDOW / DOOR NOTES:

1. ALL WINDOWS ARE BASED UPON USING ANDERSEN 200 SERIES W/ DUAL PANE HIGH PERFORMANCE LOW E, GLAZING WINDOWS AND DOOR ASSEMBLIES SHALL BE LABELLED AND CERTIFIED BY THE MANUFACTURER NOT TO EXCEED 0.3 CFM/SF AND SWINGING DOORS SHALL HAVE NO MORE THAN 0.5 CFM PER SQUARE FOOT OF LEAKAGE.
2. G.C. TO CONFIRM ALL DOOR AND WINDOW ROUGH OPENING SIZES PRIOR TO ORDERING.
3. CONFIRM HEAD HEIGHT AND SILL HEIGHT W/ OWNER IN FIELD TO DETERMINE SPECIAL CONDITIONS IN KITCHEN AND ON 2ND FLOOR.
4. GLAZING W/ IN 18" W/ FLOOR REQUIRED TO BE TEMPERED.

NOTES:

ALL BATHROOMS & LAVS. NOT HAVING OPERABLE WINDOWS OR HAVING LESS THAN 1.5 S.F. OF WINDOW VENT SPACE SHALL BE MECHANICAL VENTED TO THE EXTERIOR AND TERMINATE USING A WEATHERPROOF BAFFLE DEVICE. (SEE FOLLOWING CFM REQUIREMENTS) INTERMITTENT VENTILATION REQUIRES A MIN. OF 50 CFM (23.6 L/S) WHILE CONTINUOUS VENTILATION REQUIRES 20 CFM (9.4 L/S).

WALL NOTES:

1. ALL MTL. STUD WALLS, PROVIDE COLD ROLLED CHANNEL @ EV. 4'-0" VERT.
2. ALL MTL. STUD WALLS OVER 12'-0" & ALL BEARING WALLS, INSTALL DIAGONAL X-BEARING AT 45° ANGLE @ CORNER & ENDS. USE 2", 16 G.A. GALVANIZED STRAPS W/ (4) #10 TEK SCREWS @ ENDS & ONE @ EACH STUD INSTALL COLD ROLLED CHANNEL @ 4' AND 8'.
3. ALL DIMENSIONS ARE TO ROUGH FRAMING.
4. CLOSED CELL SPRAY FOAM INSUL. MAY BE SUBSTITUTED FOR BATT INSULATION GIVEN THAT AN IGNITION BARRIER IS PROVIDED.
5. STRUCTURAL SPECIFICATION OF METAL FRAMING MEMBERS/GAUGES AND ANY BRACING SUPERSEDE THE ARCHITECTURAL DRAWINGS.

PROJECT

PROJECT NORTH

N O R T H



KEY PLAN

AREA OF CONSTRUCTION

100% PLUNNING BOARD SUBMISSION

REVISIONS:

NUM.	DATE	DESCRIPTION

ANDERSON DESIGN GROUP

ARCHITECTURE
PLANNING
INTERIORS

25 WALLKILL AVE • MONTGOMERY • NY 12549
O. 845. 294.2724 | F.888.305.6442

WWW.ADGARCHITECT.COM
CONTACT@ADGARCHITECT.COM

Project: 117 NORTH HAMILTON
117 NORTH HAMILTON ST., POUGHKEEPSIE, NY 12601

Drawing Name: BUILDING 2 FLOOR PLAN

Drawn:	Scale:	Project:	Date:
IDEA	AS NOTED	22102	05/31/22

Drawing Number: A-202-PB

Copyright © all rights reserved - Jason T. Anderson Architect, P.C. / DBA / Anderson Design Group - Architecture - Planning - Interiors / Unauthorized addition or alteration of this document is a violation of the State Education Law.

3 DOGHOUSE MANHOLE (C501) — NO SCALE



NOTES:

1. EXISTING SANITARY LINE TO BE EXCAVATED TO A DEPTH OF 14-INCHES +/- BELOW PIPE.
2. 7-FT X 7-FT CONCRETE SLAB SHALL BE POURED AND CENTERED BENEATH PIPE. CONCRETE SHALL BE 4000 PSI FIBER REINFORCED. FIBERS TO BE POLY PROPYLENE FIBERS FOR CONCRETE AT NOT LESS THAN 1.0 LB/CY
3. DOGHOUSE SECTION SHALL BE LOWERED IN PLACE OVER THE EXISTING 8" SANITARY LINE.
4. CONCRETE SHALL BE POURED TO A DEPTH OF 6-INCHES AND THE FORMING OF THE CHANNEL FOR THE PROPOSED 10-INCH SANITARY LINE SHALL BE COMPLETED.
5. THE INLET AND OUTLET OF THE DOGHOUSE SHALL BE CEMENTED AND TAR COATED TO INSURE WATER TIGHTNESS.
6. THE MANHOLE WILL THEN BE HYDROSTATICALLY OR VACUUM TESTED PRIOR TO BACKFILLING TO ENSURE WATER TIGHTNESS.
7. THE EXISTING 8-INCH MAIN WILL BE REMOVED FOR THE COMPLETION OF THE CHANNEL WITH ADDITIONAL CONCRETE



NEW MANHOLE DETAIL
NOT TO SCALE
REMOVE AND REPLACE EXISTING MANHOLE WITH MANHOLE SECTIONS.

CITY OF POUGHKEEPSIE ENGINEERING DEPARTMENT 62 CIVIC CENTER PLAZA POUGHKEEPSIE, NY 12601	FILE NO.: MANHOLE	TYPICAL MANHOLE DETAIL	1
	DATE: 7-2-02		
	SCALE: N.T.S.		
	DRAWN BY: JP		PAGE NO.

GENERAL NOTES

1. WATER LINES CROSSING OVER SANITARY OR STORM SEWERS SHALL HAVE A MINIMUM VERTICAL SEPARATION OF 18 INCHES FROM TOP OF SEWER TO BOTTOM OF WATER LINE.
2. WATER LINES RUNNING PARALLEL TO SANITARY SEWERS SHALL MAINTAIN A VERTICAL SEPARATION OF 18 INCHES ABOVE THE SEWER AND A HORIZON- TAL SEPARATION OF 10 FEET FROM THE SEWER. SANITARY SEWERS LOCAT- ED NEARER THAN THIS MINIMUM SEPARATION REQUIREMENT SHALL BE DUCTILE IRON, CLASS 52, CEMENT LINED, MECHANICAL JOINT PRESSURE PIPE.
3. WATER LINES CROSSING UNDER SANITARY OR STORM SEWERS SHALL HAVE:
   A. A MINIMUM VERTICAL SEPARATION OF 18" FROM TOP OF WATER LINE TO BOTTOM OF SEWER (UNLESS SHOWN OTHERWISE).
   B. ADDITIONAL STRUCTURAL SUPPORT FOR THE SEWER TO PREVENT DEFLECTION.
   C. THE 18 FOOT LENGTH OF WATER PIPE SHALL BE CENTERED AT THE POINT OF CROSSING SUCH THAT THE JOINTS WILL BE EQUIDISTANT FROM THE SEWER.



5 WATER AND SEWER SEPARATION DISTANCES (C501)
NO SCALE



6 SECTION ALONG MANHOLE TROUGH (C501)
NO SCALE



7 SECTION THRU MANHOLE TROUGH (C501)
NO SCALE



8 FLEXIBLE CONNECTION AT MANHOLE (C501)
FOR PIPES 4" TO 16" — NO SCALE





DRAINBASIN STANDARD GRATE
FOR MH-1 USE SOLID COVER

NOTE:
BACK-FILL MATERIAL FOR THE SIDES OF THE STRUCTURE SHALL BE NATIVE MATERIAL IF SUITABLE, (NO PARTICLES LARGER THAN 4" IN DIAMETER). BACK-FILL SHALL BE PLACED UNIFORMLY IN 12" LIFTS AND COMPACTED TO A MINIMUM OF 90%.

9 DRAINBASIN – GRASSED AREAS (C501)
NO SCALE



NOTES

1. ALL BASINS ARE TO BE PRECAST CONCRETE DESIGNED FOR H-20 HIGHWAY LOADING PLUS PLUS 25% IMPACT.
2. ALL COMPONENTS TO CONFORM TO NYSDOT NYSDOT SPECIFICATIONS, LATEST EDITION.
3. SLOPE ADJACENT GRADES 2% MINIMUM TO ALL BASINS OR AS SHOWN.

14 CURBLESS TYPE CATCHBASIN (C501)
(ROADS AND PARKING AREAS) — NO SCALE



10 MANHOLE LID & FRAME (C501)
NO SCALE



TAPPING SLEEVE & VALVE
SCALE: N.T.S.

CITY OF POUGHKEEPSIE ENGINEERING DEPARTMENT 62 CIVIC CENTER PLAZA POUGHKEEPSIE, NY 12601	TAPPING SLEEVE & VALVE	DATE: 9/15/2014



STANDARD DROP CONNECTION
NTS

CITY OF POUGHKEEPSIE ENGINEERING DEPARTMENT 62 CIVIC CENTER PLAZA POUGHKEEPSIE, NY 12601	FILE NO.: 001-DET	STANDARD DROP CONNECTION	1
	DATE: 3-15-07		
	SCALE: AS NOTED		
	DRAWN BY: JAC		PAGE NO.



15 REFUSE ENCLOSURE (C500)
NO SCALE



11 PLASTIC MANHOLE STEP (C501)
NO SCALE



UTILITY TRENCH DETAIL IN PUBLIC R.O.W.
SCALE: 1/4" =1'-0"

NOTES:

1. DITCH WIDTH SHALL EXTEND A MINIMUM OF ONE AND ONE-HALF FT. FROM THE EDGES OF THE TRENCH.
2. REPLACED BASE MATERIAL OVER TRENCH SHALL BE ITEM 4 COMPACTED IN 12" LIFTS.
3. PIPE BEDDING SHALL BE A MINIMUM OF 6" ABOVE AND BELOW PIPE
4. ALL JOINTS SHALL BE MECHANICALLY SAWED.
5. ALL JOINTS SHALL BE SQUARED TO THE EXISTING EDGE OF CURB AND/OR PAVEMENT, AND TACK COATED PER DETAIL.
6. ROAD SURFACE REPLACEMENT SHALL BE MINIMUM OF SIX INCHES OF ASPHALIC CONCRETE.
7. BINDER COURSE ASPHALT PAVEMENT TO BE PLACED IN TWO LIFTS.

CITY OF POUGHKEEPSIE ENGINEERING DEPARTMENT 62 CIVIC CENTER PLAZA POUGHKEEPSIE, NY 12601	PROJECT: LSRP	TRENCH AND PAVEMENT DETAIL	4
	DATE: 10-30-2018		
	SCALE: NTS		
	DRAWN BY: JAC		PAGE NO.



RESIDENTIAL CLEAN-OUT DETAIL
SCALE: 3/4"-1'-0"

CITY OF POUGHKEEPSIE ENGINEERING DEPARTMENT 62 CIVIC CENTER PLAZA POUGHKEEPSIE, NY 12601	RESIDENTIAL SANITARY CLEAN-OUT	DATE: 9/22/2014



NOTES:

1. WHEN THE ELEVATION OF THE SEWER CAN NOT BE VARIED TO MEET THE ABOVE REQUIREMENTS, THE WATERMAIN SHALL BE RELOCATED TO PROVIDE THIS REQUIRED SEPARATION OR RECONSTRUCTED WITH MECHANICAL JOINT PIPE FOR A DISTANCE OF TEN (10) FEET ON EACH SIDE OF THE SEWER. ONE FULL UNCUT LENGTH OF WATERMAIN SHALL BE CENTERED OVER THE SEWER SO THAT BOTH JOINTS WILL BE AS FAR AWAY FROM THE SEWER AS POSSIBLE.
2. WHEN IT IS IMPOSSIBLE TO OBTAIN VERTICAL SEPARATION AS STIPULATED ABOVE, BOTH THE WATERMAIN AND THE SEWERMAIN SHALL BE CONSTRUCTED OF SLIP ON OR OF MECHANICAL PIPE JOINTS, CAST IRON PIPE OR SDR 26 PVC COMPLYING WITH PUBLIC WATER SUPPLY DESIGN STANDARDS OF THE AGENCY AND BE PRESSURE TESTED TO 150 PSI TO ASSURE WATER TIGHTNESS.

WATERLINE OFFSET DETAIL
SCALE: N.T.S.

CITY OF POUGHKEEPSIE ENGINEERING DEPARTMENT 62 CIVIC CENTER PLAZA POUGHKEEPSIE, NY 12601	FILE NO.: 001-DET	WATERLINE OFFSET	1
	DATE: 3-6-00		
	SCALE: AS NOTED		
	DRAWN BY: JP		PAGE NO.

NOTES

1. ALL BASINS ARE TO BE PRECAST CONCRETE DESIGNED FOR H-20 HIGHWAY LOADING PLUS PLUS 25% IMPACT.
2. ALL COMPONENTS TO CONFORM TO NYSDOT NYSDOT SPECIFICATIONS, LATEST EDITION.
3. SLOPE ADJACENT GRADES 2% MINIMUM TO ALL BASINS OR AS SHOWN.



15 CURB TYPE CATCHBASIN (C501)
NO SCALE



NOTES:
1. ALL FITTINGS SHALL BE GASKETED.
2. CLEAN OUTS SHALL BE SAME DIAMETER (D) AS SERVICE LINE.

16 DOUBLE CLEANOUT (C501)
NO SCALE



NOTES:
1. FOR PIPE GREATER THAN 15" ALL PIPE JOINTS SHALL BE CONSTRUCTED BY MEDTHODS APPROVED BY THE CITY ENGINEER.

TYPICAL SANITARY SEWER PIPE REPAIR OR WYE INSTALLATION DETAIL
SCALE: N.T.S.

FILE: *.DWG	TYPICAL SANITARY SEWER PIPE REPAIR OR WYE INSTALLATION DETAIL	CITY OF POUGHKEEPSIE ENGINEERING DEPARTMENT 62 CIVIC CENTER PLAZA POUGHKEEPSIE, NY 12601	1
DATE: 03-02-2009			
SCALE: AS NOTED			
DRAWN BY: JTK			PAGE NO.



NOTE
1. REMOVE ALL ROCKS GREATER THAN 2" IN ANY DIMENSION FROM IN-SITU MATERIAL PRIOR TO BACKFILLING AND COMPACTING.
2. 5'-0" MIN COVER FROM TOP OF PIPE TO FINISHED GRADE FOR WATER. 4'-6" MIN COVER FROM TOP OF PIPE TO FINISHED GRADE FOR SEWER.
3. PLACE MAGNETIC LOCATOR TAPE 12" BELOW FINISHED GRADE FOR WATER AND SEWER.
4. BEDDING, PIPE ZONE MATERIAL AND TRENCH BACKFILL TO CONFORM TO TOWN OF POUGHKEEPSIE WATER NOTE #18 FOR WATER AND SANITARY AND SEWER NOTE #10 FOR SEWER. TOWN OF POUGHKEEPSIE NOTES ARE LOCATED ON C-4.
5. IF REQUIRED AND AUTHORIZED BY THE ENGINEER OR THE TOWN, INSULATION SHALL BE INSTALLED PER THIS NOTE AND DETAIL. INSULATION SHALL BE CENTERED ON THE PIPE AND EXTEND THE WIDTH OF THE TRENCH OR 2' MINIMUM WHICHEVER IS LESS.

13 TRENCHING (C501)
NO SCALE

NO.	DATE	REVISION	BY

NORTH ARROW

- Alteration of this drawing, except by a Licensed Professional Engineer or Architect is illegal. Any alteration by a Professional Engineer or Architect must be indicated and bear his/her seal, signature and date of alteration.
- The user of this drawing shall verify all dimensions shown hereon and the scale of this drawing.
- This line is one inch long.

DRAWN BY: KMC
CHECKED BY: JVA
DATE: FEB 2022
SCALE: AS NOTED

ROHDE, SOYKA & ANDREWS
Consulting Engineers PC
40 Garden Street Poughkeepsie, N.Y. 12601
(845) 452-7515
Fax: (845) 452-8335

117 NORTH HAMILTON
NORTH HAMILTON STREET
CITY OF POUGHKEEPSIE
DUTCHESS COUNTY, NEW YORK

DETAILS #2

PROJECT NUMBER: 21-786-01
DRAWING NUMBER: C501
7 OF 9



CONSTRUCTION SPECIFICATIONS

1. Stone Size – Use 2" stone, or reclaimed or recycled concrete equivilent.
2. Length – As required, but not less than 50 feet (except on a single residence lot where a 30 foot minimum length would apply).
3. Thickness – Not less than six (6) inches.
4. Width – Ten (10) foot minimum, but not less than the full width at points where ingress or egress occurs.
5. Filter Cloth – Will be placed over the entire area prior to placing of stone. Filter will not be required on a single family residence lot.
6. Surface Water – All surface water flowing or diverted toward construction entrances shall be piped across the entrance. If piping is impractical, a mountable berm with 5:1 slopes will be permitted.
7. Maintenance – The entrance shall be maintained in a condition which will prevent tracking or flowing of sediment onto public rights-of-way. This may require periodic top dressing with additional stone as conditions demand and repair and/or cleanout of any measures used to trap sediment. All sediment spilled, dropped, washed or tracked onto public rights-of-way must be removed immediately.
8. Washing – Wheels shall be cleaned to remove sediment prior to entrance onto public rights-of-way. When washing is required, it shall be done on an area stabilized with stone and which drains into an approved sediment trapping device.
9. Periodic inspection and needed maintenance shall be provided after each rain.

STABILIZED CONSTRUCTION ENTRANCE

CITY OF POUGHKEEPSIE ENGINEERING DEPARTMENT 62 CIVIC CENTER PLAZA POUGHKEEPSIE, NY 12601	FILE NO.: 001-DET DATE: 3-6-00 SCALE: AS NOTED DRAWN BY: JP	STABILIZED CONSTRUCTION ENTRANCE	1 PAGE NO.

1 C601 STABILIZED CONSTRUCTION ENTRANCE
NO SCALE



NOTE:

1. STONE–SIZE: USE NYS DOT SUB–BASE TYPES 1,2,3,4 OR EQUIVALENT AS SPECIFIED. LARGER STONE CAN BE USED IN AREAS WITH HEAVY CONSTRUCTION EQUIPMENT TRAFFIC.
2. THICKNESS: NOT LESS THAN SIX (6) INCHES.
3. WIDTH: 24' MINIMUM.
4. DRAINAGE: PROVIDE SURFACE DRAINAGE AND DIVERT EXCESS RUNOFF TO STABILIZED AREAS.
5. ROAD GRADE: A MAXIMUM OF 12% IS RECOMMENDED, ALTHOUGH GRADES OF UP TO 15% ARE POSSIBLE FOR SHORT DISTANCES.
6. MAINTENANCE: INSPECT CONSTRUCTION ROADS PERIODICALLY. TOP DRESS WITH NEW GRAVEL AS NEEDED.

2 C601 STABILIZED CONSTRUCTION ROAD AND PARKING AREAS
NO SCALE



CONSTRUCTION SPECIFICATIONS

1. WOVEN WIRE FENCE TO BE FASTENED SECURELY TO FENCE POSTS WITH WIRE TIES OR STAPLES. POSTS SHALL BE STEEL EITHER 'T' OR 'U' TYPE OR HARDWOOD.
2. FILTER CLOTH TO BE TO BE FASTENED SECURELY TO WOVEN WIRE FENCE WITH TIES SPACED EVERY 24" AT TOP AND MID SECTION. FENCE SHALL BE WOVEN WIRE, 12 1/2 GAUGE, 6" MAXIMUM MESH OPENING.
3. WHEN TWO SECTIONS OF FILTER CLOTH ADJOIN EACH OTHER THEY SHALL BE OVER-LAPPED BY SIX INCHES AND FOLDED. FILTER CLOTH SHALL BE EITHER FILTER X, MIRAFI 100X, STABILINKA T140N, OR APPROVED EQUIVALENT.
4. PREFABRICATED UNITS SHALL BE GEOFAB, ENVIROFENCE, OR APPROVED EQUIVALENT.
5. MAINTENANCE SHALL BE PERFORMED AS NEEDED AND MATERIAL REMOVED WHEN "BULGES" DEVELOP IN THE SILT FENCE.

CITY OF POUGHKEEPSIE ENGINEERING DEPARTMENT 62 CIVIC CENTER PLAZA POUGHKEEPSIE, NY 12601	SILT FENCE	DATE: 9/18/2014

3 C601 SILT FENCE
NO SCALE

EROSION AND SEDIMENT CONTROL NOTES

1. THE CONSTRUCTION MANAGER IS TO COORDINATE AND BE RESPONSIBLE FOR SITE EROSION AND SEDIMENT CONTROL. THE CONSTRUCTION MANAGER MAY DELEGATE EROSION AND SEDIMENT CONTROL DUTIES TO CONTRACTORS OR SUBCONTRACTORS BASED UPON THE FIRM WITH THE APPROPRIATE EQUIPMENT OR WHO IS RESPONSIBLE FOR CREATING A VIOLATION (IE SEDIMENT TRACKING, KNOCKING DOWN SILT FENCE, BY–PASSING STABILIZED CONSTRUCTION ENTRANCE, ETC). THE CONSTRUCTION MANAGER IS RESPONSIBLE FOR THE DAY TO DAY IMPLEMENTATION OF THE SWPPP AND PREVENTING SEDIMENT–LADEN DISCHARGES FROM THE CONSTRUCTION SITE.
2. ALL EROSION AND SEDIMENT CONTROL PRACTICES ARE TO BE INSTALLED PRIOR TO SOIL DISTURBANCE, OR IN THEIR PROPER SEQUENCE, AND MAINTAINED UNTIL PERMANENT PROTECTION OR STABILIZATION IS ESTABLISHED. VEGETATED AREAS ARE CONSIDERED TO HAVE ACHIEVED FINAL STABILIZATION ONCE 80% COVERAGE DENSITY HAS BEEN ACHIEVED.
3. ANY DISTURBED AREAS THAT WILL BE LEFT EXPOSED MORE THAN TEN (10) DAYS, AND NOT SUBJECT TO CONSTRUCTION TRAFFIC, WILL IMMEDIATELY RECEIVE A TEMPORARY SEEDING AND MULCHED WITH STRAW OR EQUIVALENT MATERIAL AT A RATE OF TWO (2) TONS PER ACRE, ACCORDING TO STATE STANDARDS.
4. PERMANENT VEGETATION TO BE SEEDED OR SODDED ON ALL EXPOSED AREAS WITHIN TEN (10) DAYS AFTER FINAL GRADING. MULCHING IS REQUIRED ON ALL SEEDING. WHEN HYDROSEEDING, REFER TO MANUFACTURER'S INSTRUCTIONS.
5. ALL WORK IS TO BE DONE IN ACCORDANCE WITH THE "NEW YORK STANDARDS AND SPECIFICATIONS FOR EROSION AND SEDIMENT CONTROL," LATEST EDITION.
6. IMMEDIATELY FOLLOWING INITIAL DISTURBANCE OR ROUGH GRADING, ALL CRITICAL AREAS SUBJECT TO EROSION (I.E., STEEP SLOPES) WILL RECEIVE A TEMPORARY SEEDING IN COMBINATION WITH STRAW MULCH OR A SUITABLE EQUIVALENT, AT A RATE OF TWO (2) TONS PER ACRE, ACCORDING TO STATE STANDARDS OR EROSION CONTROL MATTING.
7. THE STANDARD FOR STABILIZED CONSTRUCTION ENTRANCE REQUIRES THE INSTALLATION OF A STONE PAD OF 2" STONE A MINIMUM OF 6" THICK, AT ALL CONSTRUCTION DRIVEWAYS, PRIOR TO INITIAL SITE DISTURBANCE. THE OWNER IS TO PROVIDE THE LOCATION OF THE STABILIZED CONSTRUCTION ENTRANCE. THE OWNER SHALL DESIGNATE AN AREA OR AREAS FOR CONSTRUCTION VEHICLE PARKING.
8. AT THE TIME THE SITE PREPARATION FOR PERMANENT VEGETATIVE STABILIZATION IS GOING TO BE ACCOMPLISHED, ANY SOIL THAT WILL NOT PROVIDE A SUITABLE ENVIRONMENT TO SUPPORT ADEQUATE VEGETATIVE GROUND COVER, SHALL BE REMOVED OR TREATED IN SUCH A WAY THAT IT WILL PERMANENTLY ADJUST THE SOIL CONDITIONS AND RENDER IT SUITABLE FOR VEGETATIVE GROUND COVER. IF THE REMOVAL OR TREATMENT OF THE SOIL WILL NOT PROVIDE SUITABLE CONDITIONS, NONVEGETATIVE MEANS OF PERMANENT GROUND STABILIZATION WILL HAVE TO BE EMPLOYED.
9. UNFILTERED DEWATERING IS NOT PERMITTED. TAKE ALL NECESSARY PRECAUTIONS DURING ALL DEWATERING OPERATIONS TO MINIMIZE SEDIMENT TRANSFER. ANY DEWATERING METHODS USED MUST BE IN ACCORDANCE WITH STATE STANDARDS. DO NOT DISCHARGE DOWN STEEP SLOPES.
10. SHOULD THE CONTROL OF DUST AT THE SITE BE NECESSARY, THE SITE WILL BE SPRINKLED UNTIL THE SURFACE IS WET, TEMPORARY VEGETATIVE COVER SHALL BE ESTABLISHED OR MULCH SHALL BE APPLIED IN ACCORDANCE WITH STATE STANDARDS FOR EROSION CONTROL.
11. ALL SOIL WASHED, DROPPED, SPILLED, OR TRACKED OUTSIDE THE LIMIT OF DISTURBANCE OR ONTO PARKING LOTS, SIDEWALKS OR PUBLIC RIGHTS–OF–WAY SHALL BE REMOVED IMMEDIATELY.
12. THE PROPERTY OWNER SHALL BE RESPONSIBLE FOR ANY EROSION AND SEDIMENTATION THAT MAY OCCUR OFF–SITE AS A RESULT OF CONSTRUCTION OF THE PROJECT.
13. STOCKPILE AND STAGING LOCATIONS DETERMINED IN THE FIELD SHALL BE PLACED WITHIN THE LIMITS OF DISTURBANCE ACCORDING TO THE CERTIFIED PLAN. STAGING AND STOCKPILES NOT LOCATED WITHIN THE LIMITS OF DISTURBANCE WILL REQUIRE A REVISED EROSION AND SEDIMENT CONTROL PLAN. THE OWNER RESERVES THE RIGHT TO DETERMINE WHEN A NEW AND SEPARATE EROSION AND SEDIMENT CONTROL PLAN WILL BE REQUIRED FOR THESE ACTIVITIES.
14. ALL SOIL STOCKPILES ARE TO BE TEMPORARILY STABILIZED IN ACCORDANCE WITH THE EROSION AND SEDIMENT CONTROL PLAN. SURROUND THE SOIL STOCKPILE WITH A RING OF SILT FENCE. DO NOT LOCATE A STOCKPILE AREA WITHIN 100 FEET OF A WETLAND BOUNDARY. DO NOT LOCATE A STOCKPILE AREA CLOSER THAN 20 FEET TO THE TOP OF A STEEP SLOPE. TEMPORARILY SEED OR COVER THE SOIL STOCKPILE IF IT WILL NOT BE DISTURBED FOR TEN (10) DAYS.
15. ALL PERMANENT EROSION AND SEDIMENT CONTROL MEASURES SHALL BE MAINTAINED BY THE PROPERTY OWNER, AND SHALL BECOME THEIR RESPONSIBILITY.
16. PAVEMENT AREAS ARE TO BE KEPT CLEAN AT ALL TIMES. ALL ROADS/DRIVEWAYS ARE TO BE SWEPT CLEAN AT THE END OF EACH WORKDAY OR AS MAY OTHERWISE BE DICTATED BY THE WORK BEING PERFORMED. PLEASE ALSO SEE NOTE 11. ALL PARKING LOTS, AND ACTIVE PEDESTRIAN WALKS ARE TO BE KEPT CLEAN ON A CONTINUOUS BASIS WHICH MAY REQUIRE MORE FREQUENT SWEEPING.
17. DURING CONSTRUCTION, ANY ADDITIONAL CONTROL MEASURES AS DEEMED NECESSARY TO PREVENT EROSION OR CONTROL SEDIMENT BEYOND THOSE MEASURES SHOWN ON THE APPROVED PLAN SHALL BE INSTALLED OR EMPLOYED AT THE DIRECTION OF THE ENGINEER, THE OWNER, THE PROJECT MANAGER OR THE CONSTRUCTION MANAGER.
18. AFTER CONSTRUCTION IS COMPLETE AND FINAL STABILIZATION HAS BEEN ACHIEVED, REMOVE ALL TEMPORARY EROSION AND SEDIMENT CONTROL PRACTICES. INSPECT ALL PREVIOUSLY SEEDED GRASS/LAWN AREAS FOR BARE OR THIN SPOTS AND RE–SEED AND MULCH AS NEEDED.
19. IN ACCORDANCE WITH GP–0–20–001, A FINAL STABILIZATION INSPECTION AND SIGN–OFF BY THE LOCAL MS4 IS REQUIRED BEFORE THE NOTICE OF TERMINATION (NOT) CAN BE FILED WITH NYSDEC.

CONSTRUCTION SEQUENCE

1. PRE–CONSTRUCTION

A. PRE–CONSTRUCTION MEETING

1. CONSTRUCTION MANAGERS, CONTRACTORS AND SUBCONTRACTORS PERFORMING EARTH–DISTURBING ACTIVITIES MUST ATTEND PRE–CONSTRUCTION MEETING. THE MEETING IS TO BE COORDINATED BY THE CONSTRUCTION MANAGERS.

2. CONSTRUCTION MANAGERS, CONTRACTORS, AND SUBCONTRACTORS PERFORMING EARTH DISTURBING ACTIVITIES MUST PROVIDE SIGNED CONTRACTOR CERTIFICATIONS AND IDENTIFY THE 'TRAINED CONTRACTOR' WHO WILL BE ON–SITE ON A DAILY BASIS IN ACCORDANCE WITH NYSDEC SPDES GENERAL PERMIT FOR STORMWATER DISCHARGES FROM CONSTRUCTION ACTIVITIES, GP–0–20–001. THE TRAINING CERTIFICATE NUMBER FOR THE 'TRAINED CONTRACTOR' MUST BE PROVIDED IN ACCORDANCE WITH CITY OF POUGHKEEPSIE.

3. IN ADDITION, THE 'QUALIFIED INSPECTOR,' SWPPP PREPARER, MS4 EROSION & SEDIMENT CONTROL INSPECTOR, AND OWNER'S REPRESENTATIVE MUST ATTEND THE PRE–CONSTRUCTION MEETING.

B. MARK LIMITS OF DISTURBANCE

C. DIVERT OFF–SITE, CLEAN RUNOFF FROM ENTERING AREAS TO BE DISTURBED.

D. ESTABLISH CONSTRUCTION ENTRANCE(S)

1. ANY SEDIMENT TRACKED ONTO PUBLIC OR PRIVATE ROADWAYS, PARKING LOTS OR SIDEWALKS OUTSIDE THE CONSTRUCTION AREA IS TO BE CLEANED/REMOVED ON A DAILY BASIS.
2. PRESERVE EXISTING ASPHALT WHERE POSSIBLE FOR USE AS CONSTRUCTION ENTRANCES AND CONSTRUCTION ROUTES.

E. ESTABLISH CONTRACTOR PARKING AND STAGING AREAS, IN ACCORDANCE WITH OWNER'S PREFERENCES. PROVIDE CONTRACTOR PARKING AND STAGING AREA STABILIZATION PRIOR TO USE.

F. INSTALL EROSION CONTROL MEASURES, SUCH AS SILT FENCE AND CATCHBASIN INLET PROTECTION, BEFORE LAND GRADING BEGINS.
1. SILT FENCE IS TO BE INSTALLED PARALLEL TO CONTOURS

G. INSTALL TREE PROTECTION FENCING.

2. CONSTRUCTION

A. LIMIT INITIAL GRADING TO AREAS THAT ARE NEEDED FOR EROSION AND SEDIMENT CONTROL.

B. STOCKPILE TOPSOIL AWAY FROM DRAINAGE PATHS, WATERBODIES AND THE TOP OF STEEP SLOPES. STABILIZE AS SOON AS POSSIBLE.

C. AVOID DISTURBANCE OF STEEP SLOPES
1. IF DISTURBANCE ON STEEP SLOPES IS REQUIRED, MINIMIZE AREA TO BE DISTURBED AND AMOUNT OF TIME AREA WILL BE DISTURBED. PLAN STEEP SLOPE DISTURBANCE DURING DRY WEATHER AND WHEN SOILS ARE NOT SATURATED. STABILIZE STEEP SLOPE DISTURBANCE AT THE END OF EACH WORKDAY. PROVIDE FINAL STABILIZATION AS SOON AS WORK ON THE STEEP SLOPE IS COMPLETED.

D. COMMENCE GENERAL SITE CONSTRUCTION

E. STABILIZE EXPOSED SOIL AS SOON AS POSSIBLE. IN AREAS WHERE SOIL DISTURBANCE ACTIVITY HAS BEEN TEMPORARILY OR PERMANENTLY CEASED, TEMPORARY AND/OR PERMANENT SOIL STABILIZATION MEASURES SHALL BE INSTALLED AND/OR IMPLEMENTED WITHIN TEN (10) DAYS FROM THE DATE THE SOIL DISTURBANCE ACTIVITY CEASED.

F. DIRECT ANY SEDIMENT RUNOFF INTO SEDIMENTATION TRAPS. IF THERE IS A SEDIMENTATION PROBLEM IN AN AREA WHERE THERE IS NO SEDIMENTATION TRAP CALLED FOR ON THE PLAN, CREATE A SEDIMENTATION TRAP AND NOTE ITS LOCATION ON THE STORMWATER DRAWING.

G. PREVENT SEDIMENT FROM BEING TRANSPORTED OFF–SITE.

H. ANY SEDIMENT TRACKED ONTO ROADS, PARKING LOTS, OR ACTIVE PEDESTRIAN WALKS SHALL BE SWEPT, AS NEEDED, BUT NOT LESS THAN ONE (1) TIME PER DAY.

3. MAINTENANCE AND INSPECTION DURING CONSTRUCTION

A. ALL EROSION AND SEDIMENT CONTROL MEASURES MUST BE MAINTAINED ON A REGULAR SCHEDULE DURING CONSTRUCTION.

B. INSPECTIONS MUST BE PERFORMED AT LEAST ONCE EVERY SEVEN (7) CALENDAR DAYS BY QUALIFIED PROFESSIONAL AS OUTLINED IN GP–0–20–001.

C. CONTRACTORS RESPONSIBLE FOR EROSION AND SEDIMENT CONTROL ARE TO INSPECT ALL PRACTICES AT LEAST ONCE A WEEK AND AFTER EVERY RAIN EVENT.

D. ENSURE THAT ALL PRACTICES ARE OPERATING AS DESIGNED.

E. ENSURE THAT NO SEDIMENT IS BEING TRANSPORTED OFF–SITE OR IS ENTERING THE DRAINAGE SYSTEM.

F. LOOK FOR EVIDENCE OF EROSION IN DISTURBED PORTIONS OF THE SITE.

G. ENSURE THAT SEDIMENT IS NOT BEING TRACKED ONTO PUBLIC OR PRIVATE ROADS, PARKING LOTS OR SIDEWALKS OUTSIDE THE CONSTRUCTION AREA.

H. RETAIN COPIES OF INSPECTION REPORTS ON–SITE WITH THE SWPPP. CONSTRUCTION MANAGER IS TO MAINTAIN SWPPP AND INSPECTION REPORTS ON–SITE.

4. FINAL GRADING & LANDSCAPING

A. ONCE CONSTRUCTION IS NEARING COMPLETION, IDENTIFY THE FINAL GRADING AND STABILIZATION PLAN.

B. ALL BARE AREAS MUST RECEIVE COVER. PERMANENT TOPSOIL AND VEGETATION SHOULD BE PLACED WHERE APPROPRIATE. REFER TO LANDSCAPING PLANS.

C. AREAS USED FOR CONSTRUCTION STAGING AND AREAS THAT WERE PREVIOUSLY IMPERVIOUS AND ARE NOW LAWN AREA ARE TO BE DE–COMPACTED PRIOR TO SPREADING OF TOPSOIL, SEED AND MULCH. REFER TO SWPPP FOR ADDITIONAL INFORMATION ON DE–COMPACTION.

D. OTHER AREAS SHALL RECEIVE COVER, SUCH AS STONE, MULCH OR RIPRAP, AS APPROPRIATE.

E. STABILIZATION MUST BE UNDERTAKEN NO LATER THAN 10 DAYS AFTER CONSTRUCTION ACTIVITY HAS CEASED.

F. FINAL PLANTING SCHEDULE TO BE DETERMINED BY LANDSCAPE ARCHITECT. IF CONSTRUCTION IS NEARING COMPLETION AT A TIME OF YEAR WHEN PLANTING IS NOT RECOMMENDED, PROVIDE TEMPORARY SEED AND MULCH IN PLACE OF LANDSCAPING UNTIL CONDITIONS ARE APPROPRIATE FOR FINAL PLANTING.

G. REMOVE TEMPORARY EROSION CONTROL MEASURES THAT WILL INTERFERE WITH FINAL GRADING AND LANDSCAPING.

5. POST–CONSTRUCTION

A. ENSURE THAT THE PERMANENT PRACTICES UTILIZED DURING CONSTRUCTION ARE SUITABLE TO FIT POST–CONSTRUCTION SITE CONDITIONS.

B. MINIMIZE THE RISK OF CONCENTRATED FLOW AND EROSION.

C. CLEAN AND PREPARE PERMANENT PRACTICES TO BE TURNED OVER TO THE OWNER/OPERATOR. PREPARE MANUAL AND DISCUSS OPERATION AND MAINTENANCE OF THE PERMANENT PRACTICE WITH THE OWNER/OPERATOR OR REPRESENTATIVE.

D. REMOVE TEMPORARY EROSION AND SEDIMENT CONTROL PRACTICES, SUCH AS SILT FENCE.

E. INSPECT PREVIOUSLY SEEDED GRASS/LAWN AREAS FOR BARE OR THIN SPOTS. RE–SEED AND MULCH AS NEEDED. WITH REMOVAL OF TEMPORARY E&SC PRACTICES, SUCH AS SILT FENCE, SEED AND MULCH AS NEEDED.

F. IN ACCORDANCE WITH GP–0–20–001, A FINAL STABILIZATION INSPECTION AND SIGN–OFF BY THE LOCAL MS4 IS REQUIRED BEFORE THE NOTICE OF TERMINATION (NOT) CAN BE FILED WITH NYSDEC.

EROSION AND SEDIMENT CONTROL MEASURES INSPECTION FREQUENCY

MEASURE	INSPECTION FREQUENCY	REPLACEMENT
SILT FENCE	ONCE PER WEEK/AFTER RAIN EVENT	WHEN BULGING, TORN OR KNOCKED DOWN.
STABILIZED CONSTRUCTION ENTRANCE	ONCE PER WEEK/AFTER RAIN EVENT	TOPDRESS STONE WHEN THERE IS EVIDENCE OF SEDIMENT TRACKED OUTSIDE CONSTRUCTION AREA. FULL REPLACEMENT WHEN TOPDRESSING IS NO LONGER EFFECTIVE.
CATCHBASIN INLET PROTECTION	ONCE PER WEEK/AFTER RAIN EVENT	RE-SHAPE STONE AS NEEDED. REMOVE BUILT-UP SEDIMENT AFTER 50% OF STORAGE VOLUME IS FILLED.
STONE CHECK DAM	ONCE PER WEEK/AFTER RAIN EVENT	RE-SHAPE STONE AS NEEDED. REPLACE STONE AS NEEDED. REMOVE BUILT-UP SEDIMENT.
TREE PROTECTION FENCING	ONCE PER WEEK/AFTER RAIN EVENT	REPLACE FENCE IF TORN OR KNOCKED DOWN.
ROAD SWEEPING	AS NEEDED; MULTIPLE TIMES PER DAY IF SEDIMENT IS TRACKED ONTO ROADS OUTSIDE CONSTRUCTION AREA.	
DUST CONTROL	AS NEEDED.	
SOIL STOCKPILE	ONCE PER WEEK/AFTER RAIN EVENT	RE-SEED & MULCH IF BARE SPOTS ARE VISIBLE. REPLACE SILT FENCE WHEN BULGING, TORN OR KNOCKED DOWN
LITTER	DAILY	LITTER IS TO BE PICKED UP AT THE END OF EVERY WORK DAY. TO PREVENT LITTER FROM BEING BLOWN OFF-SITE OR ENTERING WATERWAYS. CONSTRUCTION MANAGER TO ENSURE CONTRACTORS AND SUBCONTRACTORS ARE USING WASTE RECEPTACLES PROVIDED. CONSTRUCTION MANAGERS TO PROVIDE ADDITIONAL WASTE RECEPTACLES AS NEEDED.



NOTES:

1. TEMPORARY ORANGE CONSTRUCTION FENCES SHALL BE USED TO SEPARATE CONSTRUCTION ACTIVITIES FROM PEDESTRIANS.
2. ALL TEMPORARY ORANGE CONSTRUCTION FENCING SHALL BE PLASTIC, 48" MINIMUM HEIGHT AND ORANGE IN COLOR.
3. TEMPORARY ORANGE CONSTRUCTION FENCE USED TO SEPARATE SIDEWALKS FROM CONSTRUCTION ACTIVITIES SHALL HAVE MINIMUM ENCROACHMENT TO THE SIDEWALK.
4. CONTRACTOR TO PROVIDE ANCHORAGE (I.E. SANDBAGS) FOR FENCE IF REQUIRED BY SITE CONDITIONS.

4 C601 TEMPORARY ORANGE CONSTRUCTION FENCE
NO SCALE



NOTES:

1. TOP AND BOTTOM SELVAGE ON WIRE MESH SHALL BE KNUCKLED.
2. CONTRACTOR TO PROVIDE ANCHORAGE (I.E. SANDBAGS) FOR FENCE IF REQUIRED BY SITE CONDITIONS.
3. ATTACH OPAQUE SCREEN TO FENCE; MINIMUM 2–FT GAP BETWEEN GROUND SURFACE AND BOTTOM OF OPAQUE SCREEN.

5 C601 TEMPORARY CHAIN LINK PANEL FENCE
DURING CONSTRUCTION
NO SCALE



CONSTRUCTION SPECIFICATIONS

1. LAY ONE BLOCK ON EACH SIDE OF THE STRUCTURE ON ITS SIDE FOR DEWATERING. FOUNDATION SHALL BE 2 INCHES MINIMUM BELOW REST OF INLET AND BLOCKS SHALL BE PLACED AGAINST INLET FOR SUPPORT.
2. HARDWARE CLOTH OR 1/2" WIRE MESH SHALL BE PLACED OVER BLOCK OPENINGS TO SUPPORT STONE.
3. USE CLEAN STONE OR GRAVEL 1/2–3/4 INCH IN DIAMETER PLACED 2 INCHES BELOW TOP OF THE BLOCK ON A 2:1 SLOPE OR FLATTER.
4. FOR STONE STRUCTURES ONLY, A 1 FOOT THICK LAYER OF THE FILTER STONE WILL BE PLACED AGAINST THE 3 INCH STONE AS SHOWN ON THE DRAWINGS.
5. MAXIMUM DRAINAGE AREA 1 ACRE.
6. PROTECT INLET PROTECTION FROM DAMAGE BY CONSTRUCTION TRAFFIC; SURROUND WITH TEMPORARY ORANGE CONSTRUCTION FENCE.
7. IN PAVED AREAS, ELIMINATE CONCRETE BLOCK FOR DEWATERING. USE STONE/GRAVEL FILTER.

6 C601 STONE AND BLOCK DROP INLET PROTECTION
NO SCALE



CONSTRUCTION SPECIFICATIONS

1. AREA UNDER EMBANKMENT SHALL BE CLEARED, GRUBBED, AND STRIPPED OF ANY VEGETATION AND ROOT MATERIAL. THE TRAP AREA SHALL BE CLEARED.
2. THE FILL MATERIAL FOR THE EMBANKMENT SHALL BE FREE OF ROOTS OR OTHER WOODY VEGETATION AS WELL AS OVERSIZED STONES, ROCKS, ORGANIC MATERIAL OR OTHER QUESTIONABLE MATERIAL. THE EMBANKMENT SHALL BE COMPACTED BY TRAVERSING WITH EQUIPMENT WHILE IT IS BEING CONSTRUCTED.
3. SEDIMENT SHALL BE REMOVED AND TRAP RESTORED TO ITS ORIGINAL DIMENSION WHEN THE SEDIMENT HAS ACCUMULATED TO 1/2 THE DESIGN DEPTH OF THE TRAP. REMOVED SEDIMENT SHALL BE DEPOSITED IN A SUITABLE AREA AND IN SUCH A MANNER THAT IT WILL NOT ERODE.
4. THE STRUCTURE SHALL BE INSPECTED AFTER EACH RAIN AND REPAIRS MADE AS NECESSARY.
5. CONSTRUCTION OPERATIONS SHALL BE CARRIED OUT IN SUCH A MANNER THAT EROSION AND WATER POLLUTION IS MINIMIZED.
6. THE STRUCTURE SHALL BE REMOVED AND THE AREA STABILIZED WHEN THE DRAINAGE AREA HAS BEEN PROPERLY STABILIZED.
7. ALL CUT AND FILL SLOPES SHALL BE 2 ON 1 OR FLATTER.
8. THE CRUSHED STONE USED IN THE OUTLET SHALL MEET AASHTO DESIGNATION M43, SIZE NO. 2. OR 24 OR ITS EQUIVALENT SUCH AS MSHA NO. 2 GRAVEL MEET-ING THE ABOVE GRADATION MAY BE USED IF CRUSHED STONE IS NOT AVAILABLE. CRUSHER RUN IS NOT ACCEPTABLE.

7 C601 STONE OUTLET SEDIMENT TRAP
NO SCALE



11 C601 FLARED END SECTION AND RIPRAP OUTLET PROTECTION
NO SCALE



9 C601 SOIL STOCKPILE
NO SCALE



NOTES:

1. ALL MATERIAL TO MEET SPECIFICATIONS.
2. FILTER MEDIA TO MEET APPLICATION REQUIREMENTS.
3. FILTER MEDIA TO BE DISPERSED ON SITE, AS DETERMINED BY ENGINEER.

1 G–1 SILTSOXX (tm) SEDIMENT CONTROL ON PAVEMENT
NO SCALE



GENERAL NOTES:

1. ACTUAL LOCATION DETERMINED IN THE FIELD.
2. CONCRETE WASHOUT STRUCTURE NEEDS TO BE CLEARLY MARKED WITH SIGNAGE NOTING DEVICE.

BELOW GRADE WASHOUT STRUCTURE



GENERAL NOTES:

1. ACTUAL LOCATION DETERMINED IN THE FIELD.
2. CONCRETE WASHOUT STRUCTURE NEEDS TO BE CLEARLY MARKED WITH SIGNAGE NOTING DEVICE.

ABOVE GRADE WASHOUT STRUCTURE

WASHOUT NOTES

1. ALL CONCRETE WASHOUT FACILITIES SHALL BE INSPECTED DAILY. DAMAGED OR LEAKING FACILITIES SHALL BE DE–ACTIVATED & REPAIRED, OR REPLACED IMMEDIATELY. EXCESS RAINWATER THAT HAS ACCUMULATED OVER HARDENED CONCRETE SHALL BE PUMPED TO A STABILIZED AREA, SUCH AS A GRASS FILTER STRIP.
2. ACCUMULATED MATERIAL SHALL BE REMOVED WHEN 75% OF THE STORAGE CAPACITY OF THE STRUCTURE IS FILLED. ANY EXCESS WASH WATER SHALL BE PUMPED INTO A CONTAINMENT VESSEL AND PROPERLY DISPOSED OF OFF–SITE.
3. DISPOSE OF ALL HARDENED MATERIAL OFF–SITE IN A CONSTRUCTION/DEMOLITION LANDFILL. ON–SITE DISPOSAL MAY BE ALLOWED IF THIS HAS BEEN APPROVED & ACCEPTED AS PART OF THE PROJECTS SWPPP. IN THAT CASE, THE MATERIAL SHOULD BE RECYCLED AS SPECIFIED, OR BURIED & COVERED WITH A MINIMUM OF TWO (2) FEET OF CLEAN COMPACTED EARTH–FILL THAT IS PERMANENTLY STABILIZED TO PREVENT EROSION.
4. THE PLASTIC LINER SHALL BE REPLACED WITH EACH CLEANING OF THE WASHOUT FACILITY.
5. INSPECT THE PROJECT SITE FREQUENTLY TO ENSURE THAT NO CONCRETE DISCHARGES ARE TAKING PLACE IN NON–DESIGNATED AREAS.
6. AS AN ALTERNATIVE, A LINED ROLL–OFF CONTAINER CAN BE USED FOR THE WASHOUT FACILITY.
7. THE CONCRETE WASHOUT FACILITY SHALL BE LOCATED A MINIMUM OF 100 FEET FROM DRAINAGE SWALES, WETLANDS, STREAMS, AND OTHER WATER BODIES. THE FACILITY SHALL BE LOCATED DOWN HILL OF ANY STORM DRAINAGE INLET OR OTHERWISE 100 FEET MINIMUM FROM SUCH STRUCTURES.

11 C601 WASHOUT STRUCTURE
NO SCALE

NO.	DATE	REVISION	BY
1	5/31/22	PER COMMENTS	JVA

NORTH ARROW

- Alteration of this drawing, except by a Licensed Professional Engineer or Architect is illegal. Any alteration by a Professional Engineer or Architect must be indicated and bear his/her seal, signature and date of alteration.
- The user of this drawing shall verify all dimensions shown hereon and the scale of this drawing.
- This line is one inch long.

DRAWN BY: KMC
CHECKED BY: JVA
DATE: FEB 2022
SCALE: AS NOTED

ROHDE, SOYKA & ANDREWS
Consulting Engineers PC
40 Garden Street Poughkeepsie, N.Y. 12601
(845) 452-7515
Fax: (845) 452-8335

117 NORTH HAMILTON
NORTH HAMILTON STREET
CITY OF POUGHKEEPSIE
DUTCHESS COUNTY, NEW YORK

ESC DETAILS

PROJECT NUMBER: 21–786–01

DRAWING NUMBER: C502
8 OF 9

THE CITY OF POUGHKEEPSIE

DEPARTMENT OF PUBLIC WORKS & ENGINEERING

SITE PLAN REVIEW
Form #2

1. Date: April 4, 2023

2. Name of Site Plan: 117 North Hamilton

3. Address or Location: 117 North Hamilton Street

4. Owner: 117 N Hamilton, LLC

5. Engineer/ Architect: Rohde, Soyka & Andrews

6. Yes ☐ No ☐ The site plan as forwarded by the Planning Department is acceptable and will be signed off on with no condition(s).

7. Yes ☐ No ☐ The site plan as forwarded by the Planning Department is acceptable and has been signed off on with no condition(s).

8. Yes ☒ No ☐ The applicant should be notified that the Dept. of Public Works/Engineering requires the following comment(s) be addressed:

ENGINEERING SITE PLAN REVIEW COMMENTS:

1. Show invert elevation of existing City owned catch basin and proposed storm tie-in point.
2. Provide detail of proposed connection to City owned catch basin.
3. Show invert elevations of all proposed on-site storm sewer pipe network.
4. Submit retaining wall design stability calculations certified by a NYS licensed Professional Engineer (PE) for all retaining walls greater than 5' in height.
5. Indicate on site plan new yard hydrant to be American Darling B-62-B. No exceptions. Include Hydrant detail on site plan.

ENGINEERING SWPPP REVIEW COMMENTS:

1. Provide and include ADS Stormtech MC 3500 Stormwater Chamber cut-sheet from manufacturer. 2.
2. Provide and include manufacturer maintenance requirements as noted in Section 7.3.1 "Long Term Maintenance and Operation of Permanent Post-Construction Management Practice".
3. Provide and include Notice of Intent (Appendix A).
4. Provide and include SWPPP Acceptance (Appendix B).
5. Provide and include Soil Restoration (Appendix F).
6. Provide and include NYSDEC Spill Reporting and Initial Notification Requirements (Appendix I).

Joseph T. Kane, P.E.
Assistant Civil Engineer

Note: If #6 or #7 above are checked "yes" there is no need to go on to Form #2.

THE CITY OF POUGHKEEPSIE

DEPARTMENT OF PUBLIC WORKS & ENGINEERING

SITE PLAN REVIEW
Form #1

1. Date: June 7, 2022

2. Name of Site Plan: 117 North Hamilton

3. Address or Location: 117 North Hamilton Street

4. Owner: 117 N Hamilton, LLC

5. Engineer/ Architect: Rohde, Soyka & Andrews

6. Yes ☐ No ☐ The site plan as forwarded by the Planning Department is acceptable and will be signed off on with no condition(s).

7. Yes ☐ No ☐ The site plan as forwarded by the Planning Department is acceptable and has been signed off on with no condition(s).

8. Yes ☒ No ☐ The applicant should be notified that the Dept. of Public Works/Engineering requires the following comment(s) be addressed:

ENGINEERING SITE PLAN REVIEW COMMENTS:

1. Show existing catch basins, storm sewer, and manholes at North Hamilton Street near the south side of site. Show Invert Elevations of nearest storm sewer on utility plan.
2. Submit Storm Water Pollution Prevention Plan (SWPPP) for review and approval. Show proposed storm water facilities on site plan.
3. It is recommended that the silt fence be extended beyond the limits shown on the Erosion Control Plan.
4. Submit stability calculation and details for retaining walls greater than 5'.
5. Indicate what existing valve box and curb box at curb-cut services, verify water services have been abandoned at main.
6. Abandon existing aprons/drop curbs. Replace with 6" curb, top soil/seed and 5' wide sidewalk.
7. Replace all sidewalk in disrepair along property front.
8. Replace broken curb at property front.

Joseph T. Kane,
Assistant Civil Engineer

Note: If #6 or #7 above are checked "yes" there is no need to go on to Form #2.

July 19, 2022

City of Poughkeepsie Planning Board
Attn: Robert Levine, Chairman
63 Civic Center Plz
Poughkeepsie, NY 12601

cc: Natalie Quinn, Development Director

RE: 2022-020: 117 North Hamilton Street

MASS DESIGN GROUP

1 Chandler Street #101
Boston, MA 02118

289 Main Street #101
Poughkeepsie, NY 12601

hello@massdesigngroup.org
+1 857 233 5788
+1 845 473 4003

massdesigngroup.org

Dear City of Poughkeepsie Planning Board,

An architectural workshop was convened on July 7, 2022 with Jason Anderson, Eric Baxter, Lauren Rutkowski, Natalie Quinn, and Christopher Kroner.

We understand that the construction of this facility is a pre-engineered metal building construction, and that Anderson Design Group (Montgomery NY) is working within the manufacturer's assembly parameters. We find the palette of the dark front and silver/gray metal rear to be an attractive solution to helping each building have a clear identity, and we observe that the graphics proposed have been decreased to help the rear building diminish in appearance from the original proposal.

Materials and Methods

1. One suggestion we discussed with the design team is to **lift the corrugated metal siding from the ground at the same height as the landscape retaining wall**, and that may allow the building to appear a bit smaller in proportion and integrate with the landscape components.
2. We understand that in lieu of wood planks, a proposed aluminum 22' "Longboard" plank is currently being suggested/substituted for the rendered wood shown in the facades. We also discussed the design team's decision not to include that material on the side walls at each doorway recess. **More product information and material samples would help explain this for further planning board review.**

Lighting

The workshop discussed the lighting strategy of downlights versus wall mounted lighting. We interpret the design to use downlights exclusively in order to keep the building appearance clean and modern without adornments, which feels supportable in this particular massing, assuming the lighting levels are sufficient.

Landscape and Site Concerns

1. The planning board may want to recommend adding trees to the front yard strip to help reinforce the rhythm of the front entryways, and help alleviate the height of the building facade.
2. Fencing along the rail spur trail was discussed and we suggested that the fencing be upgraded to be more opaque to help shield the visual impact of the rear building yard's storage operations.
3. It was discussed whether permeable paving could be incorporated into the site plan, and the design team agreed to consider that further.

4. Building address signage was discussed briefly, and while that may come as a future application for signage review, alternate locations for the address signs were offered as part of the landscape walls. **Design team offered to continue to refine.**
5. **The applicant should please clarify HVAC configuration, electrical and gas meter service and meter locations for planning board review.**

We look forward to the evolution of this design of this inventive project, and are available for further followup or clarifications as needed..

Sincerely,



Chris Kroner
Principal
ckroner@mass-group.org

THE CITY OF POUGHKEEPSIE
FIRE DEPARTMENT

505 MAIN STREET
POUGHKEEPSIE, NY 12601
TEL: 845-451-4079 FAX: 845-451-4191
FIRE CHIEF JOSEPH FRANCO
JFRANCO@CITYOFPOUGHKEEPSIE.COM

SITE PLAN REVIEW FORM

TO: Planning Board

FROM: Fire Chief Joseph Franco

DATE: March 07, 2023

ADDRESS: 117 North Hamilton

____ The site plan is acceptable and will be signed without conditions.

_x___ The site plan is acceptable and will be signed with conditions:

** Previous conditions have been met from FD Letter of 9/16/2022.

Joseph Franco, Fire Chief

3/7/23
Date

CITY OF POUGHKEEPSIE POLICE DEPARTMENT

SITE PLAN REVIEW

DATE: 07/08/2022

PROJECT NAME: 117 N HAMILTON STREET

PROJECT ADDRESS: 117 N HAMILTON STREET

☒ **THE SITE PLAN IS ACCEPTABLE AND WILL BE SIGNED WITH NO CONDITIONS**

☐ **THE SITE PLAN IS UNACCEPTABLE.**

CONDITIONS:

RECEIVED
JUL 11 2022

APPROVED BY CHIEF THOMAS PAPE OR AGENT:	DATE:
Sgt SGT. E. ACKEN #112	07/08/2022

BUILDING DEPARTMENT

CITY OF POUGHKEEPSIE
62 CIVIC CENTER PLAZA, 2ND FLOOR
POUGHKEEPSIE, NY 12601
Phone: (845) 451-4007 Fax: (845) 451-4006

Eric Philipp
Building Inspector

SITE PLAN REVIEW

DATE: 7-122

PROJECT ADDRESS: 117 N Hamilton St

PROJECT NAME:

OWNER: Baxter Development Corp

ENGINEER/ARCHITECT: Rohde, Soyka & Andrews, Consulting Engineers, PC

☑ **The site plan is acceptable and will be signed with no conditions.**

☐ **The site plan cannot be approved as submitted. The following comments must be addressed or conditions satisfied:**

_____

_____

_____

_____

_____

_____

Eric Philipp
Building Inspector

THE CITY OF POUGHKEEPSIE
PLANNING BOARD
62 CIVIC CENTER PLAZA, 2ND FLOOR
POUGHKEEPSIE, NY 12601
Phone: (845) 451-4623 Fax: (845) 451-4006
DRAFT RESOLUTION OF APPROVAL
APRIL 18, 2023

At a Regular Meeting of the Planning Board held on the 18th day of April, 2023, at 6:00pm, in the matter of the application from Baxter regarding the property known as 117 North Hamilton Street, Poughkeepsie, New York:

Present	**Excused**
Anne Saylor, Chairman	
Rosaura Andujar-McNeil	
Nick DeLuccia	
Sean O'Donnell	
Marjorie Smith	
Robert Mallory	
(Brian Veltre)	

NEGATIVE DECLARATION:

WHEREAS, the Planning Board has received an application from Baxter Development Corp. for the proposed construction of a two story structure with 34 off-street parking spaces to be used as a wholesale storage, warehousing, manufacturing, creative, retail, contracting business, File #2022-020; and,

WHEREAS, this application has been classified as an Unlisted Action for the purposes of SEQRA, and a Full EAF has been submitted; and,

WHEREAS, the Planning Board has received an application from Baxter Development Corp. for the proposed construction of a two story structure with 34 off-street parking spaces to be used as a wholesale storage, warehousing, manufacturing, creative, retail, contracting business, File #2022-020; and,

WHEREAS, the Project is located in the Light Industrial Zoning District (I-1); and,

WHEREAS, the application first appeared for the Planning Board on June 22, 2022; and,

WHEREAS, the action is more fully detailed on a site plan and elevations prepared by Anderson Design Group, dated 9/2/22, and supplemental documentation; and,

WHERAS, the action is more fully detailed on the Full Environmental Assessment Form with a revision date of 3/3/23, prepared by Baxter Development Corp., and the application and plans outlined above; and,

WHEREAS, on June 22, 2022, the project underwent an uncoordinated review for the purposes of SEQRA; and,

WHEREAS, the Board has compared the impacts that are likely to result from the action against those in 617.7(c)(1)(i) through (xii), as noted in the EAF, and has determined that there will be no significant adverse environmental impacts and therefore, a draft environmental impact statement will not be prepared:

NOW THEREFORE BE IT RESOLVED that the Planning Board hereby adopts a Negative Declaration for file PB#2022-020, as detailed in the application and the above referenced plans.

Motion:
Second:
Carried:

RESOLUTION OF APPROVAL:

WHERAS, the action is more fully detailed on the Full Environmental Assessment Form with a revision date of 3/3/23, prepared by Baxter Development Corp., and the application and plans outlined above; and,

WHEREAS, a Public Hearing was held on August 16, 2022 and September 20, 2022 when it was closed; and,

WHEREAS, on August 9, 2022, the Zoning Board of Appeals granted variances regarding the landscaping buffer; and,

WHEREAS, Section 19-6.1 of the Zoning Ordinance provides that if the cost of improvements is anticipated to be in excess of $30,000, a performance bond will be established to cover the cost of improvements, based on advice from the City Engineer, following the recommendations of the Engineering Department, a performance bond will be established; and,

WHEREAS, upon completion of the project, prior to the issuance of the final certificate of occupancy, an as-built site plan set shall be submitted to the Development Department for certification of compliance with Planning Board approval;

NOW THEREFORE BE IT FURTHER RESOLVED that the Board grant site plan approval relative to the proposed construction of a two story structure with 34 off-street parking spaces to be used as a wholesale storage, warehousing, manufacturing, creative, retail or contracting business, as outline on the 10 page site plan and elevation sets submitted March 7, 2023 with page revisions dated as outlined below, with the following conditions:

- All comments be the engineering department be satisfied to that department’s satisfaction
-

Motion:
Second:
Carried:

117 NORTH HAMILTON STREET

SITE PLAN REVISION DATES		ELEVATIONS REVISION DATES	
C100	September 2, 2022	A-201-PB	March 7, 2023
C101	February 28, 2023	A-202-PB	March 7, 2023
C102	September 2, 2022	A-300-PB	May 31, 2023
C103	February 28, 2023	A-301-PB	May 31, 2023
C104	March 2, 2023	A-302-PB	May 31, 2023
C105	December 1, 2022	A-303-PB	May 31, 2023
C500	September 2, 2022	A-901-PB	May 31, 2023
C501	February 2022	A-902-PB	August 8, 2023
C502	March 2, 2023	A-903-PB	September 6, 2022
L100	September 8, 2022	A-904-PB	September 6, 2022

APPLICATION TO THE PLANNING BOARD
CITY OF POUGHKEEPSIE, NEW YORK

Application for Site Plan, Special Permit & Facade Approval

I. **PROPERTY ADDRESS:** 13 HARRISON ST.

II. **PROPERTY OWNER:** MAUREEN LASHLEE
DIRECTOR
ADDRESS: HABITAT FOR HUMANITY
DUTCHESS COUNTY
1822 SOUTH ROAD
WAPPINGERS FALLS
NEW YORK 12590 (state and zip code)

PHONE NUMBER: 845·~~340~~·297·0806 (include area code)

III. **NAME OF APPLICANT:** DAVID FREEMAN RA

ADDRESS: 26 SHELDON DRIVE
POUGHKEEPSIE
NEW YORK 12603 (state and zip code)

PHONE NUMBER: 845·452 5359 (include area code)

EMAIL ADDRESS: DAVID@DFARCHT.COM

(If applicant is NOT the owner, proof of owner's consent to the application MUST be provided.)

IV. **CONSULTANT:** _____

ADDRESS: SAME AS APPLICANT

_____

_____ (state and zip code)

PHONE NUMBER: _____ (include area code)

V. **PROPOSED USE or FAÇADE CHANGE** (Summarize proposed use or uses): SINGLE FAMILY HOME · MODULAR

VI. **ZONING DISTRICT:** R-2A

OFFICE USE ONLY
CODE: PLSF
ID # _____
FEE: _____
Total, from:
$500, plus
$_____
($150 per 1000 square feet of floor area), plus
$_____
($35 per number of required parking spaces), plus
$_____
($500 for special permit, if applicable)

(Proceed to XVII for special permit & façade approval only)

PROJECT INFORMATION

New construction: X (yes)_____ (no)

Change of use:_____ (yes) _____ (no)

Expansion/addition:_____ (yes) _____ (no)

Alteration:_____ (yes) _____ (no)

Cost of Construction: $_____

LOT AND BULK INFORMATION:

Lot area: 0.110 (acres) 4800 (square feet)

Building Footprint: 864 (proposed square feet for new construction)

_____ (existing square feet for change of use/expansion)

_____ (additional proposed square feet for expansion)

_____ (total building footprint, square feet)

Lot Coverage: 15% (percentage, building coverage only)

Gross Floor Area: 1728 (proposed square feet for new construction)

_____ (existing square feet for change of use/expansion)

_____ (additional proposed square feet for expansion)

_____ (total gross floor area, square feet)

Building Height: 2 (stories) 26 (feet)

Floor Area Ratio: 35% (ratio of gross floor area divided by lot area)

VIII. PROJECT PARKING INFORMATION

A) Number of Off-Street Parking Spaces required: 1

B) Number of Off-Street Parking Spaces provided: 1

C) Waiver Requested: _____ (Yes) _____ (No)

Is municipal parking available within 600 feet? _____ (Yes) _____ (No)

If yes, name all such municipal facilities: _____

_____

_____

(If a waiver is requested based on proximity to municipal facilities, a written request for such waiver, addressed to the City Planning Staff and the Chairman of the Planning Board, must be submitted with the application.)

If a private parking facility is to be utilized, is such facility within 600 feet?

_____ (Yes) _____ (No)

If yes, provide the address of the facility, name of the property owner, number of spaces in the lot, number of spaces available for lease, and length of lease. Attach copy of lease. Additional information may be required by the Planning Board): _____

_____

_____

_____

IX. RESIDENTIAL PROPOSALS

A) Type of Development: _____
(Townhouse, condominium, multiple residence rental, etc.)

B) Unit Breakdown:

Number of efficiency or "studio" units: _____

Number of one (1) bedroom units: _____

Number of two (2) bedroom unit's _____

Number with three or more bedrooms: _____

Total number of units: _____

C) Is funding public? ____ Yes ____ No
If yes, describe funding source: _____

X. OFFICE PROPOSALS (____ Medical/Dental ____ Professional ____ Business)

A) Number of Employees: _____
B) Number of doctors/dentists/medical practitioners: _____
C) Days/Hours of Operation: _____

XI. SERVICE BUSINESS PROPOSALS

A) Specify Business: _____
(e.g., laundromat, drycleaner, beauty parlor, travel agency, banks)

B) Number of Employees: _____

C) Number of Washing Machines (for laundromat): _____

D) Days/Hours of Operation: _____

XII. MERCANTILE PROPOSALS (Retail _____ Wholesale _____)

A) Type of Mercantile (specify): _____

B) Number of Employees: _____

C) Days/Hours of Operation: _____

XIII. STANDARD RESTAURANT/FAST FOOD RESTAURANT/COFFEE SHOP/DONUT SHOP/NIGHTCLUB/DISCOTHEQUE/BAR PROPOSALS

A) Specify Use: _____

B) Number of seats (excluding bar stools and outdoor seating):_____

C) Meals served (i.e., breakfast, lunch, dinner): _____

D) Type of Menu: _____

E) Days/Hours of Operation: _____

F) Entertainment (live and/or recorded):_____

G) Will the restaurant contain a bar/lounge?: _____ Yes _____ No

H) If yes, how many seats at the bar? _____

I) Is a drive-through window proposed? _____

J) Is a walk-up window proposed? _____

K) Is an outdoor seating area proposed? _____

L) If yes, how many seats are proposed? _____

M) If yes, is outdoor cooking proposed? _____

XIV. INDUSTRIAL/COMMERCIAL PROPOSALS (Automobile repair, taxi, motor vehicle sales, warehouse, manufacturing, animal hospital, research facilities, etc.)

A) Specify Use: _____

B) Number of shifts (if any): _____

C) Number of employees: _____
(If shifts are proposed, list number of employees per shift)

E) Number of work bays (if automobile repair): _____

F) Days/Hours of operation: _____

XV. EDUCATIONAL/INSTITUTIONAL/RECREATIONAL PROPOSALS (e.g., Museums, Theatres, Conference Centers, Hotels, Motels, Hospitals, Nursing Homes, Assisted Living Facilities, Nursery Schools, Private Schools, Day Care Centers, Places of Worship, Marinas, Membership Clubs, etc.)

A) Specify: _____

B) Number of shifts (if any): _____

C) Number of employees: _____
(If shifts are proposed, list number of employees per shift)

D) Number of beds (hospitals, nursing homes, etc): _____

E) Number of seats in largest assembly space: _____

F) Number of classrooms (schools): _____

G) Number of rental units (hotels, motels, etc.) _____

H) Number of boat slips/courts (e.g., tennis, handball, etc.), alleys: _____

I) Days/Hours of Operation: _____

XVI. PROPOSALS NOT MENTIONED ABOVE (Please be specific):

_____

_____

_____

_____

_____

XVII. APPLICANT CERTIFICATION

I, DAVID FREEMAN, certify that the this application has addressed the objectives outlined in the Zoning Ordinance with consideration given to the public health, safety and welfare; the comfort and convenience of the public in general or the residents or users of the proposed development and of the immediate neighborhood.

The applicant certifies that all information contained herein is accurate and complete as of the date of this application.

_____ 2/13/23

Signature of Applicant Date

D. FREEMAN ARCHITECT
26 SHELDON DRIVE
POUGHKEEPSIE, NEW YORK 12603
Telephone 845-452-5359
Fax 845-452-5359
Email david@dfarcht.com
Web www.dfarcht.com

Cover Letter
13 Harrison Street
For New Home for Habitat for Humanity of Dutchess County

Application to Planning Board is to construct a single family home of Modular Construction at 13 Harrison Street.

Thank you.



February 28, 2023

THE CITY OF POUGHKEEPSIE
NEW YORK
DEVELOPMENT DEPARTMENT
62 CIVIC CENTER PLAZA, 2ND FLOOR
POUGHKEEPSIE, NY 12601
Phone: (845) 451-4263 Fax: (845) 451-4006

MEMORANDUM

To: David Freeman RA, Applicant

From: Natalie Quinn, Development Director

Date: March 7, 2023

Re: 13 Harrison Street, #PB2023-010 - SEQRA Classification

Upon review of project materials provided by the applicant, including Short EAF Part 1 and site plan application, it is my understanding that the proposed action to be undertaken includes construction of a new single family modular dwelling.

Based on the above description it is the determination of the planning division that the proposed action is classified as Type II Action with regards to SEQRA pursuant to 6 NYCRR Section 617.5 (c)(11) “construction or expansion of a single-family, a two-family or a three-family residence on an approved lot including provision of necessary utility connections as provided in paragraph (13) of this subdivision and the installation, maintenance or upgrade of a drinking water well or a septic system, or both, and conveyances of land in connection therewith” The action is therefore not subject to further environmental review.

PARCEL INFORMATION

PARCEL NUMBER 131300-6162-79-339068-0000
ADDRESS 13 HARRISON STREET

OWNER: HABITAT FOR HUMANITY
1822 SOUTH ROAD
WAPPINGERS FALLS, NEW YORK 12590

ZONING

ZONE R-4
SETBACK REQUIREMENTS

	REQUIRED	PROPOSED	VARIANCE
FRONT WIDTH	A	40'	COMPLIES
FRONT	20'	20'	COMPLIES
SIDE 1	6'	6'6	COMPLIES
SIDE 2	6'	10'	COMPLIES
REAR	15'	64'	COMPLIES
LOT COVERAGE	MAX. 35%	15%	COMPLIES

THERE ARE NO EXISTING OR PROPOSED EASEMENTS, RIGHTS-OF-WAY, SETBACKS, CONVENANTS OR DEED RESTRICTIONS

EXISTING GRADE TO REMAIN

PROTECTIVE FENCING TO BE INSTALLED AND MAINTAINED ON ALL SIDES PRIOR TO THE START OF CONSTRUCTION

PRIOR TO THE START OF CONSTRUCTION OR EXCAVATION, TREES TO BE RETAINED SHALL BE PROTECTED BY SILT FENCE, SNOW FENCE, CONSTRUCTION FENCE, OR EQUAL, WHICH WILL BE PLACED AT THE DRIP LINE OR SEVERAL FEET BEYOND. HOWEVER, THE FENCING SHALL NOT CROSS PUBLIC SIDEWALKS. NO STORAGE OR STOCKPILING OF CONSTRUCTION MATERIALS, DEBRIS OR EQUIPMENT SHALL OCCUR WITHIN THE FENCED AREA.



SITE PLAN
SCALE: 1" = 20'-0"

PROPOSED NEW HOME FOR HABITAT FOR HUMANITY DUTCHESS COUNTY

13 HARRISON STREET
CITY OF POUGHKEEPSIE, NEW YORK

THIS DRAWINGS IS INTENDED FOR ZONING APPLICATION PURPOSES ONLY

D. FREEMAN
ARCHITECT
26 SHELDON DRIVE
POUGHKEEPSIE, NY 12603
845-452-5359
email david@dfarcht.com

FEBRUARY 3, 2023

FRONT ELEVATION (NORTH)

SCALE: 1/8" = 1'-0"



RIGHT SIDE ELEVATION (WEST)

SCALE: 1/8" = 1'-0"

REAR ELEVATION (SOUTH)

SCALE: 1/8" = 1'-0"



LEFT SIDE ELEVATION (EAST)

SCALE: 1/8" = 1'-0"

PROPOSED NEW HOME FOR HABITAT FOR HUMANITY DUTCHESS COUNTY

13 HARRISON STREET
CITY OF POUGHKEEPSIE, NEW YORK

THIS DRAWINGS IS INTENDED FOR ZONING APPLICATION PURPOSES ONLY

D. FREEMAN
ARCHITECT
26 SHELDON DRIVE
POUGHKEEPSIE, NY 12603
845-452-5359
email david@dfarcht.com

MARCH 3, 2023

D. FREEMAN ARCHITECT
26 SHELDON DRIVE
POUGHKEEPSIE, NEW YORK 12603
Telephone 845-452-5359
Fax 845-452-5359
Email david@dfarcht.com
Web www.dfarcht.com

Site Photo
New Home for 13 Harrison Street for Habitat for Humanity of Dutchess County

RECEIVED
MAR 03 2023

Short Environmental Assessment Form
Part 1 - Project Information

Instructions for Completing

Part 1 – Project Information. The applicant or project sponsor is responsible for the completion of Part 1. Responses become part of the application for approval or funding, are subject to public review, and may be subject to further verification. Complete Part 1 based on information currently available. If additional research or investigation would be needed to fully respond to any item, please answer as thoroughly as possible based on current information.

Complete all items in Part 1. You may also provide any additional information which you believe will be needed by or useful to the lead agency; attach additional pages as necessary to supplement any item.

Part 1 – Project and Sponsor Information

Name of Action or Project:
PROPOSED NEW HOME

Project Location (describe, and attach a location map):
13 HARRISON ST

Brief Description of Proposed Action:
CONSTRUCTION OF NEW SINGLE FAMILY HOME

Name of Applicant or Sponsor:	Telephone: 845.452.5359
DAVID FREEMAN RA	E-Mail: DAVID@DFARCHT.COM

Address: 26 SHELDON DRIVE

City/PO:	State:	Zip Code:
POUGHKEEPSIE	NY	12603

	NO	YES
1. Does the proposed action only involve the legislative adoption of a plan, local law, ordinance, administrative rule, or regulation? If Yes, attach a narrative description of the intent of the proposed action and the environmental resources that may be affected in the municipality and proceed to Part 2. If no, continue to question 2.	☑	☐
2. Does the proposed action require a permit, approval or funding from any other government Agency? If Yes, list agency(s) name and permit or approval: BUILDING PERMIT	☐	☑

3. a. Total acreage of the site of the proposed action? 0.110 acres
   b. Total acreage to be physically disturbed? .026 acres
   c. Total acreage (project site and any contiguous properties) owned or controlled by the applicant or project sponsor? .0116 acres

4. Check all land uses that occur on, are adjoining or near the proposed action:
   ☑ Urban ☐ Rural (non-agriculture) ☐ Industrial ☐ Commercial ☐ Residential (suburban)
   ☐ Forest ☐ Agriculture ☐ Aquatic ☐ Other(Specify):
   ☐ Parkland

	NO	YES	N/A
5. Is the proposed action,			
a. A permitted use under the zoning regulations?	☐	☑	☐
b. Consistent with the adopted comprehensive plan?	☐	☑	☐

	NO	YES
6. Is the proposed action consistent with the predominant character of the existing built or natural landscape?	☐	☑

	NO	YES
7. Is the site of the proposed action located in, or does it adjoin, a state listed Critical Environmental Area?		
If Yes, identify: _____	☑	☐

	NO	YES
8. a. Will the proposed action result in a substantial increase in traffic above present levels?	☑	☐
b. Are public transportation services available at or near the site of the proposed action?	☐	☑
c. Are any pedestrian accommodations or bicycle routes available on or near the site of the proposed action?	☐	☑

	NO	YES
9. Does the proposed action meet or exceed the state energy code requirements?		
If the proposed action will exceed requirements, describe design features and technologies: _____ _____	☐	☑

	NO	YES
10. Will the proposed action connect to an existing public/private water supply?		
If No, describe method for providing potable water: _____ _____	☐	☑

	NO	YES
11. Will the proposed action connect to existing wastewater utilities?		
If No, describe method for providing wastewater treatment: _____ _____	☐	☑

	NO	YES
12. a. Does the project site contain, or is it substantially contiguous to, a building, archaeological site, or district which is listed on the National or State Register of Historic Places, or that has been determined by the Commissioner of the NYS Office of Parks, Recreation and Historic Preservation to be eligible for listing on the State Register of Historic Places?	☑	☐
b. Is the project site, or any portion of it, located in or adjacent to an area designated as sensitive for archaeological sites on the NY State Historic Preservation Office (SHPO) archaeological site inventory?	☑	☐

	NO	YES
13. a. Does any portion of the site of the proposed action, or lands adjoining the proposed action, contain wetlands or other waterbodies regulated by a federal, state or local agency?	☑	☐
b. Would the proposed action physically alter, or encroach into, any existing wetland or waterbody?	☑	☐
If Yes, identify the wetland or waterbody and extent of alterations in square feet or acres: _____ _____		

14. Identify the typical habitat types that occur on, or are likely to be found on the project site. Check all that apply:

☐ Shoreline ☐ Forest ☐ Agricultural/grasslands ☐ Early mid-successional
☐ Wetland ☑ Urban ☐ Suburban

	NO	YES
15. Does the site of the proposed action contain any species of animal, or associated habitats, listed by the State or Federal government as threatened or endangered?	☑	☐
16. Is the project site located in the 100-year flood plan? HOUSE LOCATION IS NOT IN 100 YR FLOOD PLAIN	☑	☐
17. Will the proposed action create storm water discharge, either from point or non-point sources?	☑	☐
If Yes, a. Will storm water discharges flow to adjacent properties?	☑	☐
b. Will storm water discharges be directed to established conveyance systems (runoff and storm drains)?	☑	☐
If Yes, briefly describe: _____		
18. Does the proposed action include construction or other activities that would result in the impoundment of water or other liquids (e.g., retention pond, waste lagoon, dam)? If Yes, explain the purpose and size of the impoundment: _____	☑	☐
19. Has the site of the proposed action or an adjoining property been the location of an active or closed solid waste management facility? If Yes, describe: _____	☑	☐
20. Has the site of the proposed action or an adjoining property been the subject of remediation (ongoing or completed) for hazardous waste? If Yes, describe: _____	☑	☐

I CERTIFY THAT THE INFORMATION PROVIDED ABOVE IS TRUE AND ACCURATE TO THE BEST OF MY KNOWLEDGE

Applicant/sponsor/name: DAVID FREEMAN RA Date: 2/28/23

Signature: _____ Title: ARCHITECT

PRINT FORM

D. FREEMAN ARCHITECT
26 SHELDON DRIVE
POUGHKEEPSIE, NEW YORK 12603
Telephone 845-452-5359
Fax 845-452-5359
Email david@dfarcht.com
Web www.dfarcht.com

Site Plan Information
13 Harrison Street
For New Home for Habitat for Humanity of Dutchess County

I).11 Habitat for Humanity of Dutchess County has the financial capability to complete the proposed project.

I)12. A Waiver is request for the following

II)4. Showing existing contours. The lot is relatively flat. Spot elevations are shown.

II) 8. Showing locations of ALL Existing utilities. Sanitary, Water, Gas and Electric are all existing adjacent to the project at the sidewalk and will be used.

III) 6. Lighting will be residential in nature with porch lights

II)2. III) 8. There are no existing or proposed easements, rights-of-way, setback, reservations and rears dedicated to public use, outline of existing covenants and deed restriction within, adjacent or otherwise pertaining to the property.

II) 7. There are no rock outcroppings or trees with a diameter of 8” or more on the site.

III) 5. Screening and landscaping plan is not required

III)7. There are no new grades so no information is provided.

III) 9. There are no fire alarm boxes or connections to the City Fire Alarm System proposed

III) 10. This is a determination to be made by the Board or City Engineer and is not up to the applicant

IV). 1. There are no plans for storm water improvements. This is a single family home.

Thank you.

March 3, 2023

THE CITY OF POUGHKEEPSIE
FIRE DEPARTMENT
505 MAIN STREET
POUGHKEEPSIE, NY 12601
TEL: 845-451-4079 FAX: 845-451-4191
FIRE CHIEF JOSEPH FRANCO
JFRANCO@CITYOFPOUGHKEEPSIE.COM

SITE PLAN REVIEW FORM

TO: Planning Board

FROM: Fire Chief Joseph Franco

DATE: March 31, 2023

ADDRESS: 13 Harrison St.

__x__ The site plan is acceptable and will be signed without conditions.

____ The site plan is acceptable and will be signed without conditions:

(List conditions here)

Joseph Franco, Fire Chief

3/31/2023
Date

THE CITY OF POUGHKEEPSIE

DEPARTMENT OF PUBLIC WORKS & ENGINEERING

SITE PLAN REVIEW
Form #1

1. Date: April 6, 2023
2. Name of Site Plan: Habitat for Humanity
3. Address or Location: 13 Harrison Street
4. Owner: Habitat for Humanity
5. Engineer/ Architect: D Freeman Architect
6. Yes ☐ No ☐ The site plan as forwarded by the Planning Department is acceptable and will be signed off on with no condition(s).
7. Yes ☐ No ☐ The site plan as forwarded by the Planning Department is acceptable and has been signed off on with no condition(s).
8. Yes ☒ No ☐ The applicant should be notified that the Dept. of Public Works/Engineering requires the following comment(s) be addressed:

ENGINEERING SITE PLAN REVIEW COMMENTS:

1. Show proposed water and sewer services on site plan and provide details. All trenches must be delineated and edges shown as sawcut. Details are available from the City Engineering Department in AutoCAD or pdf format.
2. Provide documentation that water service for demolished house at this site was formally abandoned at main. If no such documentation is available include abandonment of water service on site plan.
3. Provide traffic control plan for utility installations.
4. Provide contours or spot elevations at a minimum. The site appears to slope to the rear.
5. Are existing shared driveway apron and driveway to remain?
6. Replace four sidewalk panels west of driveway apron and as required for utility installations.
7. What is material type of proposed driveway and parking area? Indicate on site plan.
8. Prepare brief stormwater report. The report should demonstrate how post development stormwater rates will be limited to less than predevelopment runoff rates. On site attenuation may be required. Green infrastructure practices are encouraged. A maintenance schedule and plan will be required for al post construction stormwater management practices. Maintenance records for practices are to be submitted to engineering department on a biannual basis.
9. How will soil and sediment be prevented from tracking into City ROW and street during construction?
10. What is plan for chain link fence in disrepair at west property line and rear property line?

Joseph A. Chenier, CPESC, CPMSM

THE CITY OF POUGHKEEPSIE
FIRE DEPARTMENT
505 MAIN STREET
POUGHKEEPSIE, NY 12601
TEL: 845-451-4079 FAX: 845-451-4191
FIRE CHIEF JOSEPH FRANCO
JFRANCO@CITYOFPOUGHKEEPSIE.COM

SITE PLAN REVIEW FORM

TO: Planning Board

FROM: Fire Chief Joseph Franco

DATE: March 31, 2023

ADDRESS: 13 Harrison St.

__x__ The site plan is acceptable and will be signed without conditions.

____ The site plan is acceptable and will be signed without conditions:

(List conditions here)

Joseph Franco, Fire Chief

3/31/2023
Date

THE CITY OF POUGHKEEPSIE

DEPARTMENT OF PUBLIC WORKS & ENGINEERING

SITE PLAN REVIEW
Form #1

1. Date: April 6, 2023
2. Name of Site Plan: Habitat for Humanity
3. Address or Location: 13 Harrison Street
4. Owner: Habitat for Humanity
5. Engineer/ Architect: D Freeman Architect
6. Yes ☐ No ☐ The site plan as forwarded by the Planning Department is acceptable and will be signed off on with no condition(s).
7. Yes ☐ No ☐ The site plan as forwarded by the Planning Department is acceptable and has been signed off on with no condition(s).
8. Yes ☒ No ☐ The applicant should be notified that the Dept. of Public Works/Engineering requires the following comment(s) be addressed:

ENGINEERING SITE PLAN REVIEW COMMENTS:

1. Show proposed water and sewer services on site plan and provide details. All trenches must be delineated and edges shown as sawcut. Details are available from the City Engineering Department in AutoCAD or pdf format.
2. Provide documentation that water service for demolished house at this site was formally abandoned at main. If no such documentation is available include abandonment of water service on site plan.
3. Provide traffic control plan for utility installations.
4. Provide contours or spot elevations at a minimum. The site appears to slope to the rear.
5. Are existing shared driveway apron and driveway to remain?
6. Replace four sidewalk panels west of driveway apron and as required for utility installations.
7. What is material type of proposed driveway and parking area? Indicate on site plan.
8. Prepare brief stormwater report. The report should demonstrate how post development stormwater rates will be limited to less than predevelopment runoff rates. On site attenuation may be required. Green infrastructure practices are encouraged. A maintenance schedule and plan will be required for al post construction stormwater management practices. Maintenance records for practices are to be submitted to engineering department on a biannual basis.
9. How will soil and sediment be prevented from tracking into City ROW and street during construction?
10. What is plan for chain link fence in disrepair at west property line and rear property line?

Joseph A. Chenier, CPESC, CPMSM